

GlassBench KA2D time-code semantics

Official trajectory README maps tc file codes to lag times and identifies positions[20] as isoconfigurational replicas.

target	semantic stage	corrected fixed-time observables
KA2D T=0.23 tc05	physical timecode semantics ready sparse co	t=0.1; tau_alpha=918306; members=3; time codes=2/8 MSD=0.0035641; chi4(replica)=0.0435; axis0 replica=1; frame-axis time=0 blocker=sparse_time_code_coverage; next=extract_members_across_all_official_time_codes
KA2D T=0.23 tc10	physical timecode semantics ready sparse co	t=1.1; tau_alpha=918306; members=1; time codes=2/8 MSD=0.017994; chi4(replica)=1.06; axis0 replica=1; frame-axis time=0 blocker=sparse_time_code_coverage; next=extract_members_across_all_official_time_codes
KA2D T=0.30 tc01	physical timecode semantics ready sparse co	t=0.11; tau_alpha=2200; members=4; time codes=1/6 MSD=0.0052003; chi4(replica)=0.0662; axis0 replica=1; frame-axis time=0 blocker=sparse_time_code_coverage; next=extract_members_across_all_official_time_codes

This corrects the trajectory-axis semantics; full time-code coverage is still required before real inversion.