（a）槽寄存器与 32 位结果状态

```
    require(!cfg.writeFflags && !cfg.writeVxsat && !cfg.flushPipe && !cfg.replayInst)

    val pipelineStatus = IO(Output(new VDotElasticStatus))

>   private val pValid = RegInit(false.B)
    private val rValid = RegInit(false.B)
    private val pProducts = Reg(Vec(8, SInt(16.W)))
    private val pCtrl = Reg(chiselTypeOf(io.out.bits.ctrl))
    private val pPerf = Reg(chiselTypeOf(io.out.bits.perfDebugInfo))
    // H1 stores only the architectural low word; the public result stays 128 bits.
    // Keep each slot's complete control/perf identity on the same transfer edge.
    private val rPacket = Reg(new Bundle {
      val ctrl = chiselTypeOf(io.out.bits.ctrl)
      val res = new Bundle {
        val data = UInt(32.W)
      }
      val perfDebugInfo = chiselTypeOf(io.out.bits.perfDebugInfo)
    })

    pipelineStatus.pValid := pValid
    pipelineStatus.rValid := rValid
    pipelineStatus.occupancy := pValid.asUInt +& rValid.asUInt

    private val illegalInput = vill || vsew =/= VSew.e8 || vlmul =/= VLmul.m1 ||
      !vm || vstart =/= 0.U || vl =/= 8.U || fuOpType =/= VDotOpType.s8x8
```

（b）握手与取消条件

```
PS C:\WINDOWS\system32> wsl -d Ubuntu-22.04 -- git -C /home/riscv/riscv-lab/zjhwork2-review-20261018/repo --no-pager show 0f12df675378556670afd0dd2153f47fcb330610:src/main/scala/xiangshan/backend/fu/wrapper/VDotElastic.scala | Select-String -Pattern 'private val rReady =' -Context 5,12

      !vm || vstart =/= 0.U || vl =/= 8.U || fuOpType =/= VDotOpType.s8x8
    private val killP = pValid && pCtrl.robIdx.needFlush(io.flush)
    private val killR = rValid && rPacket.ctrl.robIdx.needFlush(io.flush)
    private val liveP = pValid && !killP && !reset.asBool
    private val liveR = rValid && !killR && !reset.asBool
>   private val rReady = !liveR || io.out.ready
    private val move = liveP && rReady
    private val pReady = !liveP || rReady

    // Parent admission is enforced by its atomic child dispatch. The FU also
    // suppresses every new accept on redirect/reset, including unrelated flush.
    io.in.ready := pReady && !io.flush.valid && !reset.asBool
    io.out.valid := liveR
    io.out.bits.ctrl := rPacket.ctrl
    io.out.bits.perfDebugInfo := rPacket.perfDebugInfo
    io.out.bits.res := 0.U.asTypeOf(io.out.bits.res)
    io.out.bits.res.data := Cat(0.U(96.W), rPacket.res.data)
```

（c）状态更新与原 P 内容转入 R

```
PS C:\WINDOWS\system32>
                      > wsl -d Ubuntu-22.04 -- git -C /home/riscv/riscv-lab/zjhwork2-review-20261018/repo --no-pager show 0f12df675378556670afd0dd2153f47fcb330610:src/main/scala/xiangshan/backend/fu/wrapper/VDotElastic.scala | Select-String -SimpleMatch 'pValid := (liveP && !move) || io.in.fire' -Context 2,16

    acceptedCtrl.exceptionVec.get(ExceptionNO.illegalInstr) := illegalInput

>   pValid := (liveP && !move) || io.in.fire
    rValid := (liveR && !io.out.fire) || move

    when(io.in.fire) {
      pProducts := products.io.products
      pCtrl := acceptedCtrl
      pPerf := io.in.bits.perfDebugInfo
    }
    when(move) {
      // Reads pre-edge P even when a new request replaces it at this same edge.
      rPacket.ctrl := pCtrl
      rPacket.perfDebugInfo := pPerf
      rPacket.res.data := Mux(pCtrl.exceptionVec.get(ExceptionNO.illegalInstr),
        0.U(32.W), reduce.io.result(31, 0))
    }

    // Read-only handles for the separate G1/G2 observation harness. These carry
```