

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to Part VB of the Copyright Act 1968 (**the Act**). The material in this communication may be subject to copyright under the Act. Any further copying or communication of this material by you may be the subject of copyright protection under the Act.


Do not remove this notice.

COMPx270: Randomised and
Advanced Algorithms
Lecture 6: Hashing and Friends

Clément Canonne
School of Computer Science



THE UNIVERSITY OF
SYDNEY



A question ?

A SID is of the form 450687816 (9 digits, each between 0 and 9). How many distinct SIDs are there?

$$10^9$$

How many distinct students have there even been at U Syd?

much less than that
 $\approx 10^6$ -ish?

Dictionaries (Maps, Associative arrays...)



n points! $\approx 10^6$
 $S \subseteq \mathcal{X}$
↑
points
 $|S| \ll |\mathcal{X}|$
 $n \ll m$

	LIST	ARRAY	BST
INSERT	$\cancel{O(1)} O(n)$	$O(1)$	$O(\log n)$
LOOKUP	$O(n)$	$O(1)$	$O(\log n)$
REMOVE	$O(n)$	$O(1)$	$O(\log n)$
SPACE	$O(n)$	$O(m)$	$O(n)$

Important detour: data representation

IOIO
IOIO

- Indexing something from X takes
 $\log_2 |X| = \log_2 m$
bits.


We hide these logs, often.

$$\tilde{F} = \{h: \underset{\substack{\uparrow \\ \text{size } m}}{X} \rightarrow \underset{\substack{\uparrow \\ \text{size } m'}}{Y}\} \rightarrow |\tilde{F}| = m'^m$$

Need $m \log m'$ bits to
represent an arbitrary
function from X to Y

Hash tables

A ^{randomised} solution to the Dictionary problem (ADT)



1 doubly

time $O(1)$ INSERT
 $O(1)$ LOOKUP
 $O(1)$ REMOVE


space $O(n)$

Total storage
 $\Omega(\text{"size of } h" + \underbrace{\text{size of } A}_{m'})$

Hash tables: the data structure

$$H \equiv (\mathcal{H}, n, m, m', \text{"strategy"})$$

Store: h, A



h chosen
once and
for all
when creating
the data
structure:
 $h \leftarrow \mathcal{H} \leftarrow \text{hash family}$

INSERT(x): $A[h(x)] \leftarrow 1$

LOOKUP(x): $A[h(x)] \stackrel{?}{=} 1$

REMOVE(x): $A[h(x)] \leftarrow 0$

SPACE: $O(\log |\mathcal{H}| + m')$

ideally

(can set $m' = O(n)$?)

Collision: $x, x' \in S$
 $x \neq x'$

but $h(x) = h(x')$

Hash tables: no collisions?




$$~~m' = O(n)~~$$

"perfect hashing"

- Birthday paradox: $m' = \Omega(n^2)$
- Worse: if $m' = O(n)$, even if h was chosen truly uniformly at random there would be $\Theta\left(\frac{\log n}{\log \log n}\right)$ collisions in some bucket

Need a strategy to handle collisions.

Hash tables: ~~no~~ collisions ✨



- ① Store x in $A[h(x)]$,
not just 0 or 1
(allows to detect collisions)
- ② Strategy:
 - Chaining
 - Open addressing

Hash tables: collisions

Handling collisions: separate chaining

INSERT(x):

$A[h(x)].\text{INSERT}(x)$


LOOKUP(x):

$A[h(x)].\text{LOOKUP}(x)$

REMOVE(x):

$A[h(x)].\text{REMOVE}(x)$

Load $\alpha = \frac{n}{m}$




Can have
 $\alpha > 1$

Claim: all 3 have
expected time complexity
 $O(1 + \alpha)$
(worst case $O(n)$)

over
the initial
choice of h

Handling collisions: open addressing

Assume we have h_1, \dots, h_m hash functions
"suitable"



INSERT(x):

For $t = 1$ to m :

if $A[h_t(x)] = x$ return

else if $A[h_t(x)] = \emptyset$ or $A[h_t(x)] = \perp$ then $A[h_t(x)] \leftarrow x$; return

LOOKUP(x):

For $t = 1$ to m :

if $A[h_t(x)] = x$ then return yes

else if $A[h_t(x)] = \emptyset$ then return no

REMOVE(x):

For $t = 1$ to m :

if $A[h_t(x)] = x$ then $A[h_t(x)] \leftarrow \perp$

else if $A[h_t(x)] = \emptyset$ then return

Need
 $\alpha \leq 1$

Handling collisions: open addressing

Theorem. Assuming **stuff**, the expected time complexity of LOOKUP is $O\left(\frac{1}{1-\alpha}\right)$.

stuff: $\forall x, (h_1(x), \dots, h_{m'}(x))$ is a u.a.r. permutation of $[m']$.

Proof.
$$E[T(n, m')] = O(1) + \alpha \cdot E[T(n-1, m'-1)]$$
$$\leq \underbrace{O(1)}_{\text{"handwave"}} + \alpha E[T(n, m')]$$

$$\leadsto E[T(n, m')] = O\left(\frac{1}{1-\alpha}\right)$$

Handling collisions: open addressing (linear probing)

$$\cancel{h_1, \dots, h_m} \rightarrow \boxed{h}$$

$$h_1(x) = h(x)$$

$$h_2(x) = h(x) + 1 \quad [m']$$

$$h_3(x) = h(x) + 2 \quad [m']$$

$$h_m(x) = h(x) + m - 1 \quad [m']$$

Theorem. (Knuth '62) Under some reasonable assumption, expected time complexity of LOOKUP is

$$O\left(\frac{1}{(1-\alpha)^2}\right).$$


Handling collisions: open addressing (cuckoo hashing)



h_1, A_1
 h_2, A_2

LOOKUP, REMOVE : $O(1)$ time (worst-case) !

INSERT : $O(1)$ expected



* Each inserted x is either in $A_1[h_1(x)]$ or $A_2[h_2(x)]$
→ only need to check 2 locations
for LOOKUP and REMOVE

(complicated to prove):
these "eviction sequences"
are short in expectation

* INSERT can take longer:

- ① Try to insert x in $A_1[h_1(x)]$: full
- ② Try to insert x in $A_2[h_2(x)]$: full, so "evict" the y that was there and put x instead
- ③ Try to insert y in $A_1[h_1(y)]$: full, so "evict" the z that was there and put y instead [...]

Hash tables: summary


- h is not "a truly random function" but chosen once and for all, from a small hash family \mathcal{H} (chosen by the algorithm designer) ↑
Usually at least a **universal hash family**
- h is then kept as part of the data structure: $O(\log |\mathcal{H}|)$ bits
- the data itself is not assumed to be random: only the choice of h from \mathcal{H} is
- no silver bullet: things are only good **in expectation** (or with high probability)

Can we do better? Bloom filters!

Faster: $O(1)$ time complexity in the worst case (for real)

Less space: (by constant factors at least)

But LOOKUP is sometimes wrong: false positives



$$\text{LOOKUP}(x) = A[h_1(x)] \wedge A[h_2(x)] \wedge \dots \wedge A[h_k(x)]$$

(k : controls space usage + probability of false positives)
↑
to choose (parameter)

(More in tutorial)

Perspective: why does it work so well? 🧑

"Hashing is fundamental to many algorithms and data structures widely used in practice. For theoretical analysis of hashing, there have been two main approaches. First, one can **assume that the hash function is truly random**, mapping each data item independently and uniformly to the range. **This idealized model is unrealistic** because a truly random hash function requires an exponential number of bits to describe. Alternatively, one can provide rigorous bounds on performance when **explicit families of hash functions are used, such as 2-universal or $O(1)$ -wise independent families**. For such families, performance guarantees are often noticeably weaker than for ideal hashing.

In practice, however, it is commonly observed that simple hash functions, including 2-universal hash functions, perform as predicted by the idealized analysis for truly random hash functions."

📄 *"Why Simple Hash Functions Work: Exploiting the Entropy in a Data Stream."*
Mitzenmacher and Vadhan, 2008