

Decisions: if and if-else statements

Pieter Joubert

October 8, 2023

Decisions: if and if-else statements



Table of Contents

- 1 Planning Decision Making Logic
- 2 if and if-else statements
- 3 Using multiple statements in if and if-else statements
- 4 Nesting if and if-else statements
- 5 Using Logical AND and OR operators
- 6 Lecture summary

Section 1

Planning Decision Making Logic

Making Decisions

- So far we have just looked at storing and manipulating data, with some organisation into methods and classes.
- To really start using the power of our computing devices we need to implement decision making in our programs.
- We have two tools we can use to help us with planning our decisions before we implement them: *Pseudocode* and *Flow-Charts*



Pseudocode

- Pseudocode, as the name implies, is a natural language approach to writing out an algorithm or plan in your code, before writing it in the final language, e.g. Java.


```
01 | Get numbers from user.  
02 | Check if the numbers are bigger than zero and smaller  
    | than 100.  
03 | Add the numbers together.  
04 | Display the numbers back to the user.
```



Flow-Charts

- Flow-Charts are diagrams that show the flow of a program.
- Flow-Charts use various symbols to indicate the different parts of program (e.g. assigning variables, making decisions, display output).
- Flow-Charts use arrows to indicate the flow of logic between these symbols.

Flow-Charts: Example



Section 2

if and if-else statements

The if statement

- The simplest decision is the *if* statement, also known as the *single-alternative selection*.
- We test a condition in the *if* statement. If that condition is true we execute the code in the body of the *if* statement. If the condition is not true the execution of the code carries on after the body of the *if* statement.

```
01 |  if(<condition>) {  
02 |      <code to execute if true>  
03 |  }  
04 |  <code to execute after checking condition>
```



The if statement: Example

```
01 |  if (age >= 18) {  
02 |      System.out.println("Can vote!");  
03 |  }  
04 |  
05 |  System.out.println("Enter name")
```

The if-else statement

- Very often we want to execute some code not only when a condition is true but also if it is false.
- In this case we use the *if* — *else* statement. If the condition is true we execute the first block of code. If the condition is not true we execute the *else* block of code.



The if-else statement: Example

```
01 |  if (age >= 18) {  
02 |      System.out.println("Can vote!");  
03 |  } else {  
04 |      System.out.println("Cannot vote!");  
05 |  }  
06 |  
07 |  System.out.println("Enter name")
```



Section 3

Using multiple statements in if and if-else statements

Multiple Actions

- Very often we want to execute multiple statements if a certain condition is true.
- And multiple statements if a condition is false.
- In either case we need to ensure that all the statements we want to execute are within the same *if* or *else* block.

```
01 |  if (health > 0) {  
02 |      health = health - damage;  
03 |      System.out.println(health);  
04 |  } else {  
05 |      isDead = true;  
06 |      System.out.println("You have died");  
07 |  }
```



Section 4

Nesting if and if-else statements

Nested *if* statements

- We can execute almost any type of code within an *if* statement.
- This includes other *if* statements.
- This can be a useful technique to split up the decisions you need to make into smaller units.

```
01 |  if (health > 0) {  
02 |      health = health - damage;  
03 |      System.out.println(health);  
04 |  } else {  
05 |      if (resurrectionStone == true) {  
06 |          health = 1;  
07 |          isDead = false;  
08 |      } else {  
09 |          isDead = true;  
10 |          System.out.println("You have died");  
11 |      }  
12 |  }
```



Nested *if* statements - example

- Let's code up an example of using nested if statements to play Rock-Paper-Scissors
- We accept some input from the user (R,P,S)
- We will then use a nested if statement to determine what is the best response to the user's move and then print out that move.



Section 5

Using Logical AND and OR operators

Multiple conditions in one if statement

- In Java we can have multiple conditions in one if statement.
- Instead of checking if only ONE condition is true, we can check if condition1 and condition2 are both true, or if at least one is true.
- We can do this with as many conditions as we want.
- The AND operator is written using two ampersand characters: `&&`
- The OR operator is written using two pipe characters: `||`
- Let's update the nested if example to use the AND operator instead.



AND example

```
01 | if (health > 0 && resurrectionStone == true) {  
02 |     health = health - damage;  
03 |     System.out.println(health);  
04 | } else {  
05 |     isDead = true;  
06 |     System.out.println("You have died");  
07 | }
```

- Note that this logic is not exactly the same as the previous example.
- In this case you could die even if your health is above zero if you don't have the resurrection stone.
- Be very careful with using the AND and OR operators. Always double check that your logic is making sense.



OR example

```
01 |  if (health > 0 || resurrectionStone == true) {  
02 |      health = health - damage;  
03 |      System.out.println(health);  
04 |  } else {  
05 |      isDead = true;  
06 |      System.out.println("You have died");  
07 |  }
```

- Note that once again this logic is not exactly the same as the nested if example.
- In this case you wouldn't die if you don't have the resurrection stone but you could get into a situation where you end up with negative health.



Section 6

Lecture summary



Lecture summary

- Planning Decision Making Logic
- if and if-else statements
- Using multiple if and if-else statements
- Nesting if and if-else statements
- Using Logical AND and OR operators

Thank you! Questions?