

```
C:\Users\ccc\latex-short-intro>pdflatex --help
```

```
Usage: pdflatex [OPTION...] [COMMAND...]
```

<code>-alias=APP</code>	Pretend to be APP. This affects both the format used and the search path.
<code>-aux-directory=DIR</code>	Use DIR as the directory to write auxiliary files to.
<code>-buf-size=N</code>	Set buf_size to N.
<code>-c-style-errors</code>	Enable file:line:error style messages.
<code>-disable-8bit-chars</code>	Make only 7-bit characters printable by.
<code>-disable-installer</code>	Disable the package installer. Missing files will not be installed.
<code>-disable-pipes</code>	Disable input (output) from (to) processes.
<code>-disable-write18</code>	Disable the \write18{COMMAND} construct.
<code>-dont-parse-first-line</code>	Do not parse the first line of the input line to look for a dump name and/or extra command-line options.
<code>-draftmode</code>	Switch on draft mode (generates no output).
<code>-enable-8bit-chars</code>	Make all characters printable by default.
<code>-enable-encTeX</code>	Enable EncTeX extensions such as \mubyte.
<code>-enable-etex</code>	Enable e-TeX extensions.
<code>-enable-installer</code>	Enable the package installer. Missing files will be installed.
<code>-enable-mltex</code>	Enable MLTeX extensions such as \charsubdef.
<code>-enable-pipes</code>	Enable input (output) from (to) processes.
<code>-enable-write18</code>	Enable the \write18{COMMAND} construct.
<code>-error-line=N</code>	Set error_line to N.
<code>-extra-mem-bot=N</code>	Set extra_mem_bot to N.
<code>-extra-mem-top=N</code>	Set extra_mem_top to N.
<code>-font-max=N</code>	Set font_max to N.
<code>-font-mem-size=N</code>	Set font_mem_size to N.
<code>-half-error-line=N</code>	Set half_error_line to N.