

Bitcoin: A Peer-to-Peer Electronic Cash System

Satoshi Nakamoto (satoshin@gmx.com, bitcoin.org)

A purely peer-to-peer version of electronic cash would allow online payments to be sent directly from one party to another without going through a financial institution. Digital signatures provide part of the solution, but the main benefits are lost if a trusted third party is still required to prevent double-spending. We propose a solution to the double-spending problem using a peer-to-peer network. The network timestamps transactions by hashing them into an ongoing chain of hash-based proof-of-work, forming a record that cannot be changed without redoing the proof-of-work. The longest chain not only serves as proof of the sequence of events witnessed, but proof that it came from the largest pool of CPU power¹. As long as a majority of CPU power is controlled by nodes that are not cooperating to attack the network, they'll generate the longest chain and outpace attackers. The network itself requires minimal structure. Messages are broadcast on a best effort basis, and nodes can leave and rejoin the network at will, accepting the longest proof-of-work chain as proof of what happened while they were gone.

The original whitepaper has no footnotes or margin notes. We have added these to give further details or clarifications, including changes that have occurred in the Bitcoin implementation.

Suggestions and corrections to this document may be submitted via pull request at its GitHub repository.

¹ Due to the prevalence of specialized equipment such as ASIC miners, references to "CPU power" should be replaced by "hashrate", i.e. the number of sha256 operations per unit time.

Introduction


COMMERCE ON THE INTERNET has come to rely almost exclusively on financial institutions serving as trusted third parties to process electronic payments. While the system works well enough for most transactions, it still suffers from the inherent weaknesses of the trust based model. Completely non-reversible transactions are not really possible, since financial institutions cannot avoid mediating disputes. The cost of mediation increases transaction costs, limiting the minimum practical transaction size and cutting off the possibility for small casual transactions, and there is a broader cost in the loss of ability to make non-reversible payments for nonreversible services. With the possibility of reversal, the need for trust spreads. Merchants must be wary of their customers, hassling them for more information than they would otherwise need. A certain percentage of fraud is accepted as unavoidable. These costs and payment uncertainties can be avoided in person by using physical currency, but no mechanism exists to make payments over a communications channel without a trusted party

What is needed is an electronic payment system based on cryptographic proof instead of trust, allowing any two willing parties to transact directly with each other without the need for a trusted third party. Transactions that are computationally impractical to reverse

announced⁴, and we need a system for participants to agree on a single history of the order in which they were received. The payee needs proof that at the time of each transaction, the majority of nodes agreed it was the first received.

Timestamp Server

THE SOLUTION we propose begins with a timestamp server. A timestamp server works by taking a hash of a block of items to be timestamped and widely publishing the hash, such as in a newspaper or Usenet post^{5,6,7,8}. The timestamp proves that the data must have existed at the time, obviously, in order to get into the hash. Each timestamp includes the previous timestamp in its hash, forming a chain, with each additional timestamp reinforcing the ones before it.



Proof-of-Work

TO IMPLEMENT a distributed timestamp server on a peer-to-peer basis, we will need to use a proof-of-work system similar to Adam Back's Hashcash⁹, rather than newspaper or Usenet posts. The proof-of-work involves scanning for a value that when hashed, such as with SHA-256, the hash begins with a number of zero bits. The average work required is exponential in the number of zero bits required and can be verified by executing a single hash.

For our timestamp network, we implement the proof-of-work by incrementing a nonce in the block until a value is found that gives the block's hash the required zero bits.¹⁰ Once the CPU effort has been expended to make it satisfy the proof-of-work, the block cannot be changed without redoing the work. As later blocks are chained after it, the work to change the block would include redoing all the blocks after it.

The proof-of-work also solves the problem of determining representation in majority decision making. If the majority were based on one-IP-address-one-vote, it could be subverted by anyone able to allocate many IPs. Proof-of-work is essentially one-CPU-one-vote. The

⁴ Wei Dai. b-money. URL <http://www.weidai.com/bmoney>, 1998

⁵ Henri Massias, X Serret Avila, and J-J Quisquater. Design of a secure timestamping service with minimal trust requirement. In *the 20th Symposium on Information Theory in the Benelux*. Citeseer, 1999


⁶ Stornetta W Scott et al. How to timestamp a digital document. *Journal of Cryptology*, 1991

⁷ Dave Bayer, Stuart Haber, and W Scott Stornetta. Improving the efficiency and reliability of digital time-stamping. In *Sequences II*, pages 329–334. Springer, 1993

⁸ Stuart Haber and W Scott Stornetta. Secure names for bit-strings. In *Proceedings of the 4th ACM Conference on Computer and Communications Security*, pages 28–35, 1997

⁹ Adam Back et al. Hashcash-a denial of service counter-measure. URL <http://www.hashcash.org/papers/hashcash.pdf>, 2002

¹⁰ In practice, at current difficulty levels, miners must use an "extra nonce" field in the coinbase transaction.



majority decision is represented by the longest chain, which has the greatest proof-of-work effort invested in it.¹¹ If a majority of CPU power is controlled by honest nodes, the honest chain will grow the fastest and outpace any competing chains. To modify a past block, an attacker would have to redo the proof-of-work of the block and all blocks after it and then catch up with and surpass the work of the honest nodes. We will show later that the probability of a slower attacker catching up diminishes exponentially as subsequent blocks are added.

To compensate for increasing hardware speed and varying interest in running nodes over time, the proof-of-work difficulty is determined by a moving average targeting an average number of blocks per hour. If they're generated too fast, the difficulty increases.

Network

The steps to run the network are as follows:

- 1) New transactions are broadcast to all nodes.
- 2) Each node collects new transactions into a block.
- 3) Each node works on finding a difficult proof-of-work for its block.
- 4) When a node finds a proof-of-work, it broadcasts the block to all nodes.
- 5) Nodes accept the block only if all transactions in it are valid and not already spent.
- 6) Nodes express their acceptance of the block by working on creating the next block in the chain, using the hash of the accepted block as the previous hash.

Nodes always consider the longest chain to be the correct one and will keep working on extending it. If two nodes broadcast different versions of the next block simultaneously, some nodes may receive one or the other first. In that case, they work on the first one they received, but save the other branch in case it becomes longer. The tie will be broken when the next proof-of-work is found and one branch

¹¹ By "longest chain" Satoshi always means the chain with the greatest total POW. This is essentially the sum of the difficulties of the blocks. More precisely, it is the expected value of the number of hashes needed to produce a chain of blocks of those particular difficulties.

Difficulty is defined as the reciprocal of the *target*, which is a 32 byte integer. A block is successfully mined when the block header hash is below the target value.

Difficulty is adjusted every 2016 blocks by computing the

becomes longer; the nodes that were working on the other branch will then switch to the longer one.

New transaction broadcasts do not necessarily need to reach all nodes. As long as they reach many nodes, they will get into a block before long. Block broadcasts are also tolerant of dropped messages. If a node does not receive a block, it will request it when it receives the next block and realizes it missed one.

Incentive

BY CONVENTION, the first transaction in a block is a special transaction that starts a new coin owned by the creator of the block.¹² This adds an incentive for nodes to support the network, and provides a way to initially distribute coins into circulation, since there is no central authority to issue them. The steady addition of a constant of amount of new coins is analogous to gold miners expending resources to add gold to circulation. In our case, it is CPU time and electricity that is expended.

The incentive can also be funded with transaction fees. If the output value of a transaction is less than its input value, the difference is a transaction fee that is added to the incentive value of the block containing the transaction. Once a predetermined number of coins have entered circulation, the incentive can transition entirely to transaction fees and be completely inflation free.

The incentive may help encourage nodes to stay honest. If a greedy attacker is able to assemble more CPU power than all the honest nodes, he would have to choose between using it to defraud people by stealing back his payments, or using it to generate new coins. He ought to find it more profitable to play by the rules, such rules that favour him with more new coins than everyone else combined, than to undermine the system and the validity of his own wealth.¹³

Reclaiming Disk Space

ONCE THE LATEST TRANSACTION in a coin is buried under enough blocks, the spent transactions before it can be discarded to save disk space. To facilitate this without breaking the block's hash, transactions are hashed in a Merkle Tree^{14,15,16}, with only the root included in the block's hash. Old blocks can then be compacted by stubbing off branches of the tree. The interior hashes do not need to be stored.

A block header with no transactions would be about 80 bytes.¹⁷ If


¹² This is the "coinbase" transaction. Its input is effectively set to null values. It is allowed to have one output with an "OP_RETURN" script, which allows storing of up to 80 bytes of arbitrary data. By BIP 2, this data must include the block height. The "extra nonce" is also part of the data, as the nonce field in the block header is not sufficient for mining at current difficulties.

¹³ This still leaves the system vulnerable to a "Goldfinger attack", e.g. any attack motivated by political or ideological motives.

¹⁴ Ralph C Merkle. Protocols for public key cryptosystems. In *1980 IEEE Symposium on Security and Privacy*, pages 122–122. IEEE, 1980

¹⁵ Henri Massias, X Serret Avila, and J-J Quisquater. Design of a secure timestamping service with minimal trust requirement. In *the 20th Symposium on Information Theory in the Benelux*. Citeseer, 1999


¹⁶ Stuart Haber and W Scott Stornetta. Secure names for bit-strings. In *Proceedings of the 4th ACM Conference on Computer and Communications Security*, pages 28–35, 1997



we suppose blocks are generated every 10 minutes¹⁸, 80 bytes * 6 * 24 * 365 = 4.2MB per year. With computer systems typically selling with 2GB of RAM as of 2008, and Moore's Law predicting current growth of 1.2GB per year, storage should not be a problem even if the block headers must be kept in memory.

Simplified Payment Verification

It is possible to verify payments without running a full network node.¹⁹ A user only needs to keep a copy of the block headers of the longest proof-of-work chain, which he can get by querying network nodes until he's convinced he has the longest chain, and obtain the Merkle branch linking the transaction to the block it's timestamped in. He can't check the transaction for himself, but by linking it to a place in the chain, he can see that a network node has accepted it, and blocks added after it further confirm the network has accepted it.



As such, the verification is reliable as long as honest nodes control the network, but is more vulnerable if the network is overpowered by an attacker.²⁰ While network nodes can verify transactions for themselves, the simplified method can be fooled by an attacker's fabricated transactions for as long as the attacker can continue to

¹⁸ The difficulty adjustment is based on an average value of 10 minutes to mine a block.


¹⁹ By "full network node", Satoshi means node that does full validation alongside mining. The original Bitcoin client required mining. Current version of Bitcoin Core allow a node to run full validation on blocks without mining.

²⁰ With the current p2p protocol, a light node needs to connect to only one honest node to recognize the main chain. So a "Sybil attack" can only be successful if the light node is completely isolated from honest nodes.

overpower the network. One strategy to protect against this would be to accept alerts from network nodes when they detect an invalid block, prompting the user's software to download the full block and alerted transactions to confirm the inconsistency. Businesses that receive frequent payments will probably still want to run their own nodes for more independent security and quicker verification.

Combining and Splitting Value

Although it would be possible to handle coins individually, it would be unwieldy to make a separate transaction for every cent in a transfer. To allow value to be split and combined, transactions contain multiple inputs and outputs. Normally there will be either a single input from a larger previous transaction or multiple inputs combining smaller amounts, and at most two outputs: one for the payment, and one returning the change, if any, back to the sender.




It should be noted that fan-out, where a transaction depends on several transactions, and those transactions depend on many more, is not a problem here. There is never the need to extract a complete standalone copy of a transaction's history.

Privacy

The traditional banking model achieves a level of privacy by limiting access to information to the parties involved and the trusted third party. The necessity to announce all transactions publicly precludes this method, but privacy can still be maintained by breaking the flow of information in another place: by keeping public keys anonymous. The public can see that someone is sending an amount to someone else, but without information linking the transaction to anyone. This is similar to the level of information released by stock exchanges, where the time and size of individual trades, the "tape", is made public, but without telling who the parties were.

As an additional firewall, a new key pair should be used for each transaction to keep them from being linked to a common owner.²¹ Some linking is still unavoidable with multi-input transactions, which necessarily reveal that their inputs were owned by the same owner.

²¹ Hierarchical deterministic (HD) wallets provide this protection by generating an essentially infinite supply of keys for use from a root seed, usually represented by a 24 word mnemonic (BIP ?).



The risk is that if the owner of a key is revealed, linking could reveal other transactions that belonged to the same owner.²²

²² Satoshi recognizes the danger of "linking", but he does not propose a solution.

Calculations

We consider the scenario of an attacker trying to generate an alternate chain faster than the honest chain. Even if this is accomplished, it does not throw the system open to arbitrary changes, such as creating value out of thin air or taking money that never belonged to the attacker. Nodes are not going to accept an invalid transaction as payment, and honest nodes will never accept a block containing them. An attacker can only try to change one of his own transactions to take back money he recently spent.

The race between the honest chain and an attacker chain can be characterized as a Binomial Random Walk. The success event is the honest chain being extended by one block, increasing its lead by +1, and the failure event is the attacker's chain being extended by one block, reducing the gap by -1.

The probability of an attacker catching up from a given deficit is analogous to a Gambler's Ruin problem. Suppose a gambler with unlimited credit starts at a deficit and plays potentially an infinite number of trials to try to reach breakeven. We can calculate the probability he ever reaches breakeven, or that an attacker ever catches up with the honest chain, as follows²³:

p = probability an honest node finds the next block

q = probability the attacker finds the next block

q_z = probability the attacker will ever catch up from z blocks behind

$$q_z = \begin{cases} 1 & \text{if } p \leq q \\ (q/p)^z & \text{if } p > q \end{cases}$$

Given our assumption that $p > q$, the probability drops exponentially as the number of blocks the attacker has to catch up with increases. With the odds against him, if he doesn't make a lucky lunge forward early on, his chances become vanishingly small as he falls further behind.

²³ William Feller. An introduction to probability theory and its applications. 1957

We now consider how long the recipient of a new transaction needs to wait before being sufficiently certain the sender can't change the transaction. We assume the sender is an attacker who wants to make the recipient believe he paid him for a while, then switch it to pay back to himself after some time has passed. The receiver will be alerted when that happens, but the sender hopes it will be too late

The receiver generates a new key pair and gives the public key to the sender shortly before signing. This prevents the sender from preparing a chain of blocks ahead of time by working on it continuously until he is lucky enough to get far enough ahead, then executing the transaction at that moment. Once the transaction is sent, the dishonest sender starts working in secret on a parallel chain containing an alternate version of his transaction.

The recipient waits until the transaction has been added to a block and z blocks have been linked after it. He doesn't know the exact amount of progress the attacker has made, but assuming the honest blocks took the average expected time per block, the attacker's potential progress will be a Poisson distribution with expected value:²⁴

$$\lambda = z \frac{q}{p}$$

To get the probability the attacker could still catch up now, we multiply the Poisson density for each amount of progress he could have made by the probability he could catch up from that point:

$$\sum_{k=0}^{\infty} \frac{\lambda^k e^{-\lambda}}{k!} \cdot \begin{cases} (q/p)^{(z-p)} & \text{if } k \leq z \\ 1 & \text{if } k > z \end{cases}$$

Rearranging to avoid summing the infinite tail of the distribution...

$$1 - \sum_{k=0}^z \frac{\lambda^k e^{-\lambda}}{k!} \left(1 - (q/p)^{(z-k)}\right)$$

Converting to C code...

```
#include <math.h>
double AttackerSuccessProbability(double q, int z)
{
    double p = 1.0 - q;
    double lambda = z * (q / p);
    double sum = 1.0;
    int i, k;
    for (k = 0; k <= z; k++)
    {
```

²⁴ The assumption on the time to generate the honest blocks nails down the number of hashes the honest miners needed. Since the attacker's hashrate is in ratio $\frac{q}{p}$, this gives the formula for λ . Technically it may be more correct to consider a binomial distribution here, but the Poisson distribution is a very good approximation and is more handy for calculations here.

```

    double poisson = exp(-lambda);
    for (i = 1; i <= k; i++)
        poisson *= lambda / i;
    sum -= poisson * (1 - pow(q / p, z - k));
}
return sum;
}

```

Running some results, we can see the probability drop off exponentially with z.

```

q=0.1
z=0 P=1.0000000
z=1 P=0.2045873
z=2 P=0.0509779
z=3 P=0.0131722
z=4 P=0.0034552
z=5 P=0.0009137
z=6 P=0.0002428
z=7 P=0.0000647
z=8 P=0.0000173
z=9 P=0.0000046
z=10 P=0.0000012

```

```

q=0.3
z=0 P=1.0000000
z=5 P=0.1773523
z=10 P=0.0416605
z=15 P=0.0101008
z=20 P=0.0024804
z=25 P=0.0006132
z=30 P=0.0001522
z=35 P=0.0000379
z=40 P=0.0000095
z=45 P=0.0000024
z=50 P=0.0000006

```

Solving for P less than 0.1%...

```

P < 0.001
q=0.10 z=5
q=0.15 z=8
q=0.20 z=11

```

This table is apparently the basis for the "6 confirmations" rule-of-thumb. Note, however, that it only shows that 6 confirmations gives less than a 0.1% chance of fraud for an attacker with 10% of the hashrate. Fending off a stronger attacker, such as one of the major mining pools, or reducing the chance of fraud to less than 1 in a 1000 would require significantly more confirmations.

$q=0.25$ $z=15$
 $q=0.30$ $z=24$
 $q=0.35$ $z=41$
 $q=0.40$ $z=89$
 $q=0.45$ $z=340$

Conclusion

We have proposed a system for electronic transactions without relying on trust. We started with the usual framework of coins made from digital signatures, which provides strong control of ownership, but is incomplete without a way to prevent double-spending. To solve this, we proposed a peer-to-peer network using proof-of-work to record a public history of transactions that quickly becomes computationally impractical for an attacker to change if honest nodes control a majority of CPU power. The network is robust in its unstructured simplicity. Nodes work all at once with little coordination. They do not need to be identified, since messages are not routed to any particular place and only need to be delivered on a best effort basis. Nodes can leave and rejoin the network at will, accepting the proof-of-work chain as proof of what happened while they were gone. They vote with their CPU power, expressing their acceptance of valid blocks by working on extending them and rejecting invalid blocks by refusing to work on them. Any needed rules and incentives can be enforced with this consensus mechanism.

References

- Adam Back et al. Hashcash-a denial of service counter-measure. URL <http://www.hashcash.org/papers/hashcash.pdf>, 2002.
- Dave Bayer, Stuart Haber, and W Scott Stornetta. Improving the efficiency and reliability of digital time-stamping. In *Sequences II*, pages 329–334. Springer, 1993.
- Wei Dai. b-money. URL <http://www.weidai.com/bmoney>, 1998.
- William Feller. An introduction to probability theory and its applications. 1957.
- Stuart Haber and W Scott Stornetta. Secure names for bit-strings. In *Proceedings of the 4th ACM Conference on Computer and Communications Security*, pages 28–35, 1997.
- Henri Massias, X Serret Avila, and J-J Quisquater. Design of a secure timestamping service with minimal trust requirement. In *the 20th Symposium on Information Theory in the Benelux*. Citeseer, 1999.

Ralph C Merkle. Protocols for public key cryptosystems. In *1980 IEEE Symposium on Security and Privacy*, pages 122–122. IEEE, 1980.

StornettaW Scott et al. How to time-stamp a digital document. *Journal of Cryptology*, 1991.