

COMP 5143

Advanced Database Management System

Fall 2015

Computer Science Department


Prairie View A&M University

Mary Heejin Kim, Ph.D.

Chapter 12

Entity-Relationship Modeling

ER diagram of Branch user views of DreamHome



3

Concepts of the ER Model

- **Entity types**
- **Relationship types**
- **Attributes**

4

Entity Type

- **Entity type**
 - Group of objects with same properties, identified by enterprise as having an independent existence.
- **Entity occurrence**
 - Uniquely identifiable object of an entity type.


5

Examples of Entity Types

Physical existence	
Staff	Part
Property	Supplier
Customer	Product
Conceptual existence	
Viewing	Sale
Inspection	Work experience

6

ER diagram of Staff and Branch entity types




7

Relationship Types

- **Relationship type**
 - Set of meaningful associations among entity types.
- **Relationship occurrence**
 - Uniquely identifiable association, which includes one occurrence from each participating entity type.


8

Semantic net of *Has* relationship type



9

ER diagram of Branch *Has* Staff relationship




10

Relationship Types

- **Degree of a Relationship**
 - Number of participating entities in relationship.
- **Relationship of degree :**
 - two is binary
 - three is ternary
 - four is quaternary.


11

Binary relationship called *POwns*




12

Ternary relationship called *Registers*



13

Quaternary relationship called *Arranges*




14

Relationship Types

- **Recursive Relationship**
 - Relationship type where *same* entity type participates more than once in *different roles*.
- Relationships may be given role names to indicate purpose that each participating entity type plays in a relationship.


15

Recursive relationship called *Supervises* with role names



16

Entities associated through two distinct relationships with role names



17

Attributes

- **Attribute**
 - Property of an entity or a relationship type.
- **Attribute Domain**
 - Set of allowable values for one or more attributes.

18

Attributes

- **Simple Attribute**
 - Attribute composed of a single component with an independent existence.
- **Composite Attribute**
 - Attribute composed of multiple components, each with an independent existence.

19

Attributes

- **Single-valued Attribute**
 - Attribute that holds a single value for each occurrence of an entity type.
- **Multi-valued Attribute**
 - Attribute that holds multiple values for each occurrence of an entity type.

20

Attributes

- **Derived Attribute**
 - Attribute that represents a value that is derivable from value of a related attribute, or set of attributes, not necessarily in the same entity type.


21

Keys

- **Candidate Key**
 - Minimal set of attributes that uniquely identifies each occurrence of an entity type.
- **Primary Key**
 - Candidate key selected to uniquely identify each occurrence of an entity type.
- **Composite Key**
 - A candidate key that consists of two or more attributes.

22

ER diagram of Staff and Branch entities and their attributes




23

Entity Type

- **Strong Entity Type**
 - Entity type that is *not* existence-dependent on some other entity type.
- **Weak Entity Type**
 - Entity type that is existence-dependent on some other entity type.


24

Strong entity type called Client and weak entity type called Preference



25

Relationship called *Advertises* with attributes



26

Structural Constraints

- Main type of constraint on relationships is called *multiplicity*.
- Multiplicity - number (or range) of possible occurrences of an entity type that may relate to a single occurrence of an associated entity type through a particular relationship.
- Represents policies (called *business rules*) established by user or company.


27

Structural Constraints

- The most common degree for relationships is binary.
- Binary relationships are generally referred to as being:
 - one-to-one (1:1)
 - one-to-many (1:*)
 - many-to-many (*:*)


28

Semantic net of Staff *Manages* Branch relationship type




29

Multiplicity of Staff *Manages* Branch (1:1) relationship




30

Semantic net of Staff *Oversees* PropertyForRent relationship type




31

Multiplicity of Staff *Oversees* PropertyForRent (1:*) relationship type




32

Semantic net of Newspaper *Advertises* PropertyForRent relationship type



33

Multiplicity of Newspaper *Advertises* PropertyForRent (*:*) relationship




34

Structural Constraints

- **Multiplicity for Complex Relationships**
 - Number (or range) of possible occurrences of an entity type in an n -ary relationship when other $(n-1)$ values are fixed.


35

Semantic net of ternary *Registers* relationship with values for Staff and Branch entities fixed



36

Multiplicity of ternary *Registers* relationship



Summary of multiplicity constraints

Alternative ways to represent multiplicity constraints	Meaning
0..1	Zero or one entity occurrence
1..1 (or just 1)	Exactly one entity occurrence
0..* (or just *)	Zero or many entity occurrences
1..*	One or many entity occurrences
5..10	Minimum of 5 up to a maximum of 10 entity occurrences
0, 3, 6–8	Zero or three or six, seven, or eight entity occurrences

Structural Constraints

- Multiplicity is made up of two types of restrictions on relationships: *cardinality* and *participation*.


39

Structural Constraints

- **Cardinality**
 - Describes maximum number of possible relationship occurrences for an entity participating in a given relationship type.
- **Participation**
 - Determines whether all or only some entity occurrences participate in a relationship.

40

Multiplicity as cardinality and participation constraints



41

Problems with ER Models

- Problems may arise when designing a conceptual data model called *connection traps*.
- Often due to a misinterpretation of the meaning of certain relationships.
- Two main types of connection traps are called *fan traps* and *chasm traps*.

42

Problems with ER Models

- **Fan Trap**
 - Where a model represents a relationship between entity types, but pathway between certain entity occurrences is ambiguous.
- **Chasm Trap**
 - Where a model suggests the existence of a relationship between entity types, but pathway does not exist between certain entity occurrences.


43

An Example of a Fan Trap



44


Semantic Net of ER Model with Fan Trap



- At which branch office does staff number SG37 work?


45

Restructuring ER model to remove Fan Trap



46

Semantic Net of Restructured ER Model with Fan Trap Removed



- **SG37 works at branch B003.**


47

An Example of a Chasm Trap



48


Semantic Net of ER Model with Chasm Trap



- **At which branch office is property PA14 available?**

49

ER Model restructured to remove Chasm Trap



50

Semantic Net of Restructured ER Model with Chasm Trap Removed

