

Problem 1: Floating Point (14points)


1. [1] 7 [2] 1 1111 00000000
[3] 0 1110 11111111 [4] 0 0000 00000001 / 0 0000 00000000
2. (1 1001 00110100)₂
3. 0.40625 * 2⁻⁶
4. (1) (0 0100 10111100)₂ = 1.10111100 * 2⁻³
(0 1000 10001000)₂ = 1.10001000 * 2¹
(2) (0 0100 10111100)₂ = 1.10111100 * 2⁻³
= 0.000110111100 * 2¹
(3) 1.10001000 * 2¹+ 0.000110111100 * 2¹
= 1.101000111100 * 2¹
= 1.10100100 * 2¹(Round-to Even) (or (0 1000 10100100))

Problem 2: X86-64 (14points)


- ```
1 [1] -8(%rbp) [2] %esi [3] %edi [4] -4(%rbp)
 [5] %edx [6] -36(%rbp) [7] -32(%rbp,%rax,4)
```

### Problem 3: Memory Allocation (14points)

- 1 1) 2nd operation



- 2) 4th operation:



- 2 P3:  $24-10=14$ , P4:  $16-3=13$ , P5:  $24-15=9$ .  $14+13+9=36$  bytes. (ambiguous)
- 3 8 bytes (problematic)

### Problem 4: Cache (16points)

- |    |      |    |      |     |      |      |     |   |
|----|------|----|------|-----|------|------|-----|---|
| 1. | [1]  | 32 | [2]  | 8   | [3]  | 2    | [4] | 2 |
| 2. | [1]  | 1  | [2]  | Yes | [3]  | Oxcd |     |   |
|    | [4]  | 1  | [5]  | No  | [6]  | --   |     |   |
|    | [7]  | 1  | [8]  | Yes | [9]  | --   |     |   |
|    | [10] | 1  | [11] | No  | [12] | --   |     |   |

### Problem 5: Linking (26points)

```

1. [1] 03 [2] $0x3
 [3] 04 [4] $0x4
2. [1] R_386_32 [2] 0x2f [3] R_386_32 [4] R_386_PC32
 [5] 0x3a [6] 0x15 [7] R_386_PC32 [8] R_386_PC32
 [9] .rodata [10] R_386_32 [11] 0x2b [12] .rodata
3. [1] 05 48 a0 04 08 [2] e8 a5 ff ff ff
 [3] e8 f3 fe ff ff
4. [1] 0x08048346 [2] 5

```

#### Problem 6: Optimization (16points)

```

1. // eliminate unneeded memory references
 int local_min = 200, local_max = 99;
 // local variables for expansion of function
 int elem;
 // reduce procedure calls
 int row_cnt = row_count(p);
 // Failed to combine the two loops won't affect your grade!
 for (int i = 0; i < row_cnt; i++) {
 for (int j = 0; j < 2; j++) {
 // expansion of function in loop
 elem = p->base[i * 2 + j];
 if (elem < local_min) local_min = elem;
 if (elem > local_max) local_max = elem;
 }
 }
 // eliminate unneeded memory references
 *max = local_max; *min = local_min;

2.
 // Failed to combine the two loops won't affect your grade!
 int local_min = 200, local_max = 99;
 for (int i = 0; i < row_cnt; i++) {
 int elem0, elem1;
 elem0 = p->base[i * 2];
 if (elem0 > local_max) local_max = elem0;
 if (elem0 < local_min) local_min = elem0;
 // loop unrolling
 elem1 = p->base[i * 2 + 1];
 if (elem1 > local_max) local_max = elem1;
 if (elem1 < local_min) local_min = elem1;
 }
 *max = local_max; *min = local_min;

```

OR

```
int local_min = 200, local_max = 99;
// Treat 2d array as 1d array.
int elem_cnt = row_count(p) * 2;
for (int i = 0; i < elem_cnt; i++) {
 int elem = p->base[i];
 if (elem > local_max) local_max = elem;
 if (elem < local_min) local_min = elem;
}
*max = local_max; *min = local_min;
```