



Federal University of Rio de Janeiro

Toss a balloon to your coder

Chris Ciafrino, Letícia Freire and Gabriel de Março

Contest (1)

template.cpp30 lines

```
#include <bits/stdc++.h>
using namespace std;

using lint = long long;
using ldouble = long double;
const double PI = static_cast<double>(acosl(-1.0));

// Returns -1 if a < b, 0 if a = b and 1 if a > b.
int cmp_double(double a, double b = 0, double eps = 1e-9) {
    return a + eps > b ? b + eps > a ? 0 : 1 : -1;
}

array<int, 4> dx = {-1, 0, 1, 0};
array<int, 4> dy = {0, 1, 0, -1};

int main() {
    cin.tie(0)->sync_with_stdio(0);
    cin.exceptions(cin.failbit);
}
```

.bashrc3 lines

```
alias c='g++ -Wall -Wconversion -Wfatal-errors -g -std=c++14 \
-fsanitize=undefined,address'
xmodmap -e 'clear lock' -e 'keycode 66=less greater' #caps = ⇐
```

.vimrc6 lines

```
set cin aw ai is ts=4 sw=4 tm=50 nu noeb bg=dark ru cul
sy on | im jk <esc> | im kj <esc> | no ; :
" Select region and then type :Hash to hash your selection.
" Useful for verifying that there aren't mistypes.
ca Hash w !cpp -dD -P -fpreprocessed \ | tr -d '[:space:]' \
\ | md5sum \ | cut -c-6
```

hash.sh3 lines

```
# Hashes a file, ignoring all whitespace and comments. Use for
# verifying that code was correctly typed.
cpp -dD -P -fpreprocessed | tr -d '[:space:]' | md5sum |cut -c-6
```

troubleshoot.txt52 lines

```
Pre-submit:
Write a few simple test cases if sample is not enough.
Are time limits close? If so, generate max cases.
Is the memory usage fine?
Could anything overflow?
Make sure to submit the right file.
```

```
Wrong answer:
Print your solution! Print debug output, as well.
Are you clearing all data structures between test cases?
Can your algorithm handle the whole range of input?
Read the full problem statement again.
Do you handle all corner cases correctly?
Have you understood the problem correctly?
Any uninitialized variables?
Any overflows?
Confusing N and M, i and j, etc.?
Are you sure your algorithm works?
What special cases have you not thought of?
Are you sure the STL functions you use work as you think?
Add some assertions, maybe resubmit.
Create some testcases to run your algorithm on.
```

Go through the algorithm for a simple case.
Go through this list again.
Explain your algorithm to a teammate.
Ask the teammate to look at your code.
Go for a small walk, e.g. to the toilet.
Is your output format correct? (including whitespace)
Rewrite your solution from the start or let a teammate do it.

Runtime error:
Have you tested all corner cases locally?
Any uninitialized variables?
Are you reading or writing outside the range of any vector?
Any assertions that might fail?
Any possible division by 0? (mod 0 for example)
Any possible infinite recursion?
Invalidated pointers or iterators?
Are you using too much memory?
Debug with resubmits (e.g. remapped signals, see Various).

Time limit exceeded:
Do you have any possible infinite loops?
What is the complexity of your algorithm?
Are you copying a lot of unnecessary data? (References)
How big is the input and output? (consider scanf)
Avoid vector, map. (use arrays/unordered_map)
What do your teammates think about your algorithm?

Memory limit exceeded:
What is the max amount of memory your algorithm should need?
Are you clearing all data structures between test cases?

Mathematics (2)

2.1 Equations

$$ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

The extremum is given by $x = -b/2a$.

$$\begin{aligned} ax + by &= e & x &= \frac{ed - bf}{ad - bc} \\ cx + dy &= f & y &= \frac{af - ec}{ad - bc} \end{aligned} \Rightarrow$$

In general, given an equation $Ax = b$, the solution to a variable x_i is given by

$$x_i = \frac{\det A'_i}{\det A}$$

where A'_i is A with the i 'th column replaced by b .

2.2 Recurrences

If $a_n = c_1a_{n-1} + \dots + c_ka_{n-k}$, and r_1, \dots, r_k are distinct roots of $x^k + c_1x^{k-1} + \dots + c_k$, there are d_1, \dots, d_k s.t.

$$a_n = d_1r_1^n + \dots + d_kr_k^n.$$

Non-distinct roots r become polynomial factors, e.g.
 $a_n = (d_1n + d_2)r^n$.

2.3 Master theorem

Given a recurrence of the form $T(n) = aT(\frac{n}{b}) + f(n)$ where $a \geq 1, b > 1$.

1) If $f(n) = \mathcal{O}(n^{\log_b a - \epsilon})$ for some $\epsilon > 0$, then

$$T(n) = \Theta(n^{\log_b a})$$

2) If $f(n) = \Theta(n^{\log_b a})$, then

$$T(n) = \Theta(n^{\log_b a} \log n)$$

3) If $f(n) = \Omega(n^{\log_b a + \epsilon})$ for some $\epsilon > 0$ (and $af(\frac{n}{b}) \leq cf(n)$ for some $c < 1$ for all n sufficiently large), then

$$T(n) = \Theta(f(n))$$

2.4 Trigonometry

$$\sin(v + w) = \sin v \cos w + \cos v \sin w$$

$$\cos(v + w) = \cos v \cos w - \sin v \sin w$$

$$\tan(v + w) = \frac{\tan v + \tan w}{1 - \tan v \tan w}$$

$$\sin v + \sin w = 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$\cos v + \cos w = 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where V, W are lengths of sides opposite angles v, w .

$$a \cos x + b \sin x = r \cos(x - \phi)$$

$$a \sin x + b \cos x = r \sin(x + \phi)$$

where $r = \sqrt{a^2 + b^2}, \phi = \text{atan2}(b, a)$.

2.5 Geometry

2.5.1 Triangles

Side lengths: a, b, c

Semiperimeter: $p = \frac{a + b + c}{2}$

Area: $A = \sqrt{p(p - a)(p - b)(p - c)}$

Circumradius: $R = \frac{abc}{4A}$

Inradius: $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles):
 $m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$

Length of bisector (divides angles in two):

$$s_a = \sqrt{bc \left[1 - \left(\frac{a}{b + c} \right)^2 \right]}$$

Law of sines: $\frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}$

Law of cosines: $a^2 = b^2 + c^2 - 2bc \cos \alpha$

Law of tangents: $\frac{a+b}{a-b} = \frac{\tan \frac{\alpha+\beta}{2}}{\tan \frac{\alpha-\beta}{2}}$

Pick's: A polygon on an integer grid strictly containing i lattice points and having b lattice points on the boundary has area $i + \frac{b}{2} - 1$. (Nothing similar in higher dimensions)


2.5.2 Quadrilaterals

With side lengths a, b, c, d , diagonals e, f , diagonals angle θ , area A and magic flux $F = b^2 + d^2 - a^2 - c^2$:

$$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is 180° , $ef = ac + bd$, and $A = \sqrt{(p-a)(p-b)(p-c)(p-d)}$.

2.5.3 Spherical coordinates



$$x = r \sin \theta \cos \phi$$
$$y = r \sin \theta \sin \phi$$
$$z = r \cos \theta$$

$$r = \sqrt{x^2 + y^2 + z^2}$$
$$\theta = \arccos(z / \sqrt{x^2 + y^2 + z^2})$$
$$\phi = \operatorname{atan2}(y, x)$$

2.5.4 Centroid of a polygon

The x coordinate of the centroid of a polygon is given by $\frac{1}{3A} \sum_{i=0}^{n-1} (x_i + x_{i+1})(x_i y_{i+1} - x_{i+1} y_i)$, where A is twice the signed area of the polygon.

2.6 Derivatives/Integrals

$$\frac{d}{dx} \arcsin x = \frac{1}{\sqrt{1-x^2}}$$
$$\frac{d}{dx} \arccos x = -\frac{1}{\sqrt{1-x^2}}$$

$$\frac{d}{dx} \tan x = 1 + \tan^2 x$$
$$\frac{d}{dx} \arctan x = \frac{1}{1+x^2}$$

$$\int \tan ax = -\frac{\ln |\cos ax|}{a}$$
$$\int x \sin ax = \frac{\sin ax - ax \cos ax}{a^2}$$

$$\int e^{-x^2} = \frac{\sqrt{\pi}}{2} \operatorname{erf}(x)$$
$$\int x e^{ax} dx = \frac{e^{ax}}{a^2} (ax - 1)$$

Integration by parts:

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

2.6.1 XOR sum

$$\bigoplus_{x=0}^{n-1} x = \{0, n-1, 1, n\}[n \bmod 4]$$

$$\bigoplus_{x=l}^{r-1} x = \bigoplus_{a=0}^{r-1} a \oplus \bigoplus_{b=0}^{l-1} b$$

2.7 Sums

$$c^a + c^{a+1} + \dots + c^b = \frac{c^{b+1} - c^a}{c - 1}, c \neq 1$$

$$1 + 2 + 3 + \dots + n = \frac{n(n+1)}{2}$$
$$1^2 + 2^2 + 3^2 + \dots + n^2 = \frac{n(2n+1)(n+1)}{6}$$
$$1^3 + 2^3 + 3^3 + \dots + n^3 = \frac{n^2(n+1)^2}{4}$$
$$1^4 + 2^4 + 3^4 + \dots + n^4 = \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}$$

2.8 Series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots, (-\infty < x < \infty)$$
$$\ln(1+x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots, (-1 < x \leq 1)$$
$$\sqrt{1+x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \dots, (-1 \leq x \leq 1)$$

$$\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \dots, (-\infty < x < \infty)$$
$$\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \dots, (-\infty < x < \infty)$$

2.9 Probability theory

Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x . It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y ,

$$V(aX + bY) = a^2V(X) + b^2V(Y).$$

2.9.1 Discrete distributions

Binomial distribution

The number of successes in n independent yes/no experiments, each which yields success with probability p is $\operatorname{Bin}(n, p)$, $n = 1, 2, \dots$, $0 \leq p \leq 1$.

$$p(k) = \binom{n}{k} p^k (1-p)^{n-k}$$

$$\mu = np, \sigma^2 = np(1-p)$$

$\operatorname{Bin}(n, p)$ is approximately $\operatorname{Po}(np)$ for small p .

First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each wich yields success with probability p is $\operatorname{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1-p)^{k-1}, k = 1, 2, \dots$$

$$\mu = \frac{1}{p}, \sigma^2 = \frac{1-p}{p^2}$$

Poisson distribution

The number of events occurring in a fixed period of time t if these events occur with a known average rate κ and independently of the time since the last event is $\operatorname{Po}(\lambda)$, $\lambda = t\kappa$.

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, k = 0, 1, 2, \dots$$

$$\mu = \lambda, \sigma^2 = \lambda$$

2.9.2 Continuous distributions

Uniform distribution

If the probability density function is constant between a and b and 0 elsewhere it is $\operatorname{U}(a, b)$, $a < b$.

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$

$$\mu = \frac{a+b}{2}, \sigma^2 = \frac{(b-a)^2}{12}$$

Exponential distribution

The time between events in a Poisson process is $\operatorname{Exp}(\lambda)$, $\lambda > 0$.

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$

$$\mu = \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2}$$


```

    segtree_t(const vector<T>& other) : seg(2*N, unit), lazy(2*
        N) {
        for (int a = 0; a < int(other.size()); ++a) seg[a + N]
            = other[a];
        for (int a = N-1; a; --a) pull(a);
    }
    void push(int v, int L, int R) {
        seg[v] += (R - L + 1) * lazy[v]; // dependent on operation
        if (L != R) for(int i = 0; i < 2; ++i) lazy[2*v+i] +=
            lazy[v];
    }
    lazy[v] = 0;
    } // recalc values for current node
    void pull(int v) { seg[v] = f(seg[2*v], seg[2*v+1]); }
    void build() { for(int i = N-1; i > 0; --i) pull(i); }
    void upd(int mi,int ma,T delta,int v = 1,int L = 0, int R =
        N-1) {
        push(v,L,R); if (ma < L || R < mi) return;
        if (mi <= L && R <= ma) {
            lazy[v] = delta; push(v,L,R); return; }
        int M = (L+R)/2; upd(mi,ma,delta,2*v,L,M);
        upd(mi,ma,delta,2*v+1,M+1,R); pull(v);
    }
    T query(int mi, int ma, int v = 1, int L = 0, int R = N-1)
        {
        push(v,L,R); if (mi > R || L > ma) return unit;
        if (mi <= L && R <= ma) return seg[v];
        int M = (L+R)/2;
        return f(query(mi,ma,2*v,L,M),query(mi,ma,2*v+1,M+1,R));
    }
};

```

sparse-segtree.h

Description: Sparse Segment Tree with point update. Doesnt allocate storage for nodes with no data. Use BumpAllocator for better performance!

```

const int SZ = 1<<19;
template<class T> struct node_t {
    T delta = 0; node_t<T>* c[2];
    node_t() { c[0] = c[1] = nullptr; }
    void upd(int pos, T v, int L = 0, int R = SZ-1) { // add v
        if (L == pos && R == pos) { delta += v; return; }
        int M = (L + R)>>1;
        if (pos <= M) {
            if (!c[0]) c[0] = new node_t();
            c[0]->upd(pos, v, L, M);
        } else {
            if (!c[1]) c[1] = new node_t();
            c[1]->upd(pos, v, M+1, R);
        }
        delta = 0;
        for (int i = 0; i < 2; ++i) if (c[i]) delta += c[i]->delta;
    }
    T query(int lx, int rx, int L = 0, int R = SZ-1) { // query
        sum of segment
        if (rx < L || R < lx) return 0;
        if (lx <= L && R <= rx) return delta;
        int M = (L + R)>>1; T res = 0;
        if (c[0]) res += c[0]->query(lx, rx, L, M);
        if (c[1]) res += c[1]->query(lx, rx, M+1, R);
        return res;
    }
    void upd(int pos, node_t *a, node_t *b, int L = 0, int R = SZ
        -1) {
        if (L != R) {
            int M = (L + R)>>1;
            if (pos <= M) {
                if (!c[0]) c[0] = new node_t();
                c[0]->upd(pos, a ? a->c[0] : nullptr, b ? b->c[0] :
                    nullptr, L, M);
            }
        }
    }
};

```

```

    } else {
        if (!c[1]) c[1] = new node_t();
        c[1]->upd(pos,a ? a->c[1] : nullptr, b ? b->c[1] :
            nullptr, M+1, R);
    }
    }
    delta = (a ? a->delta : 0)+(b ? b->delta : 0);
    }
};

```

segtree-2d.h

Description: 2D Segment Tree.

```

"sparse-segtree.h" 09098e, 25 lines
template<class T> struct Node {
    node_t<T> seg; Node* c[2];
    Node() { c[0] = c[1] = nullptr; }
    void upd(int x, int y, T v, int L = 0, int R = SZ-1) { //
        add v
        if (L == x && R == x) { seg.upd(y,v); return; }
        int M = (L+R)>>1;
        if (x <= M) {
            if (!c[0]) c[0] = new Node();
            c[0]->upd(x,y,v,L,M);
        } else {
            if (!c[1]) c[1] = new Node();
            c[1]->upd(x,y,v,M+1,R);
        }
        seg.upd(y,v); // only for addition
        // seg.upd(y,c[0]?&c[0]->seg:nullptr,c[1]?&c[1]->seg:
            nullptr);
    }
    T query(int x1, int x2, int y1, int y2, int L = 0, int R =
        SZ-1) { // query sum of rectangle
        if (x1 <= L && R <= x2) return seg.query(y1,y2);
        if (x2 < L || R < x1) return 0;
        int M = (L+R)>>1; T res = 0;
        if (c[0]) res += c[0]->query(x1, x2, y1, y2, L, M);
        if (c[1]) res += c[1]->query(x1, x2, y1, y2, M+1, R);
        return res;
    }
};

```

merge-sort-tree.h

Description: Build segment tree where each node stores a sorted version of the underlying range.

Time: $\mathcal{O}(\log^2 N)$

```

struct merge_sort_tree {
    vector<int> v, id;
    vector<vector<int>> tree;
    merge_sort_tree(vector<int> &v) : v(v), tree(4*(v.size()+1)
        ) {
        for(int i = 0; i < v.size(); ++i) id.push_back(i);
        sort(id.begin(), id.end(), [&v](int i, int j) { return
            v[i] < v[j]; });
        build(1, 0, v.size()-1);
    }
    void build(int id, int left, int right) {
        if (left == right) tree[id].push_back(id[left]);
        else {
            int mid = (left + right)>>1;
            build(id<<1, left, mid);
            build(id<<1|1, mid+1, right);
            tree[id] = vector<int>(right - left + 1);
            merge(tree[id<<1].begin(), tree[id<<1].end(),
                tree[id<<1|1].begin(), tree[id<<1|1].end(),
                tree[id].begin());
        }
    }
};

```

```

// how many elements in this node have id in the range [a,b
    ]
    int how_many(int id, int a, int b) {
        return (int)(upper_bound(tree[id].begin(), tree[id].end
            (), b)
            - lower_bound(tree[id].begin(), tree[id].end(), a))
            ;
    }
    int query(int id, int left, int right, int a, int b, int x)
        {
        if (left == right) return v[tree[id].back()];
        int mid = (left + right)>>1;
        int lcount = how_many(id<<1, a, b);
        if (lcount >= x) return query(id<<1, left, mid, a, b, x
            );
        else return query(id<<1|1, mid+1, right, a, b, x -
            lcount);
        }
    int kth(int a, int b, int k) {
        return query(1, 0, v.size()-1, a, b, k);
    }
};

```

rmq.h

Description: Range Minimum/Maximum Queries on an array. Returns $\min(V[a], V[a + 1], \dots, V[b - 1])$ in constant time. Returns a pair that holds the answer, first element is the value and the second is the index.

Usage: `rmq_t<pair<int, int>> rmq(values);` // values is a vector of pairs {val(i), index(i)}
`rmq.query(inclusive, inclusive);`
`rmqt<pair<int, int>, greater<pair<int, int>>> rmq(values)`
//max query

Time: $\mathcal{O}(|V| \log |V| + Q)$

```

template<typename T, typename Cmp=less<T>>
struct rmq_t : private Cmp {
    int N = 0;
    vector<vector<T>> table;
    const T& min(const T& a, const T& b) const { return Cmp::
        operator()(a, b) ? a : b; }
    rmq_t() {}
    rmq_t(const vector<T>& values) : N(int(values.size())),
        table(__lg(N) + 1) {
        table[0].resize(N);
        for (int i = 0; i < N; ++i) table[0][i] = values[i];
        for (int a = 1; a < int(table.size()); ++a) {
            table[a].resize(N - (1 << a) + 1);
            for (int b = 0; b + (1 << a) <= N; ++b)
                table[a][b] = min(table[a-1][b], table[a-1][b +
                    (1 << (a-1))]);
        }
    }
    T query(int a, int b) const {
        int lg = __lg(b - a + 1);
        return min(table[lg][a], table[lg][b - (1 << lg) + 1]);
    }
};

```

fenwick-tree.h

Description: Computes partial sums $a[0] + a[1] + \dots + a[\text{pos} - 1]$, and updates single elements $a[i]$, taking the difference between the old and new value.

Time: Both operations are $\mathcal{O}(\log N)$.

```

template<typename T> struct FT {
    vector<T> s;
    FT(int n) : s(n) {}
    void update(int pos, T dif) { // a[pos] += dif
        for (; pos < (int)s.size(); pos |= pos + 1) s[pos] += dif;
    }
};

```

```

}
T query(int pos) { // sum of values in [0, pos)
    T res = 0;
    for (; pos > 0; pos &= pos - 1) res += s[pos-1];
    return res;
}
int lower_bound(T sum) { // min pos st sum of [0, pos] >= sum
    // Returns n if no sum is >= sum, or -1 if empty sum is.
    if (sum <= 0) return -1;
    int pos = 0;
    for (int pw = 1 << 25; pw >= 1) {
        if (pos + pw <= (int)s.size() && s[pos + pw-1] < sum)
            pos += pw, sum -= s[pos-1];
    }
    return pos;
}
};
```

fenwick-tree-2d.h

Description: Computes sums $a[i,j]$ for all $i < I, j < J$, and increases single elements $a[i,j]$. Requires that the elements to be updated are known in advance (call `fakeUpdate()` before `init()`).

Time: $\mathcal{O}(\log^2 N)$. (Use persistent segment trees for $\mathcal{O}(\log N)$.)

```
"fenwick_tree.h" 4b694a, 21 lines

template<typename T> struct FT2 {
    vector<vector<int>>> ys; vector<FT<T>>> ft;
    FT2(int limx) : ys(limx) {}
    void fakeUpdate(int x, int y) {
        for (; x < (int)ys.size(); x |= x + 1) ys[x].push_back(y);
    }
    void init() {
        for(auto v : ys) sort(v.begin(), v.end()), ft.emplace_back(
            v.size());
    }
    int ind(int x, int y) {
        return (int)(lower_bound(ys[x].begin(), ys[x].end(), y) -
            ys[x].begin());
    }
    void update(int x, int y, T dif) {
        for (; x < ys.size(); x |= x + 1)
            ft[x].update(ind(x, y), dif);
    }
    T query(int x, int y) {
        T sum = 0;
        for (; x; x &= x - 1) sum += ft[x-1].query(ind(x-1, y));
        return sum;
    }
};
```

mo.h

Description: Answer interval or tree path queries by finding an approximate TSP through the queries, and moving from one query to the next by adding/removing points at the ends. If values are on tree edges, change step to add/remove the edge (a,c) and remove the initial add call (but keep in).

Time: $\mathcal{O}(N\sqrt{Q})$

```
867473, 49 lines

void add(int ind, int end) { ... } // add a[ind] (end = 0 or 1)
void del(int ind, int end) { ... } // remove a[ind]
int calc() { ... } // compute current answer

vector<int> mo(vector<pair<int, int>> Q) {
    int L = 0, R = 0, blk = 350; // ~N/sqrt(Q)
    vector<int> s(int(Q.size())), res = s;
    #define K(x) pair<int, int>(x.first/blk, x.second ^ -(x.first/
        blk & 1))
    iota(s.begin(), S.end(), 0);
    sort(s.begin(), s.end(), [&](int s, int t){ return K(Q[s]) <
        K(Q[t]); });
    for (int qi : s) {
        auto q = Q[qi];
```

```

        while (L > q.first) add(--L, 0);
        while (R < q.second) add(R++, 1);
        while (L < q.first) del(L++, 0);
        while (R > q.second) del(--R, 1);
        res[qi] = calc();
    }
    return res;
}

vector<int> moTree(vector<array<int, 2>> Q, vector<vector<int
>>& ed, int root=0){
    int N = int(ed.size()), pos[2] = {}, blk = 350; // ~N/sqrt(
        Q)
    vector<int> s(int(Q.size())), res = s, I(N), L(N), R(N), in
        (N), par(N);
    add(0, 0), in[0] = 1;
    auto dfs = [&](int x, int p, int dep, auto& f) -> void {
        par[x] = p;
        L[x] = N;
        if (dep) I[x] = N++;
        for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
        if (!dep) I[x] = N++;
        R[x] = N;
    };
    dfs(root, -1, 0, dfs);
    #define K(x) pii(I[x[0]] / blk, I[x[1]] ^ -(I[x[0]] / blk & 1))
    iota(s.begin(), s.end(), 0);
    sort(s.begin(), s.end(), [&](int s, int t){ return K(Q[s])
        < K(Q[t]); });
    for (int qi : s) for (int end = 0; end < 2; ++end) {
        int &a = pos[end], b = Q[qi][end], i = 0;
    #define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
        else { add(c, end); in[c] = 1; } a = c; }
        while (!(L[b] <= L[a] && R[a] <= R[b]))
            I[i++] = b, b = par[b];
        while (a != b) step(par[a]);
        while (i--) step(I[i]);
        if (end) res[qi] = calc();
    }
    return res;
}
```

line-container.h

Description: Container where you can add lines of the form $kx+m$, and query maximum values at points x . Useful for dynamic programming (“convex hull trick”).

Time: $\mathcal{O}(\log N)$

```
8b2ace, 29 lines

struct Line {
    mutable lint k, m, p;
    bool operator<(const Line& o) const { return k < o.k; }
    bool operator<(lint x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    static const lint inf = LLONG_MAX;
    lint div(lint a, lint b) { // floored division
        return a / b - ((a ^ b) < 0 && a % b);
    }
    bool isect(iterator x, iterator y) {
        if (y == end()) { x->p = inf; return false; }
        if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
        else x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    }
    void add(lint k, lint m) {
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
```

```

        isect(x, erase(y));
    }
    lint query(lint x) {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.k * x + l.m;
    }
};
```

matrix.h

Description: Basic operations on square matrices.

Usage: `Matrix<int> A(N, vector<int>(N));`

1e2632, 30 lines

```
template<typename T> struct Matrix : vector<vector<T>>> {
    using vector<vector<T>>::vector;
    using vector<vector<T>>::size;
    int h() const { return int(size()); }
    int w() const { return int((*this)[0].size()); }
    Matrix operator*(const Matrix& r) const {
        assert(w() == r.h());
        Matrix res(h(), vector<T>(r.w()));
        for (int i = 0; i < h(); ++i) {
            for (int j = 0; j < r.w(); ++j) {
                for (int k = 0; k < w(); ++k) {
                    res[i][j] += (*this)[i][k] * r[k][j];
                }
            }
        }
        return res;
    }
    Matrix& operator*=(const Matrix& r) { return *this = *this
        * r; }
    Matrix pow(int n) const {
        assert(h() == w());
        Matrix x = *this, r(h(), vector<T>(w()));
        for (int i = 0; i < h(); ++i) r[i][i] = T(1);
        while (n) {
            if (n & 1) r *= x;
            x *= x;
            n >>= 1;
        }
        return r;
    }
};
```

submatrix.h

Description: Calculate submatrix sums quickly, given upper-left and lower-right corners (half-open).

Usage: `SubMatrix<int> m(matrix);`

`m.sum(0, 0, 2, 2);` // top left 4 elements

Time: $\mathcal{O}(N^2 + Q)$

```
cd3f87, 13 lines

template<class T> struct SubMatrix {
    vector<vector<T>>> p;
    SubMatrix(vector<vector<T>>& v) {
        int R = v.size(), C = v[0].size();
        p.assign(R+1, vector<T>(C+1));
        for (int r = 0; r < R; ++r)
            for (int c = 0; c < C; ++c)
                p[r+1][c+1] = v[r][c] + p[r][c+1] + p[r+1][c] - p[r][
                    c];
    }
    T sum(int u, int l, int d, int r) {
        return p[d][r] - p[d][l] - p[u][r] + p[u][l];
    }
};
```


wavelet.h

Description: Segment tree on values instead of indices.**Time:** $\mathcal{O}(\log(n))$

80ec5e, 128 lines

```

struct wavelet_t {
    struct BitVector { // space: 32N bits
        vector<int> _rank = {0};
        BitVector(vector<char> v = vector<char>()) {
            _rank.reserve(v.size() + 1);
            for (int d : v) _rank.push_back(_rank.back() + d);
        }
        int rank(bool f, int k) { return f ? _rank[k] : (k - _rank[k]); }
        int rank(bool f, int l, int r) { return rank(f, r) - rank(f, l); }
    };
    /*struct BitVector { // space: 1.5N bits
        vector<ull> v;
        vector<int> _rank;
        BitVector(vector<char> v = vector<char>()) {
            int n = int(_v.size());
            v = vector<ull>((n + 63) / 64);
            _rank = vector<int>(v.size() + 1);
            for (int i = 0; i < n; i++) {
                if (_v[i]) {
                    v[i / 64] |= 1ULL << (i % 64);
                    _rank[i / 64 + 1]++;
                }
            }
            for (int i = 0; i < int(v.size()); i++) {
                _rank[i+1] += _rank[i];
            }
        }
        int rank(int k) {
            int a = _rank[k / 64];
            if (k % 64) a += __builtin_popcountll(v[k / 64] << (64 - k % 64));
            return a;
        }
        int rank(bool f, int k) { return f ? rank(k) : k - rank(k); }
        int rank(bool f, int l, int r) { return rank(f, r) - rank(f, l); }
    };*/
    int n, lg = 1;
    vector<int> mid;
    vector<BitVector> data;
    wavelet_t(vector<int> v = vector<int>()) : n(int(v.size()))
    {
        int ma = 0;
        for (int x : v) ma = max(ma, x);
        while ((1 << lg) <= ma) lg++;
        mid = vector<int>(lg);
        data = vector<BitVector>(lg);
        for (int lv = lg - 1; lv >= 0; lv--) {
            vector<char> buf;
            vector<vector<int>> nx(2);
            for (int d : v) {
                bool f = (d & (1 << lv)) > 0;
                buf.push_back(f);
                nx[f].push_back(d);
            }
            mid[lv] = int(nx[0].size());
            data[lv] = BitVector(buf);
            v.clear();
            v.insert(v.end(), nx[0].begin(), nx[0].end());
            v.insert(v.end(), nx[1].begin(), nx[1].end());
        }
    }
};

```

```

pair<int, int> succ(bool f, int a, int b, int lv) {
    int na = data[lv].rank(f, a) + (f ? mid[lv] : 0);
    int nb = data[lv].rank(f, b) + (f ? mid[lv] : 0);
    return {na, nb};
}
// count i, s.t. (a <= i < b) &&& (v[i] < u)
int rank(int a, int b, int u) {
    if ((1 << lg) <= u) return b - a;
    int ans = 0;
    for (int lv = lg - 1; lv >= 0; lv--) {
        bool f = (u & (1 << lv)) > 0;
        if (f) ans += data[lv].rank(f, a, b);
        tie(a, b) = succ(f, a, b, lv);
    }
    return ans;
}
// k-th(0-indexed!) number in v[a..b]
int select(int a, int b, int k) {
    int u = 0;
    for (int lv = lg - 1; lv >= 0; lv--) {
        int le = data[lv].rank(false, a, b);
        bool f = (le <= k);
        if (f) {
            u += (1 << lv);
            k -= le;
        }
        tie(a, b) = succ(f, a, b, lv);
    }
    return u;
}
// k-th(0-indexed!) largest number in v[a..b]
int large_select(int a, int b, int k) {
    return select(a, b, b - a - k - 1);
}
// count i s.t. (a <= i < b) &&& (x <= v[i] < y)
int count(int a, int b, int x, int y) {
    return rank(a, b, y) - rank(a, b, x);
}
// max v[i] s.t. (a <= i < b) &&& (v[i] < x)
int pre_count(int a, int b, int x) {
    int cnt = rank(a, b, x);
    return cnt == 0 ? -1 : select(a, b, cnt - 1);
}
// min v[i] s.t. (a <= i < b) &&& (x <= v[i])
int nxt_count(int a, int b, int x) {
    int cnt = rank(a, b, x);
    return cnt == b - a ? -1 : select(a, b, cnt);
}
}

```

```

struct CompressWavelet {
    wavelet_t wt;
    vector<int> v, vidx;
    int zip(int x) {
        return int(lower_bound(vidx.begin(), vidx.end(), x) - vidx.begin());
    }
    CompressWavelet(vector<int> v = vector<int>()) : v(_v), vidx(v) {
        sort(vidx.begin(), vidx.end());
        vidx.erase(unique(vidx.begin(), vidx.end()), vidx.end());
    }
    for (auto& d : v) d = zip(d);
    wt = Wavelet(v);
}
int rank(int a, int b, int u) { return wt.rank(a, b, zip(u)); }
int select(int a, int b, int k) { return vidx[wt.select(a, b, k)]; }

```

```

int largest(int a, int b, int k) { return wt.large_select(a, b, k); }
int count(int a, int b, int mi, int ma) { return wt.count(a, b, mi, ma); }
int find_max(int a, int b, int x) { return wt.pre_count(a, b, x); }
int find_min(int a, int b, int x) { return wt.nxt_count(a, b, x); }
};

```

segtree-beats.h

Time: All operations are $\mathcal{O}(\log N)$.

708c6a, 253 lines

```

class segment_tree_beats {
    struct data_t {
        int64_t max;
        int64_t max_second;
        int max_count;
        int64_t min;
        int64_t min_second;
        int min_count;
        int64_t lazy_add;
        int64_t lazy_update;
        int64_t sum;
    };

    int n;
    vector<data_t> a;

public:
    segment_tree_beats() = default;
    segment_tree_beats(int n_) {
        n = 1; while (n < n_) n *= 2;
        a.resize(2 * n - 1);
        tag<UPDATE>(0, 0);
    }
    segment_tree_beats(vector<long long>& A) {
        int n_ = int(A.size());
        n = 1; while (n < n_) n *= 2;
        a.resize(2 * n - 1);
        for (int i = 0; i < n_; ++i) {
            tag<UPDATE>(n - 1 + i, A[i]);
        }
        for (int i = n_; i < n; ++i) {
            tag<UPDATE>(n - 1 + i, 0);
        }
        for (int i = n - 2; i >= 0; --i) update(i);
    }

    void range_chmin(int l, int r, int64_t value) { // 0-based, [l, r)
        assert (0 <= l and l <= r and r <= n);
        range_apply<CHMIN>(0, 0, n, l, r, value);
    }
    void range_chmax(int l, int r, int64_t value) { // 0-based, [l, r)
        assert (0 <= l and l <= r and r <= n);
        range_apply<CHMAX>(0, 0, n, l, r, value);
    }
    void range_add(int l, int r, int64_t value) { // 0-based, [l, r)
        assert (0 <= l and l <= r and r <= n);
        range_apply<ADD>(0, 0, n, l, r, value);
    }
    void range_update(int l, int r, int64_t value) { // 0-based, [l, r)
        assert (0 <= l and l <= r and r <= n);
        range_apply<UPDATE>(0, 0, n, l, r, value);
    }
};

```

```

int64_t range_min(int l, int r) { // 0-based, [l, r)
    assert (0 <= l and l <= r and r <= n);
    return range_get<MIN>(0, 0, n, l, r);
}
int64_t range_max(int l, int r) { // 0-based, [l, r)
    assert (0 <= l and l <= r and r <= n);
    return range_get<MAX>(0, 0, n, l, r);
}
int64_t range_sum(int l, int r) { // 0-based, [l, r)
    assert (0 <= l and l <= r and r <= n);
    return range_get<SUM>(0, 0, n, l, r);
}

private:
static constexpr char CHMIN = 0;
static constexpr char CHMAX = 1;
static constexpr char ADD = 2;
static constexpr char UPDATE = 3;
static constexpr char MIN = 10;
static constexpr char MAX = 11;
static constexpr char SUM = 12;

template <char TYPE>
void range_apply(int i, int il, int ir, int l, int r,
    int64_t g) {
    if (ir <= l or r <= il or break_condition<TYPE>(i, g))
        // break
    } else if (l <= il and ir <= r and tag_condition<TYPE>(
        i, g)) {
        tag<TYPE>(i, g);
    } else {
        pushdown(i);
        range_apply<TYPE>(2 * i + 1, il, (il + ir) / 2, l,
            r, g);
        range_apply<TYPE>(2 * i + 2, (il + ir) / 2, ir, l,
            r, g);
        update(i);
    }
}

template <char TYPE>
inline bool break_condition(int i, int64_t g) {
    switch (TYPE) {
        case CHMIN: return a[i].max <= g;
        case CHMAX: return g <= a[i].min;
        case ADD: return false;
        case UPDATE: return false;
        default: assert (false);
    }
}

template <char TYPE>
inline bool tag_condition(int i, int64_t g) {
    switch (TYPE) {
        case CHMIN: return a[i].max_second < g and g < a[i].
            max;
        case CHMAX: return a[i].min < g and g < a[i].
            min_second;
        case ADD: return true;
        case UPDATE: return true;
        default: assert (false);
    }
}

template <char TYPE>
inline void tag(int i, int64_t g) {
    int length = n >> (32 - __builtin_clz(i + 1) - 1);
    if (TYPE == CHMIN) {
        if (a[i].max == a[i].min or g <= a[i].min) {
            tag<UPDATE>(i, g);

```

```

        return;
    }
    if (a[i].max != INT64_MIN) {
        a[i].sum -= a[i].max * a[i].max_count;
    }
    a[i].max = g;
    a[i].min_second = min(a[i].min_second, g);
    if (a[i].lazy_update != INT64_MAX) {
        a[i].lazy_update = min(a[i].lazy_update, g);
    }
    a[i].sum += g * a[i].max_count;
} else if (TYPE == CHMAX) {
    if (a[i].max == a[i].min or a[i].max <= g) {
        tag<UPDATE>(i, g);
        return;
    }
    if (a[i].min != INT64_MAX) {
        a[i].sum -= a[i].min * a[i].min_count;
    }
    a[i].min = g;
    a[i].max_second = max(a[i].max_second, g);
    if (a[i].lazy_update != INT64_MAX) {
        a[i].lazy_update = max(a[i].lazy_update, g);
    }
    a[i].sum += g * a[i].min_count;
} else if (TYPE == ADD) {
    if (a[i].max != INT64_MAX) {
        a[i].max += g;
    }
    if (a[i].max_second != INT64_MIN) {
        a[i].max_second += g;
    }
    if (a[i].min != INT64_MIN) {
        a[i].min += g;
    }
    if (a[i].min_second != INT64_MAX) {
        a[i].min_second += g;
    }
    a[i].lazy_add += g;
    if (a[i].lazy_update != INT64_MAX) {
        a[i].lazy_update += g;
    }
    a[i].sum += g * length;
} else if (TYPE == UPDATE) {
    a[i].max = g;
    a[i].max_second = INT64_MIN;
    a[i].max_count = length;
    a[i].min = g;
    a[i].min_second = INT64_MAX;
    a[i].min_count = length;
    a[i].lazy_add = 0;
    a[i].lazy_update = INT64_MAX;
    a[i].sum = g * length;
} else {
    assert (false);
}

void pushdown(int i) {
    int l = 2 * i + 1;
    int r = 2 * i + 2;
    // update
    if (a[i].lazy_update != INT64_MAX) {
        tag<UPDATE>(l, a[i].lazy_update);
        tag<UPDATE>(r, a[i].lazy_update);
        a[i].lazy_update = INT64_MAX;
        return;
    }
    // add
    if (a[i].lazy_add != 0) {

```

```

        tag<ADD>(l, a[i].lazy_add);
        tag<ADD>(r, a[i].lazy_add);
        a[i].lazy_add = 0;
    }
    // chmin
    if (a[i].max < a[l].max) {
        tag<CHMIN>(l, a[i].max);
    }
    if (a[i].max < a[r].max) {
        tag<CHMIN>(r, a[i].max);
    }
    // chmax
    if (a[l].min < a[i].min) {
        tag<CHMAX>(l, a[i].min);
    }
    if (a[r].min < a[i].min) {
        tag<CHMAX>(r, a[i].min);
    }
}

void update(int i) {
    int l = 2 * i + 1;
    int r = 2 * i + 2;
    // chmin
    vector<int64_t> b { a[l].max, a[l].max_second, a[r].max
        , a[r].max_second };
    sort(b.rbegin(), b.rend());
    b.erase(unique(b.begin(), b.end()), b.end());
    a[i].max = b[0];
    a[i].max_second = b[1];
    a[i].max_count = (b[0] == a[l].max ? a[l].max_count :
        0) + (b[0] == a[r].max ? a[r].max_count : 0);
    // chmax
    vector<int64_t> c { a[l].min, a[l].min_second, a[r].min
        , a[r].min_second };
    sort(c.begin(), c.end());
    c.erase(unique(c.begin(), c.end()), c.end());
    a[i].min = c[0];
    a[i].min_second = c[1];
    a[i].min_count = (c[0] == a[l].min ? a[l].min_count :
        0) + (c[0] == a[r].min ? a[r].min_count : 0);
    // add
    a[i].lazy_add = 0;
    // update
    a[i].lazy_update = INT64_MAX;
    // sum
    a[i].sum = a[l].sum + a[r].sum;
}

template <char TYPE>
int64_t range_get(int i, int il, int ir, int l, int r) {
    if (ir <= l or r <= il) {
        return 0;
    } else if (l <= il and ir <= r) {
        // base
        switch (TYPE) {
            case MIN: return a[i].min;
            case MAX: return a[i].max;
            case SUM: return a[i].sum;
            default: assert (false);
        }
    } else {
        pushdown(i);
        int64_t value_l = range_get<TYPE>(2 * i + 1, il, (
            il + ir) / 2, l, r);
        int64_t value_r = range_get<TYPE>(2 * i + 2, (il +
            ir) / 2, ir, l, r);
        // mult
        switch (TYPE) {
            case MIN: return min(value_l, value_r);

```



```
        case MAX: return max(value_l, value_r);
        case SUM: return value_l + value_r;
        default: assert (false);
    }
}
};
```

range-color.h
Description: RangeColor structure, supports point queries and range updates, if C isn't int32.t change $freq$ to map
Time: $\mathcal{O}(\lg(L) * Q)$

```
template<class T = int64_t, class C = int32_t> struct
    RangeColor{

    struct Node{
        T left, right;
        C color;
        bool operator < (const Node &n) const{ return right < n.
            right; }
    };

    C minInf;
    set<Node> st;
    vector<T> freq;

    RangeColor(T first, T last, C maxColor, C iniColor = C(0)){
        minInf(first - T(1)), freq(maxColor + 1) {
            freq[iniColor] = last - first + T(1);
            st.insert({first, last, iniColor});
        }
        //get color in position i
        C query(T i){
            auto p = st.upper_bound({T(0), i - T(1), minInf});
            return p->color;
        }
        //set newColor in [a, b]
        void upd(T a, T b, C newColor){
            auto p = st.upper_bound({T(0), a - T(1), minInf});
            assert(p != st.end());
            T left = p->left, right = p->right;
            C old = p->color;
            freq[old] -= (right - left + T(1));
            p = st.erase(p);
            if (left < a){
                freq[old] += (a - left);
                st.insert({left, a - T(1), old});
            }
            if (b < right){
                freq[old] += (right - b);
                st.insert({b + T(1), right, old});
            }
            while ((p != st.end()) && (p->left <= b)){
                left = p->left, right = p->right;
                old = p->color;
                freq[old] -= (right - left + T(1));
                if (b < right){
                    freq[old] += (right - b);
                    st.erase(p);
                    st.insert({b + T(1), right, old});
                    break;
                } else p = st.erase(p);
            }
            freq[newColor] += (b - a + T(1));
            st.insert({a, b, newColor});
        }
    }
    T countColor(C x){ return freq[x]; }
};
```

Numerical (4)

GoldenSectionSearch.h
Description: Finds the argument minimizing the function f in the interval $[a, b]$ assuming f is unimodal on the interval, i.e. has only one local minimum. The maximum error in the result is eps . Works equally well for maximization with a small change in the code. See TernarySearch.h in the Various chapter for a discrete version.
Usage: double func(double x) { return 4+x+.3*x*x; }
double xmin = gss(-1000,1000,func);
Time: $\mathcal{O}(\log((b - a)/\epsilon))$

```
double gss(double a, double b, double (*f)(double)) {
    double r = (sqrt(5)-1)/2, eps = 1e-7;
    double x1 = b - r*(b-a), x2 = a + r*(b-a);
    double f1 = f(x1), f2 = f(x2);
    while (b-a > eps)
        if (f1 < f2) { //change to > to find maximum
            b = x2; x2 = x1; f2 = f1;
            x1 = b - r*(b-a); f1 = f(x1);
        } else {
            a = x1; x1 = x2; f1 = f2;
            x2 = a + r*(b-a); f2 = f(x2);
        }
    return a;
}
```

Polynomial.h

```
struct Poly {
    vector<double> a;
    double operator()(double x) const {
        double val = 0;
        for(int i = a.size(); i--;) (val += x) += a[i];
        return val;
    }
    void diff() {
        for(int i = 1; i < a.size(); ++i) a[i-1] = i*a[i];
        a.pop_back();
    }
    void divroot(double x0) {
        double b = a.back(), c; a.back() = 0;
        for(int i = a.size()-1; i--;) c = a[i], a[i] = a[i+1]*x0+b,
            b=c;
        a.pop_back();
    }
};
```

PolyRoots.h
Description: Finds the real roots to a polynomial.
Usage: poly_roots({{2,-3,1}},-1e9,1e9) // solve $x^2-3x+2 = 0$
Time: $\mathcal{O}(n^2 \log(1/\epsilon))$

```
"Polynomial.h"
vector<double> poly_roots(Poly p, double xmin, double xmax) {
    if ((p.a).size() == 2) { return {-p.a[0]/p.a[1]}; }
    vector<double> ret;
    Poly der = p;
    der.diff();
    auto dr = poly_roots(der, xmin, xmax);
    dr.push_back(xmin-1);
    dr.push_back(xmax+1);
    sort(dr.begin(), dr.end());
    for(int i = 0; i < dr.size()-1; ++i) {
        double l = dr[i], h = dr[i+1];
        bool sign = p(l) > 0;
        if (sign^(p(h) > 0)) {
            for(int it = 0; it < 60; ++it) { // while (h - l > 1e-8)
                double m = (l + h) / 2, f = p(m);
                if ((f <= 0) ^ sign) l = m;
            }
        }
    }
    return ret;
}
```

```
        else h = m;
    }
    ret.push_back((l + h) / 2);
}
}
return ret;
}
```

PolyInterpolate.h
Description: Given n points $(x[i], y[i])$, computes an $n-1$ -degree polynomial p that passes through them: $p(x) = a[0] * x^0 + \dots + a[n-1] * x^{n-1}$. For numerical precision, pick $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \dots n-1$.
Time: $\mathcal{O}(n^2)$

```
typedef vector<double> vd;
vd interpolate(vd x, vd y, int n) {
    vd res(n), temp(n);
    for(int k = 0; k < n-1; ++k) for(int i = k+1; i < n; ++i)
        y[i] = (y[i] - y[k]) / (x[i] - x[k]);
    double last = 0; temp[0] = 1;
    for(int k = 0; k < n; ++k) for(int i = 0; i < n; ++i) {
        res[i] += y[k] * temp[i];
        swap(last, temp[i]);
        temp[i] -= last * x[k];
    }
    return res;
}
```

Lagrange.h
Description: Lagrange Polynomials.
Time: $\mathcal{O}(N)$

```
"ModPow.h", "ModInv.h", "Factorial.h"
template<typename T> struct Lagrange {
    const int n;
    vector<T> f, den;
    Lagrange(vector<T> other) : f(other), n(other.size()) {
        den.resize(n);
        for(int i = 0; i < n; ++i) {
            f[i] = (f[i] % mod + mod) % mod;
            den[i] = ifact[n-i-1] * ifact[i] % mod;
            if ((n-i-1) % 2 == 1)
                den[i] = (mod - den[i]) % mod;
        }
    }
    T interpolate(T x) {
        x %= mod;
        vector<T> l, r;
        l.resize(n); r.resize(n);
        l[0] = r[n-1] = 1;
        for (int i = 1; i < n; ++i)
            l[i] = l[i-1] * (x - (i-1) + mod) % mod;
        for (int i = n-2; i >= 0; --i)
            r[i] = r[i+1] * (x - (i+1) + mod) % mod;
        T ans = 0;
        for (int i = 0; i < n; ++i) {
            T coef = l[i] * r[i] % mod;
            ans = (ans + coef * f[i] % mod * den[i]) % mod;
        }
        return ans;
    }
};
```

BerlekampMassey.h
Description: Recovers any n -order linear recurrence relation from the first $2n$ terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size $\leq n$.
Usage: BerlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}

Time: $\mathcal{O}(N^2)$

"ModularArithmetic.h"4c4a48, 19 lines

```
template <typename num>
vector<num> BerlekampMassey(const vector<num>& s) {
    int n = int(s.size()), L = 0, m = 0;
    vector<num> C(n), B(n), T;
    C[0] = B[0] = 1;
    num b = 1;
    for(int i = 0; i < n; i++) { ++m;
        num d = s[i];
        for (int j = 1; j <= L; j++) d += C[j] * s[i - j];
        if (d == 0) continue;
        T = C; num coef = d / b;
        for (int j = m; j < n; j++) C[j] -= coef * B[j - m];
        if (2 * L > i) continue;
        L = i + 1 - L; B = T; b = d; m = 0;
    }
    C.resize(L + 1); C.erase(C.begin());
    for (auto& x : C) x = -x;
    return C;
}
```

LinearRecurrence.h

Description: Generates the k 'th term of an n -order linear recurrence $S[i] = \sum_j S[i-j-1]tr[j]$, given $S[0 \dots n-1]$ and $tr[0 \dots n-1]$. Faster than matrix multiplication. Useful together with Berlekamp–Massey.

Usage: linearRec({0, 1}, {1, 1}, k) // k 'th Fibonacci number

Time: $\mathcal{O}(n^2 \log k)$

"ModularArithmetic.h"0baa7b, 22 lines

```
template <typename num>
num linearRec(const vector<num>& S, const vector<num>& tr, lint
    k) {
    int n = int(tr.size());
    assert(S.size() >= tr.size());
    auto combine = [&](vector<num> a, vector<num> b) {
        vector<num> res(n * 2 + 1);
        for (int i = 0; i <= n; i++) for (int j = 0; j <= n; j++)
            res[i + j] += a[i] * b[j];
        for (int i = 2 * n; i > n; --i) for (int j = 0; j < n; j++)
            res[i - 1 - j] += res[i] * tr[j];
        res.resize(n + 1);
        return res;
    };
    vector<num> pol(n + 1), e(pol);
    pol[0] = e[1] = 1;
    for (++k; k; k /= 2) {
        if (k % 2) pol = combine(pol, e);
        e = combine(e, e);
    }
    num res = 0;
    for (int i = 0; i < n; i++) res += pol[i + 1] * S[i];
    return res;
}
```

HillClimbing.h

Description: Poor man's optimization for unimodal functions.

47a385, 14 lines

```
typedef array<double, 2> P;

template<class F> pair<double, P> hillClimb(P start, F f) {
    pair<double, P> cur(f(start), start);
    for (double jmp = 1e9; jmp > 1e-20; jmp /= 2) {
        for(int j = 0; j < 100; ++j) for(int dx = -1; dx < 2; ++dx)
            for(int dy = -1; dy < 2; ++dy) {
                P p = cur.second;
                p[0] += dx*jmp;
                p[1] += dy*jmp;
                cur = min(cur, {f(p), p});
            }
    }
}
```

```
    }
    return cur;
}
```

Integrate.h

Description: Simple integration of a function over an interval using Simpson's rule. The error should be proportional to h^4 , although in practice you will want to verify that the result is stable to desired precision when epsilon changes.

7bb98e, 7 lines

```
template<class F>
double quad(double a, double b, F& f, const int n = 1000) {
    double h = (b - a) / 2 / n, v = f(a) + f(b);
    for(int i = 1; i < n*2; ++i)
        v += f(a + i*h) * (i&1 ? 4 : 2);
    return v * h / 3;
}
```

IntegrateAdaptive.h

Description: Fast integration using an adaptive Simpson's rule.

Usage: double sphereVolume = quad(-1, 1, [](double x) { return quad(-1, 1, [&](double y) { return quad(-1, 1, [&](double z) { return x*x + y*y + z*z < 1; } } });

92dd79, 15 lines

```
typedef double d;
#define S(a,b) (f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) / 6

template <class F>
d rec(F& f, d a, d b, d eps, d S) {
    d c = (a + b) / 2;
    d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
    if (abs(T - S) <= 15 * eps || b - a < 1e-10)
        return T + (T - S) / 15;
    return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps / 2, S2);
}

template<class F>
d quad(d a, d b, F f, d eps = 1e-8) {
    return rec(f, a, b, eps, S(a, b));
}
```

Determinant.h

Description: Calculates determinant of a matrix. Destroys the matrix. Tested with modnum and doubles.

Time: $\mathcal{O}(N^3)$

<../Matrix.h>;44cbeb, 27 lines

```
template<typename T> T det(Matrix<T> a) {
    assert(a.h() == a.w());
    int n = a.h();
    bool flip = false;
    for (int x = 0; x < n; ++x) {
        int my = -1;
        for (int y = x; y < n; ++y) {
            if (T(a[y][x]) != 0) {
                my = y;
                break;
            }
        }
        if (my == -1) return 0;
        if (x != my) {
            swap(a[x], a[my]);
            if ((x - my) & 1) flip = !flip;
        }
        for (int y = x + 1; y < n; ++y) {
            if (T(a[y][x]) == 0) continue;
            auto freq = a[y][x] / a[x][x];
            for (int k = x; k < n; k++) a[y][k] -= freq * a[x][k];
        }
    }
}
```

```
    }
    T det = (!flip ? 1 : -1);
    for (int i = 0; i < n; i++) det *= a[i][i];
    return det;
}
```

Elimination.h

Description: Gauss-Jordan algorithm. Transform a matrix into its row echelon form. Returns a vector of pivots (for each variable) or -1 if free variable.

9c481f, 28 lines

```
vector<int> ToRowEchelon(vector<vector<double>>& M) {
    int cons = M.size(), vars = M[0].size() - 1;
    vector<int> pivot(vars, -1);
    int cur = 0;
    for (int var = 0; var < vars; ++var) {
        if (cur >= cons) continue;
        for (int con = cur + 1; con < cons; ++con)
            if (M[con][var] > M[cur][var])
                swap(M[con], M[cur]);
        if (abs(M[cur][var]) > kEps) {
            pivot[var] = cur;
            double aux = M[cur][var];
            for (int i = 0; i <= vars; ++i)
                M[cur][i] /= aux;
            for (int con = 0; con < cons; ++con) {
                if (con != cur) {
                    double mul = M[con][var];
                    for (int i = 0; i <= vars; ++i) {
                        M[con][i] -= mul * M[cur][i];
                    }
                    assert(M[con][var] < kEps);
                }
            }
            ++cur;
        }
    }
    return pivot;
}
```

CharPoly.h

Description: Calculates the characteristic polynomial of a matrix.

Time: $\mathcal{O}(N^3)$ and div-free is $\mathcal{O}(N^4)$

79bb33, 55 lines

```
// det(x I + a)
template<class T> vector<T> charPoly(const vector<vector<T>>& a)
    ) {
    const int N = int(a.size()); auto b = a;
    for (int j = 0; j < N - 2; ++j) {
        for (int i = j + 1; i < N; ++i) {
            if (T(b[i][j])) {
                swap(b[j + 1], b[i]);
                for (int k = 0; k < N; ++k) swap(b[k][j + 1], b[k][i]);
                break;
            }
        }
        if (T(b[j + 1][j])) {
            const T r = 1 / b[j + 1][j];
            for (int i = j + 2; i < N; ++i) {
                const T s = r * b[i][j];
                for (int q = j; q < N; ++q) b[i][q] -= s * b[j + 1][q];
                for (int p = 0; p < N; ++p) b[p][j + 1] += s * b[p][i];
            }
        }
    }
    // fss[i] := det(x I - i + b[0..i][0..i])
}
```

```

vector<vector<T>> fss(N + 1);
fss[0] = {1};
for (int i = 0; i < N; ++i) {
    fss[i + 1].assign(i + 2, 0);
    for (int k = 0; k <= i; ++k) fss[i + 1][k + 1] = fss[i][k];
    for (int k = 0; k <= i; ++k) fss[i + 1][k] += b[i][i] * fss[i][k];
    T q = 1;
    for (int j = i - 1; j >= 0; --j) {
        q *= -b[j + 1][j];
        const T s = q * b[j][i];
        for (int k = 0; k <= j; ++k) fss[i + 1][k] += s * fss[j][k];
    }
    return fss[N];
}
// det(x I + a), division free
template<class T> vector<T> charPolyDivFree(const vector<vector<T>>& a) {
    const int N = int(a.size());
    vector<T> ps(N + 1, 0);
    ps[N] = 1;
    for (int h = N - 1; h >= 0; --h) {
        vector<vector<T>> sub(N, vector<T>(h + 1, 0));
        for (int i = N; i >= 1; --i)
            sub[i - 1][h] += ps[i];
        for (int i = N - 1; i >= 1; --i) for (int u = 0; u <= h; ++u) {
            for (int v = 0; v < h; ++v)
                sub[i - 1][v] -= sub[i][u] * a[u][v];
        }
        for (int i = N - 1; i >= 1; --i) for (int u = 0; u <= h; ++u) {
            ps[i] += sub[i][u] * a[u][h];
        }
    }
    return ps;
}

```

Math-Simplex.cpp

Description: Solves a general linear maximization problem: maximize $c^T x$ subject to $Ax \leq b, x \geq 0$.

Time: $\mathcal{O}(NM * \#pivots)$, where a pivot may be e.g. an edge relaxation. $\mathcal{O}(2^n)$ in the general case. WARNING- segfaults on empty (size 0) max cx st $Ax \leq b, x \geq 0$ do 2 phases; 1st check feasibility; 2nd check boundedness and ans

c3703c, 39 lines

```

vector<double> simplex(vector<vector<double>> A, vector<double>
    b, vector<double> c) {
    int n = A.size(), m = A[0].size() + 1, r = n, s = m-1;
    vector<vector<double>> D = vector<vector<double>>(n+2,
        vector<double>(m+1));
    vector<int> ix = vector<int>(n + m);
    for (int i = 0; i < n + m; ++i) ix[i] = i;
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < m-1; ++j) D[i][j] = -A[i][j];
        D[i][m - 1] = 1;
        D[i][m] = b[i];
        if (D[r][m] > D[i][m]) r = i;
    }
    for (int j = 0; j < m-1; ++j) D[n][j] = c[j];
    D[n + 1][m - 1] = -1; int z = 0;
    for (double d;;) {
        if (r < n) {
            swap(ix[s], ix[r + m]);
            D[r][s] = 1.0/D[r][s];

```

```

        for (int j = 0; j <= m; ++j) if (j != s) D[r][j] *= -D[r][s];
        for (int i = 0; i <= n+1; ++i) if (i != r) {
            for (int j = 0; j <= m; ++j) if (j != s) D[i][j]
                += D[r][j] * D[i][s];
            D[i][s] *= D[r][s];
        }
        r = -1; s = -1;
        for (int j = 0; j < m; ++j) if (s < 0 || ix[s] > ix[j])
            if (D[n+1][j] > eps || D[n+1][j] > -eps && D[n][j]
                > eps) s = j;
        if (s < 0) break;
        for (int i = 0; i < n; ++i) if (D[i][s] < -eps) {
            if (r < 0 || (d = D[r][m]/D[r][s]-D[i][m]/D[i][s])
                < -eps || d < eps && ix[r+m] > ix[i+m]) r = i;
        }
        if (r < 0) return vector<double>(); // unbounded
    }
    if (D[n+1][m] < -eps) return vector<double>(); //
        infeasible
    vector<double> x(m-1);
    for (int i = m; i < n+m; ++i) if (ix[i] < m-1) x[ix[i]] = D
        [i-m][m];
    double result = D[n][m];
    return x; // ans: D[n][m]
}

```

SolveLinear.h

Description: Solves $A * x = b$. If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in A and b is lost.

Time: $\mathcal{O}(n^2 m)$

2654db, 36 lines

```

typedef vector<double> vd;
const double eps = 1e-12;

int solveLinear(vector<vd> &A, vd &b, vd &x) {
    int n = A.size(), m = x.size(), rank = 0, br, bc;
    if (n) assert(A[0].size() == m);
    vector<int> col(m); iota(col.begin(), col.end(), 0);
    for (int i = 0; i < n; ++i) {
        double v, bv = 0;
        for (int r = i; r < n; ++r) for (int c = i; c < m; ++c)
            if ((v = fabs(A[r][c])) > bv)
                br = r, bc = c, bv = v;
        if (bv <= eps) {
            for (int j = i; j < n; ++j) if (fabs(b[j]) > eps) return
                -1;
            break;
        }
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        for (int j = 0; j < n; ++j) swap(A[j][i], A[j][bc]);
        bv = 1/A[i][i];
        for (int j = i+1; j < n; ++j) {
            double fac = A[j][i] * bv;
            b[j] -= fac * b[i];
            for (int k = i+1; k < m; ++k) A[j][k] -= fac*A[i][k];
        }
        rank++;
    }
    x.assign(m, 0);
    for (int i = rank; i--;) {
        b[i] /= A[i][i];
        x[col[i]] = b[i];
        for (int j = 0; j < i; ++j) b[j] -= A[j][i] * b[i];
    }
}

```

```

    return rank; // (multiple solutions if rank < m)
}

```

SolveLinear2.h

Description: To get all uniquely determined values of x back from SolveLinear, make the following changes:

"SolveLinear.h"

c8e85a, 7 lines

```

for (int j = 0; j < n; ++j) if (j != i) // instead of for (int j
    = i+1; j < n; ++j)
    // ... then at the end:
x.assign(m, undefined);
for (int i = 0; i < rank; ++i) {
    for (int j = rank; j < m; ++j) if (fabs(A[i][j]) > eps) goto
        fail;
    x[col[i]] = b[i] / A[i][i];
    fail;;
}

```

SolveLinearBinary.h

Description: Solves $Ax = b$ over \mathbb{F}_2 . If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys A and b .

Time: $\mathcal{O}(n^2 m)$

71d871, 34 lines

```

typedef bitset<1000> bs;

```

```

int solveLinear(vector<bs> &A, vector<int> &b, bs& x, int m) {
    int n = A.size(), rank = 0, br;
    assert(m <= x.size());
    vector<int> col(m); iota(col.begin(), col.end(), 0);
    for (int i = 0; i < n; ++i) {
        for (br=i; br<n; ++br) if (A[br].any()) break;
        if (br == n) {
            rep(j,i,n) if (b[j]) return -1;
            break;
        }
        int bc = (int)A[br]._Find_next(i-1);
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        for (int j = 0; j < n; ++j) if (A[j][i] != A[j][bc]) {
            A[j].flip(i); A[j].flip(bc);
        }
        for (int j = i+1; j < n; ++j) if (A[j][i]) {
            b[j] ^= b[i];
            A[j] ^= A[i];
        }
        rank++;
    }
}

```

```

x = bs();
for (int i = rank; i--;) {
    if (!b[i]) continue;
    x[col[i]] = 1;
    for (int j = 0; j < i; ++j) b[j] ^= A[j][i];
}
return rank; // (multiple solutions if rank < m)
}

```

MatrixInverse.h

Description: Invert matrix A . Returns rank; result is stored in A unless singular (rank < n). Can easily be extended to prime moduli; for prime powers, foreatedly set $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$ where A^{-1} starts as the inverse of $A \pmod p$, and k is doubled in each step.

Time: $\mathcal{O}(n^3)$

"../Matrix.h"

1ff78f, 33 lines

```

template<typename T> Matrix<T> inverse(Matrix<T> a) {
    assert(a.h() == a.w());
    int n = a.h();
    Matrix<T> b(n, vector<T>(n));

```

```

for (int i = 0; i < n; ++i) b[i][i] = 1;
for (int x = 0; x < n; ++x) {
    int my = -1;
    for (int y = x; y < n; ++y) {
        if (T(a[y][x]) != 0) {
            my = y;
            break;
        }
    }
    if (my == -1) return {};
    if (x != my) {
        swap(a[x], a[my]);
        swap(b[x], b[my]);
    }
    auto freq = a[x][x];
    for (int j = 0; j < n; ++j) {
        a[x][j] /= freq;
        b[x][j] /= freq;
    }
    for (int y = 0; y < n; ++y) {
        if (x == y) continue;
        if (T(a[y][x]) == 0) continue;
        freq = a[y][x];
        for (int k = 0; k < n; k++) a[y][k] -= freq * a[x][k];
        for (int k = 0; k < n; k++) b[y][k] -= freq * b[x][k];
    }
}
return b;
}

```

Tridiagonal.h

Description: $x = \text{tridiagonal}(d, p, q, b)$ solves the equation system

$$\begin{pmatrix} b_0 \\ b_1 \\ b_2 \\ b_3 \\ \vdots \\ b_{n-1} \end{pmatrix} = \begin{pmatrix} d_0 & p_0 & 0 & 0 & \cdots & 0 \\ q_0 & d_1 & p_1 & 0 & \cdots & 0 \\ 0 & q_1 & d_2 & p_2 & \cdots & 0 \\ \vdots & \vdots & \vdots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & q_{n-3} & d_{n-2} & p_{n-2} \\ 0 & 0 & \cdots & 0 & q_{n-2} & d_{n-1} \end{pmatrix} \begin{pmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ \vdots \\ x_{n-1} \end{pmatrix}.$$

This is useful for solving problems on the type

$$a_i = b_i a_{i-1} + c_i a_{i+1} + d_i, 1 \leq i \leq n,$$

where a_0, a_{n+1}, b_i, c_i and d_i are known. a can then be obtained from

$$\{a_i\} = \text{tridiagonal}(\{1, -1, -1, \dots, -1, 1\}, \{0, c_1, c_2, \dots, c_n\}, \{b_1, b_2, \dots, b_n, 0\}, \{a_0, d_1, d_2, \dots, d_n, a_{n+1}\}).$$

Fails if the solution is not unique.

If $|d_i| > |p_i| + |q_{i-1}|$ for all i , or $|d_i| > |p_{i-1}| + |q_i|$, or the matrix is positive definite, the algorithm is numerically stable and neither `tr` nor the check for `diag[i] == 0` is needed.

Time: $\mathcal{O}(N)$

d0855f, 26 lines

```

typedef double T;
vector<T> tridiagonal(vector<T> diag, const vector<T> &super,
    const vector<T> &sub, vector<T> b) {
    int n = b.size(); vector<int> tr(n);
    for(int i = 0; i < n-1; ++i) {
        if (abs(diag[i]) < 1e-9 * abs(super[i])) { // diag[i] == 0
            b[i+1] -= b[i] * diag[i+1] / super[i];
            if (i+2 < n) b[i+2] -= b[i] * sub[i+1] / super[i];
            diag[i+1] = sub[i]; tr[i+1] = 1;
        } else {
            diag[i+1] -= super[i]*sub[i]/diag[i];
            b[i+1] -= b[i]*sub[i]/diag[i];
        }
    }
}

```

```

for (int i = n; i--;) {
    if (tr[i]) {
        swap(b[i], b[i-1]);
        diag[i-1] = diag[i];
        b[i] /= super[i-1];
    } else {
        b[i] /= diag[i];
        if (i) b[i-1] -= b[i]*super[i-1];
    }
}
return b;
}

```

Polyominoes.h

Description: Generate all free polyominoes with n squares. Takes less than a sec if $n < 10$, around 2s if $n = 10$ and around 6s if $n = 11$.

d63122, 34 lines

```

using pii = pair<int,int>;
vector<int> diri = {0, 1, 0, -1};
vector<int> dirj = {1, 0, -1, 0};
vector<vector<pii>> poly[LIM];
void generate(int n){
    poly[1] = {{{0, 0}}};
    for(int i = 2; i <= n; i++) {
        set<vector<pii>> cur_om;
        for(auto &om : poly[i-1]) {
            pii mini = om[0];
            for(auto &p : om)
                for(int d = 0; d < 4; d++) {
                    int x = p.st + diri[d], y = p.nd + dirj[d];
                    if(!binary_search(om.begin(), om.end(), pii(x,y))) {
                        pii m = min(mini, {x, y});
                        pii new_cell(x - m.st, y - m.nd);
                        bool new_in = false;
                        vector<pii> norm;
                        for(pii &pn : om) {
                            pii cur(pn.st - m.st, pn.nd - m.nd);
                            if(cur > new_cell && !new_in) {
                                new_in = true;
                                norm.push_back(new_cell);
                            }
                        }
                        norm.push_back(cur);
                    }
                    if(!new_in) norm.push_back(new_cell);
                    if(!cur_om.count(norm)) cur_om.insert(norm);
                }
            }
        }
        poly[i].assign(cur_om.begin(), cur_om.end());
    }
}

```

4.1 Fourier transforms

FastFourierTransform.h

Description: $\text{fft}(a)$ computes $\hat{f}(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$ for all k . Useful for convolution: $\text{conv}(a, b) = c$, where $c[x] = \sum a[i]b[x-i]$. For convolution of complex numbers or more than two vectors: FFT, multiply pointwise, divide by n , reverse(start+1, end), FFT back. Rounding is safe if $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$ (in practice 10^{16} ; higher for random inputs). Otherwise, use long doubles/NTT/FFTMod.

Time: $\mathcal{O}(N \log N)$ with $N = |A| + |B|$ ($\sim 1s$ for $N = 2^{23}$)

9f86d0, 36 lines

```

using doublex = complex<long double>;
struct FFT {
    using i64 = int64_t;
    vector<doublex> fft(vector<doublex> y, bool invert = false)
    {
        const int N = int(y.size()); assert(N == (N&-N));
        vector<i64> rev(N);

```

```

for (int i = 1; i < N; ++i) {
    rev[i] = (rev[i]>>1]>>1) | (i&1 ? N>>1 : 0);
    if (rev[i] < i) swap(y[i], y[rev[i]]);
}
vector<doublex> rootni(N/2);
for (int n = 2; n <= N; n *= 2) {
    const doublex rootn = polar(1.0, (invert ? +1.0 : -1.0) * 2.0*acos(-1.0)/n);
    rootni[0] = 1.0;
    for (int i = 1; i < n/2; ++i) rootni[i] = rootni[i-1] * rootn;
    for (int left = 0; left != N; left += n) {
        const int mid = left + n/2;
        for (int i = 0; i < n/2; ++i) {
            const doublex temp = rootni[i] * y[mid + i];
            y[mid + i] = y[left + i] - temp; y[left + i] += temp;
        }
    }
    if (invert) for (auto &v : y) v /= (doublex)N;
    return move(y);
}
uint32_t nextpow2(uint32_t v) { return v ? 1 << __lg(2*v-1) : 1; }
vector<doublex> convolution(vector<doublex> a, vector<doublex> b) {
    const i64 n = max(int(a.size()) + int(b.size()-1), 0),
        n2 = nextpow2(n);
    a.resize(n2); b.resize(n2);
    vector<doublex> fa = fft(move(a)), fb = fft(move(b)), &fc = fa;
    for (int i = 0; i < n2; ++i) fc[i] = fc[i] * fb[i];
    vector<doublex> c = fft(move(fc), true);
    c.resize(n);
    return move(c);
}
};

```

FastFourierTransformMod.h

Description: Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$ (in practice 10^{16} or higher). Inputs must be in $[0, \text{mod})$.

Time: $\mathcal{O}(N \log N)$, where $N = |A| + |B|$ (twice as slow as NTT or FFT)

dbcea8, 85 lines

```

typedef unsigned int uint;
typedef long double ldouble;

template<typename T, typename U, typename B> struct ModularFFT
{
    inline T ifmod(U v, T mod) { return v >= (U)mod ? v - mod : v; }
    T pow(T x, U y, T p) {
        T ret = 1, x2p = x;
        while (y) {
            if (y % 2) ret = (B)ret * x2p % p;
            y /= 2; x2p = (B)x2p * x2p % p;
        }
        return ret;
    }
    vector<T> fft(vector<T> y, T mod, T gen, bool invert = false) {
        int N = y.size(); assert(N == (N&-N));
        if (N == 0) return move(y);
        vector<int> rev(N);
        for (int i = 1; i < N; ++i) {
            rev[i] = (rev[i]>>1]>>1) | (i&1 ? N>>1 : 0);
            if (rev[i] < i) swap(y[i], y[rev[i]]);
        }

```

```
assert((mod-1)%N == 0);
T rootN = pow(gen, (mod-1)/N, mod);
if (invert) rootN = pow(rootN, N/n, mod);
vector<T> rootni(N/2);
for (int n = 2; n <= N; n *= 2) {
    T rootn = pow(rootN, N/n, mod);
    rootni[0] = 1;
    for (int i = 1; i < n/2; ++i) rootni[i] = (B)rootni[i-1] * rootn % mod;
    for (int left = 0; left != N; left += n) {
        int mid = left + n/2;
        for (int i = 0; i < n/2; ++i) {
            T temp = (B)rootni[i] * y[mid+i] % mod;
            y[mid+i] = ifmod((U)y[left+i] + mod - temp, mod);
            y[left+i] = ifmod((U)y[left+i] + temp, mod);
        }
    }
}
if (invert) {
    T invN = pow(N, mod-2, mod);
    for (T &v : y) v = (B)v * invN % mod;
}
return move(y);
}

vector<T> convolution(vector<T> a, vector<T> b, T mod, T gen) {
    int N = a.size()+b.size()-1, N2 = nextpow2(N);
    a.resize(N2); b.resize(N2);
    vector<T> fa = fft(move(a), mod, gen), fb = fft(move(b), mod, gen), &fc = fa;
    for (int i = 0; i < N2; ++i) fc[i] = (B)fc[i] * fb[i] % mod;
    vector<T> c = fft(move(fc), mod, gen, true);
    c.resize(N); return move(c);
}

vector<T> self_convolution(vector<T> a, T mod, T gen) {
    int N = 2*a.size()-1, N2 = nextpow2(N);
    a.resize(N2);
    vector<T> fc = fft(move(a), mod, gen);
    for (int i = 0; i < N2; ++i) fc[i] = (B)fc[i] * fc[i] % mod;
    vector<T> c = fft(move(fc), mod, gen, true);
    c.resize(N); return move(c);
}

uint nextpow2(uint v) { return v ? 1 << __lg(2*v-1) : 1; }
};

const int mod = 998244353, mod_gen = 3;

vector<int> convolute(const vector<int> &a, const vector<int> &b) {
    if (a.empty() || b.empty()) return {};
    ModularFFT<int, uint, lint> modular_fft;
    return modular_fft.convolution(a, b, mod, mod_gen);
}

vector<int> convolute_all(const vector<vector<int>> &polys, int begin, int end) {
    if (end - begin == 0) return {1};
    else if (end - begin == 1) return polys[begin];
    else {
        int mid = begin + (end - begin) / 2;
        return convolute(convolute_all(polys, begin, mid), convolute_all(polys, mid, end));
    }
}
```

```
vector<int> convolute_all(const vector<vector<int>> &polys) {
    return convolute_all(polys, 0, (int)polys.size());
}
```

NumberTheoreticTransform.h
Description: Can be used for convolutions modulo specific nice primes of the form $2^a b + 1$, where the convolution result has size at most 2^a . Inputs must be in $[0, \text{mod})$.
Time: $\mathcal{O}(N \log N)$

```
"../number-theory/modpow.h" 1f6be8, 32 lines
const lint mod = (119 << 23) + 1, root = 62; // = 998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
// and 483 << 21 (same root). The last two are > 10^9.
```

```
typedef vector<lint> vl;
void ntt(vl& a, vl& rt, vl& rev, int n) {
    for (int i = 0; i < n; ++i) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) for (int j = 0; j < k; ++j) {
            lint z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
            a[i + j + k] = (z > ai ? ai - z + mod : ai - z);
            ai += (ai + z >= mod ? z - mod : z);
        }
}
```

```
vl conv(const vl& a, const vl& b) {
    if (a.empty() || b.empty()) return {};
    int s = a.size()+b.size()-1, B = 32 - __builtin_clz(s), n = 1 << B;
    vl L(a), R(b), out(n), rt(n, 1), rev(n);
    L.resize(n), R.resize(n);
    for (int i = 0; i < n; ++i) rev[i] = (rev[i / 2] | (i & 1) << B) / 2;
    lint curL = mod / 2, inv = modpow(n, mod - 2);
    for (int k = 2; k < n; k *= 2) {
        lint z[] = {1, modpow(root, curL /= 2)};
        for (int i = k; i < 2*k; ++i) rt[i] = rt[i / 2] * z[i & 1] % mod;
    }
    ntt(L, rt, rev, n); ntt(R, rt, rev, n);
    for (int i = 0; i < n; ++i) out[-i & (n-1)] = L[i] * R[i] % mod * inv % mod;
    ntt(out, rt, rev, n);
    return {out.begin(), out.begin() + s};
}
```

4.1.1 Duality
 $\max c^T x$ s.t. to $Ax \leq b$. Dual problem is $\min b^T x$ s.t. to $A^T x \geq c$. By strong duality, min max value coincides.

4.1.2 Strong duality
Given a linear problem Π_1 : minimize $c^T x$, s.t. to $Ax \leq b, x \geq 0$ we can define the linear problem dual standard Π_2 like the following: minimize $-b^T y$, s.t. to $A^T y \geq c$. If Π_1 is satisfied then Π_2 is also satisfied and $c^T x = b^T y$. If Π_1 is not satisfied and unbounded, then Π_2 is not satisfied and unbounded. (OBS: Can't be both unbounded!)

4.1.3 Generating functions
A list of generating functions for useful sequences:

$(1, 1, 1, 1, 1, \dots)$	$\frac{1}{1-z}$
$(1, -1, 1, -1, 1, \dots)$	$\frac{1}{1+z}$
$(1, 0, 1, 0, 1, 0, \dots)$	$\frac{1}{1-z^2}$
$(1, 0, \dots, 0, 1, 0, 1, 0, \dots, 0, 1, 0, \dots)$	$\frac{1}{1-z^2}$
$(1, 2, 3, 4, 5, 6, \dots)$	$\frac{1}{(1-z)^2}$
$(1, \binom{m+1}{m}, \binom{m+2}{m}, \binom{m+3}{m}, \dots)$	$\frac{1}{(1-z)^{m+1}}$
$(1, c, \binom{c+1}{2}, \binom{c+2}{3}, \dots)$	$\frac{1}{(1-z)^c}$
$(1, c, c^2, c^3, \dots)$	$\frac{1}{1-cz}$
$(0, 1, \frac{1}{2}, \frac{1}{3}, \frac{1}{4}, \dots)$	$\ln \frac{1}{1-z}$

A neat manipulation trick is:

$$\frac{1}{1-z} G(z) = \sum_n \sum_{k \leq n} g_k z^n$$

4.1.4 Polyominoes
How many free (rotation, reflection), one-sided (rotation) and fixed n -ominoes are there?

n	3	4	5	6	7	8	9	10
free	2	5	12	35	108	369	1.285	4.655
one-sided	2	7	18	60	196	704	2.500	9.189
fixed	6	19	63	216	760	2.725	9.910	36.446

Number theory (5)

5.1 Modular arithmetic

modular-arithmetic.h
Description: Operators for modular arithmetic.

```
template<unsigned M_> struct modnum {
    static constexpr unsigned M = M_;
    using ll = long long; using ull = unsigned long long;
    unsigned x;
    constexpr modnum() : x(0) {}
    constexpr modnum(unsigned x_) : x(x_ % M) { if (x < 0) x += M; }
    constexpr modnum(int x_) : x(((x_ %= static_cast<int>(M)) < 0) ? (x_ + static_cast<int>(M)) : x_) {}
    constexpr modnum(ull x_) : x(x_ % M) {}
    constexpr modnum(ll x_) : x(((x_ %= static_cast<ll>(M)) < 0) ? (x_ + static_cast<ll>(M)) : x_) {}
    explicit operator int() const { return x; }
    modnum& operator+=(const modnum& a) { x = ((x += a.x) >= M) ? (x - M) : x; return *this; }
    modnum& operator-=(const modnum& a) { x = ((x -= a.x) >= M) ? (x + M) : x; return *this; }
    modnum& operator*=(const modnum& a) { x = unsigned((static_cast<ull>(x) * a.x) % M); return *this; }
    modnum& operator/=(const modnum& a) { return (*this *= a.inv()); }
    modnum operator+(const modnum& a) const { return (modnum(*this) += a); }
    modnum operator-(const modnum& a) const { return (modnum(*this) -= a); }
    modnum operator*(const modnum& a) const { return (modnum(*this) *= a); }
}
```



```

modnum operator/(const modnum& a) const { return (modnum(*
    this) /= a); }
modnum operator-() const { return modnum(-x); }
modnum pow(ll e) const {
    if (e < 0) return inv().pow(-e);
    modnum x2 = x, xe = 1;
    for (; e; e >>= 1) {
        if (e & 1) xe *= x2;
        x2 *= x2;
    }
    return xe;
}
modnum inv() const {
    unsigned a = x, b = M; int y = 1, z = 0;
    while (a) {
        const unsigned q = (b/a), c = (b - q*a);
        b = a, a = c; const int w = z - static_cast<int>(q)
            * y;
        z = y, y = w;
    } assert(b == 1); return modnum(z);
}
friend modnum inv(const modnum& a) { return a.inv(); }
template<typename T> friend modnum operator+(T a, const
    modnum& b) { return (modnum(a) += b); }
template<typename T> friend modnum operator-(T a, const
    modnum& b) { return (modnum(a) -= b); }
template<typename T> friend modnum operator*(T a, const
    modnum& b) { return (modnum(a) *= b); }
template<typename T> friend modnum operator/(T a, const
    modnum& b) { return (modnum(a) /= b); }
friend bool operator==(const modnum& a, const modnum& b) {
    return a.x == b.x; }
friend bool operator!=(const modnum& a, const modnum& b) {
    return a.x != b.x; }
friend ostream& operator<<(ostream& os, const modnum& a) {
    return os << a.x; }
friend istream& operator>>(istream& in, modnum& n) { ull v_
    ; in >> v_; n = modnum(v_); return in; }
};

```

pairnum-template.h

Description: Support pairs operations using modnum template. Pretty good for string hashing.

229a89, 42 lines

```

template <typename T, typename U> struct pairnum {
    T t; U u;
    pairnum() : t(0), u(0) {}
    pairnum(long long v) : t(v), u(v) {}
    pairnum(const T& t_, const U& u_) : t(t_), u(u_) {}
    friend std::ostream& operator << (std::ostream& out, const
        pairnum& n) { return out << '(' << n.t << ', ' << ' ' <<
            n.u << ')'; }
    friend std::istream& operator >> (std::istream& in, pairnum&
        n) { long long v; in >> v; n = pairnum(v); return in; }
    friend bool operator == (const pairnum& a, const pairnum& b)
        { return a.t == b.t && a.u == b.u; }
    friend bool operator != (const pairnum& a, const pairnum& b)
        { return a.t != b.t || a.u != b.u; }
    pairnum inv() const {
        return pairnum(t.inv(), u.inv());
    }
    pairnum neg() const {
        return pairnum(t.neg(), u.neg());
    }
    pairnum operator- () const {
        return pairnum(-t, -u);
    }
    pairnum operator+ () const {
        return pairnum(+t, +u);
    }
};

```

```

}
pairnum& operator += (const pairnum& o) {
    t += o.t; u += o.u;
    return *this;
}
pairnum& operator -= (const pairnum& o) {
    t -= o.t; u -= o.u;
    return *this;
}
pairnum& operator *= (const pairnum& o) {
    t *= o.t; u *= o.u;
    return *this;
}
pairnum& operator /= (const pairnum& o) {
    t /= o.t; u /= o.u;
    return *this;
}
friend pairnum operator + (const pairnum& a, const pairnum& b
    ) { return pairnum(a) += b; }
friend pairnum operator - (const pairnum& a, const pairnum& b
    ) { return pairnum(a) -= b; }
friend pairnum operator * (const pairnum& a, const pairnum& b
    ) { return pairnum(a) *= b; }
friend pairnum operator / (const pairnum& a, const pairnum& b
    ) { return pairnum(a) /= b; }
};

```

mod-inv.h

Description: Find x such that $ax \equiv 1 \pmod{m}$. The inverse only exist if a and m are coprimes.

6ee7ac, 13 lines

```

template<typename T>
T modinv(T a, T m) {
    assert(m > 0);
    if (m == 1) return 0;
    a %= m;
    if (a < 0) a += m;
    assert(a != 0);
    if (a == 1) return 1;
    return m - modinv(m, a) * m/a;
}
const lint mod = 10000000007, LIM = 200000;
lint* inv = new lint[LIM] - 1; inv[1] = 1;
for(int i = 2; i < LIM; ++i) inv[i] = mod - (mod/i) * inv[mod%i
    ] % mod;

```

mod-pow.h

f2c0cc, 6 lines

```

lint modpow(lint b, lint e) {
    lint ret = 1;
    for (int i = 1; i <= e; i *= 2, b = b * b % mod)
        if (i & e) ret = ret * b % mod;
    return ret;
}

```

mod-sum.h

Description: Sums of mod'ed arithmetic progressions.

modsum(to, c, k, m) = $\sum_{i=0}^{to-1} (ki + c) \% m$. divsum is similar but for floored division.

Time: $\log(m)$, with a large constant.

decfb8, 17 lines

```

typedef unsigned long long ull;
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }
ull divsum(ull to, ull c, ull k, ull m) {
    ull res = k / m * sumsq(to) + c / m * to;
    k %= m; c %= m;
    if (k) {
        ull to2 = (to * k + c) / m;
        res += to * to2;
    }
}

```

```

    res -= divsum(to2, m-1 - c, m, k) + to2;
}
return res;
}
lint modsum(ull to, lint c, lint k, lint m) {
    c = ((c % m) + m) % m;
    k = ((k % m) + m) % m;
    return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
}

```

mod-mul.h

Description: Calculate $a \cdot b \pmod{c}$ (or $a^b \pmod{c}$) for $0 \leq a, b \leq c \leq 7.2 \cdot 10^{18}$.

Time: $\mathcal{O}(1)$ for modmul, $\mathcal{O}(\log b)$ for modpow

59afa8, 11 lines

```

typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
    lint ret = a * b - M * ull(1.L / M * a * b);
    return ret + M * (ret < 0) - M * (ret >= (lint)M);
}
ull modpow(ull b, ull e, ull mod) {
    ull ans = 1;
    for (; e; b = modmul(b, b, mod), e /= 2)
        if (e & 1) ans = modmul(ans, b, mod);
    return ans;
}

```

mod-sqrt.h

Description: Tonelli-Shanks algorithm for modular square roots. Finds x s.t. $x^2 = a \pmod{p}$ ($-x$ gives the other solution).

Time: $\mathcal{O}(\log^2 p)$ worst case, $\mathcal{O}(\log p)$ for most p

"mod-pow.h" 09107e, 23 lines

```

lint sqrt(lint a, lint p) {
    a %= p; if (a < 0) a += p;
    if (a == 0) return 0;
    assert(modpow(a, (p-1)/2, p) == 1); // else no solution
    if (p % 4 == 3) return modpow(a, (p+1)/4, p);
    // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
    lint s = p - 1, n = 2;
    int r = 0, m;
    while (s % 2 == 0) ++r, s /= 2;
    while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;
    lint x = modpow(a, (s + 1) / 2, p);
    lint b = modpow(a, s, p), g = modpow(n, s, p);
    for (;;) {
        lint t = b;
        for (m = 0; m < r && t != 1; ++m)
            t = t * t % p;
        if (m == 0) return x;
        lint gs = modpow(g, 1LL << (r - m - 1), p);
        g = gs * gs % p;
        x = x * gs % p;
        b = b * g % p;
    }
}

```

mul-order.h

Description: Find the smallest integer k such that $a^k \pmod{m} = 1$. $0 < k < m$.

Time: close to $\mathcal{O}(\log(N))$

<sieve.h>, <prime-factors.h>, <mod-pow.h>

cb76aa, 16 lines

```

template<typename T> T mulOrder(T a, T m) {
    auto pf = prime_factorize(m);
    T res = 1;
    for (auto &[p, e] : pf) {
        T k = 0, q = Pow(p, e);
        T t = q / p * (p - 1);
        auto factors = divisors(t); // get all divisors of t
        for (auto &pr : factors)

```



```
        if (modpow(a, pr, m) == 1) {
            k = pr;
            break;
        }
        res = res/___gcd(res, k) * k;
    }
    return res;
}
```

5.2 Primality

sieve.h
Description: Prime sieve for generating all primes up to a certain limit. $pfac[i]$ is the lowest prime factor of i . Also useful if you need to compute any multiplicative function.
Time: $\mathcal{O}(N)$

```
vector<int> run_sieve(int N) {
    vector<int> pfac(N + 1);
    vector<int> primes; primes.reserve(N+1);
    vector<int> mu(N + 1, -1); mu[1] = 1;
    vector<int> phi(N + 1); phi[1] = 1;
    for (int i = 2; i <= N; ++i) {
        if (!pfac[i]) {
            pfac[i] = i; primes.push_back(i);
            phi[i] = i - 1;
        }
        for (int p : primes) {
            if (p > N/i) break;
            pfac[p * i] = p;
            mu[p * i] *= mu[i];
            phi[p * i] = phi[i] * phi[p];
            if (i % p == 0) {
                mu[p * i] = 0;
                phi[p * i] = phi[i] * p;
                break;
            }
        }
    }
    return primes;
}
```

segmented-sieve.h
Description: Prime sieve for generating all primes smaller than S .
Time: $S=1e9 \approx 1.5s$

```
const int S = 1e6;
bitset<S> isPrime;
vector<int> eratosthenes() {
    const int S = round(sqrt(S)), R = S/2;
    vector<int> pr = {2}, sieve(S+1); pr.reserve(int(S/log(S)
        *1.1));
    vector<pair<int,int>> cp;
    for (int i = 3; i <= S; i += 2) if (!sieve[i]) {
        cp.push_back({i, i*i/2});
        for (int j = i*i; j <= S; j += 2*i) sieve[j] = 1;
    }
    for (int L = 1; L <= R; L += S) {
        array<bool, S> block{};
        for (auto &[p, idx] : cp)
            for (int idx; i < S+L; idx = (i+=p)) block[i-L] = 1;
        for (int i = 0; i < min(S, R - L); ++i)
            if (!block[i]) pr.push_back((L + i)*2 + 1);
    }
    for (int i : pr) isPrime[i] = 1;
    return pr;
}
```

mobius.h
Description: If g and f are arithmetic functions . Return 0 if divisible by any perfect square, 1 if has an even quantity of prime numbers and -1 if has an odd quantity of primes.
Time: $\mathcal{O}(\sqrt{n})$

```
template<typename T> T mobius(T n) {
    T p = 0;
    for (int i = 2; i*i <= n; ++i)
        if (n % i == 0) {
            n /= i;
            p += 1;
            if (n % i == 0) return 0;
        }
    return ((p&1) || n == 1? 1 : -1);
}
```

miller-rabin.h
Description: Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to 2^{64} ; for larger numbers, extend A randomly.
Time: 7 times the complexity of $a^b \bmod c$.

```
"mod-mul.h"
bool isPrime(ull n) {
    if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
    vector<ull> A = {2, 325, 9375, 28178, 450775, 9780504,
        1795265022};
    ull s = __builtin_ctzll(n-1), d = n >> s;
    for(ull a : A) { // ^ count trailing zeroes
        ull p = modpow(a % n, d, n), i = s;
        while (p != 1 && p != n - 1 && a % n && i--)
            p = modmul(p, p, n);
        if (p != n-1 && i != s) return 0;
    }
    return 1;
}
```

pollard-rho.h
Description: Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).
Time: $\mathcal{O}(n^{1/4})$, less for numbers with small factors.

```
"mod-mul.h", "miller-rabin.h"
ull pollard(ull n) {
    auto f = [n](ull x) { return modmul(x, x, n) + 1; };
    ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
    while (t++ % 40 || ___gcd(prd, n) == 1) {
        if (x == y) x = ++i, y = f(x);
        if ((q = modmul(prd, max(x,y) - min(x,y), n))) prd = q;
        x = f(x), y = f(f(y));
    }
    return ___gcd(prd, n);
}
vector<ull> factor(ull n) {
    if (n == 1) return {};
    if (isPrime(n)) return {n};
    ull x = pollard(n);
    auto l = factor(x), r = factor(n / x);
    l.insert(l.end(), r.begin(), r.end());
    return l;
}
```

5.3 Divisibility

extended-euclid.h
Description: Finds two integers x and y , such that $ax + by = \gcd(a, b)$. If you just need gcd, use the built in `__gcd` instead. If a and b are coprime, then x is the inverse of $a \pmod b$.

```
template<typename T>
T egcd(T a, T b, T &x, T &y) {
```

```
    if (a == 0) {
        x = 0, y = 1;
        return b;
    }
    T p = b/a, g = egcd(b - p * a, a, y, x);
    x -= y * p;
    return g;
}
```

division-lemma.h
Description: This lemma let us exploit the fact tha the sequence (harmonic on integer division) has at most $2\sqrt{N}$ distinct elements, so we can iterate through every possible value of $\lfloor \frac{N}{i} \rfloor$, using the fact that the greatest integer j satisfying $\lfloor \frac{N}{j} \rfloor = \lfloor \frac{N}{i} \rfloor$ is $\lfloor \frac{N}{\lfloor \frac{N}{i} \rfloor} \rfloor$. This one computes the $\sum_{i=1}^N \lfloor \frac{N}{i} \rfloor i$.

```
"Time:  $\mathcal{O}(\sqrt{N})$ "
int res = 0;
for (int a = 1, b; a <= N; a = b + 1) {
    b = N / (N / a);
    // for all i in [a, b] since they all have the same
    // quotient (N / a)
    // and there are (b - a + 1) elements in this interval
    int l = b - a + 1, r = a + b; // l * r / 2 = sum(i, j)
    if (l & 1) r /= 2;
    else l /= 2;
    res += l * r * (N / a);
}
```

prime-factors.h
Description: Find all prime factors of n .
Time: $\mathcal{O}(\log(n))$

```
"sieve.h"
template<typename T>
vector<pair<T, int>> prime_factorize(T n) {
    vector<pair<T, int>> factors;
    while(n != 1) {
        T p = lp[n];
        int exp = 0;
        do {
            n /= p;
            ++exp;
        } while(n % p == 0);
        factors.push_back({p, exp});
    }
    for (T p : primes) {
        if (p * p > n) break;
        if (p * p == 0) {
            factors.push_back({p, 0});
            do {
                n /= p;
                ++factors.back().second;
            } while(n % p == 0);
        }
        if (n > 1) factors.push_back({n, 1});
        return factors;
    }
}
```

num-div.h
Description: Count the number of divisors of n . Requires having run Sieve up to at least `sqrt(n)`.
Time: $\mathcal{O}(\log(N))$

```
"sieve.h"
template<typename T> T numDiv(T n) {
    T how_many = 1, prime_factors = 0;
    while(n != 1) {
        T p = lp[n];
```

```
int exp = 0;
do {
    n /= p;
    ++exp;
    ++prime_factors; //count prime factors!
} while(n % p == 0);
how_many *= 111 * (exp + 1);
}
if (n != 1) ++prime_factors;
return how_many;
}
```

sum-div.h

Description: Sum of all divisors of n.

Time: $\mathcal{O}(\log(N))$

```
"sieve.h", "mod-pow.h"
1ebc7c, 13 lines
template<typename T> T divSum(T n) {
    T sum = 1;
    while (n > 1) {
        int exp = 0;
        T p = lp[n];
        do {
            n /= p;
            ++exp;
        } while(n % p == 0);
        sum *= (Pow(p, exp + 1) - 1)/(p - 1);
    }
    return sum;
}
```

phi-function.h

Description: Euler's totient or Euler's phi function is defined as $\phi(n) := \#$ of positive integers $\leq n$ that are coprime with n . The cototient is $n - \phi(n)$. $\phi(1) = 1$, p prime $\Rightarrow \phi(p^k) = (p - 1)p^{k-1}$, m, n coprime $\Rightarrow \phi(mn) = \phi(m)\phi(n)$. If $n = p_1^{k_1} p_2^{k_2} \dots p_r^{k_r}$ then $\phi(n) = (p_1 - 1)p_1^{k_1-1} \dots (p_r - 1)p_r^{k_r-1}$. $\phi(n) = n \cdot \prod_{p|n} (1 - 1/p)$.

$\sum_{d|n} \phi(d) = n, \sum_{1 \leq k \leq n, \gcd(k,n)=1} k = n\phi(n)/2, n > 1$

Euler's thm: a, n coprime $\Rightarrow a^{\phi(n)} \equiv 1 \pmod n$.

Fermat's little thm: p prime $\Rightarrow a^{p-1} \equiv 1 \pmod p \forall a$.

```
6984ee, 22 lines
const int n = int(1e5)*5;
vector<int> phi(n);
void calculatePhi() {
    for(int i = 0; i < n; ++i) phi[i] = i&1 ? i : i/2;
    for(int i = 3; i < n; i += 2) if (phi[i] == i)
        for(int j = i; j < n; j += i) phi[j] -= phi[j]/i;
}
template<typename T> T phi(T n){
    T aux, result;
    aux = result = n;
    for (T i = 2; i*i <= n; ++i)
        if (aux % i == 0) {
            while (aux % i == 0) aux /= i;
            result /= i;
            result *= (i-1);
        }
    if (aux > 1) {
        result /= aux;
        result *= (aux-1);
    }
    return result;
}
```

discrete-log.h

Description: Returns the smallest $x > 0$ s.t. $a^x = b \pmod m$, or -1 if no such x exists. modLog(a,1,m) can be used calculate the order of a.

Time: $\mathcal{O}(\sqrt{m})$

10faf5, 11 lines

```
lint modLog(lint a, lint b, lint m) { // Careful with b = 1
    case
    lint n = (lint)sqrt(m) + 1, e = 1, f = 1, j = 1;
    unordered_map<lint, lint> A;
    while (j <= n && (e = f = e * a % m) != b % m)
        A[e * b % m] = j++;
    if (e == b % m) return j;
    if (__gcd(m, e) == __gcd(m, b))
        for(int i = 2; i <= n+1; ++i) if (A.count(e = e * f % m))
            return n * i - A[e];
    return -1;
}
```

group-order.h

Description: Calculate the order of a in Z_n . A group Z_n is cyclic if, and only if $n = 1, 2, 4, p^k$ or $2p^k$, being p an odd prime number.

Time: $\mathcal{O}(\sqrt{n}\log(n))$

```
82034c, 6 lines
template<typename T> T order(T a, T n) {
    vector<T> d = divisors(phi(n)); // divisors returns vector
    for (int i : v) // with all divisors of phi
        (n)
        if (modpow(a, i, n) == 1) return i;
    return -1;
}
```

primitive-roots.h

Description: a is a primitive root mod n if for every number x coprime to n there is an integer z s.t. $x \equiv g^z \pmod n$. The number of primitive roots mod n , if there are any, is equal to $\phi(\phi(n))$. If m isnt prime, replace $m - 1$ by $\phi(m)$.

Time: $\mathcal{O}(\log(N))$

```
<sieve.h>, <prime-factors.h>, <mod-pow.h>
05729f, 6 lines
template<typename T> bool is_primitive(T a, T m) {
    vector<pair<T, T>> D = prime_factorize(m-1);
    for (auto p : D)
        if (modpow(a, (m-1)/p.first, m) == 1) return false;
    return true;
}
```

prime-counting.h

Description: Count the number of primes up to x . Also useful for sum of primes.

Time: $\mathcal{O}\left(n^{3/4}/\log n\right)$

```
<sieve.h>
cb2aae, 32 lines
const int N = 1e5, K = 50, T = 10000000; // T<= 1e17 is fine
for N<= 10^11
vector<int> primes_until;
vector<vector<uint16_t>> dp(N+1, vector<uint16_t>(K+1)); // use
32-bit integer if N>= 2^17

void fill_primes(int n) { // get # of primes up to i
    run_sieve(n);
    int walk = 0;
    for (int i = 0; i < n; ++i) {
        if (!i) primes_until.push_back(0);
        else primes_until.push_back(primes_until.back());
        if (primes[walk] == i) walk++, primes_until.back()++;
    }
}
```

```
int64_t solve(int64_t n, int k) { // how many numbers
    if (k == 0) return n; // in [1, N] not divisible by
    int64_t p = primes[k]; // any of the first k primes
    if (n < p) return 1ll;
    if (n < min(int64_t(T), p*p)) return primes_until[n] - k + 1;
    bool mark = n < N && k < K;
```

```
if (mark && dp[n][k]) return dp[n][k];
p = primes[k-1];
int64_t res = solve(n, k-1) - solve(n/p, k-1);
if (mark) dp[n][k] = res;
return res;
}
```

```
int64_t calc(int64_t x) {
    if (x < T) return primes_until[x];
    int k = primes_until[sqrt(x)];
    return solve(x, k) + k - 1;
}
```

5.4 Chinese remainder theorem

chinese-remainder.h

Description: Chinese Remainder Theorem. crt(a, m, b, n) computes x such that $x \equiv a \pmod m$, $x \equiv b \pmod n$. If $|a| < m$ and $|b| < n$, x will obey $0 \leq x < \text{lcm}(m, n)$. Assumes $mn < 2^{62}$.

Time: $\mathcal{O}(n \log(LCM(m)))$

```
"extended-euclid.h"
ecbf25, 14 lines
template<typename T>
pair<T, T> crt(const vector<T>& a, const vector<T>& m) {
    int N = int(a.size());
    T r = 0, md = 1, x, y;
    for (int i = 0; i < N; ++i) {
        T g = egcd(md, m[i], x = 0, y = 0);
        T im = x;
        if ((a[i] - r) % g) return {0, -1};
        T tmp = (a[i] - r) / g * im % (m[i] / g);
        r += md * tmp;
        md *= m[i] / g;
    }
    return {(r % md + md) % md, md};
}
```

5.5 Fractions

fractions.h

Description: Template that helps deal with fractions.

f3ef3d, 31 lines

```
struct frac {
    lint n, d;
    frac() { n = 0, d = 1; }
    frac(lint _n, lint _d) {
        n = _n, d = _d;
        lint g = __gcd(n,d); n /= g, d /= g;
        if (d < 0) n *= -1, d *= -1;
    }
    frac(lint _n) : frac(_n,1) {}
    friend frac abs(frac F) { return frac(abs(F.n),F.d); }
    friend bool operator<(const frac& l, const frac& r) {
        return l.n*r.d < r.n*l.d; }
    friend bool operator==(const frac& l, const frac& r) {
        return l.n == r.n && l.d == r.d; }
    friend bool operator!=(const frac& l, const frac& r) {
        return !(l == r); }
    friend frac operator+(const frac& l, const frac& r) {
        return frac(l.n*r.d+r.n*l.d,l.d*r.d); }
    friend frac operator-(const frac& l, const frac& r) {
        return frac(l.n*r.d-r.n*l.d,l.d*r.d); }
    friend frac operator*(const frac& l, const frac& r) {
        return frac(l.n*r.n,l.d*r.d); }
    friend frac operator*(const frac& l, int r) { return l*frac(r,1); }
    friend frac operator*(int r, const frac& l) { return l*r; }
    friend frac operator/(const frac& l, const frac& r) {
        return l*frac(r.d,r.n); }
    friend frac operator/(const frac& l, const int& r) { return
        l/frac(r,1); }
```

```
friend frac operator/(const int& l, const frac& r) { return
    frac(l,l)/r; }
friend frac& operator+=(frac& l, const frac& r) { return l
    = l+r; }
friend frac& operator-=(frac& l, const frac& r) { return l
    = l-r; }
template<class T> friend frac& operator*=(frac& l, const T&
    r) { return l = l*r; }
template<class T> friend frac& operator/=(frac& l, const T&
    r) { return l = l/r; }
friend ostream& operator<<(ostream& strm, const frac& a) {
    strm << a.n;
    if (a.d != 1) strm << "/" << a.d;
    return strm;
}
};
```

continued-fractions.h

Description: Given N and a real number $x \geq 0$, finds the closest rational approximation p/q with $p, q \leq N$. It will obey $|p/q - x| \leq 1/qN$. For consecutive convergents, $p_{k+1}q_k - q_{k+1}p_k = (-1)^k$. (p_k/q_k alternates between $> x$ and $< x$.) If x is rational, y eventually becomes ∞ ; if x is the root of a degree 2 polynomial the a 's eventually become cyclic.
Time: $\mathcal{O}(\log N)$

```
6c75b7, 21 lines
typedef double d; // for N ~ 1e7; long double for N ~ 1e9
pair<lint, lint> approximate(d x, lint N) {
    lint LP = 0, LQ = 1, P = 1, Q = 0, inf = LLONG_MAX; d y = x;
    for (;;) {
        lint lim = min(P ? (N-LP) / P : inf, Q ? (N-LQ) / Q : inf),
            a = (lint)floor(y), b = min(a, lim),
            NP = b*P + LP, NQ = b*Q + LQ;
        if (a > b) {
            // If b > a/2, we have a semi-convergent that gives us a
            // better approximation; if b = a/2, we *may* have one.
            // Return {P, Q} here for a more canonical approximation.
            return (abs(x - (d)NP / (d)NQ) < abs(x - (d)P / (d)Q)) ?
                {NP, NQ} : {P, Q};
        }
        if (abs(y = 1/(y - (d)a)) > 3*N) {
            return {NP, NQ};
        }
        LP = P; P = NP;
        LQ = Q; Q = NQ;
    }
}
```

frac-binary-search.h

Description: Given f and N , finds the smallest fraction $p/q \in [0, 1]$ such that $f(p/q)$ is true, and $p, q \leq N$. You may want to throw an exception from f if it finds an exact solution, in which case N can be removed.
Usage: fracBS([])(Frac f) { return f.p>=3*f.q; }, 10); // {1,3}
Time: $\mathcal{O}(\log(N))$

```
f83d46, 23 lines
struct Frac { lint p, q; };
template<class F>
Frac fracBS(F f, lint N) {
    bool dir = 1, A = 1, B = 1;
    Frac left{0, 1}, right{1, 1}; // Set right to 1/0 to search
    (0, N]
    assert(!f(left)); assert(f(right));
    while (A || B) {
        lint adv = 0, step = 1; // move right if dir, else left
        for (int si = 0; step; (step *= 2) >= si) {
            adv += step;
            Frac mid{left.p * adv + right.p, left.q * adv + right.q};
            if (abs(mid.p) > N || mid.q > N || dir == !f(mid)) {
                adv -= step; si = 2;
            }
        }
    }
}
```

```

    }
    right.p += left.p * adv;
    right.q += left.q * adv;
    dir = !dir;
    swap(left, right);
    A = B; B = !!adv;
}
return dir ? right : left;
}
```

5.5.1 Bézout’s identity

For $a \neq 0, b \neq 0$, then $d = \gcd(a, b)$ is the smallest positive integer for which there are integer solutions to

$$ax + by = d$$

If (x, y) is one solution, then all solutions are given by

$$\left(x + \frac{kb}{\gcd(a, b)}, y - \frac{ka}{\gcd(a, b)}\right), \quad k \in \mathbb{Z}$$

5.5.2 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2 - n^2), \quad b = k \cdot (2mn), \quad c = k \cdot (m^2 + n^2),$$

with $m > n > 0, k > 0, m \perp n$, and either m or n even.

5.5.3 Primitive Roots

It only exists when n is $2, 4, p^k, 2p^k$, where p odd prime. If g is a primitive root, all primitive roots are of the form g^k where $k, \phi(p)$ are coprime (hence there are $\phi(\phi(p))$ primitive roots).

5.5.4 Chicken McNugget theorem

Let x and y be two coprime integers, the greater integer that can’t be written in the form of $ax + by$ is $\frac{(x-1)(y-1)}{2}$

5.6 Primes

$p = 962592769$ is such that $2^{21} \mid p - 1$, which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power p^a , except for $p = 2, a > 2$, and there are $\phi(\phi(p^a))$ many. For $p = 2, a > 2$, the group $\mathbb{Z}_{2^a}^\times$ is instead isomorphic to $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$.

5.6.1 Sum of primes

For any multiplicative f :

$$S(n, p) = S(n, p - 1) - f(p) \cdot (S(n/p, p - 1) - S(p - 1, p - 1))$$

5.6.2 Moebius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Moebius Inversion:

$$g(n) = \sum_{d|n} f(d) \Leftrightarrow f(n) = \sum_{d|n} \mu(d)g(n/d)$$

Other useful formulas/forms:

$$\sum_{d|n} \mu(d) = [n = 1] \text{ (very useful)}$$

$$g(n) = \sum_{n|d} f(d) \Leftrightarrow f(n) = \sum_{n|d} \mu(d/n)g(d)$$

$$g(n) = \sum_{1 \leq m \leq n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \leq m \leq n} \mu(m)g(\lfloor \frac{n}{m} \rfloor)$$

5.6.3 Dirichlet Convolution

Given a function $f(x)$, let

$$(f * g)(x) = \sum_{d|x} g(d)f(x/d)$$

If the partial sums $s_{f*g}(n), s_g(n)$ can be computed in $\mathcal{O}(1)$ and $s_f(1 \dots n^{2/3})$ can be computed in $\mathcal{O}(n^{2/3})$ then all $s_f(\frac{n}{d})$ can as well. Use

$$s_{f*g}(n) = \sum_{d=1}^n g(d)s_f(n/d).$$

1. If $f(x) = \mu(x)$ then $g(x) = 1, (f * g)(x) = (x == 1)$, and $s_f(n) = 1 - \sum_{i=2}^n s_f(n/i)$

2. If $f(x) = \phi(x)$ then $g(x) = 1, (f * g)(x) = x$, and $s_f(n) = \frac{n(n+1)}{2} - \sum_{i=2}^n s_f(n/i)$

5.6.4 Wilson’s theorem

Let $n > 1$. Then $n|(n - 1)! + 1$ iff n is prime.

5.6.5 Wolstenholme’s theorem

Let $p > 3$ be a prime number. Then its numerator $1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{p-1}$ is divisible by p^2 .

5.6.6 Estimates

$$\sum_{d|n} d = \mathcal{O}(n \log \log n)$$

The number of divisors of n is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200 000 for $n < 1e19$.

5.6.7 Prime counting function ($\pi(x)$)

The prime counting function is asymptotic to $\frac{x}{\log x}$, by the prime number theorem.

x	10	10 ²	10 ³	10 ⁴	10 ⁵	10 ⁶	10 ⁷	10 ⁸
$\pi(x)$	4	25	168	1.229	9.592	78.498	664.579	5.761.455

Combinatorial (6)

6.1 Permutations

6.1.1 Factorial

<i>n</i>	1	2	3	4	5	6	7	8	9	10
<i>n</i> !	1	2	6	24	120	720	5040	40320	362880	3628800
<i>n</i>	11	12	13	14	15	16	17			
<i>n</i> !	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
<i>n</i>	20	25	30	40	50	100	150	171		
<i>n</i> !	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL.MAX		

IntPerm.h
Description: Permutation -> integer conversion. (Not order preserving.)
Time: $\mathcal{O}(n)$

```
06f786, 6 lines
int permToInt(vector<int>& v) {
    int use = 0, i = 0, r = 0;
    for (auto &x : v) r=r * ++i + __builtin_popcount(use & ~(1 <<
        x)),
        use |= 1 << x;
    return r;
}
```

6.1.2 Binomials

- Sum of every element in the n -th row of pascal triangle is 2^n .
- The product of the elements in each row is $\frac{(n+1)^n}{n!}$
- $\sum_{k=0}^n \binom{n}{k}^2 = \binom{2n}{n}$
- In a row p where p is a prime number, all the terms in that row except the 1s are multiples of p
- To count odd terms in row n , convert n to binary. Let x be the number of 1s in the binary representation. Then the number of odd terms will be 2^x
- Every entry in row $2^n - 1$ is odd

nCr.h
Time: $\mathcal{O}(\min(k, n - k))$

```
7ff19d, 8 lines
ll ncr(int n, int k) {
    ll res = 1, to = min(k, n-k);
    if (to < 0) return 0;
    for (int i = 0; i < to; ++i) {
        res = res * (n - i) / (i + 1);
    }
    return res;
}
```

RollingBinomial.h
Description: $\binom{n}{k} \pmod m$ in time proportional to the difference between (n, k) and the previous (n, k) .

```
1740dc, 16 lines
cusing i64 = int64_t;
const int mod = int(1e9) + 7;
i64 invs[200015];
```

```
struct Bin {
    int N = 0, K = 0; i64 r = 1;
```

```
void m(int a, int b) { r = r * a % mod * invs[b] % mod; }
i64 choose(int n, int k) {
    if (k > n || k < 0) return 0;
    while(N < n) ++N, m(N, N - K);
    while(K < k) ++K, m(N - K + 1, K);
    while(K > k) m(K, N - K + 1), --K;
    while(N > n) m(N - K, N), --N;
    return r;
}
};
```

Lucas.h
Description: Lucas’ thm: Let n, m be non-negative integers and p a prime. Write $n = n_k p^k + \dots + n_1 p + n_0$ and $m = m_k p^k + \dots + m_1 p + m_0$. Then $\binom{n}{m} \equiv \prod_{i=0}^k \binom{n_i}{m_i} \pmod p$. fact and invt must hold pre-computed factorials / inverse factorials, e.g. from ModInv.h.
Time: $\mathcal{O}(\log_p m)$

```
2c2873, 10 lines
ll chooseModP(ll n, ll m, int p) {
    assert(m < 0 || m > n);
    ll c = 1;
    for (; m > 0; n /= p, m /= p) {
        lint n0 = n % p, m0 = m % p;
        if (n0 < m0) return 0;
        c = c * (((fact[n0] * ifact[m0]) % p) * ifact[n0 - m0]) %
            p) % p;
    }
    return c;
}
```

Multinomial.h
Description: Computes $\binom{k_1 + \dots + k_n}{k_1, k_2, \dots, k_n} = \frac{(\sum k_i)!}{k_1! k_2! \dots k_n!}$.

```
864cdb, 7 lines
lint multinomial(vector<int>& v) {
    lint c = 1, m = v.empty() ? 1 : v[0];
    for (int i = 1 < v.size(); ++i)
        for (int j = 0; j < v[i]; ++j)
            c = c * ++m / (j+1);
    return c;
}
```

6.1.3 Involutions

An involution is a permutation with maximum cycle length 2, and it is its own inverse.

$$a(n) = a(n - 1) + (n - 1)a(n - 2)$$

$$a(0) = a(1) = 1$$

1, 1, 2, 4, 10, 26, 76, 232, 764, 2620, 9496, 35696, 140152

6.1.4 Cycles

Let the number of n -permutations whose cycle lenghts all belong to the set S be denoted by $g_S(n)$

$$\sum_{n=0}^{\infty} g_S(n) \frac{x^n}{n!} = \exp \left(\sum_{n \in S} \frac{x^n}{n} \right)$$

6.1.5 Inclusion-Exclusion Principle

Let A_1, A_2, \dots, A_n be finite sets. Then $A_1 \cup A_2 \cup \dots \cup A_n$ is

$$\left| \bigcup_{i=1}^n A_i \right| = \sum_{\substack{I \subseteq \{1, 2, \dots, n\} \\ I \neq \emptyset}} (-1)^{|I|+1} \left| \bigcap_{i \in I} A_i \right|$$

6.1.6 The twelvefold way (from Stanley)

How many functions $f: N \rightarrow X$ are there?

N	X	Any f	Injective	Surjective
dist.	dist.	x^n	$\frac{x!}{(x-n)!}$	$x! \left\{ \begin{smallmatrix} n \\ x \end{smallmatrix} \right\}$
indist.	dist.	$\binom{x+n-1}{n}$	$\binom{x}{n}$	$\binom{n-1}{n-x}$
dist.	indist.	$\left\{ \begin{smallmatrix} n \\ 1 \end{smallmatrix} \right\} + \dots + \left\{ \begin{smallmatrix} n \\ x \end{smallmatrix} \right\}$	$[n \leq x]$	$\left\{ \begin{smallmatrix} n \\ k \end{smallmatrix} \right\}$
indist.	indist.	$p_1(n) + \dots p_x(n)$	$[n \leq x]$	$p_x(n)$

Where $\binom{a}{b} = \frac{1}{b!} (a)_b$, $p_x(n)$ is the number of ways to partition the integer n using x summand and $\left\{ \begin{smallmatrix} n \\ x \end{smallmatrix} \right\}$ is the number of ways to partition a set of n elements into x subsets (aka Stirling number of the second kind).

6.1.7 Burnside

Given a group G of symmetries and a set X , the number of elements of X up to symmetry equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|,$$

where X^g are the elements fixed by g ($g.x = x$).

If $f(n)$ counts “configurations” (of some sort) of length n , we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n, k)) = \frac{1}{n} \sum_{k|n} f(k) \phi(n/k).$$

6.1.8 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n - 1)(D(n - 1) + D(n - 2)) = nD(n - 1) + (-1)^n = \left\lfloor \frac{n!}{e} \right\rfloor$$

6.2 Partitions and subsets

6.2.1 Partition function

Number of ways of writing n as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1, p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k - 1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

$\frac{n}{p(n)}$	0	1	2	3	4	5	6	7	8	9	20	50	100
	1	1	2	3	5	7	11	15	22	30	627	$\sim 2e5$	$\sim 2e8$

6.3 General purpose numbers

6.3.1 Bernoulli numbers

EGF of Bernoulli numbers is $B(t) = \frac{t}{e^t - 1}$ (FFT-able).
 $B[0, \dots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \dots]$

Sums of powers:

$$\sum_{i=1}^n n^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\sum_{i=m}^\infty f(i) = \int_m^\infty f(x)dx - \sum_{k=1}^\infty \frac{B_k}{k!} f^{(k-1)}(m) \\ \approx \int_m^\infty f(x)dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m))$$

6.3.2 Stirling numbers of the first kind

Number of permutations on n items with k cycles.

$$c(n, k) = c(n - 1, k - 1) + (n - 1)c(n - 1, k), c(0, 0) = 1 \\ \sum_{k=0}^n c(n, k)x^k = x(x + 1) \dots (x + n - 1)$$

$$c(8, k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1 \\ c(n, 2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \dots$$

6.3.3 Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j :s s.t. $\pi(j) > \pi(j + 1)$, $k + 1$ j :s s.t. $\pi(j) \geq j$, k j :s s.t. $\pi(j) > j$.

$$E(n, k) = (n - k)E(n - 1, k - 1) + (k + 1)E(n - 1, k)$$

$$E(n, 0) = E(n, n - 1) = 1$$

$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

6.3.4 Stirling numbers of the second kind

Partitions of n distinct elements into exactly k groups.

$$S(n, k) = S(n - 1, k - 1) + kS(n - 1, k)$$

$$S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$$

6.3.5 Bell numbers

Total number of partitions of n distinct elements. $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \dots$

$$\mathcal{B}_{n+1} = \sum_{k=0}^n \binom{n}{k} \mathcal{B}_k$$

Also possible to calculate using Stirling numbers of the second kind,

$$B_n = \sum_{k=0}^n S(n, k)$$

If p is prime:

$$B(p^m + n) \equiv mB(n) + B(n + 1) \pmod{p}$$

6.3.6 Labeled unrooted trees

on n vertices: n^{n-2}
on k existing trees of size n_i : $n_1 n_2 \dots n_k n^{k-2}$
with degrees d_i : $(n - 2)! / ((d_1 - 1)! \dots (d_n - 1)!) \cdot \#$ forests with exactly k rooted trees:

$$\binom{n}{k} k \cdot n^{n-k-1}$$

6.3.7 Catalan numbers

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1, \quad C_{n+1} = \frac{2(2n+1)}{n+2} C_n, \quad C_{n+1} = \sum C_i C_{n-i}$$

$$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \dots$$

- sub-diagonal monotone paths in a $n \times n$ grid.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with with $n + 1$ leaves (0 or 2 children) or $2n + 1$ elements.
- ordered trees with $n + 1$ vertices.
- # ways a convex polygon with $n + 2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subsequence.

6.3.8 Super Catalan numbers

The number of monotonic lattice paths of a $n \times n$ grid that do not touch the diagonal.

$$S(n) = \frac{3(2n-3)S(n-1) - (n-3)S(n-2)}{n}$$

$$S(1) = S(2) = 1$$

$$1, 1, 3, 11, 45, 197, 903, 4279, 20793, 103049, 518859$$

6.3.9 Motzkin numbers

Number of ways of drawing any number of nonintersecting chords among n points on a circle. Number of lattice paths from $(0, 0)$ to $(n, 0)$ never going below the x -axis, using only steps NE, E, SE.

$$M(n) = \frac{3(n-1)M(n-2) + (2n+1)M(n-1)}{n+2}$$

$$M(0) = M(1) = 1$$

$$1, 1, 2, 4, 9, 21, 51, 127, 323, 835, 2188, 5798, 15511, 41835, 113634$$

6.3.10 Narayana numbers

Number of lattice paths from $(0,0)$ to $(2n,0)$ never going below the x -axis, using only steps NE and SE, and with k peaks.

$$N(n, k) = \frac{1}{n} \binom{n}{k} \binom{n}{k-1}$$

$$N(n, 1) = N(n, n) = 1$$

$$\sum_{k=1}^n N(n, k) = C_n$$

$$1, 1, 1, 1, 3, 1, 1, 6, 6, 1, 1, 10, 20, 10, 1, 1, 15, 50$$

6.3.11 Schroder numbers

Number of lattice paths from $(0, 0)$ to (n, n) using only steps N,NE,E, never going above the diagonal. Number of lattice paths from $(0, 0)$ to $(2n, 0)$ using only steps NE, SE and double east EE, never going below the x -axis. Twice the Super Catalan number, except for the first term.

$$1, 2, 6, 22, 90, 394, 1806, 8558, 41586, 206098$$

6.3.12 Triangles

Given rods of length 1, ..., n ,

$$T(n) = \frac{1}{24} \left\{ \begin{array}{ll} n(n-2)(2n-5) & n \text{ even} \\ (n-1)(n-3)(2n-1) & n \text{ odd} \end{array} \right\}$$

is the number of distinct triangles (positive are) that can be constructed, i.e., the # of 3-subsets of $[n]$ s.t. $x \leq y \leq z$ and $z \neq x + y$.

6.4 Fibonacci

$$Fib(x + y) = Fib(x + 1)Fib(y) + Fib(x)Fib(y - 1)$$

$$Fib(n + 1)Fib(n - 1) - Fib(n)^2 = (-1)^n$$

$$Fib(2n - 1) = Fib(n)^2 - Fib(n - 1)^2$$

$$\sum_{i=0}^n Fib(i) = Fib(n + 2) - 1$$

$$\sum_{i=0}^n Fib(i)^2 = Fib(n)Fib(n + 1)$$

$$\sum_{i=0}^n Fib(i)^3 = \frac{Fib(n)Fib(n + 1)^2 - (-1)^n Fib(n - 1) + 1}{2}$$

6.5 Linear Recurrences

(i) $F_n = F_{n-1} + F_{n-2}$

$$\begin{bmatrix} 0 & 1 \\ 1 & 1 \end{bmatrix} \begin{bmatrix} F_0 \\ F_1 \end{bmatrix} = \begin{bmatrix} F_1 \\ F_2 \end{bmatrix}$$

$$(ii) F_i = \sum_{j=1}^K C_j F_{i-j}$$

$$\begin{bmatrix} 0 & 1 & 0 & 0 & \cdot & 0 \\ 0 & 0 & 1 & 0 & \cdot & 0 \\ 0 & 0 & 0 & 1 & \cdot & 0 \\ \vdots & C_K & C_{K-1} & C_{K-2} & C_{K-3} & \vdots \\ & & & & & C_1 \end{bmatrix} \begin{bmatrix} F_0 \\ F_1 \\ F_2 \\ F_3 \\ \vdots \\ F_{K-1} \end{bmatrix} = \begin{bmatrix} F_1 \\ F_2 \\ F_3 \\ \vdots \\ F_K \end{bmatrix}$$

$$(iii) F_i = \sum_{j=1}^K C_j F_{i-j} + D$$

$$\begin{bmatrix} 0 & 1 & 0 & 0 & \cdot & 0 & 0 \\ 0 & 0 & 1 & 0 & \cdot & 0 & 0 \\ 0 & 0 & 0 & 1 & \cdot & 0 & 0 \\ \vdots & C_K & C_{K-1} & C_{K-2} & C_{K-3} & \vdots & C_1 \\ & & & & & & 1 \end{bmatrix} \begin{bmatrix} F_0 \\ F_1 \\ F_2 \\ F_3 \\ \vdots \\ F_{K-1} \\ D \end{bmatrix} = \begin{bmatrix} F_1 \\ F_2 \\ F_3 \\ \vdots \\ F_K \\ D \end{bmatrix}$$

6.6 Game Theory

A game can be reduced to Nim if it is a finite impartial game.

Nim and its variants include:

6.6.1 Nim

Let $X = \bigoplus_{i=1}^n x_i$, then $(x_i)_{i=1}^n$ is a winning position iff $X \neq 0$. Find a move by picking k such that $x_k > x_k \oplus X$.

6.6.2 Misère Nim

Regular Nim, except that the last player to move *loses*. Play regular Nim until there is only one pile of size larger than 1, reduce it to 0 or 1 such that there is an odd number of piles. The second player wins (a_1, \dots, a_n) if 1) there is a pile $a_i > 1$ and $\bigoplus_{i=1}^n a_i = 0$ or 2) all $a_i \leq 1$ and $\bigoplus_{i=1}^n a_i = 1$.

6.6.3 Staircase Nim

Stones are moved down a staircase and only removed from the last pile. $(x_i)_{i=1}^n$ is an L -position if $(x_{2i-1})_{i=1}^{n/2}$ is (i.e. only look at odd-numbered piles).

6.6.4 Moore's Nim_k

The player may remove from at most k piles (Nim = Nim₁). Expand the piles in base 2, do a carry-less addition in base $k+1$ (i.e. the number of ones in each column should be divisible by $k+1$).

6.6.5 Dim⁺

The number of removed stones must be a divisor of the pile size. The Sprague-Grundy function is $k+1$ where 2^k is the largest power of 2 dividing the pile size.

6.6.6 Aliquot Game

Same as above, except the divisor should be proper (hence 1 is also a terminal state, but watch out for size 0 piles). Now the Sprague-Grundy function is just k .

6.6.7 Nim (at most half)

Write $n+1 = 2^m y$ with m maximal, then the Sprague-Grundy function of n is $(y-1)/2$.

6.6.8 Lasker's Nim

Players may alternatively split a pile into two new non-empty piles. $g(4k+1) = 4k+1$, $g(4k+2) = 4k+2$, $g(4k+3) = 4k+4$, $g(4k+4) = 4k+3$ ($k \geq 0$).

6.6.9 Hackenbush on Trees

A tree with stalks $(x_i)_{i=1}^n$ may be replaced with a single stalk with length $\bigoplus_{i=1}^n x_i$.

Nim-Product.cpp

Description: Product of nimbers is associative, commutative, and distributive over addition (xor). Forms finite field of size 2^{2^k} . Application: Given 1D coin turning games G_1, G_2 $G_1 \times G_2$ is the 2D coin turning game defined as follows. If turning coins at x_1, x_2, \dots, x_m is legal in G_1 and y_1, y_2, \dots, y_n is legal in G_2 , then turning coins at all positions (x_i, y_j) is legal assuming that the coin at (x_m, y_n) goes from heads to tails. Then the grundy function $g(x, y)$ of $G_1 \times G_2$ is $g_1(x) \times g_2(y)$.
Time: 64² xors per multiplication, memorize to speed up.

```
using ull = uint64_t;
ull _nimProd2[64][64];
ull nimProd2(int i, int j) {
    if (_nimProd2[i][j]) return _nimProd2[i][j];
    if ((i & j) == 0) return _nimProd2[i][j] = 1ull << (i|j);
    int a = (i&j) & ~(i&j);
    return _nimProd2[i][j] = nimProd2(i ^ a, j) ^ nimProd2((i ^ a) | (a-1), (j ^ a) | (i & (a-1)));
}
void allNimProd2() {
    for (int i = 0; i < 64; i++) {
        for (int j = 0; j < 64; j++) {
            if ((i & j) == 0) _nimProd2[i][j] = 1ull << (i|j);
            else {
                int a = (i&j) & ~(i&j);
                _nimProd2[i][j] = _nimProd2[i ^ a][j] ^
                    _nimProd2[(i ^ a) | (a-1)][(j ^ a) | (i & (a-1))];
            }
        }
    }
}
ull nimProd(ull x, ull y) {
    ull res = 0;
    for (int i = 0; (x >> i) && i < 64; ++i)
        if ((x >> i) & 1)
            for (int j = 0; (y >> j) && j < 64; ++j)
                if ((y >> j) & 1) res ^= nimProd2(i, j);
    return res;
}
```

Partitions.cpp

Description: Fills array with partition function $p(n) \forall 0 \leq n \leq 122$.

```
array<int, 122> part; // 121 is max partition that will fit into int
void partition(int n) {
    part[0] = 1;
    for (int i = 1; i <= n; ++i) {
        part[i] = 0;
        for (int k = 1, x; k <= i; ++k) {
            x = i - k * (3*k-1)/2;
            if (x < 0) break;
            if (k&1) part[i] += part[x];
            else part[i] -= part[x];
            x = i - k * (3*k+1)/2;
            if (x < 0) break;
            if (k&1) part[i] += part[x];
            else part[i] -= part[x];
        }
    }
}
```

Graph (7)

7.1 Fundamentals

bellman-ford.h

Description: Calculates shortest paths from s in a graph that might have negative edge weights. Unreachable nodes get dist = inf; nodes reachable through negative-weight cycles get dist = -inf. Assumes $V^2 \max |w_i| < 2^{63}$.
Time: $\mathcal{O}(VE)$

```
const lint inf = LLONG_MAX;
struct edge_t { int a, b, w, s() { return a < b ? a : -a; } };
struct node_t { lint dist = inf; int prev = -1; };

void bellmanFord(vector<node_t>& nodes, vector<edge_t>& eds, int s) {
    nodes[s].dist = 0;
    sort(eds.begin(), eds.end(), [](edge_t a, edge_t b) { return a.s() < b.s(); });
    int lim = nodes.size() / 2 + 2; // /3+100 with shuffled vertices
    for(int i = 0; i < lim; ++i) for(auto &ed : eds) {
        node_t cur = nodes[ed.a], &dest = nodes[ed.b];
        if (abs(cur.dist) == inf) continue;
        lint d = cur.dist + ed.w;
        if (d < dest.dist) {
            dest.prev = ed.a;
            dest.dist = (i < lim-1 ? d : -inf);
        }
    }
    for(int i = 0; i < lim; ++i) for(auto &e : eds)
        if (nodes[e.a].dist == -inf) nodes[e.b].dist = -inf;
}
```

```
vector<int> negCyc(int n, vector<edge_t>& edges) {
    vector<int64_t> d(n); vector<int> p(n);
    int v = -1;
    for (int i = 0; i < n; ++i) {
        v = -1;
        for (edge_t &u : edges)
            if (d[u.b] > d[u.a] + u.w) {
                d[u.b] = d[u.a] + u.w;
                p[u.b] = u.a, v = u.b;
            }
        if (v == -1) return {};
    }
    for (int i = 0; i < n; ++i) v = p[v]; // enter cycle
    vector<int> cycle = {v};
    while (p[cycle.back()] != v) cycle.push_back(p[cycle.back()]);
    return {cycle.rbegin(), cycle.rend()};
}
```

floyd-warshall.h

Description: Calculates all-pairs shortest path in a directed graph that might have negative edge distances. Input is an distance matrix m , where $m[i][j] = \text{inf}$ if i and j are not adjacent. As output, $m[i][j]$ is set to the shortest distance between i and j , inf if no path, or $-\text{inf}$ if the path goes through a negative-weight cycle.
Time: $\mathcal{O}(N^3)$

```
const lint inf = 1LL << 62;
void floydWarshall(vector<vector<lint>>& m) {
    int n = m.size();
    for (int i = 0; i < n; ++i) m[i][i] = min(m[i][i], {});
    for (int k = 0; k < n; ++k)
        for (int i = 0; i < n; ++i)
            for (int j = 0; j < n; ++j)
                if (m[i][k] != inf && m[k][j] != inf) {
```



```

        auto newDist = max(m[i][k] + m[k][j], -inf);
        m[i][j] = min(m[i][j], newDist);
    }
    for (int k = 0; k < n; ++k) if (m[k][k] < 0)
        for (int i = 0; i < n; ++i)
            for (int j = 0; j < n; ++j)
                if (m[i][k] != inf && m[k][j] != inf) m[i][j] = -
                    inf;
}

```

topo-sort.h

Description: Topological sorting. Given is an oriented graph. Output is an ordering of vertices, such that there are edges only from left to right. If there are cycles, the returned list will have size smaller than n – nodes reachable from cycles will not be returned.

Time: $\mathcal{O}(|V| + |E|)$

d2ba1e, 12 lines

```

vector<int> topo_sort(const vector<vector<int>>& g) {
    vector<int> indeg(g.size()), ret;
    for(auto &li : g) for(auto &x : li) indeg[x]++;
    queue<int> q; // use priority queue for lexic. smallest ans.
    for(int i = 0; i < g.size(); ++i) if (indeg[i] == 0) q.push(-i);
    while (!q.empty()) {
        int i = -q.front(); // top() for priority queue
        ret.push_back(i); q.pop();
        for(auto &x : g[i]) if (--indeg[x] == 0) q.push(-x);
    }
    return ret;
}

```

dijkstra.h

Description: Faster implementation of Dijkstra's algorithm. Makes very easy to handle SSSP on state graphs.

Time: $\mathcal{O}(N \log N)$

67beaf, 31 lines

```

#include<bits/extc++.h> // keep-include!!

template <class D> struct MinDist {
    vector<D> dist; vector<int> from;
};

template <class D, class E> // Weight type and Edge info
MinDist<D> Dijkstra(const vector<vector<E>>& g, int s, D inf =
    numeric_limits<D>::max()) {
    int N = int(g.size());
    vector<D> dist = vector<D>(N, inf);
    vector<int> par = vector<int>(N);
    struct state_t {
        D key;
        int to;
        bool operator<(state_t r) const { return key > r.key; }
    };
    __gnu_pbds::priority_queue<state_t> q;
    q.push(state_t{0, s});
    dist[s] = D(0);
    while (!q.empty()) {
        state_t p = q.top(); q.pop();
        if (dist[p.to] < p.key) continue;
        for (E nxt : g[p.to]) {
            if (p.key + nxt.second < dist[nxt.first]) {
                dist[nxt.first] = p.key + nxt.second;
                par[nxt.first] = p.to;
                q.push(state_t{dist[nxt.first], nxt.first});
            }
        }
    }
    return MinDist<D>{dist, par};
}

```

euler-walk.h

Description: Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.

Time: $\mathcal{O}(V + E)$

c1cf41, 16 lines

```

using pii = pair<int,int>;
vector<int> eulerWalk(vector<vector<pii>>& gr, int nedges, int
    src=0) {
    int n = gr.size();
    vector<int> D(n), its(n), eu(nedges), ret, s = {src};
    D[src]++; // to allow Euler paths, not just cycles
    while (!s.empty()) {
        int x = s.back(), y, e, &it = its[x], end = int(gr[x].
            size());
        if (it == end) { ret.push_back(x); s.pop_back();
            continue; }
        tie(y, e) = gr[x][it++];
        if (!eu[e]) {
            D[x]--, D[y]++;
            eu[e] = 1; s.push_back(y);
        }
    }
    for(auto &x : D) if (x < 0 || int(ret.size()) != nedges+1)
        return {};
    return {ret.rbegin(), ret.rend()};
}

```

7.2 Network flow

push-relabel.h

Description: Push-relabel using the highest label selection rule and the gap heuristic. Quite fast in practice. To obtain the actual flow, look at positive values only. id can be used to restore each edge and its amount of flow used.

Time: $\mathcal{O}(V^2\sqrt{E})$ Better for dense graphs - Slower than Dinic (in practice)

387a0e, 42 lines

```

template<typename flow_t = int> struct PushRelabel {
    struct edge_t { int dest, back; flow_t f, c; };
    vector<vector<edge_t>> g;
    vector<flow_t> ec;
    vector<edge_t>* cur;
    vector<vector<int>> hs; vector<int> H;
    PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}
    void addEdge(int s, int t, flow_t cap, flow_t rcap = 0) {
        if (s == t) return;
        g[s].push_back({t, (int)g[t].size(), 0, cap});
        g[t].push_back({s, (int)g[s].size()-1, 0, rcap});
    }
    void addFlow(edge_t& e, flow_t f) {
        edge_t &back = g[e.dest][e.back];
        if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
        e.f += f; e.c -= f; ec[e.dest] += f;
        back.f -= f; back.c += f; ec[back.dest] -= f;
    }
    flow_t maxflow(int s, int t) {
        int v = int(g.size()); H[s] = v; ec[t] = 1;
        vector<int> co(2*v); co[0] = v-1;
        for(int i = 0; i < v; ++i) cur[i] = g[i].data();
        for(auto& e : g[s]) addFlow(e, e.c);
        for (int hi = 0; ; ) {
            while (hs[hi].empty()) if (!hi--) return -ec[s];
            int u = hs[hi].back(); hs[hi].pop_back();
            while (ec[u] > 0) // discharge u
                if (cur[u] == g[u].data() + g[u].size()) {
                    H[u] = 1e9;
                    for(auto &e : g[u]) if (e.c && H[u] > H[e.dest]+1)
                        H[u] = H[e.dest]+1, cur[u] = &e;
                    if (++co[H[u]], !--co[hi] && hi < v)

```

```

                for(int i = 0; i < v; ++i) if (hi < H[i] && H[i] <
                    v)
                    --co[H[i]], H[i] = v + 1;
                hi = H[u];
            } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
                addFlow(*cur[u], min(ec[u], cur[u]->c));
            else ++cur[u];
        }
    }
    bool leftOfMinCut(int a) { return H[a] >= int(g.size()); }
};

```

dinitz.h

Description: Flow algorithm with complexity $\mathcal{O}(VE \log U)$ where $U = \max |cap|$. $\mathcal{O}(\min(E^{1/2}, V^{2/3})E)$ if $U = 1$; $\mathcal{O}(\sqrt{VE})$ for bipartite matching. To obtain each partition A and B of the cut look at lvl , for $v \in A$, $lvl[v] > 0$, for $u \in B$, $lvl[u] = 0$.

582952, 45 lines

```

template<typename T = int> struct Dinitz {
    struct edge_t { int to, rev; T c, f; };
    vector<vector<edge_t>> adj;
    vector<int> lvl, ptr, q;
    Dinitz(int n) : lvl(n), ptr(n), q(n), adj(n) {}
    inline void addEdge(int a, int b, T c, T rcap = 0) {
        adj[a].push_back({b, (int)adj[b].size(), c, 0});
        adj[b].push_back({a, (int)adj[a].size() - 1, rcap, 0});
    }
    T dfs(int v, int t, T f) {
        if (v == t || !f) return f;
        for (int &i = ptr[v]; i < int(adj[v].size()); ++i) {
            edge_t &e = adj[v][i];
            if (lvl[e.to] == lvl[v] + 1)
                if (T p = dfs(e.to, t, min(f, e.c - e.f))) {
                    e.f += p, adj[e.to][e.rev].f -= p;
                    return p;
                }
        }
        return 0;
    }
    T maxflow(int s, int t) {
        T flow = 0; q[0] = s;
        for (int L = 0; L < 31; ++L) do { // 'int L=30' maybe
            faster for random data
            lvl = ptr = vector<int>(q.size());
            int qi = 0, qe = lvl[s] = 1;
            while (qi < qe && !lvl[t]) {
                int v = q[qi++];
                for (edge_t &e : adj[v])
                    if (!lvl[e.to] && (e.c - e.f) >> (30 - L))
                        q[qi++] = e.to, lvl[e.to] = lvl[v] + 1;
            }
            while (T p = dfs(s, t, numeric_limits<T>::max()/4)) flow
                += p;
        } while (lvl[t]);
        return flow;
    }
    bool leftOfMinCut(int v) { return bool(lvl[v] != 0); }
    pair<T, vector<pair<int,int>>> minCut(int s, int t) {
        T cost = maxflow(s, t);
        vector<pair<int,int>> cut;
        for (int i = 0; i < int(adj.size()); i++) for(edge_t &e :
            adj[i])
            if (lvl[i] && !lvl[e.to]) cut.push_back({i, e.to});
        return {cost, cut};
    }
};

```

min-cost-max-flow.h

Description: Min-cost max-flow. $\text{cap}[i][j] \neq \text{cap}[j][i]$ is allowed; double edges are not.

Time: Approximately $\mathcal{O}(E^2)$ faster than Kactl's on practice

<bits/extc++.h> // don't forget! f25a4f, 71 lines

```
template <typename flow_t = int, typename cost_t = long long>
struct MCMF_SSPA {
    int N;
    vector<vector<int>>> adj;
    struct edge_t { int dest; flow_t cap; cost_t cost; };
    vector<edge_t> edges;
    vector<char> seen;
    vector<cost_t> pi;
    vector<int> prv;
    explicit MCMF_SSPA(int N_) : N(N_), adj(N), pi(N, 0), prv(N) {}
    void addEdge(int from, int to, flow_t cap, cost_t cost) {
        assert(cap >= 0);
        assert(cost >= 0);
        int e = int(edges.size());
        edges.emplace_back(edge_t{to, cap, cost});
        edges.emplace_back(edge_t{from, 0, -cost});
        adj[from].push_back(e);
        adj[to].push_back(e+1);
    }
    const cost_t INF_COST = numeric_limits<cost_t>::max() / 4;
    const flow_t INF_FLOW = numeric_limits<flow_t>::max() / 4;
    vector<cost_t> dist;
    __gnu_pbds::priority_queue<pair<cost_t, int>> q;
    vector<typename decltype(q)::point_iterator> its;
    void path(int s) {
        dist.assign(N, INF_COST);
        dist[s] = 0;
        its.assign(N, q.end());
        its[s] = q.push({0, s});
        while (!q.empty()) {
            int i = q.top().second; q.pop();
            cost_t d = dist[i];
            for (int e : adj[i]) {
                if (edges[e].cap) {
                    int j = edges[e].dest;
                    cost_t nd = d + edges[e].cost;
                    if (nd < dist[j]) {
                        dist[j] = nd;
                        prv[j] = e;
                        if (its[j] == q.end()) its[j] = q.push({-(dist[j] - pi[j]), j});
                        else q.modify(its[j], {-(dist[j] - pi[j]), j});
                    }
                }
            }
        }
        swap(pi, dist);
    }
    pair<flow_t, cost_t> maxflow(int s, int t) {
        assert(s != t);
        flow_t totFlow = 0; cost_t totCost = 0;
        while (path(s), pi[t] < INF_COST) {
            flow_t curFlow = numeric_limits<flow_t>::max();
            for (int cur = t; cur != s; ) {
                int e = prv[cur];
                int nxt = edges[e^1].dest;
                curFlow = min(curFlow, edges[e].cap);
                cur = nxt;
            }
            totFlow += curFlow;
            totCost += pi[t] * curFlow;
            for (int cur = t; cur != s; ) {
                int e = prv[cur];
```

```
                int nxt = edges[e^1].dest;
                edges[e].cap -= curFlow;
                edges[e^1].cap += curFlow;
                cur = nxt;
            }
        }
        return {totFlow, totCost};
    }
};
```

7.3 Matching

hopcroft-karp.h

Description: Fast bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and $btoa$ should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $btoa[i]$ will be the match for vertex i on the right side, or -1 if it's not matched.

Usage: `vector<int> btoa(m, -1); hopcroftKarp(g, btoa);`

Time: $\mathcal{O}(\sqrt{VE})$

d9a55d, 35 lines

```
using vi = vector<int>;
bool dfs(int a, int L, const vector<vi> &g, vi &btoa, vi &A, vi &B) {
    if (A[a] != L) return 0;
    A[a] = -1;
    for(auto &b : g[a]) if (B[b] == L + 1) {
        B[b] = 0;
        if (btoa[b] == -1 || dfs(btoa[b], L+1, g, btoa, A, B))
            return btoa[b] = a, 1;
    }
    return 0;
}
int hopcroftKarp(const vector<vi> &g, vi &btoa) {
    int res = 0;
    vector<int> A(g.size()), B(int(btoa.size())), cur, next;
    for (;;) {
        fill(A.begin(), A.end(), 0), fill(B.begin(), B.end(), 0);
        cur.clear();
        for(auto &a : btoa) if (a != -1) A[a] = -1;
        for (int a = 0; a < g.size(); ++a) if (A[a] == 0) cur.push_back(a);
        for (int lay = 1; ++lay) {
            bool islast = 0; next.clear();
            for(auto &a : cur) for(auto &b : g[a]) {
                if (btoa[b] == -1) B[b] = lay, islast = 1;
                else if (btoa[b] != a && !B[b])
                    B[b] = lay, next.push_back(btoa[b]);
            }
            if (islast) break;
            if (next.empty()) return res;
            for(auto &a : next) A[a] = lay;
            cur.swap(next);
        }
        res += dfs(a, 0, g, btoa, A, B);
    }
}
```

bipartite-matching.h

Description: Fast Kuhn! Simple maximum cardinality bipartite matching algorithm. Better than hopcroftKarp in practice(Crazy heuristic huh). Worst case is $\mathcal{O}(VE)$ on an hairy tree. Shuffling the edges and vertices ordering should break some worst-case inputs.

Time: $\Omega(VE)$

69d629, 42 lines

```
struct Matching {
    int N, M, T;
    vector<vector<int>>> edges;
```

```
    vector<int> match, seen;
    Matching(int a, int b) : N(a), M(a + b), edges(M),
        match(M, -1), seen(M, -1), T(0) {}
    void addEdge(int a, int b) {
        assert(0 <= a && a < N && b + N < M && N <= b + N);
        edges[a].push_back(b + N);
    }
    void shuffle_edges() { // useful to break some hairy tests
        mt19937 rng(chrono::steady_clock::now());
        time_since_epoch().count();
        for (int i = 0; i < int(edges.size()); ++i)
            shuffle(edges[i].begin(), edges[i].end(), rng);
    }
    bool dfs(int v) {
        if (seen[v] == T) return false;
        seen[v] = T;
        for (int u : edges[v])
            if (match[u] == -1) {
                match[u] = v, match[v] = u;
                return true;
            }
        for (int u : edges[v])
            if (dfs(match[u])) {
                match[u] = v, match[v] = u;
                return true;
            }
        return false;
    }
    int solve() {
        int res = 0;
        while (true) {
            int cur = 0; ++T;
            for (int i = 0; i < N; ++i)
                if (match[i] == -1) cur += dfs(i);
            if (cur == 0) break;
            else res += cur;
        }
        return res;
    }
};
```

weighted-matching.h

Description: Given a weighted bipartite graph, matches every node on the left with a node on the right such that no nodes are in two matchings and the sum of the edge weights is minimal. Takes $\text{cost}[N][M]$, where $\text{cost}[i][j] = \text{cost}$ for $L[i]$ to be matched with $R[j]$ and returns (min cost, match), where $L[i]$ is matched with $R[\text{match}[i]]$. Negate costs for max cost.

Time: $\mathcal{O}(N^2M)$

7a2392, 31 lines

```
pair<int, vector<int>> hungarian(const vector<vector<int>>> &a)
{
    if (a.empty()) return {0, {}};
    int n = a.size() + 1, m = a[0].size() + 1;
    vector<int> u(n), v(m), p(m), ans(n - 1);
    for(int i = 1; i < n; ++i) {
        p[0] = i;
        int j0 = 0; // add "dummy" worker 0
        vector<int> dist(m, INT_MAX), pre(m, -1);
        vector<bool> done(m + 1);
        do {
            done[j0] = true;
            int i0 = p[j0], j1, delta = INT_MAX;
            for(int j = 1; j < m; ++j) if (!done[j]) {
                auto cur = a[i0-1][j-1] - u[i0] - v[j];
                if (cur < dist[j]) dist[j] = cur, pre[j] = j0;
                if (dist[j] < delta) delta = dist[j], j1 = j;
            }
            for(int j = 0; j < m; ++j) {
                if (done[j]) u[p[j]] += delta, v[j] -= delta;
```

```
        else dist[j] -= delta;
    }
    j0 = j1;
} while (p[j0]);
while (j0) { // update alternating path
    int j1 = pre[j0];
    p[j0] = p[j1], j0 = j1;
}
}
for(int j = 1; j < m; ++j) if (p[j]) ans[p[j]-1] = j-1;
return {-v[0], ans}; // min cost
}
```

general-matching-dfs.h

Description: Maximum Matching for general graphs (undirected and non bipartite) using a crazy chinese heuristic(Yet to find any counter case). one-indexed based implementation, be careful. *it* represents how many iterations you wanna try, something between [5, 500] suffice.

Usage: GeneralMatching G(N+1); G.addEdge(a+1, b+1); int max_matching = G.solve(5);

Time: $\mathcal{O}(EV)$

"../various/RandomNumbers.h" 596e90, 44 lines

```
struct GeneralMatching {
    int N, T;
    vector<vector<int>>> edges;
    vector<int> seen, match;
    GeneralMatching(int _N) : N(_N), T(0), edges(N), seen(N),
        match(N) {}
    void addEdge(int a, int b) { // one-based!
        edges[a].push_back(b);
        edges[b].push_back(a);
    }
    bool dfs(int v) {
        if (v == 0) return true;
        seen[v] = T;
        shuffle(edges[v].begin(), edges[v].end(), rng);
        for (int u : edges[v]) {
            int to = match[u];
            if (seen[to] < T) {
                match[v] = u, match[u] = v, match[to] = 0;
                if (dfs(to)) return true;
                match[u] = to, match[to] = u, match[v] = 0;
            }
        }
        return false;
    }
    int solve(int it) {
        int res = 0;
        for (int t = 0; t < it; ++t) {
            for (int i = 1; i < N; ++i) {
                if (match[i]) continue;
                ++T;
                res += dfs(i);
            }
        }
        return res;
    }
    vector<array<int, 2>> get_edges(int it) {
        int ma = solve(it);
        vector<array<int, 2>> E; E.reserve(ma);
        for (int i = 1; i < N; ++i) {
            if (i > match[i] || match[i] <= 0) continue;
            E.push_back({i-1, match[i]-1});
        }
        return E;
    }
};
```

general-matching.h

Description: Maximum Matching for general graphs (undirected and non bipartite) using Edmond's Blossom Algorithm.

Time: $\mathcal{O}(EV^2)$

```
0b82ee, 68 lines
struct blossom_t {
    int t, n; // 1-based indexing!!
    vector<vector<int>>> edges;
    vector<int> seen, parent, og, match, aux, Q;
    blossom_t(int _n) : n(_n), edges(n+1), seen(n+1),
        parent(n+1), og(n+1), match(n+1), aux(n+10), t(0) {}
    void addEdge(int u, int v) {
        edges[u].push_back(v);
        edges[v].push_back(u);
    }
    void augment(int u, int v) {
        int pv = v, nv; // flip states of edges on u-v path
        do {
            pv = parent[v]; nv = match[pv];
            match[v] = pv; match[pv] = v;
            v = nv;
        } while(u != pv);
    }
    int lca(int v, int w) { // find LCA in O(dist)
        ++t;
        while (1) {
            if (v) {
                if (aux[v] == t) return v; aux[v] = t;
                v = og[parent[match[v]]];
            }
            swap(v, w);
        }
    }
    void blossom(int v, int w, int a) {
        while (og[v] != a) {
            parent[v] = w; w = match[v]; // go other way around
            cycle
            if(seen[w] == 1) Q.push_back(w), seen[w] = 0;
            og[v] = og[w] = a; // merge into supernode
            v = parent[w];
        }
    }
    bool bfs(int u) {
        for (int i = 1; i <= n; ++i) seen[i] = -1, og[i] = i;
        Q = vector<int>(); Q.push_back(u); seen[u] = 0;
        for(int i = 0; i < Q.size(); ++i) {
            int v = Q[i];
            for(auto &x : edges[v]) {
                if (seen[x] == -1) {
                    parent[x] = v; seen[x] = 1;
                    if (!match[x]) return augment(u, x), true;
                    Q.push_back(match[x]); seen[match[x]] = 0;
                } else if (seen[x] == 0 && og[v] != og[x]) {
                    int a = lca(og[v], og[x]);
                    blossom(x, v, a); blossom(v, x, a);
                }
            }
        }
        return false;
    }
    int solve() {
        int ans = 0; // find random matching (not necessary,
        vector<int> V(n-1); iota(V.begin(), V.end(), 1); //
            constant improvement)
        shuffle(V.begin(), V.end(), mt19937(0x94949));
        for(auto &x : V) if(!match[x])
            for(auto &y : edges[x]) if (!match[y]) {
                match[x] = y, match[y] = x;
                ++ans; break;
            }
    }
};
```

```
    }
    for (int i = 1; i <= n; ++i)
        if (!match[i] && bfs(i)) ++ans;
    return ans;
}
};
```

max-independent-set.h

Description: To obtain a maximum independent set of a graph, find a max clique of the complement. If the graph is bipartite, see MinimumVertex-Cover.

min-vertex-cover.h

Description: Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

"BipartiteMatching.h" 1c02d3, 20 lines

```
vector<int> cover(Matching& B, int N, int M) {
    int ma = B.solve();
    vector<bool> lfound(N, true), seen(N+M);
    for (int i = N; i < N+M; ++i) if (B.match[i] != -1)
        lfound[B.match[i]] = false;
    vector<int> q, cover;
    for (int i = 0; i < N; ++i) if (lfound[i]) q.push_back(i);
    while (!q.empty()) {
        int v = q.back(); q.pop_back();
        lfound[v] = true;
        for(int e : B.edges[v]) if (!seen[e] && B.match[e] !=
            -1) {
            seen[e] = true;
            q.push_back(B.match[e]);
        }
    }
    for (int i = 0; i < N; ++i) if (!lfound[i]) cover.push_back
        (i);
    for (int i = N; i < N+M; ++i) if (seen[i]) cover.push_back(
        i);
    assert(cover.size() == ma);
    return cover;
}
```

min-edge-cover.h

Description: Finds a minimum edge cover in a bipartite graph. The size is the same as the number of vertices minus the size of a maximum matching. The mark vector represents who the vertices of set *B* has an edge to.

Usage: vector<int> mark(n+m, -1);

auto cover = minEdgeCover(g, mark, n, m);

"BipartiteMatching.h" ff9804, 13 lines

```
vector<pair<int,int>> minEdgeCover(Matching& g, vector<int>&
    mark, int N, int M) {
    int ma = g.solve();
    vector<pair<int,int>> cover;
    for (int i = 0; i < N; ++i) {
        if (g.match[i] >= 0) cover.push_back({i, g.match[i]-N})
            ;
        else if (int(g.edges[i].size()))
            cover.push_back({i, g.edges[i][0] - N});
    }
    for (int i = N; i < N + M; ++i)
        if (g.match[i] == -1 && mark[i] >= 0)
            cover.push_back({mark[i], i - N});
    return cover;
}
```

min-path-cover.h

Description: Finds a minimum vertex-disjoint path cover in a dag. The size is the same as the number of vertices minus the size of a maximum matching.

"BipartiteMatching.h" f6a830, 15 lines

```
vector<vector<int>>> minPathCover(Matching& g, int N) {
    int how_many = int(g.edges.size()) - g.solve();
    vector<vector<int>>> paths;
    for (int i = 0; i < N; ++i)
        if (g.match[i + N] == -1) {
            vector<int> path = {i};
            int cur = i;
            while (g.match[cur] >= 0) {
                cur = g.match[cur] - N;
                path.push_back(cur);
            }
            paths.push_back(path);
        }
    return paths;
}
```

7.4 DFS algorithms

dfs-tree.h

Description: Builds dfs tree. Find cut vertices and bridges.

Usage: Call solve right after build the graph

dbc136, 51 lines

```
struct tree_t {
    int timer, n;
    vector<vector<int>>> edges;
    vector<pair<int,int>>> bridges;
    vector<int> depth, mindepth, parent, st, cut, children;
    tree_t(int n) : n(n), timer(0), edges(n), parent(n,-1),
        mindepth(n,-1), depth(n,-1), st(n,-1) {}
    void addEdge(int a, int b) {
        edges[a].push_back(b); edges[b].push_back(a);
    }
    void dfs(int v) {
        st[v] = timer;
        mindepth[v] = depth[v];
        for (int u : edges[v]) {
            if (u == parent[v]) continue;
            if (st[u] == timer) {
                mindepth[v] = min(mindepth[v], depth[u]);
                continue;
            }
            depth[u] = 1 + depth[v];
            parent[u] = v;
            dfs(u);
            mindepth[v] = min(mindepth[v], mindepth[u]);
        }
    }
    vector<pair<int,int>>> find_bridges() {
        for (int i = 0; i < n; ++i)
            if (parent[i] != -1 && mindepth[i] == depth[i])
                bridges.push_back({parent[i], i});
        return bridges;
    }
    vector<bool> find_cut() {
        cut.resize(n), children.resize(n);
        for (int i = 0; i < n; ++i)
            if (parent[i] != -1 && mindepth[i] >= depth[parent[i]])
                cut[parent[i]] = 1;
        for (int i = 0; i < n; ++i)
            if (parent[i] != -1) child[parent[i]]++;
        for (int i = 0; i < n; ++i)
            if (parent[i] == -1 && child[i] < 2) cut[i] = 0;
        return cut;
    }
    void solve() {
```

```
        for (int i = 0; i < n; ++i)
            if (depth[i] == -1) {
                depth[i] = 0; parent[i] = -1;
                ++timer;
                dfs(i);
            }
    }
};
```

centroid-decomposition.h

Description: Divide and Conquer on Trees.

e35893, 57 lines

```
struct centroid_t {
    int n;
    vector<vector<int>>> edges;
    vector<vector<int>>> dist; // dist to all ancestors
    vector<bool> blocked; // processed centroid
    vector<int> sz, depth, parent; // centroid parent
    centroid_t(int _n) : n(_n), edges(n), blocked(n), sz(n),
        depth(n),
        parent(n), dist(32 - __builtin_clz(n), vector<int>(n))
    {}
    void addEdge(int a, int b) {
        edges[a].push_back(b);
        edges[b].push_back(a);
    }
    void dfs_sz(int v, int p) {
        sz[v] = 1;
        for (int u : edges[v]) {
            if (u == p || blocked[u]) continue;
            dfs_sz(u, v);
            sz[v] += sz[u];
        }
    }
    int find(int v, int p, int tsz) { // find a centroid
        for (int u : edges[v])
            if (!blocked[u] && u != p && 2*sz[u] > tsz)
                return find(u, v, tsz);
        return v;
    }
    void dfs_dist(int v, int p, int layer, int d) {
        dist[layer][v] = d;
        for (int u : edges[v]) {
            if (blocked[u] || u == p) continue;
            dfs_dist(u, v, layer, d + 1);
        }
    }
    int solve(int v, int p) {
        // solve the problem for each subtree here xD
    }
    int decompose(int v, int layer=0, int lst_x = -1) {
        dfs_sz(v, -1);
        int x = find(v, v, sz[v]);
        blocked[x] = true;
        depth[x] = layer;
        parent[x] = lst_x;
        dfs_dist(x, x, layer, 0);
        int res = solve(x, v); // solving for each subtree
        for (int u : edges[x]) {
            if (blocked[u]) continue;
            res += decompose(u, layer + 1, x);
        }
        return res;
    }
```

```
    }
};
```

tarjan.h

Description: Finds strongly connected components in a directed graph. If vertices u, v belong to the same component, we can reach u from v and vice versa.

Usage: scc(graph, [&](vi& v) { ... }) visits all components in reverse topological order. comp[i] holds the component index of a node (a component only has edges to components with lower index). ncomps will contain the number of components.

Time: $\mathcal{O}(E + V)$

9d7648, 24 lines

```
using G = vector<vector<int>>>;
vector<int> val, comp, z, cont;
int Time, ncomps;
template<class G, class F> int dfs(int j, G& g, F& f) {
    int low = val[j] = ++Time, x; z.push_back(j);
    for (auto e : g[j]) if (comp[e] < 0)
        low = min(low, val[e] ? dfs(e, g, f));
    if (low == val[j]) {
        do {
            x = z.back(); z.pop_back();
            comp[x] = ncomps;
            cont.push_back(x);
        } while (x != j);
        f(cont); cont.clear();
        ncomps++;
    }
    return val[j] = low;
}
template<class G, class F> void scc(G& g, F f) {
    int n = int(g.size());
    val.assign(n, 0); comp.assign(n, -1);
    Time = ncomps = 0;
    for (int i = 0; i < n; ++i) if (comp[i] < 0) dfs(i, g, f);
}
```

kosaraju.h

Description: Kosaraju's Algorithm, DFS twice to generate strongly connected components in topological order. a, b in same component if both $a \rightarrow b$ and $b \rightarrow a$ exist.

Time: $\mathcal{O}(V + E)$

25be07, 35 lines

```
struct Kosaraju_t {
    int n;
    vector<vector<int>>> edges, redges;
    vector<bool> seen;
    vector<int> cnt_of, cnts;
    Kosaraju_t(const int &N) : n(N), edges(N), redges(N), seen(N),
        cnt_of(N, -1) {}
    void addEdge(int a, int b) {
        edges[a].push_back(b);
        redges[b].push_back(a);
    }
    void dfs(int v) {
        seen[v] = true;
        for (int u : edges[v]) {
            if (seen[u]) continue;
            dfs(u);
        }
        toposort.push_back(v);
    }
    void dfs_fix(int v, int w) {
        cnt_of[v] = x;
        for (int u : redges[v]) {
            if (cnt_of[u] == -1) dfs_fix(u, w);
        }
    }
}
```

```
void solve() {
    for (int i = 0; i < n; ++i)
        if (seen[i] == false) dfs(i);
    reverse(toposort.begin(), toposort.end());
    for (int u : toposort) {
        if (cnt_of[u] != -1) continue;
        dfs_fix(u, u);
        cnts.push_back(u);
    }
}
};
```

bcc.h

Description: Finds all biconnected components in an undirected graph, and runs a callback for the edges in each. In a biconnected component there are at least two distinct paths between any two nodes. Note that a node can be in several components. An edge which is not in a component is a bridge, i.e., not part of any cycle.

Usage: int eid = 0; ed.resize(N);
for each edge (a,b) {
ed[a].emplace_back(b, eid);
ed[b].emplace_back(a, eid++); }
bicomps([&](const vi& edgelist) {...});

Time: $\mathcal{O}(E + V)$

1aa908, 31 lines

```
vector<int> num, st;
vector<vector<pii>> ed;
int Time;
template<class F> int dfs(int at, int par, F& f) {
    int me = num[at] = ++Time, e, y, top = me;
    for(auto &pa : ed[at]) if (pa.second != par) {
        tie(y, e) = pa;
        if (num[y]) {
            top = min(top, num[y]);
            if (num[y] < me) st.push_back(e);
        } else {
            int si = int(st.size());
            int up = dfs(y, e, f);
            top = min(top, up);
            if (up == me) {
                st.push_back(e);
                f(vector<int>(st.begin() + si, st.end()));
                st.resize(si);
            }
            else if (up < me) st.push_back(e);
            else { /* e is a bridge */ }
        }
    }
    return top;
}

template<class F> void bicomps(F f) {
    num.assign(ed.size(), 0);
    for(int i = 0; i < int(ed.size()); ++i)
        if (!num[i]) dfs(i, -1, f);
}
```

7.5 Heuristics

maximal-cliques.h

Description: Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Possible optimization: on the top-most recursion level, ignore 'cands', and go through nodes in order of increasing degree, where degrees go down as nodes are removed.

Time: $\mathcal{O}\left(3^{n/3}\right)$, much faster for sparse graphs

57e107, 12 lines

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B> &eds, F f, B P = ~B(), B X={}, B R={}) {
```

```
    if (!P.any()) { if (!X.any()) f(R); return; }
    auto q = (P | X)._Find_first();
    auto cands = P & ~eds[q];
    for(int i = 0; i < eds.size(); ++i) if (cands[i]) {
        R[i] = 1;
        cliques(eds, f, P & eds[i], X & eds[i], R);
        R[i] = P[i] = 0; X[i] = 1;
    }
}
```

maximum-clique.h

Description: Finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.

Time: Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.

261d2e, 49 lines

```
using vb = vector<bitset<40>>;
struct Maxclique {
    double limit = 0.025, pk = 0;
    struct Vertex { int i, d = 0; };
    using vv = vector<Vertex>;
    vb e;
    vv V;
    vector<vector<int>> C;
    vector<int> qmax, q, S, old;
    void init(vv& r) {
        for(auto& v : r) v.d = 0;
        for(auto& v : r) for(auto& j : r) v.d += e[v.i][j.i];
        sort(r.begin(), r.end(), [](auto a, auto b) { return a.d > b.d; });
        int mxD = r[0].d;
        for(int i = 0; i < int(r.size()); ++i) r[i].d = min(i, mxD) + 1;
    }
    void expand(vv& R, int lev = 1) {
        S[lev] += S[lev - 1] - old[lev];
        old[lev] = S[lev - 1];
        while (int(R.size())) {
            if (int(q.size()) + R.back().d <= int(qmax.size()))
                return;
            q.push_back(R.back().i);
            vv T;
            for(auto& v : R) if (e[R.back().i][v.i]) T.push_back({v.i});
            if (int(T.size())) {
                if (S[lev]++ / ++pk < limit) init(T);
                int j = 0, mxk = 1, mnk = max(int(qmax.size()) - int(q.size()), 1, 1);
                C[1].clear(), C[2].clear();
                for(auto& v : T) {
                    int k = 1;
                    auto f = [&](int i) { return e[v.i][i]; };
                    while (any_of(C[k].begin(), C[k].end(), f)) k++;
                    if (k > mxk) mxk = k, C[mxk + 1].clear();
                    if (k < mnk) T[j++] .i = v.i;
                    C[k].push_back(v.i);
                }
                if (j > 0) T[j - 1].d = 0;
                for(int k = mnk; k <= mxk; ++k) for(int i : C[k])
                    T[j].i = i, T[j++].d = k;
                expand(T, lev + 1);
            } else if (int(q.size()) > int(qmax.size())) qmax = q;
            q.pop_back(), R.pop_back();
        }
    }
}

vector<int> maxClique() { init(V), expand(V); return qmax; }
Maxclique(vb conn) : e(conn), C(int(e.size()+1), S(int(C.size()), old(S) {
```

```
    for(int i = 0; i < int(e.size()); ++i) V.push_back({i});
}
};

chromatic-number.h
Description: Compute the chromatic number of a graph. Minimum number of colors needed to paint the graph in a way s.t. if two vertices share an edge, they must have distinct colors.
Time:  $\mathcal{O}\left(N2^N\right)$ 
ea44b7, 33 lines

template<class T> int min_colors(int N, const T& gr) {
    vector<int> adj(N);
    for (int a = 0; a < N; ++a) {
        for (int b = a + 1; b < N; ++b) {
            if (!gr[a][b]) continue;
            adj[a] |= (1 << b);
            adj[b] |= (1 << a);
        }
    }
    static vector<unsigned> dp(1 << N), buf(1 << N), w(1 << N);
    for (int mask = 0; mask < (1 << N); ++mask) {
        bool ok = true;
        for (int i = 0; i < N; ++i) if (mask & 1 << i) {
            if (adj[i] & mask) ok = false;
        }
        if (ok) dp[mask]++;
        buf[mask] = 1;
        w[mask] = __builtin_popcount(mask) % 2 == N % 2 ? 1 : -1;
    }
    for (int i = 0; i < N; ++i) {
        for (int mask = 0; mask < (1 << N); ++mask) if (!(mask & 1 << i)) {
            dp[mask^(1 << i)] += dp[mask];
        }
    }
    for (int colors = 1; colors <= N; ++colors) {
        unsigned S = 0;
        for (int mask = 0; mask < (1 << N); ++mask) {
            S += (buf[mask] * dp[mask]) * w[mask];
        }
        if (S) return colors;
    }
    assert(false);
}
```

cycle-counting.cpp

Description: Counts 3 and 4 cycles

132e62, 49 lines

```
#define P 1000000007
#define N 110000
int n, m;
vector<int> go[N], lk[N];
int w[N], deg[N], pos[N], id[N];
int circle3(){
    int ans=0;
    for (int i = 1; i <= n; i++) w[i] = 0;
    for (int x = 1; x <= n; x++) {
        for(int y : lk[x]) w[y] = 1;
        for(int y:lk[x]) for(int z:lk[y]) if(w[z]){
            ans=(ans+go[x].size()+go[y].size()+go[z].size()-6)%P;
        }
        for(int y:lk[x])w[y]=0;
    }
    return ans;
}
int circle4(){
    for (int i = 1; i <= n; i++) w[i]=0;
    int ans=0;
```



```

for (int x = 1; x <= n; x++) {
    for(int y:go[x])for(int z:lk[y])if(pos[z]>pos[x]){
        ans=(ans+w[z])%P;
        w[z]++;
    }
    for(int y:go[x])for(int z:lk[y])w[z]=0;
}
return ans;
}
inline bool cmp(const int &x,const int &y){
    return deg[x]<deg[y];
}
void init() {
    scanf("%d%d", &n, &m);
    for (int i = 1; i <= n; i++)
        deg[i] = 0, go[i].clear(), lk[i].clear();
    while (m--) {
        int a,b;
        scanf("%d%d",&a,&b);
        deg[a]++;deg[b]++;
        go[a].push_back(b);go[b].push_back(a);
    }
    for (int i = 1; i <= n; i++) id[i] = i;
    sort(id+1,id+1+n,cmp);
    for (int i = 1; i <= n; i++) pos[id[i]]=i;
    for (int x = 1; x <= n; x++)
        for(int y:go[x])
            if(pos[y]>pos[x])lk[x].push_back(y);
}

```

edge-coloring.h

Description: Given a simple, undirected graph with max degree D , computes a $(D + 1)$ -coloring of the edges such that no neighboring edges share a color. (D -coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)

Time: $\mathcal{O}(NM)$

52f5bb, 32 lines

```

vector<int> MisraGries(int N, vector<pair<int, int>> eds) {
    const int M = int(eds.size());
    vector<int> cc(N + 1), ret(M), fan(N), free(N), loc;
    for (auto e : eds) ++cc[e.first], ++cc[e.second];
    int u, v, ncols = *max_element(cc.begin(), cc.end()) + 1;
    vector<vector<int>> adj(N, vi(ncols, -1));
    for (auto e : eds) {
        tie(u, v) = e;
        fan[0] = v;
        loc.assign(ncols, 0);
        int at = u, end = u, d, c = free[u], ind = 0, i = 0;
        while (d = free[v], !loc[d] && (v = adj[u][d]) != -1)
            loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
        cc[loc[d]] = c;
        for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at][cd])
            swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
        while (adj[fan[i]][d] != -1) {
            int left = fan[i], right = fan[++i], e = cc[i];
            adj[u][e] = left;
            adj[left][e] = u;
            adj[right][e] = -1;
            free[right] = e;
        }
        adj[u][d] = fan[i];
        adj[fan[i]][d] = u;
        for (int y : {fan[0], u, end})
            for (int& z = free[y] = 0; adj[y][z] != -1; z++);
    }
    for (int i = 0; i < M; ++i)
        for (tie(u, v) = eds[i]; adj[u][ret[i]] != v;) ++ret[i];
    return ret;
}

```

7.6 Trees

lca-binary-lifting.h

Description: Solve lowest common ancestor queries using binary jumps. Can also find the distance between two nodes.

Time: $\mathcal{O}(N \log N + Q \log N)$

b4e1b3, 53 lines

```

struct lca_t {
    int logn{0}, preorderpos{0};
    vector<int> invpreorder, height;
    vector<vector<int>> jump, edges;
    lca_t(int n, vector<vector<int>>& adj) :
        edges(adj), height(n), invpreorder(n) {
        while((l<<(logn+1)) <= n) ++logn;
        jump.assign(n+1, vector<int>(logn+1, 0));
        dfs(0, -1, 0);
    }
    void dfs(int v, int p, int h) {
        invpreorder[v] = preorderpos++;
        height[v] = h;
        jump[v][0] = p < 0 ? v : p;
        for (int l = 1; l <= logn; ++l)
            jump[v][l] = jump[jump[v][l-1]][l-1];
        for (int u : edges[v]) {
            if (u == p) continue;
            dfs(u, v, h + 1);
        }
    }
    int climb(int v, int dist) {
        for (int l = 0; l <= logn; ++l)
            if (dist&(1<<l)) v = jump[v][l];
        return v;
    }
    int query(int a, int b) {
        if (height[a] < height[b]) swap(a, b);
        a = climb(a, height[a] - height[b]);
        if (a == b) return a;
        for (int l = logn; l >= 0; --l)
            if (jump[a][l] != jump[b][l])
                a = jump[a][l], b = jump[b][l];
        return jump[a][0];
    }
    T dist(int a, int b) {
        return height[a] + height[b] - 2 * height[query(a,b)];
    }
    bool is_parent(int p, int v) {
        if (height[p] > height[v]) return false;
        return p == climb(v, height[v] - height[p]);
    }
    bool on_path(int x, int a, int b) {
        int v = query(a, b);
        return is_parent(v, x) && (is_parent(x, a) || is_parent(x, b));
    }
    int get_kth_on_path(int a, int b, int k) {
        int v = query(a, b);
        int x = height[a] - height[v], y = height[b] - height[v];
        if (k < x) return climb(a, k);
        else return climb(b, x + y - k);
    }
}

```

lca-euler-tour.h

Description: Data structure for computing lowest common ancestors and build Euler Tour in a tree. Edges should be an adjacency list of the tree, either directed or undirected.

Time: $\mathcal{O}(N \log N + Q + Q \log)$

e1d792, 164 lines

```
struct lca_t { // compact way!
```

```

int T = 0;
vector<int> time, path, walk, depth;
rmq_t<int> rmq;
lca_t(vector<vector<int>> &edges) : time(int(edges.size()))
{
    depth(time), rmq((dfs(edges,0,-1), walk)) {}
    void dfs(vector<vector<int>> &edges, int v, int p) {
        time[v] = T++;
        for(int u : edges[v]) {
            if (u == p) continue;
            depth[u] = depth[v] + 1;
            path.push_back(v), walk.push_back(time[v]);
            dfs(edges, u, v);
        }
    }
    int lca(int a, int b) {
        if (a == b) return a;
        tie(a, b) = minmax(time[a], time[b]);
        return path[rmq.query(a, b - 1)];
    }
};

struct lca_t {
    int N;
    vector<vector<int>> adj;
    vector<int> parent, depth, sz;
    vector<int> euler_tour, timer;
    vector<int> tour_in, tour_out, postorder;
    vector<int> idx, rev_idx;
    vector<int> heavy_root;
    rmq_t<pair<int,int>> rmq;
    int next_idx = 0, rev_next_idx = 0;
    bool built = false;
    lca_t() : N(0) {}
    lca_t(vector<vector<int>>& _adj, int root = -1, bool
        build_rmq = true) :
        N(int(_adj.size())), adj(_adj), parent(N, -1), depth(N),
        sz(N), timer(N),
        tour_in(N), tour_out(N), postorder(N), idx(N),
        heavy_root(N),
        built(false) {
        if (0 <= root && root < N) pre_dfs(root, -1);

        euler_tour.reserve(2 * N);

        for (int i = 0; i < N; ++i)
            if (parent[i] == -1) {
                if (i != root) pre_dfs(i, -1);
                dfs(i, false);
                euler_tour.push_back(-1);
            }

        rev_idx = idx;
        reverse(rev_idx.begin(), rev_idx.end());
        assert(int(euler_tour.size()) == 2 * N);
        vector<pair<int, int>> euler_tour_depths;
        euler_tour_depths.reserve(euler_tour.size());

        int id = 0;
        for (int cur : euler_tour) {
            euler_tour_depths.push_back({cur == -1 ? cur :
                depth[cur], id++});
        }

        if (build_rmq) rmq = rmq_t<pair<int, int>>({
            euler_tour_depths);
        built = true;
    }
}

```



```

void pre_dfs(int cur, int par) {
    parent[cur] = par;
    depth[cur] = (par == -1 ? 0 : 1 + depth[par]);
    adj[cur].erase(remove(adj[cur].begin(), adj[cur].end(),
        par), adj[cur].end());
    sz[cur] = 1;
    for (int nxt : adj[cur]) {
        pre_dfs(nxt, cur);
        sz[cur] += sz[nxt];
    }
    if (!adj[cur].empty()) {
        auto w = max_element(adj[cur].begin(), adj[cur].end(),
            [&](int a, int b) { return sz[a] < sz[b]; });
        swap(*adj[cur].begin(), *w);
    }
}

void dfs(int cur, bool heavy) {
    heavy_root[cur] = heavy ? heavy_root[parent[cur]] : cur;
    timer[cur] = int(euler_tour.size());
    euler_tour.push_back(cur);
    idx[next_idx] = cur;
    tour_in[cur] = next_idx++;
    bool heavy_child = true;
    for (int next : adj[cur]) {
        dfs(next, heavy_child);
        euler_tour.push_back(cur);
        heavy_child = false;
    }
    tour_out[cur] = next_idx;
    postorder[cur] = rev_next_idx++;
}

pair<int, array<int, 2>> get_diameter() const {
    assert(built);
    pair<int, int> u_max = {-1, -1};
    pair<int, int> ux_max = {-1, -1};
    pair<int, array<int, 2>> uxv_max = {-1, {-1, -1}};
    for (int cur : euler_tour) {
        if (cur == -1) break;
        u_max = max(u_max, {depth[cur], cur});
        ux_max = max(ux_max, {u_max.first - 2 * depth[cur],
            u_max.second});
        uxv_max = max(uxv_max, {ux_max.first + depth[cur],
            {ux_max.second, cur}});
    }
    return uxv_max;
}

int query(int a, int b) const {
    if (a == b) return a;
    a = timer[a], b = timer[b];
    if (a > b) swap(a, b);
    return euler_tour[rmq.query(a, b).second];
}

bool is_ancestor(int a, int b) const {
    return tour_in[a] <= tour_in[b] && tour_in[b] <
        tour_out[a];
}

bool on_path(int x, int a, int b) const {
    return (is_ancestor(x, a) || is_ancestor(x, b)) &&
        is_ancestor(query(a, b), x);
}

```

```

int dist(int a, int b) const {
    return depth[a] + depth[b] - 2 * depth[query(a, b)];
}

int child_ancestor(int a, int b) const {
    assert(a != b); assert(is_ancestor(a, b));
    // Note: this depends on rmq-t breaking ties by latest
    index.
    int child = euler_tour[rmq.query(timer[a], timer[b]).
        second + 1];
    assert(parent[child] == a);
    assert(is_ancestor(child, b));
    return child;
}

int get_kth_ancestor(int a, int k) const {
    while (a >= 0) {
        int root = heavy_root[a];
        if (depth[root] <= depth[a] - k) return idx[tour_in
            [a] - k];
        k -= depth[a] - depth[root] + 1;
        a = parent[root];
    }
    return a;
}

int get_kth_node_on_path(int a, int b, int k) const {
    int lca = query(a, b);
    int x = depth[a] - depth[lca], y = depth[b] - depth[lca];
    assert(0 <= k && k <= x + y);
    if (k < x) return get_kth_ancestor(a, k);
    else return get_kth_ancestor(b, x + y - k);
}

int get_common_node(int a, int b, int c) const {
    // Return the deepest node among lca(a, b), lca(b, c),
    and lca(c, a).
    int x = query(a, b), y = query(b, c), z = query(c, a);
    x = depth[y] > depth[x] ? y : x;
    x = depth[z] > depth[x] ? z : x;
    return x;
}
}

```

compress-tree.h

Description: Given a rooted tree and a subset S of nodes, compute the minimal subtree that contains all the nodes by adding all (at most $|S| - 1$) pairwise LCA's and compressing edges. Returns a list of (par, orig_index) representing a tree rooted at 0. The root points to itself.

Time: $\mathcal{O}(|S| \log |S|)$

```

"LCA.h"
ae0a91, 20 lines
vector<pair<int, int>> compressTree(lca_t &lca, const vector<int>
    >& subset) {
    static vector<int> rev; rev.resize(lca.time.size());
    vector<int> li = subset, &T = lca.time;
    auto cmp = [&](int a, int b) { return T[a] < T[b]; };
    sort(li.begin(), li.end(), cmp);
    int m = li.size() - 1;
    for (int i = 0; i < m; ++i) {
        int a = li[i], b = li[i + 1];
        li.push_back(lca.lca(a, b));
    }
    sort(li.begin(), li.end(), cmp);
    li.erase(unique(li.begin(), li.end(), li.end());
    for (int i = 0; i < int(li.size()); ++i) rev[li[i]] = i;
    vector<pair<int, int>> ret = {{0, li[0]}};
    for (int i = 0; i < li.size() - 1; ++i) {
        int a = li[i], b = li[i + 1];

```

```

        ret.emplace_back(rev[lca.lca(a, b)], b);
    }
    return ret;
}

```

heavylight.h

Description: Decomposes a tree into vertex disjoint heavy paths and light edges such that the path from any leaf to the root contains at most $\log(n)$ light edges. Code supports commutative segtree modifications/queries on paths, edges and subtrees. Takes as input the full adjacency list with pairs of (vertex, value). USE_EDGES being true means that values are stored in the edges and are initialized with the adjacency list, otherwise values are stored in the nodes and are initialized to the T defaults value.

Time: $\mathcal{O}((\log N)^2)$

"../data-structures/LazySegmentTree.h" 89a6f1, 94 lines

```

using G = vector<vector<pair<int, int>>>;
template<typename T, bool USE_EDGES> struct heavylight_t {
    int t, n;
    vector<int> timer, preorder;
    vector<int> chain, par;
    vector<int> dep, sz;
    vector<T> val;
    heavylight_t() {}
    heavylight_t(G &g, int r = 0) : t(0), n(g.size()), par(n, -1),
        chain(n, -1),
    dep(n), timer(n), sz(n), val(n), preorder(n) { par[r] =
        chain[r] = r;
        dfs_sz(g, r), dfs_hld(g, r);
    }
    int dfs_sz(G &g, int u) {
        int subtree = 1;
        for (auto &e : g[u]) {
            int v = e.first;
            if (par[v] != -1) continue;
            par[v] = u; dep[v] = dep[u] + 1;
            subtree += dfs_sz(g, v);
            if (sz[v] > sz[g[u][0].first]) swap(g[u][0], e);
        }
        return sz[u] = subtree;
    }
    void dfs_hld(G &g, int u) {
        preorder[timer[u] = t++] = u;
        for (auto &e : g[u]) {
            int v = e.first;
            if (chain[v] != -1) continue;
            chain[v] = (e == g[u][0] ? chain[u] : v);
            dfs_hld(g, v);
            if (USE_EDGES) val[timer[v]] = e.second;
        }
    }
    template<class F> void path(int u, int v, F op) {
        if (u == v) return op(timer[u], timer[u]);
        for (int e, p; chain[u] != chain[v]; u = p) {
            if (dep[chain[u]] < dep[chain[v]]) swap(u, v);
            u == (p = chain[u]) ? e = 0, p = par[u] : e = 1;
            op(timer[chain[u]] + e, timer[u]);
        }
        if (timer[u] > timer[v]) swap(u, v);
        op(timer[u] + USE_EDGES, timer[v]);
    }
};

template<typename T, bool USE_EDGES> struct hld_solver {
    heavylight_t<T, USE_EDGES> h;
    segtree_t<T, int> seg;
    hld_solver(const heavylight_t<T, USE_EDGES> &g) : h(g), seg(h
        .val) {}
    void updatePath(int u, int v, T value) {

```

```

    h.path(u, v, [&](int a,int b) { seg.update(a, b, value); })
        ;
}
T queryPath(int u, int v) {
    T ans = 0;
    h.path(u, v, [&](int a,int b) { ans = max(ans, seg.query(a,
        b)); });
    return ans;
}
void updateEdge(int u, int v, T value) {
    int pos = h.timer[h.dep[u] < h.dep[v] ? v : u];
    seg.update(pos, pos, value);
}
T querySubtree(int v) {
    return seg.query(h.timer[v] + USE_EDGES, h.timer[v] + h.sz[
        v] - 1);
}
void updateSubtree(int v, T value) {
    seg.update(h.timer[v] + USE_EDGES, h.timer[v] + h.sz[v] -
        1, value);
}
};

template<typename T, bool USE_EDGES> struct lca_t { // lca
    operations using hld
    heavy_light_t<T, USE_EDGES> h;
    lca_t(const heavy_light_t<T, USE_EDGES> &g) : h(g) {}
    int kth_ancestor(int u, int k) const {
        int kth = u;
        for(int p = h.chain[kth]; k && h.timer[kth]; kth = p, p = h
            .chain[kth]) {
            if (p == kth) p = h.par[kth];
            if (h.dep[kth] - h.dep[p] >= k) p = h.preorder[h.timer[
                kth]-k];
            k -= (h.dep[kth] - h.dep[p]);
        }
        return (k ? -1 : kth);
    }
    int lca(int u, int v) {
        if (u == v) return u;
        int x = h.timer[u];
        h.path(u, v, [&](int a,int b) { x = a - USE_EDGES; });
        return h.preorder[x];
    }
    int kth_on_path(int u, int v, int k) { //k 0-indexed
        int x = lca(u,v);
        if (k > h.dep[u] + h.dep[v] - 2 * h.dep[x]) return -1;
        if (h.dep[u] - h.dep[x] > k) return kth_ancestor(u, k);
        return kth_ancestor(v, h.dep[u] + h.dep[v] - 2 * h.dep[x] -
            k);
    }
};

```

tree-isomorphism.h

Time: $O(N \log(N))$

92e59f, 51 lines

```

map<vector<int>, int> delta;
struct tree_t {
    int n;
    pair<int,int> centroid;
    vector<vector<int>>> edges;
    vector<int> sz;
    tree_t(vector<vector<int>>& graph) :
        edges(graph), sz(edges.size()) {}
    int dfs_sz(int v, int p) {
        sz[v] = 1;
        for (int u : edges[v]) {
            if (u == p) continue;
            sz[v] += dfs_sz(u, v);
        }
    }
};

```

```

    }
    return sz[v];
}
int dfs(int tsz, int v, int p) {
    for (int u : edges[v]) {
        if (u == p) continue;
        if (2*sz[u] <= tsz) continue;
        return dfs(tsz, u, v);
    }
    return centroid.first = v;
}
pair<int,int> find_centroid(int v) {
    int tsz = dfs_sz(v, -1);
    centroid.second = dfs(tsz, v, -1);
    for (int u : edges[centroid.first]) {
        if (2*sz[u] == tsz)
            centroid.second = u;
    }
    return centroid;
}
int hash_it(int v, int p) {
    vector<int> offset;
    for (int u : edges[v]) {
        if (u == p) continue;
        offset.push_back(hash_it(u, v));
    }
    sort(offset.begin(), offset.end());
    if (!delta.count(offset))
        delta[offset] = int(delta.size());
    return delta[offset];
}
lint get_hash(int v = 0) {
    pair<int,int> cent = find_centroid(v);
    lint x = hash_it(cent.first, -1), y = hash_it(cent.second,
        -1);
    if (x > y) swap(x, y);
    return (x << 30) + y;
}
};

```

7.6.1 Sqrt Decomposition

HLD generally suffices. If not, here are some common strategies:

- Rebuild the tree after every \sqrt{N} queries.
- Consider vertices with $>$ or $< \sqrt{N}$ degree separately.
- For subtree updates, note that there are $O(\sqrt{N})$ distinct sizes among child subtrees of any vertex.

Block Tree: Use a DFS to split edges into contiguous groups of size \sqrt{N} to $2\sqrt{N}$.

Mo's Algorithm for Tree Paths: Maintain an array of vertices where each one appears twice, once when a DFS enters the vertex (st) and one when the DFS exists (en). For a tree path $u \leftrightarrow v$ such that $st[u] < st[v]$,

- If u is an ancestor of v , query $[st[u], st[v]]$.
- Otherwise, query $[en[u], st[v]]$ and consider $lca(u, v)$ separately.

7.7 Functional Graphs

functional-graph.h

Description: Called lumberjack technique, solve functional graphs problems for graphs, it's also pretty good for dp on trees. Consists in go cutting the leaves until there is no leaves, only cycles. For that we keep a processing queue of the leaves, note that during this processing time we go through all the childrens of v before reaching a vertex v , therefore we can compute some infos about the children, like subtree of a given vertex

1c72ef, 79 lines

```

template<int T> struct Lumberjack {
    int n, numcycle;
    vector<int> subtree, order, par, cycle;
    vector<int> parincycles, idxcycle, sz, st;
    vector<int> depth, deg, cycles[T];
    vector<bool> seen, incycle, leaf;
    vector<vector<int>>> graph;
    void init(vector<vector<int>>& _graph, vector<int>& _deg) {
        init(_graph.size());
        graph = _graph; deg = _deg;
    }
    void init(int N) {
        n = N;
        order.resize(0);
        subtree.assign(n, 0);
        seen.assign(n, false);
        sz = st = subtree;
        parincycles = par = cycle = sz;
        idxcycle = depth = deg = sz;
        incycle = leaf = seen;
        vector<int> adj; graph.assign(n, adj);
    }
    int find_par(int u) {
        for (int v : graph[u]) if (!seen[v])
            return v;
        return -1;
    }
    void find_cycle(int u) {
        int idx= ++numcycle, cur = 0, p = u;
        st[idx] = u;
        sz[idx] = 0;
        cycles[idx].clear();
        while (!seen[u]) {
            seen[u] = incycle[u] = true;
            par[u] = find_par(u);
            if (par[u] == -1) par[u] = p;
            parincycles[u] = u;
            cycle[u] = idx;
            idxcycle[u] = cur;
            cycles[idx].push_back(u);
            ++sz[idx];
            depth[u] = 0;
            ++subtree[u];
            u = par[u];
            ++cur;
        }
    }
    void bfs() {
        queue<int> q;
        for (int i = 0; i < n; ++i)
            if (deg[i] == 1) {
                seen[i] = leaf[i] = true;
                q.push(i);
            }
        while(!q.empty()) {
            int v = q.front(); q.pop();
            order.push_back(v);
            ++subtree[v];
            int curpar = find_par(v);
            deg[curpar]--;
        }
    }
};

```

```

    subtree[curpar] += subtree[v];
    if(deg[curpar] == 1){
        q.push(curpar);
        seen[curpar] = true;
    }
}
numcycle = 0;
for(int i = 0; i < n; ++i)
    if (!seen[i]) find_cycle(i);
for(int i = order.size()-1; i >= 0; --i){
    int v = order[i], curpar = par[v];
    parincycles[v] = parincycles[curpar];
    cycle[v] = cycle[curpar];
    incycle[v] = false;
    idxcycle[v] = -1;
    depth[v] = 1 + depth[curpar];
}
}
};

```

functional-digraph.h

Description: Called lumberjack technique, solve functional graphs problems for digraphs, it's also pretty good for dp on trees. Consists in go cutting the leaves until there is no leaves, only cycles. For that we keep a processing queue of the leaves, note that during this processing time we go through all the childrens of v before reaching a vertex v, therefore we can compute some infos about the children, like subtree of a given vertex

Usage: Lumberjack<10010> g; g.init(N); (Be careful with the size of cyles when declared locally!)

7211bc, 70 lines

```

template<int T> struct Lumberjack {
    int n, numcycle;
    vector<int> subtree, order, par, cycle;
    vector<int> parincycles, idxcycle, sz, st;
    vector<int> depth, indeg, cycles[T];
    vector<bool> seen, incycle, leaf;
    void init(vector<int>& _par, vector<int>& _indeg){
        init(_par.size());
        par = _par; indeg = _indeg;
    }
    void init(int N) {
        n = N;
        order.resize(0);
        subtree.assign(n, 0);
        seen.assign(n, false);
        sz = st = subtree;
        parincycles = par = cycle = sz;
        idxcycle = depth = indeg = sz;
        incycle = leaf = seen;
    }
    void find_cycle(int u){
        int idx= ++numcycle, cur = 0, p = u;
        st[idx] = u;
        sz[idx] = 0;
        cycles[idx].clear();
        while (!seen[u]) {
            seen[u] = incycle[u] = 1;
            parincycles[u] = u;
            cycle[u] = idx;
            idxcycle[u] = cur;
            cycles[idx].push_back(u);
            ++sz[idx];
            depth[u] = 0;
            ++subtree[u];
            u = par[u];
            ++cur;
        }
    }
    void bfs() {

```

```

queue<int> q;
for (int i = 0; i < n; ++i)
    if (!indeg[i]){
        seen[i] = leaf[i] = true;
        q.push(i);
    }
while(!q.empty()){
    int v = q.front(); q.pop();
    order.push_back(v);
    ++subtree[v];
    int curpar = par[v];
    indeg[curpar]--;
    subtree[curpar] += subtree[v];
    if(!indeg[curpar]){
        q.push(curpar);
        seen[curpar] = true;
    }
}
numcycle = 0;
for (int i = 0; i < n; ++i)
    if (!seen[i]) find_cycle(i);
for(int i = order.size()-1; i >= 0; --i){
    int v = order[i], curpar = par[v];
    parincycles[v] = parincycles[curpar];
    cycle[v] = cycle[curpar];
    incycle[v] = false;
    idxcycle[v] = -1;
    depth[v] = 1 + depth[curpar];
}
}
};

```

7.8 Other

erdos-gallai.h

Description: Check if an array of degrees can represent a graph

Time: if sorted $\mathcal{O}(n)$, otherwise $\mathcal{O}(n \log(n))$

56391b, 15 lines

```

bool EG(vector<int> deg) {
    sort(deg.begin(), deg.end(), greater<int>());
    vector<long long> dp(deg.size());
    int n = deg.size(), p = n-1;
    for(int i = 0; i < n; i++)
        dp[i] = deg[i] + (i > 0 ? dp[i-1] : 0);
    for(int k = 1; k <= n; k++) {
        while(p >= 0 && deg[p] < k) p--;
        long long sum;
        if (p >= k-1) sum = (p-k+1)*1ll*k + dp[n-1] - dp[p];
        else sum = dp[n-1] - dp[k-1];
        if (dp[k-1] > k*(k-1LL) + sum) return 0;
    }
    return dp[n-1] % 2 == 0;
}

```

directed-mst.h

Description: Edmonds' algorithm for finding the weight of the minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1.

Time: $\mathcal{O}(E \log V)$

"../data-structures/UnionFind.h"

dedbb2, 59 lines

```

struct Edge { int a, b; ll w; };
struct Node {
    Edge key;
    Node *l, *r;
    ll delta;
    void prop() {
        key.w += delta;
        if (l) l->delta += delta;
        if (r) r->delta += delta;
    }
}

```

```

    delta = 0;
}
Edge top() { prop(); return key; }
};
Node *merge(Node *a, Node *b) {
    if (!a || !b) return a ? b;
    a->prop(), b->prop();
    if (a->key.w > b->key.w) swap(a, b);
    swap(a->l, (a->r = merge(b, a->r)));
    return a;
}
void pop(Node& a) { a->prop(); a = merge(a->l, a->r); }

pair<ll, vector<int>> dmst(int n, int r, vector<Edge>& g) {
    RollbackUF uf(n);
    vector<Node> heap(n);
    for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node{e});
    ll res = 0;
    vector<int> seen(n, -1), path(n), par(n);
    seen[r] = r;
    vector<Edge> Q(n), in(n, {-1,-1}), comp;
    deque<tuple<int, int, vector<Edge>>> cycs;
    for(int s = 0; s < n; ++s) {
        int u = s, qi = 0, w;
        while (seen[u] < 0) {
            if (!heap[u]) return {-1, {}};
            Edge e = heap[u]->top();
            heap[u]->delta -= e.w, pop(heap[u]);
            Q[qi] = e, path[qi++] = u, seen[u] = s;
            res += e.w, u = uf.find(e.a);
            if (seen[u] == s) {
                Node* cyc = 0;
                int end = qi, time = uf.time();
                do cyc = merge(cyc, heap[w = path[--qi]]);
                while (uf.unite(u, w));
                u = uf.find(u), heap[u] = cyc, seen[u] = -1;
                cycs.push_front({u, time, {Q[qi], &Q[end]}});
            }
        }
        for(int i = 0; i < qi; ++i) in[uf.find(Q[i].b)] = Q[i];
    }
    for (auto& [u,t,comp] : cycs) { // restore sol (optional)
        uf.rollback(t);
        Edge inEdge = in[u];
        for (auto& e : comp) in[uf.find(e.b)] = e;
        in[uf.find(inEdge.b)] = inEdge;
    }
    for(int i = 0; i < n; ++i) par[i] = in[i].a;
    return {res, par};
}

```

7.9 Theorems

7.9.1 Landau

There are a tournament with outdegree $d_1 \leq d_2 \leq \dots \leq d_n$ iff:

$$\bullet d_1 + d_2 + \dots + d_n = \binom{n}{2}$$

$$\bullet d_1 + d_2 + \dots + d_k \geq \binom{k}{2} \quad \forall 1 \leq k \leq n.$$

In order to build, lets make 1 point to $2, 3, \dots, d_1 + 1$ and we follow recursively

7.9.2 Euler’s theorem

Let V , A and F be the number of vertices, edges and faces of connected planar graph, $V - A + F = 2$

7.9.3 Eulerian Cycles

The number of Eulerian cycles in a *directed* graph G is:

$$t_w(G) \prod_{v \in G} (\deg v - 1)!,$$

where $t_w(G)$ is the number of arborescences (“directed spanning” tree) rooted at w : $t_w(G) = \det(q_{ij})_{i,j \neq w}$, with $q_{ij} = [i = j] \text{indeg}(i) - \#(i, j) \in E$

7.9.4 Dilworth’s theorem

For any partially ordered set, the sizes of the max antichain and of the min chain decomposition are equal. Equivalent to König’s theorem on the bipartite graph (U, V, E) where $U = V = S$ and (u, v) is an edge when $u < v$. Those vertices outside the min vertex cover in both U and V form a max antichain

7.9.5 König-Egervary theorem

For Bipartite Graphs, the number of edges in the maximum matching is greater than or equal the number of vertices in the minimum cover

Maximum Weight Closure

Given a vertex-weighted directed graph G . Turn the graph into a flow network, adding weight ∞ to each edge. Add vertices S, T . For each vertex v of weight w , add edge (S, v, w) if $w \geq 0$, or edge $(v, T, -w)$ if $w < 0$. Sum of positive weights minus minimum $S - T$ cut is the answer. Vertices reachable from S are in the closure. The maximum-weight closure is the same as the complement of the minimum-weight closure on the graph with edges reversed.

7.9.6 Maximum Weighted Independent Set in a Bipartite Graph

This is the same as the minimum weighted vertex cover. Solve this by constructing a flow network with edges $(S, u, w(u))$ for $u \in L$, $(v, T, w(v))$ for $v \in R$ and (u, v, ∞) for $(u, v) \in E$. The minimum S, T -cut is the answer. Vertices adjacent to a cut edge are in the vertex cover.

7.9.7 Tutte-Berge formula

The theorem states that the size of a maximum matching of a graph $G = (V, E)$ equals $\frac{1}{2} \min_{U \subseteq V} (|U| - \text{odd}(G - U) + |V|)$, where $\text{odd}(H)$ counts how many of the connected components of the graph H have an odd number of vertices.

7.9.8 Tutte’s theorem

A graph $G = (V, A)$ has a perfect matching iff for all subset U of V , the induced subgraph by $V \setminus U$ has at most $|U|$ connected components with odd number of vertices.

7.9.9 Number of Spanning Trees

Define Laplacian Matrix as $L = D - A$, D being a Diagonal Matrix with $D_{i,i} = \text{deg}(i)$ and A an Adjacency Matrix. Create an $N \times N$ Laplacian matrix `mat`, and for each edge $a \rightarrow b \in G$, do `mat[a][b]--`, `mat[b][b]++` (and `mat[b][a]--`, `mat[a][a]++` if G is undirected). Remove the i th row and column and take the determinant; this yields the number of directed spanning trees rooted at i (if G is undirected, remove any row/column).

7.9.10 Tutte Matrix

- A graph has a perfect matching iff the *Tutte* matrix has a non-zero determinant.
- The rank of the *Tutte* matrix is equal to twice the size of the maximum matching. The maximum cost matching can be found by polynomial interpolation.

7.9.11 Menger’s theorem

Vertices: A graph is k -connected iff all pairwise vertices are connected to at least k internally disjoint paths.

Edges: A graph is called k -edge-connected if the removal of at least k edges of the graph keeps it connected. A graph is k -edge-connected iff for all pairwise vertices u and v , exist k paths which link u to v without sharing an edge.

Geometry (8)

8.1 Geometric primitives

Point.h

Description: Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)

```
template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
    typedef Point P;
    T x, y;
    explicit Point(T x=0, T y=0) : x(x), y(y) {}
    bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
    bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
    P operator+(P p) const { return P(x+p.x, y+p.y); }
    P operator-(P p) const { return P(x-p.x, y-p.y); }
    P operator*(T d) const { return P(x*d, y*d); }
    P operator/(T d) const { return P(x/d, y/d); }
    T dot(P p) const { return x*p.x + y*p.y; }
    T cross(P p) const { return x*p.y - y*p.x; }
    T cross(P a, P b) const { return (a-*this).cross(b-*this); }
    T dist2() const { return x*x + y*y; }
    double dist() const { return sqrt((double)dist2()); }
    // angle to x-axis in interval [-pi, pi]
    double angle() const { return atan2(y, x); }
    P unit() const { return *this/dist(); } // makes dist()==1
```

```
P perp() const { return P(-y, x); } // rotates +90 degrees
P normal() const { return perp().unit(); }
// returns point rotated 'a' radians ccw around the origin
P rotate(double a) const {
    return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
};
using P = Point<double>;
```

Complex.h

Description: Example of geometry using complex numbers. Just to be used as reference. std::complex has issues with integral data types, be careful, you can't use polar or abs.


```
145247, 63 lines
const double E = 1e-9;
typedef double T;
using P = complex<T>;
#define x real()
#define y imag()
// example of how to represent a line using complex numbers
struct line {
    P p, v;
    line(P a, P b) {
        p = a;
        v = b - a;
    }
};
P dir(T angle) { return polar((T)1, angle); }
P unit(P p) { return p/abs(p); }
P translate(P v, P p) {return p + v;}
//rotate point around origin by a
P rotate(P p, T a) { return p * polar(1.0, a); }
//around pivot
P rotate(P v, T a, P pivot) { (a-pivot) * polar(1.0, a) + pivot
; }
T dot(P v, P w) { return (conj(v)*w).x; }
T cross(P v, P w) { return (conj(v)*w).y; }
T cross(P A, P B, P C) { return cross(B - A, C - A); }
P proj(P a, P v) { return v * dot(a, v) / dot(v, v); }
P closest(P p, line l) { return l.p + proj(p - l.p, l.v); }
double dist(P p, line l) { return fabs(p - closest(p, l)); }
P reflect(P p, P v, P w) {
    P z = p - v; P q = w - v;
    return conj(z/q) * q + v;
}
P intersection(line a, line b) { // undefined if parallel
    T d1 = cross(b.p - a.p, a.v - a.p);
    T d2 = cross(b.v - a.p, a.v - a.p);
    return (d1 * b.v - d2 * b.p)/(d1 - d2);
}
vector<P> convex_hull(vector<P> points) {
    if (points.size() <= 1) return points;
    sort(points.begin(), points.end(), [](P a, P b) {
        return real(a)==real(b) ? imag(a)<imag(b) : real(a)<real(b)
; });
    vector<P> hull(points.size()+1);
    int s = 0, k = 0;
    for (int it = 2; it--; s = --k, reverse(points.begin(),
points.end()))
        for (P p : points) {
            while(k >= s+2 && cross(hull[k-2], hull[k-1], p) <=
0) k--;
            hull[k++] = p;
        }
    return {hull.begin(), hull.begin() + k - (k == 2 && hull[0]
== hull[1])};
}
P p(4, 3);
// get the absolute value and angle in [-pi, pi]
cout << abs(p) << ' ' << arg(p) << '\n'; // 5 - 0.643501
```

```
// make a point in polar form
cout << polar(2.0, -M_PI/2) << '\n'; // (1.41421, -1.41421)
P v{1, 0};
cout << rotate(v, -M_PI/2) << '\n';
// Projection of v onto Riemann sphere and norm of p
cout << proj(v) << ' ' << norm(p) << '\n';
// Distance between p and v and the squared distance
cout << abs(v-p) << ' ' << norm(v-p) << '\n';
// Angle of elevation of line vp and its slope
cout << arg(p-v) * (180/M_PI) << ' ' << tan(arg(p-v)) << '\n';
// has trigonometric functions aswell (e.g. cos, sin, cosh,
    sinh, tan, tanh)
// and exp, pow, log
```


LineDistance.h

Description:
Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. $a=b$ gives nan. P is supposed to be `Point<T>` or `Point3D<T>` where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using `Point3D` will always give a non-negative distance.

`"Point-b"`



f6bf6b, 4 lines




```
template<class P>
double lineDist(const P& a, const P& b, const P& p) {
    return (double) (b-a).cross(p-a)/(b-a).dist();
}
```

SegmentDistance.h

Description:
Returns the shortest distance between point p and the line segment from point s to e.

Usage: Point<double> a, b(2,2), p(1,1);
bool onSegment = segDist(a,b,p) < 1e-10;

"Point.h" ac751a, 5 lines



```
double segDist(P& s, P& e, P& p) {
    if (s==e) return (p-s).dist();
    auto d = (e-s).dist2(), t = min(d,max(0,(p-s).dot(e-s)));
    return ((p-s)*d-(e-s)*t).dist() / d;
}
```


SegmentClosestPoint.h

Description: Returns the closest point to p in the segment from point s to e as well as the distance between them

```
pair<P, double> SegmentClosestPoint(P &s, P &e, P &p){
    P ds=p-s, de=p-e;
    if (e==s)
        return {s, ds.dist()};
    P u=(e-s).unit();
    P proj=u*ds.dot(u);
    if (onSegment(s, e, proj+s))
        return {proj+s, (ds-proj).dist()};
    double dist_s=ds.dist(), dist_e=de.dist();
    if (cmp(dist_s, dist_e)==1)
        return {s, dist_s};
    return {e, dist_e};
}
```

SegmentIntersection.h

Description:
 If a unique intersection point between the line segments going from s1 to e1 and from s2 to e2 exists then it is returned.
 If no intersection point exists an empty vector is returned.
 If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.



Usage: vector<P> inter = segInter(s1,e1,s2,e2);
 if (sz(inter)==1)
 cout << "segments intersect at " << inter[0] << endl;
 "Point.h", "OnSegment.h" f6be16, 13 lines

```
template<class P> vector<P> segInter(P a, P b, P c, P d) {
    auto oa = c.cross(d, a), ob = c.cross(d, b),
          oc = a.cross(b, c), od = a.cross(b, d);
    // Checks if intersection is single non-endpoint point.
    if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
        return {(a * ob - b * oa) / (ob - oa)};
    set<P> s;
    if (onSegment(c, d, a)) s.insert(a);
    if (onSegment(c, d, b)) s.insert(b);
    if (onSegment(a, b, c)) s.insert(c);
    if (onSegment(a, b, d)) s.insert(d);
    return {s.begin(), s.end()};
}
```



SegmentIntersectionQ.h

Description: Like segmentIntersection, but only returns true/false. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.


```

Point.h"                                1ff4ba, 16 lines
template<class P>
bool segmentIntersectionQ(P s1, P e1, P s2, P e2) {
    if (e1 == s1) {
        if (e2 == s2) return e1 == e2;
        swap(s1,s2); swap(e1,e2);
    }
    P v1 = e1-s1, v2 = e2-s2, d = s2-s1;
    auto a = v1.cross(v2), a1 = d.cross(v1), a2 = d.cross(v2);
    if (a == 0) { // parallel
        auto b1 = s1.dot(v1), c1 = e1.dot(v1),
            b2 = s2.dot(v1), c2 = e2.dot(v1);
        return !a1 && max(b1,min(b2,c2)) <= min(c1,max(b2,c2));
    }
    if (a < 0) { a = -a; a1 = -a1; a2 = -a2; }
    return (0 <= a1 && a1 <= a && 0 <= a2 && a2 <= a);
}

```


LineIntersection.h

Description:
If a unique intersection point of the lines going through s1,e1 and s2,e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.



Usage: auto res = lineInter(s1,e1,s2,e2);
if (res.first == 1)
cout << "intersection point at " << res.second << endl;
"Point.h" a01f81, 8 lines

```
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
    auto d = (e1 - s1).cross(e2 - s2);
    if (d == 0) // if parallel
        return {-1, P(0, 0)};
    return {-(s1.cross(e1, s2) == 0), P(0, 0)};
}
```



```

auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
return {1, (s1 * p + e1 * q) / d};
}

```

LineProjectionReflection.h

Description: Projects point p onto line ab. Set refl=true to get reflection of point p across line ab insted. The wrong point will be returned if P is an integer point and the desired point doesn't have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow.

"Point.h" b5562d, 5 lines

```

template<class P>
P lineProj(P a, P b, P p, bool refl=false) {
    P v = b - a;
    return p - v.perp()*(1+refl)*v.cross(p-a)/v.dist2();
}

```

SideOf.h

Description: Returns where *p* is as seen from *s* towards *e*. 1/0/-1 \leftrightarrow left/online/distance *eps* from the line. P is supposed to be Point<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.

Usage: bool left = sideOf(p1,p2,q)==1;
"Point.h" 3af81c, 9 lines

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }
```

```
template<class P>
int sideOf(const P& s, const P& e, const P& p, double eps) {
    auto a = (e-s).cross(p-s);
    double l = (e-s).dist()*eps;
    return (a > l) - (a < -l);
}
```

OnSegment.h

Description: Returns true iff p lies on the line segment from s to e. Use (segDist(s,e,p)<=epsilon) instead when using Point<double>.


"Point.h" c597e8, 3 lines

```
template<class P> bool onSegment(P s, P e, P p) {
    return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}
```


LinearTransformation.h

Description:

Apply the linear transformation (translation, rotation and scaling) which takes line p0-p1 to line q0-q1 to point r.



"Point.h" 03a306, 6 lines



```
typedef Point<double> P;
P linearTransformation(const P& p0, const P& p1,
    const P& q0, const P& q1, const P& r) {
    P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
    return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2();
}
```

Angle.h

Description: A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.

Usage: `vector<Angle> v = {w[0], w[0].t360() ...}; // sorted`
`int j = 0; rep(i,0,n) { while (v[j] < v[i].t180()) ++j; }`
`// sweeps j such that {j-i} represents the number of positively`
`oriented triangles with vertices at 0 and i`

0f0602, 34 lines

```
struct Angle {
    int x, y;
    int t;
```



```
Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
Angle operator-(Angle b) const { return {x-b.x, y-b.y, t}; }
int half() const {
    assert(x || y);
    return y < 0 || (y == 0 && x < 0);
}
Angle t90() const { return {-y, x, t + (half() && x >= 0)}; }
Angle t180() const { return {-x, -y, t + half()}; }
Angle t360() const { return {x, y, t + 1}; }
};

bool operator<(Angle a, Angle b) {
    // add a.dist2() and b.dist2() to also compare distances
    return make_tuple(a.t, a.half(), a.y * (1l)b.x) <
           make_tuple(b.t, b.half(), a.x * (1l)b.y);
}

// Given two points, this calculates the smallest angle between
// them, i.e., the angle that covers the defined line segment.
pair<Angle, Angle> segmentAngles(Angle a, Angle b) {
    if (b < a) swap(a, b);
    return (b < a.t180() ?
           make_pair(a, b) : make_pair(b, a.t360()));
}

Angle operator+(Angle a, Angle b) { // point a + vector b
    Angle r(a.x + b.x, a.y + b.y, a.t);
    if (a.t180() < r) r.t--;
    return r.t180() < a ? r.t360() : r;
}

Angle angleDiff(Angle a, Angle b) { // angle b - angle a
    int tu = b.t - a.t; a.t = b.t;
    return {a.x*b.x + a.y*b.y, a.x*b.y - a.y*b.x, tu - (b < a)};
}
```

AngleCmp.h
Description: Useful utilities for dealing with angles of rays from origin. OK for integers, only uses cross product. Doesn't support (0,0).

```
template <class P>
bool sameDir(P s, P t) {
    return s.cross(t) == 0 && s.dot(t) > 0;
}

// checks 180 <= s..t < 360?
template <class P>
bool isReflex(P s, P t) {
    auto c = s.cross(t);
    return c ? (c < 0) : (s.dot(t) < 0);
}

// operator < (s,t) for angles in [base,base+2pi)
template <class P>
bool angleCmp(P base, P s, P t) {
    int r = isReflex(base, s) - isReflex(base, t);
    return r ? (r < 0) : (0 < s.cross(t));
}

// is x in [s,t] taken ccw? 1/0/-1 for in/border/out
template <class P>
int angleBetween(P s, P t, P x) {
    if (sameDir(x, s) || sameDir(x, t)) return 0;
    return angleCmp(s, x, t) ? 1 : -1;
}
```

LinearSolver.h
Description: Solves the linear system (a * x + b * y = e) and (c * x + d * y = f) Returns tuple (1, Point(x, y)) if solution is unique, (0, Point(0,0)) if no solution and (-1, Point(0,0)) if infinite solutions. If using integer function type, this will give wrong answer if answer is not integer.

```
template<class T>
pair<int, Point<T>> solve_linear(T a, T b, T c, T d, T e, T f)
{
    Point<T> ret;
```

```
T det = a * d - b * c;
if (det == 0) {
    if (b * f == d * e && a * f == c * e) return {-1, Point
        <T>()};
    return {0, Point<T>()};
}

//In case solution needs to be integer, use something like
//the line below.
//assert((e * d - f * b) % det == 0 && (a * f - c * e) % det
//== 0);
return {1, Point<T>((e*d - f*b) / det, (a*f - c*e) / det)};
}
```

8.2 Circles
CircleIntersection.h
Description: Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

```
"Point.h" c64785, 10 lines

bool circleInter(P a,P b,double r1,double r2,pair<P, P>* out) {
    if (a == b) { assert(r1 != r2); return false; }
    P vec = b - a;
    double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
        p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
    if (sum*sum < d2 || dif*dif > d2) return false;
    P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
    *out = {mid + per, mid - per};
    return true;
}
```

CircleTangents.h
Description: Finds the external tangents of two circles, or internal if r2 is negated. Can return 0, 1, or 2 tangents – 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case .first = .second and the tangent line is perpendicular to the line between the centers). .first and .second give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set r2 to 0.

```
"Point.h" b0153d, 13 lines


template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
    P d = c2 - c1;
    double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
    if (d2 == 0 || h2 < 0) return {};
    vector<pair<P, P>> out;
    for (double sign : {-1, 1}) {
        P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
        out.push_back({c1 + v * r1, c2 + v * r2});
    }
    if (h2 == 0) out.pop_back();
    return out;
}
```

Circumcircle.h
Description: The circumcircle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.

```
"Point.h" c98102, 8 lines

double ccRadius(const P& A, const P& B, const P& C) {
    return (B-A).dist()*(C-B).dist()*(A-C).dist()/
        abs((B-A).cross(C-A))/2;
}

P ccCenter(const P& A, const P& B, const P& C) {
    P b = C-A, c = B-A;
    return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}
```



MinimumEnclosingCircle.h
Description: Computes the minimum circle that encloses a set of points. **Time:** expected $O(n)$

```
"circumcircle.h" 8ab87f, 19 lines

pair<P, double> mec(vector<P> ps) {
    shuffle(ps.begin(),ps.end(), mt19937(time(0)));
    P o = ps[0];
    double r = 0, EPS = 1 + 1e-8;
    for(int i = 0; i < ps.size(); ++i)
        if ((o - ps[i]).dist() > r * EPS) {
            o = ps[i], r = 0;
            for(int j = 0; j < i; ++j) if ((o - ps[j]).dist() > r *
                EPS) {
                    o = (ps[i] + ps[j]) / 2;
                    r = (o - ps[i]).dist();
                    for(int k = 0; k < j; ++k)
                        if ((o - ps[k]).dist() > r * EPS) {
                            o = ccCenter(ps[i], ps[j], ps[k]);
                            r = (o - ps[i]).dist();
                        }
                }
        }
    return {o, r};
}
```

CircleUnion.h
Description: Computes the circles union total area

```
fd65da, 86 lines

struct CircleUnion {
    static const int maxn = 1e5 + 5;
    const double PI = acos((double)-1.0);
    int n;
    double x[maxn], y[maxn], r[maxn];
    int covered[maxn];
    vector<pair<double, double>> seg, cover;
    double arc, pol;
    inline int sign(double x) {return x < -EPS ? -1 : x > EPS;}
    inline int sign(double x, double y) {return sign(x - y);}
    inline double sqr(const double x) {return x * x;}
    inline double dist(double x1, double y1, double x2, double
        y2) {return sqrt(sqr(x1 - x2) + sqr(y1 - y2));}
    inline double angle(double A, double B, double C) {
        double val = (sqr(A) + sqr(B) - sqr(C)) / (2 * A * B);
        if (val < -1) val = -1;
        if (val > +1) val = +1;
        return acos(val);
    }

    CircleUnion() {
        n = 0;
        seg.clear(), cover.clear();
        arc = pol = 0;
    }

    void init() {
        n = 0;
        seg.clear(), cover.clear();
        arc = pol = 0;
    }

    void add(double xx, double yy, double rr) {
        x[n] = xx, y[n] = yy, r[n] = rr, covered[n] = 0, n++;
    }

    void getarea(int i, double lef, double rig) {
        arc += 0.5 * r[i] * r[i] * (rig - lef - sin(rig - lef))
            ;
        double x1 = x[i] + r[i] * cos(lef), y1 = y[i] + r[i] *
            sin(lef);
        double x2 = x[i] + r[i] * cos(rig), y2 = y[i] + r[i] *
            sin(rig);
        pol += x1 * y2 - x2 * y1;
    }
}
```



```
double calc() {
    for (int i = 0; i < n; i++)
        for (int j = 0; j < i; j++)
            if (!sign(x[i] - x[j]) && !sign(y[i] - y[j]) &&
                !sign(r[i] - r[j])) {
                r[i] = 0.0;
                break;
            }
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            if (i != j && sign(r[j] - r[i]) >= 0 && sign(
                dist(x[i], y[i], x[j], y[j]) - (r[j] - r[i]
                )) <= 0) {
                covered[i] = 1;
                break;
            }
    for (int i = 0; i < n; i++) {
        if (sign(r[i]) && !covered[i]) {
            seg.clear();
            for (int j = 0; j < n; j++)
                if (i != j) {
                    double d = dist(x[i], y[i], x[j], y[j])
                        ;
                    if (sign(d - (r[j] + r[i])) >= 0 ||
                        sign(d - abs(r[j] - r[i])) <= 0)
                        continue;
                    double alpha = atan2(y[j] - y[i], x[j]
                        - x[i]);
                    double beta = angle(r[i], d, r[j]);
                    pair<double, double> tmp(alpha - beta,
                        alpha + beta);
                    if (sign(tmp.first) <= 0 && sign(tmp.
                        second) <= 0)
                        seg.push_back(pair<double, double>
                            >(2 * PI + tmp.first, 2 * PI +
                            tmp.second));
                    else if (sign(tmp.first) < 0) {
                        seg.push_back(pair<double, double>
                            >(2 * PI + tmp.first, 2 * PI));
                        ;
                        seg.push_back(pair<double, double>
                            >(0, tmp.second));
                    }
                    else seg.push_back(tmp);
                }
            sort(seg.begin(), seg.end());
            double rig = 0;
            for (vector<pair<double, double> >::iterator
                iter = seg.begin(); iter != seg.end();
                iter++) {
                if (sign(rig - iter->first) >= 0)
                    rig = max(rig, iter->second);
                else {
                    getarea(i, rig, iter->first);
                    rig = iter->second;
                }
            }
            if (!sign(rig)) arc += r[i] * r[i] * PI;
            else getarea(i, rig, 2 * PI);
        }
    }
    return pol / 2.0 + arc;
}
}
} ccu;
```

CircleLine.h

Description: Finds the intersection between a circle and a line. Returns a vector of either 0, 1, or 2 intersection points. P is intended to be Point<double>

```
"Point.h", "lineDistance.h", "LineProjectionReflection.h"
debf86, 8 lines
template<class P>
vector<P> circleLine(P c, double r, P a, P b) {
    double h2 = r*r - a.cross(b,c)*a.cross(b,c)/(b-a).dist2();
    if (h2 < 0) return {};
    P p = lineProj(a, b, c), h = (b-a).unit() * sqrt(h2);
    if (h2 == 0) return {p};
    return {p - h, p + h};
}
```

CircleCircleArea.h
Description: Calculates the area of the intersection of 2 circles

```
8bf2b6, 12 lines
template<class P>
double circleCircleArea(P c, double cr, P d, double dr) {
    if (cr < dr) swap(c, d), swap(cr, dr);
    auto A = [&](double r, double h) {
        return r*r*acos(h/r)-h*sqrt(r*r-h*h);
    };
    auto l = (c - d).dist(), a = (l*l + cr*cr - dr*dr)/(2*l);
    if (l - cr - dr >= 0) return 0; // far away
    if (l - cr + dr <= 0) return M_PI*dr*dr;
    if (l - cr >= 0) return A(cr, a) + A(dr, l-a);
    else return A(cr, a) + M_PI*dr*dr - A(dr, a-l);
}
```

CirclePolygonIntersection.h
Description: Returns the area of the intersection of a circle with a ccw polygon.
Time: $\mathcal{O}(n)$

```
"Point.h"
cf9deb, 18 lines
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
    auto tri = [&](P p, P q) {
        auto r2 = r * r / 2;
        P d = q - p;
        auto a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d.dist2();
        auto det = a * a - b;
        if (det <= 0) return arg(p, q) * r2;
        auto s = max(0., -a-sqrt(det)), t = min(1., -a+sqrt(det));
        if (t < 0 || 1 <= s) return arg(p, q) * r2;
        P u = p + d * s, v = p + d * t;
        return arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) * r2;
    };
    auto sum = 0.0;
    for (int i = 0; i < ps.size(); ++i)
        sum += tri(ps[i] - c, ps[(i + 1) % ps.size()] - c);
    return sum;
}
```

8.3 Polygons

InsidePolygon.h
Description: Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.
Usage: vector<P> v = {P{4,4}, P{1,2}, P{2,1}};
bool in = inPolygon(v, P{3, 3}, false);
Time: $\mathcal{O}(n)$

```
"Point.h", "OnSegment.h", "SegmentDistance.h"
f9442d, 12 lines
template<class P>
bool inPolygon(vector<P> &p, P a, bool strict = true) {
    int cnt = 0, n = p.size();
    for(int i = 0; i < n; ++i) {
        P q = p[(i + 1) % n];
```

```
        if (onSegment(p[i], q, a)) return !strict; // change to
            // -1 if u need to detect points in the boundary
            //or: if (segDist(p[i], q, a) <= eps) return !strict;
            cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i], q) > 0;
        }
    }
    return cnt;
}
```

PolygonArea.h
Description: Returns the area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!

```
"Point.h"
3794ee, 17 lines
template<class T>
T polygonArea(vector<Point<T>> &v) {
    T a = v.back().cross(v[0]);
    for(int i = 0; i < v.size()-1; ++i)
        a += v[i].cross(v[i+1]);
    return abs(a)/2.0;
}

Point<T> polygonCentroid(vector<Point<T>> &v) { // not tested
    Point<T> cent(0,0); T area = 0;
    for(int i = 0; i < v.size(); ++i) {
        int j = (i+1) % (v.size()); T a = cross(v[i], v[j]);
        cent += a * (v[i] + v[j]);
        area += a;
    }
    return cent/area/(T)3;
}
```


PolygonCenter.h
Description: Returns the center of mass for a polygon.
Time: $\mathcal{O}(n)$

```
"Point.h"
26a00f, 8 lines
P polygonCenter(const vector<P>& v) {
    P res(0, 0); double A = 0;
    for (int i = 0, j = v.size() - 1; i < v.size(); j = ++i) {
        res = res + (v[i] + v[j]) * v[j].cross(v[i]);
        A += v[j].cross(v[i]);
    }
    return res / A / 3;
}
```

PolygonCut.h
Description: Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.
Usage: vector<P> p = ...;
p = polygonCut(p, P(0,0), P(1,0));

```
"Point.h", "lineIntersection.h"
7df36f, 11 lines
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
    vector<P> res;
    for(int i = 0; i < poly.size(); ++i) {
        P cur = poly[i], prev = i ? poly[i-1] : poly.back();
        bool side = s.cross(e, cur) < 0;
        if (side != (s.cross(e, prev) < 0))
            res.push_back(lineInter(s, e, cur, prev).second);
        if (side) res.push_back(cur);
    }
    return res;
}
```

ConvexHull.h
Description: Returns a vector of indices of the convex hull in counter-clockwise order. Points on the edge of the hull between two other points are not considered part of the hull.



Time: $\mathcal{O}(n \log n)$

"Point.h"3612d7, 12 lines

```
vector<P> convexHull(vector<P> pts) {
    if (pts.size() <= 1) return pts;
    sort(pts.begin(), pts.end());
    vector<P> h(pts.size()+1);
    int s = 0, t = 0;
    for (int it = 2; it--; s = --t, reverse(pts.begin(), pts.end()
        ()))
        for (P p : pts) {
            while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0) t--;
            h[t++] = p;
        }
    return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};
}
```

HullDiameter.h

Description: Returns the two points with max distance on a convex hull (ccw, no duplicate/colinear points).

0e0c1f, 11 lines

```
array<P, 2> hullDiameter(vector<P> S) {
    int n = S.size(), j = n < 2 ? 0 : 1;
    pair<int, array<P, 2>> res({0, {S[0], S[0]}});
    for(int i = 0; i < j; ++i)
        for (; j = (j + 1) % n) {
            res = max(res, {{S[i] - S[j]}.dist2(), {S[i], S[j]}});
            if ((S[(j + 1) % n] - S[j]).cross(S[i + 1] - S[i]) >= 0)
                break;
        }
    return res.second;
}
```

PointInsideHull.h

Description: Determine whether a point t lies inside a convex hull (CCW order, with no colinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included.

Time: $\mathcal{O}(\log N)$

"Point.h", "sideOf.h", "OnSegment.h"7b8514, 12 lines

```
bool inHull(const vector<P> &l, P p, bool strict = true) {
    int a = 1, b = l.size() - 1, r = !strict;
    if (l.size() < 3) return r && onSegment(l[0], l.back(), p);
    if (sideOf(l[0], l[a], l[b]) > 0) swap(a, b);
    if (sideOf(l[0], l[a], p) >= r || sideOf(l[0], l[b], p) <= -r)
        return false;
    while (abs(a - b) > 1) {
        int c = (a + b) / 2;
        (sideOf(l[0], l[c], p) > 0 ? b : a) = c;
    }
    return sgn(l[a].cross(l[b], p)) < r;
}
```

PolyUnion.h

Description: Calculates the area of the union of n polygons (not necessarily convex). The points within each polygon must be given in CCW order. Guaranteed to be precise for integer coordinates up to $3e7$. If epsilons are needed, add them in sideOf as well as the definition of sgn.

Time: $\mathcal{O}(N^2)$, where N is the total number of points

"Point.h", "sideOf.h"a45bd4, 33 lines

```
double rat(P a, P b) { return sgn(b.x) ? a.x/b.x : a.y/b.y; }
double polyUnion(vector<vector<P>>& poly) {
    double ret = 0;
    for(int i = 0; i < poly.size(); ++i)
        for(int v = 0; v < poly[i].size(); ++v) {
            P A = poly[i][v], B = poly[i][(v + 1) % poly[i].size()];
            vector<pair<double, int>> segs = {{0, 0}, {1, 0}};
            for(int j = 0; j < poly.size(); ++j) if (i != j) {
                for(int u = 0; u < poly[j]; ++u) {
```

P C = poly[j][u], D = poly[j][(u + 1) % poly[j].size()];

int sc = sideOf(A, B, C), sd = sideOf(A, B, D);

if (sc != sd) {

double sa = C.cross(D, A), sb = C.cross(D, B);

if (min(sc, sd) < 0)

segs.emplace_back(sa / (sa - sb), sgn(sc - sd));

} else if (!sc && !sd && j<i && sgn((B-A).dot(D-C)) >0){

segs.emplace_back(rat(C - A, B - A), 1);

segs.emplace_back(rat(D - A, B - A), -1);

}

}

}

sort(segs.begin(), segs.end());

for(auto& s : segs) s.first = min(max(s.first, 0.0), 1.0);

double sum = 0;

int cnt = segs[0].second;

for(int j = 1; j < segs.size(); ++j) {

if (!cnt) sum += segs[j].first - segs[j - 1].first;

cnt += segs[j].second;

}

ret += A.cross(B) * sum;

}

return ret / 2;

LineHullIntersection.h

Description: Line-convex polygon intersection. The polygon must be ccw and have no colinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon: $\bullet(-1, -1)$ if no collision, $\bullet(i, -1)$ if touching the corner i , $\bullet(i, i)$ if along side $(i, i + 1)$, $\bullet(i, j)$ if crossing sides $(i, i + 1)$ and $(j, j + 1)$. In the last case, if a corner i is crossed, this is treated as happening on side $(i, i + 1)$. The points are returned in the same order as the line hits the polygon. extrVertex returns the point of a hull with the max projection onto a line.

Time: $\mathcal{O}(N + Q \log n)$

"Point.h"65ebb6, 39 lines

```
typedef array<P, 2> Line;
#define cmp(i,j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n) < 0
int extrVertex(vector<P>& poly, P dir) {
    int n = poly.size(), left = 0, right = n;
    if (extr(0)) return 0;
    while (left + 1 < right) {
        int m = (left + right) / 2;
        if (extr(m)) return m;
        int ls = cmp(left + 1, left), ms = cmp(m + 1, m);
        (ls < ms || (ls == ms && ls == cmp(left, m)) ? right : left
            ) = m;
    }
    return left;
}
```

#define cmpL(i) sgn(line[0].cross(poly[i], line[1]))

array<int, 2> lineHull(Line line, vector<P>& poly) {

int endA = extrVertex(poly, (line[0] - line[1]).perp());

int endB = extrVertex(poly, (line[1] - line[0]).perp());

if (cmpL(endA) < 0 || cmpL(endB) > 0)

return {-1, -1};

array<int, 2> res;

for(int i = 0; i < 2; ++i) {

int left = endB, right = endA, n = poly.size();

while ((left + 1) % n != right) {

int m = ((left + right + (left < right ? 0 : n)) / 2) % n

;

(cmpL(m) == cmpL(endB) ? left : right) = m;

}

res[i] = (left + !cmpL(right)) % n;

}

swap(endA, endB);

}

if (res[0] == res[1]) return {res[0], -1};

if (!cmpL(res[0]) && !cmpL(res[1]))

switch ((res[0] - res[1] + sz(poly) + 1) % poly.size()) {

case 0: return {res[0], res[0]};

case 2: return {res[1], res[1]};

}

return res;

}

HalfPlane.h

Description: Halfplane intersection area

"Point.h", "lineIntersection.h"e8e2d4, 59 lines

```
#define eps 1e-8
struct Line {
    P P1, P2;
    // Right hand side of the ray P1 -> P2
    explicit Line(P a = P(), P b = P()) : P1(a), P2(b) {};
    P intpo(Line y) {
        P r;
        assert(lineIntersection(P1, P2, y.P1, y.P2, r) == 1);
        return r;
    }
    P dir() { return P2 - P1; }
    bool contains(P x) { return (P2 - P1).cross(x - P1) < eps; }
    bool out(P x) { return !contains(x); }
};

template<class T>
bool mycmp(Point<T> a, Point<T> b) {
    // return atan2(a.y, a.x) < atan2(b.y, b.x);
    if (a.x * b.x < 0) return a.x < 0;
    if (abs(a.x) < eps) {
        if (abs(b.x) < eps) return a.y > 0 && b.y < 0;
        if (b.x < 0) return a.y > 0;
        if (b.x > 0) return true;
    }
    if (abs(b.x) < eps) {
        if (a.x < 0) return b.y < 0;
        if (a.x > 0) return false;
    }
    return a.cross(b) > 0;
}
```

bool cmp(Line a, Line b) { return mycmp(a.dir(), b.dir()); }

double Intersection_Area(vector <Line> b) {

sort(b.begin(), b.end(), cmp);

int n = b.size();

int q = 1, h = 0, i;

vector<Line> c(b.size() + 10);

for (i = 0; i < n; i++) {

while (q < h && b[i].out(c[h].intpo(c[h - 1]))) h--;

while (q < h && b[i].out(c[q].intpo(c[q + 1]))) q++;

c[+h] = b[i];

if (q < h && abs(c[h].dir().cross(c[h - 1].dir())) < eps) {

h--;

if (b[i].out(c[h].P1)) c[h] = b[i];

}

}

while (q < h - 1 && c[q].out(c[h].intpo(c[h - 1]))) h--;

while (q < h - 1 && c[h].out(c[q].intpo(c[q + 1]))) q++;

// Intersection is empty. This is sometimes different from

the case when

// the intersection area is 0.

if (h - q <= 1) return 0;

c[h + 1] = c[q];

vector <P> s;

for (i = q; i <= h; i++) s.push_back(c[i].intpo(c[i + 1]));

```

    s.push_back(s[0]);
    double ans = 0;
    for (i = 0; i < (int)s.size()-1; i++) ans += s[i].cross(s[i + 1]);
    return ans/2;
}

```

8.4 Misc. Point Set Problems

ClosestPair.h

Description: Finds the closest pair of points.

Time: $\mathcal{O}(n \log n)$

"Point.h" 32b14f, 16 lines

```

pair<P, P> closest(vector<P> v) {
    assert(v.size() > 1);
    set<P> S;
    sort(v.begin(), v.end(), [](P a, P b) { return a.y < b.y; });
    pair<int64_t, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
    int j = 0;
    for(P &p : v) {
        P d{1 + (int64_t)sqrt(ret.first), 0};
        while (v[j].y <= p.y - d.x) S.erase(v[j++]);
        auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
        for (; lo != hi; ++lo)
            ret = min(ret, {(*lo - p).dist2(), (*lo, p)});
        S.insert(p);
    }
    return ret.second;
}

```

KdTree.h

Description: KD-tree (2d, can be extended to 3d)

"Point.h" 915562, 63 lines

```

typedef long long T;
typedef Point<T> P;
const T INF = numeric_limits<T>::max();

```

```

bool on_x(const P& a, const P& b) { return a.x < b.x; }
bool on_y(const P& a, const P& b) { return a.y < b.y; }

```

```

struct Node {
    P pt; // if this is a leaf, the single point in it
    T x0 = INF, x1 = -INF, y0 = INF, y1 = -INF; // bounds
    Node *first = 0, *second = 0;

    T distance(const P& p) { // min squared distance to a point
        T x = (p.x < x0 ? x0 : p.x > x1 ? x1 : p.x);
        T y = (p.y < y0 ? y0 : p.y > y1 ? y1 : p.y);
        return (P(x,y) - p).dist2();
    }
}

```

```

Node(vector<P>&& vp) : pt(vp[0]) {
    for (P p : vp) {
        x0 = min(x0, p.x); x1 = max(x1, p.x);
        y0 = min(y0, p.y); y1 = max(y1, p.y);
    }
    if (vp.size() > 1) {
        // split on x if the box is wider than high (not best heuristic...)
        sort(vp.begin(), vp.end(), x1 - x0 >= y1 - y0 ? on_x : on_y);
        // divide by taking half the array for each child (not // best performance with many duplicates in the middle)
        int half = vp.size()/2;
        first = new Node({vp.begin(), vp.begin() + half});
        second = new Node({vp.begin() + half, vp.end()});
    }
}
};

```

```

struct KdTree {
    Node* root;
    KdTree(const vector<P>& vp) : root(new Node({vp.begin(), vp.end()})) {}
}

```

```

pair<T, P> search(Node *node, const P& p) {
    if (!node->first) {
        // uncomment if we should not find the point itself:
        // if (p == node->pt) return {INF, P()};
        return make_pair((p - node->pt).dist2(), node->pt);
    }
}

```

```

Node *f = node->first, *s = node->second;
T bfirst = f->distance(p), bsec = s->distance(p);
if (bfirst > bsec) swap(bsec, bfirst), swap(f, s);

```

```

// search closest side first, other side if needed
auto best = search(f, p);
if (bsec < best.first)
    best = min(best, search(s, p));
return best;
}

```

```

// find nearest point to a point, and its squared distance
// (requires an arbitrary operator< for Point)
pair<T, P> nearest(const P& p) {
    return search(root, p);
}
};

```

DelaunayTriangulation.h

Description: Computes the Delaunay triangulation of a set of points. Each circumcircle contains none of the input points. If any three points are colinear or any four are on the same circle, behavior is undefined.

Time: $\mathcal{O}(n^2)$

"Point.h", "3dHull.h" f6175a, 10 lines

```

template<class P, class F>
void delaunay(vector<P>& ps, F trifun) {
    if (ps.size() == 3) { int d = (ps[0].cross(ps[1], ps[2]) < 0) ;
        trifun(0,1+d,2-d); }
    vector<P3> p3;
    for(auto &p : ps) p3.emplace_back(p.x, p.y, p.dist2());
    if (ps.size() > 3) for(auto &t: hull3d(p3)) if ((p3[t.b]-p3[t.a]).
        cross(p3[t.c]-p3[t.a]).dot(P3(0,0,1)) < 0)
        trifun(t.a, t.c, t.b);
}

```

FastDelaunay.h

Description: Fast Delaunay triangulation. There must be no duplicate points. If all points are on a line, no triangles will be returned. Should work for doubles as well, though there may be precision issues in 'circ'. Returns triangles in order {t[0][0], t[0][1], t[0][2], t[1][0], ...}, all counter-clockwise.

Time: $\mathcal{O}(n \log n)$

"Point.h" a1f392, 89 lines

```

typedef Point<ll> P;
typedef struct Quad* Q;
typedef __int128_t ll1; // (can be ll if coords are < 2e4)
P arb(LLONG_MAX, LLONG_MAX); // not equal to any other point

```

```

struct Quad {
    bool mark; Q o, rot; P p;
    P F() { return r()->p; }
    Q r() { return rot->rot; }
    Q prev() { return rot->o->rot; }
    Q next() { return rot->r()->o->rot; }
}

```

```

};
bool circ(P p, P a, P b, P c) { // is p in the circumcircle?
    ll1 p2 = p.dist2(), A = a.dist2()-p2,
        B = b.dist2()-p2, C = c.dist2()-p2;
    return p.cross(a,b)*C + p.cross(b,c)*A + p.cross(c,a)*B > 0;
}
Q makeEdge(P orig, P dest) {
    Q q0 = new Quad{0,0,0,orig}, q1 = new Quad{0,0,0,arb},
    q2 = new Quad{0,0,0,dest}, q3 = new Quad{0,0,0,arb};
    q0->o = q0; q2->o = q2; // 0-0, 2-2
    q1->o = q3; q3->o = q1; // 1-3, 3-1
    q0->rot = q1; q1->rot = q2;
    q2->rot = q3; q3->rot = q0;
    return q0;
}
void splice(Q a, Q b) {
    swap(a->o->rot->o, b->o->rot->o); swap(a->o, b->o);
}
Q connect(Q a, Q b) {
    Q q = makeEdge(a->F(), b->p);
    splice(q, a->next());
    splice(q->r(), b);
    return q;
}
}

```

```

pair<Q,Q> rec(const vector<P>& s) {
    if (sz(s) <= 3) {
        Q a = makeEdge(s[0], s[1]), b = makeEdge(s[1], s.back());
        if (sz(s) == 2) return { a, a->r() };
        splice(a->r(), b);
        auto side = s[0].cross(s[1], s[2]);
        Q c = side ? connect(b, a) : 0;
        return {side < 0 ? c->r() : a, side < 0 ? c : b->r() };
    }
}

```

```

#define H(e) e->F(), e->p
#define valid(e) (e->F().cross(H(base)) > 0)
Q A, B, ra, rb;
int half = (sz(s) + 1) / 2;
tie(ra, A) = rec({s.begin(), s.begin() + half});
tie(B, rb) = rec({s.begin() + half, s.end()});
while ((B->p.cross(H(A)) < 0 && (A = A->next()) ||
        (A->p.cross(H(B)) > 0 && (B = B->r()->o)));
Q base = connect(B->r(), A);
if (A->p == ra->p) ra = base->r();
if (B->p == rb->p) rb = base;

```

```

#define DEL(e, init, dir) Q e = init->dir; if (valid(e)) \
    while (circ(e->dir->F(), H(base), e->F())) { \
        Q t = e->dir; \
        splice(e, e->prev()); \
        splice(e->r(), e->r()->prev()); \
        e = t; \
    }
for (;) {
    DEL(LC, base->r(), o); DEL(RC, base, prev());
    if (!valid(LC) && !valid(RC)) break;
    if (!valid(LC) || (valid(RC) && circ(H(RC), H(LC))))
        base = connect(RC, base->r());
    else
        base = connect(base->r(), LC->r());
}
return { ra, rb };
}

```

```

vector<P> triangulate(vector<P> pts) {
    sort(pts.begin(), pts.end()); assert(unique(pts.begin(), pts.end()) == pts.end());
    if (pts.size() < 2) return {};
}

```

```
Q e = rec(pts).first;
vector<Q> q = {e};
int qi = 0;
while (e->o->F().cross(e->F(), e->p) < 0) e = e->o;
#define ADD { Q c = e; do { c->mark = 1; pts.push_back(c->p); \
q.push_back(c->r()); c = c->next(); } while (c != e); }
ADD; pts.clear();
while (qi < sz(q)) if (!(e = q[qi++])>mark) ADD;
return pts;
}
```

RectangleUnionArea.h

Description: Sweep line algorithm that calculates area of union of rectangles in the form $[x1,x2] \times [y1,y2]$
Usage: Create vector with both x coordinates and y coordinates of each rectangle.//vector<pair<int,int>,pair<int,int>>> rectangles;// rectangles.push_back({{x1, x2}, {y1, y2}});// lint result = area(rectangles);

73f787, 59 lines

```
pair<int,int> operator+(const pair<int,int>& l, const pair<int,int>& r) {
    if (l.first != r.first) return min(l,r);
    return {l.first, l.second + r.second};
}
struct segtree_t { // stores min + # of mins
    int n;
    vector<int> lazy;
    vector<pair<int,int>> tree; // set n to a power of two
    segtree_t(int _n) : n(_n), tree(2*_n, {0,0}), lazy(2*_n, 0) {}
    void build() {
        for(int i = n-1; i >= 1; --i)
            tree[i] = tree[i<<1] + tree[i<<1|1]; }
    void push(int v, int lx, int rx) {
        tree[v].first += lazy[v];
        if (lx != rx) {
            lazy[v<<1] += lazy[v];
            lazy[v<<1|1] += lazy[v];
        }
        lazy[v] = 0;
    }
    void update(int a, int b, int delta) { update(1,0,n-1,a,b,delta); }
    void update(int v, int lx, int rx, int a, int b, int delta) {
        push(v, lx, rx);
        if (b < lx || rx < a) return;
        if (a <= lx && rx <= b) {
            lazy[v] = delta; push(v, lx, rx);
        }
        else {
            int m = lx + (rx - lx)/2;
            update(v<<1, lx, m, a, b, delta);
            update(v<<1|1, m+1, rx, a, b, delta);
            tree[v] = (tree[v<<1] + tree[v<<1|1]);
        }
    }
};
lint area(vector<pair<pair<int,int>,pair<int,int>>> v) { //
    area of union of rectangles
    const int n = 1<<18;
    segtree_t tree(n);
    vector<int> y; for(auto &t : v) y.push_back(t.second.first)
        , y.push_back(t.second.second);
    sort(y.begin(), y.end()); y.erase(unique(y.begin(), y.end())
        ,y.end());
    for(int i = 0; i < y.size()-1; ++i) tree.tree[n+i].second =
        y[i+1]-y[i]; // compress coordinates
    tree.build();
```

```
vector<array<int,4>> ev; // sweep line
for(auto &t : v) {
    t.second.first = lower_bound(y.begin(), y.end(),t.
        second.first)-begin(y);
    t.second.second = lower_bound(y.begin(), y.end(),t.
        second.second)-begin(y)-1;
    ev.push_back({t.first.first,1,t.second.first,t.second.
        second});
    ev.push_back({t.first.second,-1,t.second.first,t.second.
        .second});
}
sort(ev.begin(), ev.end());
lint ans = 0;
for(int i = 0; i < ev.size()-1; ++i) {
    const auto& t = ev[i];
    tree.update(t[2],t[3],t[1]);
    int len = y.back()-y.front()-tree.tree[1].second; //
        tree.mm[0].firstshould equal 0
    ans += (lint) (ev[i+1][0]-t[0])*len;
}
return ans;
}
```

8.5 3D

PolyhedronVolume.h

Description: Magic formula for the volume of a polyhedron. Faces should point outwards.

832599, 6 lines

```
template<class V, class L>
double signed_poly_volume(const V &p, const L &trilist) {
    double v = 0;
    for(auto &i : trilist) v += p[i.a].cross(p[i.b]).dot(p[i.c]);
    return v / 6;
}
```

Point3D.h

Description: Class to handle points in 3D space. T can be e.g. double or long long.

8058ae, 32 lines

```
template<class T> struct Point3D {
    typedef Point3D P;
    typedef const P& R;
    T x, y, z;
    explicit Point3D(T x=0, T y=0, T z=0) : x(x), y(y), z(z) {}
    bool operator<(R p) const {
        return tie(x, y, z) < tie(p.x, p.y, p.z); }
    bool operator==(R p) const {
        return tie(x, y, z) == tie(p.x, p.y, p.z); }
    P operator+(R p) const { return P(x+p.x, y+p.y, z+p.z); }
    P operator-(R p) const { return P(x-p.x, y-p.y, z-p.z); }
    P operator*(T d) const { return P(x*d, y*d, z*d); }
    P operator/(T d) const { return P(x/d, y/d, z/d); }
    T dot(R p) const { return x*p.x + y*p.y + z*p.z; }
    P cross(R p) const {
        return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x);
    }
    T dist2() const { return x*x + y*y + z*z; }
    double dist() const { return sqrt((double)dist2()); }
    //Azimuthal angle (longitude) to x-axis in interval [-pi, pi]
    double phi() const { return atan2(y, x); }
    //Zenith angle (latitude) to the z-axis in interval [0, pi]
    double theta() const { return atan2(sqrt(x*x+y*y),z); }
    P unit() const { return *this/(T)dist(); } //makes dist()==1
    //returns unit vector normal to *this and p
    P normal(P p) const { return cross(p).unit(); }
    //returns point rotated 'angle' radians ccw around axis
    P rotate(double angle, P axis) const {
        double s = sin(angle), c = cos(angle); P u = axis.unit();
        return u*dot(u)*(1-c) + (*this)*c - cross(u)*s;
```

```
};
};
```

3dHull.h

Description: Computes all faces of the 3-dimension hull of a point set. *No four points must be coplanar*, or else random results will be returned. All faces will point outwards.

Time: $\mathcal{O}(n^2)$

"Point3D.h" 3ed613, 48 lines

```
typedef Point3D<double> P3;

struct PR {
    void ins(int x) { (a == -1 ? a : b) = x; }
    void rem(int x) { (a == x ? a : b) = -1; }
    int cnt() { return (a != -1) + (b != -1); }
    int a, b;
};

struct F { P3 q; int a, b, c; };

vector<F> hull3d(const vector<P3>& A) {
    assert(A.size() >= 4);
    vector<vector<PR>> E(A.size(), vector<PR>(A.size(), {-1, -1})
        );
    #define E(x,y) E[f.x][f.y]
    vector<F> FS;
    auto mf = [&](int i, int j, int k, int l) {
        P3 q = (A[j] - A[i]).cross((A[k] - A[i]));
        if (q.dot(A[l]) > q.dot(A[i]))
            q = q * -1;
        F f(q, i, j, k);
        E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i);
        FS.push_back(f);
    };
    for(int i=0;i<4;i++) for(int j=i+1;j<4;j++) for(k=j+1;k<4;k
        ++){
        mf(i, j, k, 6 - i - j - k);
        for(int i=4; i<A.size();++i) {
            for(int j=0;j<FS.size();++j) {
                F f = FS[j];
                if (f.q.dot(A[i]) > f.q.dot(A[f.a])) {
                    E(a,b).rem(f.c);
                    E(a,c).rem(f.b);
                    E(b,c).rem(f.a);
                    swap(FS[j--], FS.back());
                    FS.pop_back();
                }
            }
            int nw = FS.size();
            for(int j=0;j<nw;j++) {
                F f = FS[j];
                #define C(a, b, c) if (E(a,b).cnt() != 2) mf(f.a, f.b, i, f.c);
                C(a, b, c); C(a, c, b); C(b, c, a);
            }
        }
        for(auto &it: FS) if ((A[it.b] - A[it.a]).cross(
            A[it.c] - A[it.a]).dot(it.q) <= 0) swap(it.c, it.b);
        return FS;
    };
};
```

SphericalDistance.h

Description: Returns the shortest distance on the sphere with radius r adius between the points with azimuthal angles (longitude) f_1 (ϕ_1) and f_2 (ϕ_2) from x axis and zenith angles (latitude) t_1 (θ_1) and t_2 (θ_2) from z axis. All angles measured in radians. The algorithm starts by converting the spherical coordinates to cartesian coordinates so if that is what you have you can use only the two last rows. $dx * radius$ is then the difference between the two points in the x direction and $d * radius$ is the total distance between the points.

```
double sphericalDistance(double f1, double t1,
    double f2, double t2, double radius) {
    double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
    double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
    double dz = cos(t2) - cos(t1);
    double d = sqrt(dx*dx + dy*dy + dz*dz);
    return radius*2*asin(d/2);
}
```

Strings (9)

KMP.cpp

Description: failure[x] computes the length of the longest prefix of s that ends at x , other than $s[0...x]$ itself (abacaba -> 0010123). Can be used to find all occurrences of a pattern in a text.

Time: $\mathcal{O}(n)$

```
template<typename T> struct kmp_t {
    vector<T> word;
    vector<int> failure;
    kmp_t(const vector<T> &_word): word(_word) {
        int n = word.size();
        failure.resize(n+1, 0);
        for (int s = 2; s <= n; ++s) {
            failure[s] = failure[s-1];
            while (failure[s] > 0 && word[failure[s]] != word[s-1])
                failure[s] = failure[failure[s]];
            if (word[failure[s]] == word[s-1]) failure[s] += 1;
        }
    }
    vector<int> matches_in(const vector<T> &text) {
        vector<int> result;
        int s = 0;
        for (int i = 0; i < (int)text.size(); ++i) {
            while (s > 0 && word[s] != text[i])
                s = failure[s];
            if (word[s] == text[i]) s += 1;
            if (s == (int)word.size()) {
                result.push_back(i-(int)word.size()+1);
                s = failure[s];
            }
        }
        return result;
    }
};
```

Extended-KMP.h

Description: extended KMP $S[i]$ stores the maximum common prefix between $s[i:]$ and t ; $T[i]$ stores the maximum common prefix between $t[i:]$ and t for $i > 0$;

```
int S[N], T[N];
void extKMP(const string &s, const string &t) {
    int m = t.size(), maT = 0, maS = 0;
    T[0] = 0;
    for (int i = 1; i < m; i++) {
        if (maT + T[maT] >= i)
            T[i] = min(T[i - maT], maT + T[maT] - i);
```

```
        else T[i] = 0;
        while (T[i] + i < m && t[T[i]] == t[T[i] + i])
            T[i]++;
        if (i + T[i] > maT + T[maT]) maT = i;
    }
    int n = s.size();
    for (int i = 0; i < n; i++) {
        if (maS + S[maS] >= i)
            S[i] = min(T[i - maS], maS + S[maS] - i);
        else S[i] = 0;
        while (S[i] < m && i + S[i] < n && t[S[i]] == s[S[i] + i])
            S[i]++;
        if (i + S[i] > maS + S[maS]) maS = i;
    }
}
```

Duval.h

Description: A string is called simple (or a Lyndon word), if it is strictly smaller than any of its own nontrivial suffixes.

Time: $\mathcal{O}(N)$

```
template <typename T>
pair<int, vector<string>> duval(int n, const T &s) {
    assert(n >= 1);
    // s += s //uncomment if you need to know the min cyclic string
    vector<string> factors; // strings here are simple and in non-inc order
    int i = 0, ans = 0;
    while (i < n) { // until n/2 to find min cyclic string
        ans = i;
        int j = i + 1, k = i;
        while (j < n + n && !(s[j % n] < s[k % n])) {
            if (s[k % n] < s[j % n]) k = i;
            else k++;
            j++;
        }
        while (i <= k) {
            factors.push_back(s.substr(i, j-k));
            i += j - k;
        }
    }
    return {ans, factors};
}
// returns 0-indexed position of the least cyclic shift
// min cyclic string will be s.substr(ans, n/2)
```

```
template <typename T>
pair<int, vector<string>> duval(const T &s) {
    return duval((int) s.size(), s);
}
```

Z.h

Description: $z[x]$ computes the length of the longest common prefix of $s[i:]$ and s , except $z[0] = 0$. (abacaba -> 0010301)

Time: $\mathcal{O}(n)$

```
vector<int> Z(string& S) {
    vector<int> z(S.size());
    int l = -1, r = -1;
    for(int i = 1; i < int(S.size()); ++i) {
        z[i] = i >= r ? 0 : min(r - i, z[i - l]);
        while (i + z[i] < int(S.size()) && S[i + z[i]] == S[z[i]
            ])
            z[i]++;
        if (i + z[i] > r) l = i, r = i + z[i];
    }
    return z;
}
```

```
vector<int> get_prefix(string a, string b) {
    string str = a + '@' + b;
    vector<int> k = z(str);
    return vector<int>(k.begin() + int(a.size()+1, k.end()));
}
```

Manacher.h

Description: For each position in a string, computes $p[0][i] =$ half length of longest even palindrome around pos i , $p[1][i] =$ longest odd (half rounded down).

Time: $\mathcal{O}(N)$

```
array<vector<int>, 2> manacher(const string &s) {
    int n = s.size();
    array<vector<int>, 2> p = {vector<int>(n+1), vector<int>(n)};
    for(int z = 0; z < 2; ++z) for (int i=0,l=0,r=0; i < n; i++)
        {
            int t = r-i+!z;
            if (i<r) p[z][i] = min(t, p[z][l+t]);
            int L = i-p[z][i], R = i+p[z][i]-!z;
            while (L>=1 && R+1<n && s[L-1] == s[R+1])
                p[z][i]++, L--, R++;
            if (R > r) l = L, r = R;
        }
    return p;
}
```

MinRotation.h

Description: Finds the lexicographically smallest rotation of a string.

Usage: rotate(v.begin(), v.begin()+min.rotation(v), v.end());

Time: $\mathcal{O}(N)$

```
int min_rotation(string s) {
    int a=0, N=s.size(); s += s;
    for(int b = 0; b < N; ++b) for(int i =0; i < N; ++i) {
        if (a+i == b || s[a+i] < s[b+i]) {b += max(0, i-1); break;}
        if (s[a+i] > s[b+i]) { a = b; break; }
    }
    return a;
}
```

Trie.h

Description: Trie implementation.

Time: $\mathcal{O}(N)$

```
struct Trie {
    struct node_t {
        unordered_map<char, node_t*> child;
        int cnt = 0, prefixCnt = 0;
    } *root = new node_t();
    void add(node_t *v, const string &s) {
        node_t *cur = v;
        for (char c : s) {
            if (cur->child.count(c)) cur = cur->child[c];
            else cur = cur->child[c] = new node_t();
            cur->prefixCnt++;
        }
        cur->cnt++;
    }
    int count(node_t *v, const string &s) {
        node_t *cur = v;
        for (char c : s) {
            if (cur->child.count(c)) cur = cur->child[c];
            else return 0;
        }
        return cur->cnt;
    }
    int prefixCount(node_t *v, const string &s) {
        node_t *cur = v;
        for (char c : s) {
```



```

        if (cur->child.count(c)) cur = cur->child[c];
        else return 0;
    }
    return cur->prefixCnt;
}
Trie() {}
void add(const string &s) { add(root, s); }
bool contains(const string &s) { return count(root, s) >= 1; }
bool hasPrefix(const string &s) { return prefixCount(root, s) >= 1; }
int count(const string &s) { return count(root, s); }
int prefixCount(const string &s) { return prefixCount(root, s); }
};

```

TrieXOR.h

Description: Query get the maximum possible xor between an integer X and every possible subarray. Just insert zero and for each prefix xor, insert it in the trie and query for max xor. The answer is the maximum possible value for each prefix query.

d872eb, 26 lines

```

template<int SZ, int MXBIT> struct Trie {
    int nxt[SZ][2], num = 0; // num is last node in trie
    unordered_map<int, int> nodes;
    // change 2 to 26 for lowercase letters
    Trie() { memset(nxt, 0, sizeof nxt); }
    void add(int x) {
        int cur = 0;
        for(int i = MXBIT-1; i >= 0; --i) {
            int t = (x >> i) & 1;
            if (!nxt[cur][t]) nxt[cur][t] = ++num;
            cur = nxt[cur][t];
        }
        nodes[cur] = x; // leaf value
    }
    int query(int x) {
        int cur = 0, ma = 0;
        for (int i = MXBIT-1; i >= 0; --i) {
            int t = ((x >> i) & 1) ^ 1;
            if (!nxt[cur][t]) t ^= 1;
            cur = nxt[cur][t];
            ma <= 1; ma |= t;
        }
        // or return ma for max xor with one value instead of
        // subarray
        return x ^ nodes[cur];
    }
};

```

Hashing.h

Description: Simple, short and efficient hashing using pairs to reduce load factor.

<ModTemplate.h>, <PairNumTemplate.h> 13369f, 40 lines

```

using num = modnum<int(1e9)+7>;
using hsh = pairnum<num, num>;
const hsh BASE(163, 311);
// uniform_int_distribution<int> MULT_DIST(0.1*MOD, 0.9*MOD);
// constexpr hsh BASE(MULT_DIST(rng), MULT_DIST(rng));
struct hash_t {
    int n;
    string str;
    vector<hsh> hash, basePow;
    hash_t(const string& s) : n(s.size()), str(s), hash(n+1),
        basePow(n) {
        basePow[0] = 1;
        for (int i = 1; i < n; ++i) basePow[i] = basePow[i-1] *
            BASE;
        for (int i = 0; i < n; ++i)

```

```

        hash[i+1] = hash[i] * BASE + hsh(s[i]);
    }
    hsh get_hash(int left, int right) {
        assert(left <= right);
        return hash[right] - hash[left] * basePow[right - left];
    }
    int lcp(hash_t &other) { // need some testing
        int left = 0, right = min(str.size(), other.str.size());
        while (left < right) {
            int mid = (left + right + 1)/2;
            if (hash[mid] == other.hash[mid]) left = mid;
            else right = mid-1;
        }
        return left;
    }
};
vector<int> rabinkarp(string t, string p) {
    vector<int> matches;
    hsh h(0, 0);
    for (int i = 0; i < p.size(); ++i)
        h = BASE * h + hsh(p[i]);
    hash_t result(t);
    for (int i = 0; i + p.size() <= t.size(); ++i)
        if (result.get_hash(i, i + p.size()) == h)
            matches.push_back(i);
    return matches;
}

```

AhoCorasick.h

0b874a, 176 lines

```

template<int MIN_CHAR, int SIGMA> struct Aho {
    struct node {
        int depth;
        array<int, SIGMA> child_links; // trie links + failure links
        int dict_index = -1; // index of this node's word in the dict
        int suffix_link = 0; // link to longest proper suffix that exists in the trie
        int dict_suffix_link = 0; // link to longest suffix that exists in dict
        int count_suffixes_in_dict = 0; // number of suffixes that are words in dict
        node(int depth_) : depth(depth_) { child_links.fill(0); }
        // maybe add some other stuff here?
    };
    vector<node> data;
    vector<int> dictionary_word_links;

    int& child_link(int loc, int c) { return data[loc].child_links[c - MIN_CHAR]; }
    int child_link(int loc, int c) const { return data[loc].child_links[c - MIN_CHAR]; }

    int dict_proper_suffix_link(int loc) const {
        return data[data[loc].suffix_link].dict_suffix_link;
    }

    Aho() : data(1, node(0)) {}
    template<typename I>
    Aho(I begin, I end) : data(1, node(0)) {
        for (I iter = begin; iter != end; ++iter) add(*iter);
        build();
    }

```

```

template<typename S>
void add(const S& s) {
    int loc = 0;
    for (auto c_ : s) {
        int c = c_;
        assert(MIN_CHAR <= c && c < MIN_CHAR + SIGMA);
        if (!child_link(loc, c)) {
            child_link(loc, c) = int(data.size());
            data.push_back(node(data[loc].depth + 1));
        }
        loc = child_link(loc, c);
    }
    if (data[loc].count_suffixes_in_dict == 0) {
        data[loc].dict_suffix_link = loc;
        data[loc].dict_index = int(dictionary_word_links.size());
    }
    data[loc].count_suffixes_in_dict++;
    dictionary_word_links.push_back(loc);
}

```

```

vector<vector<int>>> children;
vector<pair<int, int>> dfs_ranges;
void build() {
    children.resize(int(data.size()));

```

```

    vector<int> bfs;
    for (int nxt : data[0].child_links) if (nxt) bfs.push_back(nxt);
    for (int v = 0; v < int(bfs.size()); ++v) {
        int loc = bfs[v];
        int parent = data[loc].suffix_link;

        children[parent].push_back(loc);
        if (data[loc].dict_suffix_link == 0)
            data[loc].dict_suffix_link = data[parent].dict_suffix_link;
        data[loc].count_suffixes_in_dict += data[parent].count_suffixes_in_dict;

        for (int c = MIN_CHAR; c < MIN_CHAR + SIGMA; ++c) {
            int& trie_child = child_link(loc, c);
            if (trie_child) {
                bfs.push_back(trie_child);
                data[trie_child].suffix_link = child_link(parent, c);
            } else trie_child = child_link(parent, c);
        }
    }

    dfs_ranges.resize(data.size());

    int visited = 0;
    auto dfs = [&](auto self, int loc) -> void {
        dfs_ranges[loc].first = visited++;
        for (int nxt : children[loc])
            self(self, nxt);
        dfs_ranges[loc].second = visited;
    };
    dfs(dfs, 0);
}

```

```

template<typename V>
void copy_results_for_duplicate_dictionary_entries(vector<V> &results) const {
    for (int dict_index = 0; dict_index < int(dictionary_word_links.size()); dict_index++) {
        int loc = dictionary_word_links[dict_index];
        if (data[loc].dict_index != dict_index) {

```

```

        results[dict_index] = results[data[loc].
            dict_index];
    }
}

/* Returns the number of matches of each dictionary word.
 * Linear in text length and number of dictionary words.
 */
template<typename S>
vector<int> count_matches(const S& text) const {
    vector<int> count(dictionary_word_links.size());
    vector<vector<int>> found_with_length;

    auto record_match = [&](int loc, int quantity) {
        int dict_index = data[loc].dict_index;
        if (dict_index == -1) return;

        if (count[dict_index] == 0) {
            if (data[loc].depth >= found_with_length.size())
                found_with_length.resize(data[loc].depth +
                    1);
            found_with_length[data[loc].depth].push_back(
                loc);
        }
        count[dict_index] += quantity;
    };

    int loc = 0;
    for (auto c_ : text) {
        int c = c_;
        assert(MIN_CHAR <= c && c < MIN_CHAR + SIGMA);
        loc = child_link(loc, c);
        record_match(data[loc].dict_suffix_link, 1);
    }
    for (int match_length = int(found_with_length.size()) -
        1; match_length > 0; match_length--) {
        for (int loc : found_with_length[match_length])
            record_match(dict_proper_suffix_link(loc),
                count[data[loc].dict_index]);
    }

    copy_results_for_duplicate_dictionary_entries(count);
    return count;
}

/* Returns the starting index of every match of each
 * dictionary word.
 * Linear in the text length, number of dictionary words,
 * and total number of matches.
 */
template<typename S>
vector<vector<int>> indices_of_matches(const S& text) const
{
    vector<vector<int>> indices(dictionary_word_links.size()
        ());

    int loc = 0;
    for (int a = 0; a < int(text.size()); ++a) {
        int c = text[a];
        assert(MIN_CHAR <= c && c < MIN_CHAR + SIGMA);
        loc = child_link(loc, c);
        for (int par = data[loc].dict_suffix_link; par !=
            0; par = dict_proper_suffix_link(par)) {
            indices[data[par].dict_index].push_back(a + 1 -
                data[par].depth);
        }
    }
}

```

```

/* Notable fact: before duplication, the total number
 * of matches is at most
 * (text length) * (number of distinct dictionary word
 * lengths), which is
 * O(text length * sqrt(sum of dictionary word lengths)
 * ).
 */
copy_results_for_duplicate_dictionary_entries(indices);
return indices;
}

/* Returns the total number of matches over all dictionary
 * words.
 * Duplicate dictionary entries each contribute to the
 * total match count.
 * Linear in the text length.
 */
template<typename S>
int64_t count_total_matches(const S& text) const {
    int64_t count = 0;

    int loc = 0;
    for (int a = 0; a < int(text.size()); ++a) {
        int c = text[a];
        assert(MIN_CHAR <= c && c < MIN_CHAR + SIGMA);
        loc = child_link(loc, c);
        count += data[loc].count_suffixes_in_dict;
    }

    return count;
}
};

```

SuffixArray.h

Description: Builds suffix array for a string. The lcp function calculates longest common prefixes for neighbouring strings in suffix array. The returned vector is of size $n + 1$.

Time: $O(N \log N)$ where N is the length of the string for creation of the SA. $O(N)$ for longest common prefixes.

```

<../data-structures/RMQ.h> 53208d, 51 lines
mt19937 rng(chrono::steady_clock::now().time_since_epoch().
    count());
struct suffix_array_t {
    int N, H;
    vector<int> sa, invsa;
    vector<int> lcp;
    rmq_t<pair<int, int>> RMQ;
    bool cmp(int a, int b) { return invsa[a + H] < invsa[b + H]
        ; }
    void ternary_sort(int a, int b) {
        if (a == b) return;
        int pivot = sa[a + rng() % (b - a)];
        int left = a, right = b;
        for (int i = a; i < b; ++i) if (cmp(sa[i], pivot)) swap
            (sa[i], sa[left++]);
        for (int i = b-1; i >= left; --i) if (cmp(pivot, sa[i])
            ) swap(sa[i], sa[--right]);
        ternary_sort(a, left);
        for (int i = left; i < right; ++i) invsa[sa[i]] = right
            -1;
        if (right-left == 1) sa[left] = -1;
        ternary_sort(right, b);
    }
    suffix_array_t() {}
    template<typename I>
    suffix_array_t(I begin, I end): N(int(end - begin)), sa(N)
    {
        vector<int> v(begin, end); v.push_back(INT_MIN);
    }
}

```

```

    invsa = v; iota(sa.begin(), sa.end(), 0);
    H = 0; ternary_sort(0, N);
    for (H = 1; H <= N; H *= 2)
        for (int j = 0, i = j; i != N; i = j)
            if (sa[i] < 0) {
                while (j < N && sa[j] < 0) j += -sa[j];
                sa[i] = -(j - i);
            }
            else { j = invsa[sa[i]] + 1; ternary_sort(i, j)
                ; }
        for (int i = 0; i < N; ++i) sa[invsa[i]] = i;

    lcp.resize(N); int res = 0;
    for (int i = 0; i < N; ++i) {
        if (invsa[i] > 0) while (v[i + res] == v[sa[invsa[i]
            ] - 1] + res) ++res;
        lcp[invsa[i]] = res; res = max(res - 1, 0);
    }
    vector<pair<int, int>> lcp_index(N);
    for (int i = 0; i < N; ++i) lcp_index[i] = {lcp[i], 1 +
        i};
    RMQ = rmq_t<pair<int, int>>(move(lcp_index));
}
pair<int, int> rmq_query(int a, int b) const { return RMQ.
    query(a, b); }
pair<int, int> get_split(int a, int b) const { return RMQ.
    query(a, b-2); }
int get_lcp(int a, int b) const {
    if (a == b) return N - a;
    a = invsa[a], b = invsa[b];
    if (a > b) swap(a, b);
    return rmq_query(a + 1, b).first;
}
};

```

SuffixAutomaton.h

Description: Suffix automaton

2717ef, 124 lines

```

struct suffix_automaton_t {
    struct node_t {
        node_t* link; // parent state
        int len, id; // length of the longest string in id'th
            class
        bool cloned;
        map<char, node_t*> next; // transitions (consider using
            an array instead)
        node_t() {}
        node_t(node_t* lnk, int t, int i, bool c) : link(lnk),
            len(t), cloned(c) {}
        int get_longest() const { return len; }
        int get_shortest() const { return (link == nullptr ? 0
            : 1 + link->len); }
        void set_next(char c, node_t* nxt) { next[c] = nxt; }
        bool has_next(char c) { return next.count(c); }
        node_t* get_next(char c) { return has_next(c) ? next[c]
            : nullptr; }
        vector<pair<char, node_t*>> get_transitions() {
            vector<pair<char, node_t*>> locs;
            for (auto x : next) locs.push_back(x);
            return locs;
        }
    };
};

int size;
int64_t cnt = 0;
node_t* top;
vector<node_t*> nodes;

```

```

suffix_automaton_t(const int N) : size(0), nodes(2 * N) {
    top = nodes.front() = make_node(0, false);
}

suffix_automaton_t(const string& S) : size(0), nodes(2 *
    int(S.size())) {
    top = nodes.front() = make_node(0, false);
    for (char c : S) {
        add(c);
    }
    topo_sort();
}
~suffix_automaton_t() { for (auto a : nodes) delete a; }

node_t* make_node(int len, bool is_clone) {
    nodes[size] = new node_t(nullptr, len, size, is_clone);
    return nodes[size++];
}

void add(char c) {
    node_t* cur = make_node(1 + top->len, false);
    node_t* par;

    cnt += nodes[cur->id]->len;

    for (par = top; par && !par->has_next(c); par = par->
        link) {
        par->set_next(c, cur);
    }

    if (par == nullptr) {
        cur->link = nodes[0];
    } else {
        node_t* Q = par->get_next(c);
        if (1 + par->len == Q->len) {
            cur->link = Q;
        } else {
            node_t* clone = make_node(1 + par->len, true);
            clone->next = Q->next;
            clone->link = Q->link;
            cnt += nodes[clone->id]->len;
            for (; par != nullptr && par->get_next(c) == Q;
                par = par->link) {
                par->set_next(c, clone);
            }
            cnt += nodes[nodes[Q->id]->link->id]->len;
            Q->link = cur->link = clone;
            cnt -= nodes[nodes[clone->id]->link->id]->len;
            cnt -= nodes[nodes[Q->id]->link->id]->len;
        }
    }
    cnt -= nodes[nodes[cur->id]->link->id]->len;
    top = cur;
}

void topo_sort() {
    vector<int> indeg(size);
    vector<node_t*> order(size);
    for (int v = 0; v < size; ++v) {
        auto trans = nodes[v]->get_transitions();
        for (auto x : trans) {
            ++indeg[x.second->id];
        }
    }

    order[0] = nodes[0];
    int cur = 1;

    for (int v = 0; v < size; ++v) {

```

```

        node_t* r = order[v];
        auto trans = nodes[r->id]->get_transitions();
        for (auto x : trans) {
            if (--indeg[x.second->id] == 0)
                order[cur++] = x.second;
        }
    }

    nodes = order;
    for (int v = 0; v < size; ++v)
        nodes[v]->id = v;
}

int64_t cur_distinct() {
    return cnt;
}

vector<int> get_terminals() {
    vector<int> terminals;
    for (auto par = top; par; par = par->link)
        terminals.push_back(par->id);
    return terminals;
}

int get_distinct() {
    int cnt = 0;
    for (int v = 0; v < size; ++v) {
        cnt += nodes[v]->len - (nodes[v]->link == nullptr ?
            0 : nodes[v]->link->len);
    }
    return cnt;
}
};

```

Various (10)

10.1 Intervals

IntervalContainer.h

Description: Add and remove intervals from a set of disjoint intervals. Will merge the added interval with any overlapping intervals in the set when adding. Intervals are [inclusive, exclusive).

Time: $\mathcal{O}(\log N)$

f47dfb, 23 lines

```

set<pair<int,int>>::iterator addInterval(set<pair<int,int>> &is
    , int L, int R) {
    if (L == R) return is.end();
    auto it = is.lower_bound({L, R}), before = it;
    while (it != is.end() && it->first <= R) {
        R = max(R, it->second);
        before = it = is.erase(it);
    }
    if (it != is.begin() && (--it)->second >= L) {
        L = min(L, it->first);
        R = max(R, it->second);
        is.erase(it);
    }
    return is.insert(before, {L, R});
}

void removeInterval(set<pair<int,int>> &is, int L, int R) {
    if (L == R) return;
    auto it = addInterval(is, L, R);
    auto r2 = it->second;
    if (it->first == L) is.erase(it);
    else (int&)it->second = L;
    if (R != r2) is.emplace(R, r2);
}

```

IntervalCover.h

Description: Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add || R.empty(). Returns empty set on failure (or if G is empty).

Time: $\mathcal{O}(N \log N)$

133eb4, 19 lines

```

template<class T>
vector<int> cover(pair<T, T> G, vector<pair<T, T>> I) {
    vector<int> S(I.size());
    iota(S.begin(), S.end(), 0);
    sort(S.begin(), S.end(), [&](int a, int b) { return I[a] < I[
        b]; });
    T cur = G.first;
    int at = 0;
    while (cur < G.second) { // (A)
        pair<T, int> mx = {cur, -1};
        while (at < I.size() && I[S[at]].first <= cur) {
            mx = max(mx, {I[S[at]].second, S[at]});
            at++;
        }
        if (mx.second == -1) return {};
        cur = mx.first;
        R.push_back(mx.second);
    }
    return R;
}

```

ConstantIntervals.h

Description: Split a monotone function on [from, to) into a minimal set of half-open intervals on which it has the same value. Runs a callback g for each such interval.

Usage: constantIntervals(0, sz(v), [&](int x){return v[x];}, [&](int lo, int hi, T val){...});

Time: $\mathcal{O}(k \log \frac{n}{k})$

753a4c, 19 lines

```

template<class F, class G, class T>
void rec(int from, int to, F& f, G& g, int& i, T& p, T q) {
    if (p == q) return;
    if (from == to) {
        g(i, to, p);
        i = to; p = q;
    } else {
        int mid = (from + to) >> 1;
        rec(from, mid, f, g, i, p, f(mid));
        rec(mid+1, to, f, g, i, p, q);
    }
}

template<class F, class G>
void constantIntervals(int from, int to, F f, G g) {
    if (to <= from) return;
    int i = from; auto p = f(i), q = f(to-1);
    rec(from, to-1, f, g, i, p, q);
    g(i, to, q);
}

```

10.2 Misc. algorithms

TernarySearch.h

Description: Find the smallest i in [a, b] that maximizes f(i), assuming that f(a) < ... < f(i) ≥ ... ≥ f(b). To reverse which of the sides allows non-strict inequalities, change the < marked with (A) to <=, and reverse the loop at (B). To minimize f, change it to >, also at (B).

Usage: int ind = ternSearch(0, n-1, [&](int i){return a[i];});

Time: $\mathcal{O}(\log(b-a))$

35ef73, 12 lines

```

template<class F>
int ternSearch(int a, int b, F f) {
    assert(a <= b);
    while (b - a >= 5) {

```

```
int mid = (a + b) / 2;
if (f(mid) < f(mid+1)) a = mid; // (A)
else b = mid+1;
}
for(int i = a+1; i <= b; ++i)
    if (f(a) < f(i)) a = i; // (B)
return a;
}
```

LowerBound.h

7422d7, 11 lines

```
int LowerBound(vector<int> v, int n, int x){
    int l = 1, r = n, m;
    while(l <= r){
        m = (l+r)/2;
        if(v[m] >= x && (m == 1 || v[m-1] < x))
            return m;
        else if(v[m] >= x) r=m-1;
        else l=m+1;
    }
    return m;
}
```

UpperBound.h

381d15, 11 lines

```
int UpperBound(vector<int> v, int n, int x){
    int l = 1, r = n, m;
    while(l <= r){
        m=(l+r)/2;
        if(v[m] > x && (m == 1 || v[m-1] <= x))
            return m;
        else if(v[m] > x) r=m-1;
        else l=m+1;
    }
    return m;
}
```

MergeSort.h

Time: $\mathcal{O}(N \log(N))$

fac159, 25 lines

```
vector<int> merge(vector<int> &values, int l, int r) {
    static vector<int> result(values.size());
    int i = l, j = l + (r - l)/2;
    int mid = j, k = i, inversions = 0;
    while (i < mid && j < r) {
        if (values[i] < values[j]) result[k++] = values[i++];
        else {
            result[k++] = values[j++];
            inversions += (mid - i);
        }
    }
    while (i < mid) result[k++] = values[i++];
    while (j < r) result[k++] = values[j++];
    for (k = l; k < r; ++k) values[k] = result[k];
    return result;
}

vector<int> msort(vector<int> &values, int l, int r) {
    if (r - l > 1) {
        int mid = l + (r - l)/2;
        msort(values, l, mid); msort(values, mid, r);
        return merge(values, l, r);
    }
    return {};
}
```

RadixSort.h

Description: Radix Sort Algorithm.

Time: $\mathcal{O}(NK)$ where K is the number of bits in the largest element of the array to be sorted.

```
889884, 54 lines

struct identity {
    template<typename T>
    T operator()(const T &x) const {
        return x;
    }
};

template<typename T, typename T_extract_key = identity>
void radix_sort(vector<T> &data, int bits_per_pass = 10, const
    T_extract_key &extract_key = identity()) {
    if (data.size() < 256) {
        sort(data.begin(), data.end(), [&](const T &a, const T
            &b) {
                return extract_key(a) < extract_key(b);
            });
        return;
    }
    using T_key = decltype(extract_key(data.front()));
    T_key minimum = numeric_limits<T_key>::max();
    for (T &x : data) minimum = min(minimum, extract_key(x));
    int max_bits = 0;
    for (T &x : data) {
        T_key key = extract_key(x);
        max_bits = max(max_bits, key == minimum ? 0 : 64 -
            __builtin_clzll(key - minimum));
    }
    int passes = max((max_bits + bits_per_pass / 2) /
        bits_per_pass, 1);
    if (32 - __builtin_clz(data.size()) <= 1.5 * passes) {
        sort(data.begin(), data.end(), [&](const T &a, const T
            &b) {
                return extract_key(a) < extract_key(b);
            });
        return;
    }
    vector<T> buffer(data.size());
    vector<int> counts;
    int bits_so_far = 0;
    for (int p = 0; p < passes; p++) {
        int bits = (max_bits + p) / passes;
        counts.assign(1 << bits, 0);
        for (T &x : data) {
            T_key key = extract_key(x) - minimum;
            counts[(key >> bits_so_far) & ((1 << bits) - 1)]++;
        }
        int count_sum = 0;
        for (int &count : counts) {
            int current = count;
            count = count_sum;
            count_sum += current;
        }
        for (T &x : data) {
            T_key key = extract_key(x) - minimum;
            int key_section = (key >> bits_so_far) & ((1 <<
                bits) - 1);
            buffer[counts[key_section]++] = x;
        }
        swap(data, buffer);
        bits_so_far += bits;
    }
}
```

CoordCompression.h

809d6a, 9 lines

```
vector<int> comp_coord(vector<int> &y, int N) {
    vector<int> result;
    for (int i = 0; i < N; ++i) result.emplace_back(y[i]);
    sort(result.begin(), result.end());
}
```

```
result.resize(unique(result.begin(), result.end())- result.
    begin());
for (int i = 0; i < N; ++i)
    y[i] = lower_bound(result.begin(), result.end(), y[i])
        - result.begin();
return result;
}
```

CountTriangles.h

Description: Counts $x, y \geq 0$ such that $Ax + By \leq C$.

8d67b3, 8 lines

```
lint count_triangle(lint A, lint B, lint C) {
    if (C < 0) return 0;
    if (A > B) swap(A, B);
    lint p = C / B;
    lint k = B / A;
    lint d = (C - p * B) / A;
    return count_triangle(B - k * A, A, C - A * (k * p + d + 1))
        + (p + 1) * (d + 1) + k * p * (p + 1) / 2;
}
```

Karatsuba.h

Description: Faster-than-naive convolution of two sequences: $c[x] = \sum a[i]b[x-i]$. Uses the identity $(aX + b)(cX + d) = acX^2 + bd + ((a + c)(b + d) - ac - bd)X$. Doesn't handle sequences of very different length welint. See also FFT, under the Numerical chapter.

Time: $\mathcal{O}(N^{1.6})$

946265, 30 lines

```
int size(int s) { return s > 1 ? 32-__builtin_clz(s-1) : 0; }

void karatsuba(lint *a, lint *b, lint *c, lint *t, int n) {
    int ca = 0, cb = 0;
    for(int i = 0; i < n; ++i) ca += !!a[i], cb += !!b[i];
    if (min(ca, cb) <= 1500/n) { // few numbers to multiply
        if (ca > cb) swap(a, b);
        for(int i = 0; i < n; ++i)
            if (a[i]) FOR(j,n) c[i+j] += a[i]*b[j];
    }
    else {
        int h = n >> 1;
        karatsuba(a, b, c, t, h); // a0*b0
        karatsuba(a+h, b+h, c+n, t, h); // a1*b1
        for(int i = 0; i < h; ++i) a[i] += a[i+h], b[i] += b[i+
            h];
        karatsuba(a, b, t, t+n, h); // (a0+a1)*(b0+b1)
        for(int i = 0; i < h; ++i) a[i] -= a[i+h], b[i] -= b[i+
            h];
        for(int i = 0; i < n; ++i) t[i] -= c[i]+c[i+n];
        for(int i = 0; i < n; ++i) c[i+h] += t[i], t[i] = 0;
    }
}

vector<lint> conv(vector<lint> a, vector<lint> b) {
    int sa = a.size(), sb = b.size(); if (!sa || !sb) return
        {};
    int n = 1<<size(max(sa,sb)); a.resize(n), b.resize(n);
    vector<lint> c(2*n), t(2*n);
    for(int i = 0; i < 2*n; ++i) t[i] = 0;
    karatsuba(&a[0], &b[0], &c[0], &t[0], n);
    c.resize(sa+sb-1); return c;
}
```

CountInversions.h

Description: Count the number of inversions to make an array sorted. Merge sort has another approach.

Time: $\mathcal{O}(n \log(n))$

<FenwickTree.h>

0002df, 22 lines

```
FT<lint> bit(n);
lint inv = 0;
```

```
for (int i = n-1; i >= 0; --i) {
    inv += bit.query(values[i]); // careful with the interval
    bit.update(values[i], 1);    // [0, x) or [0, x] ?
}

// using D&C,the constant is quite high but still nlogn
lint msort(vector<int> &values, int left, int right) {
    if ((right - left) <= 1) return 0;
    int mid = left + (right - left)/2;
    lint result = msort(values, left, mid) + msort(values, mid,
        right);
    auto cmp = [](int i, int j) { return i > j; };
    sort(values.begin() + left, values.begin() + mid, cmp);
    sort(values.begin() + mid, values.begin() + right, cmp);
    int pos = left;
    for (int i = mid; i < right; ++i) {
        while (pos != mid && values[pos] > values[i]) ++pos;
        result += (pos - left);
    }
    return result;
}
```

Histogram.h

DateManipulation.h088459, 42 lines

```
string week_day_str[7] = {"Sunday", "Monday", "Tuesday", "
    Wednesday", "Thursday", "Friday", "Saturday"};
string month_str[13] = {"", "January", "February", "March", "
    April", "May", "June", "July", "August", "September", "
    October", "November", "December"};
map<string, int> week_day_int = {{ "Sunday", 0}, {"Monday", 1},
    {"Tuesday", 2}, {"Wednesday", 3}, {"Thursday", 4}, {"
    Friday", 5}, {"Saturday", 6}};
map<string, int> month_int = {{ "January", 1}, {"February", 2},
    {"March", 3}, {"April", 4}, {"May", 5}, {"June", 6}, {"
    July", 7}, {"August", 8}, {"September", 9}, {"October",
    10}, {"November", 11}, {"December", 12}};
int month[2][13] = {{0, 31, 28, 31, 30, 31, 30, 31, 31, 30, 31,
    30, 31}, {0, 31, 29, 31, 30, 31, 30, 31, 31, 30, 31, 30,
    31}};

/* O(1) - Checks if year y is a leap year. */
bool leap_year(int y){
    return (y % 4 == 0 && y % 100 != 0) || y % 400 == 0;
}

/* O(1) - Increases the day by one. */
void update(int &d, int &m, int &y){
    if (d == month[leap_year(y)][m]){
        d = 1;
        if (m == 12) {
            m = 1;
            y++;
        }
        else m++;
    }
    else d++;
}
```

```
int intToDay(int jd) { return jd % 7; }
int dateToInt(int y, int m, int d) {
    return 1461 * (y + 4800 + (m - 14) / 12) / 4 +
        367 * (m - 2 - (m - 14) / 12 * 12) / 12 -
        3 * ((y + 4900 + (m - 14) / 12) / 100) / 4 +
        d - 32075; }
void intToDate(int jd, int &y, int &m, int &d) {
    int x, n, i, j;
    x = jd + 68569;
```

```
n = 4 * x / 146097;
x -= (146097 * n + 3) / 4;
i = (4000 * (x + 1)) / 1461001;
x -= 1461 * i / 4 - 31;
j = 80 * x / 2447;
d = x - 2447 * j / 80;
x = j / 11;
m = j + 2 - 12 * x;
y = 100 * (n - 49) + i + x; }
```

NQueens.cppDescription: NQueense97e9e, 43 lines

```
int ans;
bitset<30> rw, ld, rd; //2*MAXN-1
bitset<30> iniqueens; //2*MAXN-1
vector<int> col;
void init(int n){
    ans=0;
    rw.reset();
    ld.reset();
    rd.reset();
    col.assign(n,-1);
}
void init(int n, vector<pair<int,int>> initial_queens){
    //it does NOT check if initial queens are at valid
    positions
    init(n);
    iniqueens.reset();
    for(pair<int,int> pos: initial_queens){
        int r=pos.first, c= pos.second;
        rw[r] = ld[r-c+n-1] = rd[r+c]=true;
        col[c]=r;
        iniqueens[c] = true;
    }
}
void backtracking(int c, int n){
    if (c==n){
        ans++;
        for(int r:col) cout<<r+1<<" ";
        cout<<"\n";
        return;
    }
    else if(iniqueens[c]){
        backtracking(c+1,n);
    }
    else for(int r=0;r<n;r++){
        if(!rw[r] && !ld[r-c+n-1] && !rd[r+c]){
            // if(board[r][c]!=blocked && !rw[r] && !ld[r-c+n-1] &&
            !rd[r+c]){ // if there are blocked positions
                rw[r] = ld[r-c+n-1] = rd[r+c]=true;
                col[c]=r;
                backtracking(c+1,n);
                col[c]=-1;
                rw[r] = ld[r-c+n-1] = rd[r+c]=false;
            }
        }
    }
}
```

SudokuSolver.h6be906, 41 lines

```
int N,m; // N = n*n, m = n; where n equal number of rows or
    columns
array<array<int, 10>, 10> grid;
struct SudokuSolver {
    bool UsedInRow(int row,int num){
        for(int col = 0; col < N; ++col)
            if(grid[row][col] == num) return true;
        return false;
    }
}
```

```

}
bool UsedInCol(int col,int num){
    for(int row = 0; row < N; ++row)
        if(grid[row][col] == num) return true;
    return false;
}
bool UsedInBox(int row_0,int col_0,int num){
    for(int row = 0; row < m; ++row)
        for(int col = 0; col < m; ++col)
            if(grid[row+row_0][col+col_0] == num) return
                true;
    return false;
}
bool isSafe(int row,int col,int num){
    return !UsedInRow(row,num) && !UsedInCol(col,num) && !
        UsedInBox(row-row%m,col-col%m,num);
}
bool find(int &row,int &col){
    for(row = 0; row < N; ++row)
        for(col = 0; col < N; ++col)
            if(grid[row][col] == 0) return true;
    return false;
}
bool Solve(){
    int row, col;
    if(!find(row,col)) return true;
    for(int num = 1; num <= N; ++num){
        if(isSafe(row,col,num)){
            grid[row][col] = num;
            if(Solve()) return true;
            grid[row][col] = 0;
        }
    }
    return false;
}
};
```

FloydCycle.hDescription: Detect loop in a list. Consider using mod template to avoid
 overflow.Time: O(n)b456ab, 10 lines

```
template<class F>
pair<int,int> find(int x0, F f) {
    int t = f(x0), h = f(t), mu = 0, lam = 1;
    while (t != h) t = f(t), h = f(f(h));
    h = x0;
    while (t != h) t = f(t), h = f(h), ++mu;
    h = f(t);
    while (t != h) h = f(h), ++lam;
    return {mu, lam};
}
```

SubsetXOR.hDescription: A list of basis values sorted in decreasing order, where each
 value has a unique highest bit.d5bcd3, 48 lines

```
const int BITS = 60;

template<typename T> struct xor_basis {
    int N = 0;
    array<T, BITS> basis;

    T min_value(T start) const {
        if (N == BITS) return 0;
        for (int i = 0; i < N; ++i)
            start = min(start, start ^ basis[i]);
        return start;
    }
}
```



```
T max_value(T start = 0) const {
    if (N == BITS) return ((T) 1 << BITS) - 1;
    for (int i = 0; i < N; ++i)
        start = max(start, start ^ basis[i]);
    return start;
}

bool add(T x) {
    x = min_value(x);
    if (x == 0) return false;

    basis[N++] = x;

    // Insertion sort.
    for (int k = N - 1; k > 0 && basis[k] > basis[k - 1]; k --)
        swap(basis[k], basis[k - 1]);

    return true;
}

void merge(const xor_basis<T>& other) {
    for (int i = 0; i < other.n && N < BITS; i++)
        add(other.basis[i]);
}

void merge(const xor_basis<T>& a, const xor_basis<T>& b) {
    if (a.N > b.N) {
        *this = a;
        merge(b);
    } else {
        *this = b;
        merge(a);
    }
}
};
```

10.3 Dynamic programming

DivideAndConquerDP.h

Description: Given $a[i] = \min_{lo(i) \leq k < hi(i)} (f(i, k))$ where the (minimal) optimal k increases with i , computes $a[i]$ for $i = L..R - 1$.
Time: $\mathcal{O}((N + (hi - lo)) \log N)$

```
struct DP { // Modify at will:
    int lo(int ind) { return 0; }
    int hi(int ind) { return ind; }
    lint f(int ind, int k) { return dp[ind][k]; }
    void store(int ind, int k, lint v) { res[ind] = {k, v}; }
    void rec(int L, int R, int LO, int HI) {
        if (L >= R) return;
        int mid = (L + R) >> 1;
        pair<lint, int> best(LLONG_MAX, LO);
        for(int k = max(LO, lo(mid)); k < min(HI, hi(mid)); ++k)
            best = min(best, make_pair(f(mid, k), k));
        store(mid, best.second, best.first);
        rec(L, mid, LO, best.second+1);
        rec(mid+1, R, best.second, HI);
    }
    void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```

KnuthDP.h

Description: When doing DP on intervals: $a[i][j] = \min_{i < k < j} (a[i][k] + a[k][j]) + f(i, j)$, where the (minimal) optimal k increases with both i and j , one can solve intervals in increasing order of length, and search $k = p[i][j]$ for $a[i][j]$ only between $p[i][j - 1]$ and $p[i + 1][j]$. This is known as Knuth DP. Sufficient criteria for this are if $f(b, c) \leq f(a, d)$ and $f(a, c) + f(b, d) \leq f(a, d) + f(b, c)$ for all $a \leq b \leq c \leq d$. Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.
Time: $\mathcal{O}(N^2)$

ConvexHullTrick.h

Description: Transforms dp of the form (or similar) $dp[i] = \min_{j < i} (dp[j] + b[j] * a[i])$. Time goes from $\mathcal{O}(n^2)$ to $\mathcal{O}(n \log n)$, if using online line container, or $\mathcal{O}(n)$ if lines are inserted in order of slope and queried in order of x . To apply try to find a way to write the factor inside minimization as a linear function of a value related to i . Everything else related to j will become constant.

```
<LineContainer.h> 1e5a56, 22 lines

array<lint, 112345> dyn, a, b;

int main() {
    int n;
    cin >> n;
    for (int i = 0; i < n; ++i) cin >> a[i];
    for (int i = 0; i < n; ++i) cin >> b[i];
    dyn[0] = 0;
    LineContainer cht;
    cht.add(-b[0], 0);
    for (int i = 1; i < n; ++i) {
        dyn[i] = cht.query(a[i]);
        cht.add(-b[i], dyn[i]);
    }
    // Original DP  $\mathcal{O}(n^2)$ .
    // for (int i = 1; i < n; i++) {
    //     dyn[i] = INF;
    //     for (int j = 0; j < i; j++)
    //         dyn[i] = min(dyn[i], dyn[j] + a[i] * b[j]);
    // }
    cout << -dyn[n-1] << '\n';
}
```

Coin.h

Description: Number of ways to make value K with X coins
Time: $\mathcal{O}(NC)$

```
for (int i = 0; i < n; ++i)
    for (int j = coins[i]; j <= k; ++j)
        dp[j] += dp[j - coins[i]];
```

MinCoin.h

Description: minimum number of coins to make K
Time: $\mathcal{O}(kV)$

```
int coin(vector<int> &c, int k) {
    vector<int> dp(k+1, INF); dp[0] = 0;
    for (int i = 0; i < c.size(); ++i)
        for (int j = c[i]; j <= k; ++j)
            dp[j] = min(dp[j], 1 + dp[j-c[i]]);
    return dp[k];
}
```

EditDistance.h

Description: Find the minimum numbers of edits required to convert string s into t. Only insertion, removal and replace operations are allowed.

```
int edit_dist(string &s, string &t) {
    const int n = int(s.size()), m = int(t.size());
    vector<vector<int>> dp(n+1, vector<int>(m+1, n+m+2));
    vector<vector<int>> prv(n+1, vector<int>(m+1, 0));
```

```
dp[0][0] = 0;
for (int i = 0; i <= n; i++) {
    for (int j = 0; j <= m; j++) {
        if (i < n) { // remove
            int cnd = dp[i][j] + 1;
            if (cnd < dp[i+1][j]) {
                dp[i+1][j] = cnd;
                prv[i+1][j] = 1;
            }
        }
        if (j < m) { // insert
            int cnd = dp[i][j] + 1;
            if (cnd < dp[i][j+1]) {
                dp[i][j+1] = cnd;
                prv[i][j+1] = 2;
            }
        }
        if (i < n && j < m) { // modify
            int cnd = dp[i][j] + (s[i] != t[j]);
            if (cnd < dp[i+1][j+1]) {
                dp[i+1][j+1] = cnd;
                prv[i+1][j+1] = 3;
            }
        }
    }
}
return dp[n][m];
}
```

LIS.h

Description: Compute indices for the longest increasing subsequence.
Time: $\mathcal{O}(N \log N)$

```
template<class I> vector<int> lis(const vector<I>& S) {
    if (S.empty()) return {};
    vector<int> prev(S.size());
    typedef pair<I, int> p;
    vector<p> res;
    for(int i = 0; i < (int)S.size(); i++) {
        // change 0 -> i for longest non-decreasing subsequence
        auto it = lower_bound(res.begin(), res.end(), p {S[i], 0});
        if (it == res.end()) res.emplace_back(), it = res.end()-1;
        *it = {S[i], i};
        prev[i] = it == res.begin() ? 0 : (it-1)->second;
    }
    int L = res.size(), cur = res.back().second;
    vector<int> ans(L);
    while (L--) ans[L] = cur, cur = prev[cur];
    return ans;
}
```

LIS2.h

Description: Compute the longest increasing subsequence.
Time: $\mathcal{O}(N \log N)$

```
template<typename T> int lis(const vector<T> &a) {
    vector<T> u;
    for (const T &x : a) {
        auto it = lower_bound(u.begin(), u.end(), x);
        if (it == u.end()) u.push_back(x);
        else *it = x;
    }
    return (int)u.size();
}
```

LCS.h

Description: Finds the longest common subsequence.
Memory: $\mathcal{O}(nm)$.
Time: $\mathcal{O}(nm)$ where n and m are the lengths of the sequences.

```
template<class T> T lcs(const T &X, const T &Y) {
    int a = X.size(), b = Y.size();
    vector<vector<int>> dp(a+1, vector<int>(b+1));
    for(int i = 1; i <= a; ++i) for(int j = 1; j <= b; j++)
        dp[i][j] = X[i-1]==Y[j-1] ? dp[i-1][j-1]+1 :
            max(dp[i][j-1],dp[i-1][j]);
    int len = dp[a][b];
    T ans(len, 0);
    while (a && b)
        if (X[a-1] == Y[b-1]) ans[--len] = X[--a], --b;
        else if (dp[a][b-1] > dp[a-1][b]) --b;
        else --a;
    return ans;
}
```

Knapsack.h
Description: Same 0-1 Knapsack problem, but returns a vector that holds each chosen item.
Time: $\mathcal{O}(nW)$

```
vector<int> Knapsack(int limit, vector<int> &v, vector<int> &w)
{
    vector<vector<int>> dp(v.size()+1);
    dp[0].resize(limit+1);
    for (int i = 0; i < v.size(); ++i) {
        dp[i+1] = dp[i];
        for (int j = 0; j <= limit - w[i]; ++j)
            dp[i+1][w[i]+j] = max(dp[i+1][w[i]+j], dp[i][j] + v[i]);
    }
    vector<int> result;
    for (int i = v.size()-1; i >= 0; --i)
        if (dp[i][limit] != dp[i+1][limit]) {
            limit -= w[i];
            result.push_back(i);
        }
    return result;
}
```

01Knapsack.h
Description: Given weights and values of n items, put these items in a knapsack of capacity W to get the maximum total value possible. More efficient space-wise since we work in only one row.
Time: $\mathcal{O}(NW)$

```
int knapsack(int limit, vector<int> &v, vector<int> &w) {
    vector<int> dp(limit+1, -1); int n = w.size();
    dp[0] = 0;
    for (int i = 0; i < n; ++i)
        for (int j = limit; j >= w[i]; --j)
            if (dp[j - w[i]] >= 0)
                dp[j] = max(dp[j], dp[j - w[i]] + v[i]);

    int result = 0;
    for (int i = 0; i <= limit; ++i)
        result = max(result, dp[i]);
    return result;
}
```

LargeKnapsack.h
Description: Knapsack with definition changed. Support large values because the weight isn't a dimension in our dp anymore.
Time: $\mathcal{O}(vW)$ where v is the sum of values.

```
constexpr int limit = (int)1e5+10;
int knapsack(int capacity, vector<lint> &v, vector<lint> &w) {
    vector<lint> dp(limit, 1ll << 60); dp[0] = 0;
    for (int i = 0; i < v.size(); ++i)
        for (int j = limit-v[i]-1; j >= 0; --j)
            dp[j + v[i]] = min(dp[j + v[i]], dp[j] + w[i]);
}
```

```
for (int i = limit-1; i >= 0; --i)
    if (dp[i] <= capacity) return i;
}
```

KnapsackUnbounded.h
Description: Knapsack problem but now take the same item multiple items is allowed.
Time: $\mathcal{O}(N \log N)$

```
int knapsack(vector<int> &v, vector<int> &w, int total) {
    vector<int> dp(total+1, -1);
    int result = 0; dp[0] = 0;
    for (int i = 0; i <= total; ++i) for (int j = 0; j < n; ++j)
        if (w[j] <= i && dp[i - w[j]] >= 0)
            dp[i] = max(dp[i], dp[i - w[j]] + v[j]);
    int result = 0;
    for (int i = 0; i <= total; ++i) result = max(result, dp[i]);
    return result;
}
```

KnapsackBounded.h
Description: You are given n types of items, each items has a weight and a quantity. Is possible to fill a knapsack with capacity k using any subset of items?
Time: $\mathcal{O}(Wn)$

```
vector<int> how_many(n+1), dp(k+1);
dp[0] = 1;
for (int i = 1; i <= n; ++i) cin >> how_many[i];
for (int i = 1; i <= n; ++i) {
    for (int j = k-items[i]; j >= 0; --j) {
        if (dp[j]) {
            int x = 1;
            while (x <= how_many[i] &&
                j + x*items[i] <= k && !dp[j + x*items[i]]) {
                dp[j + x*items[i]] = 1;
                ++x;
            }
        }
    }
}
```

KnapsackBoundedCosts.h
Description: You are given n types of items, you have $e[i]$ items of i -th type, and each item of i -th type weight $w[i]$ and cost $c[i]$. What is the minimal cost you can get by picking some items weighing at most W in total?
Time: $\mathcal{O}(Wn)$

```
<MinQueue.h>
const int maxn = 1000;
const int maxm = 100000;
const int inf = 0x3f3f3f;

minQueue<int> q[maxm];

array<int, maxm> dp; // the minimum cost dp[i] I need to pay in
                    // order to fill the knapsack with total weight i
int w[maxn], e[maxn], c[maxn]; // weight, number, cost
```

```
int main() {
    int n, m;
    cin >> n >> m;
    for (int i = 1; i <= n; i++) cin >> w[i] >> c[i] >> e[i];
    for (int i = 1; i <= m; i++) dp[i] = inf;
    for (int i = 1; i <= n; i++) {
        for (int j = 0; j < w[i]; j++) q[j].clear();
        for (int j = 0; j <= m; j++) {
            minQueue<int> &mq = q[j % w[i]];

```

```
        if (mq.size() > e[i]) mq.pop();
        mq.add(c[i]);
        mq.push(dp[j]);
        dp[j] = mq.getMin();
    }
}
cout << "Minimum value i can pay putting a total weight " <<
    m << " is " << dp[m] << '\n';
for (int i = 0; i <= m; i++) cout << dp[i] << " " << i << '\n'
    << '\n';
cout << "\n";
}
```

KnapsackBitset.h
Description: Find first value greater than m that cannot be formed by the sums of numbers from v .

```
bitset<int(1e7)> dp, dp1;
int knapsack(vector<int> &items, int n, int m) {
    dp[0] = dp1[0] = true;
    for (int i = 0; i < n; ++i) {
        dp1 <= items[i];
        dp |= dp1;
        dp1 = dp;
    }
    dp.flip();
    return dp._Find_next(m);
}
```

TSP.h
Description: Solve the Travelling Salesman Problem.
Time: $\mathcal{O}\left(N^2 * 2^N\right)$

```
const int MX = 15;
array<array<int, MX>, 1<<N> dp;
array<array<int, MX>, MX> dist;
int N;
int TSP(int n) {
    dp[0][1] = 0;
    for (int j = 0; j < (1 << n); ++j)
        for (int i = 0; i < n; ++i)
            if (j & (1<<i))
                for (int k = 0; k < n; ++k)
                    if (!(j & (1<<k)))
                        dp[k][j^(1<<k)] = min(dp[k][j^(1<<k)],
                            dp[i][j]+dist[i][k]);

    int ret = (1 << 31); // = INF
    for (int i = 1; i < n; ++i)
        ret = min(ret, dp[i][(1<<n)-1] + dist[i][0]);
    return ret;
}
```

TwoMaxEqualSumDS.h
Description: Two maximum equal sum disjoint subsets, $s[i] = 0$ if $v[i]$ wasn't selected, $s[i] = 1$ if $v[i]$ is in the first subset and $s[i] = 2$ if $v[i]$ is in the second subset
Time: $\mathcal{O}(n * S)$

```
pair<int, vector<int>> twoMaxEqualSumDS(vector<int> &v) {
    const int n = int(v.size());
    const int sum = accumulate(v.begin(), v.end(), 0);
    vector<int> dp(2*sum + 1, INT_MIN/2), newdp(2*sum + 1), s(n, 0);

    vector<vector<int>> rec(n, vector<int>(2*sum + 1));
    int i; dp[sum] = 0;
    for(i = 0; i < n; i++, swap(dp, newdp))
        for(int a, b, d = v[i]; d <= 2*sum - v[i]; d++){
            newdp[d] = max({dp[d], a = dp[d - v[i]] + v[i], b =
                dp[d + v[i]]});

```

```
        rec[i][d] = newdp[d] == a ? 1 : newdp[d] == b ? 2 : 0;
    }
    for(int j = i-1, d = sum; j >= 0; j--)
        d += (s[j] == rec[j][d]) ? s[j] == 2 ? v[j] : -v[j] : 0;
    return {dp[sum], s};
}
```

DistinctSubsequences.h

Description: DP eliminates overcounting. Number of different strings that can be generated by removing any number of characters, without changing the order of the remaining.

<ModTemplate.h>6fa2c5, 7 lines

```
num tot[30];
num distinct(const string &str) {
    num ans = 1; // tot[i] stands for number of distinct
                  strings ending with character 'a'+i
    for(auto &c : str)
        tie(ans, tot[c-'a']) = {2*ans-tot[c-'a'], ans};
    return ans-1;
}
```

CircularLCS.h

Description: For strings a, b calculates LCS of a with all rotations of b
Time: $\mathcal{O}(N^2)$

a57399, 48 lines

```
pair<int,int> dp[2001][4001];
string A,B;

void init() {
    for(int i = 1; i <= A.size(); ++i)
        for(int j = 1; j <= B.size(); ++j) { // naive LCS, store
            where value came from
            pair<int,int>& bes = dp[i][j]; bes = {-1,-1};
            bes = max(bes, {dp[i-1][j].first,0});
            bes = max(bes, {dp[i-1][j-1].first+(A[i-1] == B[j-1]),-1});
            ;
            bes = mex(bes, {dp[i][j-1].first,-2});
            bes.second *= -1;
        }
}

void adjust(int col) { // remove col'th character of b, adjust
    DP
    int x = 1;
    while (x <= A.size() && dp[x][col].second == 0) x ++;
    if (x > A.size()) return; // no adjustments to dp
    pair<int,int> cur = {x,col}; dp[cur.first][cur.second].second
        = 0;
    while (cur.first <= A.size() && cur.second <= B.size()) {
        // essentially decrease every dp[cur.first][y] y >= cur.second
        /.first by 1
        if (cur.second < B.size() && dp[cur.first][cur.s+1].second
            == 2) {
            cur.second ++;
            dp[cur.first][cur.second].second = 0;
        } else if (cur.first < A.size() && cur.second < B.size()
            && dp[cur.first+1][cur.s+1].second == 1) {
            cur.first ++, cur.second ++;
            dp[cur.first][cur.second].second = 0;
        } else cur.first ++;
    }
}

int getAns(pair<int,int> x) {
    int lo = x.second-B.size()/2, ret = 0;
    while (x.first && x.second > lo) {
        if (dp[x.first][x.second].second == 0) x.first --;
        else if (dp[x.first][x.second].second == 1) ret ++, x.first
            --, x.second --;
        else x.second --;
    }
}
```

```
    }
    return ret;
}

int circLCS(str a, str b) {
    A = a, B = b+b; init();
    int ans = 0;
    for(int i = 0; i < B.size(); ++i) {
        ans = max(ans,getAns({A.size(),i+B.size()}));
        adjust(i+1);
    }
    return ans;
}
```

MaxZeroSubmatrix.h

Description: Computes the area of the largest submatrix that contains only 0s

Time: $\mathcal{O}(NM)$ d7bff2, 18 lines

```
const int MAXN = 100, MAXM = 100;
array<array<int, MAXN>, MAXM> A, H;
int solve(int N, int M) {
    stack<int, vector<int>>> s; int ret = 0;
    for (int j = 0; j < M; j++) for (int i = N - 1; i >= 0; i
        --) H[i][j] = A[i][j] ? 0 : 1 + (i == N - 1 ? 0 : H[i
            + 1][j]);
    for (int i = 0; i < N; i++) {
        for (int j = 0; j < M; j++) {
            int minInd = j;
            while (!s.empty() && H[i][s.top()] >= H[i][j]) {
                ret = max(ret, (j - s.top()) * (H[i][s.top()]))
                    ;
                minInd = s.top(); s.pop(); H[i][minInd] = H[i][
                    j];
            }
            s.push(minInd);
        }
        while (!s.empty()) ret = max(ret, (M - s.top()) * H[i][
            s.top()]); s.pop();
    }
    return ret;
}
```

10.4 Debugging tricks

- signal(SIGSEGV, [](int) { _Exit(0); }); converts segfaults into Wrong Answers. Similarly one can catch SIGABRT (assertion failures) and SIGFPE (zero divisions). _GLIBCXX_DEBUG violations generate SIGABRT (or SIGSEGV on gcc 5.4.0 apparently).
- feenableexcept(29); kills the program on NaNs (1), 0-divs (4), infinities (8) and denormals (16).

10.5 Optimization tricks

10.5.1 Bit hacks

- $x \ \& \ -x$ is the least bit in x .
- for (int x = m; x;) { --x &= m; ... } loops over all subset masks of m (except m itself).
- $c = x \& -x, \ r = x + c; ((r \wedge x) >> 2) / c) \mid r$ is the next number after x with the same number of bits set.

- rep(b,0,K) rep(i,0,(1 << K)) if (i & 1 << b) D[i] += D[i^(1 << b)]; computes all sums of subsets.

10.5.2 Pragmas

- #pragma GCC optimize ("Ofast") will make GCC auto-vectorize for loops and optimizes floating points better (assumes associativity and turns off denormals).
- #pragma GCC target ("avx,avx2") can double performance of vectorized code, but causes crashes on old machines.
- #pragma GCC optimize ("trapv") kills the program on integer overflows (but is really slow).

FastInput.h

Description: Returns an integer. Usage requires your program to pipe in input from file. Can replace calls to gc() with getchar_unlocked() if extra speed isn't necessary (60% slowdown).

Usage: ./a.out < input.txt
Time: About 5x as fast as cin/scanf.

b31afb, 18 lines

```
struct GC {
    char buf[1 << 16];
    size_t bc = 0, be = 0;
    char operator()() {
        if (bc >= be) {
            buf[0] = 0, bc = 0;
            be = fread(buf, 1, sizeof(buf), stdin);
        }
        return buf[bc++]; // returns 0 on EOF
    }
} gc;
int readInt() {
    int a, c;
    while ((a = gc()) < 40);
    if (a == '-') return -readInt();
    while ((c = gc()) >= 48) a = a * 10 + c - 48;
    return a - 48;
}
```

BumpAllocator.h

Description: When you need to dynamically allocate many objects and don't care about freeing them. "new X" otherwise has an overhead of something like 0.05us + 16 bytes per allocation.

745db2, 8 lines

```
// Either globally or in a single class:
static char buf[450 << 20];
void* operator new(size_t s) {
    static size_t i = sizeof buf;
    assert(s < i);
    return (void*)&buf[i -= s];
}
void operator delete(void*) {}
```

SmallPtr.h

Description: A 32-bit pointer that points into BumpAllocator memory.

"BumpAllocator.h"2dd6c9, 10 lines

```
template<class T> struct ptr {
    unsigned ind;
    ptr(T* p = 0) : ind(p ? unsigned((char*)p - buf) : 0) {
        assert(ind < sizeof buf);
    }
    T& operator*() const { return *(T*)(buf + ind); }
    T* operator->() const { return &*this; }
    T& operator[](int a) const { return (&this)[a]; }
```

```
explicit operator bool() const { return ind; }
};
```

BumpAllocatorSTL.h

Description: BumpAllocator for STL containers.
Usage: vector<vector<int, small<int>>> ed(N);

bb66d4, 14 lines

```
char buf[450 << 20] alignas(16);
size_t buf_ind = sizeof buf;
```

```
template<class T> struct small {
    typedef T value_type;
    small() {}
    template<class U> small(const U&) {}
    T* allocate(size_t n) {
        buf_ind -= n * sizeof(T);
        buf_ind &= 0 - alignof(T);
        return (T*)(buf + buf_ind);
    }
    void deallocate(T*, size_t) {}
};
```

Hashmap.h

Description: Faster/better hash maps, taken from CF

09a72f, 19 lines

```
#include<bits/extc++.h>
struct splitmix64_hash {
    static uint64_t splitmix64(uint64_t x) {
        x += 0x9e3779b97f4a7c15;
        x = (x^(x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x^(x >> 27)) * 0x94d049bb133111eb;
        return x^(x >> 31);
    }
    size_t operator()(uint64_t x) const {
        static const uint64_t FIXED_RANDOM = std::chrono::
            steady_clock::now().time_since_epoch().count();
        return splitmix64(x + FIXED_RANDOM);
    }
};
```

```
template <typename K, typename V, typename Hash =
    splitmix64_hash>
using hash_map = __gnu_pbds::gp_hash_table<K, V, Hash>;
```

```
template <typename K, typename Hash = splitmix64_hash>
using hash_set = hash_map<K, __gnu_pbds::null_type, Hash>;
```

Unrolling.h

```
#define F {...; ++i;}
int i = from;
while (i&3 && i < to) F // for alignment, if needed
while (i + 4 <= to) { F F F F }
while (i < to) F
```

SIMD.h

Description: Cheat sheet of SSE/AVX intrinsics, for doing arithmetic on several numbers at once. Can provide a constant factor improvement of about 4, orthogonal to loop unrolling. Operations follow the pattern "`_mm(256)?name_(si(128|256)|epi(8|16|32|64)|pd|ps)".` Not all are described here; grep for `_mm_` in `/usr/lib/gcc/*/4.9/include/` for more. If AVX is unsupported, try 128-bit operations, "emmintrin.h" and `#define __SSE__` and `__MMX__` before including it. For aligned memory use `_mm_malloc(size, 32)` or `int buf[N] alignas(32)`, but prefer `loadu/s_storeu`.

b75e03, 43 lines

```
#pragma GCC target ("avx2") // or sse4.1
#include "immintrin.h"
```

```
typedef __m256i mi;
#define L(x) _mm256_loadu_si256((mi*)&(x))

// High-level/specific methods:
// load(u)?_si256, store(u)?_si256, setzero_si256, _mm_malloc
// blendv_(epi8|ps|pd) (z?y:x), movemask_epi8 (hibits of bytes)
// i32gather_epi32(addr, x, 4): map addr[] over 32-b parts of x
// sad_epu8: sum of absolute differences of u8, outputs 4xi64
// maddubs_epi16: dot product of unsigned i7's, outputs 16xi15
// madd_epi16: dot product of signed i16's, outputs 8xi32
// extractf128_si256(, i) (256->128), cvtsi128_si32 (128->lo32)
// maddubs_epi16(x,x,1) swaps 128-bit lanes
// shuffle_epi32(x, 3*64+2*16+1*4+0) == x for each lane
// shuffle_epi8(x, y) takes a vector instead of an imm

// Methods that work with most data types (append e.g. _epi32):
// set1, blend (i8?x:y), add, adds (sat.), mullo, sub, and/or,
// andnot, abs, min, max, sign(i,x), cmp(gt|eq), unpack(lo|hi)
```

```
int sumi32(mi m) { union {int v[8]; mi m;} u; u.m = m;
    int ret = 0; rep(i,0,8) ret += u.v[i]; return ret; }
mi zero() { return _mm256_setzero_si256(); }
mi one() { return _mm256_set1_epi32(-1); }
bool all_zero(mi m) { return _mm256_testz_si256(m, m); }
bool all_one(mi m) { return _mm256_testc_si256(m, one()); }
```

```
ll example_filteredDotProduct(int n, short* a, short* b) {
    int i = 0; ll r = 0;
    mi zero = _mm256_setzero_si256(), acc = zero;
    while (i + 16 <= n) {
        mi va = L(a[i]), vb = L(b[i]); i += 16;
        va = _mm256_and_si256(_mm256_cmpgt_epi16(vb, va), va);
        mi vp = _mm256_madd_epi16(va, vb);
        acc = _mm256_add_epi64(_mm256_unpacklo_epi32(vp, zero),
            _mm256_add_epi64(acc, _mm256_unpackhi_epi32(vp, zero)));
    }
    union {ll v[4]; mi m;} u; u.m = acc; for(int i=0;i<4;i++) r
        += u.v[i];
    for (;i<n;++i) if (a[i] < b[i]) r += a[i]*b[i]; // <- equiv
    return r;
}
```

FastMod.h

Description: Compute $a\%b$ about 4 times faster than usual, where b is constant but not known at compile time. Fails for $b = 1$.

c977c5, 10 lines

```
typedef unsigned long long ull;
typedef __uint128_t L;
struct FastMod {
    ull b, m;
    FastMod(ull b) : b(b), m(ull((L(1) << 64) / b)) {}
    ull reduce(ull a) {
        ull q = (ull)((L(m) * a) >> 64), r = a - q * b;
        return r >= b ? r - b : r;
    }
};
```

LinkedList.h

Description: Simple and efficient implementation of both LinkedList and DoublyLinkedList.

00b50e, 35 lines

```
struct LinkedList {
    int n;
    vector<int> next, head;
    LinkedList(int n) : n(n), next(n), head(n) { clear(); }
    void clear() { head.assign(n, -1); }
    int front(int h) { return head[h]; }
    void pop(int h) { head[h] = next[head[h]]; }
    void push(int h, int u) { next[u] = head[h], head[h] = u; }
```

```
};
struct DoublyLinkedList {
    struct node_t { int prev, next; };
    int n;
    vector<int> head;
    vector<node_t> nodes;
    DoublyLinkedList(int n) : n(n), nodes(n) { clear(); }
    void clear() { head.assign(n, -1); }
    void erase(int h, int u) {
        int pv = nodes[u].prev, nx = nodes[u].next;
        if (nx >= 0) nodes[nx].prev = pv;
        if (pv >= 0) nodes[pv].next = nx;
        else head[h] = nx;
    }
    void insert(int h, int u) {
        nodes[u] = {-1, head[h]};
        if (head[h] >= 0) nodes[head[h]].prev = u;
        head[h] = u;
    }
    template<typename F>
    void erase_all(int first, int last, F f) {
        for (int i = first; i <= last; ++i) {
            for (int h = head[i]; h >= 0; h = nodes[h].next) f(
                h);
            head[i] = -1;
        }
    }
};
```

CustomComparator.h

1e3970, 6 lines

```
auto cmp = [] (const kind_t& a, const kind_t& b) {
    return a.func() < b.func();
};
set<kind_t, decltype(cmp)> my_set(cmp);
map<kind_t, int, decltype(cmp)> my_map(cmp);
priority_queue<kind_t, vector<kind_t>, decltype(cmp)> my_pq(cmp
);
```

Floor.h

e7f4c9, 7 lines

```
template<typename T> T mfloor(T a, T b) {
    return a / b - (((a ^ b) < 0 && a % b != 0) ? 1 : 0);
}

template<typename T> T mceil(T a, T b) {
    return a / b + (((a ^ b) > 0 && a % b != 0) ? 1 : 0);
}
```

10.6 Bit Twiddling Hack

Hacks.h

59c333, 51 lines

```
// Returns one plus the index of the least significant 1-bit of
x, or if x is zero, returns zero.
__builtin_ffs(x)

// Returns the number of leading 0-bits in x, starting at the
most significant bit position. If x is 0, the result is
undefined.
__builtin_clz(x)

// Returns the number of trailing 0-bits in x, starting at the
least significant bit position. If x is 0, the result is
undefined.
__builtin_ctz(x)

// Returns the number of 1-bits in x.
__builtin_popcount(x)
```

```
// For long long versions append ll (e.g. __builtin_popcountll)

// Least significant bit in x.
x & -x

// Iterate on non-empty submasks of a bitmask.
for (int submask = mask; submask > 0; submask = (mask & (
    submask - 1)))

// Iterate on non-zero bits of a bitset.
for (int j = bitset._Find_next(0); j < MAXV; j = bitset.
    _Find_next(j))

int __builtin_clz(int x); // number of leading zero
int __builtin_ctz(int x); // number of trailing zero
int __builtin_clzll(int x); // number of leading zero
int __builtin_ctzll(int x); // number of trailing zero
int __builtin_popcount(int x); // number of 1-bits in x
int __builtin_popcountll(int x); // number of 1-bits in x

// compute next perm. i.e. 00111, 01011, 01101, 10011, ...
lint next_perm(lint v) {
    lint t = v | (v-1);
    return (t + 1) | (((~t & ~t) - 1) >> (__builtin_ctz(v) +
        1));
}

template<typename F> // All subsets of size k of {0..N-1}
void iterate_k_subset(ll N, ll k, F f){
    ll mask = (1ll << k) - 1;
    while (!(mask & 1ll<<N)) { f(mask);
        ll t = mask | (mask-1);
        mask = (t+1) | (((~t & ~t) - 1) >> (__builtin_ctzll(mask)
            +1));
    }
}

template<typename F> // All subsets of set
void iterate_mask_subset(ll set, F f){ ll mask = set;
    do f(mask), mask = (mask-1) & set;
    while (mask != set);
}
```

Bitset.h

Description: Some bitset functions 2859c6, 5 lines

```
int main() {
    bitset<100> bt;
    cin >> bt;
    cout << bt[0] << "\n";
    cout << bt.count() << "\n"; // number of bits set
    cout << (~bt).none() << "\n"; // return true if has no bits
        set
    cout << (~bt).any() << "\n"; // return true if has any bit
        set
    cout << (~bt).all() << "\n"; // retun true if has all bits
        set
    cout << bt._Find_first() << "\n"; // return first set bit
    cout << bt._Find_next(10) << "\n"; // returns first set bit
        after index i
    cout << bt.flip() << '\n'; // flip the bitset
    cout << bt.test(3) << '\n'; // test if the ith bit of bt is
        set
    cout << bt.reset(3) << '\n'; // reset the ith bit
    cout << bt.set() << '\n'; // turn all bits on
    cout << bt.set(4, 1) << '\n'; // set the 4th bit to value 1
    cout << bt << "\n";
}
```

10.7 Random Numbers

RandomNumbers.h

Description: An example on the usage of generator and distribution. Use shuffle instead of random shuffle. 2859c6, 5 lines

```
mt19937 rng(random_device{}());
mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().
    count());
shuffle(permutation.begin(), permutation.end(), rng);
uniform_int_distribution<int> uid(1, 100); // [1, 100]
        inclusive!
uniform_real_distribution<double> urd(1, 100);
```

10.8 Other languages

MiscJava.java

Description: Basic template/info for Java 186de5, 47 lines

```
import java.math.BigInteger;
import java.util.*;

public class prob4 {
    void run() {
        Scanner scanner = new Scanner(System.in);
        while (scanner.hasNextBigInteger()) {
            BigInteger n = scanner.nextBigInteger();
            int k = scanner.nextInt();
            if (k == 0) {
                for (int p = 2; p <= 100000; p++) {
                    BigInteger bp = BigInteger.valueOf(p);
                    if (n.mod(bp).equals(BigInteger.ZERO)) {
                        System.out.println(bp.toString() + " * " + n.divide
                            (bp).toString());
                        break;
                    }
                }
            } else {
                BigInteger ndivk = n.divide(BigInteger.valueOf(k));
                BigInteger sqndivk = sqrt(ndivk);
                BigInteger left = sqndivk.subtract(BigInteger.valueOf
                    (100000)).max(BigInteger.valueOf(2));
                BigInteger right = sqndivk.add(BigInteger.valueOf
                    (100000));
                for (BigInteger p = left; p.compareTo(right) != 1; p =
                    p.add(BigInteger.ONE)) {
                    if (n.mod(p).equals(BigInteger.ZERO)) {
                        BigInteger q = n.divide(p);
                        System.out.println(p.toString() + " * " + q.
                            toString());
                        break;
                    }
                }
            }
        }
        BigInteger sqrt(BigInteger n) {
            BigInteger left = BigInteger.ZERO;
            BigInteger right = n;
            while (left.compareTo(right) != 1) {
                BigInteger mid = left.add(right).divide(BigInteger.
                    valueOf(2));
                int s = n.compareTo(mid.multiply(mid));
                if (s == 0) return mid;
                if (s > 0) left = mid.add(BigInteger.ONE); else right =
                    mid.subtract(BigInteger.ONE);
            }
            return right;
        }
    }
    public static void main(String[] args) {
        (new prob4()).run();
    }
}
```