Option 4 · DC1 and DC2 lab paths on one host, side by side

DC1 lab path · vamd-dc1-p3

18 nodes · 43 cables · mgmt network vamd-dc1-mgmt 10.250.0.0/24

- DC1-HOST-ISP-A / B
- DC1-ISP-A / ISP-B (carriers)
- DC1-ISP1 / ISP2 · AS65050
- DC1-EDGE1 / EDGE2 (L2)
- DC1-INETFW1 · AS65140 · NAT 198.51.100.0/24
- DC1-S1 / S2 (spines) · AS65100
- DC1-BL1/BL2 · DC1-L11 · DC1-SL1/SL2
- DC1-INTFW1 (Internal FW)

PROD test host on L11 · about 80 GB · details: the DC1 lab path PDF

no link

no BGW, no DCI

DC2 lab path · vamd-dc2-p3

17 nodes · 42 cables · mgmt network vamd-dc2-mgmt 10.250.16.0/24

- DC2-HOST-ISP-A / B
- DC2-ISP-A / ISP-B (carriers)
- DC2-ISP1 / ISP2 · AS65050
- DC2-EDGE1 / EDGE2 (L2)
- DC2-INETFW1 · AS65240 · NAT 203.0.113.0/24
- DC2-S1 / S2 (spines) · AS65200
- DC2-BL1/BL2 · DC2-L11 · DC2-SL1/SL2
- DC2-INTFW1 (Internal FW)

no PROD test host · about 80 GB · details: the DC2 lab path PDF

The two labs share nothing: separate containerlab labs, separate mgmt networks, separate carriers.
Multi-Site (BGW1/2, DCI1/2 between the sites) is not in either lab path; it is in option 5 (entire DC1, with a DC2 stand-in).

What you need

Item	Value
Memory	About 160 GB free: 18 Nexus × 8 GB = 144 GB plus 17 FRR / Alpine containers
CPU	18 × 3 vCPU for the Nexus guests, KVM on the host
Status	Not run. DC1 ran alone on a 123 GB host; DC2 has never run

Bring both up (one after the other)

```
for s in DC1 DC2; do
  .venv/bin/python lab/labctl.py fetch $s --compare-baselines
  .venv/bin/python lab/labctl.py validate $s
  .venv/bin/python lab/labctl.py deploy $s
  .venv/bin/python lab/labctl.py push $s
  .venv/bin/python lab/labctl.py carve $s
done
```

Take both down

```
.venv/bin/python lab/labctl.py destroy DC1
.venv/bin/python lab/labctl.py destroy DC2
```

How to tell them apart

	DC1	DC2
Lab name	`vamd-dc1-p3`	`vamd-dc2-p3`
Containers	`clab-vamd-dc1-p3-DC1-…`	`clab-vamd-dc2-p3-DC2-…`
Mgmt network	vamd-dc1-mgmt 10.250.0.0/24	vamd-dc2-mgmt 10.250.16.0/24
Fabric AS / loopbacks	65100 / 10.19.0.0/24	65200 / 10.23.0.0/24
Public block (NAT)	198.51.100.0/24	203.0.113.0/24
Internet hosts	198.18.1.10, 198.18.2.10	198.18.1.10, 198.18.2.10 (same addresses, separate lab)
Topology file	`lab/build/DC1/topology.boot.yml`	`lab/build/DC2/topology.boot.yml`

Everything else (logins, stop/start, cutting a cable, post-checks) is the same as in each site's lab path PDF; use the site name in every command.