6.4 Thermal Information: OPA227, OPA228

THERMAL METRIC[1]		OPA227P, OPA227PA, OPA228P, OPA228PA	OPA227U, OPA227UA, OPA228U, OPA228UA	UNIT
		P (PDIP)	D (SOIC)	
		8 PINS	8 PINS	
$R_{\theta JA}$	Junction-to-ambient thermal resistance	48.9	110.1	°C/W
$R_{\theta JC(top)}$	Junction-to-case(top) thermal resistance	37.7	52.2	°C/W
$R_{\theta JB}$	Junction-to-board thermal resistance	26.1	52.3	°C/W
ψ_{JT}	Junction-to-top characterization parameter	15.1	10.4	°C/W
ψ_{JB}	Junction-to-board characterization parameter	26	51.5	°C/W
$R_{\theta JC(bot)}$	Junction-to-case(bottom) thermal resistance	N/A	N/A	°C/W

(1) For more information about traditional and new thermal metrics, see the Semiconductor and IC Package Thermal Metrics application report.

6.5 Thermal Information: OPA2227, OPA2228

THERMAL METRIC[1]		OPA2227P, OPA2227PA, OPA2228P, OPA2228PA	OPA2227U, OPA2227UA, OPA2228U, OPA2228UA	UNIT
		P (PDIP)	D (SOIC)	
		8 PINS	8 PINS	
$R_{\theta JA}$	Junction-to-ambient thermal resistance	110.1	101.9	°C/W
$R_{\theta JC(top)}$	Junction-to-case(top) thermal resistance	52.2	46.3	°C/W
$R_{\theta JB}$	Junction-to-board thermal resistance	52.3	45.5	°C/W
ψ_{JT}	Junction-to-top characterization parameter	10.4	6.6	°C/W
ψ_{JB}	Junction-to-board characterization parameter	51.5	42.8	°C/W
$R_{\theta JC(bot)}$	Junction-to-case(bottom) thermal resistance	N/A	N/A	°C/W

(1) For more information about traditional and new thermal metrics, see the Semiconductor and IC Package Thermal Metrics application report.

6.6 Thermal Information: OPA4227, OPA4228

THERMAL METRIC[1]		OPA4227P, OPA4227PA, OPA4228P, OPA4228PA	OPA4227U, OPA4227UA, OPA4228U, OPA4228UA	UNIT
		N (PDIP)	D (SOIC)	
		14 PINS	14 PINS	
$R_{\theta JA}$	Junction-to-ambient thermal resistance	65.5	65	°C/W
$R_{\theta JC(top)}$	Junction-to-case(top) thermal resistance	20	23.1	°C/W
$R_{\theta JB}$	Junction-to-board thermal resistance	25.9	20.3	°C/W
ψ_{JT}	Junction-to-top characterization parameter	1.9	1.8	°C/W
ψ_{JB}	Junction-to-board characterization parameter	25.3	19.9	°C/W
$R_{\theta JC(bot)}$	Junction-to-case(bottom) thermal resistance	N/A	N/A	°C/W

(1) For more information about traditional and new thermal metrics, see the Semiconductor and IC Package Thermal Metrics application report.

Copyright © 2023 Texas Instruments Incorporated