Dynamic, Secure Resource Control in the Cloud

Edward J. Nava, Viswanath Nandina, José Marcio Luna, Christopher C. Lamb, Gregory L. Heileman, Chaouki T. Abdallah
University of New Mexico
Department of Electrical and Computer Engineering
Albuquerque, NM 87131-0001
{ejnava, vishu, jmarcio, cclamb, heileman, chaouki}@ece.unm.edu

ABSTRACT

In this paper we describe the development of a system that provides security and performance controls over content in a cloud environment. Using artifacts that are classed at different sensitivity levels associated with service level agreements (SLAs) describing how and where they can be used, we are able to successfully provision resources in a hybrid cloud environment. These provisioned resources are created to match both performance characteristics as well as specific sensitivity restrictions specified within associated SLAs.

Categories and Subject Descriptors

D.3.0 [Software]: Programming Languages—General

General Terms

Design, Languages, Security

Keywords

Access Control, Interoperability, DRM, Usage Management

1. INTRODUCTION

With the advent and widespread use of cloud computing, those responsible for a given usage managed resource are almost never those responsible for the computing systems, except at edge devices like mobile phones or other small profile computing devices. Resources are regularly moved across national boundaries and regional areas without either the content owner's or creator's knowledge. Furthermore, this kind of transfer is generally according to pre-established algorithms or data routing protocols over which users have no control. Managing these issues requires new usage management capabilities that can run on platforms ranging from small, hand-held devices to nodes in large data centers.

Herein, we define usage management as the ability to control actions over resources and data across and within computing environments. More than access control or digital

rights management, usage management addresses with finegrained control of all aspects of how a given digital resource is used. As digital environments become more open over time, the need for usage management for resources that span utility computational environments (e.g. cloud provider systems) will become increasingly important [26, 27].

Furthermore, cloud computing is emerging as the future of utility systems hosting for consumer-facing applications. In these kinds of systems, components, applications, and hardware are provided as utilities over the Internet with associated pricing schemes pegged by system demand. Users accept specific Quality-of-Service (QoS) guidelines that providers use to provision and eventually allocate resources. These guidelines become the basis over which providers charge for services.

Over the past few years multiple service-based paradigms such as web services, cluster computing and grid computing have contributed to the development of what we now call cloud computing [12]. Cloud computing distinctly differentiates itself from other service-based computing paradigms via a collective set of distinguishing characteristics: market orientation, virtualization, dynamic provisioning of resources, and service composition via multiple service providers [13]. This implies that in cloud computing, a cloud-service consumer's data and applications reside inside that cloud provider's infrastructure for a finite amount of time. Partitions of this data can in fact be handled by multiple cloud services, and these partitions may be stored, processed and routed through geographically distributed cloud infrastructures. These activities occur within a cloud, giving the cloud consumer an impression of a single virtual system. These operational characteristics of cloud computing can raise concerns regarding the manner in which cloud consumer's data and applications are managed within a given cloud. Unlike other computing paradigms with a specific computing task focus, cloud systems enable cloud consumers to host entire applications on the cloud (i.e. software as a service) or to compose services from different providers to build a single system. As consumers aggressively start exploiting these advantages to transition IT services to external utility computing systems, the manner in which data and applications are handled within those systems by various cloud services will become a matter of serious concern [22].

A growing body of research has begun to appear over the past two years applying control theory to tuning computer systems. These range from controlling network infrastructure [8] to controlling virtualized infrastructure and specific computer systems [34], [24] to exploring feedforward solutions based on predictive modeling [6]. Significant open questions remain within this field [37], [19].

To address these issues, we first applied the principles of system design to develop a framework for usage management in open, distributed environments that supports interoperability. These principles have been used by researchers in large network design to create a balance between interoperability and open, flexible architectures [7, 11, 15], without sacrificing innovation. Initially we standardized certain features of the framework operational semantics, and left free of standards features that necessitate choice and innovation.

2. MOTIVATION

Current policy-centric systems are being forced to move to cloud environments and incorporate much more open systems. Some of these environments will be private or hybrid cloud systems, where private clouds are infrastructure that is completely run and operated by a single organization for use and provisioning, while hybrid clouds are combinations of private and public cloud systems. Driven by both cost savings and efficiency requirements, this migration will result in a loss of control of computing resources by involved organizations as they attempt to exploit economies of scale and utility computing.

Robust usage management will become an even more important issue in these environments. Federal organizations poised to benefit from this migration include agencies like the National Security Agency (NSA) and the Department of Defense (DoD), both of whom have large installed bases of compartmentalized and classified data. The DoD realizes the scope of this effort, understanding that such technical change must incorporate effectively sharing needed data with other federal agencies, foreign governments, and international organizations [3]. Likewise, the NSA is focused on using cloud-centric systems to facilitate information dissemination and sharing [5].

Cloud systems certainly exhibit economic incentives for use, providing cost savings and flexibility, but they also have distinct disadvantages as well. Specifically, the are not intrinsically as private as some current systems, generally can be less secure than department-level solutions, and have the kinds of trust issues that the best of therapists cannot adequately address [28].

How to address these issues is an open research question. Organizations ranging from cloud service providers to the military are exploring how to engineer solutions to these problems, and to more clearly understand the trade-offs required between selected system architectures [4]. The problems themselves are wide ranging, appearing in a variety of different systems. Military and other government systems are clearly impacted by these kinds of trust and security issues, and they also have clear information sensitivity problems. This, coupled with the fact that these organizations have been dealing with these issues in one form or another for decades make them very well suited for prototypical implementation and study.

Current federal standards in place to deal with these issues in this environment are managed by the Unified Cross Domain Management Office (UCDMO). UCDMO stakeholders range from the DoD to the NSA. The current standard architectural model in place and governed by the UCDMO to deal with this kinds of issues are guard-centric cross domain architectures.

Usage management incorporates specific characteristics of traditional access control and digital rights management incorporating encryption mechanisms, trust management, and trusted computing platforms [22]. In order to be effective, it must be flexible enough to provide users with opportunities for differentiation and extension, but interoperable enough to provide services across widely diverging computational environments.

3. CONCLUSIONS AND FUTURE WORKS

Usage management is a common problem set with features embodied in domains ranging from security systems to video games to music production and retail. The ability to provide management of resources with regard to authorized subjects is being addressed in multiple different forums, many of which are taking remarkably different approaches. Common features however generally include the need for either ubiquitous rights expression language acceptance or for extensive translation between all supported rights languages.

In this paper, we first demonstrated the development of the initial model used to define the problem space. Here, we described the general use of the system, who the primary users were, what the expected life-cycle of policies was, and what the domain model looked like. We then implemented the syntax of the DSL, in Ruby, as an internal DSL with specific examples. We concluded the paper with demonstrations of equivalence to common rights management frameworks like the creative commons, ODRL, and XrML.

We have only begun to specify and use this particular DSL. Future focus on this effort will include additional language elaboration, exploration, and use in specific scenarios. We need to spend additional time engineering the underlying software as well, so we can ensure that policies are in fact platform and environment agnostic, portable, and executable. Finally, this implementation is an internal DSL within the Ruby language; we need to explore the application of external DSL techniques to this domain to better understand the required compromises between expressiveness and development difficulty and begin to apply more stringent security models to the system itself.

4. REFERENCES

- Enabler release definition for DRM V2.0. Technical report, Open Mobile Alliance, 2003.
 xml.coverpages.org/OMA-ERELD_DRM-V2_0_0-20040401-D.pdf.
- [2] Open digital rights language ODRL version 2 requirements. ODRL, Feb. 2005. odrl.net/2.0/v2req.html.
- [3] DoD Information Sharing Strategy. http://cionii.defense.gov/docs/InfoSharingStrategy.pdf, May 2007.
- [4] Assured Information Sharing in Clouds.

- http://www.zyn.com/sbir/sbres/sttr/dod/af/af11-bt30.htm, August 2011.
- [5] NSA Pursues Intelligence-Sharing Architecture. http://www.informationweek.com/news/government/cloud-saas/229401646, April 2011.
- [6] S. Abdelwahed, J. Bai, R. Su, and N. Kandasamy. On the application of predictive control techniques for adaptive performance management of computing systems. *Network and Service Management, IEEE Transactions on*, 6(4):212 –225, 2009.
- [7] H. Alverstrand. The role of the standards process in shaping the internet. *Proceeding of the IEEE*, 92(9):1371–1374, 2004.
- [8] Y. Ariba, F. Gouaisbaut, and Y. Labit. Feedback control for router management and tcp/ip network stability. Network and Service Management, IEEE Transactions on, 6(4):255 –266, 2009.
- [9] A. Arnab and A. Hutchison. Persistent access control: A formal model for drm. In DRM '07: Proceedings of the 2007 ACM workshop on Digital Rights Management, pages 41–53, New York, NY, USA, 2007. ACM.
- [10] A. Barth and J. C. Mitchell. Managing digital rights using linear logic. In LICS '06: Proceedings of the 21st Annual IEEE Symposium on Logic in Computer Science, pages 127–136, Washington, DC, USA, 2006. IEEE Computer Society.
- [11] M. S. Blumenthal and D. D. Clark. Rethinking the design of the Internet: The end-to-end arguments vs. the brave new world. ACM Transactions on Internet Technology, 1(1):70–109, Aug. 2001.
- [12] R. Buyya. Market-oriented cloud computing: Vision, hype, and reality of delivering computing as the 5th utility. In Proceedings of the 2009 9th IEEE/ACM International Symposium on Cluster Computing and the Grid, CCGRID '09, pages 1-, Washington, DC, USA, 2009. IEEE Computer Society.
- [13] R. Buyya, C. S. Yeo, S. Venugopal, J. Broberg, and I. Brandic. Cloud computing and emerging IT platforms: Vision, hype, and reality for delivering computing as the 5th utility. Future Generation Computer Systems, 25(6):599-616, 2009.
- [14] C. N. Chong, R. Corin, S. Etalle, P. Hartel, W. Jonker, and Y. W. Law. LicenseScript: A novel digital rights language and its semantics. In *Third* International Conference on the Web Delivery of Music, pages 122–129, Los Alamitos, CA, Sept. 2003.
- [15] D. D. Clark, J. Wrocławski, K. R. Sollins, and R. Braden. Tussle in cyberspace: Defining tomorrow's internet. In SIGCOMM, pages 347–356, Pittsburg, Pennsylvania, USA, Aug. 2002.
- [16] J. Y. Halpern and V. Weissman. A formal foundation for XrML licenses. In *Proceedings of the 17th IEEE* Computer Security Foundations Workshop, pages 251–265, Asilomar, CA, June 2004.
- [17] J. Y. Halpern and V. Weissman. A formal foundation for XrML. J. ACM, 55(1):1–42, 2008.
- [18] G. L. Heileman and P. A. Jamkhedkar. DRM interoperability analysis from the perspective of a layered framework. In *Proceedings of the Fifth ACM*

- Workshop on Digital Rights Management, pages 17–26, Alexandria, VA, Nov. 2005.
- [19] J. Hellerstein, S. Singhal, and Q. Wang. Research challenges in control engineering of computing systems. Network and Service Management, IEEE Transactions on, 6(4):206 –211, 2009.
- [20] P. A. Jamkhedkar and G. L. Heileman. DRM as a layered system. In *Proceedings of the Fourth ACM* Workshop on Digital Rights Management, pages 11–21, Washington, DC, Oct. 2004.
- [21] P. A. Jamkhedkar and G. L. Heileman. Handbook of Research on Secure Multimedia Distribution, chapter Rights Expression Languages. IGI Publishing, 2008.
- [22] P. A. Jamkhedkar, G. L. Heileman, and C. C. Lamb. An interoperable usage management framework. In Proceedings of the tenth annual ACM workshop on Digital rights management, DRM '10, pages 73–88, New York, NY, USA, 2010. ACM.
- [23] P. A. Jamkhedkar, G. L. Heileman, and I. Martinez-Ortiz. The problem with rights expression languages. In *Proceedings of the Sixth ACM Workshop* on *Digital Rights Management*, pages 59–67, Alexandria, VA, Nov. 2006.
- [24] M. Kjaer, M. Kihl, and A. Robertsson. Resource allocation and disturbance rejection in web servers using slas and virtualized servers. *Network and Service Management, IEEE Transactions on*, 6(4):226 –239, 2009.
- [25] R. H. Koenen, J. Lacy, M. MacKay, and S. Mitchell. The long march to interoperable digital rights management. *Proceedings of the IEEE*, 92(6):883–897, 2004.
- [26] C. C. Lamb, P. A. Jamkhedkar, G. L. Heileman, and C. T. Abdallah. Managed control of composite cloud systems. In 6th IEEE International Conference on System of Systems Engineering (SOSE). IEEE.
- [27] C. C. Lamb, P. A. Jamkhedkar, G. L. Heileman, and C. T. Abdallah. Managed control of composite cloud systems. In System of Systems Engineering (SoSE), 2011 6th International Conference on, pages 167 –172, june 2011.
- [28] S. Pearson and A. Benameur. Privacy, security and trust issues arising from cloud computing. In Cloud Computing Technology and Science (CloudCom), 2010 IEEE Second International Conference on, pages 693 -702, 30 2010-dec. 3 2010.
- [29] J. Polo, J. Prados, and J. Delgado. Interoperability between ODRL and MPEG-21 REL. In *Proceedings of the first international ODRL workshop*, Vienna, Austria, Apr. 2004.
- [30] R. Pucella and V. Weissman. A logic for reasoning about digital rights. In *Proceedings of the 15th IEEE Computer Security Foundations Workshop*, pages 282–294, Nova Scotia, Canada, June 2002.
- [31] R. Safavi-Naini, N. P. Sheppard, and T. Uehara. Import/export in digital rights management. In Proceedings of the Fourth ACM Workshop on Digital Rights Management, pages 99–110, Washington, DC, Oct. 2004.
- [32] A. U. Schmidt, O. Tafreschi, and R. Wolf. Interoperability challenges for DRM systems. In IFIP/GI Workshop on Virtual Goods, Ilmenau,

- Germany, 2004. http://virtualgoods.tu-ilmenau.de/2004/program.html.
- [33] X. Wang. MPEG-21 rights expression language: Enabling interoperable digital rights management. *IEEE Multimedia*, 11(4):84–87, Oct./Dec. 2004.
- [34] Z. Wang, Y. Chen, D. Gmach, S. Singhal, B. Watson, W. Rivera, X. Zhu, and C. Hyser. Appraise: application-level performance management in virtualized server environments. Network and Service Management, IEEE Transactions on, 6(4):240 –254, 2009.
- [35] J. Xiang, D. Bjorner, and K. Futatsugi. Formal digital license language with OTS/CafeOBJ method. In Proceedings of the sixth ACS/IEEE International Conference on Computer Systems and Applications, Doha, Qatar, Apr. 2008.
- [36] eXtensible Rights Markup Language (XrML) 2.0 Specification, November 2001. www.xrml.org.
- [37] X. Zhu, M. Uysal, Z. Wang, S. Singhal, A. Merchant, P. Padala, and K. Shin. What does control theory bring to systems research? SIGOPS Oper. Syst. Rev., 43:62–69, January 2009.