

Signal	Direction	FPGA pin	Diablo	Connected	IDC50 pin	drive pullup	terminator	pcb term	unused	Option only
Strobe_L	T	11	SS	X	4		220/510	10K		
Head_Select_L	T	12	AA	X	6		220/510	10K		
Rd_Gate_L	T	13	E	X	10		220/510	10K		
Track7	T	34	BB	X	36		220/510	10K		
Track6	T	35	T	X	32		220/510	10K		
Track5	T	36	FF	X	30		220/510	10K		
Track4	T	37	X	X	26		220/510	10K		
Track3	T	38	J	X	22		220/510	10K		
Track2	T	39	RR	X	18		220/510	10K		
Track1	T	40	N	X	16		220/510	10K		
Track0	T	41	LL	X	12		220/510	10K		
Write_Clk_Data_L	T	10K pullup	B	X	44		120/300	10K	X	
Restore_L	T	10K pullup	VV	X	40		220/510	10K	X	
Write_Gate_L	T	10K pullup	EE	X	42		120/300	10K	X	
write protect	T	10K pullup	H	X	46		220/510	10K	X	X
erase gate	T	10K pullup	K	X	48		220/510	10K	X	X
Select 4	T	10K pullup	Z				220/510		X	
Select 3	T	10K pullup	V				220/510		X	
Select 2	T	10K pullup	R				220/510		X	
Select 1	G	ground	L	X	50		220/510	grounded		
ground	G	ground	D, DD, WW	X	odd #s					
Ready_Seek_L	F	0	F	X	38	5V/10K		120/300		
Seek_Incomp_L	F	1	TT	X	34	5V/10K		120/300		
Rd_Data_L	F	2	C	X	28	3V/diode	120/300	120/300		
Rd_Clk_L	F	3	A	X	24	3V/diode	120/300	120/300		
Log_Addr_Inlk_L	F	4	XX	X	20	5V/10K		120/300		X
SM_L	F	5	W	X	14	3V/diode		120/300		
IM_L	F	6	Y	X	8	3V/diode		120/300		
Addr_Ack_L	F	7	NN	X	2	5V/10K		120/300		
File_Ready_L	F		U			5V/10K			X	
Write_Check_L	F		HH			5V/10K			X	
Sector4	F		UU			5V/10K			X	
Sector 3	F		MM			5V/10K			X	
Sector 2	F		KK			5V/10K			X	
Sector 1	F		JJ			5V/10K			X	
Sector 0	F		CC			5V/10K			X	

Pseudo_SM_L	F	S	5V/10K	220/510	X	X
HD_L	F	M	5V/10K		X	X
Write protect indicator	F	P	5V/10K		X	X
+5 terminator power	F	PP			X	