

# Memory Management


*Changwoo Min*

# Today: Memory Management

- Pages and zones
- Page allocation
- kmalloc, vmalloc
- Slab allocator
- Stack, high memory, per-CPU data structures

# Pages

- Memory is divided into **physical pages** or **frames**



- The **page** is the basic management unit in the kernel
- Page size is machine-dependent
  - Determined by the the memory management unit (MMU) support
  - 4 KB** in general, some are 2 MB and 1 GB: `getconf PAGESIZE`

# Pages

- Each **physical page** is represented by `struct page`
- Defined in `include/linux/mm_types.h`

```
struct page {  
    unsigned long flags;    /* page status (permission, dirty, etc.) */  
    unsigned counters;     /* usage count */  
    struct address_space *mapping; /* address space mapping */  
    pgoff_t index;         /* offset within the mapping */  
    struct list_head lru;  /* LRU list buffer cache */  
    void *virtual;        /* virtual address */  
}
```

# Pages

- The kernel uses `struct page` to keep track of the owner of the page
  - User-space process, kernel statically/dynamically allocated data, page cache, etc.
- There is one `struct page` object per physical memory page
  - `sizeof(struct page)` : 64 bytes
  - Assuming 8GB of RAM and 4K-sized pages: 128MB reserved for `struct page` objects (~1.5%)

# Zones


- Certain contexts require certain physical pages due to hardware limitations
  - Some devices can only access the lowest 16 MB of physical memory
  - High memory should be mapped before being accessed
- Physical memory is partitioned into **zones** having the same constraints
  - Zone layout is architecture- and machine-dependent
- Page allocator considers the constraints while allocating pages

# Zones


Name	Description
ZONE_DMA	Pages can be used for DMA
ZONE_DMA32	Pages for 32-bit DMA devices
ZONE_NORMAL	Pages always mapped to the address space
ZONE_HIGHMEM	Pages should be mapped prior to access

# Zones

- x86\_32 zones layout



- x86\_64 zones layout





# Zones


- Each zone is managed with `struct zone` data structure defined in `include/linux/mmzone.h`

```
struct zone {  
    const char *name;           /* Name of this zone */  
    unsigned long zone_start_pfn; /* starting page frame number of the zone */  
    unsigned long watermark[NR_WMARK];  
                                /* minimum, low, and high watermarks  
                                * for per-zone memory allocation */  
    spinlock_t lock; /* protects against concurrent accesses */  
    struct free_area free_area[MAX_ORDER];  
                                /* list of free pages of different sizes */  
}
```

# Memory layout (x86\_32)

# Memory layout (x86\_32)

# Hierarchy of memory allocators




# Low-level memory allocator (Buddy system)

- Low-level mechanisms to allocate memory at the *page* granularity
- Interfaces in `include/linux/gfp.h`

# Buddy system

- Prevent memory from being fragmented



# Status of Buddy System

```
$> cat /proc/buddyinfo
```

```
Node 0, zone DMA 1 0 0 1 2 1 1 0
      1 1 2
Node 0, zone DMA32 9 7 8 9 7 11 8 7
      8 9 525
Node 0, zone Normal 18184 5454 2414 2628 1562 727 254 721
      999 451 4352
```

# Page allocation / deallocation

```
/**
 * Allocate 2^{order} *physically* contiguous pages
 * Return the address of the first allocated `struct page`
 */
struct page *alloc_pages(gfp_t gfp_mask, unsigned int order);
struct page *alloc_page(gfp_t gfp_mask);

/**
 * Deallocate 2^{order} *physically* contiguous pages
 * Be careful to put the correct order otherwise corrupt the memory
 */
void __free_pages(struct page *page, unsigned int order);
void __free_page(struct page *page);
```



# Page access

```
/**
 * Obtain the virtual address to the page frame
 */
void *page_address(struct page *page);

/**
 * Allocate and get the virtual address directly
 */
unsigned long __get_free_pages(gfp_t gfp_mask, unsigned int order);
unsigned long __get_free_page(gfp_t gfp_mask);

/**
 * Free pages using their addresses
 */
void free_pages(unsigned long addr, unsigned int order);
void free_page(unsigned long addr);
```

# Allocate zeroed page

- By default, the page *data* is not cleared
- May leak information through the page allocation
- To prevent information leakage, allocate a zero-out page for user-space request
  - `unsigned long get_zeroed_page(gfp_t gfp_mask);`

# **gfp\_t**: get free page flags

- Specify options for memory allocation
  - Action modifier
    - How the memory should be allocated
  - Zone modifier
    - From which zone the memory should be allocated
  - Type flags
    - Combination of action and zone modifiers
    - Generally preferred compared to the direct use of action/zone
- Defined in `include/linux/gfp.h`

# **gfp\_t**: action modifiers

Flag	Description
<code>__GFP_WAIT</code>	Allocator may sleep
<code>__GFP_HIGH</code>	Allocator can access emergency pools
<code>__GFP_IO</code>	Allocator can start disk IO
<code>__GFP_FS</code>	Allocator can start filesystem IO
<code>__GFP_NOWARN</code>	Allocator does not print failure warnings
<code>__GFP_REPEAT</code>	Repeat the allocation if it fails
<code>__GFP_NOFAIL</code>	The allocation is guaranteed
<code>__GFP_NORETRY</code>	No retry on allocation failure

## **gfp\_t**: action modifiers

- Some action modifiers can be used together

```
struct page *p = alloc_page(__GFP_WAIT | __GFP_FS | __GFP_IO);
```

# **gfp\_t**: zone modifiers

Flag	Description
<b>__GFP_DMA</b>	Allocate only from <b>ZONE_DMA</b>
<b>__GFP_DMA32</b>	Allocate only from <b>ZONE_DMA32</b>
<b>__GFP_HIGHMEM</b>	Allocate from <b>ZONE_HIGHMEM</b> or <b>ZONE_NORMAL</b>

- If not specified, allocated from **ZONE\_NORMAL** or **ZONE\_DMA** (high preference to **ZONE\_NORMAL** )

## **gfp\_t**: type flags

- **GFP\_ATOMIC**: Allocate without sleeping
  - **\_\_GFP\_HIGH**
- **GFP\_NOWAIT**: Same to **GFP\_ATOMIC** but does not fall back to the emergency pools

## `gfp_t`: type flags

- `GFP_NOIO` : Can block but does not initiate disk IO
  - Used in block layer code to avoid recursion
  - `__GFP_WAIT`
- `GFP_NOFS` : Can block and perform disk IO, but does not initiate filesystem operations
  - Used in filesystem code
  - `__GFP_WAIT | __GFP_IO`



## **gfp\_t** : type flags

- **GFP\_KERNEL** : Default. Can sleep and perform IO
  - **\_\_GFP\_WAIT** | **\_\_GFP\_IO** | **\_\_GFP\_FS**
- **GFP\_USER** : Normal allocation for user-space memory
- **GFP\_HIGHUSER** : Normal allocation for user-space memory
  - **GFP\_USER** | **\_\_GFP\_HIGHMEM**
- **GFP\_DMA** : Allocate from **ZONE\_DMA**

# **gfp\_t**: Cheat sheet

Context	Solution
Process context, can sleep	GFP_KERNEL
Process context, cannot sleep	GFP_ATOMIC
Interrupt handler	GFP_ATOMIC
Softirq, tasklet	GFP_ATOMIC
DMA-able, can sleep	GFP_DMA   GFP_KERNEL
DMA-able, cannot sleep	GFP_DMA   GFP_ATOMIC

# Low-level memory allocation example

```
#include <linux/module.h>
#include <linux/kernel.h>
#include <linux/init.h>
#include <linux/gfp.h>

#define PRINT_PREF          "[LOWLEVEL]: "
#define PAGES_ORDER_REQUESTED 3
#define INTS_IN_PAGE        (PAGE_SIZE/sizeof(int))

unsigned long virt_addr;

static int __init my_mod_init(void)
{
    int *int_array;
    int i;

    printk(PRINT_PREF "Entering module.\n");

    virt_addr = __get_free_pages(GFP_KERNEL, PAGES_ORDER_REQUESTED);
    if(!virt_addr) {
        printk(PRINT_PREF "Error in allocation\n");
        return -1;
    }
}
```

# Low-level memory allocation example

```
int_array = (int *)virt_addr;
for(i=0; i<INTS_IN_PAGE; i++)
    int_array[i] = i;

for(i=0; i<INTS_IN_PAGE; i++)
    printk(PRINT_PREF "array[%d] = %d\n", i, int_array[i]);

return 0;
}

static void __exit my_mod_exit(void)
{
    free_pages(virt_addr, PAGES_ORDER_REQUESTED);
    printk(PRINT_PREF "Exiting module.\n");
}

module_init(my_mod_init);
module_exit(my_mod_exit);

MODULE_LICENSE("GPL");
```

# High memory

- On x86\_32, physical memory above 896 MB is not permanently mapped within the kernel address space
  - Due to the limited size of the address space and the 1/3 GB kernel/user-space memory split
- Before use, pages from highmem should be mapped to the address space

# High memory

```
/**
 * Permanent mappings
 * - Maps the `page` and return the address to the `page`
 * - May sleep
 * - Has a limited number of slots
 */
void *kmap(struct page *page);
void kunmap(struct page *page);

/**
 * Temporary mappings
 * - Use a per-CPU pre-reserved mapping slots
 * - Disable kernel preemption
 * - Should not sleep while holding the mapping
 */
void *kmap_atomic(struct page *page);
void kunmap_atomic(void *addr);
```

# High memory

- Example

```
struct page *my_page;  
void *my_addr;  
  
my_page = alloc_page(GFP_HIGHUSER);  
my_addr = kmap(my_page);  
  
memcpy(my_addr, buffer, sizeof(buffer));  
  
kunmap(my_page);  
__free_page(my_page);
```

# `kmalloc()` / `kfree()`

- `void *kmalloc(size_t size, gfp_t flags)`
  - Allocates byte-sized chunks of memory
  - Similar to the user-space `malloc()`
    - Returns a pointer to the first allocated byte on success
    - Returns NULL on error
  - Allocated memory is *physically contiguous*
- `void kfree(const void *ptr)`
  - Free the memory allocated with `kmalloc()`



# kmalloc() / kfree()

- Example

```
struct my_struct *p;  
  
p = kmalloc(sizeof(*p), GFP_KERNEL);  
if (!p) {  
    /* Handle error */  
} else {  
    /* Do something */  
    kfree(p);  
}
```

# `vmalloc()`

- `void *vmalloc(unsigned long size)`
  - Allocates *virtually contiguous* chunk of memory
    - May not be physically contiguous
    - Cannot be used for I/O buffers requiring physically contiguous memory
  - Used for allocating a large virtually contiguous memory chunk
  - May sleep so cannot be called from interrupt context
- Free using `vfree()`
  - `void vfree(const void *addr)`

# `vmalloc()`

- However, most of the kernel uses `kmalloc()` for performance reasons
  - Pages allocated with `kmalloc()` are directly mapped
  - Less overhead in virtual to physical mapping setup and translation
- `vmalloc()` is still needed to allocate large portions of memory
- Declared in `include/linux/vmalloc.h`

# vmalloc() vs. kmalloc()

```
#include <linux/module.h>
#include <linux/kernel.h>
#include <linux/init.h>
#include <linux/slab.h>

#define PRINT_PREF "[KMALLOC_TEST]: "

static int __init my_mod_init(void)
{
    unsigned long i;
    void *ptr;

    printk(PRINT_PREF "Entering module.\n");

    for(i=1;;i*=2) {
        ptr = kmalloc(i, GFP_KERNEL);
        if(!ptr) {
            printk(PRINT_PREF "could not allocate %lu bytes\n", i);
            break;
        }
        kfree(ptr);
    }
}
```

# `vmalloc()` vs. `kmalloc()`

```
    return 0;
}

static void __exit my_mod_exit(void)
{
    printk(KERN_INFO "Exiting module.\n");
}

module_init(my_mod_init);
module_exit(my_mod_exit);

MODULE_LICENSE("GPL");
```

# vmalloc() vs. kmalloc()


```

pierre@bulbi: ~/Desktop/VM
root@debian:~# insmod kmalloc_test.ko
12.949562] kmalloc_test: loading out-of-tree module taints kernel.
12.950338] [KMALLOC_TEST]: Entering module.
12.950746] -----[ cut here ]-----
12.951171] WARNING: CPU: 1 PID: 2071 at mm/page_alloc.c:3541 __alloc_pages_s
Lowpath+0x9de/0xb10
12.951894] Modules linked in: kmalloc_test(0+)
12.952320] CPU: 1 PID: 2071 Comm: insmod Tainted: G          0  4.10.4 #5
12.952908] Hardware name: QEMU Standard PC (i440FX + PIIX, 1996), BIOS Ubuntu
U-1.8.2-1ubuntu2 04/01/2014
12.953315] Call Trace:
12.953315] dump_stack+0x4d/0x66
12.953315] __warn+0xc6/0xe0
12.953315] warn_slowpath_null+0x18/0x20
12.953315] __alloc_pages_slowpath+0x9de/0xb10
12.953315] ? get_page_from_freelist+0x514/0xa80
12.953315] ? serial8250_console_putchar+0x22/0x30
12.953315] ? wait_for_xmitr+0x90/0x90
12.953315] __alloc_pages_nodemask+0x183/0x1f0
12.953315] alloc_pages_current+0x9e/0x150
12.953315] kmalloc_order_trace+0x29/0xe0
12.953315] _kmalloc+0x18c/0x1a0
12.953315] ? __free_pages+0x13/0x20
12.953315] my_mod_init+0x23/0x49 [kmalloc_test]
12.959278] ? 0xfffffffffa0002000
12.959278] do_one_initcall+0x3e/0x160
12.959278] ? kmem_cache_alloc_trace+0x33/0x150
12.959278] do_init_module+0x5a/0x1c9
12.959278] load_module+0x1dd4/0x23f0
12.959278] ? __symbol_put+0x40/0x40
12.959278] ? kernel_read_file+0x19e/0x1c0
12.959278] ? kernel_read_file_from_fd+0x44/0x70
12.959278] SYSC_finit_module+0xba/0xc0
12.959278] SyS_finit_module+0x9/0x10
12.959278] entry_SYSCALL_64_fastpath+0x13/0x94
12.959278] RIP: 0033:0x7f7ef56495b9
12.959278] RSP: 002b:00007fff22a92f78 EFLAGS: 00000206 ORIG_RAX: 0000000000
00139
12.959278] RAX: ffffffffef56495b9 RBX: 00007f7ef590a620 RCX: 00007f7ef56495b9
12.959278] RDX: 0000000000000000 RSI: 000055a2bd49b3d9 RDI: 0000000000000003
12.959278] RBP: 00000000000001021 R08: 0000000000000000 R09: 00007f7ef590cf20
12.959278] R10: 0000000000000003 R11: 0000000000000206 R12: 000055a2bf0091c0
12.959278] R13: 000055a2bf0091b0 R14: 00000000000001018 R15: 00007f7ef590a678
12.971803] ---[ end trace 3bed3649938d2598 ]---
12.972456] [KMALLOC_TEST]: could not allocate 8388608 bytes
root@debian:~#

```

# Slab allocator

- Allocating/freeing data structures is done very often in the kernel
- **Q: how to make memory allocation faster? → caching using a free list**
- **Free lists:**
  - Block of pre-allocated memory for a given type of data structure
  - Allocate from the free list = pick an element in the free list
  - Deallocate an element = add an element to the free list



# Slab allocator


- Issue with ad-hoc free lists: no global control
  - **When and how to free free lists?**
- **Slab allocator**
  - Generic allocation caching interface
  - Cache **objects** of a data structure type
    - E.g., an object cache for `struct task_struct`
  - Consider the data structure size, page size, NUMA, and cache coloring



# Slab allocator

- A cache has one or more **slabs**
  - One or several physically contiguous pages
- **Slabs** contain **objects**
- A slab may be empty, partially full, or full
- Allocate objects from the partially full slabs to prevent memory fragmentation

# Slab allocator




# Slab allocator

```
/**
 * Create a cache for a data structure type
 */
struct kmem_cache *kmem_cache_create(
    const char *name,      /* Name of the cache */
    size_t size,          /* Size of objects */
    size_t align,         /* Offset of the first element
                           within pages */
    unsigned long flags, /* Options */
    void (*ctor)(void *) /* Constructor */
);

/**
 * Destroy the cache
 * - Should be only called when all slabs in the cache are empty
 * - Should not access the cache during the destruction
 */
void kmem_cache_destroy(struct kmem_cache *cachep);
```

# Slab allocator

- `SLAB_HW_CACHEALIGN`
  - Align objects to the cache line to prevent false sharing
  - Increase memory footprint



# Slab allocator

- **SLAB\_POISON**
  - Initially fill slabs with a known value( `0xa5a5a5a5` ) to detect accesses to uninitialized memory
- **SLAB\_RED\_ZONE**
  - Put extra padding around objects to detect overflows
- **SLAB\_PANIC**
  - Panic if allocation fails
- **SLAB\_CACHE\_DMA**
  - Allocate from DMA-enabled memory

# Slab allocator

```
/**  
 * Allocate an object from the cache  
 */  
void *kmem_cache_alloc(struct kmem_cache *cachep, gfp_t flags);  
  
/**  
 * Free an object allocated from a cache  
 */  
void kmem_cache_free(struct kmem_cache *cachep, void *objp);
```

# Slab allocator example

```
#include <linux/module.h>
#include <linux/kernel.h>
#include <linux/init.h>
#include <linux/slab.h>

#define PRINT_PREF "[SLAB_TEST] "

struct my_struct {
    int int_param;
    long long_param;
};

static int __init my_mod_init(void)
{
    int ret = 0;
    struct my_struct *ptr1, *ptr2;
    struct kmem_cache *my_cache;

    printk(PRINT_PREF "Entering module.\n");

    my_cache = kmem_cache_create("lkp-cache", sizeof(struct my_struct),
                                0, 0, NULL);
```

# Slab allocator example

```
ptr1 = kmem_cache_alloc(my_cache, GFP_KERNEL);
if(!ptr1){
    ret = -ENOMEM;
    goto destroy_cache;
}

ptr2 = kmem_cache_alloc(my_cache, GFP_KERNEL);
if(!ptr2){
    ret = -ENOMEM;
    goto freeptr1;
}

ptr1->int_param = 42;
ptr1->long_param = 42;
ptr2->int_param = 43;
ptr2->long_param = 43;

printk(PRINT_PREF "ptr1 = {%d, %ld} ; ptr2 = {%d, %ld}\n", ptr1->int_param,
        ptr1->long_param, ptr2->int_param, ptr2->long_param);

kmem_cache_free(my_cache, ptr2);
```



# Slab allocator example

```
freeptr1:
    kmem_cache_free(my_cache, ptr1);

destroy_cache:
    kmem_cache_destroy(my_cache);

    return ret;
}

static void __exit my_mod_exit(void)
{
    printk(KERN_INFO "Exiting module.\n");
}

module_init(my_mod_init);
module_exit(my_mod_exit);

MODULE_LICENSE("GPL");
```

## Status of Slab allocator

```
$> sudo cat /proc/slabinfo
slabinfo - version: 2.1
# name                <active_objs> <num_objs> <objsize> <objperslab> <pagesperslab>
                    : tunables <limit> <batchcount> <sharedfactor> : slabdata <active_slabs>
                    <num_slabs> <sharedavail>
nf_contrack           575      675      320      25      2 : tunables      0      0      0 :
      slabdata        27      27        0
rpc_inode_cache       46      46      704      46      8 : tunables      0      0      0 :
      slabdata         1        1        0
fat_inode_cache       133     176      744      44      8 : tunables      0      0      0 :
      slabdata         4        4        0
fat_cache             0        0      40     102      1 : tunables      0      0      0 :
      slabdata         0        0        0
squashfs_inode_cache  368     368      704      46      8 : tunables      0      0      0 :
      slabdata         8        8        0
kvm_async_pf          0        0     136      30      1 : tunables      0      0      0 :
      slabdata         0        0        0
kvm_vcpu              0        0    15104       2      8 : tunables      0      0      0 :
      slabdata         0        0        0
kvm_mmu_page_header   0        0     168      24      1 : tunables      0      0      0 :
      slabdata         0        0        0
x86_emulator          0        0     2672     12      8 : tunables      0      0      0 :
      slabdata         0        0        0
```

# Slab allocator variants

- **SLOB (Simple List Of Blocks)**
  - Used in early Linux version (from 1991)
  - Low memory footprint, suitable for embedded systems
- **SLAB**
  - Integrated in 1999
  - Cache-friendly
- **SLUB**
  - Integrated in 2008
  - Improved scalability over SLAB on many cores

# Per-CPU data structure

- Allow each core to have their own values
  - No locking required
  - Reduce cache thrashing
- Implemented through arrays in which each index corresponds to a CPU

```
unsigned long my_percpu[NR_CPUS];  
int cpu;  
cpu = get_cpu();    /* get_cpu() disables kernel preemption  
                    * otherwise `cpu` might become incorrect  
                    * across context switches */  
  
my_percpu[cpu]++;  
put_cpu();          /* put_cpu() enables kernel preemption */
```

# Per-CPU API

- Defined in `include/linux/percpu.h`

```
DEFINE_PER_CPU(type, name);  
DECLARE_PER_CPU(name, type);
```

```
get_cpu_var(name); /* Start accessing the per-CPU variable */  
put_cpu_var(name); /* Done accessing the per-CPU variable */
```

```
/* Access per-CPU data through pointers */  
get_cpu_ptr(name);  
put_cpu_ptr(name);
```

```
per_cpu(name, cpu); /* Access other CPU's data */
```

# Per-CPU data structure

- Example

```
DEFINE_PER_CPU(int, my_var);

int cpu;
for (cpu = 0; cpu < NR_CPUS; cpu++)
    per_cpu(my_var, cpu) = 0;

printk("%d\n", get_cpu_var(my_var));
put_cpu_var(my_var);

int *my_var_ptr;
my_var_ptr = get_cpu_ptr(my_var);
put_cpu_ptr(my_var_ptr);
```

# Stack

- Each process has
  - A user-space stack for execution
  - A kernel stack for in-kernel execution
- **User-space stack** is large and grows dynamically
- **Kernel-stack** is small and has a fixed-size → two pages (= 8 KB)
- **Interrupt stack** is for interrupt handlers → one page for each CPU
- Reduce kernel stack usage to a minimum
  - Local variables and function parameters

# Take-away

- Need physically contiguous memory
  - `kmalloc()` or `alloc_page()` series
- Virtually contiguous chunk
  - `vmalloc()`
- Frequently creating/destroying large amount of the same data structures
  - Use the slab allocator
- Need to allocate from high memory
  - Use `alloc_page()` then `kmap()/kmap_atomic()`



# Further readings

- [Virtual Memory: 3 What is Virtual Memory?](#)
- [Complete virtual memory map x86\\_64 architecture](#)

# Next Lecture

- Process Address Space