

# Learning


Computational Cognitive Neuroscience  
Randall O'Reilly

## Overview of Learning

- Biology: synaptic plasticity
- Computation:
  - Self organizing – soaking up statistics
  - Error-driven – getting the right answers


2

### Synapses Change Strength (in response to patterns of activity)




3

### What Changes??



4

### Gettin' AMPA'd



5

### Hebbian Learning


Neurons that **fire** together, **wire** together!

$$dW = f(x \ y)$$

Change in synaptic weight is a function of both sending (x) and receiving (y) activity!


6

## Which Way?




7

## XCAL = Linearized BCM




- Bienenstock, Cooper & Munro (1982) – BCM:
- adaptive threshold  $\Theta$** 
  - Lower when less active
  - Higher when more.. (homeostatic)



8

## Threshold Does Adapt




9

## Computational: Self-Organizing and Error-Driven

- Self-organizing = learn general statistics of the world.
- Error-driven = learn from difference between expectation and outcome.
- Both can be achieved through XCAL.

10

## Floating Threshold = Long Term Average Activity (Self Org)



11

## Self Organizing Learning

- Inhibitory Competition: only some get to learn
- Rich get richer: winners detect even better
  - But also get more selective (hopefully)
- Homeostasis: keeping things more evenly distributed (higher taxes for the rich!)

12

## Limitations of Self-Organizing

Can't learn to solve challenging problems – driven by statistics, not error..

13

## Fix It!

Error-driven learning drives weight changes as a function of **errors**: directly tries to fix the problem!

Delta rule:

$$\text{Error} \quad dW = x(t - y) \quad \leftarrow t = \text{target}, y = \text{recv}, x = \text{send}$$

vs. Hebbian:

$$dW = xy$$

14

## Two Phases


**Minus** phase: guess / prediction / expectation  
(what the network comes up with)

**Plus** phase: target / outcome / reality  
(what it *should* have come up with)

$$dW = x(y^+ - y^-)$$

15


## Floating Threshold = Medium Term Synaptic Activity (Error-Driven)



$$dW = \text{Outcome} - \text{Expectation} = \langle xy \rangle_s - \langle xy \rangle_m$$


16

## Backpropagation: Mathematics of Error-driven Learning




17

## Evidence of Dynamic Thresholds (Lim, McKee, Woloszyn et al., 2015)




Threshold changes dynamically on a rapid time scale, as a function of short-term activity level!

## Where Does Error Come From?




19

## Thalamocortical Loop Biology (Sherman & Guillery, 2006)



## The Pulvinar = Projection Screen (c.f. Mumford, 1991 "blackboard")




Pulvinar receives connections from all over visual cortex

and projects back out to these same areas


Two inputs:

1. Few strong feedforward: "what happens"
2. Many weaker feedback: prediction

## Deep Predictive Learning




## Fast Threshold Adaptation: Late Trains Early




Essence of Err-Driven:  $dW = \text{outcome} - \text{expectation}$

23

## Backpropagation & GeneRec



## GeneRec: Derivative Approximation




25

## Biological Derivation of XCAL Curve

- Can use a detailed model of Spike Timing Dependent Plasticity (STDP) to derive the XCAL learning curve
- Provides a different perspective on STDP..

26


## Causal Learning?



STDP, Bi & Poo, 1998

27


## Let's Get Real..



28


## Urakubo et al, 2008 Model

- Highly detailed combination of 3 existing strongly-validated models:




29

## "Allosteric" NMDA Captures STDP (including higher-order and time integration effects)




## What About Real Spike Trains?




31

## Extended Spike Trains = Emergent Simplicity




32

## Leabra



33

## Hebbian Learns Correlations



34