

Filling your notebook with code and text

Create your first R Notebook: Steps

1. Create a new R Notebook
2. **Create Content**
 - Add text elements as Markdown syntax
 - Add code elements in any supported program language
 - Use LaTeX in your R Notebook

Elements of an R Notebook

There are three types of content in an R Notebook:

- **YAML header
(basic information)**

```
1 ---
2 title: "R Notebook"
3 output: html_notebook
4 ---
```

1 The YAML ("Yet another Markup Language") header is optional and surrounded by ---

- **Inline text**

```
11
12 ## R Markdown
13
14 This is an R Markdown document. Markdown is a simple formatting syntax
15 for authoring HTML, PDF, and MS Word documents. For more details on using
R Markdown see <http://rmarkdown.rstudio.com>.
```

2 Inline text helps you structuring your document

- **R code chunks**

```
18 ```{r cars}
19 summary(cars)
20 ```
```

3 Code chunks include your R calculations and are surrounded by ```

Elements of an R Notebook

There are three types of content in an R Notebook:

- **YAML header
(basic information)**

```
1 ---  
2 title: "R Notebook"  
3 output: html_notebook  
4 ---
```

1 The YAML ("Yet another Markup Language") header is optional and surrounded by ---

- **Inline text**

```
11  
12 ## R Markdown  
13  
14 This is an R Markdown document. Markdown is a simple formatting syntax  
15 for authoring HTML, PDF, and MS Word documents. For more details on using  
R Markdown see <http://rmarkdown.rstudio.com>.
```

2 Inline text helps you structuring your document

- **R code chunks**

```
18 ```{r cars}  
19 summary(cars)  
20 ```
```

3 Code chunks include your R calculations and are surrounded by ```

Use Markdown syntax to format the report:

Basics (1/2)

Basic Font Styles

`bold**`** and **`__bold__`**

*`*italics*`* and *`_italics_`*

~~`~scratched text~`~~

subscript^{`^2^`}

[`link`](`www.google.com`)

>This is a quote.

>

>[Author]

Use > to create
quotes ¹

bold and bold

italics and italics

~~scratched text~~

subscript²

[link](#)

This is a quote.

[Author]

Use \ to escape
special signs ²

Lines

--

...

Escape

*

\\

_

—

...

*

\

_

Use Markdown syntax to format the report:

Basics (1/2)

Basic Font Styles

`bold**`** and `__bold__`

*`*italics*`* and `_italics_`

`~~scratched text~~`

subscript^{`^2^`}

`[link](www.google.com)`

`>This is a quote.`

`>`

`>[Author]`

Use `>` to create
quotes ¹

bold and bold

italics and italics

~~scratched text~~

subscript²

[link](#)

This is a quote.

[Author]

Use `\` to escape
special signs ²

Lines

`--`

`---`

`...`

Escape

`*`

`\\`

`_`

`-`

`_____`

`...`

`*`

`\`

`_`

Use Markdown syntax to format the report:

Basics (1/2)

Basic Font Styles

`bold**`** and `__bold__`

*`*italics*`* and `_italics_`

`~~scratched text~~`

subscript^{`^2^`}

`[link](www.google.com)`

`>This is a quote.`

`>`

`>[Author]`

Use `>` to create
quotes ¹

bold and bold

italics and italics

~~scratched text~~

subscript²

[link](#)

This is a quote.

[Author]

Use `\` to escape
special signs ²

Lines

`--`

`---`

`...`

Escape

`*`

`\\`

`\`

`-`

`_____`

`...`

`*`

`\`

`-`

Use Markdown syntax to format the report: Basics (2/2)

Headers

Header 1

Header 2

Header 3

Header 4

Header 5

Header 1

Header 2

Header 3

Header 4

Header 5

Lists

Space required ¹

- * list item
- * list item
 - + list sub item
 - + list sub item

Use **two** tabs ²

1. num list item
2. num list item
3. num list item

Images

![Caption](RLogo.png)



Caption

Use Markdown syntax to format the report: Basics (2/2)

Headers

Header 1

Header 2

Header 3

Header 4

Header 5

Header 1

Header 2

Header 3

Header 4

Header 5

Lists

Space required ¹

```
* list item
* list item
  + list sub item
  + list sub item
```

Use **two** tabs ²

```
1. num list item
2. num list item
3. num list item
```

Images


![Caption](RLogo.png)



Caption

Embed code into your R Notebook: Inline R Code

Print your R results inline with other text:

6 minus 4 equals ``r` 6-4``.  6 minus 4 equals 2.

any text ``r`` + `r code here` + ``` any text

“back-tick + r + code + back-tick”


Embed code into your R Notebook:

R code chunks (1/2)

Insert R code as chunks:

```
```{r}
n <- 10
seq(10)
```
```

[1] 1 2 3 4 5 6 7 8 9 10



```
n <- 10
seq(10)
```

[1] 1 2 3 4 5 6 7 8 9 10

Hide

```
```{r}
```

r code here

```
```
```

1
Add display options
here i.e.
{r, warning =
TRUE}

“3 back-ticks + {r}
code
3 back-ticks”

| option | default | effect |
|------------|----------|---|
| eval | TRUE | Whether to evaluate the code and include its results |
| echo | TRUE | Whether to display code along with its results |
| warning | TRUE | Whether to display warnings |
| error | FALSE | Whether to display errors |
| message | TRUE | Whether to display messages |
| tidy | FALSE | Whether to reformat code in a tidy way when displaying it |
| results | "markup" | "markup", "asis", "hold", or "hide" |
| cache | FALSE | Whether to cache results for future renders |
| comment | "##" | Comment character to preface results with |
| fig.width | 7 | Width in inches for plots created in chunk |
| fig.height | 7 | Height in inches for plots created in chunk |

2
Use display
options to
show how R
Code chunks
are "treated"


Embed code into your R Notebook:

R code chunks (1/2)

Insert R code as chunks:

```
```{r}
n <- 10
seq(10)
```
```

[1] 1 2 3 4 5 6 7 8 9 10



Hide

```
n <- 10
seq(10)
```

[1] 1 2 3 4 5 6 7 8 9 10

```
```{r}
```

r code here

```
```
```

“3 back-ticks + {r}
code
3 back-ticks”

Add display options
here i.e.
{r, warning =
TRUE}

| option | default | effect |
|------------|----------|---|
| eval | TRUE | Whether to evaluate the code and include its results |
| echo | TRUE | Whether to display code along with its results |
| warning | TRUE | Whether to display warnings |
| error | FALSE | Whether to display errors |
| message | TRUE | Whether to display messages |
| tidy | FALSE | Whether to reformat code in a tidy way when displaying it |
| results | "markup" | "markup", "asis", "hold", or "hide" |
| cache | FALSE | Whether to cache results for future renders |
| comment | "##" | Comment character to preface results with |
| fig.width | 7 | Width in inches for plots created in chunk |
| fig.height | 7 | Height in inches for plots created in chunk |


Use display
options to
show how R
Code chunks
are "treated"

Embed code into your R Notebook:

R code chunks (2/2)

Code chunks may also include **plots** and **tables**:

Put any plotting function here



Variable containing an object like a
`data.table` or `data.frame`

```
{r}
cars
```

| speed
<dbl> | dist
<dbl> |
|----------------|---------------|
| 4 | 2 |
| 4 | 10 |
| 7 | 4 |
| 7 | 22 |
| 8 | 16 |
| 9 | 10 |
| 10 | 18 |
| 10 | 26 |
| 10 | 34 |
| 11 | 17 |

1-10 of 50 rows

Previous 1 2 3 4 5 Next

Use LaTeX syntax to format the report

- LaTeX is a typeset system for scientific documentation. LaTeX enables the simple construction of mathematical and statistical formulas.
- With R Notebooks, it is easy to include LaTeX documentation in your report:

Inline Latex: `$A= \pi*r^{2}$`

Inline Latex: $A = \pi * r^2$

Block equation:

`$$\sqrt{100}=10$$`

Block equation:

$$\sqrt{100} = 10$$

centered

- See i.e. <http://reu.dimacs.rutgers.edu/Symbols.pdf> for a LaTeX math cheat sheet.

Use LaTeX syntax to format the report

- LaTeX is a typeset system for scientific documentation. LaTeX enables the simple construction of mathematical and statistical formulas.
- With R Notebooks, it is easy to include LaTeX documentation in your report:

Inline Latex: `$A= \pi*r^{2}$`

Inline Latex: $A = \pi * r^2$

Block equation:

`$$\sqrt{100}=10$$`

Block equation:

$\sqrt{100} = 10$

centered

- See i.e. <http://reu.dimacs.rutgers.edu/Symbols.pdf> for a LaTeX math cheat sheet.

Use LaTeX syntax to format the report

- LaTeX is a typeset system for scientific documentation. LaTeX enables the simple construction of mathematical and statistical formulas.
- With R Notebooks, it is easy to include LaTeX documentation in your report:

Inline Latex: `$A= \pi*r^{2}$`

Inline Latex: $A = \pi * r^2$

Block equation:

`$$\sqrt{100}=10$$`

Block equation:

$$\sqrt{100} = 10$$

centered

- See i.e. <http://reu.dimacs.rutgers.edu/Symbols.pdf> for a LaTeX math cheat sheet.