








Reading data

Why data matters








"Companies are vacuuming up data **to make better decisions** about everything from product development and advertising to hiring. In their 2012 feature on big data, Andrew McAfee and Erik Brynjolfsson describe the opportunity and report that 'companies in the top third of their industry **in the use of data-driven decision making were, on average, 5% more productive and 6% more profitable than their competitors**' even after accounting for several confounding factors." (Walter Frick (2014), HBR)

Sidenote: Data comes from different sources and has different shapes and sizes

Data source	Data format examples		suffix	Package to read data
Flat files		Comma separated values	.csv	pandas
Declarative Languages (similar to a data format)		JSON	.json	json
		XML	.xml	ElementTree
Foreign data formats		Stata data files	.dta	pandas
		SPSS data files	.sav	savReaderWriter
		SAS data files	.sas	Pandas
Relational databases		SQLite		Sqlite3
		MySQL		MySQLdb








... and many more!

Sidenote: Data comes from different sources and has different shapes and sizes

Data source		Data format examples	suffix	Package to read data
Flat files		Comma separated values	.csv	pandas
Declarative Languages (similar to a data format)		JSON	.json	json
		XML	.xml	ElementTree
Foreign data formats		Stata data files	.dta	pandas
		SPSS data files	.sav	savReaderWriter
		SAS data files	.sas	Pandas
Relational databases		SQLite		Sqlite3
		MySQL		MySQLdb

... and many more!

Sidenote: Data comes from different sources and has different shapes and sizes

Data source		Data format examples	suffix	Package to read data
Flat files		Comma separated values	.csv	pandas
Declarative Languages (similar to a data format)		JSON	.json	json
		XML	.xml	ElementTree
Foreign data formats		Stata data files	.dta	pandas
		SPSS data files	.sav	savReaderWriter
		SAS data files	.sas	Pandas
Relational databases		SQLite		Sqlite3
		MySQL		MySQLdb

... and many more!

Comma separated values (CSV) and relational databases are the most common forms of data




CSV files are loaded directly into Python ¹



Data is read from an existing database ²

```
transactionData.csv
Customer,TransDate,Quantity,PurchAmount,Cost,TransID
149332,15/11/05,1,1.9995E2,107,127998739
172951,29/08/08,1,1.9995E2,108,128888288
120621,19/10/07,1,9.995E1,49,125375247
149236,14/11/05,1,3.995E1,1.895E1,127996226
149236,12/06/07,1,7.995E1,35,128670302
140729,19/11/09,1,1.2995E2,59,127637750
140729,19/11/09,1,7.995E1,3.918E1,127637750
140729,19/11/09,1,2.495E1,1.15E1,127637750
140729,19/11/09,1,7.95,2.96,127637750
140729,28/04/12,1,8.995E1,35,129377737
140729,28/04/12,1,6.995E1,2.64E1,129377737
180970,19/06/09,1,1.1995E2,5.846E1,129195647
180970,19/06/09,1,2.795E1,1.251E1,129195647
149332,13/12/05,1,4.995E1,2.487E1,129878743
149332,05/10/06,1,2.495E1,1.25E1,129883508
182927,11/02/09,2,5.99E1,1.592E1,129290963
182927,11/02/09,1,3.495E1,1.575E1,129290963
182927,11/02/09,1,1.2995E2,6.308E1,129290963
182927,11/02/09,1,2.495E1,8,129290963
```




Reading CSV data in 3 simple steps

1. Ensure your data is in CSV format or create a CSV file out of data.
2. Load data into Python.
3. Make data available for processing.



Step 1:

Create CSV out of spreadsheet



Step 1:

Create CSV out of spreadsheet

The screenshot shows a spreadsheet application with a table of transaction data. The table has columns for Customer, TransDate, Quantity, and PurchAmount. A callout window displays the CSV export of this data, showing the same information separated by commas. A yellow callout box explains that values are separated by commas, but semicolons may also be used as separators.

	A	B	C	D
1	Customer	TransDate	Quantity	PurchAmount
2	80365	19.12.2010	1	79.95
3	80365	19.12.2010	1	69.95
4	42886	21.12.2010	1	349.95
5	84374	18.04.2011	1	249.95
6	42291	03.05.2011	1	49.95
7	21451	04.05.2011	1	59.95
8	83675	21.05.2011	2	59.95
9	25737	14.08.2011	1	39.95
10	23634	19.09.2011	5	999.95
11	35844	24.12.2011	1	69.95
12	83675	24.12.2011	1	79.95
13	25737	03.01.2012	1	39.95

```


Customer,TransDate,Quantity,PurchAmount,Cost,TransID
149332,15/11/05,1,1.9995E2,107,127998739
172951,29/08/08,1,1.9995E2,108,128888288
120621,19/10/07,1,9.995E1,49,125375247
149236,14/11/05,1,3.995E1,1.895E1,127996226
149236,12/06/07,1,7.995E1,35,128670302
140729,19/11/09,1,1.2995E2,59,127637750
140729,19/11/09,1,7.995E1,3.918E1,127637750
140729,19/11/09,1,2.495E1,1.15E1,127637750
140729,19/11/09,1,7.95,2.96,127637750
140729,28/04/12,1,8.995E1,35,129377737
140729,28/04/12,1,6.995E1,2.64E1,129377737
180970,19/06/09,1,1.1995E2,5.846E1,129195647
180970,19/06/09,1,2.795E1,1.251E1,129195647
149332,13/12/05,1,4.995E1,2.487E1,129878743
149332,05/10/06,1,2.495E1,1.25E1,129883508
182927,11/02/09,2,5.99E1,1.592E1,129290963
182927,11/02/09,1,3.495E1,1.575E1,129290963
182927,11/02/09,1,1.2995E2,6.308E1,129290963
182927,11/02/09,1,2.495E1,8,129290963

```

Values are separated by commas (but you also may see semicolons ";")

Step 2:

How to load data into Python from a CSV file



Customer	TransDate	Quantity	PurchAmount	Cost
149332	15/11/05	1	199.95	107.00
172951	29/08/08	1	199.95	108.00
120621	19/10/07	1	99.95	49.00
149236	14/11/05	1	39.95	18.95
149236	12/06/07	1	79.95	35.00
...





```
pd.read_csv(input, sep=",", ...)
```

We have already
imported the
pandas library ¹

Name of CSV file ²

Step 2:

How to load data into Python from a CSV file



Customer	TransDate	Quantity	PurchAmount	Cost
149332	15/11/05	1	199.95	107.00
172951	29/08/08	1	199.95	108.00
120621	19/10/07	1	99.95	49.00
149236	14/11/05	1	39.95	18.95
149236	12/06/07	1	79.95	35.00
...



```
pd.read_csv(input, sep=",", ...)
```

We have already
imported the
pandas library ¹

Name of CSV file ²

Python Basics: A function performs a specific action and is controlled through arguments

1
Function reads in a CSV file

```
pd.read_csv(filepath_or_buffer, sep=",",  
             header="infer", names=None, ...)
```

2
filepath_or
buffer does **not**
have a default

Differentiate two types of function arguments:

- **No default** if argument is not specified, error is returned
- **Default** if argument is not specified, default is used

Python Basics: A function performs a specific action and is controlled through arguments

1
Function reads in a CSV file

```
pd.read_csv(filepath_or_buffer, sep="," ,  
             header="infer", names=None, ...)
```

2
filepath_or
buffer does **not**
have a default

Differentiate two types of function arguments:

- **No default** if argument is not specified, error is returned
- **Default** if argument is not specified, default is used

Python Basics: A function performs a specific action and is controlled through arguments

1
Function reads in a CSV file

3
sep specifies the character used to separate the values in the CSV

```
pd.read_csv(filepath_or_buffer, sep=",",  
             header="infer", names=None, ...)
```

2
filepath_or
buffer does **not**
have a default

4
sep has a **default**

Differentiate two types of function arguments:

- **No default** if argument is not specified, error is returned
- **Default** if argument is not specified, default is used

Why pandas?

- The **pandas** library speeds up data manipulations:
 - fast file reader
 - add/modify/delete columns by using groups without copying
 - data aggregation
 - ordered joins etc.
- Especially useful for large data (>1 GB in RAM)

Python Basics: Specifying your working directory

- To find the current working directory use:

```
os.getcwd()
```

1
The `os` - module is responsible for Mac and Windows. Review lecture 1 to see how to load a module.

- To set a new working directory use:

```
os.chdir("~/path/to/my/directory/")
```

2
Plug in your intended path here

Python Basics: Specifying your working directory

- To find the current working directory use:

```
os.getcwd()
```

¹
The `os` - module is responsible for Mac and Windows. Review lecture 1 to see how to load a module.

- To set a new working directory use:



```
os.chdir("~/path/to/my/directory/")
```

²
Plug in your intended path here

Step 3:

Make data available for use

Customer	TransDate	Quantity	PurchAmount	Cost
149332	15/11/05	1	199.95	107.00
172951	29/08/08	1	199.95	108.00
120621	19/10/07	1	99.95	49.00
149236	14/11/05	1	39.95	18.95
149236	12/06/07	1	79.95	35.00
...



Name of new variable ¹

```
variableName = (...)
```

Use equal sign to store
object to variableName ²

Sidenote: Choose variable names wisely

- Do **not** name your variables after existing variables or functions.



Reading data