Bit16 Instruction Set

Contents

ALU
Conditional Jump Logic
Registers
Controller

Figure 1: Layout of the bit CPU

Bit16 Specifications

Instructions and Cycle Times

Each instruction is 16 bits long. More information on the formats of each type of 16-bit instruction can be found later in this document. Every microcode instruction has a clock cycle of 1 except for the *load immediate* instruction which takes 2 clock cycles.

Registers

The bit16 CPU contains addressable registers: 4 general-purpose 16-bit registers and 4 special purpose registers. The general-purpose registers can be used for anything including arithmetic and address calculations. There is also a 16-bit instruction register that stores the current instruction being executed and a 4-bit flag register which stores the different flags from the ALU's operations.

The stack pointer (SP) register is used to keep track of the current top of the stack. The stack starts at the last address in RAM (hex FFFF) and grows downward.

The frame pointer (FP) points to the beginning of the current stack frame and is used to load and store local variables on the stack.

The link register (LR) is used for calling and returning from procedures. LR is 16 bits and should only be used to calculate addresses for the RAM module.

The program counter (PC) register keeps track of the current instruction being executed. The program counter starts at 0 and is incremented after every instruction unless the instruction is a jump instruction in which case, the value in the PC becomes the target for the jump.

Code	Mnemonic	Purpose	Bits	Addressable
0	A	General purpose	16	✔
1	B	General purpose	16	✔
2	C	General purpose	16	✔
3	D	General purpose	16	✔
4	FP	Frame pointer	16	✔
5	SP	Stack pointer	16	✔
6	LR	Link register	16	✔
7	PC	Program counter	16	✔
None	F	Flag register	4	
None	IR	Instruction register	16	

Table 1: bit16 CPU registers

RAM Module

The Random-Access-Memory (RAM) module uses full 16-bit addresses. This allows for 65,536 16-bit data/instruction locations. This makes the RAM module roughly 128 kilobytes in size.


Figure 2: Random-access-memory module

Format Summary

The bit16 instruction set formats are shown in the following figure.

	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	
0	0	0	0	Cond					Const10								Jump
1	0	0	1														No operation
2	0	1	0	Op4							Rs		Rd				Binary ALU operation
2	0	1	0	Op1	1	0	1				Rd		Rd				Unary ALU operation
3	0	1	1	Op4				Const6					Rd				Binary ALU operation w/ immediate
4	1	0	0	Op3			Rs2			Rs		Rd					Binary ALU operation
5	1	0	1	Op3			Const4			Rs		Rd					Binary ALU operation w/ immediate
6	1	1	0	S	0			Ro		Rb		Rd					Load/store w/ register offset
6	1	1	0	S	1		Offset5			Rb		Rd					Load/store w/ immediate offset
7	1	1	1										Rd				Load immediate 16-bit value
	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	

Figure 3: bit16 instruction set formats

bit16 Data Sheet

Microcode Summary

The following section summarizes the bit16 instruction set microcode.

ALU Opcode Summary

The following table summarizes the bit16 instruction set operations.

Op3 code	Op4 code	Mnemonic	Instruction	Condition codes set
0	0	ADD	Add	
	1	CMN	Compare negative	✔
1	2	SUB	subtract	
	3	CMP	Compare	✔
2	4	MUL	Multiply	
	0 (5)	NOT	Bitwise not	
3	6	AND	Bitwise and	
	7	TST	Test bits	✔
4	8	OR	Bitwise or	
5	10	XOR	Bitwise exclusive or	
	11	TEQ	Test bits equality	✔
6	12	SHR	Shift right	
	1 (13)	NEG	Negate	
7	14	SHL	Shift left	
	15	MOV	Move to register	

Table 2: bit16 instruction set opcodes

Load Operation Summary

The following table summarizes the Load operation for the bit16 instruction set.

Mnemonic	Instruction
LD	Load/store

Table 3: bit16 load instruction

Jump Instructions Summary

The following table summarizes the jump codes for the bit16 instruction set.

Code	Mnemonic	Instruction
0	JNV	**J**ump **nev**er
1	JEQ	**J**ump if **eq**ual
2	JNE	**J**ump if **n**ot **e**qual
3	JGT	**J**ump if **g**reater **t**han
4	JLT	**J**ump if **l**ess **t**han
5	JGE	**J**ump if **g**reater than or **e**qual to
6	JLE	**J**ump if **l**ess than or **e**qual to
7	JR	**J**ump **r**elative

Table 4: bit16 jump instructions

Macrocode Summary

The following section summarizes the bit16 instruction set macrocode. Macrocode instructions are instructions that are not supported by the hardware and are made up of one or more microcode instructions.

Mnemonic	Instruction	Microcode
PUSH	Push register(s) to stack	`PUSH A = SUB SP, 1` `          LD [SP, 0], A`
POP	Pop register(s) from stack	`POP A = LD A, [SP, 0]` `        ADD SP, 1`
CALL	Call procedure	`CALL L = ADD LR, PC, 3` `         JUMP L`
RET	Return from procedure	`RET = MOV PC, LR`
JUMP	Jump to immediate address	`JUMP L = LD PC, L`
HALT	Halt execution	`HALT = MOV PC, PC`

Table 5: bit16 macro code instructions

Micro Instructions Formats

The following section covers the 8 different instruction formats of the bit16 CPU instruction set.

Format 0: Jump

15	14	13	12 11 10	9 8 7 6 5 4 3 2 1 0
0	0	0	Cond	Offset10

Offset10: Immediate signed 10-bit offset value

Cond: Condition code

Figure 4: Format 0

Operation

Instructions of this format perform a conditional relative jump. This means that the given immediate value is added to the program counter depending on the state of the flag register.

Examples

```
JR     loop  ; Unconditionally jumps to the label "loop"

JNE    .L0   ; Jumps to the label ".L0" if the Z bit is clear

JGE    end   ; Jumps to label "end" if greater than or equal to
```

Format 1: No Operation

(Reserved for potential future features)

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	0	1													

Figure 5: Format 1

Operation

Instructions of this format do nothing except increment the program counter.

Format 2: Binary ALU Operation

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	0		Op4							Rs			Rd	

Rd: Source/destination register

Rs: Source register

Op4: 4-bit opcode

Figure 6: Format 2

Operation
Instructions of this format perform a binary ALU operation on the given registers and place the result in the destination register (Rd) unless it's a comparison operation (CMP, CMN, TST, TEQ).

Examples

```
ADD   A, B  ; A = A + B

CMP   A, B  ; Subtract B from A and set the condition codes

OR    A, B  ; A = A | B

TST   A, B  ; Bitwise AND A and B together and set the condition codes

MOV   A, B  ; Move the value in B to A
```

Format 2: Unary ALU Operation

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	0	Op1	1	0	1					Rd			Rd	

Rd: Source/destination register

Op1: 1-bit opcode. (0 = NOT, 1 = NEG)

Figure 7: Format 2 (Unary)

Operation
Instructions of this format perform a unary ALU operation on the given source register and place the result in the destination register.

Examples

```
NOT   A      ; A = ~A

NEG   A      ; A = -A
```

Format 3: ALU Operation with Constant

15	14	13	12 11 10 9	8 7 6 5 4 3	2 1 0
0	1	1	Op4	Const6	Rd

Rd: Source/destination register

Const6: Immediate signed 6-bit value

Op4: 4-bit opcode

Figure 8: Format 3

Operation

Instructions of this format perform a binary ALU operation on the given register and the given immediate value and place the result in the destination register (Rd) unless it's a comparison operation (CMP, CMN, TST, TEQ).

Examples

```
ADD    SP, 1        ; SP = SP + 1

CMP    B, 0         ; Subtract 0 from B and set the condition codes

AND    A, b111      ; A = A & 0b111

MOV    A, -1        ; Move the value -1 to A
```

Format 4: Binary ALU Operation with Register

15	14	13	12 11 10 9	8	7 6 5	4 3	2 1 0
1	0	0	Op3		Rs2	Rs	Rd

Rd: Source/destination register

Rs: Source register

Rs2: Source register 2

Op3: 3-bit opcode

Figure 9: Format 4

Operation

Instructions of this format perform a binary ALU operation on the given source registers (Rs and Rs2) and place the result in the destination register (Rd).

Examples

```
ADD   A, B, C    ; A = B + C

SHL   A, B, C    ; A = B << C

SUB   A, A, B    ; A = A – B. Equivalent to SUB A, B
```

Format 5: Binary ALU Operation with Constant

15	14	13	12 11 10	9 8 7 6	5 4 3	2 1 0
1	0	1	Op3	Const4	Rs	Rd

Rd: Source/destination register

Rs: Source Register

Const4: Immediate signed 4-bit value

Op3: 3-bit opcode

Figure 10: Format 5

Operation

Instructions of this format perform a binary ALU operation on the given source register and immediate value and place the result in the destination register (Rd).

Examples

```
ADD   A, B, 1     ; A = B + 1

SHR   A, B, 3     ; A = B >> 3

SUB   A, A, xff   ; A = A – 0xff. Equivalent to SUB A, xff
```

Format 6: Load

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	S	0				Ro			Rb			Rd	

Rd: Source/destination register

Rb: Base register

Ro: Offset register

S: Store flag (0 = Load, 1 = Store)

Figure 11: Format 6

Operation

Instructions of this format transfer 16-bit values to and from registers and the RAM module. The load or store operation depends on the S flag. The value in the offset register is added to the value in the base register and sent to the RAM module's address BUS.

Examples

```
LD    [B, C], A    ; Stores the value in A to the address B + C

LD    A, [B, C]    ; Loads the value at address B + C into A
```

Format 6: Load (with Immediate Offset)

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	S	1	Offset5					Rb			Rd		

Rd: Source/destination register

Rb: Base register

Offset5: Immediate unsigned 5-bit offset

S: Store flag (0 = Load, 1 = Store)

**Figure 12: Format 6 with immediate offset**

Operation

Instructions of this format transfer 16-bit values to and from registers and the RAM module. The load or store operation depends on the S flag. The offset value is added to the value in the base register and sent to the RAM module's address BUS.

Examples

```
LD    [SP, 2], C  ; Stores the value in C to the address SP + 2

LD    C, [SP, 2]  ; Loads the value at address SP + 2 into C

LD    A, [A]      ; Loads the value at the address in A into A

LD    [B], A      ; Stores the value in A to the address in B
```

Format 7: Load Immediate

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1											Rd		

Rd: Source/destination register

Figure 13: Format 7

Operation

Instructions of this format load a full 16-bit immediate value into one of the addressable registers. The 16-bit value is stored in the next location in memory.

Examples

```
LD    A, 3000     ; Loads the value 3000 from memory into register A

LD    B, =msg     ; Loads the label address into register B

LD    C, x7fff    ; Loads the hex value 7fff into register A
```