

Overview of Query Evaluation

Computer Science Department
Columbia University

Overview of Query Evaluation

- ❖ Plan: Tree of R.A. ops, with choice of alg for each op.
 - Each operator typically implemented using a 'pull' interface: when an operator is 'pulled' for the next output tuples, it 'pulls' on its inputs and computes them.
- ❖ Two main issues in query optimization:
 - For a given query, **what plans are considered?**
 - Algorithm to search plan space for cheapest (estimated) plan.
 - How is the **cost of a plan estimated?**
- ❖ **Ideally**: Want to find best plan. **Practically**: Avoid worst plans!
- ❖ We will study the System R approach.

Some Common Techniques

- ❖ Algorithms for evaluating relational operators use some simple ideas extensively:
 - **Indexing:** Can use WHERE conditions to retrieve small set of tuples (selections, joins)
 - **Iteration:** Sometimes, faster to scan all tuples even if there is an index. (And sometimes, we can scan the data entries in an index instead of the table itself.)
 - **Partitioning:** By using sorting or hashing, we can partition the input tuples and replace an expensive operation by similar operations on smaller inputs.

** Watch for these techniques as we discuss query evaluation!*

Statistics and Catalogs

- ❖ Need information about the relations and indexes involved. *Catalogs* typically contain at least:
 - # tuples (NTuples) and # pages (NPages) for each relation.
 - # distinct key values (NKeys) and NPages for each index.
 - Index height, low/high key values (Low/High) for each tree index.
- ❖ Catalogs updated periodically.
 - Updating whenever data changes is too expensive; lots of approximation anyway, so slight inconsistency ok.
- ❖ More detailed information (e.g., histograms of the values in some field) are sometimes stored.

System Catalogs (aka *System Tables*)

- ❖ For each index:
 - structure (e.g., B+ tree) and search key fields
- ❖ For each relation:
 - name, file structure (e.g., Heap file)
 - attribute name and type, for each attribute
 - index name, for each index
 - integrity constraints
- ❖ For each view:
 - view name and definition
- ❖ Plus statistics, authorization, buffer pool size, etc.

Catalogs are themselves stored as relations!

Attr_Cat(attr_name, rel_name, type, position)

attr_name	rel_name	type	position
attr_name	Attribute_Cat	string	1
rel_name	Attribute_Cat	string	2
type	Attribute_Cat	string	3
position	Attribute_Cat	integer	4
sid	Students	string	1
name	Students	string	2
login	Students	string	3
age	Students	integer	4
gpa	Students	real	5
fid	Faculty	string	1
fname	Faculty	string	2
sal	Faculty	real	3

Access Paths

- ❖ An access path is a method of retrieving tuples:
 - **File scan**, or **index** that **matches** a selection (in the query)
- ❖ A tree index matches (a conjunction of) terms that involve only attributes in a *prefix* of the search key.
 - E.g., Tree index on $\langle a, b, c \rangle$ **matches** the selection $a=5$ **AND** $b=3$, and $a=5$ **AND** $b>6$, but not $b=3$.
- ❖ A hash index matches (a conjunction of) terms that has a term *attribute = value* for every attribute in the search key of the index.
 - E.g., Hash index on $\langle a, b, c \rangle$ **matches** $a=5$ **AND** $b=3$ **AND** $c=5$; but it does not match $b=3$, or $a=5$ **AND** $b=3$, or $a>5$ **AND** $b=3$ **AND** $c=5$.

A Note on Complex Selections

$(day < 8/9/94 \text{ AND } rname = 'Paul') \text{ OR } bid = 5 \text{ OR } sid = 3$

- ❖ Selection conditions are first converted to conjunctive normal form (CNF):
 $(day < 8/9/94 \text{ OR } bid = 5 \text{ OR } sid = 3) \text{ AND } (rname = 'Paul' \text{ OR } bid = 5 \text{ OR } sid = 3)$
- ❖ We only discuss case with no ORs; see text if you are curious about the general case.

One Approach to Selections

- ❖ Find the *most selective access path*, retrieve tuples using it, and apply any remaining terms that don't **match** the index:
 - *Most selective access path*: An index or file scan that we estimate will require the fewest page I/Os.
 - Terms that match this index reduce the number of tuples *retrieved*; other terms are used to discard some retrieved tuples, but do not affect number of tuples/pages fetched.
 - Consider *day < 8/9/94 AND bid = 5 AND sid = 3*. A B+ tree index on *day* can be used; then, *bid = 5* and *sid = 3* must be checked for each retrieved tuple. Similarly, a hash index on *<bid, sid>* could be used; *day < 8/9/94* must then be checked.

Using an Index for Selections

- ❖ Cost depends on #qualifying tuples, and clustering.
 - Cost of finding qualifying data entries (typically small) plus cost of retrieving records (could be large w/o clustering).
 - In example, assuming uniform distribution of names, about 10% of tuples qualify (100 pages, 10,000 tuples). With a clustered index, cost is little more than 100 I/Os; if unclustered, upto 10,000 I/Os!

```
SELECT *  
FROM   Reserves R  
WHERE  R.rname < 'C%'
```

Projection

SELECT	DISTINCT
	R.sid, R.bid
FROM	Reserves R

- ❖ The expensive part is removing duplicates.
 - SQL systems don't remove duplicates unless the keyword DISTINCT is specified in a query.
- ❖ Sorting Approach: Sort on <sid, bid> and remove duplicates. (Can optimize this by dropping unwanted information while sorting.)
- ❖ Hashing Approach: Hash on <sid, bid> to create partitions. Load partitions into memory one at a time, build in-memory hash structure, and eliminate duplicates.
- ❖ If there is an index with both R.sid and R.bid in the search key, may be cheaper to sort data entries!

Join: Block (Index) Nested Loops ($R \bowtie_{i=j} S$)

foreach tuple r in R do

 foreach tuple s in S where $r_i == s_j$ do

 add $\langle r, s \rangle$ to result

- ❖ If there is an index on the join column of one relation (say S), can make it the inner and exploit the index.
 - Cost: $M + (M \cdot p_R) \cdot \text{cost of finding matching } S \text{ tuples}$
 - $M = \# \text{pages of } R$, $p_R = \# \text{ } R \text{ tuples per page}$
- ❖ For each R tuple, cost of probing S index is about 1 for hash index, 3 for B+ tree. Cost of then finding S tuples (assuming Alt. (2) or (3) for data entries) depends on clustering.
 - Clustered index: 1 I/O (typical), unclustered: upto 1 I/O per matching S tuple.

Join: Sort-Merge ($R \bowtie_{i=j} S$)

- ❖ Sort R and S on the join column, then scan them to do a “merge” (on join col.), and output result tuples.
 - Advance scan of R until current R-tuple \geq current S tuple, then advance scan of S until current S-tuple \geq current R tuple; do this until current R tuple = current S tuple.
 - At this point, all R tuples with same value in R_i (*current R group*) and all S tuples with same value in S_j (*current S group*) match; output $\langle r, s \rangle$ for all pairs of such tuples.
 - Then resume scanning R and S.
- ❖ R is scanned once; each S group is scanned once per matching R tuple. (Multiple scans of an S group are likely to find needed pages in buffer.)

Example of Sort-Merge Join

<u>sid</u>	sname	rating	age	<u>sid</u>	<u>bid</u>	<u>day</u>	rname
22	dustin	7	45.0	28	103	12/4/96	guppy
28	yuppy	9	35.0	28	103	11/3/96	yuppy
31	lubber	8	55.5	31	101	10/10/96	dustin
44	guppy	5	35.0	31	102	10/12/96	lubber
58	rusty	10	35.0	31	101	10/11/96	lubber
				58	103	11/12/96	dustin

- ❖ Cost: $M \log M + N \log N + (M+N)$
 - The cost of scanning, $M+N$, could be $M*N$ (very unlikely!)

Highlights of System R Optimizer

- ❖ Impact:
 - Most widely used currently; works well for < 10 joins.
- ❖ Cost estimation: Approximate art at best.
 - Statistics, maintained in system catalogs, used to estimate cost of operations and result sizes.
 - Considers combination of CPU and I/O costs.
- ❖ Plan Space: Too large, must be pruned.
 - Only the space of *left-deep plans* is considered.
 - Left-deep plans allow output of each operator to be pipelined into the next operator without storing it in a temporary relation.
 - Cartesian products avoided.

Cost Estimation

- ❖ For each plan considered, must estimate cost:
 - Must *estimate cost* of each operation in plan tree.
 - Depends on input cardinalities.
 - We've already discussed how to estimate the cost of operations (sequential scan, index scan, joins, etc.)
 - Must also *estimate size of result* for each operation in tree!
 - Use information about the input relations.
 - For selections and joins, assume independence of predicates.

Size Estimation and Reduction Factors

```
SELECT attribute list  
FROM relation list  
WHERE term1 AND ... AND termk
```

- ❖ Consider a query block:
- ❖ Maximum # tuples in result is the product of the cardinalities of relations in the FROM clause.
- ❖ *Reduction factor (RF)* associated with each *term* reflects the impact of the *term* in reducing result size. *Result cardinality* = Max # tuples * product of all RF's.
 - Implicit *assumption* that *terms* are independent!
 - Term *col=value* has RF $1/NKeys(I)$, given index *I* on *col*
 - Term *col1=col2* has RF $1/MAX(NKeys(I1), NKeys(I2))$
 - Term *col>value* has RF $(High(I)-value)/(High(I)-Low(I))$

Schema for Examples

Sailors (*sid*: integer, *sname*: string, *rating*: integer, *age*: real)



Reserves (*sid*: integer, *bid*: integer, *day*: dates, *rname*: string)

❖ Similar to old schema; *rname* added for variations.


Motivating Example

```
SELECT S.sname
FROM Reserves R, Sailors S
WHERE R.sid=S.sid AND
      R.bid=100 AND S.rating>5
```

- ❖ Cost of plan = cost of join
- ❖ By no means the worst plan!
- ❖ Misses several opportunities: selections could have been 'pushed' earlier, no use is made of any available indexes, etc.
- ❖ *Goal of optimization:* To find more efficient plans that compute the same answer.



Alternative Plans 1 (No Indexes)



- ❖ **Main difference:** push down selects.
- ❖ Cost of plan =
 - Cost of selection (bid=100) + write results to temp file T1 +
 - Cost of selection (rating>5) + write results to temp file T2 +
 - Cost of sort-merge join of T1 and T2
- ❖ Significant cost improvement due to the fact that we join smaller tables.
- ❖ **If we push projections,** T1 has only *sid*, T2 only *sid* and *sname*:
 - Even smaller tables to perform the join.


Alternative Plans 2

With Indexes

- ❖ With clustered index on *bid* of Reserves
- ❖ INL with pipelining (outer is not materialized).

–Projecting out unnecessary fields from outer doesn't help.

- ❖ Join column *sid* is a key for Sailors.
 - At most one matching tuple, unclustered index on *sid* OK.
- ❖ Decision not to push *rating*>5 before the join is based on availability of *sid* index on Sailors.
- ❖ Cost: Selection of Reserves tuples; for each, must get matching Sailors tuple.



Summary

- ❖ There are several alternative evaluation algorithms for each relational operator.
- ❖ A query is evaluated by converting it to a tree of operators and evaluating the operators in the tree.
- ❖ Must understand query optimization in order to fully understand the performance impact of a given database design (relations, indexes) on a workload (set of queries).
- ❖ Two parts to optimizing a query:
 - Consider a set of alternative plans.
 - Must prune search space; typically, left-deep plans only.
 - Must estimate cost of each plan that is considered.
 - Must estimate size of result and cost for each plan node.
 - *Key issues:* Statistics, indexes, operator implementations.