

XMLSTARLET USER'S GUIDE

see also <http://xmlstar.sourceforge.net/>

1. BASIC COMMAND LINE OPTIONS

=====

```
xml
XMLStarlet Toolkit: Command line utilities for XML
Usage: xml [<options>] <command> [<cmd-options>]
where <command> is one of:
    ed    (or edit)      - Edit/Update XML document(s)
    sel    (or select)   - Select data or query XML document(s) (XPATH, etc)
    tr     (or transform) - Transform XML document(s) using XSLT
    val    (or validate) - Validate XML document(s) (well-formed/DTD/XSD)
    fo     (or format)   - Format XML document(s)
    el     (or elements) - Display element structure of XML document
<options> are:
    --version          - show version
    --help             - show help
Wherever file name mentioned in command help it is assumed
that URL can be used instead as well.
```

Type: xml <command> --help <ENTER> for command help

XMLStarlet is a command line toolkit to query/edit/check/transform
XML documents (for more information see <http://xmlstar.sourceforge.net/>)

2. Select/Query XML documents

=====

```
xml sel --help
XMLStarlet Toolkit: Select from XML document(s)
Usage: xml sel <global-options> {<template>} [ <xml-file> ... ]
where
    <global-options> - global options for selecting
    <xml-file>       - input XML document file name/uri (stdin is used if missing)
    <template>       - template for querying XML document with following syntax:
```

```
<global-options> are:
-C or --comp          - display generated XSLT
-R or --root          - print root element <xsl-select>
-T or --text          - output is text (default is XML)
-I or --indent        - indent output
-D or --xml-decl      - do not omit xml declaration line
-B or --noblanks      - remove insignificant spaces from XML tree
--net                 - allow fetch DTDs or entities over network
--help               - display help
```

Syntax for templates: -t|--template <options>

```
where <options>
-c or --copy-of <xpath> - print copy of XPATH expression
-v or --value-of <xpath> - print value of XPATH expression
-o or --output <string> - output string literal
-n or --nl          - print new line
-f or --inp-name     - print input file name (or URL)
-m or --match <xpath> - match XPATH expression
-i or --if <test-xpath> - check condition <xsl:if test="test-xpath">
-e or --elem <name>    - print out element <xsl:element name="name">
-a or --attr <name>    - add attribute <xsl:attribute name="name">
-b or --break        - break nesting
-s or --sort op xpath - sort in order (used after -m) where
op is X:Y:Z,
    X is A - for order="ascending"
    X is D - for order="descending"
    Y is N - for data-type="numeric"
    Y is T - for data-type="text"
    Z is U - for case-order="upper-first"
    Z is L - for case-order="lower-first"
```

There can be multiple --match, --copy-of, --value-of, etc options in a single template. The effect of applying command line templates can be illustrated with the following XSLT analogue

```
xml sel -t -c "xpath0" -m "xpath1" -m "xpath2" -v "xpath3" \
-t -m "xpath4" -c "xpath5"
```

is equivalent to applying the following XSLT

```
<?xml version="1.0"?>
<xsl:stylesheet version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
<xsl:template match="/">
  <xsl:call-template name="t1" />
  <xsl:call-template name="t2" />
</xsl:template>
<xsl:template name="t1">
  <xsl:copy-of select="xpath0" />
  <xsl:for-each select="xpath1">
    <xsl:for-each select="xpath2">
      <xsl:value-of select="xpath3" />
    </xsl:for-each>
  </xsl:for-each>
</xsl:template>
<xsl:template name="t2">
  <xsl:for-each select="xpath4">
    <xsl:copy-of select="xpath5" />
  </xsl:for-each>
</xsl:template>
</xsl:stylesheet>
```

XMLStarlet is a command line toolkit to query/edit/check/transform XML documents (for more information see <http://xmlstar.sourceforge.net/>)

Current implementation uses libxslt from GNOME codebase as XSLT processor (see <http://xmlsoft.org/> for more details)

3. Editing XML documents

=====

```
xml ed --help
XMLStarlet Toolkit: Edit XML document(s)
Usage: xml ed {<action>} [ <xml-file-or-uri> ... ]
where <action>
  -d or --delete <xpath>
  -i or --insert <xpath> -t (--type) elem|text|attr -v (--value) <value>
  -a or --append <xpath> -t (--type) elem|text|attr -v (--value) <value>
  -s or --subnode <xpath> -t (--type) elem|text|attr -v (--value) <value>
  -m or --move <xpath1> <xpath2>
  -r or --rename <xpath1> -v <new-name>
  -u or --update <xpath> -v (--value) <value>
  -x (--expr) <xpath>
```

XMLStarlet is a command line toolkit to query/edit/check/transform XML documents (for more information see <http://xmlstar.sourceforge.net/>)

4. Using XSLT to transform XML documents

=====

```
xml tr --help
XMLStarlet Toolkit: Transform XML document(s) using XSLT
Usage: xml tr [<options>] <xsl-file> {-p|-s <name>=<value>} [ <xml-file-or-uri> ... ]
where
  <xsl-file>      - main XSLT stylesheet for transformation
  <xml-file>      - input XML document file name (stdin is used if missing)
  <name>=<value>  - name and value of the parameter passed to XSLT processor
  -p             - parameter is XPATH expression ("string" to quote string)
  -s             - parameter is a string literal
<options> are:
  --omit-decl    - omit xml declaration <?xml version="1.0"?>
  --show-ext     - show list of extensions
  --val          - allow validate against DTDs or schemas
  --net          - allow fetch DTDs or entities over network
```

```
--xinclude      - do XInclude processing on document input
--maxdepth val  - increase the maximum depth
--html          - input document(s) is(are) in HTML format
--docbook       - input document(s) is(are) in SGML docbook format
--catalogs      - use SGML catalogs from $SGML_CATALOG_FILES
                  otherwise XML catalogs starting from
                  file:///etc/xml/catalog are activated by default
```

XMLStarlet is a command line toolkit to query/edit/check/transform
XML documents (for more information see <http://xmlstar.sourceforge.net/>)

Current implementation uses libxslt from GNOME codebase as XSLT processor
(see <http://xmlsoft.org/> for more details)

5. Formatting XML documents

=====

```
xml fo --help
XMLStarlet Toolkit: Format XML document(s)
Usage: xml fo [<options>] <xml-file>
where <options> are
  -n or --noindent      - do not indent
  -t or --indent-tab    - indent output with tabulation
  -s or --indent-spaces <num> - indent output with <num> spaces
  -o or --omit-decl     - omit xml declaration <?xml version="1.0"?>
  -H or --html          - input is HTML
  -h or --help          - print help
```

XMLStarlet is a command line toolkit to query/edit/check/transform
XML documents (for more information see <http://xmlstar.sourceforge.net/>)

6. Validating XML documents

=====

```
xml val --help
XMLStarlet Toolkit: Validate XML document(s)
Usage: xml val <options> [ <xml-file-or-uri> ... ]
where <options>
  -d or --dtd <dtd-file>      - validate against DTD
  -s or --xsd <xsd-file>      - validate against schema
  -r or --relaxng <rng-file>  - validate against Relax-NG schema
  -e or --err                 - print verbose error messages on stderr
  -b or --list-bad            - list only files which do not validate
  -g or --list-good           - list only files which validate
  -q or --quiet               - do not list files (return result code only)
  -w or --well-formed         - check only if XML is well-formed (default)
```

NOTE: XML Schemas are not fully supported yet due to its incomplete
support in libxml (see <http://xmlsoft.org/>)

XMLStarlet is a command line toolkit to query/edit/check/transform
XML documents (for more information see <http://xmlstar.sourceforge.net/>)

7. Displaying structure of XML documents

=====

```
xml el --help
XMLStarlet Toolkit: Display element structure of XML document
Usage: xml el [<options>] <xml-file>
where
  <xml-file> - input XML document file name (stdin is used if missing)
  <options>:
    -a - show attributes as well
    -v - show attributes and their values
```

XMLStarlet is a command line toolkit to query/edit/check/transform
XML documents (for more information see <http://xmlstar.sourceforge.net/>)

8. Examples:

=====

Input1
examples/xml/table.xml

```
<?xml version="1.0"?>
<xml>
  <table>
    <rec id="1">
      <numField>123</numField>
      <stringField>String Value</stringField>
    </rec>
    <rec id="2">
      <numField>346</numField>
      <stringField>Text Value</stringField>
    </rec>
    <rec id="3">
      <numField>-23</numField>
      <stringField>stringValue</stringField>
    </rec>
  </table>
</xml>
```

Input2
examples/xml/tab-obj.xml

```
<?xml version="1.0"?>
<xml>
  <table>
    <rec id="1">
      <numField>123</numField>
      <stringField>String Value</stringField>
      <object name="Obj1">
        <property name="size">10</property>
        <property name="type">Data</property>
      </object>
    </rec>
    <rec id="2">
      <numField>346</numField>
      <stringField>Text Value</stringField>
    </rec>
    <rec id="3">
      <numField>-23</numField>
      <stringField>stringValue</stringField>
    </rec>
  </table>
</xml>
```

Input3
examples/html/hello1.html

```
<html>
<head>
  <title>Hello World</title>
  <meta http-equiv="content-type" content="text/html; charset=ISO-8859-1">
</head>
<body>
  <div align="center">Hello World!<br></div>
</body>
</html>
```

Input4
examples/sgml/docbook1.sgml

```
<!DOCTYPE book
PUBLIC "-//OASIS//DTD DocBook XML V4.1.2//EN"
"http://www.oasis-open.org/docbook/xml/4.1.2/docbookx.dtd">
<book>

<bookinfo>
  <title>DocBook document example</title>
  <author>
    <firstname>Mikhail</firstname>
```

```

    <surname>Grushinskiy</surname>
  </author>

  <copyright>
    <year>2002</year>
    <holder>Mikhail Grushinskiy</holder>
  </copyright>
</bookinfo>

<preface>
  <title>Sample document</title>

  <para>A simple DocBook example document.</para>
</preface>

<chapter>
  <title>XMLStarlet Example</title>

  <para>The <emphasis>XMLStarlet</emphasis> command line toolkit
  allows querying/checking/editing/transforming/formatting XML documents
  from command line</para>

  <para>To find out more on how to use the
  <emphasis>XMLStarlet</emphasis> for XML processing, point
  your browser to <ulink
  url="http://xmlstar.sourceforge.net/">http://xmlstar.sourceforge.net/</ulink>.
  </para>

</chapter>
</book>

```

Stylesheet1
examples/xsl/sum1.xsl

```

<?xml version="1.0"?>
<xsl:stylesheet version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
<xsl:output method="text"/>
<xsl:param name="inputFile">-</xsl:param>
<xsl:template match="/">
  <xsl:call-template name="t1"/>
</xsl:template>
<xsl:template name="t1">
  <xsl:value-of select="sum(/xml/table/rec/numField)"/>
  <xsl:value-of select="'&#10;'" />
</xsl:template>
</xsl:stylesheet>

```

Stylesheet2
examples/xsl/hello1.xsl

```

<?xml version="1.0"?>
<xsl:stylesheet version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
<xsl:output method="text"/>
<xsl:param name="inputFile">-</xsl:param>
<xsl:template match="/">
  <xsl:call-template name="t1"/>
</xsl:template>
<xsl:template name="t1">
  <xsl:for-each select="/">
    <xsl:value-of select="/html/body/div"/>
  </xsl:for-each>
</xsl:template>
</xsl:stylesheet>

```

Stylesheet3
examples/xsl/param1.xsl

```

<?xml version="1.0"?>
<xsl:stylesheet version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
<xsl:output method="text"/>
<xsl:param name="Text"/>
<xsl:param name="Count"/>

```

```

<xsl:template match="/">
  <xsl:call-template name="t1" />
</xsl:template>
<xsl:template name="t1">
  <xsl:for-each select="/xml">
    <xsl:value-of select="$Text"/>
    <xsl:value-of select="$Count"/>
    <xsl:value-of select="'&#10;'" />
  </xsl:for-each>
</xsl:template>
</xsl:stylesheet>

```

Command:

```

# Count elements matching XPath expression
./xmlstarlet sel -t -v "count(/xml/table/rec/numField)" xml/table.xml
Result Output:
3

```

Command:

```

# Count all nodes in XML document
./xmlstarlet sel -t -f -o " " -v "count(//node())" xml/table.xml xml/tab-obj.xml
Result Output:
xml/table.xml 32
xml/tab-obj.xml 41

```

Command:

```

# Delete elements matching XPath expression
./xmlstarlet ed -d /xml/table/rec[@id='2'] xml/table.xml
Result Output:
<?xml version="1.0"?>
<xml>
  <table>
    <rec id="1">
      <numField>123</numField>
      <stringField>String Value</stringField>
    </rec>
    <rec id="3">
      <numField>-23</numField>
      <stringField>stringValue</stringField>
    </rec>
  </table>
</xml>

```

Command:

```

# Generate HTML from given SGML docbook document
./xmlstarlet tr --omit-decl --docbook /usr/share/sgml/docbook/yelp/docbook/html/docbook.xml sgml/docbook1.sgml
./xmlstarlet fo --html --indent-spaces 2
Result Output:
<?xml version="1.0" encoding="ISO-8859-1" standalone="yes"?>
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/REC-html40/loose.dtd">
<html>
  <head>
    <meta content="text/html; charset=ISO-8859-1" http-equiv="Content-Type" />
    <title>DocBook document example</title>
    <meta name="generator" content="DocBook XSL Stylesheets V1.48"/>
  </head>
  <body bgcolor="white" text="black" link="#0000FF" vlink="#840084" alink="#0000FF">
    <div class="book">
      <div class="titlepage">
        <div>
          <h1 class="title"><a name="id2765244"/>DocBook document example</h1>
        </div>
        <div>
          <h3 class="author">Mikhail Grushinskiy</h3>
        </div>
        <div>
          <p class="copyright">Copyright © 2002 Mikhail Grushinskiy</p>
        </div>
        <hr/>
      </div>
      <div class="toc">
        <p>

```

```

    <b>Table of Contents</b>
  </p>
  <dl>
    <dt>
      <a href="#id2765482">Sample document</a>
    </dt>
    <dt>1. <a href="#id2767329">XMLStarlet Example</a></dt>
  </dl>
</div>
<div class="preface">
  <div class="titlepage">
    <div>
      <h2 class="title"><a name="id2765482"/>Sample document</h2>
    </div>
  </div>
  <p>A simple DocBook example document.</p>
</div>
<div class="chapter">
  <div class="titlepage">
    <div>
      <h2 class="title"><a name="id2767329"/>Chapter 1. XMLStarlet Example</h2>
    </div>
  </div>
  <p>The <span class="emphasis"><i>XMLStarlet</i></span> command line toolkit
allows querying/checking/editing/transforming/formatting XML documents
from command line</p>
  <p>To find out more on how to use the
<span class="emphasis"><i>XMLStarlet</i></span> for XML processing, point
your browser to <a href="http://xmlstar.sourceforge.net/" target="_top">http://xmlstar.sourceforge.net/</a>.
</p>
</div>
</body>
</html>

```

```

Command:
# Validate XML document against DTD
./xmlstarlet val --dtd dtd/table.dtd xml/tab-obj.xml >/dev/null 2>&1; echo $?
Result Output:
1

```

```

Command:
# Validate XML document against DTD
./xmlstarlet val --dtd dtd/table.dtd xml/table.xml >/dev/null 2>&1; echo $?
Result Output:
0

```

```

Command:
# Display element structure of XML document
./xmlstarlet el ./xml/tab-obj.xml
Result Output:
xml
xml/table
xml/table/rec
xml/table/rec/numField
xml/table/rec/stringField
xml/table/rec/object
xml/table/rec/object/property
xml/table/rec/object/property
xml/table/rec
xml/table/rec/numField
xml/table/rec/stringField
xml/table/rec
xml/table/rec/numField
xml/table/rec/stringField

```

```

Command:
# Display element structure of XML document (including attributes)
./xmlstarlet el -a ./xml/tab-obj.xml
Result Output:
xml
xml/table
xml/table/rec

```

```

xml/table/rec/@id
xml/table/rec/numField
xml/table/rec/stringField
xml/table/rec/object
xml/table/rec/object/@name
xml/table/rec/object/property
xml/table/rec/object/property/@name
xml/table/rec/object/property
xml/table/rec/object/property/@name
xml/table/rec
xml/table/rec/@id
xml/table/rec/numField
xml/table/rec/stringField
xml/table/rec
xml/table/rec/@id
xml/table/rec/numField
xml/table/rec/stringField

```

Command:

```

# Display element structure of XML document (including attribute values)
./xmlstarlet el -v ./xml/tab-obj.xml

```

Result Output:

```

xml
xml/table
xml/table/rec[@id='1']
xml/table/rec/numField
xml/table/rec/stringField
xml/table/rec/object[@name='Obj1']
xml/table/rec/object/property[@name='size']
xml/table/rec/object/property[@name='type']
xml/table/rec[@id='2']
xml/table/rec/numField
xml/table/rec/stringField
xml/table/rec[@id='3']
xml/table/rec/numField
xml/table/rec/stringField

```

Command:

```

# Calculate EXSLT (XSLT extentions) XPath value
echo "<x/>" | ./xmlstarlet sel -t -v "math:abs(-1000)"

```

Result Output:

```

1000

```

Command:

```

# Find XML files matching XPath expression (containing 'object' element)
./xmlstarlet sel -t -m //object -f xml/table.xml xml/tab-obj.xml

```

Result Output:

```

xml/tab-obj.xml

```

Command:

```

# Generate XML document using command line xml sel
echo "<x/>" | ./xmlstarlet sel -t -m / -e xml -e child -a data -o value

```

Result Output:

```

<xml><child data="value"/></xml>

```

Command:

```

# Apply XSLT stylesheet to HTML input file
./xmlstarlet tr --html xsl/hello1.xsl html/hello1.html

```

Result Output:

```

Hello World!

```

Command:

```

# Use local-name() XSLT function in XPath expression
./xmlstarlet sel -t -v "//*[local-name()='query']" xsql/jobserve.xsql

```

Result Output:

```

SELECT substr(title,1,26) short_title, title, location, skills
FROM job
WHERE UPPER(title) LIKE '%ORACLE%'
ORDER BY first_posted DESC

```



```

Command:
# Select text value of an XML element mathing given XPath expression
./xmlstarlet sel -t -m "/xml/table/rec[@id='2']" -v numField xml/table.xml
Result Output:
346

```

```

Command:
# Format XML document disabling indent
cat xml/tab-obj.xml | ./xmlstarlet fo --noindent
Result Output:
<?xml version="1.0"?>
<xml>
<table>
<rec id="1">
<numField>123</numField>
<stringField>String Value</stringField>
<object name="Obj1">
<property name="size">10</property>
<property name="type">Data</property>
</object>
</rec>
<rec id="2">
<numField>346</numField>
<stringField>Text Value</stringField>
</rec>
<rec id="3">
<numField>-23</numField>
<stringField>stringValue</stringField>
</rec>
</table>
</xml>

```

```

Command:
# xsl:copy-of in xml sel command
./xmlstarlet sel -B -t -m /xml/table/rec -c . -n xml/table.xml
Result Output:
<rec id="1"><numField>123</numField><stringField>String Value</stringField></rec>
<rec id="2"><numField>346</numField><stringField>Text Value</stringField></rec>
<rec id="3"><numField>-23</numField><stringField>stringValue</stringField></rec>

```

```

Command:
# Query XML document and produce sorted text table
./xmlstarlet sel -T -t -m /xml/table/rec -s D:N:- "@id" -v "concat(@id,'|',numField,'|',stringField)" -n xml/ta
Result Output:
3|-23|stringValue
2|346|Text Value
1|123|String Value

```

```

Command:
# Print structure of XML element using xml sel (advanced XPath expressions and xml sel command usage)
./xmlstarlet sel -T -t -m '//*' \
-m 'ancestor-or-self::*' -v 'name()' -i 'not(position()=last())' -o . -b -b -n \
xml/structure.xml
Result Output:
a1
a1.a11
a1.a11.a111
a1.a11.a111.a1111
a1.a11.a112
a1.a11.a112.a1121
a1.a12
a1.a13
a1.a13.a131

```

```

Command:
# Calculating running sum on XML document
./xmlstarlet sel -t -v "sum(/xml/table/rec/numField)" xml/table.xml
Result Output:
446

```

```

Command:
# Indent XML document with tabs
cat xml/tab-obj.xml | ./xmlstarlet fo --indent-tab
Result Output:
<?xml version="1.0"?>
<xml>
  <table>
    <rec id="1">
      <numField>123</numField>
      <stringField>String Value</stringField>
      <object name="Obj1">
        <property name="size">10</property>
        <property name="type">Data</property>
      </object>
    </rec>
    <rec id="2">
      <numField>346</numField>
      <stringField>Text Value</stringField>
    </rec>
    <rec id="3">
      <numField>-23</numField>
      <stringField>stringValue</stringField>
    </rec>
  </table>
</xml>

```

```

Command:
# Generate plain text table from XML document
./xmlstarlet sel -T -t -m /xml/table/rec -v "@id" -o "|" -v numField -o "|" -v stringField -n xml/table.xml
Result Output:
1|123|String Value
2|346|Text Value
3|-23|stringValue

```

```

Command:
# Generate plain text table from XML document
./xmlstarlet sel -T -t -m /xml/table/rec -v "concat(@id,'|',numField,'|',stringField)" -n xml/table.xml
Result Output:
1|123|String Value
2|346|Text Value
3|-23|stringValue

```

```

Command:
# Generate plain text table from XML document
./xmlstarlet sel -T \
  -t -o "===== " -n \
  -m xml/table/rec -v "concat(@id,'|',numField,'|',stringField)" -n \
  -t -o "===== " -n xml/table.xml
Result Output:
=====
1|123|String Value
2|346|Text Value
3|-23|stringValue
=====

```

```

Command:
# Validate XML documents using well-formedness/DTD/XSD/RelaxNG checks
echo "===== "
echo "Well-Formedness Validation Tests"
echo "- 1 ===== "
./xmlstarlet val xml/table.xml xml/tab-obj.xml xml/tab-bad.xml 2>/dev/null; echo $?
echo "- 2 ===== "
./xmlstarlet val -g xml/table.xml xml/tab-obj.xml xml/tab-bad.xml 2>/dev/null; echo $?
echo "- 3 ===== "
./xmlstarlet val -b xml/table.xml xml/tab-obj.xml xml/tab-bad.xml 2>/dev/null; echo $?
echo "- 4 ===== "
./xmlstarlet val -q xml/table.xml xml/tab-obj.xml 2>/dev/null; echo $?

echo "===== "
echo "DTD Validation Tests"
echo "- 1 ===== "
./xmlstarlet val -d dtd/table.dtd xml/table.xml xml/tab-obj.xml xml/tab-bad.xml 2>/dev/null; echo $?

```

```

echo "- 2 -----"
./xmlstarlet val -g -d dtd/table.dtd xml/table.xml xml/tab-obj.xml xml/tab-bad.xml 2>/dev/null; echo $?
echo "- 3 -----"
./xmlstarlet val -b -d dtd/table.dtd xml/table.xml xml/tab-obj.xml xml/tab-bad.xml 2>/dev/null; echo $?
echo "- 4 -----"
./xmlstarlet val -q -d dtd/table.dtd xml/table.xml 2>/dev/null; echo $?

echo "====="
echo "Schema Validation Tests"
echo "- 1 -----"
./xmlstarlet val -s xsd/table.xsd xml/table.xml xml/tab-obj.xml xml/tab-bad.xml 2>/dev/null; echo $?
echo "- 2 -----"
./xmlstarlet val -g -s xsd/table.xsd xml/table.xml xml/tab-obj.xml xml/tab-bad.xml 2>/dev/null; echo $?
echo "- 3 -----"
./xmlstarlet val -b -s xsd/table.xsd xml/table.xml xml/tab-obj.xml xml/tab-bad.xml 2>/dev/null; echo $?
echo "- 4 -----"
./xmlstarlet val -q -s xsd/table.xsd xml/table.xml 2>/dev/null; echo $?

echo "====="
echo "RelaxNG Schema Validation Tests"
echo "- 1 -----"
./xmlstarlet val -r relaxng/address.rng relaxng/address.xml relaxng/address-bad.xml 2>/dev/null; echo $?
echo "- 2 -----"
./xmlstarlet val -g -r relaxng/address.rng relaxng/address.xml relaxng/address-bad.xml 2>/dev/null; echo $?
echo "- 3 -----"
./xmlstarlet val -b -r relaxng/address.rng relaxng/address.xml relaxng/address-bad.xml 2>/dev/null; echo $?
echo "- 4 -----"
./xmlstarlet val -q -r relaxng/address.rng relaxng/address.xml 2>/dev/null; echo $?
Result Output:
=====
Well-Formedness Validation Tests
- 1 -----
xml/table.xml - valid
xml/tab-obj.xml - valid
xml/tab-bad.xml - invalid
1
- 2 -----
xml/table.xml
xml/tab-obj.xml
1
- 3 -----
xml/tab-bad.xml
1
- 4 -----
0
=====
DTD Validation Tests
- 1 -----
xml/table.xml - valid
xml/tab-obj.xml - invalid
xml/tab-bad.xml - invalid
1
- 2 -----
xml/table.xml
1
- 3 -----
xml/tab-obj.xml
xml/tab-bad.xml
1
- 4 -----
0
=====
Schema Validation Tests
- 1 -----
xml/table.xml - valid
xml/tab-obj.xml - invalid
xml/tab-bad.xml - invalid
1
- 2 -----
xml/table.xml
1
- 3 -----
xml/tab-obj.xml
xml/tab-bad.xml
1
- 4 -----
0

```

```

=====
RelaxNG Schema Validation Tests
- 1 -----
relaxng/address.xml - valid
relaxng/address-bad.xml - invalid
1
- 2 -----
relaxng/address.xml
1
- 3 -----
relaxng/address-bad.xml
1
- 4 -----
0

```

Command:

```
# Include one XML document into another using XML include
./xmlstarlet tr --xinclude xsl/cat.xsl xml/document.xml
```

Result Output:

```

<?xml version="1.0" encoding="utf-8"?>
<document xmlns:xi="http://www.w3.org/2001/XInclude">
  <p>l20 Mz is adequate for an average home user.</p>
  <disclaimer xml:base="xml/disclaimer.xml">
    <p>The opinions represented herein represent those of the individual
    and should not be interpreted as official policy endorsed by this
    organization.</p>
  </disclaimer>
</document>

```

Command:

```
# Passing parameters to XSLT stylesheet
./xmlstarlet tr xsl/param1.xsl -p Count='count(/xml/table/rec)' -s Text="Count=" xml/table.xml
```

Result Output:

Count=3

Command:

```
# Applying XSLT stylesheet to XML document
./xmlstarlet tr xsl/sum1.xsl xml/table.xml
```

Result Output:

446