

The Pennsylvania State University
The Graduate School
College of Engineering

INITIAL RESIDUAL FORMULATION OF CTF

A Thesis in
Nuclear Engineering
by
Christopher A. Dances

© 2015 Christopher A. Dances

Submitted in Partial Fulfillment
of the Requirements
for the Degree of

Master of Science

May 2015

I grant The Pennsylvania State University the non-exclusive right to use this work for the University's own purposes and to make single copies of the work available to the public on a not-for-profit basis if copies are not otherwise available.

Christopher A. Dances

The thesis of Christopher A. Dances was reviewed and approved* by the following:

Maria Avramova
Associate Professor of Nuclear Engineering
Thesis Advisor, Chair of Committee

Kostadin Ivanov
Distinguished Professor of Nuclear Engineering

Arthur Motta
Professor of Nuclear Engineering and Materials Science and Engineering
Chair of Nuclear Engineering

Vince Mousseau
Mentor from Sandia National Labs
External Reviewer

*Signatures are on file in the Graduate School.

Abstract

Table of Contents

List of Figures	v
List of Tables	vi
List of Symbols	vii
Acknowledgments	viii
Chapter 1	
Introduction	2
1.1 Background	2
Bibliography	4

List of Figures

1.1	The finite volume structure for COBRA-TF	3
-----	--	---

List of Tables

List of Symbols

α

Acknowledgments

Dedication

Chapter 1 |

Introduction

For the past several decades, the primary focus in nuclear engineering within the United States has been focused on light water reactors (LWR). Commercially, all nuclear reactors are either boiling water reactors (BWR) or pressurized water reactors (PWR). Correct computation of the thermal hydraulics within the reactor core leads to efficient design and accuracy in the safety analysis. A popular subchannel code for modelling the hydrodynamics within the reactor core is COBRA-TF. This FORTRAN based code solves 8 conservation equations for liquid, entrained droplet, and vapor phases in 3-D dimensions [1]. The conservation equations analytically reduce into a pressure matrix in a semi-implicit method with rod temperatures solved for explicitly. Because the physics are integrated into the numerical solution, the equations must be linear and the solution method semi-implicit. With a residual formulation, greater flexibility and control over the numerical solution is possible. COBRA-TF was originally written in FORTRAN 77, but over the years has been partially updated to newer versions of Fortran.

The finite volume structure in COBRA-TF in figure 1.1 is for a one-dimensional channel in the axial direction with n number of cells. The first and last cells at 0 and $n + 1$ are ghost cells and act as the boundary conditions for the problem. Pressure, enthalpy, and density are averaged over the cell volume and are located at the center of the cell. Mass flow rate and velocity are located at the faces in between cells. The cells are represented with an index i , and the faces with indexes of $i + \frac{1}{2}$ or $i - \frac{1}{2}$. This project will initially focus on this 1-D configuration. Usually the code is three dimensional, with channels connecting to each other in two more dimensions. Fully 3-D equations will be considered in future work.

1.1 Background




Figure 1.1. The finite volume structure for COBRA-TF

Bibliography

- [1] SALKO, R. K. (2014) *CTF Theory Manual, Tech. rep.*, The Pennsylvania State University.