

The Effects of Mode Choice Model Consistency between Activity-based Models and Microsimulation Tools

Christopher Day^{a,*}, Gregory Macfarlane^a

^a*Civil and Environmental Engineering Department, 430 Engineering Building, Provo, Utah 84602*

Abstract

This is where the abstract should go.

Keywords: Accessibility Passive Data Location Choice

1. Question

In recent years, there has been variation in how the mode choice is estimated within activity-based travel demand modeling. Originally, Bhat and Koppelman (1999) stated that travel demand models should use individual trips as the primary unit of analysis, and to calculate mode at a trip level. More recently, Eluru et al. (2010) developed a joint multiple discrete continuous extreme value (MDCEV) framework to model the individual's mode choice (among other decisions). Hasnine and Nurul Habib (2021) listed differing estimation techniques found in activity-based models, some of which include tour-based modeling, nested model structures, iterative and dynamic processes, and simply calculating the mode choice elsewhere and feeding it in as an input. Variation among activity-based models has always existed.

Like with activity-based models, mode choice estimation in microsimulation tools is not universal. W Axhausen et al. (2016) explain that mode choice in MATSim is chosen using the Charypar-Nagel Utility Function, where agents pick the best alternative based on their uniquely calculated utility score. Alternatively, Ciari et al. (2008) proposed introducing multinomial logit models on the subtour level to increase mode choice estimation accuracy in MATSim. In addition, BEAM originally used a Latent Class Choice Model as its mode choice structure, but then switched to a simple multinomial logit model. Alternatively, Barth et al. (2020) proposed that BEAM implements a fundamental influencing factor (FIF) mode choice model instead. As can be seen with MATSim and BEAM, no current common ground has been established in mode choice model structure among microsimulation tools.

Since there is no way to model human behavior perfectly, it does not seem ideal to develop one universal technique to estimating mode choice. However, a useful advancement in travel demand modeling could be to align the internal structure of mode choice in microsimulation with mode choice in activity-based models. Oftentimes, the outputs of activity-based models are used as the inputs to microsimulation tools. Yet, the way mode choice is estimated in a microsimulation tool rarely matches that of its parent activity-based model. This heterogeneity of estimation between models may lead to increased variability in the final microsimulation results.

We hypothesize that a microsimulation tool with a mode choice structure that mimics that of its parenting activity-based model more accurately simulates the distribution of mode choice across a population. In addition, we explore which population characteristics within the mode choice model has the most significant effect in estimating realistic results.

*Corresponding Author

**Present affiliation: some nice job

Email addresses: christophersday@gmail.com (Christopher Day), christophersday@gmail.com (Gregory Macfarlane)

2. Methods

In our research, the input population used to model behavior corresponds to individuals in the Salt Lake City, Utah, US Region. The activity-based model used to generate the microsimulation input data is ActivitySim (act, 2021). The microsimulation tool used to generate travel behavior data is BEAM (bea, 2021).

ActivitySim implements a multifaceted mode choice model that is dependent on trip, tour, and purpose. One model determines the primary mode for each tour and a separate model determines the mode for each trip. In addition, each modal decision is dependent on the current tour purpose value. Contrastingly, BEAM’s default mode choice structure uses a simple multinomial logit model, independent of tour purpose value. Therefore, in order to test our hypothesis, we aligned the mode choice structure of BEAM (a microsimulation tool) with that of ActivitySim (an activity-based model).

To closely align the mode choice structure of BEAM with ActivitySim, we changed much about the code structure inside of BEAM. More specifically, we wrote code that forced modal decisions to be based on tour purpose values. We also implemented the use of ActivitySim’s path, person, and location utility parameter values to calculate modal alternative probabilities. These simple steps allowed us to create consistency between an activity-based model and a microsimulation tool.

To test the effectiveness of our calibrated mode choice model, we conducted five different test scenarios within BEAM and compared their outputs with each other. Each test scenario that we simulated used a multinomial logit function to determine modal probabilities. Although all used a multinomial logit function, each scenario used a different utility function to predict behavior.

The first scenario we ran used the default BEAM structure. This represented a model with an inconsistent mode choice structure (1). The next three scenarios we ran used a purpose based model with part of ActivitySim’s utility function (either using the path (2), person (3), or location type (4) variables). These represented models with semi-consistent mode choice structures. The last scenario we ran used a purpose based model with ActivitySim’s complete utility function. This represented a model with a consistent mode choice structure (5). Simplified versions of the utility function used in each of the scenarios can be seen in the following equations.

Eq 1: BEAM’s Default Utility Equation

$$V_j = ASC_j + \beta_c(c) + \beta_t(t) + \beta_{xfer}(xfer) \quad (1)$$

where

- j is the modal alternative,
- c is the cost,
- t is the travel time, and
- $xfer$ is the number of transfers.

Eq 2: Utility Equation using ActivitySim’s Path Variables

$$V_j = \beta_{t_v}(t_v) + \beta_{t_w}(t_w) + \beta_{t_e}(t_e) + \beta_{tr_p}(tr_p) + \beta_{xfer}(xfer) + \beta_{w_{dis}}(w_{dis}) + \beta_{b_{dis}}(b_{dis}) + \beta_{d_{dis}}(d_{dis}) \quad (2)$$

where

- j is the modal alternative,
- t_v is the in vehicle travel time (mins),
- t_w is the wait time (mins),
- t_e is the egress time (mins),
- tr_p is the proximity to transit (miles),
- $xfer$ is the number of transfers,
- w_{dis} is the walk distance (miles),

- b_{dis} is the bike distance (miles),
- d_{dis} is the drive distance (miles),
- β_{tr_p} differs between origin/destination and length, and
- $\beta_{w_{dis}}$, $\beta_{b_{dis}}$, and $\beta_{d_{dis}}$ differ between lengths.
- *Note:* All β values differ between mode and tour purpose.

Eq 3: Utility Equation using ActivitySim's Person Variables

$$V_j = ASC_{auto} + \beta_c(c) + \beta_{ag}(ag) \quad (3)$$

where

- j is the modal alternative,
- ASC_{auto} is the alternative specific constant that differs between modal alternative and auto ownership dependency,
- c is the cost, and
- ag is the age grouping (if the person is between 0-10 or 16-19 years old).
- *Note:* All β values differ between mode and tour purpose.

Eq 4: Utility Equation using ActivitySim's Location Variables

$$V_j = \beta_{zdi}(zdi) + \beta_{cbd}(cbd) \quad (4)$$

where

- j is the modal alternative
- zdi is the zonal density index,
- cbd is a classifier for zones labeled as central business district, and
- β_{zdi} differs between origin/destination.
- *Note:* All β values differ between mode and tour purpose.

Eq 5: Utility Equation using All of ActivitySim's Variables

$$V_j = Eq : 2 + Eq : 3 + Eq : 4 \quad (5)$$

where

- j is the modal alternative.

3. Findings

The findings of our study are gathered from the events files generated by BEAM for each scenario run. The events file stores all the decisions made by all individuals during the simulation, including their mode choice decisions. Using the events files, each model's modal shares were thus calculated. To thoroughly understand the affect that each model had on modal shares, modal shares dependent on different variables were calculated. Specifically, the following three modal share outputs were created:

1. Total Modal Share
2. Modal Share based on Vehicle Ownership
3. Modal Share based on Tour Purpose

The modal share in general describes the percentage of individuals in the simulation that chose each modal alternative. A total of 9 modal alternatives were given to the agents:

1. Car
2. Drive Transit




Figure 1: The Total Modal Split of each Scenario compared with Real World Data.

3. Ride Hail
4. Ride Hail Pooled
5. Ride Hail Tranist
6. Shared 2 Ride
7. Shared 3+ Ride
8. Walk
9. Walk Transit

Comparing the modal share of each of the models with the actual modal share of the region allows one to determine the optimal mode choice structure. In the following comparison, the variable *WFRC* represents the actual modal share of the region.


3.1. Total Modal Share

The total modal share simply describes the total division of mode choice alternatives for the entire population. The following figure shows the total modal share.

By examining the graph above, it can clearly be seen that the MNL model provides the car modal share closest to that of the actual region . Although this is true, the ALL model provides a closer walk modal share than the rest. The other modal alternatives all seem relatively similar.

3.2. Modal Share by Vehicle Ownership

The modal share by vehicle ownership provides a more detailed view of how the modes are distributed across the population based on their vehicle ownership status. The following figure shows the modal share by vehicle ownership.




By examining the graph above, the MNL model seems to be much less accurate than the other models for agents that are auto deficient and auto sufficient. The Path model as well as the All model seem to be closest to the WFRC results in these vehicle ownership categories. As a result, the Path variable has the largest affect on the vehicle ownership modal estimation.

For the no auto category though, the MNL and Path models seem to predict relatively well. The All model however, does not seem to be a very good predictor of modal shares for this category.

3.3. Modal Share by Tour Purpose

The modal share by tour purpose provides a more detailed view of how the modes are distributed across the population based on the tour purpose of the agent's trip. The following figure shows the modal share by tour purpose.



Unfortunately, the figure above does not include real world data from WFRC. By examining the figure though, it is clear to see that there is a difference in mode choice depending on the tour purpose chosen by the agent. For example, in all the models, car is the highest chosen mode for work trips, whereas for school trips, walking is slightly higher than carpooling and car trips.

3.4. Additional Analysis

Overall, it can be seen that a microsimulation tool with a mode choice structure that mimics that of its parenting activity-based model does not seem to more accurately simulate the distribution of mode choice across a population. This can be verified by examining the comparison modal share graphs; the All model does not seem to most accurately predict actual modal shares.

Although this is true, we see that the variables relating to Person types have the most significant effect in estimating realistic results. The Location and Path variable types seemed to predict relatively little in comparison to the Person types. This can be verified by examining the comparison modal share graphs; the Person variable seemed to be the most different when compared to the other factors.

In conclusion, we suggest that future analyzts attempt to rerun a similar scenario that has been presented. Unfortunately, sufficient model calibration was not able to be completed. With a more accurately calibrated scenario, we hypothesize that a microsimulation tool with a mimiced mode choice structure will more accurately simulate the mode choice of a population. We also advise analyzts to pay special attention to Person variable types, as they have a greater affect in modal decisions than other variable types.

References

- (2021). Activitysim.
- (2021). Beam's user guide.

- Barth, M., Hao, P., Wu, G., Tanvir, S., Wang, C., Gonder, J., Holden, J., Devall, A., and Sun, B. (2020). Evaluating energy efficiency opportunities from connected and automated vehicle deployments coupled with shared mobility in california. Technical report, University of California-Riverside.
- Bhat, C. R. and Koppelman, F. S. (1999). Activity-based modeling of travel demand. In *Handbook of transportation Science*, pages 35–61. Springer.
- Ciari, F., Balmer, M., and Axhausen, K. W. (2008). A new mode choice model for a multi-agent transport simulation. *Arbeitsberichte Verkehrs-und Raumplanung*, 529.
- Eluru, N., Pinjari, A., Pendyala, R., and Bhat, C. (2010). An econometric multi-dimensional choice model of activity-travel behavior. *Transportation Letters*, 2(4):217–230.
- Hasnine, M. S. and Nurul Habib, K. (2021). Tour-based mode choice modelling as the core of an activity-based travel demand modelling framework: a review of state-of-the-art. *Transport Reviews*, 41(1):5–26.
- W Axhausen, K., Horni, A., and Nagel, K. (2016). *The multi-agent transport simulation MATSim*. Ubiquity Press.