| Normal ⬍ | **B** *I* S̶ U̲ | ≣ ≣ ≣ | 🖼 🔗 ━ | " ⓐ </> 🄰 | I̶ₓ | ••• |

☐ usual CLI commands made in Windows CMD

```
docker network list
docker image list
docker container list -a
docker network create spring-micros-net
docker run -d -p 5000:5000 --network=spring-micros-net --name=micro1 -e SERVICE_URL=http://micro2:5001
cosdin/07-micro-1:0.0.1-SNAPSHOT
docker run -d -p 5001:5001 --network=spring-micros-net --name=micro2 cosdin/07-micro-2:0.0.1-SNAPSHOT
```

☐ Docker (Desktop) has to be started locally for all this to work
☐ git log pretty oneline

```
git log --pretty=oneline
```

☐ In order to reproduce everything in this clickup subtask the 2 Java projects have to be at the following commits (versions)
    ☐ commits (versions):
        ☐ 07-micro-1: `6d237cdbaefbe133369ff39b4e377f794ef23a25`
        ☐ 07-micro-2: `fdea41f622cce408fef26dc397783150d1674489`
    ☐ That is because I've made changes to the projects after I recorded this side project
    ☐ I am reproducing them by going back to those versions

```
mvn clean package
docker compose up -d
```