



- ☐ Zipkin
 - ☐ is used to trace requests in micro group
 - ☐ Sleuth adds to each request has id that is centralized in Zipkin server
 - ☐ can be configured to store data in memory or in database
- ☐ in micros 07-micro-1, 07-micro-2, Zuul
 - ☐ check or add Sleuth, Zipkin, RabbitMQ Maven dependencies
 - ☐ in .properties


```
spring.sleuth.sampler.probability=1.0
spring.rabbitmq.host=rabbitmq
```
- ☐ In docker compose file
 - ☐ add RabbitMQ and Zipkin micros
 - ☐ 07-micro-1, 07-micro-2, Zuul and Zipkin micros have the RabbitMQ uri configured because it talks to RabbitMQ micro
 - ☐ add "depends on" in all 6 micros config
- ☐ commits


```
git log --pretty=oneline --all
```

 - ☐ 07-micro-1 : 8e30699436e6e42c9336445b8b291f99af307c33
 - ☐ 07-micro-2 : c6d9610ad4a748f30a5fd3347d3619cb378e53fc
 - ☐ 07-netflix-eureka : 72f3d8b524bdc4f77e2638235954a226909aa64e
 - ☐ 07-netflix-zuul : d4f219c287b8df556c15f66a4960a5ea1b3a0aa5

