

playwrightDemo - One-page repo summary

Evidence-based summary from repo files (README.md, playwright.config.ts, tests/, .github/workflows/playwright.yml).

What it is

Small Playwright Test (TypeScript) demo repository that runs end-to-end browser automation against public demo sites and outputs an HTML report.

Application source code under test: Not found in repo (tests target external websites).

Who it's for

Developers and QA/SDET engineers learning or prototyping Playwright Test patterns in TypeScript.

How to run

```
npm ci
npx playwright install
npx playwright test
npx playwright show-report
```

Notes: Requires internet access (tests navigate to external sites). Optional config:

```
npx playwright test -c playwright.config.dev.ts
```

What it does

- Runs Playwright Test specs in `tests/` using `@playwright/test`.
- Executes across Chromium, Firefox, and WebKit with HTML reporting and trace capture on first retry.
- Validates login flows (Opencart account login + the-internet login) and negative login error messaging.
- Demonstrates interactions: form fill, role-based locators, dropdown select, focus, checkbox/radio checks, and locator chaining.
- Includes smoke coverage for the "Challenging DOM" page, with retry/skip on intermittent server errors.
- Demonstrates HTTP Basic Auth via an `Authorization` header.
- Shows a persistent browser context with a profile stored under `test-results/`.

How it works (architecture)

- **Runner:** `npx playwright test` loads `playwright.config.ts` (browser projects + HTML reporter).
- **Tests:** Specs drive `page` interactions and assertions against external URLs (e.g., `the-internet.herokuapp.com`, `naveenautomationlabs.com`).
- **Resilience:** Helper `tests/helpers/opencart.ts` retries navigation and skips when unreachable.
- **Outputs:** HTML report in `playwright-report/`; run artifacts in `test-results/`.
- **CI:** GitHub Actions workflow installs deps + browsers, runs tests, and uploads the HTML report artifact.

Not found in repo

- A local app/server to start via Playwright `webServer` (config block exists but is commented out).
- Centralized test data/secret management (some tests use hard-coded credentials and values).