

# CopperCoins 3.0 – Core Database Schema

This document defines the foundational database schema for the CopperCoins 3.0 platform. It is intended to support die numbering continuity, tombstone handling, catalog change logging, images, stages, and cross-reference systems.

## Table: dies

- id (PK)
- year (SMALLINT)
- mint (CHAR)
- denom (SMALLINT)
- die\_type (CHAR)
- proof (BOOLEAN)
- star\_rating (TINYINT, nullable)
- class (VARCHAR, nullable)
- notes (MEDIUMTEXT, nullable)
- timestamps

## Table: die\_numbers

- id (PK)
- die\_number (VARCHAR, UNIQUE)
- year, mint, denom, die\_type, proof
- index\_num (SMALLINT)
- die\_id (FK → dies.id, nullable)
- status (ENUM: assigned, reserved\_unassigned, available\_unassigned)
- reserved\_until (DATETIME, nullable)
- timestamps
- UNIQUE(year, mint, denom, die\_type, proof, index\_num)

## Table: catalog\_change\_events

- id (PK)
- event\_type (ENUM)
- die\_number\_id (FK → die\_numbers.id)
- from\_die\_id (FK → dies.id, nullable)
- to\_die\_id (FK → dies.id, nullable)
- admin\_user\_id (BIGINT, nullable)
- reason (TEXT)
- effective\_at (DATETIME)
- timestamps

## Table: die\_stages

- id (PK)

- die\_id (FK → dies.id)
- stage\_letter (CHAR)
- stage\_sort (SMALLINT)
- die\_state (ENUM, nullable)
- markers (MEDIUMTEXT, nullable)
- notes (MEDIUMTEXT, nullable)
- timestamps

#### Table: images

- id (PK)
- storage\_driver (ENUM)
- path (VARCHAR)
- sha1 (CHAR, nullable)
- width, height (SMALLINT, nullable)
- filesize (INT, nullable)
- mime (VARCHAR, nullable)
- created\_at

#### Table: die\_images

- id (PK)
- die\_id (FK → dies.id)
- image\_id (FK → images.id)
- stage\_id (FK → die\_stages.id, nullable)
- kind (ENUM)
- caption (VARCHAR, nullable)
- sort (SMALLINT)
- timestamps

#### Table: xref\_systems

- id (PK)
- code (VARCHAR, UNIQUE)
- name (VARCHAR)

#### Table: die\_xrefs

- id (PK)
- die\_id (FK → dies.id)
- system\_id (FK → xref\_systems.id)
- xref\_code (VARCHAR)
- note (VARCHAR, nullable)
- timestamps

