# **Contents**

1	Intr	roduction 1						
	1.1	Study of fo	orested areas	2				
	1.2	Remote se	nsing for forested areas	2				
	1.3	Context of	the thesis	4				
	1.4	Objectives		4				
	1.5	Strategy .		5				
	1.6	Structure o	of the thesis	6				
2	Stat	e of the art		9				
	2.1	Stand segn	nentation	10				
	2.2	Segmentat	ion	13				
		2.2.1 Tra	ditional segmentation methods	14				
		2.2.2 Seg	mentation of point cloud	14				
		2.2.3 Sup	perpixels methods	15				
	2.3	Classificat	ion	16				
		2.3.1 Sup	pervised classification	16				
		2.3.2 Dir	nension reduction and feature selection $\ldots \ldots$	17				
		Dir	nension reduction	19				
		Fea	ture selection	19				
	2.4	Smoothing	g methods	19				
			cal methods					
		2.4.2 Glo	obal methods	19				
3	Met	hod		21				
	3.1	General flo	owchart	22				
	3.2	Over-segm	nentation	24				
		3.2.1 Lid	ar-based methods	24				
		3.2.2 Ima	age-based methods	24				
	3.3	Feature ex	traction	24				

	3.4 Classification				
		3.4.1	Training set design	24	
		3.4.2	Feature selection	24	
		3.4.3	Classification	24	
	3.5	Smoot	thing	24	
		3.5.1	Local methods	24	
		3.5.2	Global methods	24	
4	Rest	ults		27	
5	Con	clusion	and perspectives	29	
A	Color code				
В	Pub	licatior	1	35	
	B.1	Journa	al articles	36	
	B.2	Peer-r	eviewed conference papers	36	
Bi	bliog	raphy		39	



# Introduction

$\sim$	~~~~~	
1.1	Study of forested areas	2
1.2	Remote sensing for forested areas	2
1.3	Context of the thesis	4
1.4	Objectives	4
1.5	Strategy	5
1.6	Structure of the thesis	6

## 1.1 Study of forested areas

Forests are an important component of planet's life. They represent 30% of the world land surface. They also hold about 90% of terrestrial biodiversity. Forests are also benefit for the environment; they capt and store the CO<sub>2</sub> [Fah+10]. About 45% of the total global carbon is held by forests. They also filter dust and microbial pollution of the air [Smi12]. Finally, They also play an important role in hydrological regulation and water purification [Lem+08].

Forest are complex structures [Pom02], for which informations are needed for management. The information can be the tree species or the tree maturity of the forest. There are two ways to extract such information from forest; field inventory or remote sensing. The field inventories are very expensive to set up and are also not adapted for a national study. A more adapted to obtain such information is remote sensing since it allows to extract them at a large scale.

## 1.2 Remote sensing for forested areas

The analysis of forested areas from a remote sensing point of view can be performed at three different levels: pixel, object (mainly trees) or stand. In statistical national forest inventory (NFI), an automated and accurate tree segmentation is needed in order to extract tree level features (basal area, dominant tree height, etc., [Mea+00; KM06]). However, the tree level is not the only reliable level of analysis for forest studies. When a joint mapping and statistical reasoning is required (e.g., land-cover (LC) mapping and forest inventory), forest stands remain the prevailing scale of analysis [Mea+00; Whi+16]. A stand can be defined in many different ways in terms of homogeneity: tree specie, age, height, maturity, and its definition varies according to the countries.

3

From a remote sensing point of view, the delineation of the stands is a segmentation problem. Forest stands are interesting in order to extract reliable and statistically meaningful features and to provide an input for multisource statistical inventory. For land-cover mapping, this is highly helpful for forest database updating [KMW09], whether the labels of interest are vegetated areas (e.g., deciduous/evergreen/mixed/non-forested), or, more precisely, the tree species. Most of the time in national forestry inventory institutes, for reliability purposes, each area is manually interpreted by human operators with very high resolution (VHR) geospatial images focusing on the infra-red channel [KM06]. This work is extremely time consuming and subjective [Wul+08]. Furthermore, in many countries, the wide variety of tree species (e.g., >20) significantly complicates the problem. The design of an automatic procedure based on remote sensing data would fasten such process. Additionally, the standard manual delineation procedure only takes into account the species, and few characteristics (alternatively height, age, stem density or crown closure), while an automatic method could offer more flexibility and would allow to combine characteristics extracted from all complementary data sources.

The use of remote sensing data for the automatic analysis of forests has been growing in the last 15 years, especially with the synergistic use of airborne laser scanning (ALS) and optical VHR imagery (multispectral imagery and hyperspectral imagery) [TMS14; Whi+16]. They appear to be both well adapted and complementary inputs for stand segmentation [DBG12; Dal+15; Lee+16]. ALS provides a direct access to the vertical distribution of the trees and to the ground underneath. Hyperspectral and multispectral images are particularly relevant for tree species classification: spectral and textural information from VHR images can allow a fine discrimination of many species, respectively. Multispectral images are often preferred due to their higher availability, and higher spatial resolution.

A prerequisite for data fusion is the most accurate alignment of the two data [TMS14]. A frequently used technique is to geo-rectify images using ground controls points (GCPS). A geometric transformation is established between the coordinates of GCPs and their corresponding pixels in the image. It is

then applied for each pixel, so that coordinate differences on those checkpoints are reduced to the lowest possible level. This method can be easily applied and is relatively fast in terms of computation time. However the use of GCPs can still cause that the unknowns in the trajectory of the platforms produce some remarkable residual errors. Automatic methods for data registration have also been developed [Hab+05; MKF09].

### 1.3 Context of the thesis

In France, the study of forests is two fold. They need to be mapped and inventoried. The forest inventory allows to obtain the wood stock at a national scale. Statistics such as volume per hectare, deciduous volume or conifer volume can then be derived. The inventory is performed through field inventory and extrapolated using the forest mapping. Thus, the mapping of forest is very important in order to derive accurate statistics.

The forest mapping is given by a national forest LC database. It is manually interpreted by human operators with VHR infra-red colored (IRC) orthoimages. It assigns a vegetation type to each mapped beach of more than 5000 m<sup>2</sup>. The nomenclature is composed of 32 classes based on hierarchical criteria such as pure stands of the main tree species of the French forest. The forest LC should be updated in a 10 years cycle.

## 1.4 Objectives

Currently, the forest LC is obtained through remote sensing (namely photo-interpretation), an method could be developed to update it automatically. Since an old version of the forest LC is available, it can be used as a ground truth input subsequent classification [Gre+13]. However, the learning process should be carried out carefully [Gre+14b]. Indeed, some area might have change (e.g. forest cuts). Furthermore, the database is designed generalized [SS77]. A simple classification would then not be sufficient in order to retrieve homogeneous patches similar to the forest LC. Such results

1.5. Strategy 5

could be obtained using smoothing methods [Sch12]. Furthermore, an automatic method would allow to enrich the LC, i.e. retrieve homogeneous tree species stands also homogeneous in terms of height [Gre+14a].

## 1.5 Strategy

Two remote sensing modalities are available for the mapping of forested areas at IGN; VHR optical images and lidar cloud points. The VHR images are a part of a national database. In this thesis, the images used have a spatial resolution of 50 cm. Two type of ortho-images are available, a color image (3 bands; red: 600-720 nm, green: 490-610 nm and blue: 430-550 nm) and and IRC image (3 bands; near infra-red: 750-950 nm, red and green) captured by the IGN digital cameras [Sou+12]. It is then possible to obtain four band ortho-images by the combination of the two ortho-images type. IGN also process lots of test flight over forested areas with a laser scanning device. The airborne lidar data were collected using an Optech 3100EA device. The footprint was 0.8 m in order to increase the probability to reach the ground. The point density for all echoes ranges from 2 to 4 points/m².

The registration between airborne lidar point clouds and VHR multispectral images was performed by IGN itself using ground control points. This is a standard procedure in the French mapping agency since IGN operates both sensors and has also a strong expertise in data georeferencing (this is in fact the national institute responsible for that in France for both airborne and spaceborne sensors).

Data were acquired under leaf-on conditions and fit with the standards used in many countries for large-scale operational forest mapping purposes.

The combination of these two data is very relevant for the study of forest, indeed, optical images provide the major information about the tree species, while lidar give information about the vertical structure of the forest. Furthermore, the lidar allows to extract consistent object such as trees.

In order to extract more information from these two modalities, the fusion should be performed at different levels. 3 levels could be defined:

- Low level: It corresponds to the fusion of the observations, in this case, only the reflectance from the optical images and the height of the lidar points.
- Medium level: It corresponds to the fusion of the features, they are derived at the same level (e.g. the pixel) and merged together. It also corresponds to the cooperative understanding of the data; a feature is derived on a modality (e.g. trees from lidar) and use on the other.
- High level: It corresponds to the fusion of decision. One or many classifications have been performed and the final decision is a smart combination of the classifications and the input data.

## 1.6 Structure of the thesis

• State of the art: Chapter 2

• Method: Chapter 3

• Results: Chapter 4

Conclusion and perspectives: Chapter 5

# State of the art

_	_		_
2.1	Stand	segmentation	10
2.2	Segme	entation	13
	2.2.1	Traditional segmentation methods	14
	2.2.2	Segmentation of point cloud	14
	2.2.3	Superpixels methods	15
2.3	Classi	ification	16
	2.3.1	Supervised classification	16
	2.3.2	Dimension reduction and feature selection	17
		Dimension reduction	19
		Feature selection	19
2.4	Smoo	thing methods	19
	2.4.1	Local methods	19
	2.4.2	Global methods	19
_	_		_

## 2.1 Stand segmentation

One should note that the literature remains focused on individual tree extraction and tree species classification, developing site-specific workflows with similar advantages, drawbacks and classification performance. More authors have focused on forest delineation [Eys+12], that do not convey information about the tree species and their spatial distribution. Consequently, no operational framework embedding the automatic analysis of remote sensing data has been yet proposed in the literature for forest stand segmentation [Dec+17].

In the large amount of literature in the field, only few papers focus on the issue of stand segmentation or delineation. They can be categorized with regard to the type of data processed.

First, stand segmentation can be achieved with a single remote sensing source. A stand delineation technique using VHR airborne multispectral imagery is proposed in [Lec+03]. The trees are extracted using a valley following approach and classified into 7 tree species (5 coniferous, 1 deciduous, and 1 non-specified) with a maximum likelihood classifier. A semi-automatic iterative clustering procedure is then introduced to generate the forest polygons.

A hierarchical and multi-scale approach for the identification of stands is adopted in [Her+12]. The data inputs were the 4 bands of an airborne 0.5 m orthoimage (Red, Green, Blue, and Near Infra-Red) allowing to derive the Normalized Difference Vegetation Index (NDVI). The stand mapping solution is based on the Object-Based Image Analysis concept. It is composed of two main phases in a cyclic process: first, segmentation, then classification. The first level consists in over-segmenting the area of interest and performing fine-grained land cover classification. The second level aims to transfer the vegetation type provided by a land cover geodatabase in the stand polygons, already retrieved from another segmentation procedure. The multi-scale analysis appears to have a significant benefit on the stand labeling but it is highly heuristic and requires a correct definition of the stand while we consider it is an interleaved problem.

A seminal stand mapping method using low density airborne lidar data

is proposed in [Koc+09]. It is composed of several steps of feature extraction, creation and raster-based classification. Forest stands are created by grouping neighboring cells within each class. Then, only the stands with a pre-defined minimum size are accepted. Neighboring small areas of different forest types that do not reach the minimum size are merged together to an existing forest stand. The approach offers the advantage of detecting 15 forest types that match very well with the ground truth but to the detriment of simplicity: the flowchart has to be highly reconsidered to fit to other stand specifications. Additionally, the tree species discrimination is not addressed.

The forest stand delineation proposed in [Sul+09] also uses low density airborne lidar still coupling an object-oriented image segmentation and a supervised classification procedure. Three features are computed and rasterized. The segmentation is performed using a region growing approach. Spatially adjacent pixels are grouped into homogeneous discrete image objects or regions. Then, a supervised discrimination of the segmented image is performed using a Battacharya classifier, in order to determine the maturity of the stands. The tree species are ignored and the procedure requires a careful inspection of the raw data both for feature generation and model training.

Following the work of [Wul+08] with IKONOS images, Quickbird-2 panchromatic images are used in [MWW10] to automatically delineate forest stands. A standard image segmentation technique is used and the novelty mainly lies on the fact that its initial parameters are optimized with respect to NFI protocols. They show that meaningful stand heights can be derived, which are a critical input for various modeled inventory attributes.

The method proposed in [Eys+12] aims to generate a forest mask (*forested area* label only) using low density airborne lidar. A Canopy Height Model (CHM) with a spatial resolution of 1 m is derived. The positions and heights of single trees are determined from the CHM using a local maximum filter, based on a moving window approach. Only detected positions with a CHM height superior to 3 m are considered. The crown radii are estimated using an empirical function. The three neighboring trees are connected using a Delaunay triangulation applied to the previously-detected tree position.

The crown cover is then calculated using the crown areas of three neighboring trees and the area of their convex hull for each tree triple. The forest mask is derived from the canopy cover values. While this is not a genuine stand delineation method, this approach could be easily extended to a multi-class problem and enlightens the necessity of individual tree extraction even with limited point densities as a basis for the stand-level analysis. A forest stand delineation also based on airborne lidar data is proposed in [Wu+14]. Three features are first directly extracted from the point cloud. A coarse forest stand delineation is then performed on the feature image using the unsupervised Mean-Shift algorithm, in order to obtain undersegmented raw forest stands. A forest mask is then applied to the segmented image in order to retrieve forest and non-forest raw stands. It may create some small isolated areas, iteratively merged to their most similar neighbor until their size is larger than a user-defined threshold in order to product big raw forest stands. They are then refined into finer level using a seeded region growing based on superpixels. The idea is to select several different superpixels in a raw forest stand and merge them. This method provides a coarse-to-fine segmentation with relatively large stands. The process was only applied on a small area of a forest in Finland, thus, general conclusions can not be drawn.

Secondly, several methods fusing various types of remote sensing data have also been developed. The analysis of the lidar and multispectral data is performed at three levels in [TBH04], following a given hierarchical nomenclature of classes in forested environments. The first level represents small objects (single tree scale, individual trees or small groups of trees) that can be differentiated by spectral and structural characteristics using a rule-based classification. The second level corresponds to the stand level. It is built using the same classification process which summarizes forest development phases by referencing to small scale sub-objects at level 1. The third level is generated by merging objects of the same classified forest-development into larger spatial units. The multi-scale analysis offers the advantage of alleviating the standard issue of individual tree crown detection and proposing development stage labels. Nevertheless, the pipeline is highly heuristic,

under-exploits lidar data and significant confusion between classes are reported.

The automatic segmentation process of forests in [DKW04] is also supplied with lidar and VHR multispectral images. The idea is to divide the forests into higher and lower sections with lidar. An unsupervised classification process is applied to the two new images. The final stand delineation is achieved by segmenting the classification results with pre-defined thresholds. The segmentation results are improved using morphological operators such as opening and closing, which fill the gaps and holes at a specified extent. This method is efficient if the canopy structure is homogeneous and requires a strong knowledge on the area of interest. Since it is based on height information only, it cannot differentiate two stands of similar height but different species.

In [Lep+08] a stand segmentation technique for a forest composed of *Scots Pine*, *Norway Spruce* and *Hardwood* is defined. A hierarchical segmentation on the Crown Height Model followed by a restricted iterative region growing approach is performed on images composed of rasterized lidar data and Colored Infra-Red images. The process was only applied on a limited area of Finland and prevents from drawing strong conclusions. However, the quantitative analysis carried out by the authors shows that lidar data can help to define statistically meaningful stands (here the criterion was the timber volume) and that multispectral images are inevitable inputs for tree species discrimination.

## 2.2 Segmentation

The direct segmentation of the optical image and/or the lidar point clouds is not sufficient in order to retrieve forest stands. However, with adapted parameters, segmentations algorithms might be useful to obtain relevant over-segmentation of the data [Dec+17]. They can be divide in two categories:

• The pure segmentation methods, in theses methods, a specific attention must be paid to the choice of the parameter in order to obtain a

relevant over-segmentation. Such segmentation can be applied on an image or a point cloud. Specific methods have also been developed for the segmentation of lidar point cloud.

• The superpixels segmentation methods, they natively produce an oversegmentation of the image. The parameters control the size and the shape of the resulting segments.

### 2.2.1 Traditional segmentation methods

The segmentation of an image can be performed using number of techniques [PP93].

The easiest way to segment an image is the thresholding of a gray level histogram of the image [TFJ89]. When the image is noisy or the background is uneven and illumination is poor, such thresholding might be not sufficient. Thus, adaptive thresholding methods have been developed [YB89].

The segmentation can be considered as an unsupervised classification problem. Algorithms dealing with such problems use iterative process. The most popular algorithm is the k-means algorithm. Segmentation methods using the spatial interaction models like Markov Random Field (CRF) [HE82] or Gibbs Random Field (GRF) [DE87]. Neural networks are also interesting for image segmentation [GPP91] as they take into account the contextual information.

Lastly, the segmentation of an image can be obtained by the detection of the edges of the image [PM82]. The idea is to extract points of significant changes in depth values. Edges are local features and are determined based on local information.

### 2.2.2 Segmentation of point cloud

The segmentation of point cloud has been highly assessed [NL13]. The aim is to extract meaningful objects. Such extraction has two principal objectives:

- Objects are detected so as to ease or strengthen subsequent classification task. A precise extraction is not mandatory since the labels would be refined after.
- Objects are precisely delineated in order to derive features from these objects. A high spatial resolution is therefore expected.

In forested areas, the only reliable objects to extract are trees. The first way to extract trees from lidar data is to rasterize the point cloud and use image-based segmentation techniques to obtain trees. Several methods have been developed for single tree delineation [Dal+14; Vég+14; Kan+14].

### 2.2.3 Superpixels methods

Several superpixels algorithms have been developed [Ach+12]. They group pixels into perceptually meaningful atomic regions. Many traditional segmentation algorithms have been employed with more or less success to generate superpixels [SM00; FH04; CM02; VS08; VS91]. These algorithms produce satisfactory results, however, they may be relatively slow and the number, size and shape of the superpixels might not be specified.

Superpixels algorithms have then been developed. One can control the number of superpixel, their size and their shape. [Moo+08] creates superpixels based on a grid. Optimal path are found using graph cut methods. [VBM10] proposes a generation of superpixels based on a global optimization. They are obtained by stitching together overlapping image patches such that each pixel belongs to only one of the overlapping regions. [Lev+09] generate superpixels by a dilatation of a set of seed locations using level-set geometric flow. Resulting superpixels are constrained to have uniform size, compactness, and boundary adherence. Finally, [Ach+12] proposes a generation of superpixels based on the k-means algorithms. A weighted distance that combines color and spatial proximity is introduced in order to control the size and the compactness of the superpixels.

### 2.3 Classification

A classification is a process that aim to categorize observation. The idea is to assign an observation to one or more classes. This can be done manually or algorithmically. The classification can be unsupervised, the classes need to be learned and the observation assigned. Such classification is similar to segmentation (see section 2.2). The classification can be supervised, the target classes are known and observations with labels are available.

### 2.3.1 Supervised classification

A great number of supervised classification algorithms have been developed and used for remote sensing issues [Lan05; LW07; MT16]. There are two kind of algorithms: the parametric and the non-parametric methods. The parametric method assume that each class follow a specific distribution (mainly gaussian). The parameters of the distribution are estimated using the learning set. This is the case for the maximum likelihood [Str80], maximum a posteriori [Fau+15] or in [TSB05].

The non parametric method do not make any assumption on the classes distribution. In this category of algorithms, the most popular are the Support Vector Machines (SVM) [BGV92; SS01] and the Random Forest (RF) [Bre01]. The artificial neural networks are also efficient algorithms [Hep+90; ACL97]. Simpler methods exist, such as the k-nearest neighbor [IM98] or the decision trees [Bre+84]. The non parametric methods are more efficient for the discrimination of complex classes [PS95; Foo02], and are considered as a basis for land cover classification [CVB09].

We chose to use the RF, which besides their widespread use, since they also offer the possibility of obtaining the probability of belonging of a pixel to a class. This posterior probabilities can be then integrated into a smoothing process. The RF are described in the following paragraph.

#### **RF**

The RF have been introduced by [Bre01] and are defined by the aggregation of collection of predictor (decision trees). Here, we refer to the RF with random inputs proposed in this article.

2.3. Classification 17

The idea is to create an ensemble of samples  $S_n^{\Theta_1}$ , ...,  $S_n^{\Theta_k}$ . A Classification and Regression Tree (CART) [Bre+84] is built on each sample  $S_n^{\Theta_i}$ . Each tree is built using a a random pool of m features. The final classification is obtained by majority vote; each tree vote for a class, the class with the most vote wins (see Figure 2.1. This algorithm has two parameters: the number of trees k and the number of features m used to build a tree. The first parameter is arbitrary fixed to a high value. The second is generally fixed to the square root of the total number of feature [GBS06]. RF have shown better classification performances than traditional Boosting methods [Bre01] or SVM [Pal05]. They are also able to handle big dataset with large number of feature. Furthermore, a measure of feature importance have been introduced in [Bre01]. It allows to qualify the relevance of the feature in the classification process [Str+07].

The importance of a feature  $\mathbf{X}_j$ ,  $j \in \{1,...,q\}$  (with q the number of feature) is defined as follow. Let  $\mathcal{S}_n^{\Theta_i}$  be a sample and  $OOB_i$  all the observations that does not belong to  $\mathcal{S}_n^{\Theta_i}$ .  $errOOB_i$ , the error on  $OOB_i$  using  $\mathcal{S}_n^{\Theta_i}$ , is then computed. A random permutation on the value of the  $j^{\text{th}}$  feature of  $OOB_i$  is performed in order to obtain  $OOB_i^j$ .  $errOOB_i^j$  is then computed. The importance of the feature j,  $FI(\mathbf{X_j})$  is the mean of the difference of the errors (see Equation 2.1).

$$FI(\mathbf{X_j}) = \frac{1}{k} \sum_{i=1}^{k} (errOOB_i^j - errOOB_i)$$
 (2.1)

where k is the number of CART.

#### 2.3.2 Dimension reduction and feature selection

The feature selection methods try to overcome the curse of high dimensionality [Bel15; Hug68]. Indeed, the increasing number of feature available tends to decrease the accuracy of the classifiers. Furthermore, the computation times increase with the number of feature. Thus, reducing the feature dimension is beneficial for the classification task.

Two approaches exist, first the ones based on the transformation of the data, generally using a projection in a space of lower dimensionality. Secondly,




FIGURE 2.1: General diagram of the operation of the Random Forest

there are approaches based on the feature selection, that aim to search for an optimal subset of the features.

#### **Dimension reduction**

The most popular dimension reduction method is the Principal Component Analysis (PCA). It is an unsupervised method that aim to maximize the variance between data [Jol11]. However, it has been demonstrated that PCA is not optimal for the purpose of classification [CB03]. Other methods have been developed based on the PCA: the Independent Component Analysis (ICA) [JH91] maximize the statistical independence between data, and the Maximum Autocorrelation Factor (MAF) [Lar02] maximize the spatial autocorrelation.

#### **Feature selection**

## 2.4 Smoothing methods

#### 2.4.1 Local methods

#### 2.4.2 Global methods



# Method

~		_
3.1	General flowchart	
3.2	Over-segmentation	
	3.2.1 Lidar-based methods	
	3.2.2 Image-based methods	
3.3	Feature extraction	
3.4	Classification	
	3.4.1 Training set design	
	3.4.2 Feature selection	
	3.4.3 Classification	
3.5	Smoothing	
	3.5.1 Local methods	
	3.5.2 Global methods	
_		

### 3.1 General flowchart

With respect to the methods mentioned above, it appears that there are no forest stand segmentation method, based on tree species, that can satisfactorily handle a large number of classes (>5). The proposed framework is a fully automatic and modular method for species-based forest stand segmentation. The method is composed of four main steps; over-segmentation feature computation, vegetation type (mainly tree species) classification and regularization (see Figure 3.1).

Features are first derived at the pixel and at the object level. The most relevant ones are subsequently selected in a supervised way. The objects are extracted using various segmentation methods, since they appear to be sufficient for subsequent steps. A classification is performed at the object level as it significantly improves the discrimination results (about 10% better than the pixel-based approach). This classification is then smoothed. The smoothing may produce homogeneous vegetation type (mainly tree species) areas with smooth borders. The contributions of this method are two-fold:

- Such framework can be fed with specific constraints allowing to tailor the results to specific criteria (height, age, specie, maturity, density,...).
- Here, the training set is automatically derived from an existing forest land-cover geodatabase. Specific attention is paid to the extraction of the most relevant training pixels, which is highly challenging with outdated and generalized vector databases.

23




FIGURE 3.1: Flowchart of the proposed method.

- 3.2 Over-segmentation
- 3.2.1 Lidar-based methods
- 3.2.2 Image-based methods
- 3.3 Feature extraction
- 3.4 Classification
- 3.4.1 Training set design
- 3.4.2 Feature selection
- 3.4.3 Classification
- 3.5 Smoothing
- 3.5.1 Local methods
- 3.5.2 Global methods



# Results





# **Conclusion and perspectives**





# Color code

- Chênes décidus
- Chênes sempervirents
- Hêtre
- Châtaignier
- Robinier
- Autre feuillu pur
- Pin maritime
- Pin sylvestre
- Pin laricio ou pin noir
- Pin d'Alep
- *Pin à crochet ou pin cembro*
- Autre pin pur
- Sapin ou épicéa
- Mélèze
- Douglas
- Autre conifère pur autre que pin
- Lande ligneuse
- Formation herbacée
- Peupleraie

TABLE A.1: Vegetation type color code



## **Publication**

$\sim$	~~~~	
B.1	Journal articles	36
B.2	Peer-reviewed conference papers	36

## **B.1** Journal articles

C. Dechesne, C. Mallet, A. Le Bris, V. Gouet-Brunet. *Semantic segmentation of forest stands of pure species combining airborne lidar data and very high resolution multispectral imagery*. ISPRS Journal of Photogrammetry and Remote Sensing, 126 (2017), pp.129–145, 2017.

M. Fauvel, C. Dechesne, A. Zullo, F. Ferraty. *Fast forward feature selection of hyperspectral images for classification with gaussian mixture models*. IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing, vol. 8(6), pp. 2824-2831, 2015.

## **B.2** Peer-reviewed conference papers

C. Dechesne, C. Mallet, A. Le Bris, V. Gouet-Brunet. *How to combine LI-DAR and very high resolution multispectral images for forest stand segmentation?* Proc. of the IEEE International Geoscience and Remote Sensing Symposium (IGARSS), Fort Worth, USA, July 2017.

C. Dechesne, C. Mallet, A. Le Bris, V. Gouet-Brunet. *Semantic segmentation of forest stands of pure specie as a global optimisation problem*. ISPRS Annals of the Photogrammetry, Remote Sensing and Spatial Information Sciences, 2017.

C. Dechesne, C. Mallet, A. Le Bris, V. Gouet-Brunet. Segmentation sémantique de données de télédétection multimodale : application aux peuplements forestiers. ORASIS, Colleville-sur-Mer, France, Juin 2017.

C. Dechesne, C. Mallet, A. Le Bris, V. Gouet-Brunet, A. Hervieu. *Forest stand segmentation using airborne Lidar data and very high resolution multispectral imagery*. International Archives of Photogrammetry, Remote Sensing and Spatial Information Sciences, vol. 41 (B3), pp 207-214, ISPRS Congress, Prague, Juillet 2016.

## Bibliography

- [Ach+12] Radhakrishna Achanta et al. "SLIC superpixels compared to state-of-the-art superpixel methods". In: *IEEE transactions on pattern analysis and machine intelligence* 34.11 (2012), pp. 2274–2282.
- [ACL97] PM Atkinson, MEJ Cutler, and H Lewis. "Mapping sub-pixel proportional land cover with AVHRR imagery". In: *International Journal of Remote Sensing* 18.4 (1997), pp. 917–935.
- [Bel15] Richard E Bellman. *Adaptive control processes: a guided tour*. Princeton university press, 2015.
- [BGV92] Bernhard E Boser, Isabelle M Guyon, and Vladimir N Vapnik. "A training algorithm for optimal margin classifiers". In: *Proceedings of the fifth annual workshop on Computational learning theory*. ACM. 1992, pp. 144–152.
- [Bre+84] Leo Breiman et al. Classification and regression trees. CRC press, 1984.
- [Bre01] Leo Breiman. "Random forests". In: *Machine learning* 45.1 (2001), pp. 5–32.
- [CB03] Anil Cheriyadat and L Mann Bruce. "Why principal component analysis is not an appropriate feature extraction method for hyperspectral data". In: *Geoscience and Remote Sensing Symposium*, 2003. IGARSS'03. Proceedings. 2003 IEEE International. Vol. 6. IEEE. 2003, pp. 3420–3422.
- [CM02] Dorin Comaniciu and Peter Meer. "Mean shift: A robust approach toward feature space analysis". In: *IEEE Transactions on pattern analysis and machine intelligence* 24.5 (2002), pp. 603–619.

[CVB09] Gustau Camps-Valls and Lorenzo Bruzzone. *Kernel methods for remote sensing data analysis*. John Wiley & Sons, 2009.

- [Dal+14] Michele Dalponte et al. "Tree crown delineation and tree species classification in boreal forests using hyperspectral and ALS data". In: *Remote Sensing of Environment* 140 (2014), pp. 306–317.
- [Dal+15] Michele Dalponte et al. "Delineation of Individual Tree Crowns from ALS and Hyperspectral data: a comparison among four methods". In: *European Journal of Remote Sensing* 48 (2015), pp. 365–382.
- [DBG12] Michele Dalponte, Lorenzo Bruzzone, and Damiano Gianelle. "Tree species classification in the Southern Alps based on the fusion of very high geometrical resolution multispectral/hyperspectral images and LiDAR data". In: *Remote Sensing of Environment* 123 (2012), pp. 258–270.
- [DE87] Haluk Derin and Howard Elliott. "Modeling and segmentation of noisy and textured images using Gibbs random fields". In: *IEEE Transactions on pattern analysis and machine intelligence* 1 (1987), pp. 39–55.
- [Dec+17] Clément Dechesne et al. "Semantic segmentation of forest stands of pure species combining airborne lidar data and very high resolution multispectral imagery". In: ISPRS Journal of Photogrammetry and Remote Sensing 126 (2017), pp. 129–145.
- [DKW04] Oliver Diedershagen, Barbara Koch, and Holger Weinacker. "Automatic segmentation and characterisation of forest stand parameters using airborne lidar data, multispectral and fogis data". In: International Archives of Photogrammetry, Remote Sensing and Spatial Information Sciences 36(8/W2) (2004), pp. 208–212.
- [Eys+12] Lothar Eysn et al. "Forest delineation based on airborne LIDAR data". In: *Remote Sensing* 4.3 (2012), pp. 762–783.
- [Fah+10] Timothy J Fahey et al. "Forest carbon storage: ecology, management, and policy". In: *Frontiers in Ecology and the Environment* 8.5 (2010), pp. 245–252.

[Fau+15] Mathieu Fauvel et al. "Fast forward feature selection of hyperspectral images for classification with Gaussian mixture models". In: *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing* 8.6 (2015), pp. 2824–2831.

- [FH04] Pedro F Felzenszwalb and Daniel P Huttenlocher. "Efficient graph-based image segmentation". In: *International journal of computer vision* 59.2 (2004), pp. 167–181.
- [Foo02] Giles M Foody. "Status of land cover classification accuracy assessment". In: *Remote sensing of environment* 80.1 (2002), pp. 185–201.
- [GBS06] Pall Oskar Gislason, Jon Atli Benediktsson, and Johannes R Sveinsson. "Random forests for land cover classification". In: *Pattern Recognition Letters* 27.4 (2006), pp. 294–300.
- [GPP91] Ashish Ghosh, Nikhil R Pal, and Sankar K Pal. "Image segmentation using a neural network". In: *Biological Cybernetics* 66.2 (1991), pp. 151–158.
- [Gre+13] Adrien Gressin et al. "Updating land cover databases using a single very high resolution satellite image". In: *The ISPRS Workshop on Image Sequence Analysis*. Vol. 2. 3. 2013, pp. 13–18.
- [Gre+14a] Adrien Gressin et al. "A unified framework for land-cover database update and enrichment using satellite imagery". In: *Image Processing (ICIP)*, 2014 IEEE International Conference on. IEEE. 2014, pp. 5057–5061.
- [Gre+14b] Adrien Gressin et al. "Updating the new French national land cover database". In: *Geoscience and Remote Sensing Symposium* (IGARSS), 2014 IEEE International. IEEE. 2014, pp. 3534–3537.
- [Hab+05] Ayman Habib et al. "Photogrammetric and LiDAR data registration using linear features". In: *Photogrammetric Engineering & Remote Sensing* 71.6 (2005), pp. 699–707.

[HE82] FR Hansen and Howard Elliott. "Image segmentation using simple Markov field models". In: *Computer Graphics and Image Processing* 20.2 (1982), pp. 101–132.

- [Hep+90] Georgef Hepner et al. "Artificial neural network classification using a minimal training set- Comparison to conventional supervised classification". In: *Photogrammetric Engineering and Remote Sensing* 56.4 (1990), pp. 469–473.
- [Her+12] A Hernando et al. "Spatial and thematic assessment of object-based forest stand delineation using an OFA-matrix". In: *International Journal of Applied Earth Observation and Geoinformation* 19 (2012), pp. 214–225.
- [Hug68] Gordon Hughes. "On the mean accuracy of statistical pattern recognizers". In: *IEEE transactions on information theory* 14.1 (1968), pp. 55–63.
- [IM98] Piotr Indyk and Rajeev Motwani. "Approximate nearest neighbors: towards removing the curse of dimensionality". In: *Proceedings of the thirtieth annual ACM symposium on Theory of computing*. ACM. 1998, pp. 604–613.
- [JH91] Christian Jutten and Jeanny Herault. "Blind separation of sources, part I: An adaptive algorithm based on neuromimetic architecture". In: *Signal processing* 24.1 (1991), pp. 1–10.
- [Jol11] Ian Jolliffe. "Principal component analysis". In: *International encyclopedia of statistical science*. Springer, 2011, pp. 1094–1096.
- [Kan+14] Kaja Kandare et al. "A new procedure for identifying single trees in understory layer using discrete LiDAR data". In: *Geoscience and Remote Sensing Symposium (IGARSS)*, 2014 IEEE International. IEEE. 2014, pp. 1357–1360.
- [KM06] Annika Kangas and Matti Maltamo. Forest inventory: methodology and applications. Vol. 10. Springer Science & Business Media, 2006.

[KMW09] M. Kim, M. Madden, and T.A. Warner. "Forest Type Mapping using Object-specific Texture Measures from Multispectral Ikonos Imagery: Segmentation Quality and Image Classification Issues".
In: Photogrammetric Engineering & Remote Sensing 75.7 (2009), pp. 819–829.

- [Koc+09] B Koch et al. "Airborne laser data for stand delineation and information extraction". In: *International Journal of Remote Sensing* 30.4 (2009), pp. 935–963.
- [Lan05] David A Landgrebe. *Signal theory methods in multispectral remote sensing*. Vol. 29. John Wiley & Sons, 2005.
- [Lar02] Rasmus Larsen. "Decomposition using maximum autocorrelation factors". In: *Journal of Chemometrics* 16.8-10 (2002), pp. 427–435.
- [Lec+03] Donald G Leckie et al. "Stand delineation and composition estimation using semi-automated individual tree crown analysis". In: *Remote Sensing of Environment* 85.3 (2003), pp. 355–369.
- [Lee+16] J. Lee et al. "Individual Tree Species Classification From Airborne Multisensor Imagery Using Robust PCA". In: *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing* 9.6 (2016), pp. 2554–2567. ISSN: 1939-1404.
- [Lem+08] TC Lemprière et al. "The importance of forest sector adaptation to climate change". In: *Nat. Resour. Can., Can. For. Serv., North. For. Cent., Edmonton, AB. Inf. Rep. NOR-X-416E* (2008).
- [Lep+08] VJ Leppänen et al. "Automatic delineation of forest stands from LIDAR data". In: *International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences 38(4/C1)* (2008), pp. 5–8.
- [Lev+09] Alex Levinshtein et al. "Turbopixels: Fast superpixels using geometric flows". In: *IEEE transactions on pattern analysis and machine intelligence* 31.12 (2009), pp. 2290–2297.

[LW07] Dengsheng Lu and Qihao Weng. "A survey of image classification methods and techniques for improving classification performance". In: *International journal of Remote sensing* 28.5 (2007), pp. 823–870.

- [Mea+00] Joseph E Means et al. "Predicting forest stand characteristics with airborne scanning lidar". In: *Photogrammetric Engineering & Remote Sensing* 66.11 (2000), pp. 1367–1372.
- [MKF09] Andrew Mastin, Jeremy Kepner, and John Fisher. "Automatic registration of LIDAR and optical images of urban scenes". In: Computer Vision and Pattern Recognition, 2009. CVPR 2009. IEEE Conference on. IEEE. 2009, pp. 2639–2646.
- [Moo+08] Alastair P Moore et al. "Superpixel lattices". In: Computer Vision and Pattern Recognition, 2008. CVPR 2008. IEEE Conference on. IEEE. 2008, pp. 1–8.
- [MT16] Paul Mather and Brandt Tso. Classification methods for remotely sensed data. CRC press, 2016.
- [MWW10] Brice Mora, Michael A. Wulder, and Joanne C. White. "Segment-constrained regression tree estimation of forest stand height from very high spatial resolution panchromatic imagery over a boreal environment". In: *Remote Sensing of Environment* 114.11 (2010), pp. 2474 –2484.
- [NL13] Anh Nguyen and Bac Le. "3D point cloud segmentation: A survey". In: *Robotics, Automation and Mechatronics (RAM), 2013 6th IEEE Conference on.* IEEE. 2013, pp. 225–230.
- [Pal05] M Pal. "Random forest classifier for remote sensing classification". In: *International Journal of Remote Sensing* 26.1 (2005), pp. 217–222.
- [PM82] Tamar Peli and David Malah. "A study of edge detection algorithms". In: *Computer graphics and image processing* 20.1 (1982), pp. 1–21.

[Pom02] Arne Pommerening. "Approaches to quantifying forest structures". In: *Forestry: An International Journal of Forest Research* 75.3 (2002), pp. 305–324.

- [PP93] Nikhil R Pal and Sankar K Pal. "A review on image segmentation techniques". In: *Pattern recognition* 26.9 (1993), pp. 1277–1294.
- [PS95] JD Paola and RA Schowengerdt. "A review and analysis of backpropagation neural networks for classification of remotely-sensed multi-spectral imagery". In: *International Journal of remote sensing* 16.16 (1995), pp. 3033–3058.
- [Sch12] Konrad Schindler. "An overview and comparison of smooth labeling methods for land-cover classification". In: *IEEE Transactions on Geoscience and Remote Sensing* 50.11 (2012), pp. 4534–4545.
- [SM00] Jianbo Shi and Jitendra Malik. "Normalized cuts and image segmentation". In: *IEEE Transactions on pattern analysis and machine intelligence* 22.8 (2000), pp. 888–905.
- [Smi12] William H Smith. *Air pollution and forests: interactions between air contaminants and forest ecosystems*. Springer Science & Business Media, 2012.
- [Sou+12] Jean-Philippe Souchon et al. "A large format camera system for national mapping purposes". In: *Revue Française de Photogram-métrie et de Télédétection* 200 (2012), pp. 48–53.
- [SS01] Bernhard Scholkopf and Alexander J Smola. *Learning with kernels: support vector machines, regularization, optimization, and beyond.* MIT press, 2001.
- [SS77] John Miles Smith and Diane CP Smith. "Database abstractions: aggregation and generalization". In: *ACM Transactions on Database Systems (TODS)* 2.2 (1977), pp. 105–133.

[Str+07] Carolin Strobl et al. "Bias in random forest variable importance measures: Illustrations, sources and a solution". In: *BMC bioinformatics* 8.1 (2007), p. 25.

- [Str80] Alan H Strahler. "The use of prior probabilities in maximum likelihood classification of remotely sensed data". In: *Remote sensing of Environment* 10.2 (1980), pp. 135–163.
- [Sul+09] Alicia A Sullivan et al. "Object-oriented classification of forest structure from light detection and ranging data for stand mapping". In: Western Journal of Applied Forestry 24.4 (2009), pp. 198–204.
- [TBH04] Dirk Tiede, Thomas Blaschke, and Marco Heurich. "Object-based semi automatic mapping of forest stands with Laser scanner and Multi-spectral data". In: *International Archives of Photogrammetry, Remote Sensing and Spatial Information Sciences* 36(8/W2) (2004), pp. 328–333.
- [TFJ89] Torfinn Taxt, Patrick J Flynn, and Anil K Jain. "Segmentation of document images". In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 11.12 (1989), pp. 1322–1329.
- [TMS14] Hossein Torabzadeh, Felix Morsdorf, and Michael E Schaepman. "Fusion of imaging spectroscopy and airborne laser scanning data for characterization of forest ecosystems—A review". In: ISPRS Journal of Photogrammetry and Remote Sensing 97 (2014), pp. 25–35.
- [TSB05] Roger Trias-Sanz and Didier Boldo. "A high-reliability, high-resolution method for land cover classification into forest and non-forest". In: *Image Analysis* (2005), pp. 417–441.
- [VBM10] Olga Veksler, Yuri Boykov, and Paria Mehrani. "Superpixels and supervoxels in an energy optimization framework". In: *Computer Vision–ECCV 2010* (2010), pp. 211–224.
- [VS08] Andrea Vedaldi and Stefano Soatto. "Quick shift and kernel methods for mode seeking". In: *Computer vision–ECCV 2008* (2008), pp. 705–718.

[VS91] Luc Vincent and Pierre Soille. "Watersheds in digital spaces: an efficient algorithm based on immersion simulations". In: *IEEE Transactions on Pattern Analysis & Machine Intelligence* 6 (1991), pp. 583–598.

- [Vég+14] Cédric Véga et al. "PTrees: A point-based approach to forest tree extraction from lidar data". In: *International Journal of Applied Earth Observation and Geoinformation* 33 (2014), pp. 98–108.
- [Whi+16] Joanne C White et al. "Remote sensing technologies for enhancing forest inventories: A review". In: *Canadian Journal of Remote Sensing* 42.5 (2016), pp. 619–641.
- [Wu+14] Zhengzhe Wu et al. "ALS data based forest stand delineation with a coarse-to-fine segmentation approach". In: *IEEE Congress on Image and Signal Processing (CISP)*. Dalian, China, 2014, pp. 547–552.
- [Wul+08] Michael A Wulder et al. "Towards automated segmentation of forest inventory polygons on high spatial resolution satellite imagery". In: *The Forestry Chronicle* 84.2 (2008), pp. 221–230.
- [YB89] Shimon D Yanowitz and Alfred M Bruckstein. "A new method for image segmentation". In: *Computer Vision, Graphics, and Image Processing* 46.1 (1989), pp. 82–95.