

```
1: //
2: //  AppDelegate.h
3: //  LeapPaint
4: //
5: //  Created by cj on 5/7/13.
6: //  Copyright (c) 2013 cjdesch. All rights reserved.
7: //
8:
9: #import <Cocoa/Cocoa.h>
10: #import "cocos2d.h"
11:
12: /** Application Delegate
13:  Creates app instance and binds libraries to interface builder xibs
14:
15:  Serves as an application wide callback object for events that affects the whole application, such as
low-memory, etc.
16:  */
17: @interface AppDelegate : NSObject <UIApplicationDelegate>
18: {
19:
20:     NSWindow      *window_; /**< window is the main window to be displayed */
21:     CCGLView      *glView_; /**< glView is the embedded view in which cocos2d will run inside the windo
w */
22: }
23: @property (strong) IBOutlet NSWindow *window;
24: @property (strong) IBOutlet CCGLView *glView;
25:
26: /** RunGameScene sets up the Cocos2d environment and runs it in the application.
27:  */
28: - (void)runGameScene;
29:
30: /** Toggles from a window to full screen view point
31:  @param sender is the action sending the command
32:  @return IBAction binding to interface builder
33:  */
34: - (IBAction)toggleFullScreen:(id)sender;
35:
36: @end
```

```
1: //
2: //  AppDelegate.m
3: //  LeapPaint
4: //
5: //  Created by cj on 5/7/13.
6: //  Copyright (c) 2013 cjdesch. All rights reserved.
7: //
8:
9: #import "AppDelegate.h"
10: #import "GameScene.h"
11:
12: @implementation AppDelegate
13:
14: @synthesize window=window_, glView=glView_;
15:
16: - (void)applicationDidFinishLaunching:(NSNotification *)aNotification
17: {
18:     // Insert code here to initialize your application
19:     [self runGameScene];
20: }
21:
22:
23: - (void)runGameScene{
24:
25:     CCDirectorMac *director = (CCDirectorMac*) [CCDirector sharedDirector];
26:
27:     //NSRect screensFrame = [[NSScreen mainScreen] frame];
28:     NSRect screensFrame = [[NSScreen mainScreen] visibleFrame];
29:
30:
31:     [glView_ setFrameSize:NSMakeSize(screensFrame.size.width,screensFrame.size.height)];
32:     // enable FPS and SPF
33:     [director setDisplayStats:YES];
34:
35:     // connect the OpenGL view with the director
36:     [director setView:glView_];
37:
38:     // EXPERIMENTAL stuff.
39:     // 'Effects' don't work correctly when autoscale is turned on.
40:     // Use kCCDirectorResize_NoScale if you don't want auto-scaling.
41:     [director setResizeMode:kCCDirectorResize_AutoScale];
42:
43:     //[glView_ setFrameSize:NSMakeSize(window_.frame.size.width>window_.frame.size.height-42)];
44:     // Enable "moving" mouse event. Default no.
45:     [window_ setAcceptsMouseMovedEvents:NO];
46:
47:     // Center main window
48:     [window_ center];
49:
50:     //CCScene *scene = [GameScene node];
51:
52:     CCScene* scene = [GameScene scene];
53:     //[scene addChild:[GameScene node]];
54:
55:
56:
57:     [director runWithScene:scene];
58:
59: }
60:
61:
62:
63: #pragma mark AppDelegate - IBActions
64:
65: - (IBAction)toggleFullScreen: (id)sender
66: {
67:     CCDirectorMac *director = (CCDirectorMac*) [CCDirector sharedDirector];
68:     [director setFullScreen: ! [director isFullScreen] ];
69: }
70:
71:
72:
73:
74: @end
```

```
1: //
2: //  BackgroundLayer.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/9/13.
6: //
7: //
8:
9: #import <Foundation/Foundation.h>
10: #import "cocos2d.h"
11:
12:
13: /** Background Layer
14:     Displays a background image for the scene
15: */
16: @interface BackgroundLayer : CCLayer
17:
18: @end
```

```
1: //
2: // BackgroundLayer.m
3: // LeapPuzz
4: //
5: // Created by cj on 4/9/13.
6: //
7: //
8:
9: #import "BackgroundLayer.h"
10:
11: @implementation BackgroundLayer
12:
13: /** init */
14: - (id)init
15: {
16:     if ((self = [super init]))
17:     {
18:         // Get window size
19:         CGSize size = [[CCDirector sharedDirector] winSize];
20:
21:         // Add a button which takes us back to HelloWorldScene
22:
23:         // Add the generated background
24:         CCSprite *background = [CCSprite spriteWithFile:@"background-fullscreen.png"];
25:         [background setPosition:ccp(size.width / 2, size.height / 2)];
26:
27:         [self addChild:background];
28:
29:     }
30:     return self;
31: }
32:
33: @end
```

```
1: //
2: //  BrushSelectionLayer.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/9/13.
6: //
7: //
8:
9:
10: #import "cocos2d.h"
11: #import "CCControlExtension.h"
12:
13:
14: /** BrushSelectionLayer Delegate
15:  Provides a delegate interface for the layer to notify of actions
16:  */
17: @protocol BrushSelectionLayerDelegate <NSObject>
18: /**
19:  Calls back to notify that the layer can be hidden
20:  */
21: - (void)hidePanel;
22: /**
23:  Calls back to notify a new brushname has been selected
24:  @param brushname is the name of the brush that has been selected.
25:  */
26: - (void)brushSelected:(NSString*)brushname;
27: @end
28:
29: /** BrushSelectionLayer
30:  This user interface layer provides a collection view of all the available brushes that can be selected.
31:  */
32: @interface BrushSelectionLayer : CCLayer{
33:
34:     NSMutableDictionary* imageNameDictionary; /**< imageNameDictionary is the list of brush names available for selection */
35:
36: }
37:
38: @property (nonatomic, weak) id <BrushSelectionLayerDelegate> delegate;/**< delegate is the instance reference for triggering delegate call back functions */
39: @property (nonatomic, readwrite) bool layerHidden;/**< layerHidden tracks the visibility state of the layer */
40:
41:
42: @end
```

```

1: //
2: // BrushSelectionLayer.m
3: // LeapPuzz
4: //
5: // Created by cj on 4/9/13.
6: //
7: //
8:
9: #import "BrushSelectionLayer.h"
10:
11: @implementation BrushSelectionLayer
12: @synthesize delegate;
13: @synthesize layerHidden;
14: - (id)init
15: {
16:     if ((self = [super init]))
17:     {
18:         // Get window size
19:         CGSize size = [[CCDirector sharedDirector] winSize];
20:
21:         // Add a button which takes us back to HelloWorldScene
22:         CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"BrushSelectionLayer" fontName:@"Marker
Felt" fontSize:30];
23:         titleLabel.position = ccp(size.width / 2.0f , 125);
24:
25:
26:         [self addChild:titleLabel];
27:         // Add the generated background
28:         CCSprite *background = [CCSprite spriteWithFile:@"background-fullscreen.png"];
29:         [background setPosition:ccp(size.width / 2, size.height / 2)];
30:         self.layerHidden = true;
31:         [self addChild:background];
32:
33:         [self buttoninit];
34:
35:         int brushCount = 30;
36:         //NSMutableArray* menuItems = [[NSMutableArray alloc] init];
37:         imageNamesDictionary = [[NSMutableDictionary alloc] init];
38:         CCMenu *starMenu = [CCMenu menuWithItems:nil];
39:         for (int i = 0; i < brushCount; i++){
40:             NSString* imagename = [NSString stringWithFormat:@"brush_%d.png",i];
41:             CCMenuItem *starMenuItem = [CCMenuItemImage
42:                                     initWithNormalImage:imagename selectedImage:imagename
43:                                     target:self selector:@selector(brushSelectedAction:)];
44:             //starMenuItem.position = ccp(size.width / 2, size.height / 2);
45:             starMenuItem.tag = i;
46:             [imageNamesDictionary setObject:imagename forKey:[NSString stringWithFormat:@"%d",i]];
47:
48:
49:
50:             [starMenu addChild:starMenuItem];
51:         }
52:
53:         //[starMenu alignItemsHorizontally];
54:         NSNumber* itemsPerRow = [NSNumber numberWithInt:5];
55:         [starMenu alignItemsInColumns:itemsPerRow,itemsPerRow,itemsPerRow,itemsPerRow,itemsPerRow,item
sPerRow, nil];
56:
57:
58:
59:
60:
61:         starMenu.position = ccp(size.width / 2, size.height / 2);
62:         [self addChild:starMenu];
63:
64:     }
65:     return self;
66: }
67:
68:
69:
70: - (void)buttoninit{
71:     CGSize screenSize = [[CCDirector sharedDirector] winSize];
72:     // Add the button
73:     CCScale9Sprite *backgroundButton = [CCScale9Sprite spriteWithFile:@"button.png"];
74:     CCScale9Sprite *backgroundHighlightedButton = [CCScale9Sprite spriteWithFile:@"buttonHighlighted.p
ng"];
75:
76: #ifdef __IPHONE_OS_VERSION_MAX_ALLOWED
77:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"Touch Me!" fontName:@"HelveticaNeue-Bold"

```

```
fontSize:30];
78: #elif __MAC_OS_X_VERSION_MAX_ALLOWED
79:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"Hide" fontName:@"Marker Felt" fontSize:30]
;
80: #endif
81: [titleLabel setColor:ccc3(159, 168, 176)];
82:
83: CCControlButton *controlButton = [CCControlButton buttonWithLabel:titleButton
84:                                     backgroundImage:backgroundButton];
85: [controlButton setBackgroundImage:backgroundHighlightedButton forState:CCControlStateHighlighted]
;
86: [controlButton setTitleColor:ccWHITE forState:CCControlStateHighlighted];
87:
88: controlButton.anchorPoint = ccp(0.5f, 1);
89: controlButton.position = ccp(screenSize.width / 2.0f, screenSize.height -100);
90: [self addChild:controlButton z:1];
91:
92: // Add the black background
93: CCScale9Sprite *background = [CCScale9Sprite spriteWithFile:@"buttonBackground.png"];
94: [background setContentSize:CGSizeMake(300, 170)];
95: [background setPosition:ccp(screenSize.width / 2.0f, screenSize.height / 2.0f)];
96: //[[self addChild:background];
97:
98: // Sets up event handlers
99: [controlButton addTarget:self action:@selector(touchDownAction:) forControlEvents:CCControlEventTo
uchDown];
100: }
101:
102: - (void)touchDownAction:(CCControlButton *)sender
103: {
104:
105:
106:     [self.delegate hidePanel];
107: }
108:
109:
110: - (void)brushSelectedAction:(id)sender
111: {
112:     NSLog(@"Selected Brush");
113:
114:     CCMenuItemImage* menuItem = (CCMenuItemImage*)sender;
115:     int i = menuItem.tag;
116:     NSString* imageName = [imageNameDictionary objectForKey:[NSString stringWithFormat:@"%d",i]];
117:     [self.delegate brushSelected:imageName];
118:     [self.delegate hidePanel];
119:
120: }
121:
122:
123:
124: @end
```

```

1: //
2: //  ControlsLayer.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/9/13.
6: //
7: //
8:
9: #import <Foundation/Foundation.h>
10: #import "cocos2d.h"
11: #import "CCControlExtension.h"
12: #import "BrushSelectionLayer.h"
13: #import "GameSettings.h"
14: /**
15:  Controls Layer Delegate
16:  Provides a delegate interface for the layer to notify of actions
17:  */
18: @protocol ControlsLayerDelegate <NSObject>
19:
20: /**
21:  Callback with a change in color of the brush
22:  @param color is the new selected color value
23:  */
24: - (void)changeColorControl:(ccColor3B)color;
25: /**
26:  Callback with a change in thickness of the brush
27:  @param value is the new selected color value
28:  */
29: - (void)changeThicknessControl:(float)value;
30: /**
31:  Callback with a change in brush texture
32:  @param brushname is the new selected brush value
33:  */
34: - (void)changeBrushControl:(NSString*)brushname;
35: /**
36:  Callback with a change in opacity
37:  @param value is the new selected opacity value
38:  */
39: - (void)changeOpacityControl:(float)value;
40: /**
41:  Callback to notify to clear the drawing
42:  */
43: - (void)clearDrawing;
44: /**
45:  Callback with a change in color
46:  @param mode is the toggled eraser mode
47:  TODO: Turn off eraser mode when new color is selected
48:  */
49: - (void)eraserMode:(bool)mode;
50:
51:
52: @end
53:
54: /** Controls Layer
55:  User interface controls for operating buttons, switches, sliders
56:  */
57:
58: @interface ControlsLayer : CCLayer <BrushSelectionLayerDelegate>{
59:
60:     CCLabelTTF *colorLabel;           /**< colorLabel displays name of color in hash value */
61:     CCLabelTTF *displayValueLabel;    /**< displayValueLabel displays coordinate */
62:     GameSettings* gameSettings;       /**< gameSettings global reference to shared settings instance */
63: }
64: @property (nonatomic, strong) CCControlSlider *slider;           /**< slider is the thickne
ss control of the brush */
65: @property (nonatomic, strong) CCControlSlider *opacitySlider;    /**< opacitySlider is the
opacity contro of the brush*/
66: @property (nonatomic, strong) CCControlSwitch *opacitySwitchControl; /**< opacitySwitchControl
is the control for setting automatic or manual opacity control */
67: @property (nonatomic, strong) CCLabelTTF *opacitydisplayValueLabel; /**< opacitydisplayValueL
abel shows the state of the opacitySwitchControl*/
68: @property (nonatomic, weak) id <ControlsLayerDelegate> delegate; /**< delegate is the insta
nce reference for triggering delegate call back functions */
69: @property (nonatomic, strong) BrushSelectionLayer *brushSelection; /**< brushSelection layer
expands as a drawer to allow for brush selection */
70: @property (nonatomic, strong) CCLabelTTF *displayValueLabel;    /**< displayValueLabel dis
plays eraser toggle state */
71: @property (nonatomic, strong) CCControlSwitch *switchControl;   /**< switchControl is the
eraser toggle */
72:

```



```
73: /**
74:  Recieves brushSizeControl delegate callbacks and updates values in the interface
75:  @param sender is the object performing the callback
76:  */
77: - (void)valueChanged:(CCControlSlider *)sender;
78:
79: /**
80:  Recieves opacitySliderControl delegate callbacks and updates values in the interface
81:  @param sender is the object performing the callback
82:  */
83: - (void)opacitySliderChanged:(CCControlSlider *)sender;
84:
85: /** Expands brushes panel */
86: - (void)expandPanel;
87: /** Collapses Brushes Panel */
88: - (void)collapsePanel;
89:
90: /** Creates and returns a new CCControlSwitch.
91:  @return a generate ControlSwitch
92:  */
93: - (CCControlSwitch *)makeControlSwitch;
94: /** Callback for the change value.
95:  @param sender is the object performing the callback */
96: - (void)switchValueChanged:(CCControlSwitch *)sender;
97: /** Callback for opacity changing with the slider
98:  @param sender is the object performing the callback
99:  */
100: - (void)updateOpacitySlider:(float)value;
101:
102: @end
```

```
1: //
2: // ControlsLayer.m
3: // LeapPuzz
4: //
5: // Created by cj on 4/9/13.
6: //
7: //
8:
9: #import "ControlsLayer.h"
10:
11: @implementation ControlsLayer
12: @synthesize slider;
13: @synthesize opacitySlider;
14: @synthesize opacitydisplayValueLabel;
15: @synthesize opacitySwitchControl;
16: @synthesize delegate;
17:
18: @synthesize displayValueLabel;
19: @synthesize switchControl;
20: @synthesize brushSelection;
21: - (id)init
22: {
23:     if ((self = [super init]))
24:     {
25:         // Get window size
26:         CGSize screenSize = [[CCDirector sharedDirector] winSize];
27:
28:         gameSettings = [GameSettings sharedInstance];
29:
30:         //LayerBackground
31:
32:
33:         [self sliderinit];
34:         //[self buttoninit];
35:         //[self initEraserButton];
36:         [self initEraserSwitch];
37:         [self colorpickerinit];
38:
39:         [self initResetButton];
40:
41:         //Open button
42:
43:         //Close Button
44:         self.brushSelection = [BrushSelectionLayer node];
45:         self.brushSelection.position = ccp(-screenSize.width,0);
46:
47:         self.brushSelection.delegate = self;
48:
49:         [self addChild:brushSelection z:10];
50:         [self initBrushSelectionButton];
51:         [self opacitySliderInit];
52:         [self initOpacitySwitch];
53:         //buttons
54:
55:         // Color picker
56:
57:         //
58:
59:
60:     }
61:     return self;
62: }
63:
64:
65: - (void)sliderinit{
66:
67:     //Slideer
68:     CGSize screenSize = [[CCDirector sharedDirector] winSize];
69:     // Add the slider
70:     self.slider = [CCControlSlider sliderWithBackgroundFile:@"sliderTrack.png"
71:                                                         progressFile:@"sliderProgress.png"
72:                                                         thumbFile:@"sliderThumb.png"];
73:     self.slider.anchorPoint = ccp(0.5f, 1.0f);
74:     self.slider.minimumValue = 0.0f; // Sets the min value of range
75:     self.slider.maximumValue = 5.0f; // Sets the max value of range
76:     self.slider.position = ccp(screenSize.width / 2.0f, 100);
77:
78:
79:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"Size" fontName:@"Marker Felt" fontSize:30]
```

```

80:     titleButton.position = ccp(screenSize.width / 2.0f , 125);
81:
82:     // Add the black background
83:     CCScale9Sprite *background = [CCScale9Sprite spriteWithFile:@"buttonBackground.png"];
84:     [background setContentSize:CGSizeMake(350,100)];
85:     [background setPosition:ccp(screenSize.width / 2.0f, 100)];
86:     [self addChild:background];
87:
88:     [self addChild:titleButton];
89:     // When the value of the slider will change, the given selector will be call
90:     [self.slider addTarget:self action:@selector(valueChanged:) forControlEvents:CCControlEvents:CCControlEventValueCh
anged];
91:
92:     [self addChild:self.slider z:0 tag:1];
93: }
94:
95: - (void)valueChanged:(CCControlSlider *)sender
96: {
97:     // Change value of label.
98:     //NSLog(@"slider value %@", [NSString stringWithFormat:@"Slider value = %.02f", sender.value])
;
99:     [self.delegate changeThicknessControl:sender.value];
100: }
101:
102:
103: - (void)opacitySliderInit{
104:
105:     //Slideer
106:     CGSize screenSize = [[CCDirector sharedDirector] winSize];
107:     CCNode *layer = [CCNode node];
108:     layer.position = ccp(screenSize.width / 2.0f + 200, 100);
109:     [self addChild:layer z:3];
110:
111:     double layer_width = 0;
112:
113:
114:     // Add the black background
115:     CCScale9Sprite *background = [CCScale9Sprite spriteWithFile:@"buttonBackground.png"];
116:     [background setContentSize:CGSizeMake(350,100)];
117:     [background setPosition:ccp(background.contentSize.width / 2.0f, 0)];
118:     [layer addChild:background];
119:     layer_width += background.contentSize.width;
120:
121:     CCLabelTTF *titleButton = [CCLabelTTF labelWithString:@"Opacity" fontName:@"Marker Felt" fontSize:
30];
122:     titleButton.position = ccp(layer_width / 2.0f , 25);
123:
124:
125:     [layer addChild:titleButton];
126:     // When the value of the slider will change, the given selector will be call
127:
128:     // Add the slider
129:     self.opacitySlider = [CCControlSlider sliderWithBackgroundFile:@"sliderTrack.p
ng"
progressFile:@"sliderProgres
s.png"
thumbFile:@"sliderThumb.p
ng"];
132:     self.opacitySlider.anchorPoint = ccp(0.5f, 1.0f);
133:     self.opacitySlider.minimumValue = 0.0f; // Sets the min value of range
134:     self.opacitySlider.maximumValue = 100.0f; // Sets the max value of range
135:     self.opacitySlider.position = ccp(layer_width / 2.0f, 0);
136:
137:     [self.opacitySlider addTarget:self action:@selector(opacitySliderChanged:) forControlEvents:CCCont
rolEventValueChanged];
138:
139:     [layer addChild:self.opacitySlider z:0 tag:2];
140: }
141:
142: - (void)opacitySliderChanged:(CCControlSlider *)sender
143: {
144:
145:     // Change value of label.
146:     //NSLog(@"slider value %@", [NSString stringWithFormat:@"Slider value = %.02f", sender.value])
;
147:     [self.delegate changeOpacityControl:sender.value];
148: }
149:
150: - (void)updateOpacitySlider:(float)value{
151:

```

```
152:
153:     //ensure the value is within its bounds
154:     if(value > self.opacitySlider.maximumValue){
155:         //Max Value
156:         self.opacitySlider.value = self.opacitySlider.maximumValue;
157:     }else if(value < self.opacitySlider.minimumValue){
158:         //Min Value
159:         self.opacitySlider.value = self.opacitySlider.minimumValue;
160:     }else{
161:         self.opacitySlider.value = value;
162:     }
163: }
164:
165:
166: - (void)initOpacitySwitch{
167:
168:     CGSize screenSize = [[CCDirector sharedDirector] winSize];
169:
170:     CCNode *layer = [CCNode node];
171:     //layer.position = ccp(screenSize.width / 2, screenSize.height / 2);
172:     layer.position = ccp(screenSize.width / 2.0f + 400, 125);
173:     [self addChild:layer z:5];
174:
175:     double layer_width = 0;
176:
177:     // Add the black background for the text
178:     CCScale9Sprite *background = [CCScale9Sprite spriteWithFile:@"buttonBackground.png"];
179:     background.contentSize = CGSizeMake(80, 50);
180:     background.position = ccp(layer_width + background.contentSize.width / 2.0f, 0);
181:     //[layer addChild:background];
182:
183:     layer_width += background.contentSize.width;
184:
185: #ifdef __IPHONE_OS_VERSION_MAX_ALLOWED
186:     self.displayValueLabel = [CCLabelTTF labelWithString:@"on" fontName:@"HelveticaNeue-Bold" font
tSize:30];
187: #elif __MAC_OS_X_VERSION_MAX_ALLOWED
188:     self.opacitydisplayValueLabel = [CCLabelTTF labelWithString:@"Auto" fontName:@"Marker Felt" f
ontSize:30];
189: #endif
190:     self.opacitydisplayValueLabel.position = background.position;
191:     //[layer addChild:self.opacitydisplayValueLabel];
192:
193:     // Create the switch
194:     self.opacitySwitchControl = [self makeControlSwitch];
195:     self.opacitySwitchControl.position = ccp(layer_width + 10 + self.opacitySwitchControl.conten
tSize.width / 2, 0);
196:     self.opacitySwitchControl.on = NO;
197:     [layer addChild:self.opacitySwitchControl];
198:
199:     [self.opacitySwitchControl addTarget:self action:@selector(opacitySwitchValueChanged:) forControlEvents:CCControlEventsValueChanged];
200:
201:     // Set the layer size
202:     layer.contentSize = CGSizeMake(layer_width, 0);
203:     layer.anchorPoint = ccp(0.5f, 0.5f);
204:
205:
206: }
207:
208:
209:
210:
211: - (void)opacitySwitchValueChanged:(CCControlSwitch *)sender
212: {
213:     if ([sender isOn])
214:     {
215:         //displayValueLabel.string = @"Eraser";
216:
217:         gameSettings.depthOpacityMode = true;
218:     } else
219:     {
220:         //displayValueLabel.string = @"Eraser";
221:         gameSettings.depthOpacityMode = false;
222:     }
223: }
224:
225:
226:
227: #pragma mark - button
```

```

228:
229: - (void)buttoninit{
230:     CGSize screenSize = [[CCDirector sharedDirector] winSize];
231:     // Add the button
232:     CCScale9Sprite *backgroundButton = [CCScale9Sprite spriteWithFile:@"button.png"];
233:     CCScale9Sprite *backgroundHighlightedButton = [CCScale9Sprite spriteWithFile:@"buttonHighlighted.p
ng"];
234:
235: #ifdef __IPHONE_OS_VERSION_MAX_ALLOWED
236:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"Touch Me!" fontName:@"HelveticaNeue-Bold"
fontSize:30];
237: #elif __MAC_OS_X_VERSION_MAX_ALLOWED
238:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"Touch Me!" fontName:@"Marker Felt" fontSiz
e:30];
239: #endif
240:     [titleLabel setColor:ccc3(159, 168, 176)];
241:
242:     CCControlButton *controlButton = [CCControlButton buttonWithLabel:titleButton
243:                                     backgroundImage:backgroundButton];
244:     [controlButton setBackgroundImage:backgroundHighlightedButton forState:CCControlStateHighlighted]
;
245:     [controlButton setTitleColor:ccWHITE forState:CCControlStateHighlighted];
246:
247:     controlButton.anchorPoint = ccp(0.5f, 1);
248:     controlButton.position = ccp(screenSize.width / 2.0f, screenSize.height / 2.0f);
249:     [self addChild:controlButton z:1];
250:
251:     // Add the black background
252:     CCScale9Sprite *background = [CCScale9Sprite spriteWithFile:@"buttonBackground.png"];
253:     [background setContentSize:CGSizeMake(300, 170)];
254:     [background setPosition:ccp(screenSize.width / 2.0f, screenSize.height / 2.0f)];
255:     [self addChild:background];
256:
257:     // Sets up event handlers
258:     [controlButton addTarget:self action:@selector(touchDownAction:) forControlEvents:CCControlEventTo
uchDown];
259: }
260:
261:
262:
263:
264:
265: - (void)touchDownAction:(CCControlButton *)sender
266: {
267:     NSLog(@"button value %@", [NSString stringWithFormat:@"Touch Down"]);
268: }
269:
270: - (void)initEraserButton{
271:
272:
273:     // Add the button
274:     CCScale9Sprite *backgroundButton = [CCScale9Sprite spriteWithFile:@"button.png"];
275:     CCScale9Sprite *backgroundHighlightedButton = [CCScale9Sprite spriteWithFile:@"buttonHighlighted.p
ng"];
276:
277: #ifdef __IPHONE_OS_VERSION_MAX_ALLOWED
278:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"Touch Me!" fontName:@"HelveticaNeue-Bold"
fontSize:30];
279: #elif __MAC_OS_X_VERSION_MAX_ALLOWED
280:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"Eraser" fontName:@"Marker Felt" fontSize:3
0];
281: #endif
282:     [titleLabel setColor:ccc3(159, 168, 176)];
283:
284:     CCControlButton *controlButton = [CCControlButton buttonWithLabel:titleButton
285:                                     backgroundImage:backgroundButton];
286:     [controlButton setBackgroundImage:backgroundHighlightedButton forState:CCControlStateHighlighted]
;
287:     [controlButton setTitleColor:ccWHITE forState:CCControlStateHighlighted];
288:
289:     controlButton.anchorPoint = ccp(0.5f, 1);
290:     controlButton.position = ccp(100, 100);
291:     [self addChild:controlButton z:1];
292:
293:     // Add the black background
294:     CCScale9Sprite *background = [CCScale9Sprite spriteWithFile:@"buttonBackground.png"];
295:     background.anchorPoint = ccp(0, 0);
296:     [background setContentSize:CGSizeMake(100, 75)];
297:     [background setPosition: ccp(50, 50)];
298:     [self addChild:background];

```

```

299:
300:     // Sets up event handlers
301:     [controlButton addTarget:self action:@selector(eraserAction:) forControlEvents:CCControlEventsTouch
Down];
302: }
303:
304: - (void)eraserAction:(CCControlButton *)sender
305: {
306:     [self.delegate changeColorControl:ccWHITE];
307: }
308: }
309: - (void)initResetButton{
310:
311:     CGSize screenSize = [[CCDirector sharedDirector] winSize];
312:     // Add the button
313:     CCScale9Sprite *backgroundButton = [CCScale9Sprite spriteWithFile:@"button.png"];
314:     CCScale9Sprite *backgroundHighlightedButton = [CCScale9Sprite spriteWithFile:@"buttonHighlighted.p
ng"];
315:
316: #ifdef __IPHONE_OS_VERSION_MAX_ALLOWED
317:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"Touch Me!" fontName:@"HelveticaNeue-Bold"
fontSize:30];
318: #elif __MAC_OS_X_VERSION_MAX_ALLOWED
319:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"Reset" fontName:@"Marker Felt" fontSize:30
];
320: #endif
321:     [titleLabel setColor:ccc3(159, 168, 176)];
322:
323:     CCControlButton *controlButton = [CCControlButton buttonWithLabel:titleLabel
backgroundSprite:backgroundButton];
324:     [controlButton setBackgroundSprite:backgroundHighlightedButton forState:CCControlStateHighlighted]
;
325:
326:     [controlButton setTitleColor:ccWHITE forState:CCControlStateHighlighted];
327:
328:     controlButton.anchorPoint = ccp(0.5f, 1);
329:     controlButton.position = ccp(100, screenSize.height -100);
330:     [self addChild:controlButton z:1];
331:
332:     // Add the black background
333:     CCScale9Sprite *background = [CCScale9Sprite spriteWithFile:@"buttonBackground.png"];
334:     [background setContentSize:CGSizeMake(100, 75)];
335:     [background setPosition:ccp(100, screenSize.height -125)];
336:     [self addChild:background];
337:
338:     // Sets up event handlers
339:     [controlButton addTarget:self action:@selector(resetAction:) forControlEvents:CCControlEventsTouchD
own];
340: }
341:
342:
343: - (void)resetAction:(CCControlButton*)sender{
344:     [self.delegate clearDrawing];
345: }
346:
347:
348: - (CCControlButton *)standardButtonWithTitle:(NSString *)title
349: {
350:     /** Creates and return a button with a default background and title color. */
351:     CCScale9Sprite *backgroundButton = [CCScale9Sprite spriteWithFile:@"button.png"];
352:     CCScale9Sprite *backgroundHighlightedButton = [CCScale9Sprite spriteWithFile:@"buttonHighlighted.p
ng"];
353:
354: #ifdef __IPHONE_OS_VERSION_MAX_ALLOWED
355:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:title fontName:@"HelveticaNeue-Bold" fontSiz
e:30];
356: #elif __MAC_OS_X_VERSION_MAX_ALLOWED
357:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:title fontName:@"Marker Felt" fontSize:30];
358: #endif
359:     [titleLabel setColor:ccc3(159, 168, 176)];
360:
361:     CCControlButton *button = [CCControlButton buttonWithLabel:titleLabel backgroundSprite:background
Button];
362:     [button setBackgroundSprite:backgroundHighlightedButton forState:CCControlStateHighlighted];
363:     [button setTitleColor:ccWHITE forState:CCControlStateHighlighted];
364:
365:     return button;
366: }
367:
368:
369: #pragma mark - ColorPicker

```

```

370:
371: - (void)colorpickerinit{
372:     CGSize screenSize = [[CCDirector sharedDirector] winSize];
373:     CCNode *layer = [CCNode node];
374:     layer.position = ccp (screenSize.width -300 , screenSize.height / 2);
375:     [self addChild:layer z:1];
376:
377:     double layer_width = 0;
378:
379:     // Add the black background for the text
380:     CCScale9Sprite *background = [CCScale9Sprite spriteWithFile:@"buttonBackground.png"];
381:     [background setContentSize:CGSizeMake(150, 50)];
382:     [background setPosition:ccp(layer_width + background.contentSize.width / 2.0f, 0)];
383:     //[layer addChild:background];
384:
385:     layer_width += background.contentSize.width;
386:
387: #ifdef __IPHONE_OS_VERSION_MAX_ALLOWED
388:     colorLabel = [CCLabelTTF labelWithString:@"#color" fontName:@"HelveticaNeue-Bold" fontSize:30];
389: #elif __MAC_OS_X_VERSION_MAX_ALLOWED
390:     colorLabel = [CCLabelTTF labelWithString:@"#color" fontName:@"Marker Felt" fontSize:30];
391: #endif
392:     colorLabel.position = background.position;
393:     //[layer addChild:colorLabel];
394:
395:     // Create the colour picker
396:     CCControlColourPicker *colourPicker = [CCControlColourPicker colourPickerWithHueFile:@"hueBackgrou
nd.png"
397:                                             tintBackgroundFile:@"tintBackgro
und.png"
398:                                             tintOverlayFile:@"tintOverlay
.png"
399:                                             pickerFile:@"picker.png"
400:                                             arrowFile:@"arrow.png"];
401:
402:     colourPicker.color = ccc3(37, 46, 252);
403:     colourPicker.position = ccp (layer_width + colourPicker.contentSize.width / 2, 0);
404:     colourPicker.arrowDirection = CCControlColourPickerArrowDirectionLeft;
405:
406:     // Add it to the layer
407:     [layer addChild:colourPicker];
408:
409: #if NS_BLOCKS_AVAILABLE
410:     // Add block for value changed event
411:     [colourPicker setBlock:^(id sender, CCControlEvent event)
412:     {
413:         [self colourValueChanged:sender];
414:     }
415:     forControlEvents:CCControlEventsValueChanged];
416: #else
417:     // Add the target-action pair
418:     [colourPicker addTarget:self action:@selector(colourValueChanged:) forControlEvents:CCControlEvents
ValueChanged];
419: #endif
420:
421:     layer_width += colourPicker.contentSize.width;
422:
423:     // Set the layer size
424:     layer.contentSize = CGSizeMake(layer_width, 0);
425:     layer.anchorPoint = ccp (0.5f, 0.5f);
426:
427:     // Update the color text
428:     [self colourValueChanged:colourPicker];
429: }
430: - (void)colourValueChanged:(CCControlColourPicker *)sender
431: {
432:     colorLabel.string = [NSString stringWithFormat:@"%02X%02X%02X",sender.color.r, sender.color.g,
sender.color.b];
433:
434:     [self.delegate changeColorControl:sender.color];
435: }
436:
437:
438: #pragma mark - Window Controls
439:
440: - (void)expandPanel{
441:
442:
443: }

```

```

444:
445: - (void)collapsePanel{
446: }
447: }
448:
449: - (void)initEraserSwitch{
450:
451:
452:
453:     CCNode *layer                = [CCNode node];
454:     //layer.position              = ccp (screenSize.width / 2, screenSize.height / 2);
455:     layer.position = ccp(100, 100);
456:     [self addChild:layer z:1];
457:
458:     double layer_width = 0;
459:
460:     // Add the black background for the text
461:     CCScale9Sprite *background = [CCScale9Sprite spriteWithFile:@"buttonBackground.png"];
462:     background.contentSize     = CGSizeMake(80, 50);
463:     background.position        = ccp(layer_width + background.contentSize.width / 2.0f, 0);
464:     [layer addChild:background];
465:
466:     layer_width += background.contentSize.width;
467:
468: #ifdef __IPHONE_OS_VERSION_MAX_ALLOWED
469:     self.displayValueLabel      = [CCLabelTTF labelWithString:@"on" fontName:@"HelveticaNeue-Bold" fontSi
tSize:30];
470: #elif __MAC_OS_X_VERSION_MAX_ALLOWED
471:     self.displayValueLabel      = [CCLabelTTF labelWithString:@"Eraser" fontName:@"Marker Felt" fontSi
ze:30];
472: #endif
473:     displayValueLabel.position = background.position;
474:     [layer addChild:displayValueLabel];
475:
476:     // Create the switch
477:     self.switchControl          = [self makeControlSwitch];
478:     switchControl.position      = ccp (layer_width + 10 + switchControl.contentSize.width / 2, 0);
479:     switchControl.on            = NO;
480:     [layer addChild:switchControl];
481:
482:     [switchControl addTarget:self action:@selector(switchValueChanged:) forControlEvents:CCControlEvents:CCControlEven
tValueChanged];
483:
484:     // Set the layer size
485:     layer.contentSize           = CGSizeMake(layer_width, 0);
486:     layer.anchorPoint           = ccp (0.5f, 0.5f);
487:
488:
489: }
490:
491:
492: - (CCControlSwitch *)makeControlSwitch
493: {
494:     return [CCControlSwitch switchWithMaskSprite:[CCSprite spriteWithFile:@"switch-mask.png"]
495:         onSprite:[CCSprite spriteWithFile:@"switch-on.png"]
496:         offSprite:[CCSprite spriteWithFile:@"switch-off.png"]
497:         thumbSprite:[CCSprite spriteWithFile:@"switch-thumb.png"]
498:         onLabel:[CCLabelTTF labelWithString:@"On" fontName:@"Arial-Bo
ldMT" fontSize:16]
499:         offLabel:[CCLabelTTF labelWithString:@"Off" fontName:@"Arial-B
oldMT" fontSize:16]];
500: }
501:
502:
503: - (void)switchValueChanged:(CCControlSwitch *)sender
504: {
505:     if ([sender isOn])
506:     {
507:         displayValueLabel.string    = @"Eraser";
508:
509:         [self.delegate eraserMode:true];
510:     } else
511:     {
512:         displayValueLabel.string    = @"Eraser";
513:         [self.delegate eraserMode:false];
514:     }
515: }
516:
517:
518: #pragma mark- Brush Selection Delegate

```



```
519:
520: - (void)initBrushSelectionButton{
521:
522:     CGSize screenSize = [[CCDirector sharedDirector] winSize];
523:     // Add the button
524:     CCScale9Sprite *backgroundButton = [CCScale9Sprite spriteWithFile:@"button.png"];
525:     CCScale9Sprite *backgroundHighlightedButton = [CCScale9Sprite spriteWithFile:@"buttonHighlighted.p
ng"];
526:
527: #ifdef __IPHONE_OS_VERSION_MAX_ALLOWED
528:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"Touch Me!" fontName:@"HelveticaNeue-Bold"
fontSize:30];
529: #elif __MAC_OS_X_VERSION_MAX_ALLOWED
530:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:@"Brushes" fontName:@"Marker Felt" fontSize:
30];
531: #endif
532:     [titleLabel setColor:ccc3(159, 168, 176)];
533:
534:     CCControlButton *controlButton = [CCControlButton buttonWithLabel:titleLabel
535:                                     backgroundImage:backgroundButton];
536:     [controlButton setBackgroundImage:backgroundHighlightedButton forState:CCControlStateHighlighted]
;
537:     [controlButton setTitleColor:ccWHITE forState:CCControlStateHighlighted];
538:
539:     controlButton.anchorPoint = ccp(0.5f, 1);
540:     controlButton.position = ccp(screenSize.width -100, screenSize.height -100);
541:     [self addChild:controlButton z:1];
542:
543:     // Add the black background
544:     CCScale9Sprite *background = [CCScale9Sprite spriteWithFile:@"buttonBackground.png"];
545:     [background setContentSize:CGSizeMake(100, 75)];
546:     [background setPosition:ccp(screenSize.width -100, screenSize.height -125)];
547:     [self addChild:background];
548:
549:     // Sets up event handlers
550:     [controlButton addTarget:self action:@selector(brushButtonAction:) forControlEvents:CCControlEvents
TouchDown];
551: }
552:
553:
554: - (void)brushButtonAction:(CCControlButton*)sender{
555:     if (self.brushSelection.layerHidden) {
556:         [self showBrushSelectionPanel];
557:     }else{
558:         [self hideBrushSelectionPanel];
559:     }
560: }
561: }
562:
563:
564: - (void)showBrushSelectionPanel{
565:
566:     self.brushSelection.layerHidden = false;
567:     //[[sprite runAction:[CCMoveBy actionWithDuration:2 position:ccp(50,10)]];
568:     [self.brushSelection runAction:[CCMoveTo actionWithDuration:2 position:ccp(0,0)]];
569: }
570:
571: - (void)hideBrushSelectionPanel{
572:     // Get window size
573:     CGSize screenSize = [[CCDirector sharedDirector] winSize];
574:
575:     self.brushSelection.layerHidden = true;
576:     [self.brushSelection runAction:[CCMoveTo actionWithDuration:2 position:ccp(-screenSize.width,0)]];
577: }
578: }
579:
580: - (void)hidePanel{
581:
582:     [self hideBrushSelectionPanel];
583: }
584:
585:
586: - (void)brushSelected:(NSString *)brushname{
587:     [self.delegate changeBrushControl:brushname];
588: }
589:
590:
591: @end
```

```

1: //
2: //  GameManager.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/2/13.
6: //
7: //
8:
9: #import <Foundation/Foundation.h>
10: #import "cocos2d.h"
11: #import "LeapObjectiveC.h"
12: #import "HUDLayer.h"
13:
14:
15: #import "SketchRenderTextureScene.h"
16: #import "BackgroundLayer.h"
17: #import "ControlsLayer.h"
18: #import "GameSettings.h"
19: #import "SimplePoint.h"
20:
21: /**
22:  Core Application Management
23:  Provides interfaces and controls the various inputs, controls and outputs
24:
25:  */
26: @interface GameManager : CCScene <LeapListener, HUDDelegate, ControlsLayerDelegate>
27: {
28:     InputMode inputMode;    /**< colorLabel displays name of color in hash value */
29:     LeapPointable* currentPointable; /**< colorLabel displays name of color in hash value */
30:     CGPoint currentPoint;    /**< colorLabel displays name of color in hash value */
31:     //Settings
32:     BOOL painting;           /**< painting indicates wether or not the application is painting at that mome
nt*/
33:
34:     GameSettings* gameSettings; /**< gameSettings singleton to global seetings*/
35:
36:
37:     int lastTag;              /**< lastTag is the last tag value tracked of a LeapPointable */
38:     SimplePoint* lastPoint;    /**< lastPoint is the last known point on the screen of the LeapPointa
ble */
39:     int framesSinceLastFound; /**< framesSinceLastFound number of frames since last finding a LeapPo
intable */
40:
41:
42: }
43:
44: @property (nonatomic,strong) HUDLayer* hudLayer;           /**< hudLayer displays the icons f
or tracking where a leapPointable is pointing */
45: @property (nonatomic,strong) SketchRenderTextureScene* textureScene; /**< textureScene is the drawing l
ayer */
46: @property (nonatomic,strong) BackgroundLayer* backgroundLayer; /**< backgroundLayer is the layer
for setting up the background */
47: @property (nonatomic,strong) ControlsLayer* controlsLayer; /**< controlsLayer is the layer fo
r managing interface controls */
48:
49: @property (nonatomic,strong) LeapController* controller;    /**< controller is the leapControl
ler */
50: @property (nonatomic,strong) LeapScreen* leapScreen;         /**< leapScreen references the scr
een being used on the system */
51:
52: /**
53:  Finds the percentage of a number between two values
54:  If the number is greater or less than the range, that boundry of the range will be returned.
55:  @param max is the top range value
56:  @param min is the bottom range value
57:  @param value is the number we are seeking the percentage from
58:  @return the a percentage between 0 and 100%
59:  */
60: - (float)findPercentageDifference:(float)max withMin:(float)min withValue:(float)value;
61:
62: /**
63:  Determines the opacity based upon the Z axis coordinate
64:  @param value is the Z axis coordinate
65:  @return the opacity value to set the brush at.
66:  */
67: - (float)opacityPercentage:(float)value;
68:
69: @end

```

```
1: //
2: //  GameManager.m
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/2/13.
6: //
7: //
8:
9: #import "GameManager.h"
10:
11: @implementation GameManager
12:
13: @synthesize hudLayer;
14: @synthesize textureScene;
15: @synthesize backgroundLayer;
16: @synthesize controlsLayer;
17: @synthesize controller;
18: @synthesize leapScreen;
19:
20:
21: // On "init" you need to initialize your instance
22: -(id) init
23: {
24:     // always call "super" init
25:     // Apple recommends to re-assign "self" with the "super" return value
26:     if( (self=[super init])) {
27:
28:
29:         // create and initialize a Label
30:         CCLabelTTF *label = [CCLabelTTF labelWithString:@"Leap Paint" fontName:@"Marker Felt"
fontSize:64];
31:
32:         // ask director the the window size
33:         CGSize size = [[CCDirector sharedDirector] winSize];
34:
35:         NSLog(@"Window size (pixels)-- Width: %0.0f Height: %0.0f",size.width, size.height);
36:
37:         // position the label on the center of the screen
38:         label.position = ccp( size.width /2 , size.height - 25 );
39:         // add the label as a child to this Layer
40:
41:         [self addChild: label];
42:         [self run];
43:
44:         inputMode = kPressKeyMode;
45:         painting = false;
46:
47:         gameSettings = [GameSettings sharedInstance];
48:
49:         lastTag = -1;
50:         lastPoint = [[SimplePoint alloc] initWithX:0.0f withY:0.0f withZ:0.0f];
51:         framesSinceLastFound = 0;
52:
53:     }
54:     return self;
55: }
56:
57: #pragma mark - SampleDelegate Callbacks
58:
59: /**
60:  LeapMotion SDK Delegate Callback
61:  Init's a LeapMotion instance to initiate connection and tracking with the LeapMotion and assigns the
delegate or listener for the controller
62:  */
63: - (void)run
64: {
65:     controller = [[LeapController alloc] init];
66:     [controller addListener:self];
67: }
68:
69: /**
70:  LeapMotion SDK Delegate Callback
71:  Initialize
72:  Verifies the LeapMotion has been initialized and any additional steps for setup can continue.
73:  */
74:
75: - (void)onInit:(NSNotification *)notification{
76:     NSLog(@"Leap: Initialized");
77: }
78: /**
```

```
79: LeapMotion SDK Delegate Callback
80: Connect
81: Verifies the LeapMotion is connected and additional steps for setup can continue.
82:
83: Sets up the screens to be track intersecting vectors from pointables.
84: */
85:
86: - (void)onConnect:(NSNotification *)notification;
87: {
88:     NSLog(@"Leap: Connected");
89:
90:
91:     //NSArray* screens = controller.calibratedScreens;
92:     NSArray* screens = controller.locatedScreens;
93:
94:
95:     if ([screens count] > 0){
96:         leapScreen = [screens objectAtIndex:0];
97:         NSLog(@"Screens: %0.0ld", (unsigned long)[screens count]);
98:
99:
100:    }else{
101:        NSLog(@"No Screens");
102:    }
103:
104:    NSLog(@"running");
105:
106: }
107: /**
108: LeapMotion SDK Delegate Callback
109: Disconnect
110: Notifies the application that the LeapMotion has been disconnected and hold or release any processes
in regard to the LeapMotion
111: */
112:
113: - (void)onDisconnect:(NSNotification *)notification{
114:     NSLog(@"Leap: Disconnected");
115: }
116:
117: /**
118: LeapMotion SDK Delegate Callback
119: Exits
120: Releases memory and sets object instances to nil (null)
121: */
122: - (void)onExit:(NSNotification *)notification{
123:     NSLog(@"Leap: Exited");
124: }
125: /**
126: LeapMotion SDK Delegate Callback
127: OnFrame Event notifies the application that an incoming frame has been processed and the data can be
used to control the application
128: */
129:
130: - (void)onFrame:(NSNotification *)notification{
131:     //NSLog(@"OnFrame");
132:     LeapController *aController = (LeapController *)[notification object];
133:     // Get the most recent frame and report some basic information
134:     LeapFrame *frame = [aController frame:0];
135:
136:     //Try and find the same one as last time.
137:     if ([[frame pointables] count] != 0) {
138:         NSArray* leapPointables = [frame pointables];
139:
140:         LeapPointable* tool;
141:         if (lastTag != -1){
142:             for (LeapPointable* pointable in leapPointables){
143:
144:                 if (lastTag == pointable.id){
145:
146:                     tool = pointable;
147:                     lastTag = pointable.id;
148:                     break;
149:                 }
150:
151:             }
152:
153:             //Find a new point able
154:             if (tool == nil){
155:
156:                 tool = [self pointableClosestToScreen:leapPointables];
```

```
157:         lastTag = tool.id;
158:
159:     }
160:
161:
162:     }else{
163:         //Find a new pointable
164:         tool = [self pointableClosestToScreen:leapPointables];
165:         lastTag = tool.id;
166:
167:     }
168:
169:     //Get the screen
170:     LeapVector* normalized = [leapScreen intersect:tool normalize:YES clampRatio:2.0];
171:
172:     if ([leapScreen isValid]){
173:         double x = normalized.x * [leapScreen widthPixels];
174:         double y = normalized.y * [leapScreen heightPixels];
175:
176:         CGPoint pointer = CGPointMake(x, y);
177:
178:         //Convert to Local coordinates from Screen Coordinates
179:         CCDirector* director = [CCDirector sharedDirector];
180:         NSPoint var = [director.view.window convertScreenToBase:pointer];
181:
182:         //Logging
183:         //NSLog(@"x %0.0f y %0.0f z %0.0f Pointer: x %0.0f y %0.0f ", x, y, tool.tipPosition.z, var
.x, var.y);
184:         //SimplePoint* simplePoint = [[SimplePoint alloc] initWithPosition:var withZ:tool.tipPosit
ion.z];
185:         //[[NSNotificationCenter defaultCenter] postNotificationName:@"CoordHUDUpdate" object:simp
lePoint];
186:
187:         if (gameSettings.depthOpacityMode){
188:
189:             float opacity = [self opacityPercentage:tool.tipPosition.z];
190:
191:             //Update the controls
192:             [controlsLayer updateOpacitySlider:opacity];
193:
194:         }
195:
196:         if (inputMode == kDepthMode){
197:
198:             if (tool.tipPosition.z > 0){
199:                 painting = FALSE;
200:
201:
202:             }else{
203:                 painting = TRUE;
204:
205:             }
206:
207:
208:             //Update the HUD View
209:             [self.hudLayer toolMoved:var toolID:[NSString stringWithFormat:@"%0.0d",tool.id]];
210:             if (painting){
211:                 [self movedToolTexture:var tool:tool];
212:             }else{
213:                 // NSLog(@"Not Painting");
214:             }
215:
216:         }else{
217:             NSLog(@"Leap Screen is invalid");
218:
219:         }
220:     }else{
221:
222:
223:         NSLog(@"No frame");
224:         //Remove the marker from the HUD view
225:         if (currentPointable != nil) {
226:
227:             [self endLineDrawingTexture:currentPoint tool:currentPointable];
228:             [self.hudLayer endTrackingTool];
229:
230:         }
231:         lastTag = -1;
232:
233:         framesSinceLastFound ++;
```

```
234:         if (framesSinceLastFound > kMaxFrames){
235:
236:             framesSinceLastFound = 0;
237:         }
238:     }
239: }
240: }
241:
242: #pragma mark - TextureScene
243:
244: /** Moves the tool on the screen when painting */
245: - (void)movedToolTexture:(CGPoint)point tool:(LeapPointable*)pointable{
246:
247:     if (currentPointable != nil){
248:
249:         [self moveLineDrawingTexture:point tool:pointable];
250:         currentPointable = pointable;
251:     }else{
252:         [self beginLineDrawingTexture:point tool:pointable];
253:         currentPointable = pointable;
254:     }
255: }
256:
257: /** Begin drawing to the canvas
258: @param point is the current coordinate the LeapPointable is interescting with the screen
259: @param pointable is a reference to the pointable currently drawing
260: */
261:
262: - (void)beginLineDrawingTexture:(CGPoint)point tool:(LeapPointable*)pointable{
263:
264:     [self.textureScene beginDraw:point withZ:pointable.tipPosition.z];
265:     currentPoint = point;
266: }
267: /** Update drawing with a moved image on the canvas
268: @param point is the current coordinate the LeapPointable is interescting with the screen
269: @param pointable is a reference to the pointable currently drawing
270: */
271: - (void)moveLineDrawingTexture:(CGPoint)point tool:(LeapPointable*)pointable{
272:
273:     [self.textureScene updateDraw:point withZ:pointable.tipPosition.z];
274:     currentPoint = point;
275:
276: }
277:
278: /** End the drawing
279: @param point is the current coordinate the LeapPointable is interescting with the screen
280: @param pointable is a reference to the pointable currently drawing
281: */
282: - (void)endLineDrawingTexture:(CGPoint)point tool:(LeapPointable*)pointable{
283:     [self.textureScene endDraw:point];
284:     currentPointable = nil;
285: }
286:
287: #pragma mark - Keyboard Events
288:
289: /** Change Input Mode */
290: - (void)changeMode:(InputMode)mode{
291:     //NSLog(@"Changemode");
292:     inputMode = mode;
293:     gameSettings.inputMode = mode;
294: }
295:
296:
297: /** Change Paiting state
298: @param paintState changes the painting sate
299: */
300: - (void)painting:(BOOL)paintingState{
301:     painting = paintingState;
302:     gameSettings.painting = paintingState;
303: }
304:
305:
306: #pragma mark - ControlsDelegate
307:
308: /** Change the color of the brush
309: Updates the HUD Layer and the Texture Layer
310: @param color is the color to be changed
311: */
312:
313: - (void)changeColorControl:(ccColor3B)color{
```

```
314:
315:     [self.hudLayer changeColor:color];
316:     [self.textureScene changeColor:color];
317:
318: }
319: /** Change the thickness of the brush
320: Updates the HUD Layer and the Texture Layer
321: @param value is the thickness(width) value
322: */
323: - (void)changeThicknessControl:(float)value{
324:
325:     [self.hudLayer changeScale:value];
326:     [self.textureScene changeScale:value];
327: }
328: /** Change the brush type
329: Updates the HUD Layer and the Texture Layer
330: @param brushname is the name of the brush to be changed
331: */
332: - (void)changeBrushControl:(NSString *)brushname{
333:
334:     [self.hudLayer changeBrush:brushname];
335:     [self.textureScene changeBrush:brushname];
336: }
337: /** Change the opacity of the brush
338: Updates the HUD Layer and the Texture Layer
339: @param value is the opacity value
340: */
341: - (void)changeOpacityControl:(float)value{
342:     [self.textureScene changeOpacity:value];
343: }
344:
345: /** Clears the drawing */
346: - (void)clearDrawing{
347:
348:     [self.textureScene clearDrawing];
349:
350:     /**Turns off eraser mode if it is on
351:     if (gameSettings.eraserMode){
352:         gameSettings.eraserMode = false;
353:
354:         //Update texture mode and update Controls layer
355:     }
356: }
357: /** Update the eraser mode
358: Updates the HUD Layer and the Texture Layer
359: @param mode is the current state of the eraser
360: */
361: - (void)eraserMode:(bool)mode{
362:
363:     [self.hudLayer erasingMode:mode];
364:     [self.textureScene erasingMode:mode];
365:
366: }
367:
368: /** Return the Opacity value based on Z position */
369: - (float)opacityPercentage:(float)value{
370:     //NSLog(@"value %0.0f", value);
371:     if (value < kOpMinRange){
372:         return kOpMax;
373:     }else if (value > kOpMaxRange){
374:         return kOpMin;
375:     }else {
376:
377:         float percentage = [self findPercentageDifference:kOpMaxRange withMin:kOpMinRange withValue:val
ue];
378:         //NSLog(@"percentage %0.0f", percentage);
379:
380:         percentage = 100 - percentage;
381:
382:         return percentage;
383:     }
384: }
385:
386: }
387:
388:
389: /** Find the percentage between two numbers */
390: - (float)findPercentageDifference:(float)max withMin:(float)min withValue:(float)value{
391:     return (value - min)/(max - min)*100;
392: }
```

```
393:
394:
395: /**
396:  Using all the pointables, gets the closest one to the screen
397:  @param pointables is an array of pointables currently observed by the LeapMotion
398:  @return pointer that is closest by the screen
399:  */
400: - (LeapPointable*)pointerClosestToScreen:(NSArray*)pointables{
401:
402:     LeapPointable* closestPointable;
403:     for (LeapPointable*pointer in pointables){
404:
405:         //Check for the first iteration that the closest is not equal to nil
406:         if (closestPointable != nil){
407:
408:             if (closestPointable.tipPosition.z > pointer.tipPosition.z){
409:                 closestPointable = pointer;
410:             }
411:
412:         }else{
413:             closestPointable = pointer;
414:         }
415:     }
416: }
417:
418:     return closestPointable;
419: }
420:
421: /**
422:  Find the closest LeapPointable to the current last vector
423:  @param leapVector is the position of the last pointbale
424:  @param pointables is an array of pointables currently observed by the LeapMotion
425:  @return LeapPointable closest to a leapVector
426:  */
427: - (LeapPointable*)pointerClosestToVector:(LeapVector*)leapVector withPointables:(NSArray*)pointables
{
428:
429:
430:     LeapPointable* closestPointable;
431:     //Check to make sure there is atleast one object in the array
432:
433:     //if the array is empty, throw an exception
434:     if ([pointables count] == 0){
435:         NSLog(@"Cannot pass item 0 array");
436:         return nil;
437:     }
438:     //If there is only one object in the array, return it
439:     else if ([pointables count] == 1){
440:         return [pointables objectAtIndex:0];
441:     }else{
442:
443:         //Get the distance for the first point
444:         float minDistance = 0;
445:         closestPointable = [pointables objectAtIndex:0];
446:         minDistance = [leapVector distanceTo:closestPointable.tipPosition];
447:
448:
449:         for (int i = 1; i < [pointables count]; i++){
450:
451:             LeapPointable* point = [pointables objectAtIndex:i];
452:             float distance = [leapVector distanceTo:point.tipPosition];
453:             if ( distance < minDistance){
454:                 minDistance = distance;
455:                 closestPointable = point;
456:             }
457:         }
458:     }
459:
460:     return closestPointable;
461: }
462:
463:
464: @end
```



```
1: //
2: //  GameScene.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/1/13.
6: //
7: //
8:
9: #import <Foundation/Foundation.h>
10: #import "cocos2d.h"
11: #import "HUDLayer.h"
12: #import "GameManager.h"
13: #import "LeapObjectiveC.h"
14: #import "SketchRenderTextureScene.h"
15: #import "BackgroundLayer.h"
16: #import "ControlsLayer.h"
17:
18: /**
19:  GameScene
20:  Initializes and assembles all of the layers and gameobjects into the GameManager
21:
22:  */
23: @interface GameScene : CCScene {
24:
25: }
26: /**
27:  Scene initializes each object and assigns interlinking pointers and delegates to each class
28:  @return scene for CCDirector to begin running
29:  */
30: +(CCScene *) scene;
31:
32: @end
```

```
1: //
2: //  GameScene.m
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/1/13.
6: //
7: //
8:
9: #import "GameScene.h"
10:
11: @implementation GameScene
12:
13: +(CCScene *) scene
14: {
15:     // 'scene' is an autorelease object.
16:     GameManager*scene = [GameManager node];
17:
18:     HUDLayer* hudLayer = [HUDLayer node];
19:     BackgroundLayer* backgroundLayer = [BackgroundLayer node];
20:     ControlsLayer* controlsLayer = [ControlsLayer node];
21:
22:     //setup delegates
23:     hudLayer.delegate = scene;
24:     controlsLayer.delegate = scene;
25:
26:
27:     SketchRenderTextureScene* textureScene = [SketchRenderTextureScene node];
28:     [scene addChild:backgroundLayer z:0];
29:     [scene addChild:controlsLayer z:3];
30:     // add layer as a child to scene
31:     [scene addChild:hudLayer z:5];
32:
33:
34:     [scene addChild:textureScene z:2];
35:
36:
37:     scene.hudLayer = hudLayer;
38:     scene.backgroundLayer = backgroundLayer;
39:     scene.controlsLayer = controlsLayer;
40:
41:     scene.textureScene = textureScene;
42:
43:     // return the scene
44:     return scene;
45: }
46: @end
```

```
1: //
2: //  GameSettings.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/16/13.
6: //
7: //
8:
9: #import <Foundation/Foundation.h>
10:
11:
12: #define kVelMax 1000
13: #define kVelMin 0
14:
15: #define kOpMinRange -80
16: #define kOpMaxRange 120
17:
18: #define kOpMin 0
19: #define kOpMax 100
20:
21: #define kNormalizedVelMax 15
22: #define kNormalizedVelMin 0
23:
24: #define kMaxFrames 1000
25:
26: extern int const BLOCK_SIZE;
27:
28:
29: typedef enum {
30:     kPressKeyMode,
31:     kDepthMode,
32: } InputMode;
33:
34: /**
35:  GameSettings is a globally shared class instance which tracks all the game settings.
36:
37:  This class can be accessed by any object in the game.
38:  */
39: @interface GameSettings : NSObject{
40:
41:
42: }
43: @property (nonatomic,readwrite) BOOL depthOpacityMode;    /**< depthOpacityMode controls use of z axis
44: is control of opacity */
45: @property (nonatomic,readwrite) BOOL painting;            /**< painting indicates whether or not the applicat
46: ion is painting at that moment*/
47: @property (nonatomic,readwrite) BOOL eraserMode;          /**< eraserMode controls erasing on drawin
48: g canvas */
49: @property (nonatomic,readwrite) InputMode inputMode;      /**< inputMode controller input mode for l
50: eapmotion */
51: /** Singleton
52:  Intializes and Returns a shared instance of the class
53:  @return sharedInstance of the class.
54:  */
55: + (GameSettings *)sharedInstance;
56:
57: @end
```

```
1: //
2: //  GameSettings.m
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/16/13.
6: //
7: //
8:
9: #import "GameSettings.h"
10:
11: //Constants
12: int const BLOCK_SIZE = 128;
13:
14: @implementation GameSettings
15: @synthesize depthOpacityMode;
16: @synthesize eraserMode;
17: @synthesize inputMode;
18: @synthesize painting;
19:
20: /** Singleton SharedInstance
21:  Intializes and Returns a shared instance of the class
22:  */
23: + (GameSettings *)sharedInstance
24: {
25:     static GameSettings *sharedInstance;
26:
27:     @synchronized(self)
28:     {
29:         if (!sharedInstance)
30:             sharedInstance = [[GameSettings alloc] init];
31:         return sharedInstance;
32:     }
33: }
34:
35: /**
36:  Initialize the class and sets the default values
37:  */
38: - (id)init
39: {
40:     if (self = [super init]) {
41:         // Init Defaults
42:         self.depthOpacityMode = false;
43:         self.painting = false;
44:     }
45:     return self;
46: }
47: @end
```

```

1: //
2: //  HUDLayer.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/1/13.
6: //
7: //
8:
9: #import <Foundation/Foundation.h>
10: #import "cocos2d.h"
11: #import "LPTool.h"
12: #import "LeapObjectiveC.h"
13: #import "SimplePoint.h"
14: #import "GameSettings.h"
15:
16:
17: /** HUD Delegate Protocol
18:  User interface controls for operating buttons, switches, sliders
19:  */
20: @protocol HUDDelegate <NSObject>
21: /**
22:  Calls back to notify a new input mode has been selected by the keyboard interface
23:  @param mode is the state of the input mode
24:  */
25: - (void)changeMode:(InputMode)mode;
26: /**
27:  Calls back to notify a new change in painting state
28:  @param paintingState
29:  */
30: - (void)painting:(BOOL)paintingState;
31:
32: @end
33:
34: /** HUD Layer
35:  Tracks the position of the LeapCursor on the screen
36:  */
37: @interface HUDLayer : CCLayer {
38:     NSString* primaryToolID; /**< primaryToolID stores the id tag to the pointable in reference*/
39:     LPTool* primaryTool; /**< primaryTool points to the current pointable object*/
40:
41:     InputMode inputMode; /**< inputMode is the current mode of input*/
42:
43:     ccColor3B lastColor; /**< lastColor is the lastColor to be selected */
44:     ccColor3B previousColor; /**< previousColor is the color before the lastcolor to be selected */
45:     NSString* lastBrush; /**< lastBrush is last brush to be selected */
46:     float lastScale; /**< lastScale is last scale to be selected */
47:
48:
49:
50:     CCSprite* paintingIndicator; /**< paintingIndicator shows the state at which the object is current
ly paintg */
51:     BOOL eraseMode; /**< eraseMode determines weather the pointable is painting or erasing
*/
52:
53:
54:     GameSettings* gameSettings; /**< gameSettings singleton to global seetings*/
55:
56:
57: }
58:
59: @property (nonatomic, weak) id <HUDDelegate> delegate; /**< colorLabel displays name of color in hash
value */
60: @property (nonatomic, strong) CCLabelTTF* xyzcoords; /**< xyzcoords is the X,Y,Z coordinates in string
form for displaying on the HUD in real-time for debugging */
61:
62:
63: /**
64:  ToolMoved updates the last known tracked position of the tool.
65:  @param point is the coordinate location on the screen in which pointable intereseects
66:  @param toolid is LeapSDK provided tool id of the tool moving
67:  */
68: - (void)toolMoved:(CGPoint)point toolID:(NSString*)toolid;
69: /**
70:  StartTrackingTool begins the process of tracking a tool starting with a new path
71:  @param point is the coordinate location on the screen in which pointable intereseects
72:  @param toolid is LeapSDK provided tool id of the tool moving
73:  */
74: - (void)startTrackingTool:(CGPoint)point toolID:(NSString*)toolid;
75: /**
76:  MoveTrackingTool updates the position and path of a tool.

```

```
77:  @param point is the coordinate location on the screen in which pointable intersects
78:  @param toolid is LeapSDK provided tool id of the tool moving
79:  */
80: - (void)moveTrackingTool:(CGPoint)point toolID:(NSString*)toolid;
81: /**
82:  EndTracking tool singles the end of the tool being tracked.
83:  The tool may be lost or no longer drawing
84:  */
85: - (void)endTrackingTool;
86:
87:
88: - (void)changeColor:(ccColor3B)color;
89: - (void)changeBrush:(NSString*)brushname;
90: - (void)changeScale:(float)size;
91: - (void)erasingMode:(BOOL)mode;
92:
93: @end
```

```
1: //
2: //  HUDLayer.m
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/1/13.
6: //
7: //
8:
9: #import "HUDLayer.h"
10:
11: @implementation HUDLayer
12: @synthesize delegate;
13: @synthesize xyzcoords;
14: - (id)init
15: {
16:     if ((self = [super init]))
17:     {
18:         // Get window size
19:         CGSize size = [[CCDirector sharedDirector] winSize];
20:
21:         // Add a button which takes us back to HelloWorldScene
22:
23:         // Create a label with the text we want on the button
24:         CCLabelTTF *label = [CCLabelTTF labelWithString:@"Tap Here" fontName:@"Helvetica" font
Size:32.0];
25:
26:         // Create a button out of the label, and tell it to run the "switchScene" method
27:         CCMenuItem *button = [CCMenuItemLabel itemWithLabel:label target:self selector:@select
or(testing:)];
28:
29:         // Add the button to a menu - "nil" terminates the list of items to add
30:         CCMenu *menu = [CCMenu menuWithItems:button, nil];
31:
32:         // Place the menu in center of screen
33:         [menu setPosition:ccp(size.width / 2, size.height / 2)];
34:
35:         lastColor = ccWHITE;
36:         lastBrush = @"roundbrush.png";
37:         lastScale = 1.0;
38:
39:         eraseMode = false;
40:
41:         // Finally add the menu to the layer
42:         //[self addChild:menu];
43: #ifdef __IPHONE_OS_VERSION_MAX_ALLOWED
44:         self.isTouchEnabled = YES;
45:         self.isAccelerometerEnabled = YES;
46: #elif defined(__MAC_OS_X_VERSION_MAX_ALLOWED)
47:         self.isMouseEnabled = YES;
48:         self.isKeyboardEnabled = YES;
49: #endif
50:         inputMode = kDepthMode;
51:
52:         /*
53:         self.xyzcoords = [CCLabelTTF labelWithString:@"Coords" fontName:@"Helvetica" fontSize:16.0];
54:         self.xyzcoords.position = ccp(size.width / 2, 50);
55:         [self addChild:self.xyzcoords];
56:
57:         [[NSNotificationCenter defaultCenter] addObserver:self
58:             selector:@selector(handleHUDCoordUpdate:)
59:             name:@"CoordHUDUpdate"
60:             object:nil];
61:
62:         */
63:
64:     }
65:     return self;
66: }
67:
68:
69: //Add the sprite hud
70: - (LPTool*)addLPTool:(CGPoint)p objectID:(NSString*)objectID withBrushName:(NSString*)brushname{
71:
72:     LPTool *sprite = [LPTool spriteWithFile:brushname];
73:
74:     [self addChild:sprite];
75:
76:     sprite.updated = TRUE;
77:     sprite.toolID = objectID;
78:     [sprite setScale:lastScale];
```

```
79:     sprite.position = ccp( p.x, p.y);
80:     sprite.color = lastColor;
81:
82:     return sprite;
83: }
84:
85: /* Tool Moved */
86: - (void)toolMoved:(CGPoint)point toolID:(NSString*)toolid{
87:
88:     if (primaryTool == nil){
89:         [self startTrackingTool:point toolID:toolid];
90:     }else{
91:         [self moveTrackingTool:point toolID:toolid];
92:     }
93: }
94:
95: /* Start Tracking Tool */
96: - (void)startTrackingTool:(CGPoint)point toolID:(NSString*)toolid{
97:     if (primaryTool == nil){
98:         primaryTool = [self addLPTool:point objectID:toolid withBrushName:lastBrush];
99:     }
100: }
101:
102: /* Move Tracking Tool*/
103: - (void)moveTrackingTool:(CGPoint)point toolID:(NSString*)toolid{
104:
105:     //Create tool if it does not exist
106:     if (primaryTool == nil){
107:         primaryTool = [self addLPTool:point objectID:toolid withBrushName:lastBrush];
108:     }else{
109:         //Update since it does exist
110:         primaryTool.position = point;
111:         if ([toolid isEqualToString:primaryTool.toolID]){
112:             primaryTool.toolID = toolid;
113:         }
114:     }
115: }
116:
117: /* End Trackingn Tool */
118: - (void)endTrackingTool{
119:     if (primaryTool != nil){
120:         [self removeChild:primaryTool cleanup:YES];
121:         primaryTool = nil;
122:     }
123: }
124:
125:
126: //Key up event
127: -(BOOL) ccKeyUp:(NSEvent*)event{
128:
129:     unichar ch = [event keyCode];
130:
131:     if (inputMode == kPressKeyMode){
132:         if ( ch == 49){
133:             [self.delegate painting:FALSE];
134:         }
135:     }
136:
137:     if ( ch == 18){
138:         //change to space bar press mode
139:         inputMode = kPressKeyMode;
140:         [self.delegate changeMode:inputMode];
141:     }else if(ch == 19){
142:         //Change to depth mode
143:         inputMode = kDepthMode;
144:         [self.delegate changeMode:inputMode];
145:     }
146:
147:     return YES;
148: }
149: //Key down event
150: -(BOOL) ccKeyDown:(NSEvent*)event{
151:     unichar ch = [event keyCode];
152:
153:     if (inputMode == kPressKeyMode){
154:         if ( ch == 49){
155:             [self.delegate painting:TRUE];
156:         }
157:     }
158:     return YES;
```



```
159: }
160:
161: - (void)changeColor:(ccColor3B)color{
162:
163:
164:
165:     if(primaryTool != nil){
166:
167:         [primaryTool setColor:color];
168:
169:     }
170:     lastColor = color;
171: }
172:
173: - (void)changeBrush:(NSString*)brushname{
174:
175:     lastBrush = brushname;
176:     if (primaryTool != nil){
177:         //Save important data
178:         CGPoint lastlocation = primaryTool.position;
179:         NSString* toolid = [primaryTool.toolID copy];
180:
181:         //Remove Tool
182:         [self removeChild:primaryTool cleanup:YES];
183:
184:         //Add it back
185:         primaryTool = [self addLPTool:lastlocation objectID:toolid withBrushName:lastBrush];
186:     }
187:
188: }
189:
190:
191: - (void)changeScale:(float)size{
192:
193:     lastScale = size;
194:     if(primaryTool != nil){
195:
196:         [primaryTool setScale:size];
197:     }
198: }
199:
200:
201: - (void)erasingMode:(BOOL)mode{
202:
203:     eraseMode = mode;
204:
205:     //turn Erasing Mode on
206:     if (mode){
207:         previousColor = lastColor;
208:         lastColor = ccRED;
209:         [primaryTool setColor:ccRED];
210:     }else{
211:         //Turn erasing mode off
212:         lastColor = previousColor;
213:         [primaryTool setColor:lastColor];
214:     }
215:
216: }
217:
218: - (void)updateCoordsHUDWithX:(float)x withY:(float)y withZ:(float)z{
219:
220:     self.xyzcoords.string = [NSString stringWithFormat:@"Coords x: %0.0f, y %0.0f, z %0.0f",x,y,z];
221:
222: }
223:
224: - (void)handleHUDCoordUpdate:(id)sender{
225:
226:     NSNotification* note = sender;
227:     //LEDColor* ledColor = note.object;
228:
229:     SimplePoint* point = note.object;
230:
231:     [self updateCoordsHUDWithX:point.x withY:point.y withZ:point.z];
232:
233:
234: }
235:
236:
237: @end
```

```
1: //
2: //  LPCCControlButtonVariableSize.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/9/13.
6: //
7: //
8: #import "cocos2d.h"
9: #import "CCControlExtension.h"
10: /**
11:  LPCCControlButtonVariableSize Extends CCLayer to have a customizable control button interface
12:  */
13: @interface LPCCControlButtonVariableSize : CCLayer
14:
15: /** Creates and return a button with a default background and title color. */
16: - (CCControlButton *)standardButtonWithTitle:(NSString *)title;
17: @end
```

```

1: //
2: // LPCCControlButtonVariableSize.m
3: // LeapPuzz
4: //
5: // Created by cj on 4/9/13.
6: //
7: //
8:
9: #import "LPCCControlButtonVariableSize.h"
10:
11: @implementation LPCCControlButtonVariableSize
12: - (id)init
13: {
14:     if ((self = [super init]))
15:     {
16:         CGSize screenSize = [[CCDirector sharedDirector] winSize];
17:
18:         // Defines an array of title to create buttons dynamically
19:         NSArray *stringArray = [NSArray arrayWithObjects:@"Hello",@"Variable",@"Size",@"!", nil];
20:
21:         CCNode *layer = [CCNode node];
22:         [self addChild:layer z:1];
23:
24:         double total_width = 0, height = 0;
25:
26:         // For each title in the array
27:         for (NSString *title in stringArray)
28:         {
29:             // Creates a button with this string as title
30:             CCControlButton *button = [self standardButtonWithTitle:title];
31:             [button setPosition:ccp (total_width + button.contentSize.width / 2, button.contentSize.height / 2)];
32:             [layer addChild:button];
33:
34:             // Compute the size of the layer
35:             height = button.contentSize.height;
36:             total_width += button.contentSize.width;
37:         }
38:
39:         [layer setAnchorPoint:ccp (0.5, 0.5)];
40:         [layer setContentSize:CGSizeMake(total_width, height)];
41:         [layer setPosition:ccp(screenSize.width / 2.0f, screenSize.height / 2.0f)];
42:
43:         // Add the black background
44:         CCScale9Sprite *background = [CCScale9Sprite spriteWithFile:@"buttonBackground.png"];
45:         [background setContentSize:CGSizeMake(total_width + 14, height + 14)];
46:         [background setPosition:ccp(screenSize.width / 2.0f, screenSize.height / 2.0f)];
47:         [self addChild:background];
48:     }
49:     return self;
50: }
51:
52: #pragma mark -
53: #pragma CCControlButtonTest_HelloVariableSize Public Methods
54:
55: #pragma CCControlButtonTest_HelloVariableSize Private Methods
56:
57: - (CCControlButton *)standardButtonWithTitle:(NSString *)title
58: {
59:     /** Creates and return a button with a default background and title color. */
60:     CCScale9Sprite *backgroundButton = [CCScale9Sprite spriteWithFile:@"button.png"];
61:     CCScale9Sprite *backgroundHighlightedButton = [CCScale9Sprite spriteWithFile:@"buttonHighlighted.png"];
62:     CCLabelTTF *titleLabel = [CCLabelTTF labelWithString:title fontName:@"Marker Felt" fontSize:30];
63:     [titleLabel setColor:ccc3(159, 168, 176)];
64:     CCControlButton *button = [CCControlButton buttonWithLabel:titleLabel backgroundSprite:background
65: Button];
66:     [button setBackgroundSprite:backgroundHighlightedButton forState:CCControlStateHighlighted];
67:     [button setTitleColor:ccWHITE forState:CCControlStateHighlighted];
68:     return button;
69: }
70:
71:
72: @end

```

```
1: //
2: //  LPLine.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/2/13.
6: //
7: //
8:
9: #import <Foundation/Foundation.h>
10: /**
11:  LPLine is tracks the points in one line from beginning to end
12:  */
13: @interface LPLine : NSObject {
14:
15: }
16:
17: @property (nonatomic, strong) NSMutableArray* points;  /**< points is a an array of points for the lin
e */
18: @property (nonatomic, readwrite) float width;  /**< width is a constant width for the line */
19:
20: @end
```

```
1: //
2: //  LPLine.m
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/2/13.
6: //
7: //
8:
9: #import "LPLine.h"
10:
11: @implementation LPLine
12:
13: @synthesize points;
14: @synthesize width;
15:
16: - (id)init
17: {
18:     if ((self = [super init]) != nil) {
19:         self.points = [[NSMutableArray alloc] init];
20:         self.width = 1.0f;
21:     }
22:     return self;
23: }
24:
25: @end
```

```
1: //
2: //  LPPoint.h
3: //  LeapPaint
4: //
5: //  Created by cj on 5/8/13.
6: //  Copyright (c) 2013 cjdesch. All rights reserved.
7: //
8:
9: #import <Foundation/Foundation.h>
10:
11:
12:
13: /**
14:  LPLinePoint is a plotted point for drawing onto the canvas
15:  */
16: @interface LPLinePoint : NSObject{
17:
18:
19: }
20:
21: @property (nonatomic, readwrite) float x; /**< x coordinate */
22: @property (nonatomic, readwrite) float y; /**< y coordinate */
23: @property (nonatomic, readwrite) float width; /**< width of the point */
24:
25: /**
26:  * Init constructor with existing point to create with no width
27:  * @param p an point (x,y)
28:  * @return object instance
29:  */
30: - (id)initWithPosition:(CGPoint)p;
31: /**
32:  * Init constructor with x and y values with no width
33:  * @param xVal coordinate value
34:  * @param yVal coordinate value
35:  * @return object instance
36:  */
37: - (id)initWithX:(float)xVal withY:(float)yVal;
38: /**
39:  * Init constructor with existing point with width
40:  * @param p a point (x,y)
41:  * @param wVal width of the point
42:  * @return object instance
43:  */
44: - (id)initWithPosition:(CGPoint)p withWidth:(float)wVal;
45: /**
46:  * Init constructor with x and y values with width
47:  * @param xVal coordinate value
48:  * @param yVal coordinate value
49:  * @param wVal width of the point
50:  * @return object instance
51:  */
52: - (id)initWithX:(float)xVal withY:(float)yVal withWidth:(float)wVal;
53:
54: /**
55:  * Returns point based on x and y
56:  * @return CGPoint
57:  */
58: - (CGPoint)point;
59: @end
```

```
1: //
2: //  LPPoint.m
3: //  LeapPaint
4: //
5: //  Created by cj on 5/8/13.
6: //  Copyright (c) 2013 cjdesch. All rights reserved.
7: //
8:
9: #import "LPLinePoint.h"
10:
11: @implementation LPLinePoint
12: @synthesize x;
13: @synthesize y;
14: @synthesize width;
15:
16: /** init 2d point with CGPoint */
17: - (id)initWithPosition:(CGPoint)p{
18:     if (self = [super init]) {
19:
20:         self.x = p.x;
21:         self.y = p.y;
22:         self.width = 0.0f;
23:
24:     }
25:     return self;
26: }
27:
28:
29: /** Init Point with 2 separate values */
30: - (id)initWithX:(float)xVal withY:(float)yVal{
31:
32:     if (self = [super init]) {
33:
34:         self.x = xVal;
35:         self.y = yVal;
36:         self.width = 0.0f;
37:
38:     }
39:     return self;
40: }
41:
42:
43:
44: /** Init point with CGPoint and width Value */
45: - (id)initWithPosition:(CGPoint)p withWidth:(float)wVal{
46:     if (self = [super init]) {
47:
48:         self.x = p.x;
49:         self.y = p.y;
50:         self.width = wVal;
51:
52:     }
53:     return self;
54: }
55:
56:
57:
58: /** Init Point with x and y values with width*/
59: - (id)initWithX:(float)xVal withY:(float)yVal withWidth:(float)wVal{
60:
61:     if (self = [super init]) {
62:
63:         self.x = xVal;
64:         self.y = yVal;
65:         self.width = wVal;
66:
67:     }
68:     return self;
69: }
70:
71:
72: /** Return the CGPoint type from the object */
73: - (CGPoint)point{
74:     return CGPointMake(self.x, self.y);
75: }
76:
77:
78:
79: @end
```

```
1: //
2: //  LPTool.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 3/29/13.
6: //
7: //
8:
9: #import <Foundation/Foundation.h>
10: #import "cocos2d.h"
11:
12: /**
13:  Extends CCSprite object with two properties for tracking sprites with pointable objects
14:  */
15:
16: @interface LPTool : CCSprite
17:
18: @property (nonatomic, strong) NSString* toolID; /**< toolID is the ID number assigned by the LeapMotion SDK */
19: @property (nonatomic, readwrite) BOOL updated; /**< updated is if the sprite has been updated in that frame.*/
20:
21:
22:
23:
24: @end
```



```
1: //
2: // LPTool.m
3: // LeapPuzz
4: //
5: // Created by cj on 3/29/13.
6: //
7: //
8:
9: #import "LPTool.h"
10:
11: @implementation LPTool
12:
13:
14: @end
```

```
1: //
2: //  main.m
3: //  LeapPaint
4: //
5: //  Created by cj on 5/7/13.
6: //  Copyright (c) 2013 cjdesch. All rights reserved.
7: //
8:
9: #import <Cocoa/Cocoa.h>
10:
11: int main(int argc, char *argv[])
12: {
13:     return NSApplicationMain(argc, (const char **)argv);
14: }
```

```
1: //
2: // SimplePoint.h
3: // LeapPuzz
4: //
5: // Created by cj on 2/19/13.
6: //
7: //
8:
9: #import <Foundation/Foundation.h>
10: #import "cocos2d.h"
11:
12:
13: /**
14:  * 2D or 3D space coordinate for temporarily manipulating points
15:  *
16:  */
17:
18: @interface SimplePoint : NSObject {
19:
20: }
21:
22: @property (nonatomic, readwrite) float x; /**< x coordinate */
23: @property (nonatomic, readwrite) float y; /**< y coordinate */
24: @property (nonatomic, readwrite) float z; /**< z coordinate */
25: @property (nonatomic, readwrite) BOOL is3d; /**< is3d is 2d or 3d point type */
26:
27:
28: /**
29:  * Init constructor with existing point to create a 2d Point
30:  * @param p an point (x,y)
31:  * @return object instance
32:  */
33: - (id)initWithPosition:(CGPoint)p;
34: /**
35:  * Init constructor with x and y values to create a 2d point
36:  * @param xVal coordinate value
37:  * @param yVal coordinate value
38:  * @return object instance
39:  */
40: - (id)initWithX:(float)xVal withY:(float)yVal;
41: /**
42:  * Init constructor with existing point to create a 3d Point
43:  * @param p a point (x,y)
44:  * @param zVal coordinateValue
45:  * @return object instance
46:  */
47: - (id)initWithPosition:(CGPoint)p withZ:(float)zVal;
48: /**
49:  * Init constructor with x, y and z values to create 3D point
50:  * @param xVal coordinate value
51:  * @param yVal coordinate value
52:  * @param zVal coordinate value
53:  * @return object instance
54:  */
55: - (id)initWithX:(float)xVal withY:(float)yVal withZ:(float)zVal;
56:
57: /**
58:  * Returns point based on x and y
59:  * @return CGPoint
60:  */
61: - (CGPoint)point;
62: @end
```

```
1: //
2: // SimplePoint.m
3: // LeapPuzz
4: //
5: // Created by cj on 2/19/13.
6: //
7: //
8:
9: #import "SimplePoint.h"
10:
11: @implementation SimplePoint
12:
13: @synthesize x,y,z;
14: @synthesize is3d;
15:
16:
17: /** init 2d point with CGPoint */
18: - (id)initWithPosition:(CGPoint)p{
19:     if (self = [super init]) {
20:
21:         self.x = p.x;
22:         self.y = p.y;
23:         self.z = 0.0f;
24:         self.is3d = false;
25:
26:     }
27:     return self;
28: }
29:
30: /** Init 2d Point with 2 separate values */
31: - (id)initWithX:(float)xVal withY:(float)yVal{
32:
33:     if (self = [super init]) {
34:
35:         self.x = xVal;
36:         self.y = yVal;
37:         self.z = 0.0f;
38:         self.is3d = false;
39:
40:     }
41:     return self;
42: }
43:
44:
45: /** Init 3d point with CGPoint and z Value */
46: - (id)initWithPosition:(CGPoint)p withZ:(float)zVal{
47:     if (self = [super init]) {
48:
49:         self.x = p.x;
50:         self.y = p.y;
51:         self.z = zVal;
52:         self.is3d = true;
53:
54:     }
55:     return self;
56: }
57:
58:
59: /** Init 3d Point with 3 separate values */
60: - (id)initWithX:(float)xVal withY:(float)yVal withZ:(float)zVal{
61:
62:     if (self = [super init]) {
63:
64:         self.x = xVal;
65:         self.y = yVal;
66:         self.z = zVal;
67:         self.is3d = true;
68:
69:     }
70:     return self;
71: }
72:
73: /** Return the CGPoint type from the object */
74: - (CGPoint)point{
75:     return CGPointMake(self.x, self.y);
76: }
77:
78:
79: @end
```

```
1: //
2: //  Point.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 2/19/13.
6: //
7: //
8:
9: #import <Foundation/Foundation.h>
10:
11: /**
12:  * 2D space coordinate for temporarily manipulating points
13:  *
14:  */
15:
16: @interface SimplePointObject : NSObject {
17:
18:
19: }
20:
21: @property (nonatomic, readwrite) CGPoint point; /**< point is the X and Y coordinates */
22:
23: - (id)initWithPosition:(CGPoint)p;
24: - (id)initWithX:(float)x withY:(float)y;
25:
26: @end
```

```
1: //
2: //  Point.m
3: //  LeapPuzz
4: //
5: //  Created by cj on 2/19/13.
6: //
7: //
8:
9: #import "SimplePointObject.h"
10:
11: @implementation SimplePointObject
12:
13:
14: - (id)initWithPosition:(CGPoint)p{
15:     if (self = [super init]) {
16:
17:         self.point = p;
18:
19:     }
20:     return self;
21: }
22:
23: - (id)initWithX:(float)x withY:(float)y{
24:
25:     if (self = [super init]) {
26:
27:         self.point = CGPointMake(x, y);
28:
29:     }
30:     return self;
31: }
32: @end
```

```
1: //
2: // SketchRenderTextureScene.h
3: // Cocos2D-CCRenderTexture-Demo
4: //
5: // Copyright (c) 2011 Steffen Itterheim.
6: // Distributed under MIT License.
7: //
8:
9: #import "cocos2d.h"
10: #import "SimplePoint.h"
11: #import "GameSettings.h"
12: @interface SketchRenderTextureScene : CCLayer
13: {
14:     CCSprite* brush;
15:     NSMutableArray* touches;
16:
17:
18:     ccColor3B lastColor;
19:     ccColor3B previousColor;
20:     NSString* lastBrush;
21:     float lastScale;
22:     bool eraseMode;
23:
24:
25: }
26:
27:
28: @property (nonatomic,readwrite) float opacity;
29:
30: - (void)beginDraw:(CGPoint)point withZ:(float)z;
31: - (void)updateDraw:(CGPoint)point withZ:(float)z;
32: - (void)endDraw:(CGPoint)point;
33:
34: - (void)changeColor:(ccColor3B)color;
35: - (void)changeBrush:(NSString*)brushname;
36: - (void)changeScale:(float)size;
37: - (void)changeOpacity:(float)o;
38: - (void)erasingMode:(BOOL)mode;
39:
40: - (void)clearDrawing;
41: @end
```

```
1: //
2: // SketchRenderTextureScene.m
3: // Cocos2D-CCRenderTexture-Demo
4: //
5: // Copyright (c) 2011 Steffen Itterheim.
6: // Distributed under MIT License.
7: //
8:
9: #import "SketchRenderTextureScene.h"
10:
11:
12: @implementation SketchRenderTextureScene
13: @synthesize opacity;
14:
15: -(id) init
16: {
17:     if ((self = [super init]))
18:     {
19:         // create a simple rendertexture node and clear it with the color white
20:
21:         //target = [CCRenderTexture renderTextureWithWidth:s.width height: s.height pixelFormat:kCCTex
ture2DPixelFormat_RGBA8888];
22:         CGSize s = [CCDirector sharedDirector].winSize;
23:
24:         CCDirector* sharedDirector = [CCDirector sharedDirector];
25:         CGSize frameSize = sharedDirector.view.frame.size;
26:
27:
28:
29:         float topbottombar = 300;
30:         float sidebars = 300;
31:
32:
33:
34:
35:         //CCSprite* imageBackground = [CCSprite spriteWithFile:@"squarebrush.png"] ;
36:         //imageBackground set
37:
38:
39:         CCRenderTexture* rtx = [CCRenderTexture renderTextureWithWidth:frameSize.width-sidebars height
: frameSize.height-topbottombar];
40:         [rtx clear:1.0f
41:             g:1.0f
42:             b:1.0f
43:             a:1.0f];
44:
45:         rtx.position = CGPointMake(s.width/2, s.height/2);
46:         [self addChild:rtx z:0 tag:1];
47:
48:
49:
50:
51:         //CCLabelTTF* label = [CCLabelTTF labelWithString:@"Drawing onto CCRenderTexture witho
ut clear" fontName:@"Arial" fontSize:16];
52:         //label.position = CGPointMake(240, 15);
53:         //label.color = ccGRAY;
54:         //[self addChild:label];
55:
56:         // create and retain the brush sprite, but don't add it as child
57:
58:         lastColor = ccWHITE;
59:         lastBrush = @"roundbrush.png";
60:         lastScale = 1.0;
61:
62:         eraseMode = false;
63:         self.opacity = 10;
64:
65:         [self addBrush:lastBrush];
66:
67:
68:
69:         //brush.scale = 0.5f;
70:
71:         // create the array holding the touches
72:         touches = [[NSMutableArray alloc] init];
73:
74:         //[CCTouchDispatcher sharedDispatcher] addTargetedDelegate:self priority:0 swallowsTou
ches:NO];
75:
76:         [self scheduleUpdate];
```



```
77:
78:     }
79:     return self;
80: }
81:
82: - (void)addBrush:(NSString*)brushName{
83:
84:     brush = [CCSprite spriteWithFile:brushName] ;
85:     [brush setScale:lastScale];
86:
87:
88:     if(eraseMode){
89:         [[brush setBlendFunc:(ccBlendFunc) { GL_ZERO, GL_ONE_MINUS_SRC_ALPHA }]];
90:         [brush setBlendFunc:(ccBlendFunc) { GL_ONE, GL_ONE }]];
91:
92:
93:
94:         [brush setOpacity:80];
95:     }else{
96:         brush.color = lastColor;
97:         brush.opacity = opacity;
98:     }
99: }
100:
101: - (void) cleanup
102: {
103:     brush = nil;
104:     touches = nil;
105:
106:     [super cleanup];
107: }
108:
109: - (void)beginDraw:(CGPoint)point withZ:(float)z{
110:     //NSLog(@"Begin Draw");
111:     SimplePoint* simplePoint = [[SimplePoint alloc] initWithPosition:point withZ:z];
112:     [touches addObject:simplePoint];
113: }
114:
115: - (void)updateDraw:(CGPoint)point withZ:(float)z{
116:
117:     // NSLog(@"update Draw");
118:     SimplePoint* simplePoint = [[SimplePoint alloc] initWithPosition:point withZ:z];
119:     [touches addObject:simplePoint];
120: }
121: }
122: - (void)endDraw:(CGPoint)point {
123:     [touches removeAllObjects];
124: }
125:
126:
127: /*
128: - (BOOL) ccTouchBegan:(UITouch *)touch withEvent:(UIEvent *)event
129: {
130:     // add new touches to the array as they come in
131:     [touches addObject:touch];
132:     return YES;
133: }
134:
135: - (void) ccTouchEnded:(UITouch *)touch withEvent:(UIEvent *)event
136: {
137:     // must remove the touches that have ended or where cancelled
138:     [touches removeObject:touch];
139: }
140:
141: - (void) ccTouchCancelled:(UITouch *)touch withEvent:(UIEvent *)event
142: {
143:     [self ccTouchEnded:touch withEvent:event];
144: }
145:
146: */
147: - (void) setBrushColor:(int)color
148: {
149:     switch (color)
150:     {
151:         default:
152:             case 0:
153:                 brush.color = ccWHITE;
154:                 break;
155:             case 1:
156:                 brush.color = ccGREEN;
```

```
157:             break;
158:         case 2:
159:             brush.color = ccRED;
160:             break;
161:         case 3:
162:             brush.color = ccc3(0, 255, 255);
163:             break;
164:         case 4:
165:             brush.color = ccBLUE;
166:             break;
167:     }
168: }
169:
170: -(void) update:(ccTime)delta
171: {
172:
173:     CCRenderTexture* rtx = (CCRenderTexture*)[self getChildByTag:1];
174:
175:     // explicitly don't clear the rendertexture
176:     [rtx begin];
177:
178:     //int color = 0;
179:
180:     // Since we store all current touches in an array, we can render a sprite at each touch locati
on
181:     // even if the touch isn't moving. That way a continued press will increase the opacity of the
sprite
182:     // simply because the sprite is drawn repeatedly with low opacity at the same location.
183:     NSArray* tempTouches = [[NSArray alloc] initWithArray:touches];
184:     for (SimplePoint* touch in tempTouches)
185:     {
186:         //CGPoint touchLocation = [director convertToGL:[touch locationInView:director.openGLV
iew]];
187:         CGPoint touchLocation = [touch point];
188:
189:         // the location must be converted to the rendertexture sprite's node space
190:         touchLocation = [rtx.sprite convertToNodeSpace:touchLocation];
191:
192:         // because the rendertexture sprite is flipped along its Y axis the Y coordinate must
be flipped:
193:         touchLocation.y = rtx.sprite.contentSize.height - touchLocation.y;
194:
195:         //CCLOG(@"touch: %.0f, %.0f", touchLocation.x, touchLocation.y);
196:
197:         // set the brush at that location and render it
198:         brush.position = touchLocation;
199:         //[self setBrushColor:color++];
200:         [brush visit];
201:     }
202:
203:
204:     [rtx end];
205:
206:     [touches removeAllObjects];
207: }
208:
209: - (void)changeColor:(ccColor3B)color{
210:
211:
212:     if(brush != nil){
213:         brush.color = color;
214:     }
215:     lastColor = color;
216: }
217:
218: - (void)changeBrush:(NSString*)brushname{
219:
220:     lastBrush = brushname;
221:     if (brush != nil){
222:         //Save important data
223:         CGPoint lastlocation = brush.position;
224:         [self addBrush:lastBrush];
225:         brush.position = lastlocation;
226:     }
227: }
228:
229:
230:
231: }
232:
```

```
233: - (void)changeScale:(float)size{
234:
235:     lastScale = size;
236:     if (brush != nil){
237:
238:         [brush setScale:size];
239:     }
240: }
241: }
242:
243: - (void)changeOpacity:(float)o{
244:
245:     self.opacity = o;
246:     if (brush != nil){
247:
248:         brush.opacity = self.opacity;
249:     }
250: }
251: }
252:
253: - (void)clearDrawing{
254:
255:     CCRenderTexture* rtx = (CCRenderTexture*)[self getChildByTag:1];
256:
257:     // explicitly don't clear the rendertexture
258:     // [rtx begin];
259:     // glClearColor(r, g, b, a);
260:     // glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
261:     // get rid of the mask
262:     // glColorMask(TRUE, TRUE, TRUE, FALSE);
263:     // [rtx end];
264:
265:     [rtx clear:1 g:1 b:1 a:0];
266:
267: }
268:
269:
270:
271: - (void)erasingMode:(BOOL)mode{
272:
273:     eraseMode = mode;
274:
275:     //turn Erasing Mode on
276:     if (mode){
277:         previousColor = lastColor;
278:         lastColor = ccRED;
279:
280:         CGPoint lastlocation = brush.position;
281:         [self addBrush:lastBrush];
282:         brush.position = lastlocation;
283:
284:     }else{
285:         //Turn erasing mode off
286:         lastColor = previousColor;
287:         CGPoint lastlocation = brush.position;
288:         [self addBrush:lastBrush];
289:         brush.position = lastlocation;
290:
291:     }
292: }
293: }
294:
295:
296:
297:
298:
299: @end
```

```
1: //
2: //  Utility.h
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/24/13.
6: //
7: //
8:
9: #import <Foundation/Foundation.h>
10:
11:
12:
13: /**
14:  Utility class provides common usage function throughout the application.
15:  */
16:
17: @interface Utility : NSObject {
18: }
19:
20: /**
21:  Generates a random number between two designated integers
22:  @param from is the bottom of the range
23:  @param to is the top of the range
24:  @return a random number between the from and to parameters
25:  */
26: + (int) getRandomNumberBetween:(int)from to:(int)to;
27: /**
28:  Generates a random number between 0 designated integer
29:  @param to is the top of the range
30:  @return a random number between 0 and to parameters
31:  */
32: + (int) getRandomUniformNumberUnder:(int)to;
33: /**
34:  Generates a random number between 0 designated integer
35:  @param to is the top of the range
36:  @return a random number between 0 and to parameters
37:  */
38: + (int) getRandomNumberUnder:(int)to;
39: // - (void) initRandomSeed(long firstSeed);
40: // float nextRandomFloat();
41: @end
```

```
1: //
2: //  Utility.m
3: //  LeapPuzz
4: //
5: //  Created by cj on 4/24/13.
6: //
7: //
8:
9: #import "Utility.h"
10:
11: @implementation Utility
12:
13: /** returns random number within a range with defined upper and lower bounds */
14: + (int) getRandomNumberBetween:(int)from to:(int)to {
15:
16:     //Check that one isn't greater than the other
17:     //if so, flip them
18:
19:     return (int)from + arc4random() % (to-from+1);
20: }
21:
22: /** Returns a random number from 0 to an upper bound */
23: + (int) getRandomNumberUnder:(int)to {
24:     return (arc4random() % to);
25: }
26:
27:
28: /** Returns a Uniform Random Number from 0 to an upper bound */
29: + (int) getRandomUniformNumberUnder:(int)to {
30:     //Check if uniform available
31:     if (arc4random_uniform != NULL)
32:         return arc4random_uniform(to);
33:     else
34:         return (arc4random() % to);
35: }
36:
37:
38:
39:
40:
41: /*
42: static unsigned long seed;
43:
44: void initRandomSeed(long firstSeed)
45: {
46:     seed = firstSeed;
47: }
48:
49: float nextRandomFloat()
50: {
51:     return (((seed= 1664525*seed + 1013904223)>>16) / (float)0x10000);
52: }*/
53:
54:
55:
56: @end
```