



专业从事LED显示屏、LED照明、智能交通与系统解决方案提供商

2019

# LED应用产品及系统集成解决方案提供商

户外屏  
户内屏  
小间距屏

LED显示屏

道路照明  
室内商照  
室内家居

LED照明

LED显示控制系统  
智慧照明控制系统  
灯联网

系统集成解决方案







智能交通

可 变 信 息  
情 报 板 及 交  
通 诱 导 屏 绍  
案 例 介 绍



# 项目案例- 宁杭高速可变情报板项目



宁杭高速

## 项目技术参数 - 宁杭高速可变情报板项目

项目	参数						
产品名称	LED显示屏C0402	门架式可变信息标志（CMS）显示板（12个模块）C0630-KXB	悬臂式可变信息标志（FCMS）显示板（8个模块）C0630-KXB	雨棚信号灯C0720-MSL	费额显示器C0730-FX	ETC可变信息屏C0630-KXB	ETC综合信息显示屏C0730-ZX
像素间距	6.35mm	25 mm	25 mm		4.75mm	25 mm	7.62mm
显示颜色	双基色（1R1G）	双基色（2R1G）	双基色（2R1G）		单色（红色）	双基色（2R1G）	双基色（1R1G）
显示尺寸	8. 505m×0. 4884m	14. 4m×1.2m	1. 6m×3. 2m	600mm×600mm	380mm（高）×608mm（宽）	2. 4m×0. 6m	1098mm×549mm
维护方式	后维护						
箱体材料	冷轧钢板						
视角	120度（左右各60度）	半功率角： >30°					
亮度	≥600nits	≥8000nits			≥1500nits	≥8000nits	≥1500nits
输入电压	AC220/380V±15%						
工作环境温度	-20～60℃						
贮存环境温度	-40～85℃						
工作环境湿度	5～95%RH						
贮存环境湿度	5～95%RH						
LED使用寿命	≥10万小时						



# 项目设备清单 - 宁杭高速可变情报板项目

产品名称	型号与规格	品牌	数量	单价（元）	金额（元）	备注
LED显示屏 C0402	显示尺寸: 8. 505mX0.4884m 显示点阵: 1344X64 点间距: 6.35mm 显示颜色: 双基色（1R1G）	三思	1			
门架式可变信息标志（CMS） 显示板（12个模块） C0630-KXB	显示尺寸: 14. 4mx1.2m 显示点阵: 560x48 点间距: 25 mm 显示颜色: 双基色（2R1G）	三思	16			
悬臂式可变信息标志（FCMS） 显示板（8个模块） C0630-KXB	显示尺寸: 1. 6m×3. 2m 显示点阵: 64x128 点间距: 25 mm 显示颜色: 双基色（2R1G）		15			
雨棚信号灯 C0720-MSL	显示内容: 正面红“X”，绿“↓”反面红“X” 外形尺寸: 600 mmx600 mm 光源: 超高亮度LED 半功率角: >30°		87			
费额显示器 C0730-FX	采用LED点阵式显示屏 超高亮度发光二极管（红色） 显示尺寸: 380mm（高）X608mm（宽） 分辨率: 80X128 像素间距: 4.75mm		56			
ETC可变信息屏 C0630-KXB	显示尺寸: 2.4m×0.6m 点间距: 25mm 显示颜色: 双基色（2R1G）		27			
ETC综合信息显示屏 C0730-ZX	采用红绿双色表贴LED显示 显示尺寸: 1098mm×549mm 点间距: 7.62mm		22			

A city skyline at dusk, featuring a prominent tall building with the Tencent logo. The sky is a mix of purple, blue, and orange, with scattered clouds. In the foreground, there are several modern buildings and a road with some traffic. The overall scene is a vibrant urban landscape.

谢谢  
Thank You

---