



Features

- TI AM335x ARM Cortex A8 CPU
- Onboard 256MB DDR3 SDRAM
- Onboard 256MB NAND Flash
- 10/100M Ethernet
- 2*RS232/485
- 2*USB 2.0
- 4G/GPRS/WIFI/NB-IOT Option
- Support Linux 4.4.12/3.2.0
- Support Modbus TCP/RTU/ASCII、MQTT、OPC UA

Specifications

Spec Item	ARiio-5120	ARiio-5120W	
System			
Processor	ARM Cortex-A8 series TI-AM335x		
Memory	Onboard 256MB DDR3		
Storage	Onboard 256MB NAND Flash		
I/O Interface			
Reset IP	1*Reset switch Reset IP		
Ethernet	2*10/100M LAN Port RJ45 Connector	1*10/100M LAN Port RJ45 Connector	
Serial/Parallel	2*RS232/RS485 Support 2.5KV photoelectr	2*RS232/RS485 Support 2.5KV photoelectric isolation protection	
USB	2*USB2.0 (2*6 Pin header female,1*Type	2*USB2.0 (2*6 Pin header female,1*Type A connector)	
Expansion	4*DI: 2*Dry Contact、2*Wet Contact (5V/12V/24V)		
	4*AI: 4-20mA or 1-5V		
	6*DO: 2*Relay、4*Wet Contact (5V/12V/24V@200mA)		
Wireless		4G/GPRS/WIFI/NB-IOT Option	
Storage Space			
Storage	1*Micro SD on board		
Display			

LED	1*PWR 1*RUN 2*GPIO (for RS232/485)		
Power			
Power Input	Wide Range DC 9~36V Input		
Power Connector	3.5mm 1*2 Pin power input connector		
Power consumption	180mA/12V, MAX: 350mA/12V		
Dimension			
Dimension(L*H*W)	160mm*25mm *110mm		
Environmental			
Operating Temperature	-20~70°C		
Storage temperature	-40~85°C		
Humidity	10 to 90% @ 40°C		
Certification	Meet CE/FCC Class A		
Support Protocol			
Protocol	Modbus TCP/RTU/ACSII、MQTT、OPC UA		
Support OS			
OS	Support Linux kernel 4.4.12/3.2.0		

深圳市南山区留仙大道1213号众冠红花岭5区3栋2楼 网址: www.aplexiot.cn 电话: 0755-26647540

邮箱: sales@aplex.com.tw

