

Vessel-GNC: a compact C++/Python laboratory for simulation, estimation and optimal control of autonomous surface vessels

Charles Dhainaut

Abstract

This note documents **vessel-gnc**, a compact simulation, estimation and control stack for autonomous surface vessels. A 3-DOF horizontal-plane model (Fossen-style) is integrated by a C++20 kernel and, independently, by a symbolic CasADi predictor; the two are cross-validated to 10^{-8} on every test run. Around this kernel sit an extended Kalman filter with an augmented current-equivalent state, classical LOS/PID baselines, a disturbance-aware nonlinear MPC and a geometric model predictive contouring controller. Four controllers are compared on one flagship scenario (a 200 m S-curve under rotating current and wind gusts, with noisy sensors and a perturbed truth plant): RMS cross-track error falls from 0.69 m (LOS) to 0.23 m (disturbance-aware NMPC). Every number quoted here is regenerated from committed JSON artifacts by one tool, and a determinism check replays the whole scenario against them. What the project validates is the numerics and the control chain; the physical parameters are illustrative and are not fitted to a real hull.

1 Introduction

Autonomous-vessel guidance work usually falls into one of two camps: a flight-stack style autopilot, where the model is buried under hardware abstraction, or a research codebase, where the model is explicit but the engineering is thin. **vessel-gnc** sits deliberately in between. It is small enough to read in an afternoon, but it is built like instrument software: deterministic by default, cross-validated where two implementations of the same physics meet, and honest about what is verified, what is validated, and what is merely illustrative.

The chain is the one that matters in practice:

$$\text{plant} \rightarrow \text{sensors} \rightarrow \text{estimator} \rightarrow \text{controller} \rightarrow \text{actuators}, \quad (1)$$

run closed-loop, with the controller never seeing the true state or the true environment. The sections below walk through each block, then the measured comparison of four controllers, and finally the reproducibility contract that keeps the published numbers honest.

2 Vessel model

Frames and state. Positions and headings are inertial North–East, with ψ clockwise from North (equivalently a z -down convention); body axes are x forward (surge), y starboard (sway). The pose and body velocity are $\eta = [x, y, \psi]^\top$ and $\nu = [u, v, r]^\top$, with

$$\dot{\eta} = R(\psi) \nu, \quad R(\psi) = \begin{bmatrix} \cos \psi & -\sin \psi \\ \sin \psi & \cos \psi \end{bmatrix}. \quad (2)$$

Hydrodynamics. The momentum equation is written on the velocity *relative* to the water,

$$M\dot{\nu} + C(\nu_{\text{rel}}) \nu_{\text{rel}} + D(\nu_{\text{rel}}) \nu_{\text{rel}} = \tau + \tau_{\text{env}} + \dot{\nu}_c^b, \quad (3)$$

with the diagonal mass matrix $M = \text{diag}(m + X_{\dot{u}}, m + Y_{\dot{v}}, I_z + N_{\dot{r}})$ and the skew-symmetric Coriolis form for diagonal M ,

$$C(\nu_{\text{rel}}) \nu_{\text{rel}} = \begin{bmatrix} -m_{22} v_{\text{rel}} r \\ m_{11} u_{\text{rel}} r \\ (m_{22} - m_{11}) u_{\text{rel}} v_{\text{rel}} \end{bmatrix}. \quad (4)$$

The yaw component is the destabilizing Munk coupling: for a slender hull ($m_{22} > m_{11}$) it assists a turn once the vessel develops sideslip. It is kept on purpose, and the default parameters leave yaw damping dominant at cruise so the vessel is directionally stable. Damping is linear plus quadratic in the relative velocity, $X_u u_r + X_{|u|u} |u_r| u_r$ per axis.

The current is uniform and irrotational. Because the body frame rotates under a turning vessel, the inertially constant current gains a transport acceleration in body coordinates,

$$\dot{v}_c^b = -S(r) v_c^b = (r v_c, -r u_c, 0)^T. \quad (5)$$

This term is small, easy to forget, and exactly the kind of detail the cross-validation tests exist for (Sect. 3). Wind is a constant inertial force rotated into the body frame.

Actuators. Commanded forces are not applied directly. Each channel is a rate-limited first-order response with a smooth saturation model (docs/model.md gives the derivation):

$$\dot{T} = \dot{T}_{\text{max}} \tanh\left(\frac{\text{clamp}(T_{\text{cmd}}) - T}{\tau_T \dot{T}_{\text{max}}}\right), \quad (6)$$

which keeps $|\dot{T}| < \dot{T}_{\text{max}}$ exactly, is C^1 (good for gradient-based solvers), and reduces to a plain lag for small errors. The state is projected back into the physical bounds after every step.

3 Simulation kernel and cross-validation

The C++20 kernel owns the plant: kinematics, hydrodynamics, actuator and a fixed-step RK4 integrator, exposed to Python through pybind11. The controllers need symbolic dynamics, so the predictor is a *second*, independent implementation of Eqs. (3) in CasADi, with the 8-state (vessel + actuator) composition matching the kernel step for step: actuator first, then the vessel with the resulting forces held constant.

These two implementations are tested against each other over random states with non-zero current and wind, including out-of-bound actuator states and out-of-range commands; agreement is better than 10^{-8} . This is the cheap insurance that pays for itself whenever either side changes.

4 State estimation

The filter is an extended Kalman filter over $x = [\eta, \nu, c_N, c_E]$, where the last two components are an *equivalent-current* velocity. The augmented state is a proxy: under combined uncertainty (wind plus model mismatch) it absorbs whatever low-frequency velocity the model cannot explain. That is a feature, not a bug, and the flag is made explicit in the reports.

Sensors (GNSS position, compass, gyro, speed log) are sampled asynchronously with Gaussian noise, seeded, and delivered at their own rates. The prediction uses the nominal plant: the same RK4 kernel as the simulator, with the *estimated* current as the relative-velocity reference. The update is a linear observation of state components, applied in Joseph form with explicit symmetrization. Figure 1 shows the equivalent-current state in the flagship scenario: it converges toward the physical current, and the residual is the wind/model part it was never meant to separate.

5 Controllers

Four controllers share the same estimator output and the same actuator model.




Figure 1: Physical current and EKF equivalent-current state in the combined-uncertainty flagship run. The difference (bottom) is dominated by gusts and model mismatch; it is not a current-sensor error.

LOS + PID/PI. The classical baseline: a lookahead point at 8 m drives the desired heading, tracked by a PID on the wrapped heading error (derivative on the measurement, conditional anti-windup), with a PI speed loop.

Nonlinear MPC. A discrete-time OCP over a 10 s horizon ($N = 25$, $t_s = 0.4$ s, two RK4 sub-steps per step),

$$\min \sum_{k=0}^{N-1} q_p \|p_k - p_k^{\text{ref}}\|^2 + q_\psi e_{\psi,k}^2 + r \Delta u_k^2 + s u_k^2, \quad (7)$$

subject to the 8-state predictor and hard actuator bounds, solved with IPOPT through CasADi at 5 Hz, warm-started from the previous solution shifted by one step. Termination is iteration- and tolerance-based ($\text{tol} = 10^{-4}$); there is deliberately no wall-clock cut, which would make accepted iterates depend on machine load.

Disturbance-aware NMPC. The same OCP, but the current-equivalent estimate enters the predictor and is held constant over the horizon. The controller does not get the true environment; it gets the filter’s guess.

Geometric MPCC. The fourth controller drops the mission clock entirely and follows the path geometry: a monotone chord-progress state s is driven by a bounded virtual speed V_s , and the cost trades contouring and lag errors,

$$e_c = t_\perp^\top (p - p(s)), \quad e_l = t^\top (p - p(s)), \quad (8)$$

against heading error and progress reward. A small quadratic term on V_s ($r_{vs} = 0.5$) keeps the corresponding Hessian block positive definite; without it IPOPT stalls on the first S-curve turn. Failed solves are never applied: the fallback is the previously commanded action.

6 Results

The flagship scenario is one smooth S-curve (200.087 m chord progress), 120 s at $t = 0.01$ s, seed 42. The plant uses *perturbed* truth parameters (+10% mass, +15% inertia, reduced damping) behind a rate-limited actuator; the environment is a rotating current with two wind gusts; the sensors are noisy and asynchronous. Controllers see only the EKF output. Table 1 is generated from the committed artifacts; Fig. 2 shows the same comparison in time domain.

	LOS	Nominal NMPC	Aware NMPC	MPCC
RMS cross-track [m]	0.69	0.41	0.23	0.25
P95 cross-track [m]	0.98	0.65	0.53	0.61
Max cross-track [m]	1.07	0.74	0.63	0.71
RMS heading error [deg]	7.1	10.5	11.2	9.8
Final path progress [m]	154.9	156.2	156.1	164.2
RMS thrust [N]	31.8	33.7	33.5	36.6
Either channel saturated [s]	0.0	2.5	1.7	2.3

Table 1: Deterministic flagship metrics (120 s, seed 42). The disturbance-aware NMPC halves the LOS tracking error; MPCC buys progress at the cost of actuator effort.

Mean solve times on this workload are 20.1 ms (nominal NMPC), 16.7 ms (disturbance-aware NMPC) and 27.5 ms (MPCC), against a 200 ms budget at 5 Hz. These are wall-clock measurements of a workload, kept strictly apart from the deterministic metrics; no real-time capability is claimed.

7 Reproducibility

Every public number is produced by one tool from one reference run and written to committed JSON artifacts (scenario configuration, deterministic metrics, benchmark timings, software provenance). A content fingerprint of the source tree binds the artifacts to the code that produced them; `--check` validates schema, fingerprint, hashes and the generated documentation tables without simulating anything, and `--verify-determinism` replays the full flagship and compares it against the committed metrics (LOS exactly, solver-based metrics within 10^{-6} relative). Canonical generation pins single-threaded BLAS, since threaded factorizations can flip the last ulps of an IPOPT iterate and with it the accepted status of a borderline solve.

8 Limitations and outlook

The parameter set is illustrative (a ~ 1.5 m, 30 kg USV, order-of-magnitude values) and is not identified from a real hull; the model is 3-DOF with no waves, no actuator dynamics beyond the rate limits, and a uniform irrotational current. What the repository demonstrates is the chain and its numerics, not vessel-specific fidelity. Planned work: Monte-Carlo comparison of LOS against nominal and robust NMPC, and a coastal environment for the flagship visual.

References

- [1] T. I. Fossen, *Handbook of Marine Craft Hydrodynamics and Motion Control*, Wiley, 2011.
- [2] T. I. Fossen, *Marine Control Systems: Guidance, Navigation, and Control of Ships, Rigs and Underwater Vehicles*, Marine Cybernetics, 2002.




Figure 2: Cross-track error, applied thrust and yaw moment with the physical bounds, and the deterministic metrics. The four controllers face the same estimator, the same perturbed plant and the same disturbances.

- [3] D. Q. Mayne, J. B. Rawlings, C. V. Rao and P. O. M. Scokaert, “Constrained model predictive control: Stability and optimality,” *Automatica*, 36(6), 2000.
- [4] R. E. Kalman, “A new approach to linear filtering and prediction problems,” *ASME Journal of Basic Engineering*, 82(1), 1960.
- [5] A. Wächter and L. T. Biegler, “On the implementation of an interior-point filter line-search algorithm for large-scale nonlinear programming,” *Mathematical Programming*, 106(1), 2006.
- [6] J. A. E. Andersson, J. Gillis, G. Horn, J. B. Rawlings and M. Diehl, “CasADi: a software framework for nonlinear optimization and optimal control,” *Mathematical Programming Computation*, 11(1), 2019.