

```
<node>
  <deviceClass>
    <basicDeviceClass>ROUTING_SLAVE</basicDeviceClass>
    <genericDeviceClass>BINARY_SWITCH</genericDeviceClass>
    <specificDeviceClass>POWER_SWITCH_BINARY</specificDeviceClass>
  </deviceClass>
  <homeId>0xc337cda1</homeId>
  <nodeId>5</nodeId>
  <version>4</version>
  <manufacturer>0x63</manufacturer>
  <deviceId>0x3533</deviceId>
  <deviceType>0x5257</deviceType>
  <listening>true</listening>
  <frequentlyListening>false</frequentlyListening>
  <routing>true</routing>
  <security>false</security>
  <beaming>true</beaming>
  <maxBaudRate>40000</maxBaudRate>
  <nodeInformationFrame>
    <commandClass>SWITCH_BINARY</commandClass>
    <commandClass>SWITCH_ALL</commandClass>
    <commandClass>POWERLEVEL</commandClass>
    <commandClass>CONFIGURATION</commandClass>
    <commandClass>VERSION</commandClass>
    <commandClass>MANUFACTURER_SPECIFIC</commandClass>
    <commandClass>NODE_NAMING</commandClass>
  </nodeInformationFrame>
  <supportedCommandClasses>
    <entry>
      <commandClass>SWITCH_BINARY</commandClass>
      <binarySwitchCommandClass>
        <version>1</version>
        <instances>1</instances>
        <versionSupported>1</versionSupported>
        <isGetSupported>true</isGetSupported>
      </binarySwitchCommandClass>
    </entry>
    <entry>
      <commandClass>NO_OPERATION</commandClass>
      <noOperationCommandClass>
        <version>1</version>
        <instances>1</instances>
        <versionSupported>1</versionSupported>
      </noOperationCommandClass>
    </entry>
    <entry>
      <commandClass>MANUFACTURER_SPECIFIC</commandClass>
      <manufacturerSpecificCommandClass>
        <version>1</version>
        <instances>1</instances>
        <versionSupported>1</versionSupported>
      </manufacturerSpecificCommandClass>
    </entry>
  </supportedCommandClasses>
</node>
```

```
<commandClass>SWITCH_ALL</commandClass>
<switchAllCommandClass>
  <version>1</version>
  <instances>1</instances>
  <versionSupported>1</versionSupported>
  <isGetSupported>true</isGetSupported>
  <mode>SWITCH_ALL_INCLUDE_ON_OFF</mode>
</switchAllCommandClass>
</entry>
<entry>
  <commandClass>POWERLEVEL</commandClass>
  <powerLevelCommandClass>
    <version>1</version>
    <instances>1</instances>
    <versionSupported>1</versionSupported>
    <powerLevel>0</powerLevel>
    <powerTimeout>0</powerTimeout>
  </powerLevelCommandClass>
</entry>
<entry>
  <commandClass>NODE_NAMING</commandClass>
  <nodeNameingCommandClass>
    <version>1</version>
    <instances>1</instances>
    <versionSupported>1</versionSupported>
    <name></name>
    <location></location>
  </nodeNameingCommandClass>
</entry>
<entry>
  <commandClass>CONFIGURATION</commandClass>
  <configurationCommandClass>
    <version>1</version>
    <instances>1</instances>
    <versionSupported>1</versionSupported>
    <configParameters>
      <entry>
        <int>3</int>
        <configurationParameter>
          <index>3</index>
          <size>1</size>
          <value>0</value>
          <readOnly>>false</readOnly>
          <writeOnly>>false</writeOnly>
        </configurationParameter>
      </entry>
      <entry>
        <int>4</int>
        <configurationParameter>
          <index>4</index>
          <size>1</size>
          <value>0</value>
          <readOnly>>false</readOnly>
          <writeOnly>>false</writeOnly>
        </configurationParameter>
      </entry>
    </configParameters>
  </configurationCommandClass>
</entry>
```

```
    </configurationParameter>
  </entry>
</configParameters>
</configurationCommandClass>
</entry>
<entry>
  <commandClass>BASIC</commandClass>
  <basicCommandClass>
    <version>1</version>
    <instances>1</instances>
    <versionSupported>1</versionSupported>
    <isGetSupported>true</isGetSupported>
  </basicCommandClass>
</entry>
<entry>
  <commandClass>VERSION</commandClass>
  <versionCommandClass>
    <version>1</version>
    <instances>1</instances>
    <versionSupported>1</versionSupported>
    <libraryType>LIB_CONTROLLER_BRIDGE</libraryType>
    <protocolVersion>2.97</protocolVersion>
    <applicationVersion>3.20</applicationVersion>
  </versionCommandClass>
</entry>
</supportedCommandClasses>
<securedCommandClasses/>
<nodeNeighbors>
  <int>1</int>
  <int>2</int>
  <int>3</int>
  <int>4</int>
  <int>6</int>
</nodeNeighbors>
<lastSent>2016-06-26 14:32:07.732 UTC</lastSent>
<lastReceived>2016-06-26 14:32:07.773 UTC</lastReceived>
```