					and the second s	and the same and the same and the	1 - Commercial Commerc					on the contract of the contrac					
Other	Pit Pictures	HS Transects	Slush Ram	Powder Ram	Standard ram	Stratigraphy pictures	Digital LWC	Instrument	Tree Canopy	Wind	Sky	riecip type	Pracin Type	Precip Rate		Time:	Location:
	4	2	2	X	Y	~	2	Y/N SN	No trees	Calmy (0 mph)	Clear	Za	D C	None		1521	Colon
	SSA / NIR Box	Snow Scope Transects	Force Snow Scope	Force Ram	SMP	Lyte Probe	Snow Scope	Instrument	Sparse (5 - 20%)	Light (1 - 16 mph)	Few (< 1/4 of sky)	Ollow		(0.5 cm / hr)	Vondinkt		enapo
	opusio.		~	7	N	~	~	NS N/A	Open (20 - 70%)	Moderate (17 - 25mph)	Scattered)	Glaubei	Grainel	(1 cm / hr)		Observers:	
	S.	naruness			7-		Worth	Addition	Closed (> 70%)	Strong (26 - 38 mph)	Broken (> 1/2 of sky)	ā	Цэi	(5 cm / hr)	Moderate	217	Site:
ų				1 8 1 0				Additional Comments		Extereme (> 38 mph)	Overcast (complete cover)	Zalli Gliow	Dain/Crow	Heavy (10 cm / hr)		and a	UPXPSPOS
	*					a a	8	Height of Ground Vegetation	Ground Vegetation	Ground roughness	Ground condition	Sample C	Sample B	Sample A			POY
								Vegetation (cm)	Bare	Smooth (<5 cm)	Frozen		7	75	Depth (cm)	Interval t	Date:
. ,					g.				Grass	Rough (5 - 20 cm)	Moist	1			SWE (mm)	Interval board SWE measurement	20150173
			=					15	Shrub	Rugged (> 20 cm)	Saturated				Density (kg/m3)	urement	23
								15	Deadfall				1	resulting in SWE loss? (Y/N)	Evidence of melt		

Scale)	_	rvers	nitial & last na	ame):			Temperature profile	re profile	Comments/Notes:	s/Notes:
Site (Study Plot)	Time (pit opened)	لار «ر		,			times START	END		
HOPSTING	4521						1300			
Snow Depth (cm)	LWC Device & SN	UTME		UMN	Ž	Zone (two digit)		certainty:		
89 4218312A44117	NA	425602	12	HH	258	Z	Sent ungil F	sent sso,		
Density	LWC	Temperature					"	Stratigraphy	4	
Height above Density Density Extra ground profile A profile B Density	Permittivity Permittivity profile A profile B	Height T ground	Height above ground	above	Grain Sia (mm)	Size n)	Grain	Hand	Manual	Stratigraphy Comments
top - bottom kg/m3 kg/m3 kg/m3 (cm) (cm)	(unitless) (unitless)	(cm) oC	top (cm)	bottom (cm)	Max Min	Avg	Туре	Hardness	Wetness	
18 58 174 138 53 48 198 204	200	5/H- 2/- 200 3/-	8	39	1.0 4.0	2,0	FLL	77)	7	some Orde
43 142 86 - 84		0		i		9	e C	1	1	
922 82.			06	20	1.0 0.0	5:07	orst	7	9	
5-18 243	< **	+,	B	Re Pe	. N = N		17 7	Ī	C	Sans anos
10 - 0 25+ 250		36.9	, 6		,	- 1	30		7	Some hard
			2	2	1 6.5		10 75%	-1	C	
			1	1	Û	18	741	†	y	1
			de	4	6.7	1	275	1	0	
16 COX				F	77	N	せ、	q	7	
			3	, ,	1	4) '	1) (71.6
			-	C	7	<u> </u>	2 2 2 7	7	0	ナナ
10			ac is	= 1	+		*:			011/8
-		1 1.					963			
7.6 8.5						4				
14.0 37.0				2:						
7.0 23.5	3									
7,0 14,0	X				1	1			9	
	Se Se				+					
	7					<u>1</u>			ıī	
	L PC		• 2000		3		1 12			
	756								=	

YCoord Time Data Type SN Profile # Force Gage N GM GS		521950240E HEK -JU OCHUON	Date: 20250 Time: /254 Observers: /C	CA36		Force	Depth manual	Depth digital	Grnd
20 2000 2000	$\dashv \mathcal{H}$		Yers:	$\exists \mathcal{C}$	Force Gage	N max	manual	digital cm	Grnd Y/N
26.2	\dashv		Serve			3 12	R	1 12	
26.0 26.0 27.0	30	8	POW RAY	11 1 ig			70.5	= 17.1	
26.2 24.0 24.0 24.0 24.0 25.0 24.0 25.0 25.0 25.0 27.0		SCOR				120		1 2 3	
50 60 DAM W FEDELC BETT SON 1745 1200 120	0	2 18		7	i	180	66		
20 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	R	S					49		
20 1	8	60		1 () () () () () () () () () (1536	25.19	70		
120 120 120 120 120 120 120 120 120 120	90	60			914	All I	69		<
90 724 4 504 7.45 90 70 724 7200 90 70 724 7200 90 70 724 7200 90 725 4 7200 90 726 4	120	60					69		
70 72m w/ FM2CC 27 50N 7.45 70 70 70 70 70 70 70 70 70 70 70 70 70 7				2 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -				1 1	
20 2 2.75 20 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		tem	FERCE	1		202	7	g.	
20 20 20 20 20 20 20 20 20 20 20 20 20 2	02	00	4	15	-0,	19.80	49		
100 2000 4 1 2000 1200 1200 1200 1200 12	B	00			10		60		2
190 HARCE W 1200 120 HARCE 127 SON 3.70 120 120 127 SON 3.70 120 120 1275	90	60	2	7	- 1	26.70	63		2
120 5696 W/FBALE 127 50N 3.70 120 120 127 50N 3.70 120 120 175 120 170	120	3				12.00	67		
120 KBRC W/FARLE 127 SON 3.70 120 120 120 120 120 120 120 120 120 120			-						
120 120 120 120 120 120 120 120 120 120	1 2	BRE	-						
720 720 1720 1720 1720 1720 1720 1720 17	0		7	7	5011	3,70	29		2
720 0.45	30	027				46.16	42		
2.95	60	120	E1			0.75	83	=	5
	90	021				2.95	62		
	120	120			~	1.10	22	1	5
								8	1 1
		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1							11111

Ram Penetrometer Field Data Sheet

		= 1		Nam	Penetro									
Locatio	n: <i>CO</i>	1900	AUC								Tube	weight	T	kg
LUCALIO	IT	X	00	GIXLI					*	На	ammer	weight	Н	kg
ite:	y C			DOF		2076	1	2		1	lumber		n	
	ted pit/ti			LIVIT	42	00	212	_/_		''			f	cm
	2025	012	3		Time:					 		height		cm
bserve	er: K	E	We				1	T				of point	р	
JTME:				UTMN:	T			Zone:		†	T + H +			kg
Ram typ	pe:				Ram ma	iss:	,	,	kg	RR = 9	9.81 (T	+ H + n1	H/p)	N
T	Н	n	f	р	T	Н	n	f	р	T	Н	n	f	р
67	D	121	AM)		Po	WD	SPL	15	117			1	15	34_
	i e											(35
1	0	0	0	54	0.1	0	0	0	5,5					36
7	0.5	0	0	54	0.1	0.1	0	0	7					32
-		1	1	61			1	1	10.5					3 8
-		4	1	62					17.5	Ī				39
		1	2	63.5			- 1-		12,5			1	20	40.5
				64.5					13.5					42
		79.		64.5 65					14,5			1		43
				0.0			1	2	15.5	1				43
					1		-	-						46
٠,									16.5					47
- 3							1	3	17,5				- 11	48
-									18.0					49
					1				18.5					7/1
						19 711		5	19					51
									19.5					51 52 54,5
									71					RUL
					1		1	10	20			1	10	55.5
•							1	00	22,			2	10	57
												-	10	58.5
						e a m			225					~6.7
			_		32 - 3	= 1			23.5 24.8 25.5 26.3 27.5 28.5 28.5 29.5 30.5 31.5 32.5 33.5		-	1	110	59.5 60 60.5 61 62 63 64 66.5 69 69.5 70.5
									755			-	10	60
					-			<i>-</i>	20			 		60,5
						-1			26	-	-	-		61
									26,3	-		-	-	62
			5 14		ļ				4.5	 	-	-	 	63
			•					-	200	 	-	-	-	64
			- 12		} -			ļ	18,5			-	-	66.5
					ļ				27	-	-		ļ	68
				·	ļ				24.5		-	1		69
					ļ				20,5	ļ	-	ļ		69,5
					71 :		ļ <u>.</u>		51		<u> </u>	/	25	70.5
					, ,		1	15	31.5					
					,				325					
=	-				Ľ				33					
									33.5					
												1		
otes:				=										•