

The isodoc class* for letters, invoices, and more

Wybo Dekker
wybo@dekkerdocumenten.nl

February 22, 2012

Abstract

The isodoc class can be used for the preparation of letters, invoices, and, in the future, similar documents. Documents are set up with options, thus making the class easily adaptable to user's wishes and extensible for other document types.

Keywords: letter, invoice, key/value, NEN1026

Contents

1	Introduction	1
2	Options	2
3	Commands	7
4	Usage: letters	11
4.1	A simple letter	11
4.2	Multiple letters, redefined logo	15
5	Usage: invoices	17
5.1	A simple invoice	17
5.2	Invoice with redefined logo	19
6	Implementation	19
6.1	The options and their defaults	20
6.1.1	General options	20
6.1.2	Logo	21

*This document corresponds to isodoc v0.10, dated 2012/02/21.

6.1.3	Address window	22
6.1.4	Header	22
6.1.5	Footer	23
6.1.6	Folding mark	23
6.1.7	Header fields	24
6.1.8	Closing, autograph, signature	24
6.1.9	Invoice specific data	25
6.2	User Macros	26
6.2.1	Logo	27
6.3	Internal Macros	33

1 Introduction

This class is intended to be used for the preparation of letters and invoices. Its starting point was Victor Eijkhout’s NTG brief class¹, which implements the NEN 1026 standard. The brief class does not provide facilities for invoices and it is not easily extensible.

The goal for the isodoc class is to be extensible and easy to use by providing *key=value* configuration. Furthermore, texts that need to be placed on prescribed positions on the page (there are many such texts) are positioned by using the textpos package.² This provides a very robust construction of the page.

The class itself contains many general definitions, but variable data, such as opening, closing, address and many more, have to be defined using *key=value* definitions, either in the document or in a style file. The latter is indicated for definitions that don’t vary on a per document basis, such as your company name, address, email address and so on. Thus if you run a company and also are the secretary of a club, you would have style files for each of them, plus one for your private letters or invoices.³

The general setup of a document producing one or more letters is (see figures 1–3, page 13–14, for examples):

```

\documentclass{isodoc}
\usepackage{<somestyle>}
\setupdocument{<generaloptions>}
\begin{document}
\letter[<addressee_specific_options>]{<letter_content>}
... more \letter calls ...
\end{document}

```

Similarly, the general setup of a document producing one or more invoices is (figure 4, page 16):

```

\documentclass{isodoc}
\usepackage{<somestyle>}
\setupdocument{<generaloptions>}
\begin{document}
\invoice[<addressee_specific_options>]{<invoice_content>}
... more \invoice calls ...
\end{document}

```

¹CTAN: ntgclass/briefdoc.pdf

²CTAN: textpos/textpos.pdf

³If you archive your documents in their source form only, it may be wise to work without a style file and set all options in the document itself!

2 Options

Options are given as key=value pairs, separated by comma's. Extra comma's, including one behind the last pair, don't hurt. An option argument should be enclosed in braces if it contains comma's or equals signs.

As shown in the two examples in the previous section, there are three commands that can set options: `\setupdocument`, `\letter`, and `\invoice`. These commands will be further explained in the *Commands* section. `\setupdocument` is normally used to set options that are common to all letters or invoices in the document, like your company data; the optional arguments of `\letter` and `\invoice` set only those options that are different for each letter or invoice, such as the to and opening options.

This section lists and explains all available options. All options can be used in both the style files and in the document source, although several will normally only be used in style files (such as `company`) and some only in the document source (such as `to` or `opening`).

Language

The options described here relate to the language used for the isodoc interface (headings, footings, date, banking data and so on.) This language is independent of the language you set with the `babel` or `polyglossia` packages. So, for example, you can write your document in english and use `dutch` for the interface. Also, use of `babel` or `polyglossia` is not required.

Currently only a few interface languages are defined. As I am not particularly strong in the translation of administrative terminology, please feel free to send me corrections. And if you don't find your own language here, please send me your translations and your language will be added.

The options below set the language, UKenglish is used by default. Preferably, the language option should be used; the other options are there for compatibility with earlier versions.

<code>language = ...</code>	sets the interface language to any language defined by the class. Currently these are: UKenglish, USenglish, french, german, dutch, italian, spanish, catalan, norsk, serbian
<code>dutch</code>	a synonym for <code>language = dutch</code> ,
<code>english</code>	a synonym for <code>language = UKenglish</code> ,
<code>german</code>	a synonym for <code>language = german</code> ,
<code>american</code>	a synonym for <code>language = USenglish</code> ,
<code>french</code>	a synonym for <code>language = french</code> .

Logo

Information about the sender is defined here. The logo, by default, consists of a large company name on top a rule with, hanging under the rule, a contact person's data. You can define the latter either explicitly with the `logoaddress` option, or let it automatically be created from the contents of the options `who`, `street`, `prezip`, `zip`, `city`, `country`, and `foreign`, as far as you have defined those. Definition in parts can be useful if you need them elsewhere in your document.

<code>company = ...</code>	Your company name as it should appear in the logo (if you use the default logo) and in the return address (where it may get overridden by the <code>returnaddress</code> keyword.) For private documents, use your name or nickname here.
<code>logoaddress = ...</code>	Contact person's data; use <code>\\</code> commands for line breaks. If you don't define this option, the data will be constructed from the following options.
<code>who = ...</code>	Contact person's name; probably your own name.

<code>street = ...</code>	Street in the sender's address.
<code>city = ...</code>	City in the sender's address.
<code>zip = ...</code>	Zip in the sender's address.
<code>cityzip</code>	Place zip <i>after</i> city, instead of before it (the default).
<code>country = ...</code>	Country in the sender's address. Only used if <code>foreign</code> key was used.
<code>countrycode = ...</code>	Sender's country code. For The Netherlands: NL
<code>areacode = ...</code>	Sender's area code. For The Netherlands: 31
<code>foreign</code>	Use this key if you send your letter to a foreign country. With it, your country will be added to return and logo addresses, your zip code will be prefixed with your country code, telephone numbers will be prefixed with +31- (or whatever your areacode option has been set to) instead of just a 0. In the <code>\accountdata</code> command, it causes IBAN en BIC code to be included, unless the <code>localbank</code> option is used.

Address window

The addressee's address is printed in a window. The width of the window is two columns (70 mm), and its contents are vertically centered in it. There are no limits to the vertical size of the window, other than the physical size of the window in the envelopes you use. The vertical position of the window's center is set with the `addresscenter` keyword. Horizontally there are two options: left or right.

<code>leftaddress</code>	Places the window over columns 2 and 3; this is the default.
<code>rightaddress</code>	Places the window over columns 4 and 5.
<code>addresscenter = ...</code>	Distance in mm of the center of the window from the top of the paper; the default value is 63.5 mm, fitting for a DL envelope for triple folded A4 (110x220mm) with a window at 50 mm from the top, 30mm high. ⁴
<code>addresswidth = ...</code>	The address window's width. The default is 70 mm (2 columns).
<code>to = ...</code>	The addressee's address. New lines can be introduced with the <code>\\</code> command; lines longer than 70 mm will cause extra newlines.
<code>[no]return</code>	Do or don't print a return address on top of the addressee's address. This is useful if blank window envelopes are used. The return address is composed from the contents of the <code>company</code> , <code>street</code> , <code>zip</code> , <code>city</code> , and <code>country</code> keywords; it is printed in a bold script size sans serif font and is separated from the addressee's address with a rule. The country will only be printed if the <code>foreign</code> keyword has been used.
<code>returnaddress = ...</code>	The return address, if it is composed as just described, may become too long to fit in the address window. Or you may want to define a completely different return address. With the <code>returnaddress</code> keyword you can redefine the return address. Use <code>\\</code> to insert bullets.

⁴The middle of the window is at $50+30/2=65$ mm from the top of the envelope; the paper is folded (see the folding options below) to give the folded paper a tolerance of 1.5mm on both sides in the envelope, so the address should be placed 1.5 mm higher at $65-1.5=63.5$ mm.

Header fields

Under the address window, a header is printed. The page is vertically divided in six columns, one each for the left and right margins, and four which, in the header, say: *Your letter of*, *Your reference*, *Our reference*, and *Date*, each with their respective contents under them. If the subject keyword is used, an extra line starting with *Subject:* will appear, followed by the contents on the same line and over a width of 2.5 columns. If needed, extra lines will be used.

<code>bodyshift = ...</code>	The header starts 98mm from the top of the paper, but it can be shifted with the <code>bodyshift</code> option.
<code>[no]header</code>	The <code>noheader</code> option disables all header fields, the <code>header</code> option re-enables them (<code>header</code> is the default.)
<code>yourletter = ...</code>	first field in the header: the date of the letter this document is reaction on; empty by default.
<code>yourref = ...</code>	second field in the header: addressee's reference of the letter this document is reaction on; empty by default.
<code>ourref = ...</code>	third field in the header: your own reference for this document.
<code>date = ...</code>	fourth field of the header. The argument must have the form <code>yyyymmdd</code> or <code>yyyy-mm-dd</code> ; it will be translated into a date like "May 3, 2006" if the document language is English, or into its translation in the actual language. The default value is 'Undefined date', i.e. the date of <code>\today</code> is not the default as this would make the date untraceable from the document source only. However, you can force the use of <code>\today</code> by providing the string <code>today</code> for the argument.
<code>forcedate = ...</code>	The restrictions of the date option can be overridden by using the <code>forcedate</code> option instead; you can thus enter anything you like for the date.
<code>subject = ...</code>	subject of this document; is placed raggedright under the other fields, over the full <code>textwidth</code> . Use newlines if you want to restrict the width of the text.

Opening and Closing

A letter is started with an opening – something like 'Dear John', and ended with a closing – something like 'Regards,<newline>Betty', perhaps with an autograph (or white space) in between.

<code>opening = ...</code>	Dear John
<code>openingcomma = ...</code>	by default, the opening phrase is followed by a comma, but you can change that here.
<code>closing = ...</code>	Regards
<code>closingcomma = ...</code>	by default, the closing phrase is followed by a comma, but you can change that here.
<code>signature = ...</code>	Betty
<code>autograph = ...</code>	This keyword can have one of the 10 values 0–9: <ul style="list-style-type: none">0: no autograph; the signature appears right under the closing. This is the default if the autograph option is not used (using it without a value is equivalent to <code>autograph=2</code>).1: generates extra whitespace between signature and closing for a hand-written autograph. Change with the <code>closingskip</code> key.2–9: inserts one of eight autograph images which, with the <code>\autograph</code> command, may have been defined in the style file.

enclosures = ...	This keyword can be used to add a note, at the end of the document, which starts with Enclosure: followed by the value of the keyword. Multiple enclosures can be separated with \\ commands. If those are found, the starting text will be Enclosures: .
closingskip = ...	white space between signature and closing. The default is 2\baselineskip.

Footer fields

Footer fields are shown in the order in which they appear below; they are empty by default, and empty fields are not displayed. The order of the fields can be changed with the footorder option.

[no]footer	enables or disables printing a page footer; there is room for upto four fields, if you set five fields, the last one will appear in the right margin.
footorder = ...	changes the order of footer fields. The argument should be a semicolon (;) separated list of fieldnames. The default is website;phone;cellphone;fax;email.
phoneprefix	prefix for phone numbers. The default is '0'; will be changed into '+<areacode>-' if the foreign option is used.
phone = ...	if not empty, prints 'phone' in the first field of the page footer, with the contents under it, prefixed with a 0 or, if the foreign option was used, the areacode (set with the areacode option.) Telephone numbers should thus be entered without a prefix.
cellphone = ...	same for cellphone...
fax = ...	fax...
email = ...	email...
website = ...	and website.

Folding marks

Folding marks can be useful, particularly if your address window is used to its limits. Correctly folding your letter then prevents parts of the address to become invisible because of the letter loosely filling the envelope.

nofold	Disable folding marks.
foldleft	The folding mark is printed in the left margin.
foldright	The folding mark is printed in the right margin. This is the default.
fold2	Folding mark at about halfway, set for tight fitting into a 220x162 mm envelope, with a tolerance of 2 mm at both sides.
fold3	Folding mark at about one third from the top, set for tight fitting into a 220x110 mm envelope, with a tolerance of 1.5 mm at both sides.
fold = ...	For non-standard envelopes and paper formats the position of the folding mark can be set at any position (in mm) from the top of the paper.

Payment data

In invoices you probably want to make clear where you want your debtor to transfer his money to. You can do so by calling the \accountdata command, which generates a little table containing these data. The contents of this table can be defined with the following keywords:

<code>term = ...</code>	Payment term in days; default is 30.
<code>currency = ...</code>	Currency; default is euro.
<code>accountno = ...</code>	Your bank account number.
<code>routingno = ...</code>	Your bank's routing number. Will not be cited if undefined.
<code>accountname = ...</code>	Your bank account's ascription. Will not be cited if undefined.
<code>iban = ...</code>	Your account's IBAN...
<code>bic = ...</code>	and BIC code; IBAN and BIC are only reported in invoices to foreign customers—see the <code>foreign</code> keyword.
<code>vatno = ...</code>	Your VAT reference number, not yet used.
<code>chamber = ...</code>	Your Chamber of Commerce subscription number, not yet used.

Accept data

These keys pertain to data needed for accept forms:

<code>acceptaccount = ...</code>	Payer's bank account number
<code>acceptaddress = ...</code>	Payer's address lines, separated with \\
<code>accepteuros = ...</code>	Euro part of the amount to be paid
<code>acceptcents = ...</code>	Cents part of the amount to be paid
<code>acceptdescription = ...</code>	Description to be quoted on the accept form
<code>acceptdesc = ...</code>	Short version of the description for the detachable strip of the form to be kept by the payer
<code>acceptreference = ...</code>	Reference

Miscellaneous

<code>[no]fill</code>	Use the <code>fill</code> keyword to justify text both left and right; the default is <code>nofill</code> : left justification only.
<code>shift = ...</code>	The many textpositions in isodoc are defined in millimeters, but sometimes printers show an aberration in their horizontal or vertical printing position. You can correct for this with the <code>shift = x,y</code> option, where <code>x</code> and <code>y</code> (both 0 by default) shift the output to the right and down, respectively, in millimeters.

3 Commands

<code>\showkeys</code>	The <code>\showkeys</code> command can be useful for debugging. It prints a table showing the option keys described in the previous section, and their current values.
<code>\setupdocument</code>	Most of the setup, both in the style files and in the documents themselves, is done setting options in a call to the class-defined <code>\setupdocument</code> command. The options can be either a key/value pair, or just a key. Options with values and those without may occur in any order, with the exception of <code>addresscenter</code> (see there.) Values need their surrounding <code>{}</code> 's only if they contain any comma's. The <i>Options</i> section explains the available options.

Most of the options have a corresponding command with the same name. Although not very often, it may sometimes be useful to have those commands available. These are the options with a corresponding command:⁵

⁵Note for developers: the table lines below can be generated with a ruby script `listkeys` (included in the distribution): `listkeys show`

accept	cellphone	fold	nofill	subject
acceptaccount	chamber	fold2	nofold	term
acceptaddress	city	fold3	nofooter	to
acceptcents	cityzip	foldleft	noheader	vatno
acceptdesc	closing	foldright	noreturn	website
acceptdescription	closingskip	footer	opening	who
accepteuros	company	footorder	openingcomma	yourletter
acceptreference	country	forcedate	ourref	yourref
accountname	countrycode	foreign	phone	zip
accountno	currency	french	phoneprefix	
addresscenter	date	german	return	
addresswidth	dutch	header	returnaddress	
american	email	iban	rightaddress	
areacode	enclosures	language	routingno	
autograph	english	leftaddress	shift	
bic	fax	localbank	signature	
bodyshift	fill	logoaddress	street	

So you could write in your letter: “please send me the money on my bank account: \accountno\ as soon as possible.”

\letter The `\letter` command produces one letter and can be called multiple times. It has two arguments. The first argument is optional and must be a list of *key=value* pairs. The options set here are usually those that vary among different letters. The second argument contains the letter’s content. This content will, depending on the options set, automatically be surrounded by an opening, a closing, an autograph, a signature and a remark about any enclosures. The first page of each letter will be decorated with a logo, the addressee’s address, a return address, various reference fields, a footer, a folding mark—all as defined by *key=value* pairs in `\setupdocument` or in the `\letter` command itself.

The second and following pages will have a heading, quoting the name of the addressee and a page number. Examples of letters can be found in the section *Usage: letters*.

\invoice The `\invoice` command is essentially the same as the `\letter` command, except that the opening is always “INVOICE”, and the content (argument 2) is largely composed using the `\itable`, `\iitem`, `\itotal`, and `\accountdata` commands described hereafter. Closing, autograph, and signature are disabled.

In the Netherlands, invoices can be provided with an accept form on the lower third part of the page. If the `accept` option was used, this accept form will be filled with the available data, in the `ocrb` font where needed.

\itable The following commands pertain to invoices: The `\itable` command uses `tabularx` to create a two-column table. The first column of the table will have the header ‘Description’ (or its equivalent in the language selected), the header of the second column says ‘Amount (EUR)’. The single argument of `\itable` should contain the contents of the table and is of the form:

```

item 1 & amount 1\NN
item 2 & amount 2\NN
...
item n & amount n \NN
\cmidrule[.05em]{2-2}
Total & amount \NN

```

However, the next two commands may be used to enter these data more cleanly:

\iitem The `\iitem{item}{amount}` command (`iitem` stands for Invoice Item) is equivalent to writing `item & amount\NN`.

\itotal The `\itotal{amount}` command (`itotal` stands for Invoice total) is equivalent to writing: `\cmidrule[.05em]{2-2} Total & amount \NN`, with the additional

advantage that the word ‘Total’ will be replaced with its equivalent in the current language. Thus, the argument to the `\itable` command show above can also be written:

```
\iitem{item 1}{amount 1}
\iitem{item 2}{amount 2}
...
\iitem{item n}{amount n}
\total{amount}
```

`\accountdata` The `\accountdata` command prints a little table with accounting information needed by the creditor for paying the invoice. It is constructed using the values of the options `accountno`, `accountname`, `routingno`, `iban`, and `bic`. The latter two are only included if the `foreign` option was used.

`\autograph` The `\autograph` command, which will normally appear in a style file, serves to define up to eight autographs based on PDF, JPEG or PNG images. One of these autographs will be drawn between the closing (*Best regards*) and the signature (*Betty*) if you use the `autograph` option with a value from 2 through 9. `\autograph` has 7 arguments:

```
arg 1: 2,3,...9: autograph number; will be translated internally to define
        \autographA, \autographB... \autographH
2:      scaling factor for the image
3:      distance the autograph outdents in the margin
4:      vertical position of the baseline of the closing (Regards,) from the top
5:      vertical position of the baseline of the signature (John Letterwriter) from
        the top
6:      height of the image
7:      the image (jpg, png, pdf...)
```

The arguments 3–6 must be dimensions, and for a given autograph image should be inferred by inspecting the image with an image manipulation program like, for example, the gimp. In the lower left corner of the gimp window, select the units of length, move the pointer to the positions where you want margin, closing, and signature and to the bottom of the image, read the x, y, y and y positions respectively and use those for the argument 3, 4, 5, and 6.

`\logo` The `\logo` command is internally used to define the default logo; you can redefine it with `\renewcommand{\logo}{...}`. An example of logo redefinition can be found on page 15.

`\EUROSymbol` Several symbols are frequently used in letters and invoices. These are usually taken from `marvosym.sty`; however, `marvosym` collides frequently with command names used in `isodoc`. So they have gotten their own names here:

`\EuroSymbol`
`\EUR`
`\EmailSymbol`
`\LetterSymbol`
`\MobileSymbol`
`\PhoneSymbol`

command	ascii	result
<code>\LetterSymbol</code>	66	✉
<code>\EuroSymbol</code>	164	€
<code>\EuroSymbol</code>	164	€
<code>\EUR</code>	99	€
<code>\EmailSymbol</code>	107	✉
<code>\PhoneSymbol</code>	84	☎
<code>\MobileSymbol</code>	72	📞

If you need other symbols, then please email me.

The Letter Company

Wybo Dekker
Deilsedijk 60
4158 CH Deil

Letter Cy • Deilsedijk 60 • Deil

TeX Users Group
1466 NW Naito Parkway, Suite 3141
Portland, OR 97208-2311
U.S.A

Vostra lettera del:

Vostro riferimento:

Nostro riferimento:

Data:

1029


Undefined date

Oggetto: An example letter using the isodoc class

L.S.,

This letter was composed using the L^AT_EX isodoc class.

Had our solar system included two suns, the problem would have involved three bodies (the two suns and each planet), and chaos would have been immediately obvious. Planets would have had erratic and unpredictable orbits, and creatures living on one of these planets would never have been able to perceive the slightest harmony. Nor would it have occurred to them that the universe might be ruled by laws and that it is up to man's intellect to discover them. Besides, it is not at all obvious that life and conscience could even emerge in such a chaotic system.

Best regards

W.H. Dekker

Allegati:

isodoc documentation
LPPL documentation

sito Web:

www.xs4all.nl

telefono:

087-87 48 496

cellulare:

06-15 49 20 70

e-mail:

wybo@xs4all.nl

Figure 1: Minimal letter example

4 Usage: letters

Usage of the class is best explained by example.

4.1 A simple letter

Here is the latex source for a small letter; its result appears in figure 1:

```
\documentclass[11pt]{isodoc}
\usepackage{mystyle}
\definecolor{headcolor}{gray}{.5}
\setupdocument{
  to = {TeX Users Group\\
        1466 NW Naito Parkway, Suite 3141\\
        Portland, OR 97208-2311\\
        U.S.A
      },
  ourref = 1029,
  enclosures = isodoc documentation\\LPPL documentation,
  subject = An example letter using the isodoc class,
  autograph = 2,
}

\begin{document}
\letter[language=italian]{
  This letter was composed using the \LaTeX{} isodoc class.
  \par\input{thuan} % for some body
}
\end{document}
```

This source essentially shows three items:

1. the inclusion of a package `mystyle`; we'll come to that shortly.
2. the command `\setupdocument` called with many *key=value* arguments, each defining one of the texts that go into the letter.
3. the command `\letter`, enclosing the body of the letter; just to give the letter some real body, a small text has been included using `\input`.

Of course this is not all of the information needed to create a letter. For example, there should be a logo, telling the addressee who I am and there should be contact information such as my address, telephone number and so on. This is where the included `mystyle` package plays its part. Here is an example of such a style file:

```
\NeedsTeXFormat{LaTeX2e}[1999/12/01]
\ProvidesPackage{mystyle}
  [2010/08/21 v1.1 Letter Company style file for isodoc]
\RequirePackage{pxfonts}

\setupdocument{return,footer,fold3,
  autograph      = 0,
  company         = The Letter Company,
  returnaddress  = Letter Cy\\Deilsedijk 60\\Deil,
  who            = Wybo Dekker,
  street         = Deilsedijk 60,
  city           = Deil,
  zip            = 4158 CH,
  country        = The Netherlands,
  countrycode    = NL,
  areacode       = 31,
  phone          = {87-87\,48\,496},
  cellphone      = {6-15\,49\,20\,70},
  fax            = {},
```

```


website      = www.xs4all.nl,
email        = wybo@xs4all.nl,
accountno    = {3040\,46221},
iban         = nl61pstb0006238747,
bic          = pstbnl21,
vatno        = 28750482B01,
chamber      = 11023220,
opening      = L.S.,
closing      = Best regards,
signature    = W.H. Dekker
}
\graphicspath{{./graphics/}}
\autograph{2}{.30}{75bp}{87bp}{216bp}{261bp}{signw_marked}
\endinput

```

So in the style file, too, `\setupdocument` is used to register information that will common to almost all of my letters. The `\autograph` command sets up an autograph, based on an image file. Apart from the code shown here, a style file can contain definitions for more autographs, and a definition for a logo. Without the latter, a default logo is produced. Note also that I have included defaults for opening, closing, and signature in the style file, and that I did not override those in the letter's source.

The letter source example shown above, in combination with this style example, compiles to the letter shown in figure 1. This example illustrates some aspects of isodoc:

- At the top, you see the default letterhead (logo). You can create your own logo by redefining the `\logo` command.
- Under it is the address. It has a return address in script sized sans serif boldface over it, because the return key has been used. A return address is useful if you send your letters in a standard window envelope. The positioning of the address is done in the style file, using the `addresscenter` and `leftaddress` or `rightaddress` keywords.
- The paper is vertically divided in six equally wide columns. The outer two columns are the left and right margins, the second to fifth columns contain header and footer fields.
- The “Your reference” and “Our reference” fields have not been set (with the `yourref` and `ourref` keys) and therefore stay empty by default, the date field has also not been set, but it should be. Therefore, the default value is “Undefined date”, and a warning is issued by a pink background.
- A folding mark has been printed in the extreme right margin, such that on folding the paper along it, it will correctly fit in a 220 x 110 mm envelope; this has been achieved by using the `fold3` key.
- In between closing (*Best regards,*) and signature (*W.H. Dekker*) an autograph has been placed. This was done by setting `autograph=2`. Alternative values are 0 (nothing between closing and signature), 1 for white space where an autograph can be placed with a pen after printing, or one of the values 2-9, which may have been associated with other autograph images. In this case, I have used an autograph image in which I have drawn the boundary box and the *outdent*, *closing*, and *signature* positions defined in the `\autograph` command (see the section *Commands*) with red lines.
- The bottom of the letter has (up to) four fields with contact information. This is useful if your logo does not show that information. If it does, you can omit these fields by using the `nofooter` key, or by not using the `footer` key, depending on the default set in the style file.



The Shiva Shakti Foundation

Main Building 567th floor Room 125 Bangkok

Wybo Dekker
Deilsedijk 60
4158 CH Deil

Your letter of	Your reference	Our reference	Date
May 12	MAPS #34	1029	22nd February 2012

Subject: Sample letter with the isodoc class

Beste Wybo,

This is an example of a letter made with the isodoc class. It has been compiled with XeLaTeX. Note that the date was set to 'today', so the date above the letter depends upon the day of compilation.

The picture in the logo was designed by Pieter Weltevrede. The text in the logo is Chopin Script, the body text is MinionPro Regular. The text¹ has no meaning, its only goal is to get a long letter.

Typografie wordt meestal toegepast om het doel en de inhoud van een tekst te ondersteunen. Een tekst moet bijvoorbeeld prettig leesbaar zijn. Daarom worden teksten in boeken en kranten vaak uit een lettertype met schreef gezet, maar op het beeldscherm juist vaak met een schreefloos lettertype zoals Verdana of Tahoma opgemaakt.

Voor een reclame- of waarschuwingsbord is het van belang dat woorden opvallen door ze met felle kleuren te accentueren. In een lange tekst wordt het juist als storend wordt ervaren wanneer er vetgedrukte woorden uitspringen en wordt bij voorkeur cursivering gebruikt om de lezer te attenderen.

Ook met andere zaken die de leesbaarheid van een tekst beïnvloeden houdt typografie zich bezig. Bijvoorbeeld het gebruik (doelgroep) en de indeling van een pagina. De typograaf let op:

- de zetbreedte (regellengte): de breedte van een tekstblok of kolom. De typograaf let daarbij op het maximum aantal tekens of woorden per regel. Bij een tekst met te lange regels moet het oog van de lezer namelijk een te grote afstandssprong maken van het eind van de regel naar het begin van de volgende. In het algemeen worden maxima gehanteerd van gemiddeld ca. 85 tekens (inclusief spaties en leestekens) of van gemiddeld twaalf woorden.
- de diverse lettergroottes (corpsen) en -soorten Door een combinatie daarvan (naast o.a. kleurgebruik) kan de typograaf de diverse tekstelementen visueel onderscheidend maken en daarmee de inhoudelijke hiërarchie goed visualiseren en ordenen. Letterfamilies bestaan uit diverse lettersoorten, meestal minimaal romein (normaal), vet, cursief en vet-cursief. Er zijn ook uitgebreide letterfamilies, die dan bijv. als extra lettersoort vet-cursief, halfvet, extra vet, versmald en verbreed hebben.

¹gathered from the T_EX-distribution

Figure 2: Long letter example with a non-standard logo, page 1

- de interlinie: het wit tussen twee regels.
- de regelafstand: de grootte van de letter (het korps) opgeteld bij de grootte van de interlinie. (Voorbeeld: corps 10 punt + 4 punt interlinie geeft een regelafstand van 14 punt.)
- de woordspaties: het wit (de ruimte) tussen twee woorden.
- de letterspatiëring: het wit tussen de letters onderling
- de leestekens
- de gebruikte letterfamilie(s) (lettertypen).
- het vaste (verticale) tussenwit (bij meerdere kolommen)
- het bijeenblijven van inhoudelijke eenheden
- het bijeenblijven van inhoudelijke eenheden

Om een bekend voorbeeld te geven: de staartregel van een alinea die niet alleen boven aan een pagina mag staan (het zgn. 'hoerenjong'). Zo bestaat er o.a. ook de 'wees' of de 'weduwe' (uit het engels: the 'widow'). Deze termen staan beiden voor de eerste regel van een alinea die alleen staat onderaan een pagina.

Voor woordenboeken of kranten,² waar ruimte schaars is, worden er opzettelijk smalle lettertypen uitgezocht, waardoor het papier efficiënter benut kan worden. De marges worden dan uiteraard ook klein gehouden. Een voorbeeld is de Lexicon (Bram de Does, 1992), die wordt gebruikt in de krant NRC Handelsblad en het woordenboek de Dikke Van Dale.

Sommige aspecten en gewoontes van de typografie zijn universeel: te lange regels, te weinig interlinie en te kleine woordspaties lezen niet prettig. Andere gewoontes zoals het gebruik van aanhalingstekens en gedachtestreepjes verschillen van tijd tot tijd en van land tot land en daarbinnen nog weer van publicatie tot publicatie.

Kind regards

 Wybo Dekker

Enclosure:
 Isodoc documentatie

²en wat u nog maar zelf kunt bedenken...

Figure 3: Long letter example with a non-standard logo, page 2

4.2 Multiple letters, redefined logo

Let's try another illustrative example, see figures 2 and 3: we use a modified style file, with a redefined logo, so we don't need a page footer; we use preprinted right-windowed envelopes, so a return address is not needed. Here is the style file (logostyle.sty):

```
\NeedsTeXFormat{LaTeX2e}[1999/12/01]
\ProvidesPackage{logostyle}
  [2010/08/21 v1.1 Shiva Shakti style file for isodoc]
\usepackage{fontspec,polyglossia}
\setupdocument{
  nofooter,fold2,autograph=1,
  company      = The Shiva Shakti Foundation,
  who          = Wybo Dekker,
  street       = Deilsedijk 60,
  city        = Deil,
  zip         = 4158 CH,
  country     = The Netherlands,
  countrycode = IN,
  areacode    = 31,
  phone       = {87-87\,48\,496},
  cellphone   = {6-15\,49\,20\,70},
  fax         = {},
  website     = www.xs4all.nl,
  email       = wybod@xs4all,
  accountno   = {3040\,46221},
  iban        = nl61pstb0006238747,
  bic         = pstbnl21,
  addresscenter = 70,
  rightaddress
}
\autograph{2}{.20}{75bp}{47bp}{238bp}{261bp}{signblue}

\definecolor{headcolor}{rgb}{0.42, 0.57, 0.14} % goldenrod2
\definecolor{shivablue}{rgb}{.14,.33,.43}
\definecolor{shivaback}{rgb}{.78,.89,.68}
\graphicspath{./graphics/}

\renewcommand{\logo}{
  \pagecolor{shivaback}
  \begin{textblock}{2}(10,13)
    \includegraphics[scale=.3]{shiva_shakti.jpg}
  \end{textblock}
  \begin{textblock}{105}(88,15)
    \begin{center}
      \fontspec{ChopinScript.otf}
      {\Huge\noindent\textcolor{shivablue}{The Shiva Shakti Foundation}}\\[2ex]
      Main Building\quad
      567\textsuperscript{th} floor\quad
      Room 123\quad
      Bangkok
    \end{center}
  \end{textblock}
}
\setmainfont[Mapping=tex-text]{MinionPro-Regular}
\setdefaultlanguage{english}
\setotherlanguage{dutch}
\endinput
```

The letter source does not use the autograph key, so the default value of 2 is used; we write it in Dutch and use a larger text, just to see what happens if more than one page is generated:

Wybo Dekker
Deilsedijk 60
4158 CH Deil

NTG
Maasstraat 2
5836 BB Sambeek

Datum
1 april 2006

REKENING

Omschrijving	Bedrag(€)
enveloppen	6,60
postzegels	9,00
Totaal	15,60

rekening nr: 304046221
ten name van: W.H. Dekker
kenmerk: 8234

webstek	telefoon	telefax	e-mail
www.xs4all.nl	087-8748496	0842-234393	wybo@xs4all.nl

Figure 4: Invoice example


```

%!xelatex
\documentclass[11pt,twoside]{isodoc}
\usepackage{logostyle}
\setupdocument{
  ourref = 1029,
  yourletter = May 12,
  yourref = MAPS \#34,
  date = today,
  closing = Kind regards,
  signature = Wybo Dekker,
  enclosures = Isodoc documentatie,
  subject = Sample letter with the isodoc class,
  autograph = 2,
}
\newcommand{\letterbody}{%
  This is an example of a letter made with the isodoc class.
  It has been compiled with XeLaTeX.
  Note that the date was set to 'today', so the date above the
  letter depends upon the day of compilation.

  The picture in the logo was designed by Pieter Weltevrede.
  The text in the logo is Chopin Script, the body text is MinionPro Regular.
  The text\footnote{gathered from the \TeX-distribution} has no meaning,
  its only goal is to get a long letter.
  % It's in dutch, so we select that language:
  \begin{dutch}
    \par\input{typo}
  \end{dutch}
}

\begin{document}
\letter[to = Wybo Dekker\\
        Deilsedijk 60\\
        4158 CH Deil,
        opening = Beste Wybo
]{\letterbody}
\letter[to = MAPS redactie\\
        Spuiboulevard 269\\
        3311 GP Dordrecht,
        opening = Beste Taco
]{\letterbody}
\end{document}

```

In this case, the same letter had to be sent to two different people, with different openings and addresses of course. So the letter's body is separately defined and the `\letter` command is called twice, with the same body, but different to and opening keys. Figures 2 and 3 show the first two pages (the first letter) of this document, which actually has four pages.

5 Usage: invoices

5.1 A simple invoice

Invoices (can) have the same structure as letters, except that the `\opening` isn't "Dear Somebody" anymore, but something like "Invoice". And the `\closing` doesn't say "Best regards", but may provide payment information. And the body is not a simple text, but a table with descriptions of things to be paid, and the corresponding amounts of money.

An example, as usual, is most instructive:



NEDERLANDSTALIGE T_EX GEBRUIKERSGROEP

Wybo Dekker
Deilsedijk 60
4158 CH Deil

NTG • Deilsedijk 60 • Deil 4158 CH

W.H. Dekker
Deilsedijk 60
4158 CH Deil

Uw brief van

Uw kenmerk

Ons kenmerk
308

Datum
3 mei 2006

Onderwerp: Contributie 2006

REKENING

Omschrijving	Bedrag(€)
Contributie NTG voor 2006	40,00

Betalingsgegevens:

rekening nr: 1306238
ten name van: NTG
kenmerk: 308

deze strook niet meezenden

euro-acceptgiro

over te schrijven/te storten

€ euro ct

van girorekening of bankrekening

van/door

naam

adres

plaats

handtekening

zijn alle rode rubrieken ingevuld?

formulier uitsluitend bestemd voor betaling in euro's

110675-E05
0602

op rekening 1306238
NTG
Deilsedijk 60
4158 CH Deil

op rekening 1306238
van NTG
Deilsedijk 60, 4158 CH Deil

formulier met blauwe of zwarte inkt invullen
© gezamenlijke banken en postbank

nadruk verboden de ruimte hieronder niet beschrijven

betalingskenmerk ☒ van rekening ☐ euro ☐ ct ☒ diversen ☒ naar rekening ☐ code

0021306238+ 12>

Figure 5: Invoice example with accept form

```

\documentclass[12pt]{isodoc}
\usepackage{isowybo}
\setupdocument{
  ourref=8234,
  date=20060401,
  subject=Declaratie verzending aanmaningen,
  to=NTG\Maasstraat 2\5836 BB Sambeek
}
\begin{document}
\invoice{
  \itable{
    \iitem{enveloppen}{6,60}
    \iitem{postzegels}{9,00}
    \itotal{15,60}
  }
  \[3ex]\accountdata
}
\end{document}

```

The result is shown in figure 4.

5.2 Invoice with redefined logo

When the `accept` option is used, the invoice will be created with an invoice form on the lower third part of the page. Here is an example:

```

\documentclass{isodoc}
\usepackage{isontg}
\setupdocument{accept,
  acceptdesc=NTG\2006,
  acceptdescription=Contributie 2006,
  acceptreference=4000 0000 2006 0308,
  date=20060503,
  subject=Contributie 2006,
  nofooter
}
\begin{document}
\invoice[
  to=W.H. Dekker\Deilsedijk 60\4158 CH Deil,
  acceptaccount=304046221,
  accepteuro=40,
  acceptcents=00,
  ourref=308,
]\itable{\iitem{Contributie NTG voor 2006}{40,00}}\[3ex]
\accountdata
\begin{textblock}{210}(0,199.5)
  \noindent\includegraphics[width=210mm]{acceptform.jpg}
\end{textblock}
}
\end{document}

```

Normally such invoices are printed on preprinted paper with an easily detachable, perforated form. In this example, the form itself has been printed, too. The `graphicx` and `textpos` packages have already been made available by the `isodoc` class. Figure 5 shows the output of this example.

6 Implementation

The basis is the `article` class with all options:

```

1 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}
2 \ProcessOptions
3 \LoadClass{article}

```

We use `\ctable` floats here, and we need `ctable`'s commands for decent spacing in tables and more. `ctable` also brings us `array`, `tabularx`, `color`, and `xkeyval`. `eurosym` is used for the euro symbol.

```

4 \RequirePackage{ctable,eurosym,graphicx,stringstrings,calc}
5 \RequirePackage{forarray}

```

Since the name of the package contains 'iso', make the page A4. For `textpos`, divide the page in 210 columns of 1mm each and 297 rows, 1mm each. The page is vertically divided in 6 columns of 35mm each: a left margin, 4 fields, and a right margin.

```

6 \RequirePackage[nofoot,head=\baselineskip]{geometry}
7 \RequirePackage[absolute,overlay]{textpos}
8 \geometry{papersize={210mm,297mm},margin=35mm}
9 \TPGrid{210}{297}

```

Several colors can be changed, by using the `\definecolor` command; the defaults (all black) are set here:

<code>headcolor</code>	<code>headcolor</code> : color for the header and footer field texts
<code>headingcolor</code>	<code>headingcolor</code> : color for the fancy headings
<code>markercolor</code>	<code>markercolor</code> : color for the folding marks

```

10 \definecolor{headcolor}{gray}{0}
11 \definecolor{headingcolor}{gray}{0}
12 \definecolor{markercolor}{gray}{0}

```

Use fancy headings, except for the first page. The heading, on a rule, looks like:

To: John Doe (April 1st, 2006)

Page 2 of 3

```

13 \RequirePackage{fancyhdr}
14 \pagestyle{fancy}
15 \AtBeginDocument{\addtolength{\headheight}{\baselineskip}}

```

The `\xxdoc` commands (like `\dutchdoc`) set the default language via `\AtBeginDocument`, but other language changes should be done without that. So we must have a boolean to check if we are in the preamble:

```

16 \newif\ifpreamble\preambletrue
17 \AtBeginDocument{\preamblefalse}

```

Background color for signaling items that should have been defined, but weren't:

```

18 \definecolor{isodocpink}{rgb}{1,.7,.7}
19 \def\Undefined#1{\colorbox{isodocpink}{Undefined #1}}

```

A small sans serif font is used for header and footer field names and the sender's address information. The idea is that this is used for all pre-printed text on the letter paper.

```

20 \def\@hft{\footnotesize\sffamily\color{headcolor}}

```

6.1 The options and their defaults

6.1.1 General options

`shift` The default shift is 0mm,0mm. The `shift` option moves the output to the right

and down:

```
21 \def\@xyshift#1,#2@@{\def\@xshift{#1}\def\@yshift{#2}}
22 \define@key{isodoc}{shift}{%
23   \@xyshift#1@@
24   \AtBeginDocument{\textblockorigin{\@xshift mm}{\@yshift mm}}
25 }
```

foreign Several items in the letter/invoice will be different in documents that are to be sent abroad; this is set with the foreign option, false by default:

```
26 \define@key{isodoc}{foreign}[\foreigntrue]{\foreigntrue}
27                                     \newif\ifforeign\foreignfalse
```

cityzip By default, the zip code is typeset before the city. The cityzip option reverses this:

```
28 \define@key{isodoc}{cityzip}[\cityziptrue]{\cityziptrue}
29                                     \newif\ifcityzip\cityzipfalse
```

localbank When the foreign option is used, IBAN and BIC codes are reported, but this can be suppressed with the localbank option:

```
30 \define@key{isodoc}{localbank}[\localbanktrue]{\localbanktrue}
31                                     \newif\iflocalbank\localbankfalse
```

dutch The following keys set the language; English, set at the \EndOfClass is the default.
 english
 german
 american
 french
 language

```
32 \define@key{isodoc}{dutch} []{\isodoc@dutch}
33 \define@key{isodoc}{english} []{\isodoc@UKenglish}
34 \define@key{isodoc}{german} []{\isodoc@german}
35 \define@key{isodoc}{american} []{\isodoc@USenglish}
36 \define@key{isodoc}{french} []{\isodoc@french}
37 \define@key{isodoc}{language}{\csname isodoc@#1\endcsname}
```

fill The default is to have left, but not right justification, allowing for hyphenation in
 nofill extreme cases:

```
38 \define@key{isodoc}{fill} []{\rightskip=1\rightskip}
39 \define@key{isodoc}{nofill} []{\rightskip=0mm plus 35mm}
40                                     \rightskip=0mm plus 35mm
```

6.1.2 Logo

company The logo, by default, consists of a large company or personal name on top a rule,
 logoaddress with a contact person's name (probably your own name) and address hanging
 who under the rule. Its contents are defined by the following options:

```
street 41 \define@key{isodoc}{company} {\def\company{#1}}
city 42 \def\company{\Undefined{company}}
zip 43 \define@key{isodoc}{logoaddress}{\def\logoaddress{#1}}
country 44 \define@key{isodoc}{who} {\def\who{#1}}
countrycode 45 \def\who{\Undefined{who}}
46 \define@key{isodoc}{street} {\def\street{#1}}
47 \def\street{\Undefined{street}}
48 \define@key{isodoc}{city} {\def\city{#1}}
49 \def\city{\Undefined{city}}
50 \define@key{isodoc}{country} {\def\country{#1}}
51 \def\country{\Undefined{country}}
52 \define@key{isodoc}{countrycode}{\def\countrycode{#1}}
53 \def\countrycode{\Undefined{countrycode}}
54 \define@key{isodoc}{zip} {\def\zip{#1}}
55 \def\zip{\Undefined{zip}}
56 \def\prezip{\ifforeign\countrycode\else\fi}
```

6.1.3 Address window

leftaddress The address can be positioned vertically with the `addresscenter` option; the default is 63.5mm. This is the vertical position of the center of the address. Horizontally, the address is positioned either left or right, depending on the `leftaddress` or `rightaddress` options being used. In the first case, the address start at `x=35mm`, which is the left margin (the default), and thus in line with the first header field, in the second case at 105mm, in line with the one-but-last header field.

```
57 \define@key{isodoc}{leftaddress} []{\def\xaddress{35}}
58                               \def\xaddress{35}}
59 \define@key{isodoc}{rightaddress} []{\def\xaddress{105}}
60 \define@key{isodoc}{addresscenter} {\def\addresscenter{#1}}
61                               \def\addresscenter{63.5}}
62 \define@key{isodoc}{addresswidth} {\def\addresswidth{#1}}
63                               \def\addresswidth{70}}
```

to The `to` option takes the addressee's address lines. Use `\\` to separate lines. The info will be split by `\processto` on the first `\\` separator into the addressee's name (`\toname`) and his address (`\toaddress`) The `\toname` will be reported in the pdf's document properties. However, this works only if the `to` key is set, with `\setupdocument`, in the preamble. If several letters are composed, `to` is normally set in the `\letter` or `\invoice` commands and thus is not seen by the `\hypersetup`, which is called `\AtBeginDocument`; so set the defaults to Various people for the `\toname` and make the address undefined:

```
64 \define@key{isodoc}{to}{\processto{#1}}\def\toname{Various people}
65                               \def\toaddress{\Undefined{to}}
66 \long\def\processto#1{\xproc #1\\@@@{\ifx\toaddress\empty
67   \else \yproc #1@@@{\fi}
68 \long\def\xproc #1\\#2@@@{\def\toname{#1}\def\toaddress{#2}}
69 \long\def\yproc #1\\#2@@@{\def\toaddress{#2}}}
```

return The default is to have no return address; but this can be changed by using the `return` (either in the style file or in the source) or, if the default was changed in the style file, remove it with `noreturn` in the source. Company and country names are often too long to fit in the address window. Or you may want to define an entirely different return address. The `returnaddress` option is provided to redefine the return address:

```
70 \define@key{isodoc}{return} []{\returntrue}
71                               \newif\ifreturn\returnfalse
72 \define@key{isodoc}{noreturn} []{\returnfalse}
73 \define@key{isodoc}{returnaddress} {\def\returnaddress{#1}}
```

6.1.4 Header

header A header is switched on or off with the `header` and `noheader` options. The default is to have a header.

```
74 \define@key{isodoc}{header} []{\headertrue}
75                               \newif\ifheader\headertrue
76 \define@key{isodoc}{noheader} []{\headerfalse}
```

bodyshift The header is the start of the body. It is initially positioned at 98mm from the top of the paper, but it can be shifted with the `bodyshift` option.

```
77 \define@key{isodoc}{bodyshift} {\advance\headerpos#1}
78 \newcount\headerpos\headerpos=98
79 \newcount\footerpos\footerpos=275
80 \newcount\subjectpos
81 \newcount\openingpos
82 \newcount\textskip
```

6.1.5 Footer

footer A footer is switched on or off with the `footer` and `nofooter` options. The default
nofooter is the have no footer.

```
83 \define@key{isodoc}{footorder} {\def\footorder{#1}}
84 \def\footorder{website;phone;cellphone;fax;email}
85 \define@key{isodoc}{footer} []{\footertrue}
86 \newif\iffooter\footerfalse
87 \define@key{isodoc}{nofooter}[]{\footerfalse}
```

If there is a page footer, only those fields will be displayed which are not empty.

areacode Currently the `phone`, `cellphone`, `fax`, `email` and `website` are recognised as possible
phone footer fields. Phone and fax number will be prefixed with a 0, unless the
phoneprefix foreign option was used: then the prefix will be '+nn-', where nn is the area-
cellphone code. The latter is set with the `areacode` option, which is 'Undefined areacode' by
fax default.

```
88 \define@key{isodoc}{areacode} {\def\areacode{#1}}
89 \def\areacode{\Undefined{areacode}}
90 \define@key{isodoc}{phone} {\def\isodoc@phone{#1}}
91 \def\isodoc@phone{}
92 \define@key{isodoc}{phoneprefix}{\def\phoneprefix{#1}}
93 \def\phoneprefix{0}
94 \define@key{isodoc}{cellphone} {\def\isodoc@cellphone{#1}}
95 \def\isodoc@cellphone{}
96 \define@key{isodoc}{fax} {\def\isodoc@fax{#1}}
97 \def\isodoc@fax{}
98 \define@key{isodoc}{website} {\def\website{#1}}
99 \def\website{}
100 \define@key{isodoc}{email} {\def\email{#1}}
101 \def\email{}
```

6.1.6 Folding mark

nofold The default is to have no folding mark. So start with the folding mark position
outside the paper boundaries:

```
102 \define@key{isodoc}{nofold}[]{\yfold=-1mm}
103 \newdimen\yfold\yfold=-1mm
```

foldleft The folding mark is in the right margin, but it can be moved to the left margin
foldright with the `foldleft` option, or, if made that the default in your style file, back to
the right margin with the `foldright` option:

```
104 \define@key{isodoc}{foldleft}[]{\xfold=9mm}
105 \newdimen\xfold\xfold=201mm
106 \define@key{isodoc}{foldright}[]{\xfold=201mm}
```

fold2 The envelope for double folded A4 is C5: 162x220mm, window 40x110mm, upper
left corner at 20x50mm. Fold the A4 to have a tolerance of 2mm at top and
bottom, by putting the fold mark at $162-4=158$ mm.

```
107 \define@key{isodoc}{fold2}[]{\yfold=158mm}
```

fold3 The envelope for triple folded A4 is DL: 110x220mm, Fold the A4 to have a toler-
ance of 1.5mm at top and bottom, by putting the fold mark at $110-3=107$ mm.

```
108 \define@key{isodoc}{fold3}[]{\yfold=107mm}
```

fold For non-standard envelopes and paper formats the position of the folding mark
can be set at any position (in mm) from the top of the paper:

```
109 \define@key{isodoc}{fold}{\yfold=#1mm}
```

6.1.7 Header fields

There are four header fields, each one quarter of the textwidth wide. Under those, if the subject has been defined, a subject line. The header position is 98mm by default, but it can be shifted with the `bodyshift` option.

<p>ourref</p> <p>yourref</p> <p>yourletter</p>	<pre> 110 \define@key{isodoc}{ourref} {\def\ourref{#1}} 111 \def\ourref{} 112 \define@key{isodoc}{yourref} {\def\yourref{#1}} 113 \def\yourref{} 114 \define@key{isodoc}{yourletter}{\def\yourletter{#1}} 115 \def\yourletter{} </pre>
--	---

<p>date</p>	<p>The date must be entered in either of three formats: <code>yyyy-mm-dd</code>, <code>yyyymmdd</code> or the string <code>today</code>. Here we check that a correct format is offered and that the values for <code>mm</code> and <code>dd</code> are in the range 1–12 and 1–31 respectively. The string <code>today</code> sets the date to today's date.</p>
-------------	---

```

116 \define@key{isodoc}{date}{\@ismakedate{#1}}
117                               \def\date{\Undefined{date}}

```

<p>forcedate</p>	<p>If you know what you do you can substitute anything you like for the date by using the <code>forcedate</code> option instead of <code>date</code>:</p>
------------------	---

```

118 \define@key{isodoc}{forcedate}{\def\forcedate{#1}}\def\forcedate{}

```

<p>subject</p>	<p>The subject is empty by default and will be typeset only if you give it a value.</p>
----------------	---

```

119 \define@key{isodoc}{subject}{\def\subject{#1}}
120                               \def\subject{}

```

<p>opening</p> <p>openingcomma</p>	<p>The opening, something like 'Dear Reader', is set by the <code>opening</code> option; the default is 'Undefined opening'. It is followed by a comma, unless the <code>openingcomma</code> has been used to set it to a different character, like a semicolon or an exclamation mark.</p>
------------------------------------	---

```

121 \define@key{isodoc}{opening}    {\def\opening{#1}}
122                               \def\openingcomma{,}
123 \define@key{isodoc}{openingcomma}{\def\openingcomma{#1}}
124                               \def\opening{\Undefined{opening}}

```

6.1.8 Closing, autograph, signature

<p>closing</p> <p>closingskip</p>	<p>The closing, something like 'Best regards', is set by the <code>closing</code> option; the default is 'Undefined closing'. It will be preceded by a vertical skip, which can be set by the <code>closingskip</code> option, which is <code>2\baselineskip</code> by default:</p>
-----------------------------------	---

```

125 \define@key{isodoc}{closing}    {\def\closing{#1}}
126 \def\closingcomma{,}
127                               \def\closing{\Undefined{closing}}
128 \define@key{isodoc}{closingskip}{\closingskip=#1}
129                               \newdimen\closingskip\closingskip=2\baselineskip

```

<p>autograph</p>	<p>The autograph is either just a newline, or a vertical spacing where you can put your autograph manually, or a graphic. In the latter case, it must have been defined with the macro <code>\autograph</code>, which defines an autograph from an image, see the section <i>User Macros</i>. Not using the <code>autograph</code> option is equivalent to <code>autograph=0</code> (just a newline). Using it without a value is equivalent to <code>autograph=2</code> (image inserted):</p>
------------------	--

```

130 \define@key{isodoc}{autograph}[2]{\def\autographversion{#1}}
131                               \def\autographversion{0}

```

<p>signature</p>	<p>The signature, something like 'John Letterwriter', is set by the <code>signature</code> option;</p>
------------------	--

the default is 'Undefined signature'.

```
132 \define@key{isodoc}{signature}{\def\signature{#1}}
133 \def\signature{\Undefined{signature}}
```

enclosures Enclosures are set by the enclosures option. There are none by default.

```
134 \define@key{isodoc}{enclosures} {\def\enclosures{#1}}
135 \def\enclosures{}
```

6.1.9 Invoice specific data

term Invoices need to state some specific data, like account data and term of payment:

```
accountno 136 \define@key{isodoc}{term} [30]{\def\term{#1}}
routingno 137 \define@key{isodoc}{accountno} {\def\accountno{#1}}
accountname 138 \define@key{isodoc}{routingno} {\def\routingno{#1}}
iban 139 \define@key{isodoc}{accountname}{\def\accountname{#1}}
bic 140 \define@key{isodoc}{iban} {\def\iban{#1}}
vatno 141 \define@key{isodoc}{bic} {\def\bic{#1}}
chamber 142 \define@key{isodoc}{vatno} {\def\vatno{#1}}
currency 143 \define@key{isodoc}{chamber} {\def\chamber{#1}}
144 \def\chamber{\Undefined{chamber}}
145 \define@key{isodoc}{currency} {\def\currency{#1}}
146 \def\currency{\EuroSymbol}
```

accept If an accept form is to be printed, here are the options to fill in all the fields:

```
acceptaccount 147 \define@key{isodoc}{accept}[E05]{\def\accepttype{#1}}
acceptaddress 148 \newfont\ocrb{ocrb10}
149 }
acceptdescription 150 \define@key{isodoc}{acceptaccount} {\def\acceptaccount{#1}}
151 \def\acceptaccount{}
accepteuros 152 \define@key{isodoc}{acceptaddress} {\def\acceptaddress{#1}}
acceptreference 153 \def\acceptaddress{}
154 \define@key{isodoc}{acceptcents} {\def\acceptcents{#1}}
155 \def\acceptcents{\Undefined{}}
156 \define@key{isodoc}{acceptdescription}{\def\acceptdescription{#1}}
157 \def\acceptdescription{}
158 \define@key{isodoc}{acceptdesc} {\def\acceptdesc{#1}}
159 \def\acceptdesc{}
160 \define@key{isodoc}{accepteuros} {\def\accepteuros{#1}}
161 \def\accepteuros{\Undefined{}}
162 \define@key{isodoc}{acceptreference} {\def\acceptreference{#1}}
163 \def\acceptreference{\Undefined{ref}}
```

For now, we define field positions for the E05 accept form only; when data for other forms become available, the content of \accepttype will have to be checked. Here is a rough layout of the E05 accept form – the last character tells if the items are typeset in a Tbox (T) or in a Cbox (C):

		description	T
ref		description	T
ref	euros cents	reference	C
eur ct	account		C
desc	address		T
desc	address		
desc	address		

```
164 \def\xacceptdescription{105}\def\yacceptdescription{200}\def\wacceptdescription{100} %T
165 \def\xacceptref{7} \def\yacceptref{212} \def\wacceptref{30} %T
166 \def\xaccepteuros{60} \def\yaccepteuros{216} \def\waccepteuros{32} %C
```

```

167 \def\xacceptcents{89}      \def\yacceptcents{216}      \def\wacceptcents{13}      %C
168 \def\xacceptreference{125} \def\yacceptreference{216} \def\wacceptreference{55} %C
169 \def\xaccepteur{14.4}      \def\yaccepteur{228.5}      \def\waccepteur{21}      %C
170 \def\xacceptct{32}        \def\yacceptct{228.5}      \def\wacceptct{9}      %C
171 \def\xacceptaccount{75}    \def\yacceptaccount{228.5} \def\wacceptaccount{65} %C
172 \def\xacceptdesc{7}       \def\yacceptdesc{241}      \def\wacceptdesc{26}     %T
173 \def\xacceptaddress{58}    \def\yacceptaddress{241}   \def\wacceptaddress{90}  %T

```

This is the `\baselineskip` for the two-line reference of the detachable strip:

```

174 \newdimen\acceptreferenceskip\acceptreferenceskip=5.15mm

```

6.2 User Macros

Some symbols taken from `marvosym.sty`:

```

175 \RequirePackage{isodocsymbols}

```

The autograph is either just a newline, or a vertical spacing where you can put your autograph manually, or a graphic. In the latter case, it must have been defined with the macro `\autograph`, which defines an autograph from an image.⁶ The arguments 3 - 6 can be found by measuring those (with the `gimp`, for example) in the unscaled (raw) image (which is the last argument).

```

arg 1: 2,3,...9: autograph number; will be translated internally to define
        \autographA, \autographB... \autographH
2:      scaling factor for the image
3:      the distance the autograph outdents in the margin
4:      the vertical position of the baseline of the closing (Regards,) from the top
5:      the vertical position of the baseline of the signature (John Letterwriter)
        from the top
6:      the height of the image
7:      the image (jpg, png, pdf...)

```

`\autograph`

```

176 \newdimen\myoutdent
177 \newdimen\signskip
178 \newdimen\mydown
179 \def\autograph#1#2#3#4#5#6#7{%
180   \ifnum #1<2
181     \ClassError{isodoc}{autograph #1 cannot be changed (first arg must be 2..9)}{}
182   \fi
183   \ifnum #1>9
184     \ClassError{isodoc}{autograph #1 cannot be changed (first arg must be 2..9)}{}
185   \fi
186   \bgroup
187   \lccode'2='A \lccode'6='E
188   \lccode'3='B \lccode'7='F
189   \lccode'4='C \lccode'8='G
190   \lccode'5='D \lccode'9='H
191   \lowercase{\def\temp{#1}}%
192   \expandafter\egroup\expandafter\def\csname autograph\temp\endcsname{%
193     \myoutdent=#3
194     \signskip=#5\advance\signskip-#4
195     \mydown=#6\advance\mydown-#4
196     \par\hspace*{-#2\myoutdent}%
197     \raisebox{-#2\mydown}[0bp][0bp]{\includegraphics[scale=#2]{#7}}\[-\baselineskip]
198     \closing\[-2\baselineskip]\[-#2\signskip]\signature%

```

⁶Thanks, Hans Hagen and Piet van Oostrum, for its definition

```
199 }
200 }
```

6.2.1 Logo

The logo, by default, consists of a large company name on top a rule, with a contact person's name (probably your own name) and address hanging under the rule. If the osf-txfonts package is used, oldstyle figures are disabled here.

```
\logo
201 \newcommand{\zippedcity}{\ifcityzip\city\ \prezip\ \zip\else\prezip\ \zip\ \city\fi}
202 \newcommand{\logo}{%
203   { \parskip=0pt\parindent=0pt
204     \begin{textblock}{140}[0,1](35,20)%
205       \textsf{\LARGE\company}\[-1.7ex] % large company name
206       \rule{\hspace}{.3pt} % on top a rule
207     \end{textblock}
208   }
209   \Tbox{140}{22}{35}{\noindent
210     \footnotesize\sffamily
211     \ifx\undefined\logoaddress%
212       \ifx\undefined\tbfigures\else\tbfigures\fi
213       \ifx\who\empty\else\who\\\fi
214       \ifx\street\empty\else\street\\\fi
215       \zippedcity
216       \ifforeign\\\country\fi
217     \else\logoaddress\fi
218   }
219 }

\returnaddress
220 \def\returnaddress{%
221   \ifx\undefined\tbfigures\else\tbfigures\fi % when using osf-txfonts... just for me
222   \company\\
223   \street\\
224   \zippedcity
225   \ifforeign\\\country\fi
226 }

\setupdocument
227 \newcommand{\setupdocument}[1]{
228   \setkeys{isodoc}{#1}
229   \iffooter\else\geometry{bottom=25mm}\fi
230 }

\@isomakedate
231 \newcount\@isoyear \@isoyear=\year \year=0
232 \newcount\@isomonth \@isomonth=\month
233 \newcount\@isoday \@isoday=\day
234 \def\@isomakedate#1{%
235   \def\@isoarg{#1}\def\@isotoday{today}
236   \ifx\@isoarg\@isotoday
237     \year=\@isoyear
238     \month=\@isomonth
239     \day=\@isoday
240   \else
241     \stringlength[q]{\@isoarg}
242     \ifnum\theresult=10
243       \substring[q]{\@isoarg}{5}{5}
244       \if\thestring-\else\ClassError{isodoc}{
245         Illegal date separator: \thestring (must be -)}\fi
246       \substring[q]{\@isoarg}{8}{8}
247       \if\thestring-\else\ClassError{isodoc}{
```

```

248     Illegal date separator: \thestring (must be -)}}\fi
249 \else
250     \ifnum\theresult=8\else\ClassError{isodoc}{
251     Illegal date: not yyyyymmdd | yyyy-mm-dd | today}}\fi
252 \fi
253 \Treatments{0}{0}{0}{1}{0}{0}
254 \substring[q]{\@isoarg}{1}{\$} \let\@isodigits=\thestring \def\@isoarg{\thestring}
255 \stringlength[q]{\@isodigits}
256 \ifnum\theresult=8\else\ClassError{isodoc}{Illegal date: must have 8 digits}}\fi
257 \substring[q]{\@isoarg}{1}{4} \year=\thestring \def\@isoarg{\@isodigits}
258 \substring[q]{\@isoarg}{5}{6} \month=\thestring \def\@isoarg{\@isodigits}
259 \substring[q]{\@isoarg}{7}{8} \day=\thestring \def\@isoarg{\@isodigits}
260 \ifnum \month > 12 \ClassError{isodoc}{Illegal date: month>12}}\fi
261 \ifnum \day > 31 \ClassError{isodoc}{Illegal date: day>31}}\fi
262 \fi
263 }

```

\accountdata Print a table with banking information. Show account number, account name + city, and a reference. If the foreign key was used, IBAN and BIC codes are also reported, but can be suppressed with the localbank option.

```

264 \def\accountdata{
265 \textbf{\accountdatatext:}\\
266 \begin{tabular}{@{}rl@{}}
267 \ifx\term\undefined\else
268 \termtext: & \term\ \daystext\\
269 \fi
270 \accountnotext: & \accountno\\
271 \ifx\accountname\undefined\else
272 \accountnametext: & \accountname}\\
273 \fi
274 \ifx\routingno\undefined\else
275 \routingnotext: & \routingno}\\
276 \fi
277 \referencetext: & \ourref\\
278 \ifforeign
279 \iflocalbank\else
280 \iban: & \scshape \iban\\
281 \bic: & \scshape \bic\\
282 \fi
283 \fi
284 \ifx\vatno\undefined\else
285 \vatnotext: & \vatno\\
286 \fi
287 \end{tabular}
288 }

```

The \showkeys command is useful for debugging. It prints a table showing the values of most keys.⁷

```

289 \def\showkeys{%
290 \begin{tabular}{ll}
291 \accept & \accept\NN
292 \acceptaccount & \acceptaccount\NN
293 \acceptaddress & \acceptaddress\NN
294 \acceptcents & \acceptcents\NN
295 \acceptdesc & \acceptdesc\NN
296 \acceptdescription & \acceptdescription\NN
297 \accepteuros & \accepteuros\NN
298 \acceptreference & \acceptreference\NN
299 \accountname & \accountname\NN
300 \accountno & \accountno\NN

```

⁷Note for developers: the table lines below can be generated with a ruby script listkeys (included in the distribution): `listkeys defs`

301 addresscenter & \addresscenter\NN
 302 addresswidth & \addresswidth\NN
 303 american & \american\NN
 304 areacode & \areacode\NN
 305 autograph & \autograph\NN
 306 bic & \bic\NN
 307 bodyshift & \bodyshift\NN
 308 cellphone & \cellphone\NN
 309 chamber & \chamber\NN
 310 city & \city\NN
 311 cityzip & \cityzip\NN
 312 closing & \closing\NN
 313 closingskip & \closingskip\NN
 314 company & \company\NN
 315 country & \country\NN
 316 countrycode & \countrycode\NN
 317 currency & \currency\NN
 318 date & \date\NN
 319 dutch & \dutch\NN
 320 email & \email\NN
 321 enclosures & \enclosures\NN
 322 english & \english\NN
 323 fax & \fax\NN
 324 fill & \fill\NN
 325 fold & \fold\NN
 326 fold2 & \fold2\NN
 327 fold3 & \fold3\NN
 328 foldleft & \foldleft\NN
 329 foldright & \foldright\NN
 330 footer & \footer\NN
 331 footorder & \footorder\NN
 332 forcedate & \forcedate\NN
 333 foreign & \foreign\NN
 334 french & \french\NN
 335 german & \german\NN
 336 header & \header\NN
 337 iban & \iban\NN
 338 language & \language\NN
 339 leftaddress & \leftaddress\NN
 340 localbank & \localbank\NN
 341 logoaddress & \logoaddress\NN
 342 nofill & \nofill\NN
 343 nofold & \nofold\NN
 344 nofooter & \nofooter\NN
 345 noheader & \noheader\NN
 346 noreturn & \noreturn\NN
 347 opening & \opening\NN
 348 openingcomma & \openingcomma\NN
 349 ourref & \ourref\NN
 350 phone & \phone\NN
 351 phoneprefix & \phoneprefix\NN
 352 return & \return\NN
 353 returnaddress & \returnaddress\NN
 354 rightaddress & \rightaddress\NN
 355 routingno & \routingno\NN
 356 shift & \shift\NN
 357 signature & \signature\NN
 358 street & \street\NN
 359 subject & \subject\NN
 360 term & \term\NN
 361 to & \to\NN
 362 vatno & \vatno\NN
 363 website & \website\NN

```

364             who & \who\NN
365         yourletter & \yourletter\NN
366         yourref & \yourref\NN
367         zip & \zip\NN
368     \end{tabular}
369 }
370 \AtEndOfClass{%
371     \usepackage{hyperref}
372     \year=0
373 }
374 \AtEndDocument{%
375     \hypersetup{pdfauthor={\who},
376                 pdfproducer={isodoc v\fileversion}
377     }
378 }
379 % \DescribeMacro{\itable}
380 % |\itable| inserts an invoice table; arg1 should be the rows of the table.
381 %     \begin{macrocode}
382 \def\itable#1{
383     \begin{tabularx}{\hsize}{@{}X@{\barsep\quad\qqquad}r@{}}
384         \multicolumn{2}{@{}c@{}}{\sffamily\descriptiontext\hfill
385         \amounttext (\currency)}\ML
386         #1
387     \end{tabularx}
388 }
389 % \DescribeMacro{\iitem}
390 % |\iitem| inserts an invoice item in the |\itable|.
391 % It inserts |arg1 & % arg2\NN|:
392 %     \begin{macrocode}
393 \def\iitem#1#2{#1&#2\NN}
394 % \DescribeMacro{\itotal}

\itotal inserts an invoice total in the \itable.
It inserts \cmidrule[.05em]{2-2}Total & arg1\NN:

395 \def\itotal#1{\cmidrule[.05em]{2-2}\totaltext&\textbf{#1}\NN}

```

The counter `\lettercount` is used to construct a label on the last page of each letter/invoice of this document; it will be set to `LastPageOfn`, where n is the letter number: 1, 2, 3, ... This allows for page headings saying “Page n of m .” This label is automatically added at the end of each letter.

```

396 \newcounter{lettercount}\setcounter{lettercount}{0}

```

`\invoice` `\invoice` prints an invoice. The first argument is optional, and may contain the same `key=value` statement as `\setupdocument`. This is useful if the document contains more than one invoice for different addressees.

The second argument creates a two-column table with headings “Description” and “Amount (EuroSymbol)”. The two columns are separated with a vertical rule; its construction is somewhat complicated, as the `booktabs`/`ctable` packages are in use that don’t provide decent vertical separators. The `\barsep` macro extends these separators vertically.

```

397 \newif\ifclosing\closingtrue
398 \newcount\footcount
399 \newcommand{\invoice}[2][\%
400     \closingfalse
401     \def\barsep{\raisebox{-1.5ex}[0pt][0pt]{\rule{.05em}{4ex}}}%
402     \letter[1,
403         opening={\bfseries\scshape\Large\invoicetext},
404         openingcomma={},
405         closing={},
406         signature={}}{\Tbox{35}{127}{140}{\ignorespaces#2}}
407 }

```

`\letter` `\letter` prints a letter... The code is enclosed in an extra pair of braces, in order to keep option changes local

```

408 \newcommand{\letter}[2][]{{%
409   \newpage
410   \setkeys{isodoc}{#1}
411   \def\isodoc@lead{\ifforeign+\areacode-\else\phoneprefix\fi}
412   \ifx\isodoc@phone\empty\else\def\phone{\isodoc@lead\isodoc@phone}\fi
413   \ifx\isodoc@cellphone\empty\else\def\cellphone{\isodoc@lead\isodoc@cellphone}\fi
414   \ifx\isodoc@fax\empty\else\def\fax{\isodoc@lead\isodoc@fax}\fi

```

By now, a language should have been chosen; if not, issue a warning and set the language to the default: UKenglish

```

415   \ifx\yourlettertext\undefined\ClassWarning{isodoc}{
416     You did not use the language option; using the default: UKenglish
417   }\isodoc@UKenglish\fi
418   \ifnum\value{lettercount}=0%
419     \hypersetup{pdftitle={letter to \toname\ dated \today},
420                pdfsubject={\subject}}
421   \fi
422   \addtocounter{lettercount}{1}
423   \setcounter{page}{1}
424   \setcounter{footnote}{0}
425   \fancyhf{}
426   \if@twoside
427     \fancyhead[LE,RO]{\color{headingcolor}%
428       \pagetext\ \thepage\ \oftext{}
429       \begin{NoHyper}\pageref{LastPageOf\thelettercount}\end{NoHyper}}
430     \fancyhead[RE,LO]{\color{headingcolor}%
431       \totext: \toname\ (\date)}
432   \else
433     \fancyhead[L]{\color{headingcolor}%
434       \totext: \toname\ (\date)}
435     \fancyhead[R]{\color{headingcolor}%
436       \pagetext\ \thepage\ \oftext{}
437       \begin{NoHyper}\pageref{LastPageOf\thelettercount}\end{NoHyper}}
438   \fi
439   \logo

```

`addresscenter` is the center, vertically, of the to-address block: `xaddress` should be 1 or 3 for left- and right address windows

```

440 { \parskip=0pt\parindent=0pt
441   \begin{textblock}{\addresswidth}[0,.5](\xaddress,\addresscenter)%
442     \ifreturn
443       {\def\{\unskip\enspace\textbullet\enspace\ignorespaces}%
444         \sffamily\bfseries\scriptsize\returnaddress
445         }\\[-.8\baselineskip]
446         \rule{\hsize}{.2pt}\\
447       \fi
448       \toname\\toaddress
449     \end{textblock}
450 }
451 \subjectpos=\headerpos
452 \textskip=\headerpos\advance\textskip-12
453 \ifx\subject\empty\advance\textskip-10\else\advance\subjectpos10\fi
454 \openingpos=\subjectpos
455 \ifheader
456   \openingpos=\subjectpos\advance\openingpos12
457   \Tbox{35}{\headerpos}{35}{\noindent
458     {\@hft\yourlettertext}\\
459     \yourletter
460   }
461   \Tbox{70}{\headerpos}{35}{\noindent

```

```

462     {\@hft\yourreftext}\\
463     \raggedright\yourref
464   }
465   \Tbox{105}{\headerpos}{35}{\noindent
466     {\@hft\ourreftext}\\
467     \raggedright\ourref
468   }
469   \Tbox{140}{\headerpos}{35}{\noindent
470     {\@hft\datetext}\\
471     \ifx\forcedate\empty%
472       \ifnum\year=0\Undefined{date}\else\date\fi
473     \else\forcedate\fi
474   }
475   \ifx\subject\empty\else%
476     \Tbox{35}{\subjectpos}{140}{\noindent
477       \begin{tabularx}{\hspace}{@{}l>\raggedright}X@{}
478       {\@hft\subjecttext&\subject
479       \end{tabularx}
480     }
481   \fi
482 \else
483   \advance\textskip-12
484 \fi

```

Create any non-empty footfields, starting at the left; (==> must have to be made variable with an option footfieldorder):

```

485 \footcount=35
486 \iffooter
487   \ForEachX{;}{%
488     \setbox0=\hbox{\csname\thislevelitem\endcsname}
489     \ifdim\wd0=0pt\else
490       \Tbox{\footcount}{\footerpos}{35}{\noindent
491         {\@hft\csname\thislevelitem text\endcsname}\\
492         \csname\thislevelitem\endcsname
493       }
494       \advance\footcount35
495     \fi
496   }{\footorder}
497 \fi
498 { \parskip=0pt\parindent=0pt
499   \begin{textblock*}{3mm}(\xfold,\yfold)%
500     {\color{markercolor}\rule{\hspace}{.2pt}}
501   \end{textblock*}
502 }
503 \ifx\undefined\accepttype\else\accept\fi
504 \noindent\Tbox{35}{\openingpos}{140}{\opening\openingcomma}
505 \vspace{\textskip mm}
506 \thispagestyle{empty}
507 \noindent\ignorespaces#2
508 {\parindent=0pt\parskip=\baselineskip
509   \ifclosing
510     \ifcase\autographversion
511       \par\closing\closingcomma\\\signature % 0: closing on the next line
512       \or\par\closing\closingcomma\\\[\closingskip]\signature % 1: whiteskip
513       \or\autographA
514       \or\autographB
515       \or\autographC
516       \or\autographD
517       \or\autographE
518       \or\autographF
519       \or\autographG
520       \or\autographH
521     \else

```



```

522     \par\Undefined{autograph: \autographversion}\\
523     \fi
524     \fi
525     \ifx\enclosures\empty\else
526         \vfill
527         \setbox1=\vbox{\enclosures}%
528         \textbf{\ifdim\ht1>\baselineskip\enclosurestext\else\enclosuretext\fi}%
529         \\enclosures
530     \fi
531 }
532 \label{LastPageOf\thelettercount}
533 }}

```

6.3 Internal Macros

The accept is produced from \Tbox and \Cbox commands only, using the textpos package: \Cbox{x}{y}{width}{text} places text in a box of \tests1{width} mm, centered around (x,y) in mm:

```

534 \def\Cbox#1#2#3#4{%
535 { \parskip=0pt\parindent=0pt
536   \begin{textblock}{#3}[.5,.5](#1,#2)%
537     \begin{center}
538       #4
539     \end{center}
540   \end{textblock}
541 }
542 }

```

\Tbox \Tbox{x}{y}{width}{text} places text in a box of \tests1{width} mm, with the upper left corner at (x,y) in mm:

```

543 \long\def\Tbox#1#2#3#4{%
544 { \parskip0pt\parindent=0pt
545   \begin{textblock}{#3}(#1,#2)%
546     \begin{minipage}[t]{\hspace}
547       \noindent#4
548     \end{minipage}
549   \end{textblock}
550 }
551 }

```

\accept This macro will have a parameter if other accept forms will have to be programmed:

```

552 \def\accept{
553   \Tbox{\xacceptdescription}
554     {\yacceptdescription}
555     {\wacceptdescription}
556     {\acceptdescription}
557   \Tbox{\xacceptdesc}
558     {\yacceptdesc}
559     {\wacceptdesc}
560     {\acceptdesc}
561   \Tbox{\xacceptaddress}
562     {\yacceptaddress}
563     {\wacceptaddress}
564     {\ifx\acceptaddress\empty\toname\\toaddress\else\acceptaddress\fi}
565   \Cbox{\xacceptreference}
566     {\yacceptreference}
567     {\wacceptreference}
568     {\ocrb\acceptreference}
569   \Tbox{\xacceptref}
570     {\yacceptref}

```

```

571      {\wacceptref}
572      {\baselineskip=\acceptreferenceskip\ocrb\acceptreference}
573 \Cbox{\xaccepteuros}
574      {\yaccepteuros}
575      {\waccepteuros}
576      {\ocrb\accepteuros}
577 \Cbox{\xacceptaccount}
578      {\yacceptaccount}
579      {\wacceptaccount}
580      {\ocrb\acceptaccount}
581 \Cbox{\xacceptcents}
582      {\yacceptcents}
583      {\wacceptcents}
584      {\ocrb\acceptcents}
585 \Cbox{\xaccepteur}
586      {\yaccepteur}
587      {\waccepteur}
588      {\ocrb\accepteuros}
589 \Cbox{\xacceptct}
590      {\yacceptct}
591      {\wacceptct}
592      {\ocrb\acceptcents}
593 }

```

\isodoc@catalan contributed by Cristian Peraferrer:

```

594 \def\isodoc@catalan{%
595   \gdef\accountdatatext {Dades banc\'aries}
596   \gdef\accountnametext {a nom de}
597   \gdef\accountnotext   {N\'um. de compte}
598   \gdef\amounttext      {Quantitat}
599   \gdef\ccname           {cc}
600   \gdef\cellphonetext   {M\'obil}
601   \gdef\chambertext     {Cambra de comer\c{c}}
602   \gdef\datetext        {Data}
603   \gdef\daystext        {dies}
604   \gdef\descriptiontext {Descripci\'o}
605   \gdef\emailtext       {E-mail}
606   \gdef\enclosurestext  {Annexos:}
607   \gdef\enclosuretext   {Annex:}
608   \gdef\faxtext         {Fax}
609   \gdef\invoicetext     {factura}
610   \gdef\oftext          {de}
611   \gdef\ourreftext      {La nostra refer\'encia}
612   \gdef\pagetext        {P\'agina}
613   \gdef\phonetext       {Tel\'efon}
614   \gdef\referencetext   {Refer\'encia}
615   \gdef\routingnotext   {Nombre de ruta}
616   \gdef\subjecttext     {Assumpte}
617   \gdef\termtext        {Termini del pagament}
618   \gdef\totaltext       {Total}
619   \gdef\totext          {A}
620   \gdef\vatnotext       {N\'um. IVA}
621   \gdef\vattext         {IVA}
622   \gdef\websitetext     {Web}
623   \gdef\yourlettertext  {La seva carta del}
624   \gdef\yourreftext     {La seva refer\'encia}
625   \gdef\date             {\number\day\space\ifcase\month\or
626     gener\or febrer\or mar\c{c}\or abril\or maig\or juny\or
627     juliol\or agost\or setembre\or octubre\or novembre\or desembre\fi
628     \space \number\year
629   }
630 }

```

\isodoc@dutch

```

631 \def\isodoc@dutch{%
632   \gdef\accountdatatext {Betalingsgegevens}
633   \gdef\accountnametext {ten name van}
634   \gdef\accountnotext   {rekening nr}
635   \gdef\amounttext      {Bedrag}
636   \gdef\ccname           {Cc:}
637   \gdef\cellphonetext   {mobiel}
638   \gdef\chambertext     {kvk}
639   \gdef\datetext        {Datum}
640   \gdef\daystext        {dagen}
641   \gdef\descriptiontext {Omschrijving}
642   \gdef\emailtext       {e-mail}
643   \gdef\enclosurestext  {Bijlagen:}
644   \gdef\enclosuretext   {Bijlage:}
645   \gdef\faxtext         {telefax}
646   \gdef\invoicetext     {rekening}
647   \gdef\oftext          {van}
648   \gdef\ourreftext      {Ons kenmerk}
649   \gdef\pagetext        {Bladnummer}
650   \gdef\phonetext       {telefoon}
651   \gdef\referencetext   {kenmerk}
652   \gdef\routingnotext   {banknummer}
653   \gdef\subjecttext     {Onderwerp:}
654   \gdef\termtext        {betalingstermijn}
655   \gdef\totaltext       {Totaal}
656   \gdef\totext          {Aan}
657   \gdef\vatnotext       {btw nr}
658   \gdef\vattext         {Btw}
659   \gdef\websitetext     {webstek}
660   \gdef\yourlettertext  {Uw brief van}
661   \gdef\yourreftext     {Uw kenmerk}
662   \gdef\date            {\number\day\space\ifcase\month\or
663     januari\or februari\or maart\or april\or mei\or juni\or juli\or
664     augustus\or september\or oktober\or november\or december\fi
665     \space \number\year}
666 }

```

\isodoc@french

```

667 \def\isodoc@french{%
668   \gdef\accountdatatext {Donn\'ees bancaires}
669   \gdef\accountnametext {au nom de}
670   \gdef\accountnotext   {no. compte}
671   \gdef\amounttext      {Montant}
672   \gdef\ccname           {Copie \'a}
673   \gdef\cellphonetext   {portable}
674   \gdef\chambertext     {c.c.i.}
675   \gdef\datetext        {Date:}
676   \gdef\daystext        {jours}
677   \gdef\descriptiontext {Description}
678   \gdef\emailtext       {email}
679   \gdef\enclosurestext  {Pi\'eces jointes:}
680   \gdef\enclosuretext   {Pi\'ece jointe:}
681   \gdef\faxtext         {t\'el\'efax}
682   \gdef\invoicetext     {facture}
683   \gdef\oftext          {de}
684   \gdef\ourreftext      {Nos r\'ef\'erences:}
685   \gdef\pagetext        {Page}
686   \gdef\phonetext       {t\'el\'ephone}
687   \gdef\referencetext   {r\'ef\'erence}
688   \gdef\routingnotext   {num\'ero d\'acheminement}
689   \gdef\subjecttext     {Objet:}
690   \gdef\termtext        {terme}
691   \gdef\totaltext       {Total}

```

```

692 \gdef\totext      {\‘A l’attention de}
693 \gdef\vatnotext    {no. T.V.A.}
694 \gdef\vattext      {T.V.A.}
695 \gdef\websitetext  {site Web}
696 \gdef\yourlettertext {Votre lettre du}
697 \gdef\yourreftext  {Vos r\’ef\’erences:}
698 \gdef\date          {\number\day\ifnum\day=1$\{er}\$ \fi \space \ifcase\month\or
699   janvier\or f\’evrier\or mars\or avril\or mai\or juin\or
700   juillet\or ao\’ut\or septembre\or octobre\or
701   novembre\or d\’ecembre\fi \space \number\year}
702 }

```

\isodoc@german

```

703 \def\isodoc@german{%
704   \gdef\accountdatatext {Bezahlungsdaten}
705   \gdef\accountnametext {Name}
706   \gdef\accountnotext   {Konto Nr}
707   \gdef\amounttext      {Betrag}
708   \gdef\ccname           {Kopien an}
709   \gdef\cellphonetext    {Handy}
710   \gdef\chambertext      {Register Nr}
711   \gdef\datetext         {Datum}
712   \gdef\daystext         {Tage}
713   \gdef\descriptiontext  {Umschreibung}
714   \gdef\emailtext       {E-mail}
715   \gdef\enclosurestext   {Anlagen:}
716   \gdef\enclosuretext    {Anlage:}
717   \gdef\faxtext          {Telefax}
718   \gdef\invoicetext      {rechnung}
719   \gdef\oftext           {aus}
720   \gdef\ourreftext       {Unser Zeichen}
721   \gdef\pagetext         {Seite}
722   \gdef\phonetext        {Telefon}
723   \gdef\referencetext    {Beleg Nr}
724   \gdef\routingnotext    {BLZ}
725   \gdef\subjecttext      {Betrifft:}
726   \gdef\termtext         {Zahlungstermin}
727   \gdef\totaltext        {Insgesamt}
728   \gdef\totext           {An}
729   \gdef\vatnotext        {Ustid Nr}
730   \gdef\vattext          {MwSt}
731   \gdef\websitetext      {Webseite}
732   \gdef\yourlettertext   {Ihr Brief vom}
733   \gdef\yourreftext      {Ihr Zeichen}
734   \gdef\date              {\number\day.\space \ifcase\month\or
735   Januar\or Februar\or M"arz\or April\or Mai\or Juni\or
736   Juli\or August\or September\or Oktober\or November\or Dezember\fi
737   \space\number\year}
738 }

```

\isodoc@italian contributed by Walter Giocosio:

```

739 \def\isodoc@italian{%
740   \gdef\accountdatatext {Coordinate bancarie}
741   \gdef\accountnametext {intestato a}
742   \gdef\accountnotext   {n$^o$~del conto}
743   \gdef\amounttext      {Prezzo}
744   \gdef\ccname           {Per conoscenza a:}
745   \gdef\cellphonetext    {cellulare:}
746   \gdef\chambertext      {}
747   \gdef\datetext         {Data:}
748   \gdef\daystext         {giorni}
749   \gdef\descriptiontext  {Descrizione}
750   \gdef\emailtext        {e-mail:}

```

```

751 \gdef\enclosurestext {Allegati:}
752 \gdef\enclosuretext {Allegato:}
753 \gdef\faxtext {fax:}
754 \gdef\invoicetext {fattura}
755 \gdef\oftext {di}
756 \gdef\ourreftext {Nostro riferimento:}
757 \gdef\pagetext {Pagina}
758 \gdef\phonetext {telefono:}
759 \gdef\referencetext {riferimento}
760 \gdef\routingnotext {numero di routing}
761 \gdef\subjecttext {Oggetto:}
762 \gdef\termtext {scadenza}
763 \gdef\totaltext {Totale}
764 \gdef\totext {All'attenzione di:}
765 \gdef\vatnotext {Partita I.V.A.}
766 \gdef\vatttext {I.V.A.}
767 \gdef\websitetext {sito Web:}
768 \gdef\yourlettertext {Vostra lettera del:}
769 \gdef\yourreftext {Vostro riferimento:}
770 \gdef\date {\number\day\ifnum\day=1\fi
771 ~\ifcase\month\or
772 Gennaio\or Febbraio\or Marzo\or Aprile\or Maggio\or Giugno\or
773 Luglio\or Agosto\or Settembre\or Ottobre\or Novembre\or Dicembre\fi
774 \space \number\year}
775 }

```

\isodoc@norsk contributed by Sveinung Heggen:

```

776 \def\isodoc@norsk {%
777 \gdef\accountdatatext {betales til}
778 \gdef\accountnametext {til}
779 \gdef\accountnotext {faktura nr}
780 \gdef\amounttext {Bel\o{}p}
781 \gdef\ccname {kopi til:}
782 \gdef\cellphonetext {mobil}
783 \gdef\chambertext {}
784 \gdef\datetext {Dato}
785 \gdef\daystext {dager}
786 \gdef\descriptiontext {Beskrivelse}
787 \gdef\emailtext {e-post}
788 \gdef\enclosurestext {Vedlegg:}
789 \gdef\enclosuretext {Vedlegg:}
790 \gdef\faxtext {telefaks}
791 \gdef\invoicetext {faktura}
792 \gdef\oftext {av}
793 \gdef\ourreftext {V\aa{}r ref:}
794 \gdef\pagetext {Side}
795 \gdef\phonetext {telefon}
796 \gdef\referencetext {referanse}
797 \gdef\routingnotext {routing-nummer}
798 \gdef\subjecttext {Vedr:}
799 \gdef\termtext {betalingsfrist}
800 \gdef\totaltext {Total}
801 \gdef\totext {Til}
802 \gdef\vatnotext {Org. nr.}
803 \gdef\vatttext {Mva}
804 \gdef\websitetext {hjemmeside}
805 \gdef\yourlettertext {Deres brev av}
806 \gdef\yourreftext {Deres ref:}
807 \gdef\date {\number\day.\space\ifcase\month\or
808 januar\or februar\or mars\or april\or mai\or juni\or
809 juli\or august\or september\or oktober\or november\or desember\fi
810 \space \number\year}
811 }

```

\isodoc@serbian contributed by Zoran T. Filipovic:

```
812 \def\isodoc@serbian {%
813   \gdef\totaltext {Ukupno}
814   \gdef\vattext {PDV}
815   \gdef\accountdatatext {Podaci o bankarskom sektoru}
816   \gdef\accountnametext {na ime}
817   \gdef\accountnotext {Ra\v cun br.}
818   \gdef\amounttext {Iznos}
819   \gdef\ccname {Kopije}
820   \gdef\cellphonetext {Mobilni}
821   \gdef\chambertext {Spisak br.}
822   \gdef\datetext {Datum}
823   \gdef\daystext {dana}
824   \gdef\descriptiontext {Opis}
825   \gdef\emailtext {Email}
826   \gdef\enclosurestext {Prilozi:}
827   \gdef\enclosuretext {Prilog:}
828   \gdef\faxtext {Telefax}
829   \gdef\invoicetext {faktura}
830   \gdef\oftext {od}
831   \gdef\ourreftext {Na\v s broj}
832   \gdef\pagetext {Strana}
833   \gdef\phonetext {Telefon}
834   \gdef\referencetext {Dokument br.}
835   \gdef\routingnotext {BLZ}
836   \gdef\subjecttext {Predmet:}
837   \gdef\termtext {rok pla\' canja}
838   \gdef\totext {U}
839   \gdef\vatnotext {porez br.}
840   \gdef\websitetext {Website}
841   \gdef\yourlettertext {Va\v se pismo od}
842   \gdef\yourreftext {Va\v s broj}
843   \gdef\date{\number\day.\~\ifcase\month\or
844     Januar\or Februar\or Mart\or April\or Maj\or Jun\or
845     Jul\or Avgust\or Septembar\or Oktobar\or Novembar\or Decembar\fi
846     \space\number\year}
847 }
```

\isodoc@spanish contributed by Cristian Peraferrer:

```
848 \def\isodoc@spanish{%
849   \gdef\accountdatatext {Datos bancarios}
850   \gdef\accountnametext {a nombre de}
851   \gdef\accountnotext {N\'um. de cuenta}
852   \gdef\amounttext {Cantidad}
853   \gdef\ccname {cc}
854   \gdef\cellphonetext {M\'ovil}
855   \gdef\chambertext {C\'amara de comercio}
856   \gdef\datetext {Fecha}
857   \gdef\daystext {d\'{i}as}
858   \gdef\descriptiontext {Descripci\'on}
859   \gdef\emailtext {E-mail}
860   \gdef\enclosurestext {Anexos:}
861   \gdef\enclosuretext {Anexo:}
862   \gdef\faxtext {Fax}
863   \gdef\invoicetext {factura}
864   \gdef\oftext {de}
865   \gdef\ourreftext {Nuestra referencia}
866   \gdef\pagetext {P\'agina}
867   \gdef\phonetext {Tel\'efono}
868   \gdef\referencetext {Referencia}
869   \gdef\routingnotext {n\'umero de ruta}
870   \gdef\subjecttext {Asunto}
871   \gdef\termtext {Plazo de pago}
```

```

872 \gdef\totaltext      {Total}
873 \gdef\totext          {A}
874 \gdef\vatnotext       {N\'um. IVA}
875 \gdef\vatttext        {IVA}
876 \gdef\websitetext     {Web}
877 \gdef\yourlettertext  {Su carta de}
878 \gdef\yourreftext     {Su referencia}
879 \gdef\date             {\number\day\space\ifcase\month\or
880     enero\or febrero\or marzo\or abril\or mayo\or junio\or
881     julio\or agosto\or septiembre\or octubre\or noviembre\or diciembre\fi
882     \space \number\year
883 }
884 }
885 % \DescribeMacro{\isodoc@UKenglish}
886 % \begin{macrocode}
887 \def\isodoc@UKenglish{%
888     \gdef\accountdatatext {Banking data}
889     \gdef\accountnametext {in the name of}
890     \gdef\accountnotext   {Account no.}
891     \gdef\amounttext      {Amount}
892     \gdef\ccname          {cc}
893     \gdef\cellphonetext   {cellphone}
894     \gdef\chambertext     {ch.comm.}
895     \gdef\datetext        {Date}
896     \gdef\daystext        {days}
897     \gdef\descriptiontext {Description}
898     \gdef\emailtext       {email}
899     \gdef\enclosurestext  {Enclosures:}
900     \gdef\enclosuretext   {Enclosure:}
901     \gdef\faxtext         {telefax}
902     \gdef\invoicetext     {invoice}
903     \gdef\oftext          {of}
904     \gdef\ourreftext      {Our reference}
905     \gdef\pagetext        {Page}
906     \gdef\phonetext       {telephone}
907     \gdef\referencetext   {Reference}
908     \gdef\routingnotext   {Routing no}
909     \gdef\subjecttext     {Subject:}
910     \gdef\termtext        {term of payment}
911     \gdef\totaltext       {Total}
912     \gdef\totext          {To}
913     \gdef\vatnotext       {vat no.}
914     \gdef\vatttext        {Vat}
915     \gdef\websitetext     {website}
916     \gdef\yourlettertext  {Your letter of}
917     \gdef\yourreftext     {Your reference}
918     \gdef\date{\ifcase\day\or
919         1st\or 2nd\or 3rd\or 4th\or 5th\or
920         6th\or 7th\or 8th\or 9th\or 10th\or
921         11th\or 12th\or 13th\or 14th\or 15th\or
922         16th\or 17th\or 18th\or 19th\or 20th\or
923         21st\or 22nd\or 23rd\or 24th\or 25th\or
924         26th\or 27th\or 28th\or 29th\or 30th\or
925         31st\fi\space\ifcase\month\or
926         January\or February\or March\or April\or May\or June\or
927         July\or August\or September\or October\or November\or December\fi
928         \space \number\year}
929 }

```

\isodoc@USenglish

```

930 \def\isodoc@USenglish{%
931     \gdef\accountdatatext {Bank details}
932     \gdef\accountnametext {in the name of}

```

```

933 \gdef\accountnotext {Account no.}
934 \gdef\amounttext {Amount}
935 \gdef\ccname {cc}
936 \gdef\cellphonetext {cellphone}
937 \gdef\chambertext {ch.comm.}
938 \gdef\datetext {Date}
939 \gdef\daystext {days}
940 \gdef\descriptiontext {Description}
941 \gdef\emailtext {email}
942 \gdef\enclosurestext {Enclosures:}
943 \gdef\enclosuretext {Enclosure:}
944 \gdef\faxtext {telefax}
945 \gdef\invoicetext {invoice}
946 \gdef\oftext {of}
947 \gdef\ourreftext {Our reference}
948 \gdef\pagetext {Page}
949 \gdef\phonetext {telephone}
950 \gdef\referencetext {Reference}
951 \gdef\routingnotext {Routing no}
952 \gdef\subjecttext {Subject:}
953 \gdef\termtext {term of payment}
954 \gdef\totaltext {Total}
955 \gdef\totext {To}
956 \gdef\vatnotext {vat no.}
957 \gdef\vattext {Vat}
958 \gdef\websitetext {website}
959 \gdef\yourlettertext {Your letter of}
960 \gdef\yourreftext {Your reference}
961 \gdef\date {\ifcase\month\or
962   January\or February\or March\or April\or May\or June\or
963   July\or August\or September\or October\or November\or December\fi
964   \space\number\day, \number\year}
965 }

```

Change History

v0.1	General: Initial version 1	text adapted 1
v0.10	General: bug: missing prefixes for phone numbers added option footorder, setting the order of footer fields 1	v0.3 General: several errors in documen- tation corrected 1
v0.2	General: added options phonepre- fix, routingno, logoaddress ac- countname now optional ac- countnumber ⇒ accountno ger- man and french translations corrected indents removed in header fields expect printer to have more unprintable bor- der ascriptiontext ⇒ account- nametext for dutch Interdoc- ument language changes now work; Vatno, if defined, is re- ported with accountdata; coun- try in returnaddress now sepa- rated with dot; option changes kept local to the letter/invoice; English/American accountname	v0.3b General: non-zero parskip gener- ated whitespace in standard textblocks; several accept posi- tions fixed, added option shift, whitespace problems solved, added option currency, added option cityzip - without docu- mentation 1
		v0.4 General: options shift, currency, cityzip added norwegian trans- lations added (thanks Sveinung Heggen) 1
		v0.5 General: text misplacement in subject-less letters corrected norwegian translations cor- rected 1
		v0.6 General: moved all documentation

files in subdirectory doc, because files appeared to be wrongly placed on the TeX Collection DVD Some minor corrections . .	1
v0.7	
General: using eurosym package instead of marvosym; using frenchb package instead of french; added addresswidth option, default stays 2 cols; changes suggested by Fabrice Niessen (thanks): added header/noheader options; added bodyshift option; date format can be yyyy-mm-dd or a literal ‘today’; added force-date option to enter anything	
	for date; added foldleft and foldright options, default stays right; headingcolor, if defined, colors fancy headings; headingcolor, if defined, colors headings in header and footer; foldmarkcolor, if defined, colors foldmark
	1
v0.9	
General: subject text uses full textwidth; use newlines if needed introducing isodocsymbols.sty new option closingcomma subject uses full textwidth new option closingcomma using foreach package for footfields removed some unwanted whitespace . . .	1

Index

Symbols		
\@hft	20, 458, 462, 466, 470, 478, 491	
\@isoarg	235, 236, 241, 243, 246, 254, 257–259	
\@isoday	233, 239	
\@isodigits	254, 255, 257–259	
\@isomakedate	27, 116, 234	
\@isomonth	232, 238	
\@isotoday	235, 236	
\@isoyear	231, 237	
\@xshift	21, 24	
\@xyshift	21, 23	
\@yshift	21, 24	
\^	700	
_	201, 268, 419, 428, 431, 434, 436	
A		
\accept	25, 33, 291, 503, 552	
\acceptaccount	150, 151, 292, 580	
\acceptaddress	152, 153, 293, 564	
\acceptcents	25, 154, 155, 294, 584, 592	
\acceptdesc	25, 158, 159, 295, 560	
\acceptdescription	25, 156, 157, 296, 556	
\accepteuros	25, 160, 161, 297, 576, 588	
\acceptreference	25, 162, 163, 298, 568, 572	
\acceptreferenceskip	174, 572	
\accepttype	147, 503	
\accountdata	9, 28, 264	
\accountdatatext	265, 595, 632, 668, 704, 740, 777, 815, 849, 888, 931	
\accountname	25, 139, 271, 272, 299	
\accountnametext	272, 596, 633, 669, 705, 741, 778, 816, 850, 889, 932	
\accountno	25, 137, 270, 300	
\accountnotext	270, 597, 634, 670, 706, 742, 779, 817, 851, 890, 933	
\addresscenter	22, 60, 61, 301, 441	
\addresswidth	22, 62, 63, 302, 441	
\addtolength	15	
\american	21, 303	
\amounttext	385, 598, 635, 671, 707, 743, 780, 818, 852, 891, 934	
\areacode	23, 88, 89, 304, 411	
\AtEndOfClass	370	
\autograph	9, 24, 26, 179, 305	
\autographA	513	
\autographB	514	
\autographC	515	
\autographD	516	
\autographE	517	
\autographF	518	
\autographG	519	
\autographH	520	
\autographversion	130, 131, 510, 522	
B		
\bic	25, 141, 281, 306	
\bodyshift	22, 307	
C		
\c	601, 626	
\Cbox	33	
\ccname	599, 636, 672, 708, 744, 781, 819, 853, 892, 935	
\cellphone	23, 308, 413	
\cellphonetext	600, 637, 673, 709, 745, 782, 820, 854, 893, 936	
\chamber	25, 143, 144, 309	
\chambertext	601, 638, 674, 710, 746, 783, 821, 855, 894, 937	
\city	21, 48, 49, 201, 310	
\cityzip	21, 311	
\cityzipfalse	29	
\cityziptrue	28	
\ClassError	181, 184, 244, 247, 250, 256, 260, 261	
\ClassWarning	415	
\closing	24, 125, 127, 198, 312, 511, 512	
\closingcomma	126, 511, 512	
\closingfalse	400	
\closingskip	24, 128, 129, 313, 512	
\closingtrue	397	

\color 20, 427, 430, 433, 435, 500	717, 753, 790, 828, 862, 901, 944	718, 754, 791, 829, 863, 902, 945
\company 21, 41, 42, 205, 222, 314	\fill 21, 324	\isodoc@catalan 34, 594
\country 21, 50, 51, 216, 225, 315	\fold 23, 325–327	\isodoc@cellphone 94, 95, 413
\countrycode 21, 52, 53, 56, 316	\fold2 23	\isodoc@dutch 32, 34, 631
\currency 25, 145, 146, 317, 385	\fold3 23	\isodoc@fax 96, 97, 414
	\foldleft 23, 328	\isodoc@french 35, 36, 667
	\foldright 23, 329	\isodoc@german 34, 36, 703
D	\footcount 398, 485, 490, 494	\isodoc@italian 36, 739
\date . . 24, 117, 318, 431, 434, 472, 625, 662, 698, 734, 770, 807, 843, 879, 918, 961	\footer 23, 330	\isodoc@lead . . 411–414
\datetext 470, 602, 639, 675, 711, 747, 784, 822, 856, 895, 938	\footerfalse 86, 87	\isodoc@norsk . . 37, 776
\day 233, 239, 259, 261, 625, 662, 698, 734, 770, 807, 843, 879, 918, 964	\footerpos 79, 490	\isodoc@phone 90, 91, 412
\daystext 268, 603, 640, 676, 712, 748, 785, 823, 857, 896, 939	\footertrue 85	\isodoc@serbian 38, 812
\descriptiontext 384, 604, 641, 677, 713, 749, 786, 824, 858, 897, 940	\footorder 83, 84, 331, 496	\isodoc@spanish 38, 848
\dutch 21, 319	\forcedate 24, 118, 332, 471, 473	\isodoc@UKenglish . . . 33, 417, 885, 887
E	\ForEachX 487	\isodoc@USenglish 35, 39, 930
\email . 23, 100, 101, 320	\foreign 21, 333	\itable 8, 379, 380, 382, 390
\EmailSymbol 9	\foreignfalse 27	\itotal 8, 394, 395
\emailtext 605, 642, 678, 714, 750, 787, 825, 859, 898, 941	\foreigntrue 26	
\enclosures 25, 134, 135, 321, 525, 527, 529	\french 21, 334	
\enclosurestext 528, 606, 643, 679, 715, 751, 788, 826, 860, 899, 942	G	L
\enclosuretext . 528, 607, 644, 680, 716, 752, 789, 827, 861, 900, 943	\gdef 595– 625, 632–662, 668–698, 704– 734, 740–770, 777–807, 813– 843, 849–879, 888–918, 931–961	\label 532
\english 21, 322	\german 21, 335	\language 21, 338
\EUR 9	H	\lccode 187–190
\EUROSymbol 9	\hbox 488	\leftaddress . . . 22, 339
\EuroSymbol 9, 146	\headcolor 20	\letter . . 8, 31, 402, 408
F	\header 22, 336	\LetterSymbol 9
\fax 23, 323, 414	\headerfalse 76	\localbank 21, 340
\faxtext 608, 645, 681,	\headerpos 77, 78, 451, 452, 457, 461, 465, 469	\localbankfalse 31
	\headertrue 74, 75	\localbanktrue 30
	\headheight 15	\logo 9, 27, 202, 439
	\headingcolor 20	\logoaddress . . . 21, 43, 211, 217, 341
	\hypersetup . . 375, 419	\lowercase 191
	I	M
	\i 857	\markercolor 20
	\iban . . 25, 140, 280, 337	\MobileSymbol 9
	\if 244, 247	\month 232, 238, 258, 260, 625, 662, 698, 734, 771, 807, 843, 879, 925, 961
	\ifcityzip 29, 201	\mydown . . . 178, 195, 197
	\ifclosing 397, 509	\myoutdent 176, 193, 196
	\iffooter . . 86, 229, 486	N
	\ifforeign . . 27, 56, 216, 225, 278, 411	\newcounter 396
	\ifheader 75, 455	\newfont 148
	\iflocalbank . . . 31, 279	\newpage 409
	\ifpreamble 16	\nofill 21, 342
	\ifreturn 71, 442	\nofold 23, 343
	\iitem . . 8, 389, 390, 393	\nofooter 23, 344
	\invoice 8, 30, 399	\noheader 22, 345
	\invoicetext . . 403, 609, 646, 682,	\noreturn 22, 346
		O
		\ocrb 148, 568, 572, 576, 580, 584, 588, 592

\oftext ... 428, 436, 610, 647, 683, 719, 755, 792, 830, 864, 903, 946	\stringlength . 241, 255	729, 765, 802, 839, 874, 913, 956
\opening 24, 121, 124, 347, 504	\subject 24, 119, 120, 359, 420, 453, 475, 478	\vattext 621, 658, 694, 730, 766, 803, 814, 875, 914, 957
\openingcomma ... 24, 122, 123, 348, 504	\subjectpos 80, 451, 453, 454, 456, 476	
\openingpos 81, 454, 456, 504	\subjecttext ... 478, 616, 653, 689, 725, 761, 798, 836, 870, 909, 952	W
\ourref 24, 110, 111, 277, 349, 467	\substring 243, 246, 254, 257–259	\wacceptaccount 171, 579
\ourreftext ... 466, 611, 648, 684, 720, 756, 793, 831, 865, 904, 947		\wacceptaddress 173, 563
	T	\wacceptcents . 167, 583
P	\Tbox 33	\wacceptct ... 170, 591
\pagetext . 428, 436, 612, 649, 685, 721, 757, 794, 832, 866, 905, 948	\temp 191, 192	\wacceptdesc .. 172, 559
\phone 23, 350, 412	\term 25, 136, 267, 268, 360	\wacceptdescription 164, 555
\phoneprefix 23, 92, 93, 351, 411	\termtext 268, 617, 654, 690, 726, 762, 799, 837, 871, 910, 953	\waccepteur .. 169, 587
\PhoneSymbol 9	\textblockorigin ... 24	\waccepteuross . 166, 575
\phonetext 613, 650, 686, 722, 758, 795, 833, 867, 906, 949	\textsf 205	\wacceptref .. 165, 571
\preamblefalse 17	\textskip 82, 452, 453, 483, 505	\wacceptreference 168, 567
\preambletrue 16	\thelettercount 429, 437, 532	\wd 489
\prezip 56, 201	\theresult 242, 250, 256	\website . 23, 98, 99, 363
\processto 64, 66	\thestring 244, 245, 247, 248, 254, 257–259	\websitetext 622, 659, 695, 731, 767, 804, 840, 876, 915, 958
	\thislevelitem 488, 491, 492	\who 21, 44, 45, 213, 364, 375
R	\to 22, 361	X
\referencetext . 277, 614, 651, 687, 723, 759, 796, 834, 868, 907, 950	\toaddress 65, 66, 68, 69, 448, 564	\xacceptaccount 171, 577
\return 22, 352	\today 419	\xacceptaddress 173, 561
\returnaddress 22, 27, 73, 220, 353, 444	\toname . 64, 68, 419, 431, 434, 448, 564	\xacceptcents . 167, 581
\returnfalse 71, 72	\totaltext 395, 618, 655, 691, 727, 763, 800, 813, 872, 911, 954	\xacceptct ... 170, 589
\returntrue 70	\totext ... 431, 434, 619, 656, 692, 728, 764, 801, 838, 873, 912, 955	\xacceptdesc .. 172, 557
\rightaddress .. 22, 354	\Treatments 253	\xacceptdescription 164, 553
\routingno 25, 138, 274, 275, 355	U	\xaccepteur .. 169, 585
\routingnotext . 275, 615, 652, 688, 724, 760, 797, 835, 869, 908, 951	\Undefined 19, 42, 45, 47, 49, 51, 53, 55, 65, 89, 117, 124, 127, 133, 472, 522	\xaccepteuross . 166, 573
S		\xacceptref .. 165, 569
\setupdocument 7, 27, 227	V	\xacceptreference 168, 565
\shift 20, 356	\v ... 817, 831, 841, 842	\xaddress .. 57–59, 441
\showkeys ... 7, 28, 289	\value 418	\xfold 104–106, 499
\signature 24, 132, 133, 198, 357, 511, 512	\vatno 25, 142, 284, 285, 362	\xproc 66, 68
\signskip . 177, 194, 198	\vatnotext 285, 620, 657, 693,	
\street 21, 46, 47, 214, 223, 358		Y
		\yacceptaccount 171, 578
		\yacceptaddress 173, 562
		\yacceptcents . 167, 582
		\yacceptct ... 170, 590
		\yacceptdesc .. 172, 558
		\yacceptdescription 164, 554
		\yaccepteur .. 169, 586
		\yaccepteuross . 166, 574
		\yacceptref .. 165, 570
		\yacceptreference 168, 566
		\year 231, 237, 257, 372, 472, 628, 665, 701, 737, 774, 810, 846, 882, 928, 964

\yfold 102,	732, 768, 805,	842, 878, 917, 960
103, 107–109, 499	841, 877, 916, 959	\yproc 67, 69
\yourletter 24,	\yourref 24,	
114, 115, 365, 459	112, 113, 366, 463	
\yourlettertext . . .	\yourreftext . . . 462,	Z
. . . . 415, 458,	624, 661, 697,	\zip . 21, 54, 55, 201, 367
623, 660, 696,	733, 769, 806,	\zippedcity 201, 215, 224