

Image Classification as Pure Sequence Modeling with Traced Polygons

Anonymous CVPR submission

Paper ID *****

Abstract

Image classification can be cast into a pure sequence classification problem from a vector graphics point of view. Traditional raster image is a multi-dimensional array, and can be traced into vector graphics, representing images in a sequence of paths directly presenting the shape information and resembling human strokes. Namely, the vector graphics can be a sequence (contains a variable number of paths) of sequences (each path is a variable-length sequence of x - y coordinates). To classify such nested sequences, we present Hierarchical Path Sequence Transformer (HPST). Specifically, the first level of sequence model computes the representation of a single path with its fill color, while the second level of sequence model aggregates all path representations for an image and yields the logits. The proposed method is evaluated on six commonly used datasets, including MNIST, Fashion-MNIST, CIFAR-10, CIFAR-100, Tiny-ImageNet, as well as ImageNet-1k. Extensive experimental results demonstrate the effectiveness of image classification as a pure sequence classification problem. [TODO] characteristics. Ultimately, we assert that raster image is not the sole starting point for computer vision problems. This is expected to be beneficial to adversarial defense.

1. Introduction

Nobody has done this. But this is a more natural way to represent images in a sequence. And such sequence is approximate to human strokes.

This will be novel enough as long as it works reasonably for MNIST, CIFAR-10, CIFAR-100, Tiny-ImageNet, and ImageNet.

Reference: Image Vectorization: LIVE [1,2]

In raster images representing textures as the first-order information, the shapes as edges are stored as high-order information (computed from the difference). In contrast, in a vector image, both shape and texture are presented meanwhile as the first-order information. Namely, the polygon paths are directly shape information, while a combination of a series of polygons in different colors form a texture




Figure 1. Demonstration

(although the texture may become coarse-grained if we want to limit the number of paths).

2. Raster Graphics Vectorization

Raster Graphics.

Raster Image Standard: PBM, BMP, JPEG, HEIF, etc.

Vector Graphics.

Vector Graphics standards: SVG.

Vector Image Rasterization.

Raster Image Vectorization. Bitmap Tracing (approximation)
related: Primal sketches
stochastic grammar, songchun zhu, and/or graph

3. Our Approach

(preliminary design)
hierarchical transformer.
path transformer for path representation. input is paths,
sequence of points. init vector is color.
image transformer for image representation. input is sequence of paths.

4. Experiments

4.1. Discussion on Vectorization Methods

(1) inkscape bitmap trace is very basic. It leverages some traditional edge information from the image but the edges are not well separated among objects.

(2) vtracer performs perfectly on MNIST, but for complicated images, it creates too many paths. For instance, a daisy image from ImageNet leads to more than 1000 paths. Training with such long nested sequences is expectedly very difficult.

(3) LIVE [2] image vectorization.

(4) DiffVG [1] painterly rendering?

4.2. Classification Performance

GRU and HGRU works for both mnist and cifar

Dataset	Model	Accuracy	Parameters
=====			
MNIST	LeNet	98.9	431k

MNIST	RNN	96.43	34k
..	GRU	97.31	84k
..	LSTM	96.89	109k
..	PST	97.30	211k

MNIST	HRNN	96.66	59k
..	HGRU	98.00	159k
..	HLSTM	97.24	209k
..	HPST	98.17	412k

FashionMNIST	LeNet	88.9	431k

FashionMNIST	RNN	65.97	34k
..	GRU	72.88	84k
..	LSTM	72.08	109k
..	PST	72.19	412k

FashionMNIST	HRNN	78.66	59k
..	HGRU	83.96	159k

..	HLSTM	82.79	209k	
..	HPST	85.57	412k	

CIFAR10	ResNet18		11.6m	

CIFAR10	HRNN		59k	
..	HGRU	55.21	159k	
..	HLSTM		209k	
..	HPST	68.78	412k	
=====				
CIFAR10	(DDP 8 : RTX A6000)			
	HRNN	33.08	59k	
	HGRU	37.73	159k	
	HGRU	43.24	828k (hidden_size=1024)	
	HLSTM	31.82	209k	
	HPST	53.06	412k	
	HPST		1.6m (hidden_size=1024)	
=====				

References

- [1] Tzu-Mao Li, Michal Lukáč, Gharbi Michaël, and Jonathan Ragan-Kelley. Differentiable vector graphics rasterization for editing and learning. *ACM Trans. Graph. (Proc. SIGGRAPH Asia)*, 39(6):193:1–193:15, 2020. 1, 2
- [2] Xu Ma, Yuqian Zhou, Xingqian Xu, Bin Sun, Valerii Filev, Nikita Orlov, Yun Fu, and Humphrey Shi. Towards layer-wise image vectorization. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2022. 1, 2