EUROCONTROL

cat019 category specification

Release 2010-12-01, 1.3

Multilateration System Status Messages

2010-12-01

CONTENTS:

category: 019

edition: 1.3

date: 2010-12-01

PREAMBLE

Surveillance data exchange.

DESCRIPTION OF STANDARD DATA ITEMS

2.1 I019/000 - Message Type

Definition: This Data Item allows for a more convenient handling of the messages at the receiver side by further defining the type of information.

Structure:

- 8 bits [. . . . .]
- values:

> 1: Start of Update Cycle
> 2: Periodic Status Message
> 3: Event-triggered Status Message

NOTES:

1. In applications where data of various types is exchanged, the Message Type Data Item facilitates the proper message handling at the receiver side.

2. All Message Type values are reserved for common standard use.

2.2 I019/010 - Data Source Identifier

Definition: Identification of the system from which the data is received.

Structure:

SAC - *System Area Code*

- 8 bits [. . . . .]
- raw value

SIC - *System Identification code*

- 8 bits [. . . . .]
- raw value

Note:

- The up-to-date list of SACs is published on the EUROCONTROL Web Site (http://www.eurocontrol.int/asterix).

2.3 I019/140 - Time of Day

Definition: Absolute time stamping expressed as UTC.

Structure:

- 24 bits [. . . . .]
- unsigned quantity
- scaling factor: 1
- fractional bits: 7
- unit: "s"
- LSB = $1/2^7$ s = $1/128$ s ≈ 0.0078125 s

Note:

> The time of day value is reset to zero each day at midnight.

2.4 I019/550 - System Status

Definition: Information concerning the configuration and status of a System.

Structure:

NOGO - *Operational Release Status of the System*

- 2 bits [. .]
- values:

> 0: Operational
> 1: Degraded
> 2: NOGO
> 3: undefined

OVL - *Overload indicator*

- 1 bit [.]
- values:

> 0: No overload
> 1: Overload

TSV - *Time Source Validity*

- 1 bit [.]
- values:

> 0: valid
> 1: invalid

TTF - *Test Target*

- 1 bit [.]
- values:

> 0: Test Target Operative
> 1: Test Target Failure

(spare)

- 3 bits [...]

Note:

A time source is considered as valid when either externally synchronised or running on a local oscillator within the required accuracy of UTC.

2.5 I019/551 - Tracking Processor Detailed Status

Definition: Information concerning the configuration and status of the Tracking processors.

Structure:

TP1A

- 1 bit [.]
- values:

   0: Standby
   1: Exec

TP1B

- 1 bit [.]
- values:

   0: Faulted
   1: Good

TP2A

- 1 bit [.]
- values:

   0: Standby
   1: Exec

TP2B

- 1 bit [.]
- values:

   0: Faulted
   1: Good

TP3A

- 1 bit [.]
- values:

   0: Standby
   1: Exec

TP3B

- 1 bit [.]
- values:

   0: Faulted
   1: Good

TP4A

- 1 bit [.]
- values:

    0: Standby
    1: Exec

TP4B

- 1 bit [.]
- values:

    0: Faulted
    1: Good

Note:

Both Bits of one TP set to zero means, that this TP is not used in the system.

2.6 I019/552 - Remote Sensor Detailed Status

Definition: Information concerning the configuration and status of the Remote Sensors (RS)

Structure:

Repetitive item, repetition factor 8 bits.

RSI - *8-bit Identification number of RS*

- 8 bits [........]
- raw value

(spare)

- 1 bit [.]

RS1090 - *Receiver 1090 MHz*

- 1 bit [.]
- values:

    0: Not present
    1: present

TX1030 - *Transmitter 1030 MHz*

- 1 bit [.]
- values:

    0: Not present
    1: present

TX1090 - *Transmitter 1090 MHz*

- 1 bit [.]
- values:

    0: Not present
    1: present

RSS - *RS Status*

- 1 bit [.]

- values:

    0: Faulted
    1: Good

RSO - *RS Operational*

- 1 bit [.]

- values:

    0: Offline
    1: Online

(spare)

- 2 bits [..]

2.7 I019/553 - Reference Transponder Detailed Status

Definition: Information concerning the configuration and status of the Reference Transponder.

Structure:

Extended item with first part 8 bits long and optional 8 bits extends.

REFTr1 - *Ref Trans 1 Status*

- 2 bits [..]

- values:

    1: Warning
    2: Faulted
    3: Good

(spare)

- 2 bits [..]

REFTr2 - *Ref Trans 2 Status*

- 2 bits [..]

- values:

    1: Warning
    2: Faulted
    3: Good

(spare)

- 1 bit [.]

(FX)

- extension bit

    0: End of data item
    1: Extension into next extent

REFTr3 - *Ref Trans 3 Status*

- 2 bits [..]

- values:

    1: Warning

      2: Faulted

      3: Good

`(spare)`

- 2 bits [. .]

REFTr4 - *Ref Trans 4 Status*

- 2 bits [. .]

- values:

      1: Warning

      2: Faulted

      3: Good

`(spare)`

- 1 bit [.]

`(FX)`

- extension bit

      0: End of data item

      1: Extension into next extent

2.8 I019/600 - Position of the MLT System Reference Point

Definition: Position of the MLT reference point in WGS-84 Coordinates.

Structure:

LAT - *Latitude*

- 32 bits [. . . .]

- signed quantity

- scaling factor: 180

- fractional bits: 30

- unit: "deg"

- LSB = $180/2^{30}$ deg = $180/1073741824$ deg $\approx 1.6763806343078613e - 07$ deg

- value $>= -90$ deg

- value $<= 90$ deg

LON - *Longitude*

- 32 bits [. . . .]

- signed quantity

- scaling factor: 180

- fractional bits: 30

- unit: "deg"

- LSB = $180/2^{30}$ deg = $180/1073741824$ deg $\approx 1.6763806343078613e - 07$ deg

- value $>= -180$ deg

- value < 180 deg

2.9 I019/610 - Height of the MLT System Reference Point

Definition: Height of the MLT system reference point in two's complement form. The height shall use mean sea level as the zero reference level.

Structure:

- 16 bits [. . . . .]
- signed quantity
- scaling factor: 1
- fractional bits: 2
- unit: "m"
- LSB = $1/2^2$ m = $1/4$ m ≈ 0.25 m
- value $>= -8192$ m
- value $<= 8192$ m

2.10 I019/620 - WGS-84 Undulation

Definition: WGS-84 undulation value of the MLT system reference point, in meters. Geoid undulation value is the difference between the ellipsoidal height and the height above mean sea level

Structure:

- 8 bits [. . . . .]
- signed quantity
- scaling factor: 1
- fractional bits: 0
- unit: "m"
- LSB = 1 m

2.11 I019/RE - Reserved Expansion Field

Definition: Expansion

Structure:

Explicit item

2.12 I019/SP - Special Purpose Field

Definition: Special Purpose Field

Structure:

Explicit item

USER APPLICATION PROFILE FOR CATEGORY 019

- (1) `I019/010` - Data Source Identifier
- (2) `I019/000` - Message Type
- (3) `I019/140` - Time of Day
- (4) `I019/550` - System Status
- (5) `I019/551` - Tracking Processor Detailed Status
- (6) `I019/552` - Remote Sensor Detailed Status
- (7) `I019/553` - Reference Transponder Detailed Status
- `(FX)` - Field extension indicator
- (8) `I019/600` - Position of the MLT System Reference Point
- (9) `I019/610` - Height of the MLT System Reference Point
- (10) `I019/620` - WGS-84 Undulation
- (11) `(spare)`
- (12) `(spare)`
- (13) `I019/RE` - Reserved Expansion Field
- (14) `I019/SP` - Special Purpose Field
- `(FX)` - Field extension indicator

INDICES AND TABLES

- genindex
- modindex
- search