TRUST Reference Manual V1.9.6

Support team: trust@cea.fr

May 26, 2025

Contents

1	Syntax to define a mathematical function	16
2	Existing & predefined fields names	17
3	interprete	19
	3.1 Create_domain_from_sub_domain	20
	3.2 Write med	20
	3.3 Link_cgns_files	21
	3.4 Merge_med	
	3.5 Multiplefiles	
	3.6 Op_conv_ef_stab_polymac_face	
	3.7 Op_conv_ef_stab_polymac_p0p1nc_elem	
	3.8 Op_conv_ef_stab_polymac_p0p1nc_face	
	3.9 Op_conv_ef_stab_polymac_p0_face	
	3.10 Option_cgns	
	3.11 Option_dg	23
	3.12 Option_ijk	
	3.13 Option_interpolation	
	3.14 Option_polymac	24
	3.15 Parallel_io_parameters	24
	3.16 Raffiner_isotrope_parallele	25
	3.17 Read med	25
	3.18 Test_sse_kernels	26
	3.19 Analyse_angle	27
	3.20 Associate	27
	3.21 Axi	27
		27
	3.22 Bidim_axi	28
	3.23 Calculer_moments	28
	3.24 Lecture_bloc_moment_base	28
	3.24.1 Calcul	
	3.24.2 Centre_de_gravite	28
	3.24.3 Un_point	28
	3.25 Corriger_frontiere_periodique	29
	3.26 Criteres_convergence	
	3.27 Debog	
	3.28 {	
	3.29 Decoupebord_pour_rayonnement	
	3.30 Decouper_bord_coincident	31
	3.31 Dilate	31
	3.32 Dimension	32
	3.33 Disable_tu	32
	3.34 Discretiser_domaine	32
	3.35 Discretize	32
	3.36 Distance_paroi	
	3.37 Ecrire_champ_med	
	3.38 Ecrire_fichier_formatte	
	3.39 Ecrire_fichier_xyz_valeur	33
	3.40 Ecriturelecturespecial	34
	3.41 Espece	34
	3.42 Execute_parallel	35
	3.43 Export	35
	3.44 Extract 2d from 3d	35

3.45		35
3.46	Extraire_domaine	36
3.47	Extraire_plan	36
3.48	Extraire_surface	37
3.49	Extrudebord	38
3.50	Extrudeparoi	38
3.51	Extruder	39
3.52	Troisf	39
3.53	Extruder_en20	40
3.54	Extruder_en3	40
3.55	Facsec_expert	40
		41
	,	41
3.58	Imprimer_flux	42
3.59	Bloc_lecture	42
	3.59.1 Bloc_criteres_convergence	42
	3.59.2 Solveur_petsc_option_cli	42
3.60	Imprimer_flux_sum	43
3.61	Integrer_champ_med	43
3.62	Interprete_geometrique_base	43
3.63	Lata_to_cgns	44
3.64	Format_lata_to_cgns	44
3.65	Lata_2_med	44
		44
3.67	Lata_2_other	45
		45
3.69	Lml_2_lata	45
		46
		46
	3.71.1 Mailler_base	46
	3.71.2 Pave	46
	3.71.3 Bloc_pave	46
		48
	3.71.5 Bord_base	48
		48
		48
		48
		49
		49
	3.71.11 Bord	50
	3.71.12 Epsilon	50
	3.71.13 Domain	50
3.72	Maillerparallel	50
	Mass_source	51
	Mkdir	52
	Modif_bord_to_raccord	52
	Modifydomaineaxi1d	52
	Moyenne_volumique	53
	Multigrid_solver	54
	Coarsen_operators	55
	3.79.1 Coarsen_operator_uniform	55
3.80	Nettoiepasnoeuds	55
	Option_vdf	55
	Orientefacesbord	56

3.83 Partition	56
3.84 Bloc_decouper	56
3.85 Partition_multi	58
3.86 Pilote_icoco	58
3.87 Polyedriser	58
3.88 Postraiter_domaine	59
3.89 Precisiongeom	59
3.90 Raffiner_anisotrope	60
3.91 Raffiner_isotrope	60
3.92 Read	61
3.93 Read_file	62
3.94 Read_file_binary	62
	62
	63
3.97 Orienter_simplexes	63
3.98 Redresser_hexaedres_vdf	63
	63
	64
	64
	64
	65
	65
	65
$=$ \mathcal{C}	66
	66
	66
	67
	67
	67
	67
	68
11 -	68
-	68
	68
	69
	69
$=$ 1 $^{\circ}$	69
3.120Tetraedriser_homogene	70
3.121Tetraedriser_homogene_compact	70
3.122Tetraedriser_homogene_fin	71
3.123Tetraedriser_par_prisme	72
3.124Transformer	73
3.125Trianguler	73
3.126Trianguler_fin	73
3.127Trianguler_h	74
3.128Verifier_qualite_raffinements	74
3.129 Vect_nom	75
3.130Verifier_simplexes	75
3.131 Verifiercoin	75
3.132 Verifiercoin_bloc	75
	76
3.133Ecrire	76
	/ 1 1

4	pb_g	gen_base 76
	4.1	Pb_conduction
	4.2	Corps_postraitement
		4.2.1 Definition_champs
		4.2.2 Definition_champ
		4.2.3 Definition_champs_fichier
		4.2.4 Sondes
		4.2.5 Sonde
		4.2.6 Sonde_base
		4.2.7 Points
		4.2.8 Listpoints
		4.2.9 Point
		4.2.10 Segmentpoints
		4.2.11 Segment
		4.2.12 Segmentfacesx
		4.2.13 Segmentfacesy
		4.2.14 Segmentfacesz
		4.2.15 Radius
		4.2.16 Numero_elem_sur_maitre
		4.2.17 Position_like
		4.2.17 Position_fixe
		4.2.21 Circle_3
		4.2.22 Sondes_fichier
		4.2.23 Champs_posts
		4.2.24 Champs_a_post
		4.2.25 Champ_a_post
		4.2.26 Champs_posts_fichier
		4.2.27 Bloc_fichier
		4.2.28 Stats_posts
		4.2.29 List_stat_post
		4.2.30 Stat_post_deriv
		4.2.31 T_deb
		4.2.32 T_fin
		4.2.33 Moyenne
		4.2.34 Ecart_type
		4.2.35 Correlation
		4.2.36 Stats_posts_fichier
		4.2.37 Stats_serie_posts
		4.2.38 Stats_serie_posts_fichier
	4.3	Post_processings
		4.3.1 Un_postraitement
	4.4	Liste_post_ok
		4.4.1 Nom_postraitement
		4.4.2 Postraitement_base
		4.4.3 Post_processing
	4.5	Liste_post
		4.5.1 Un_postraitement_spec
		4.5.2 Type_un_post
		4.5.3 Type_postraitement_ft_lata
	4.6	Format_file_base
		4.6.1 Binaire
		4.6.2 Formatte 94

	4.6.3 Xyz
	4.6.4 Single_hdf
	4.6.5 Pdi
	4.6.6 Pdi_expert
4.7	Pb_conduction_ibm
4.8	Pb_hydraulique_cloned_concentration
4.9	Pb_hydraulique_cloned_concentration_turbulent
4.10	Pb_hydraulique_ibm_turbulent
4.11	Pb_hydraulique_list_concentration
4.12	Listeqn
	Pb_hydraulique_list_concentration_turbulent
	Pb_multiphase
	Pb_multiphase_h
	Pb_hem
	Pb_thermohydraulique_cloned_concentration
	Pb_thermohydraulique_cloned_concentration_turbulent
	Pb_thermohydraulique_ibm_turbulent
	Pb_thermohydraulique_list_concentration
	Pb_thermohydraulique_list_concentration_turbulent
	Pb_base
	Probleme_couple
	Pb_avec_passif
	Pb_hydraulique
	Pb_hydraulique_concentration
	Pb_hydraulique_concentration_scalaires_passifs
	Pb_hydraulique_concentration_turbulent
	Pb_hydraulique_concentration_turbulent_scalaires_passifs
	Pb_hydraulique_ibm
	Pb_hydraulique_melange_binaire_qc
	Pb_hydraulique_melange_binaire_wc
	Pb_hydraulique_melange_binaire_turbulent_qc
	Pb_hydraulique_turbulent
	Pb_post
	Pb_thermohydraulique
4.39	Pb_thermohydraulique_qc
4.40	Pb_thermohydraulique_wc
4.41	Pb_thermohydraulique_concentration
4.42	Pb_thermohydraulique_concentration_scalaires_passifs
4.43	Pb_thermohydraulique_concentration_turbulent
	Pb_thermohydraulique_concentration_turbulent_scalaires_passifs
	Pb_thermohydraulique_especes_qc
	Pb_thermohydraulique_especes_wc
	Pb_thermohydraulique_especes_turbulent_qc
	Pb_thermohydraulique_ibm
	Pb_thermohydraulique_scalaires_passifs
	Pb_thermohydraulique_turbulent
	Pb_thermohydraulique_turbulent_qc
	Pb_thermohydraulique_turbulent_scalaires_passifs
	Pbc_med
	List_info_med
∓. J+	4.54.1 Info_med
1 55	Problem read generic
+.33	11001cm 1cau generic

5	mor	ean 15	52.
	5.1	Conduction	
	5.2	Bloc convection	
	3.2	5.2.1 Convection deriv	
		5.2.2 Ale	-
		5.2.3 Muscl_old	
		5.2.4 Muscl3	
		5.2.7 Di_12	
		5.2.8 Amont_old	
		5.2.9 Generic	
		5.2.10 Ef_stab	
		5.2.11 Listsous_zone_valeur	
		5.2.12 Sous_zone_valeur	
		5.2.13 Kquick	
		5.2.14 Muscl	57
		5.2.15 Muscl_new	
		5.2.16 Quick	57
		5.2.17 Centre_old	57
		5.2.18 Negligeable	58
		5.2.19 Amont	58
		5.2.20 Centre	58
		5.2.21 Centre4	58
		5.2.22 Btd	58
		5.2.23 Supg	59
	5.3	Bloc_diffusion	59
		5.3.1 Diffusion_deriv	59
		5.3.2 Turbulente	59
		5.3.3 Type_diffusion_turbulente_multiphase_deriv	
		5.3.4 Interfacial_area	
		5.3.5 Wale	50
		5.3.6 L_melange	
		5.3.7 Smago	
		5.3.8 Prandtl	
		5.3.9 Sgdh	
		5.3.10 Stab	
		5.3.11 Standard	
		5.3.12 Bloc_diffusion_standard	
		5.3.13 Plncplb	
		5.3.14 P1b	
		5.3.15 Negligeable	
		5.3.16 Option	
	<i>-</i> 1	5.3.17 Op_implicite	
	5.4	Condlims	
		5.4.1 Condlimlu	
	5.5	Condinits	-
	,	5.5.1 Condinit	-
	5.6	Sources	
	5.7	Parametre_equation_base	-
		5.7.1 Parametre_implicite	
		5.7.2 Parametre_diffusion_implicite	
	5.8	Conduction_ibm	
	59	Convection diffusion espece binaire turbulent ac	57

	aine_base	213
J.44	INAVIET_STOKES_UITOUTETIL_qc	Z11
	Navier_stokes_turbulent_qc	
	Navier_stokes_turbulent	
5.42	Navier_stokes_standard	
	5.41.8 Null	
	5.41.7 Mod_turb_hyd_rans	
	5.41.6 Longueur_melange	
	5.41.5 Sous_maille_wale	
	5.41.4 Sous_maille_smago	
	5.41.3 Form_a_nb_points	
	5.41.2 Mod_turb_hyd_ss_maille	
	5.41.1 Dt_impr_ustar_mean_only	
	Modele_turbulence_hyd_deriv	
	Navier_stokes_ibm_turbulent	
5.39	Navier_stokes_ibm	196
	Navier_stokes_wc	
	Floatfloat	
	5.36.7 Thi	
	5.36.6 Ec	
	5.36.5 Chmoy_faceperio	
	5.36.4 Canal	
	5.36.3 Temperature	
	5.36.2 Profils_thermo	
	5.36.1 Traitement_particulier_base	
5.36	Traitement_particulier	
	Deuxmots	
	Navier_stokes_qc	
	Eqn_base	
	Convection_diffusion_temperature_turbulent	
	Convection_diffusion_temperature_ibm_turbulent	
	Convection_diffusion_temperature_ibm	
5.3 2	5.29.1 Penalisation_12_ftd_lec	
5.29	Pp	
	Convection_diffusion_temperature	
	Convection_diffusion_espece_multi_turbulent_qc	
	Convection_diffusion_espece_multi_wc	
	Convection_diffusion_espece_multi_qc	
	Convection_diffusion_espece_binaire_wc	
	Convection_diffusion_espece_binaire_qc	
	Convection_diffusion_concentration_turbulent	
	Convection_diffusion_concentration	
	Convection_diffusion_chaleur_turbulent_qc	
	Convection_diffusion_chaleur_wc	
	Convection_diffusion_chalcum_uva	
	Taux_dissipation_turbulent	
	Qdm_multiphase	
	Masse_multiphase	
	Energie_cinetique_turbulente_wit	
	Energie_cinetique_turbulente	
	Energie_multiphase_h	
	Energie_multiphase	
	Echelle_temporelle_turbulente	
7.10		1.00

7	inter	rface_base	213
	7.1	Interface_sigma_constant	214
	7.2	Saturation_base	214
	7.3	Saturation_constant	214
	7.4	Saturation_sodium	
8	/ *		215
	8.1	/*	215
9	chan	np_generique_base	216
	9.1	Champ_post_de_champs_post	
	9.1	Listchamp_generique	
	9.3	List_nom_virgule	
	9.4	Champ_post_operateur_base	
	9.5	Champ_post_operateur_eqn	
	9.6	Champ_post_statistiques_base	
	9.7	Correlation	
	9.8	Champ_post_operateur_divergence	
	9.9	Ecart_type	
	9.10	Champ_post_extraction	220
	9.11	Champ_post_operateur_gradient	221
	9.12	Interpolation	221
	9.13	Champ_post_morceau_equation	222
		Moyenne	
	9.15	Predefini	224
		Champ_post_reduction_0d	
		Champ_post_refchamp	
		Champ_post_tparoi_vef	
		Champ_post_transformation	
		1-1 -	
10	chim		227
	10.1	Reactions	
		10.1.1 Reaction	227
11	class	s_generic	228
11		Amg	
		Amgx	
		Cholesky	
			229
		-	229
		-	230
		-	230
		1—	230
	11.9	Gen	231
	11.10	OGmres	232
	11.13	1Optimal	232
	11.12	2Petsc	233
			233
		C1	233
		5Gcp	
		•	234
			- *
12			235
	12.1	#	235

13	condlim_base	235
	13.1 Echange_couplage_thermique	235
	13.2 Paroi_echange_interne_global_impose	235
	13.3 Paroi_echange_interne_global_parfait	236
	13.4 Paroi_echange_interne_impose	236
	13.5 Paroi_echange_interne_parfait	236
	13.6 Neumann_homogene	236
	13.7 Neumann_paroi	237
	13.8 Neumann_paroi_adiabatique	237
	13.9 Paroi	237
	13.10Dirichlet	
	13.11Paroi_echange_externe_radiatif	
	13.12Entree_temperature_imposee_h	
	13.13Frontiere_ouverte	
	13.14Frontiere_ouverte_alpha_impose	
	13.15Frontiere_ouverte_concentration_imposee	
	13.16Frontiere_ouverte_fraction_massique_imposee	
	13.17Frontiere_ouverte_gradient_pression_impose	
	13.18Frontiere_ouverte_gradient_pression_impose_vefprep1b	
	13.19Frontiere_ouverte_gradient_pression_libre_vef	
	13.20Frontiere_ouverte_gradient_pression_libre_vefprep1b	
	13.21Frontiere_ouverte_pression_imposee	
	13.22Frontiere_ouverte_pression_imposee_orlansky	
	13.23Frontiere_ouverte_pression_moyenne_imposee	
	13.24Frontiere_ouverte_rho_u_impose	
	13.25Frontiere_ouverte_enthalpie_imposee	
	13.26Frontiere_ouverte_vitesse_imposee	
	13.27Frontiere_ouverte_vitesse_imposee_sortie	
	13.28Neumann	
	13.29Paroi_adiabatique	
	13.30Paroi_contact	
	13.31Paroi_contact_fictif	
	13.32Paroi_decalee_robin	
	13.33Paroi_defilante	
	13.34Paroi_echange_contact_correlation_vdf	
	13.35Paroi_echange_contact_correlation_vef	
	13.36Paroi_echange_contact_vdf	
	13.37Paroi_echange_externe_impose	
	13.38Paroi_echange_externe_impose_h	
	13.39Paroi_echange_global_impose	247
	13.40Paroi_fixe	247
	13.41Paroi_fixe_iso_genepi2_sans_contribution_aux_vitesses_sommets	247
	13.42Paroi_flux_impose	248
	13.43Paroi_knudsen_non_negligeable	248
	13.44Paroi_temperature_imposee	248
	13.45Periodique	249
	13.46Scalaire_impose_paroi	249
	13.47Sortie_libre_temperature_imposee_h	249
	13.48Symetrie	249
	13.49Enthalpie_imposee_paroi	249

14	discretisation_base	250
	14.1 Dg	250
	14.2 Ef_axi	250
	14.3 Ef	250
	14.4 Ijk	250
	14.5 Polymac	251
	14.6 Polymac_p0p1nc	251
	14.7 Polymac_p0	
	14.8 Vdf	251
	14.9 Vef	
15	domaine	252
	15.1 Domaineaxi1d	
	15.2 Ijk_grid_geometry	252
1.		252
16	champ_base	253
	16.1 Champ_base	
	16.2 Champ_fonc_interp	
	16.3 Champ_fonc_med_table_temps	
	16.4 Champ_fonc_med_tabule	
	16.5 Champ_tabule_morceaux	
	16.6 Champ_fonc_tabule_morceaux_interp	
	16.7 Champ_parametrique	
	16.8 Champ_composite	
	16.9 Champ_don_base	
	16.10Champ_don_lu	
	16.11Champ_fonc_fonction	257
	16.12Champ_fonc_fonction_txyz	257
	16.13Champ_fonc_fonction_txyz_morceaux	258
	16.14Champ_fonc_med	258
	16.15Champ_fonc_reprise	259
	16.16Fonction_champ_reprise	259
	16.17Champ_fonc_t	260
	16.18Champ_fonc_tabule	260
	16.19Champ_init_canal_sinal	260
	16.20Bloc_lec_champ_init_canal_sinal	
	16.21Champ_input_base	
	16.22Champ_input_p0	262
	16.23Champ_input_p0_composite	
	16.24Champ_musig	
	16.25Champ_ostwald	
	16.26Champ_som_lu_vdf	
	16.27Champ_som_lu_vef	
	16.28Champ_tabule_lu	
	16.29Champ_tabule_temps	
	16.30Champ_uniforme_morceaux	
	16.31Champ_uniforme_morceaux_tabule_temps	
	16.32Champ_fonc_txyz	
	16.33Champ_fonc_xyz	
	16.34Init_par_partie	
	16.35Tayl_green	
	16.36Uniform_field	
	16.37 Valeur_totale_sur_volume	
	10.5/ *aicai_totaic_sai_voiaiic	207

17	champ_front_base	267
	17.1 Champ_front_base	
	17.2 Champ_front_xyz_tabule	
	17.3 Champ_front_parametrique	
	17.4 Champ_front_debit_qc_vdf	
	$17.5 \ Champ_front_debit_qc_vdf_fonc_t \ \dots $	
	17.6 Boundary_field_inward	
	17.7 Ch_front_input	
	17.8 Ch_front_input_uniforme	
	17.9 Champ_front_med	
	17.10Champ_front_bruite	
	17.11Champ_front_calc	
	17.12Champ_front_composite	
	17.13Champ_front_contact_vef	
	17.14Champ_front_debit	
	17.15Champ_front_debit_massique	
	17.16Champ_front_fonc_pois_ipsn	
	17.17Champ_front_fonc_pois_tube	
	17.18Champ_front_fonc_t	273
	17.19Champ_front_fonc_txyz	273
	17.20Champ_front_fonc_xyz	273
	17.21Champ_front_fonction	273
	17.22Champ_front_lu	274
	17.23Champ_front_musig	274
	17.24Champ_front_normal_vef	274
	17.25Champ_front_pression_from_u	
	17.26Champ_front_recyclage	
	17.27Champ_front_tabule	
	17.28Champ_front_tabule_lu	
	17.29Champ_front_tangentiel_vef	
	17.30Champ_front_uniforme	
	17.31Champ_front_xyz_debit	
18	interpolation_ibm_base	277
	18.1 Interpolation_ibm_power_law_tbl_u_star	277
	18.2 Ibm_aucune	278
	18.3 Ibm_element_fluide	278
	18.4 Ibm_hybride	279
	18.5 Ibm_gradient_moyen	280
	18.6 Ibm_power_law_tbl	280
19	loi_etat_base	281
	19.1 Eos_qc	
	19.2 Eos_wc	
	19.3 Binaire_gaz_parfait_qc	
	19.4 Binaire_gaz_parfait_wc	
	19.5 Coolprop_qc	283
	19.6 Coolprop_wc	
	19.7 Loi_etat_gaz_parfait_base	
	19.8 Loi_etat_gaz_reel_base	
	19.9 Loi_etat_tppi_base	284
	19.10Multi_gaz_parfait_qc	284
	19.11Multi_gaz_parfait_wc	285
	19.12Gaz_parfait_qc	

28	porosites 28.1. Place legture, pare	309
27	pb_champ_evaluateur	309
	26.8 Union	309
	26.7 Tranche	308
	26.6 Sous_zones	308
	26.5 Sous_dom	307
	26.4 Partition	307
	26.3 Metis	
	26.2 Fichier_decoupage	
	26.1 Fichier_med	305
26	partitionneur_deriv	305
	25.1 Nom_anonyme	305
25	nom	304
	24.5 Profil	304
	24.4 Logarithmique	
	24.3 Interpolation	
	24.2 Connexion_exacte	
	24.1 Connexion_approchee	
24	moyenne_imposee_deriv	302
	23.4 Schmidt	
	23.3 Prandtl	
	23.2 Null	
	23.1 Dt_impr_nusselt_mean_only	
23	modele_turbulence_scal_base	299
	22.1330Huc	∠ y 8
	22.13Solide	
	22.11Fluide_stiffened_gas	
	22.10Fluide_sodium_liquide	
	22.9 Fluide_sodium_gaz	
	22.8 Fluide_reel_base	
	22.7 Bloc_sutherland	
	22.6 Fluide_quasi_compressible	
	22.5 Fluide_ostwald	
	22.4 Fluide_incompressible	
	22.3 Fluide_dilatable_base	
	22.2 Fluide_base	
	22.1 Constituant	
22	milieu_base	288
21	loi_horaire	287
	20.1 Loi_fermeture_test	
20	loi_fermeture_base	287
	19.15Rhot_gaz_reel_qc	201
	19.14Rhot_gaz_parfait_qc	
	19.13Gaz_parfait_wc	
	10.120	201

29	precond_base	310
	29.1 Ilu	
	29.2 Precondsolv	
	29.3 Ssor	
	29.4 Ssor_bloc	
30	preconditionneur_petsc_deriv	312
	30.1 Block_jacobi_icc	312
	30.2 Eisentat	312
	30.3 Block_jacobi_ilu	313
	30.4 Boomeramg	313
	30.5 C-amg	313
	30.6 Diag	313
	30.7 Jacobi	313
	30.8 Lu	313
	30.9 Null	314
	30.10Pilut	314
	30.11Sa-amg	314
	30.12Spai	314
	30.13Ssor	315
31	schema_temps_base	315
	31.1 Sch_cn_ex_iteratif	
	31.2 Sch_cn_iteratif	
	31.3 Scheme_euler_explicit	
	31.4 Leap_frog	
	31.5 Runge_kutta_ordre_2	
	31.6 Runge_kutta_ordre_2_classique	328
	31.7 Runge_kutta_ordre_3	330
	31.8 Runge_kutta_ordre_3_classique	332
	31.9 Runge_kutta_ordre_4_d3p	334
	31.10Runge_kutta_ordre_4_classique	336
	31.11Runge_kutta_ordre_4_classique_3_8	338
	31.12Runge_kutta_rationnel_ordre_2	340
	31.13Schema_adams_bashforth_order_2	342
	31.14Schema_adams_bashforth_order_3	
	31.15Schema_adams_moulton_order_2	346
	31.16Schema_adams_moulton_order_3	348
	31.17Schema_backward_differentiation_order_2	351
	31.18Schema_backward_differentiation_order_3	353
	31.19Scheme_euler_implicit	356
	31.20Schema_implicite_base	359
	31.21Schema_predictor_corrector	361
32	solveur_implicite_base	363
	32.1 Ice	363
	32.2 Implicite	
	32.3 Piso	
	32.4 Sets	
	32.5 Simple	
	32.6 Simpler	
	32.7 Solveur_lineaire_std	
	32.8 Solveur u.p	369

33	solveur_petsc_deriv	370
	33.1 Bicgstab	
	33.2 Cholesky_out_of_core	371
	33.3 Cholesky_pastix	
	33.4 Cholesky_superlu	
	33.5 Cholesky_umfpack	
	33.6 Ibicgstab	
	33.7 Pipecg	
	33.8 Cholesky	
	33.9 Cholesky_mumps_blr	
	33.10Cli	
	33.11Cli_quiet	
	33.12Gcp	
	33.13Gmres	
	33.14Lu	379
24	common have	200
34	source_base 34.1 Correction antal	380
	34.2 Correction_tomiyama	
	34.3 Dp_impose	
	34.4 Type_perte_charge_deriv	
	34.4.1 Dp	
	34.4.2 Dp_regul	
	34.5 Dispersion_bulles	
	34.6 Portance_interfaciale	
	34.7 Source_dep_inco_bases	
	34.8 Acceleration	
	34.9 Boussinesq_concentration	
	34.11Canal_perio	
	34.12Coriolis	
	34.13Darcy	
	34.14Dirac	
	34.15Flux interfacial	
	34.16Forchheimer	
	34.17Frottement_interfacial	
	34.18Perte_charge_anisotrope	
	34.19Perte_charge_circulaire	
	34.20Perte_charge_directionnelle	
	34.21Perte_charge_isotrope	
	34.22Perte_charge_reguliere	
	34.23Spec_pdcr_base	
	34.23.1 Longitudinale	
	34.23.2 Transversale	
	34.24Perte_charge_singuliere	
	34.25Puissance_thermique	
	34.26Radioactive_decay	
	34.27Source_constituant	
	34.28Source_generique	
	34.29Source_pdf	
	34.30Bloc_pdf_model	
	34.31Source_pdf_base	
	34.32Source_qdm	
	34.33Source odm lambdaup	393

40	index	400
	39.3 Entierfloat	400
	39.2 Quatremots	
	39.1 Troismots	
39		399
	38.5 Listobj	
	38.4 Un_pb	
	38.3 List_un_pb	
	38.2 Milieu_composite	
38	listobj_impl 38.1 Milieu_musig	398 398
	37.1 Negligeable_scalaire	398
37		397
	36.1 Negligeable	397
36		397
	35.4 Bloc_tube	397
	35.3 Bloc_couronne	396
	35.2 Deuxentiers	396
35	sous_zone 35.1 Bloc_origine_cotes	395 396
	34.37 Vitesse_derive_base	
	34.36Travail_pression	
	34.35Terme_puissance_thermique_echange_impose	
	34.34Source_th_tdivu	

1 Syntax to define a mathematical function

In a mathematical function, used for example in field definition, it's possible to use the predifined function (an object parser is used to evaluate the functions):

ABS : absolute value function

COS : cosine function
SIN : sine function
TAN : tangent function
ATAN : arctangent function
EXP : exponential function
LN : natural logarithm function
SQRT : square root function
INT : integer function
ERF : error function

RND(x): random function (values between 0 and x)

COSH : hyperbolic cosine function
SINH : hyperbolic sine function
TANH : hyperbolic tangent function
ACOS : inverse cosine function
ASIN : inverse sine function

ATANH: inverse hyperbolic tangent function NOT(x): NOT x (returns 1 if x is false, 0 otherwise)

```
SGN(x) : SGN(x) = S
x_AND_y : boolean logical operation AND (returns 1 if both x and y are true, else 0)
x_OR_y : boolean logical operation OR (returns 1 if x or y is true, else 0)
x_GT_y: greater than (returns 1 if x>y, else 0)
x_GE_y : greater than or equal to (returns 1 if x>=y, else 0)
x_LT_y: less than (returns 1 if x<y, else 0)
x_LE_y: less than or equal to (returns 1 if x \le y, else 0)
x MIN y : returns the smallest of x and y
x_MAX_y : returns the largest of x and y
x_MOD_y : modular division of x per y
x_EQ_y
                              : equal to (returns 1 if x==y, else 0)
x_NEQ_y : not equal to (returns 1 if x!=y, else 0)
You can also use the following operations:
+ : addition
- : subtraction
/ : division
*: multiplication
%: modulo
$ : max
: power
< : less than
> : greater than
[ : less than or equal to
] : greater than or equal to
You can also use the following constants:
Pi : pi value (3,1415...)
The variables which can be used are:
x,y,z : coordinates
t: time
Examples:
Champ_front_fonc_txyz 2 \cos(y+x^2) t+\ln(y)
Champ_fonc_xyz dom 2 \tanh(4*y)*(0.95+0.1*rnd(1)) 0.
Possible errors:
Error 1:
Champ_fonc_txyz 1 \cos(10*t)*(1<x<2)*(1<y<2)
Previous line is wrong. It should be written as:
Champ_fonc_txyz 1 \cos(10^*t)^*(1 < x)^*(x < 2)^*(1 < y)^*(y < 2)
Champ_front_fonc_xyz 1 20*(x<-2)+10*(y]-5)+3*(z>0)
Previous line is wrong because negative values are not written between parentheses. It should be written
Champ_front_fonc_xyz 1 20*(x<(-2))+10*(y](-5))+3*(z>0)
```

2 Existing & predefined fields names

Here is a list of post-processable fields, but it is not the only ones.

Physical values	Keyword for field_name	Unit
Velocity	Vitesse or Velocity	$m.s^{-1}$
Velocity residual	Vitesse_residu	$m.s^{-2}$
Kinetic energy per elements		
$(0.5\rho u_i ^2)$	Energie_cinetique_elem	$kg.m^{-1}.s^{-2}$
Total kinetic energy		
$\left(\frac{\sum_{i=1}^{nb_elem} 0.5\rho u_i ^2 vol_i}{\sum_{i=1}^{nb_elem} vol_i}\right)$		1 0
$\left[\begin{array}{c} 2^{n} \\ \hline \\ \hline \\ \hline \\ \hline \\ \hline \\ \\ \hline \\ \\ \\ \\ \\ \\ $	Energie_cinetique_totale	$kg.m^{-1}.s^{-2}$
$\frac{\sum_{i=1} voi_i}{\text{Vorticity}}$	Vorticite	s^{-1}
Pressure in incompressible flow	vorucite	8
Pressure in incompressible now $(P/\rho + gz)$	Pression ¹	$Pa.m^3.kg^{-1}$
For Front Tracking probleme	1 Tession	_
		Pa
$\frac{(P + \rho gz)}{\text{Pressure in incompressible flow}}$		I u
Pressure in incompressible flow $(P+\rho gz)$	Pression_pa or Pressure	Pa
Pressure in compressible flow	Pression	Pa
Hydrostatic pressure (ρgz)	Pression hydrostatique	Pa
Totale pressure (when	1 ression_nydrostatique	I u
quasi compressible model		
is used)=Pth+P	Pression_tot	Pa
Pressure gradient	1 Tession_tot	I u
1	Gradient_pression	m a-2
$\frac{(\nabla(P/\rho + gz))}{\text{Velocity gradient}}$	gradient_vitesse	$m.s^{-2}$ s^{-1}
Temperature	Temperature	°C or K
Temperature residual	Temperature_residu	${}^{o}\text{C.}s^{-1} \text{ or K.}s^{-1}$
Phase temperature of	Temperature_residu	C.S OF K.S
a two phases flow	Temperature_EquationName	°C or K
Mass transfer rate	Temperature_Equation value	COLK
between two phases	Temperature_mpoint	$k_{am}^{-2}e^{-1}$
Temperature variance	Variance_Temperature	$\frac{kg.m^{-2}.s^{-1}}{K^2}$
Temperature dissipation rate	Taux_Dissipation_Temperature	$K^{2}.s^{-1}$
Temperature dissipation rate Temperature gradient	Gradient_temperature	$K.m^{-1}$
Heat exchange coefficient	H_echange_Tref ²	$W.m^{-2}.K^{-1}$
Turbulent heat flux	Flux_Chaleur_Turbulente	$m.K.s^{-1}$
	Viscosite_turbulente	$m.K.s^{-1}$ $m^2.s^{-1}$
Turbulent viscosity	viscosite_turbulente	TH .S
Turbulent dynamic viscosity	Vicacita dynamicus tumbulanta	$kg.m.s^{-1}$
(when quasi compressible model is used)	Viscosite_dynamique_turbulente	кули.s
Turbulent kinetic energy	K	$m^2.s^{-2}$
Turbulent dissipation rate	Eps	$m \cdot s = m^3 \cdot s^{-1}$
Turbulent quantities	Lps	111 .5
K and Epsilon	K_Eps	$(m^2.s^{-2}, m^3.s^{-1})$
Residuals of turbulent quantities	K_12/ps	(111.3 ,111.3)
K and Epsilon residuals	K_Eps_residu	$(m^2.s^{-3}, m^3.s^{-2})$
Constituent concentration	Concentration	(111.3 ,111.3)
Constituent concentration residual	Concentration_residu	
Component velocity along X	VitesseX	$m.s^{-1}$
	continued on next page	1111.5
•••	continued on next page	

The post-processed pressure is the pressure divided by the fluid's density $(P/\rho+gz)$ on incompressible laminar calculation. For turbulent, pressure is $P/\rho+gz+2/3*k$ cause the turbulent kinetic energy is in the pressure gradient.

2Tref indicates the value of a reference temperature and must be specified by the user. For example, H_echange_293 is the keyword

to use for Tref=293K.

Physical values	Keyword for field_name	Unit
Component velocity along Y	VitesseY	$m.s^{-1}$
Component velocity along Z	VitesseZ	$m.s^{-1}$
Mass balance on each cell	Divergence_U	$m^3.s^{-1}$
Irradiancy	Irradiance	$W.m^{-2}$
Q-criteria	Critere_Q	s^{-1}
Distance to the wall $Y^+ = yU/\nu$		
(only computed on	Y_plus	dimensionless
boundaries of wall type)		
Friction velocity	U_star	$m.s^{-1}$
Void fraction	alpha	dimensionless
Cell volumes	Volume_maille	m^3
Chemical potential	Potentiel_Chimique_Generalise	
Source term in non		
Galinean referential	Acceleration_terme_source	$m.s^{-2}$
Stability time steps	Pas_de_temps	S
Listing of boundary fluxes	Flux_bords	cf each *.out file
Volumetric porosity	Porosite_volumique	dimensionless
Distance to the wall	Distance_Paroi ³	m
Volumic thermal power	Puissance_volumique	$W.m^{-3}$
Local shear strain rate defined as		
$\sqrt{(2SijSij)}$	Taux_cisaillement	s^{-1}
Cell Courant number (VDF only)	Courant_maille	dimensionless
Cell Reynolds number (VDF only)	Reynolds_maille	dimensionless
Viscous force	viscous_force	$kg.m^2.s^{-1}$
Pressure force	pressure_force	$kg.m^2.s^{-1}$
Total force	total_force	$kg.m^2.s^{-1}$
Viscous force along X	viscous_force_x	$kg.m^2.s^{-1}$
Viscous force along Y	viscous_force_y	$kg.m^2.s^{-1}$
Viscous force along Z	viscous_force_z	$kg.m^2.s^{-1}$
Pressure force along X	pressure_force_x	$kg.m^2.s^{-1}$
Pressure force along Y	pressure_force_y	$kg.m^2.s^{-1}$
Pressure force along Z	pressure_force_z	$kg.m^{2}.s^{-1}$
Total force along X	total_force_x	$kg.m^{2}.s^{-1}$
Total force along Y	total_force_y	$kg.m^2.s^{-1}$
Total force along Z	total_force_z	$kg.m^2.s^{-1}$

3 interprete

Description: Basic class for interpreting a data file. Interpretors allow some operations to be carried out on objects.

See also: objet_u (40) { (3.28) } (3.57) export (3.43) ecrire_fichier_xyz_valeur (3.39) option_vdf (3.81) criteres_convergence (3.26) residuals (3.107) espece (3.41) mass_source (3.73) Option_PolyMAC (3.14) Op_Conv_EF_Stab_PolyMAC_Face (3.6) Op_Conv_EF_Stab_PolyMAC_P0P1NC_Elem (3.7) Op_Conv_EF_Stab_PolyMAC_P0P1NC_Face (3.8) Op_Conv_EF_Stab_PolyMAC_P0_Face (3.9) Option_DG (3.11) verifiercoin (3.131) scatter (3.109) read_med (3.17) integrer_champ_med (3.61) ecriturelecturespecial (3.40) facsec_expert (3.55) trianguler (3.125) nettoiepasnoeuds (3.80) extraire_surface (3.48) precisiongeom (3.89) tetraedriser (3.119) redresser_hexaedres_vdf (3.98) Raffiner_isotrope_parallele (3.16) transformer (3.124)

³distance_paroi is a field which can be used only if the mixing length model (see 2.15.1.2) is used in the data file.

modifydomaineAxi1d (3.76) modif_bord_to_raccord (3.75) remove_invalid_internal_boundaries (3.103) extrudebord (3.49) analyse_angle (3.19) lire_ideas (3.68) extruder (3.51) reorienter_triangles (3.105) corrigerfrontiere periodique (3.25) reorienter tetraedres (3.104) refine mesh (3.99) bidim axi (3.22) extraire-_plan (3.47) dimension (3.32) polyedriser (3.87) orientefacesbord (3.82) orienter_simplexes (3.97) verifier-_qualite_raffinements (3.128) interprete_geometrique_base (3.62) distance_paroi (3.36) extrudeparoi (3.50) reordonner (3.106) calculer_moments (3.23) regroupebord (3.100) extract_2d_from_3d (3.44) raffineranisotrope (3.90) mailler (3.70) discretiser domaine (3.34) maillerparallel (3.72) axi (3.21) extruderen20 (3.53) rotation (3.108) imprimer flux (3.58) lire tgrid (3.95) dilate (3.31) supprime bord (3.113) decouper bord coincident (3.30) decoupebord pour rayonnement (3.29) remove elem (3.101) raffinerisotrope (3.91) extraire domaine (3.46) verifier simplexes (3.130) partition multi (3.85) partition (3.83) associate (3.20) debog (3.27) discretize (3.35) solve (3.111) testeur (3.117) end (3.56) read (3.92) mkdir (3.74) ecrire_fichier_bin (3.134) system (3.115) stat_per_proc_perf_log (3.112) disable_TU (3.33) MultipleFiles (3.5) Option_Interpolation (3.13) ecrire (3.133) read_file (3.93) execute_parallel (3.42) testeur-_medcoupling (3.118) pilote_icoco (3.86) test_solveur (3.116) lata_to_CGNS (3.63) lml_2_lata (3.69) Link_CGNS_Files (3.3) ecrire_champ_med (3.37) Write_MED (3.2) Merge_MED (3.4) lata_2_med (3.65) lata_2_other (3.67) postraiter_domaine (3.88) Option_CGNS (3.10) moyenne_volumique (3.77) Parallel-_io_parameters (3.15) Option_IJK (3.12) Test_SSE_Kernels (3.18) multigrid_solver (3.78)

Usage:

interprete

3.1 Create_domain_from_sub_domain

Description: This keyword fills the domain domaine_final with the subdomaine par_sous_zone from the domain domaine_init. It is very useful when meshing several mediums with Gmsh. Each medium will be defined as a subdomaine into Gmsh. A MED mesh file will be saved from Gmsh and read with Lire_Med keyword by the TRUST data file. And with this keyword, a domain will be created for each medium in the TRUST data file.

```
See also: interprete_geometrique_base (3.62)

Usage:
Create_domain_from_sub_domain {
    [domaine_final str]
    [par_sous_dom|par_sous_zone str]
    domaine_init str
}

where
```

- domaine final str: new domain in which faces are stored
- par_sous_dom|par_sous_zone str: a sub-area (a group in a MED file) allowing to choose the elements
- **domaine_init** *str*: initial domain

3.2 Write_med

Description: Write a domain to MED format into a file.

```
See also: interprete (3)
```

Usage:

```
Write_MED nom_dom file where
```

- nom_dom str: Name of domain.
- file str: Name of file.

3.3 Link_cgns_files

Description: Creates a single CGNS xxxx.cgns file that links to a xxxx.grid.cgns and xxxx.solution.*.cgns files

See also: interprete (3)

Usage:

Link_CGNS_Files base_name output_name

where

• base_name str: Base name of the gid/solution cgns files.

• output_name str: Name of the output cgns file.

3.4 Merge_med

Description: This keyword allows to merge multiple MED files produced during a parallel computation into a single MED file.

See also: interprete (3)

Usage:

Merge_MED med_files_base_name time_iterations

where

- med_files_base_name *str*: Base name of multiple med files that should appear as base_name_xxxxx.med, where xxxxx denotes the MPI rank number. If you specify NOM_DU_CAS, it will automatically take the basename from your datafile's name.
- **time_iterations** *str into ['all_times'*, *'last_time']*: Identifies whether to merge all time iterations present in the MED files or only the last one.

3.5 Multiplefiles

Description: Change MPI rank limit for multiple files during I/O

See also: interprete (3)

Usage:

MultipleFiles type

where

• type int: New MPI rank limit

```
3.6 Op_conv_ef_stab_polymac_face
Description: Class Op_Conv_EF_Stab_PolyMAC_Face_PolyMAC
See also: interprete (3)
Usage:
Op_Conv_EF_Stab_PolyMAC_Face {
     [ alpha float]
}
where
   • alpha float: parametre ajustant la stabilisation de 0 (schema centre) a 1 (schema amont)
3.7 Op_conv_ef_stab_polymac_p0p1nc_elem
Description: Class Op_Conv_EF_Stab_PolyMAC_P0P1NC_Elem
See also: interprete (3)
Usage:
Op_Conv_EF_Stab_PolyMAC_P0P1NC_Elem {
     [ alpha float]
}
where
   • alpha float: parametre ajustant la stabilisation de 0 (schema centre) a 1 (schema amont)
3.8 Op_conv_ef_stab_polymac_p0p1nc_face
Description: Class Op_Conv_EF_Stab_PolyMAC_P0P1NC_Face
See also: interprete (3)
Usage:
3.9 Op_conv_ef_stab_polymac_p0_face
Description: Class Op_Conv_EF_Stab_PolyMAC_P0_Face
See also: interprete (3)
Usage:
3.10 Option_cgns
Description: Class for CGNS options.
See also: interprete (3)
Usage:
Option_CGNS {
```

```
[ single_precision ]
    [ multiple_files ]
    [ parallel_over_zone ]
    [ use_links ]
}
where
```

- **single_precision**: If used, data will be written with a single_precision format inside the CGNS file (it concerns both mesh coordinates and field values).
- multiple_files: If used, data will be written in separate files (ie: one file per processor).
- parallel_over_zone : If used, data will be written in separate zones (ie: one zone per processor). This is not so performant but easier to read later ...
- use_links: If used, data will be written in separate files; one file for mesh, and then one file for solution time. Links will be used.

3.11 Option_dg

```
Description: Class for DG options.

See also: interprete (3)

Usage:
Option_DG {

    [order int]
    [velocity_order int]
    [pressure_order int]
    [temperature_order int]
    [gram_schmidt int]
}

where
```

- order int: global order for the DG unknowns (1 by default)
- velocity_order int: optional order for DG velocity unknown
- pressure_order int: optional order for DG pressure unknown
- temperature order *int*: optional order for DG temperature unknown
- gram_schmidt int: Gram Schmidt orthogonalization (1 by default)

3.12 Option_ijk

```
Description: Class of IJK options.

See also: interprete (3)

Usage:
Option_IJK {
    [check_divergence]
    [disable_diphasique]
}
where
```

- $\bullet \ \ check_divergence : Flag \ to \ compute \ and \ print \ the \ value \ of \ div(u) \ after \ each \ pressure-correction$
- **disable_diphasique**: Disable all calculations related to interfaces (phase properties, interfacial force, ...)

3.13 Option_interpolation

Description: Class for interpolation fields using MEDCoupling.

```
See also: interprete (3)

Usage:
Option_Interpolation {
    [without_declsans_dec]
    [sharing_algo int]
}
where

• without_declsans_dec: Use remapper even for a parallel calculation
• sharing_algo int: Setting the DEC sharing algo: 0,1,2
```

3.14 Option_polymac

```
Description: Class of PolyMAC options.
```

```
See also: interprete (3)

Usage:
Option_PolyMAC {

    [ use_osqp ]
    [ vdf_meshlmaillage_vdf ]
    [ interp_ve1 ]
    [ traitement_axi ]
}
where
```

- **use_osqp**: Flag to use the old formulation of the M2 matrix provided by the OSQP library. Only useful for PolyMAC version.
- vdf_mesh|maillage_vdf: Flag used to force the calculation of the equiv tab.
- **interp_ve1**: Flag to enable a first-order face-to-element velocity interpolation. By default, it is not activated which means a second order interpolation. Only useful for PolyMAC_P0 version.
- **traitement_axi**: Flag used to relax the time-step stability criterion in case of a thin slice geometry while modelling an axi-symetrical case. Only useful for PolyMAC_P0 version.

3.15 Parallel_io_parameters

Description: Object to handle parallel files in IJK discretization

```
See also: interprete (3)

Usage:
Parallel_io_parameters {
```

```
[ block_size_bytes int]
  [ block_size_megabytes int]
  [ writing_processes int]
  [ bench_ijk_splitting_write str]
  [ bench_ijk_splitting_read str]
}
where
```

- **block_size_bytes** *int*: File writes will be performed by chunks of this size (in bytes). This parameter will not be taken into account if block_size_megabytes has been defined
- **block_size_megabytes** *int*: File writes will be performed by chunks of this size (in megabytes). The size should be a multiple of the GPFS block size or lustre stripping size (typically several megabytes)
- writing_processes *int*: This is the number of processes that will write concurrently to the file system (this must be set according to the capacity of the filesystem, set to 1 on small computers, can be up to 64 or 128 on very large systems).
- **bench_ijk_splitting_write** *str*: Name of the splitting object we want to use to run a parallel write bench (optional parameter)
- **bench_ijk_splitting_read** *str*: Name of the splitting object we want to use to run a parallel read bench (optional parameter)

3.16 Raffiner_isotrope_parallele

```
Description: Refine parallel mesh in parallel

See also: interprete (3)

Usage:
Raffiner_isotrope_parallele {
    name_of_initial_zoneslname_of_initial_domaines str
    name_of_new_zoneslname_of_new_domaines str
    [ ascii ]
    [ single_hdf ]
}
where
```

- name_of_initial_zones|name_of_initial_domaines str: name of initial Domaines
- name of new zones|name of new domaines str: name of new Domaines
- ascii: writing Domaines in ascii format
- single_hdf: writing Domaines in hdf format

3.17 Read med

Synonymous: lire_med

Description: Keyword to read MED mesh files where 'domain' corresponds to the domain name, 'file' corresponds to the file (written in the MED format) containing the mesh named mesh_name.

Note about naming boundaries: When reading 'file', TRUST will detect boundaries between domains (Raccord) when the name of the boundary begins by 'type_raccord

-_'. For example, a boundary named type_raccord_wall in 'file' will be considered by TRUST as a boundary named 'wall' between two domains.

NB: To read several domains from a mesh issued from a MED file, use Read_Med to read the mesh then use Create_domain_from_sub_domain keyword.

NB: If the MED file contains one or several subdomaine defined as a group of volumes, then Read_MED will read it and will create two files domain_name_ssz.geo and domain_name_ssz_par.geo defining the subdomaines for sequential and/or parallel calculations. These subdomaines will be read in sequential in the datafile by including (after Read_Med keyword) something like:

```
Read_Med ....

Read_file domain_name_ssz.geo;

During the parallel calculation, you will include something:

Scatter { ... }

Read_file domain_name_ssz_par.geo;

See also: interprete (3)

Usage:

read_med {

    [ convertalltopoly ]
    domaineldomain str
    fichierlfile str
    [ maillagelmesh str]
    [ exclure_groupeslexclude_groups n word1 word2 ... wordn]
    [ inclure_groupes_faces_additionnelslinclude_additional_face_groups n word1 word2 ... wordn]
}

where
```

- convertalltopoly: Option to convert mesh with mixed cells into polyhedral/polygonal cells
- **domaineldomain** *str*: Corresponds to the domain name.
- fichierlfile str: File (written in the MED format, with extension '.med') containing the mesh
- maillagelmesh str: Name of the mesh in med file. If not specified, the first mesh will be read.
- exclure_groupeslexclude_groups n word1 word2 ... wordn: List of face groups to skip in the MED file
- inclure_groupes_faces_additionnelslinclude_additional_face_groups n word1 word2 ... wordn: List of face groups to read and register in the MED file.

3.18 Test_sse_kernels

Description: Object to test the different kernel methods used in the multigrid solver in IJK discretization

```
See also: interprete (3)
Usage:
Test_SSE_Kernels {
    [ nmax int]
}
where
```

• nmax int: Number of tests we want to perform

3.19 Analyse_angle

Description: Keyword Analyse_angle prints the histogram of the largest angle of each mesh elements of the domain named name_domain. nb_histo is the histogram number of bins. It is called by default during the domain discretization with nb_histo set to 18. Useful to check the number of elements with angles above 90 degrees.

See also: interprete (3)

Usage:
analyse_angle domain_name nb_histo
where

- domain name str: Name of domain to resequence.
- nb_histo int

3.20 Associate

Synonymous: associer

Description: This interpretor allows one object to be associated with another. The order of the two objects in this instruction is not important. The object objet_2 is associated to objet_1 if this makes sense; if not either objet_1 is associated to objet_2 or the program exits with error because it cannot execute the Associate (Associer) instruction. For example, to calculate water flow in a pipe, a Pb_Hydraulique type object needs to be defined. But also a Domaine type object to represent the pipe, a Scheme_euler_explicit type object for time discretization, a discretization type object (VDF or VEF) and a Fluide_Incompressible type object which will contain the water properties. These objects must then all be associated with the problem.

See also: interprete (3)

Usage:
associate objet_1 objet_2
where

objet_1 str: Objet_1
 objet_2 str: Objet_2

3.21 Axi

axi

Description: This keyword allows a 3D calculation to be executed using cylindrical coordinates (R, θ, Z) . If this instruction is not included, calculations are carried out using Cartesian coordinates.

See also: interprete (3)
Usage:

3.22 Bidim axi

Description: Keyword allowing a 2D calculation to be executed using axisymetric coordinates (R, Z). If this instruction is not included, calculations are carried out using Cartesian coordinates.

```
See also: interprete (3)
Usage:
bidim_axi
3.23
       Calculer_moments
Description: Calculates and prints the torque (moment of force) exerted by the fluid on each boundary in
output files (.out) of the domain nom_dom.
See also: interprete (3)
Usage:
calculer_moments nom_dom mot
where
   • nom dom str: Name of domain.
   • mot lecture_bloc_moment_base (3.24): Keyword.
3.24 Lecture_bloc_moment_base
Description: Auxiliary class to compute and print the moments.
See also: objet_lecture (39) calcul (3.24.1) centre_de_gravite (3.24.2)
Usage:
3.24.1 Calcul
Description: The centre of gravity will be calculated.
See also: (3.24)
Usage:
calcul
3.24.2 Centre_de_gravite
Description: To specify the centre of gravity.
See also: (3.24)
Usage:
centre_de_gravite point
where
   • point un_point (3.24.3): A centre of gravity.
3.24.3 Un_point
Description: A point.
See also: objet_lecture (39)
Usage:
```

pos where

• pos x1 x2 (x3): Point coordinates.

3.25 Corriger_frontiere_periodique

Description: The Corriger_frontiere_periodique keyword is mandatory to first define the periodic boundaries, to reorder the faces and eventually fix unaligned nodes of these boundaries. Faces on one side of the periodic domain are put first, then the faces on the opposite side, in the same order. It must be run in sequential before mesh splitting.

```
See also: interprete (3)

Usage:
corriger_frontiere_periodique {
    domaine str
    bord str
    [ direction n x1 x2 ... xn]
    [ fichier_post str]
}
where
```

- domaine str: Name of domain.
- bord str: the name of the boundary (which must contain two opposite sides of the domain)
- **direction** n x1 x2 ... xn: defines the periodicity direction vector (a vector that points from one node on one side to the opposite node on the other side). This vector must be given if the automatic algorithm fails, that is:
 - when the node coordinates are not perfectly periodic
 - when the periodic direction is not aligned with the normal vector of the boundary faces
- fichier_post str: .

3.26 Criteres convergence

```
Description: convergence criteria

See also: interprete (3)

Usage:
aco [inco][val] acof
where

aco str into ['{'}]: Opening curly bracket.
inco str: Unknown (i.e: alpha, temperature, velocity and pressure)
val float: Convergence threshold
acof str into ['}']: Closing curly bracket.
```

3.27 Debog

Description: Class to debug some differences between two TRUST versions on a same data file. If you want to compare the results of the same code in sequential and parallel calculation, first run (mode=0)

in sequential mode (the files fichier1 and fichier2 will be written first) then the second run in parallel calculation (mode=1).

During the first run (mode=0), it prints into the file DEBOG, values at different points of the code thanks to the C++ instruction call. see for example in Kernel/Framework/Resoudre.cpp file the instruction: Debog::verifier(msg,value); Where msg is a string and value may be a double, an integer or an array.

During the second run (mode=1), it prints into a file Err_Debog.dbg the same messages than in the DEBOG file and checks if the differences between results from both codes are less than a given value (error). If not, it prints Ok else show the differences and the lines where it occured.

See also: interprete (3)

Usage:

debog pb fichier1 fichier2 seuil mode

where

- **pb** *str*: Name of the problem to debug.
- fichier1 str: Name of the file where domain will be written in sequential calculation.
- fichier2 str: Name of the file where faces will be written in sequential calculation.
- seuil *float*: Minimal value (by default 1.e-20) for the differences between the two codes.
- **mode** *int*: By default -1 (nothing is written in the different files), you will set 0 for the sequential run, and 1 for the parallel run.

3.28 {

Description: Block's beginning.

See also: interprete (3)

Usage:
{

3.29 Decoupebord_pour_rayonnement

Synonymous: decoupebord

Description: To subdivide the external boundary of a domain into several parts (may be useful for better accuracy when using radiation model in transparent medium). To specify the boundaries of the fine_domain_name domain to be splitted. These boundaries will be cut according the coarse mesh defined by either the keyword domaine_grossier (each boundary face of the coarse mesh coarse_domain_name will be used to group boundary faces of the fine mesh to define a new boundary), either by the keyword nb_parts_naif (each boundary of the fine mesh is splitted into a partition with nx*ny*nz elements), either by a geometric condition given by a formulae with the keyword condition_geometrique. If used, the coarse_domain_name domain should have the same boundaries name of the fine_domain_name domain.

A mesh file (ASCII format, except if binaire option is specified) named by default newgeom (or specified by the nom_fichier_sortie keyword) will be created and will contain the fine_domain_name domain with the splitted boundaries named boundary_name

```
See also: interprete (3)

Usage:
decoupebord_pour_rayonnement {
    domaine str
    [domaine_grossier str]
```

```
[ nb_parts_naif  n n1 n2 ... nn]
     [ nb_parts_geom n n1 n2 ... nn]
     [ condition_geometrique n word1 word2 ... wordn]
     bords_a_decouper n word1 word2 ... wordn
     [ nom_fichier_sortie str]
     [binaire int]
}
where
   • domaine str
   • domaine_grossier str
   • nb_parts_naif n n1 n2 ... nn
   • nb_parts_geom n n1 n2 ... nn
   • condition_geometrique n word1 word2 ... wordn
   • bords_a_decouper n word1 word2 ... wordn
   • nom_fichier_sortie str
   • binaire int
```

3.30 Decouper_bord_coincident

Description: In case of non-coincident meshes and a paroi_contact condition, run is stopped and two external files are automatically generated in VEF (connectivity_failed_boundary_name and connectivity_failed_pb_name.med). In 2D, the keyword Decouper_bord_coincident associated to the connectivity_failed_boundary_name file allows to generate a new coincident mesh.

```
Usage:
decouper_bord_coincident domain_name bord
where

• domain_name str: Name of domain.
• bord str: connectivity_failed_boundary_name
```

3.31 Dilate

Description: Keyword to multiply the whole coordinates of the geometry.

```
See also: interprete (3)

Usage:
dilate domain_name alpha
where
```

- domain name str: Name of domain.
- alpha float: Value of dilatation coefficient.

3.32 Dimension

Description: Keyword allowing calculation dimensions to be set (2D or 3D), where dim is an integer set to 2 or 3. This instruction is mandatory.

See also: interprete (3)

Usage:

dimension dim

where

• dim int into [2, 3]: Number of dimensions.

3.33 Disable_tu

Description: Flag to disable the writing of the .TU files

See also: interprete (3)

Usage:

 $disable_TU$

3.34 Discretiser_domaine

Description: Useful to discretize the domain domain_name (faces will be created) without defining a problem.

See also: interprete (3)

Usage:

discretiser_domaine domain_name

where

• domain_name str: Name of the domain.

3.35 Discretize

Synonymous: discretiser

Description: Keyword to discretise a problem_name according to the discretization dis. IMPORTANT: A number of objects must be already associated (a domain, time scheme, central object) prior to invoking the Discretize (Discretiser) keyword. The physical properties of this central object must also have been read.

See also: interprete (3)

Usage:

discretize problem_name dis

where

- problem_name str: Name of problem.
- dis str: Name of the discretization object.

3.36 Distance_paroi

Description: Class to generate external file Wall_length.xyz devoted for instance, for mixing length modelling. In this file, are saved the coordinates of each element (center of gravity) of dom domain and minimum distance between this point and boundaries (specified bords) that user specifies in data file (typically, those associated to walls). A field Distance_paroi is available to post process the distance to the wall.

See also: interprete (3)

Usage:

distance_paroi dom bords format

where

- dom str: Name of domain.
- **bords** *n word1 word2* ... *wordn*: Boundaries.
- **format** *str into* ['binaire', 'formatte']: Value for format may be binaire (a binary file Wall_length.xyz is written) or formatte (moreover, a formatted file Wall_length_formatted.xyz is written).

3.37 Ecrire_champ_med

Description: Keyword to write a field to MED format into a file.

See also: interprete (3)

Usage:

ecrire_champ_med nom_dom nom_chp file

where

nom_dom str: domain namenom_chp str: field name

• **file** *str*: file name

3.38 Ecrire_fichier_formatte

Description: Keyword to write the object of name name_obj to a file filename in ASCII format.

See also: ecrire_fichier_bin (3.134)

Usage:

ecrire_fichier_formatte name_obj filename

where

- name obj str: Name of the object to be written.
- filename str: Name of the file.

3.39 Ecrire_fichier_xyz_valeur

Description: This keyword is used to write the values of a field only for some boundaries in a text file with the following format: n_valeur

```
x_1 y_1 [z_1] val_1
```

...

x_n y_n [z_n] val_n

The created files are named: pbname_fieldname_[boundaryname]_time.dat

```
See also: interprete (3)

Usage:
ecrire_fichier_xyz_valeur {

[binary_file]
[dt float]
[fields n word1 word2 ... wordn]
[boundaries n word1 word2 ... wordn]
}
where

• binary_file: To write file in binary format
• dt float: File writing frequency
• fields n word1 word2 ... wordn: Names of the fields we want to write
• boundaries n word1 word2 ... wordn: Names of the boundaries on which to write fields
```

3.40 Ecriturelecturespecial

Description: Class to write or not to write a .xyz file on the disk at the end of the calculation.

```
See also: interprete (3)
Usage:
```

ecriturelecturespecial type

where

• **type** *str*: If set to 0, no xyz file is created. If set to 1 (the default) the .xyz file is written at the end of the computation.

3.41 Espece

```
Description: not_set

See also: interprete (3)

Usage:
espece {

mu champ_base
cp champ_base
masse_molaire float
}

where

• mu champ_base (16.1): Species dynamic viscosity value (kg.m-1.s-1).
• cp champ_base (16.1): Species specific heat value (J.kg-1.K-1).
```

• masse_molaire float: Species molar mass.

3.42 Execute_parallel

Description: This keyword allows to run several computations in parallel on processors allocated to TRUST. The set of processors is split in N subsets and each subset will read and execute a different data file. Error messages usually written to stderr and stdout are redirected to .log files (journaling must be activated).

```
See also: interprete (3)

Usage:
execute_parallel {

liste_cas n word1 word2 ... wordn

[nb_procs n n1 n2 ... nn]
}
where
```

- **liste_cas** *n word1 word2 ... wordn*: N datafile1 ... datafileN. datafileX the name of a TRUST data file without the .data extension.
- **nb_procs** *n n1 n2 ... nn*: nb_procs is the number of processors needed to run each data file. If not given, TRUST assumes that computations are sequential.

3.43 Export

Description: Class to make the object have a global range, if not its range will apply to the block only (the associated object will be destroyed on exiting the block).

```
See also: interprete (3)
Usage:
export
```

3.44 Extract 2d from 3d

Description: Keyword to extract a 2D mesh by selecting a boundary of the 3D mesh. To generate a 2D axisymmetric mesh prefer Extract_2Daxi_from_3D keyword.

```
See also: interprete (3) extract_2daxi_from_3d (3.45)
```

Usage:

```
extract_2d_from_3d dom3D bord dom2D where
```

- dom3D str: Domain name of the 3D mesh
- **bord** *str*: Boundary name. This boundary becomes the new 2D mesh and all the boundaries, in 3D, attached to the selected boundary, give their name to the new boundaries, in 2D.
- dom2D str: Domain name of the new 2D mesh

3.45 Extract_2daxi_from_3d

Description: Keyword to extract a 2D axisymetric mesh by selecting a boundary of the 3D mesh.

```
See also: extract_2d_from_3d (3.44)
```

```
Usage:
```

```
extract_2daxi_from_3d dom3D bord dom2D where
```

- dom3D str: Domain name of the 3D mesh
- **bord** *str*: Boundary name. This boundary becomes the new 2D mesh and all the boundaries, in 3D, attached to the selected boundary, give their name to the new boundaries, in 2D.
- dom2D str: Domain name of the new 2D mesh

3.46 Extraire_domaine

See also: interprete (3)

Description: Keyword to create a new domain built with the domain elements of the pb_name problem verifying the two conditions given by Condition_elements. The problem pb_name should have been discretized.

Keyword Discretize should have already been used to read the object.

```
Usage:
extraire_domaine {

domaine str
probleme str
[condition_elements str]
[sous_zonelsous_domaine str]
}
where
```

- domaine str: Domain in which faces are saved
- probleme str: Problem from which faces should be extracted
- condition elements str
- sous_zone|sous_domaine str

3.47 Extraire_plan

Description: This keyword extracts a plane mesh named domain_name (this domain should have been declared before) from the mesh of the pb_name problem. The plane can be either a triangle (defined by the keywords Origine, Point1, Point2 and Triangle), either a regular quadrangle (with keywords Origine, Point1 and Point2), or either a generalized quadrangle (with keywords Origine, Point1, Point2, Point3). The keyword Epaisseur specifies the thickness of volume around the plane which contains the faces of the extracted mesh. The keyword via_extraire_surface will create a plan and use Extraire_surface algorithm. Inverse_condition_element keyword then will be used in the case where the plane is a boundary not well oriented, and avec_certains_bords_pour_extraire_surface is the option related to the Extraire_surface option named avec_certains_bords.

Keyword Discretize should have already been used to read the object. See also: interprete (3)

```
Usage:
extraire_plan {
domaine str
```

```
probleme str
origine n x1 x2 ... xn
point1 n x1 x2 ... xn
point2 n x1 x2 ... xn
[point3 n x1 x2 ... xn]
[triangle]
epaisseur float
[via_extraire_surface]
[inverse_condition_element]
[avec_certains_bords_pour_extraire_surface n word1 word2 ... wordn]
}
where
```

- domaine str: domain name
- **probleme** *str*: pb_name
- **origine** *n x1 x2 ... xn*
- **point1** n x1 x2 ... xn
- point2 n x1 x2 ... xn
- point3 n x1 x2 ... xn
- triangle
- epaisseur float: thickness
- via extraire surface
- inverse_condition_element
- avec_certains_bords_pour_extraire_surface n word1 word2 ... wordn: name of boundaries to include when extracting plan

3.48 Extraire surface

See also: interprete (3)

where

Description: This keyword extracts a surface mesh named domain_name (this domain should have been declared before) from the mesh of the pb_name problem. The surface mesh is defined by one or two conditions. The first condition is about elements with Condition_elements. For example: Condition_elements x*x+y*y+z*z<1

Will define a surface mesh with external faces of the mesh elements inside the sphere of radius 1 located at (0,0,0). The second condition Condition_faces is useful to give a restriction.

By default, the faces from the boundaries are not added to the surface mesh excepted if option avec_les_bords is given (all the boundaries are added), or if the option avec_certains_bords is used to add only some boundaries.

Keyword Discretize should have already been used to read the object.

```
Usage:
extraire_surface {

domaine str
probleme str
[condition_elements str]
[condition_faces str]
[avec_les_bords]
[avec_certains_bords n word1 word2 ... wordn]
```

- domaine str: Domain in which faces are saved
- **probleme** *str*: Problem from which faces should be extracted
- condition elements str: condition on center of elements
- condition faces str
- avec_les_bords
- avec_certains_bords n word1 word2 ... wordn

3.49 Extrudebord

Description: Class to generate an extruded mesh from a boundary of a tetrahedral or an hexahedral mesh. Warning: If the initial domain is a tetrahedral mesh, the boundary will be moved in the XY plane then extrusion will be applied (you should maybe use the Transformer keyword on the final domain to have the domain you really want). You can use the keyword Postraiter_domaine to generate a latalmedl... file to visualize your initial and final meshes.

This keyword can be used for example to create a periodic box extracted from a boundary of a tetrahedral or a hexaedral mesh. This periodic box may be used then to engender turbulent inlet flow condition for the main domain.

Note that ExtrudeBord in VEF generates 3 or 14 tetrahedra from extruded prisms.

```
Usage:
extrudebord {

domaine_init str
direction x1 x2 (x3)
nb_tranches int
domaine_final str
nom_bord str
[hexa_old]
[trois_tetra]
[vingt_tetra]
[sans_passer_par_le2d int]
}
where
```

- **domaine init** *str*: Initial domain with hexaedras or tetrahedras.
- **direction** $x1 \ x2 \ (x3)$: Directions for the extrusion.
- **nb_tranches** *int*: Number of elements in the extrusion direction.
- domaine_final str: Extruded domain.
- nom_bord str: Name of the boundary of the initial domain where extrusion will be applied.
- hexa old: Old algorithm for boundary extrusion from a hexahedral mesh.
- trois tetra: To extrude in 3 tetrahedras instead of 14 tetrahedras.
- vingt tetra: To extrude in 20 tetrahedras instead of 14 tetrahedras.
- sans_passer_par_le2d int: Only for non-regression

3.50 Extrudeparoi

Description: Keyword dedicated in 3D (VEF) to create prismatic layer at wall. Each prism is cut into 3 tetraedra.

See also: interprete (3)

```
Usage:
extrudeparoi {

domaine str
nom_bord str
[epaisseur n x1 x2 ... xn]
[critere_absolu]
[projection_normale_bord]
}
where
```

- domaine str: Name of the domain.
- nom_bord str: Name of the (no-slip) boundary for creation of prismatic layers.
- epaisseur n x1 x2 ... xn: n r1 r2 rn : (relative or absolute) width for each layer.
- critere_absolu: use absolute width for each layer instead of relative.
- **projection_normale_bord**: keyword to project layers on the same plane that contiguous boundaries. defaut values are: epaisseur_relative 1 0.5 projection_normale_bord 1

3.51 Extruder

Description: Class to create a 3D tetrahedral/hexahedral mesh (a prism is cut in 14) from a 2D triangular/quadrangular mesh.

```
See also: interprete (3) extruder_en3 (3.54)

Usage:
extruder {

domaine str
nb_tranches int
direction troisf
}
where
```

- **domaine** *str*: Name of the domain.
- **nb_tranches** *int*: Number of elements in the extrusion direction.
- **direction** *troisf* (3.52): Direction of the extrude operation.

3.52 Troisf

Description: Auxiliary class to extrude.

```
See also: objet_lecture (39)
Usage:
lx lv lz
```

where

- lx *float*: X direction of the extrude operation.
- ly float: Y direction of the extrude operation.
- Iz *float*: Z direction of the extrude operation.

3.53 Extruder_en20

Description: It does the same task as Extruder except that a prism is cut into 20 tetraedra instead of 3. The name of the boundaries will be devant (front) and derriere (back). But you can change these names with the keyword RegroupeBord.

```
See also: interprete (3)

Usage:
extruder_en20 {

domaine str
nb_tranches int
[direction troisf]
}
where
```

- **domaine** str: Name of the domain.
- **nb** tranches *int*: Number of elements in the extrusion direction.
- **direction** troisf(3.52): 0 Direction of the extrude operation.

3.54 Extruder_en3

Description: Class to create a 3D tetrahedral/hexahedral mesh (a prism is cut in 3) from a 2D triangular/quadrangular mesh. The names of the boundaries (by default, devant (front) and derriere (back)) may be edited by the keyword nom_cl_devant and nom_cl_derriere. If 'null' is written for nom_cl, then no boundary condition is generated at this place.

Recommendation: to ensure conformity between meshes (in case of fluid/solid coupling) it is recommended to extrude all the domains at the same time.

```
See also: extruder (3.51)

Usage:
extruder_en3 {

domaine n word1 word2 ... wordn
 [nom_cl_devant str]
 [nom_cl_derriere str]
 nb_tranches int
 direction troisf
}
where
```

- **domaine** *n word1 word2* ... *wordn*: List of the domains
- nom_cl_devant str: New name of the first boundary.
- **nom_cl_derriere** *str*: New name of the second boundary.
- **nb_tranches** *int* for inheritance: Number of elements in the extrusion direction.
- **direction** *troisf* (3.52) for inheritance: Direction of the extrude operation.

3.55 Facsec_expert

Description: To parameter the safety factor for the time step during the simulation.

```
See also: interprete (3)

Usage:
facsec_expert {

    [facsec_ini float]
    [facsec_max float]
    [rapport_residus float]
    [nb_ite_sans_accel_max int]
}

where
```

- facsec_ini float: Initial facsec taken into account at the beginning of the simulation.
- facsec_max *float*: Maximum ratio allowed between time step and stability time returned by CFL condition. The initial ratio given by facsec keyword is changed during the calculation with the implicit scheme but it couldn't be higher than facsec_max value.

Warning: Some implicit schemes do not permit high facsec_max, example Schema_Adams_Moulton_order_3 needs facsec=facsec_max=1.

Advice:

The calculation may start with a facsec specified by the user and increased by the algorithm up to the facsec_max limit. But the user can also choose to specify a constant facsec (facsec_max will be set to facsec value then). Faster convergence has been seen and depends on the kind of calculation:

- -Hydraulic only or thermal hydraulic with forced convection and low coupling between velocity and temperature (Boussinesq value beta low), facsec between 20-30
- -Thermal hydraulic with forced convection and strong coupling between velocity and temperature (Boussinesq value beta high), facsec between 90-100
- -Thermohydralic with natural convection, facsec around 300
- -Conduction only, facsec can be set to a very high value (1e8) as if the scheme was unconditionally stable

These values can also be used as rule of thumb for initial facsec with a facsec max limit higher.

- rapport_residus *float*: Ratio between the residual at time n and the residual at time n+1 above which the facsec is increased by multiplying by sqrt(rapport_residus) (1.2 by default).
- **nb_ite_sans_accel_max** *int*: Maximum number of iterations without facsec increases (20000 by default): if facsec does not increase with the previous condition (ration between 2 consecutive residuals too high), we increase it by force after nb ite sans accel max iterations.

3.56 End

Synonymous: fin

Description: Keyword which must complete the data file. The execution of the data file stops when reaching this keyword.

```
See also: interprete (3)

Usage: end

3.57 }

Description: Block's end.

See also: interprete (3)
```

```
Usage:
3.58
       Imprimer_flux
Description: This keyword prints the flux per face at the specified domain boundaries in the data set.
The fluxes are written to the .face files at a frequency defined by dt_impr, the evaluation printing frequency
(refer to time scheme keywords). By default, fluxes are incorporated onto the edges before being displayed.
See also: interprete (3) imprimer_flux_sum (3.60)
Usage:
imprimer_flux domain_name noms_bord
where
   • domain name str: Name of the domain.
   • noms_bord bloc_lecture (3.59): List of boundaries, for ex: { Bord1 Bord2 }
3.59
       Bloc_lecture
Description: to read between two braces
See also: objet_lecture (39) bloc_criteres_convergence (3.59.1) solveur_petsc_option_cli (3.59.2)
Usage:
bloc_lecture
where
   • bloc_lecture str
3.59.1 Bloc_criteres_convergence
Description: Not set
See also: (3.59)
Usage:
bloc_lecture
where
   • bloc lecture str
3.59.2 Solveur_petsc_option_cli
Description: solver
See also: (3.59)
```

• bloc_lecture str

Usage: **bloc_lecture** where

3.60 Imprimer_flux_sum

Description: This keyword prints the sum of the flux per face at the domain boundaries defined by the user in the data set. The fluxes are written into the .out files at a frequency defined by dt_impr, the evaluation printing frequency (refer to time scheme keywords).

3.61 Integrer_champ_med

Description: his keyword is used to calculate a flow rate from a velocity MED field read before. The method is either debit_total to calculate the flow rate on the whole surface, either integrale_en_z to calculate flow rates between z=zmin and z=zmax on nb_tranche surfaces. The output file indicates first the flow rate for the whole surface and then lists for each tranche: the height z, the surface average value, the surface area and the flow rate. For the debit_total method, only one tranche is considered. file:z Sum(u.dS)/Sum(dS) Sum(dS) Sum(u.dS)

```
See also: interprete (3)

Usage:
integrer_champ_med {
    champ_med str
    methode str into ['integrale_en_z', 'debit_total']
    [ zmin float]
    [ zmax float]
    [ nb_tranche int]
    [ fichier_sortie str]
}
where
```

- champ_med str
- **methode** *str into ['integrale_en_z', 'debit_total']*: to choose between the integral following z or over the entire height (debit_total corresponds to zmin=-DMAXFLOAT, ZMax=DMAXFLOAT, nb_tranche=1)
- zmin float
- zmax float
- nb tranche int
- fichier_sortie str: name of the output file, by default: integrale.

3.62 Interprete_geometrique_base

```
Description: Class for interpreting a data file

See also: interprete (3) Create_domain_from_sub_domain (3.1)

Usage:
interprete geometrique base
```

3.63 Lata_to_cgns

Description: To convert results file written with LATA format to CGNS file. Warning: Fields located on faces are not supported yet.

See also: interprete (3)

Usage:

lata_to_CGNS [format] file file_CGNS

where

- **format** *format_lata_to_cgns* (3.64): generated file post_CGNS.data use format (CGNS or LATA or LML keyword).
- file str: LATA file to convert to the new format.
- file_CGNS str: Name of the CGNS file.

3.64 Format_lata_to_cgns

Description: not_set

See also: objet_lecture (39)

Usage:

mot [format]

where

- mot str into ['format_post_sup']
- **format** *str into ['lml', 'lata', 'lata_v2', 'med', 'cgns']*: generated file post_CGNS.data use format (CGNS or LATA or LML keyword).

3.65 Lata_2_med

Synonymous: lata_to_med

Description: To convert results file written with LATA format to MED file. Warning: Fields located on faces are not supported yet.

See also: interprete (3)

Usage:

lata_2_med [format] file file_med

where

- **format** *format_lata_to_med* (3.66): generated file post_med.data use format (MED or LATA or LML keyword).
- file str: LATA file to convert to the new format.
- file_med str: Name of the MED file.

3.66 Format_lata_to_med

Description: not_set

See also: objet_lecture (39)

Usage:

mot [format]

where

- mot str into ['format_post_sup']
- **format** *str into ['lml', 'lata', 'lata_v2', 'med']*: generated file post_med.data use format (MED or LATA or LML keyword).

3.67 Lata_2_other

Synonymous: lata_to_other

Description: To convert results file written with LATA format to CGNS, MED or LML format. Warning: Fields located at faces are not supported yet.

See also: interprete (3)

Usage:

lata_2_other [format] file file_post

where

- **format** *str into ['lml', 'lata', 'lata_v2', 'med', 'cgns']:* Results format (CGNS, MED or LATA or LML keyword).
- file str: LATA file to convert to the new format.
- file_post str: Name of file post.

3.68 Lire_ideas

Description: Read a geom in a unv file. 3D tetra mesh elements only may be read by TRUST.

See also: interprete (3)

Usage:

lire ideas nom dom file

where

- nom_dom str: Name of domain.
- file str: Name of file.

3.69 Lml_2_lata

Synonymous: lml_to_lata

Description: To convert results file written with LML format to a single LATA file.

See also: interprete (3)

Usage:

lml_2_lata file_lml file_lata

where

- **file_lml** *str*: LML file to convert to the new format.
- file_lata str: Name of the single LATA file.

3.70 Mailler

{

```
Description: The Mailler (Mesh) interpretor allows a Domain type object domaine to be meshed with ob-
jects objet_1, objet_2, etc...
See also: interprete (3)
Usage:
mailler domaine bloc
where
   • domaine str: Name of domain.
   • bloc list_bloc_mailler (3.71): Instructions to mesh.
3.71 List_bloc_mailler
Description: List of block mesh.
See also: listobj (38.5)
Usage:
{ object1, object2.... }
list of mailler_base (3.71.1) separeted with,
3.71.1 Mailler_base
Description: Basic class to mesh.
See also: objet_lecture (39) pave (3.71.2) epsilon (3.71.12) domain (3.71.13)
Usage:
3.71.2 Pave
Description: Class to create a pave (block) with boundaries.
See also: mailler_base (3.71.1)
Usage:
pave name bloc list_bord
where
   • name str: Name of the pave (block).
   • bloc bloc_pave (3.71.3): Definition of the pave (block).
   • list_bord list_bord (3.71.4): Domain boundaries definition.
3.71.3 Bloc_pave
Description: Class to create a pave.
See also: objet_lecture (39)
Usage:
```

```
[Origine x1 \ x2 \ (x3)]
     [longueurs x1 \ x2 \ (x3)]
     [ nombre de noeuds n1 n2 (n3)]
     [ facteurs x1 x2 (x3)]
     [symx]
     [symy]
     [symz]
     [xtanh float]
     [ xtanh dilatation int into [-1, 0, 1]]
     [ xtanh_taille_premiere_maille float]
     [ytanh float]
     [ ytanh dilatation int into [-1, 0, 1]]
     [ ytanh_taille_premiere_maille float]
     [ ztanh float]
     [ ztanh dilatation int into [-1, 0, 1]]
     [ ztanh_taille_premiere_maille | float]
}
where
```

• **Origine** x1 x2 (x3): Keyword to define the pave (block) origin, that is to say one of the 8 block points (or 4 in a 2D coordinate system).

- **longueurs** $x1 \ x2 \ (x3)$: Keyword to define the block dimensions, that is to say knowing the origin, length along the axes.
- **nombre_de_noeuds** *n1 n2 (n3)*: Keyword to define the discretization (nodenumber) in each direction.
- **facteurs** x1 x2 (x3): Keyword to define stretching factors for mesh discretization in each direction. This is a real number which must be positive (by default 1.0). A stretching factor other than 1 allows refinement on one edge in one direction.
- **symx**: Keyword to define a block mesh that is symmetrical with respect to the YZ plane (respectively Y-axis in 2D) passing through the block centre.
- **symy**: Keyword to define a block mesh that is symmetrical with respect to the XZ plane (respectively X-axis in 2D) passing through the block centre.
- symz: Keyword defining a block mesh that is symmetrical with respect to the XY plane passing through the block centre.
- xtanh float: Keyword to generate mesh with tanh (hyperbolic tangent) variation in the X-direction.
- xtanh_dilatation int into [-1, 0, 1]: Keyword to generate mesh with tanh (hyperbolic tangent) variation in the X-direction. xtanh_dilatation: The value may be -1,0,1 (0 by default): 0: coarse mesh at the middle of the channel and smaller near the walls -1: coarse mesh at the left side of the channel and smaller at the right side 1: coarse mesh at the right side of the channel and smaller near the left side of the channel.
- **xtanh_taille_premiere_maille** *float*: Size of the first cell of the mesh with tanh (hyperbolic tangent) variation in the X-direction.
- ytanh float: Keyword to generate mesh with tanh (hyperbolic tangent) variation in the Y-direction.
- ytanh_dilatation int into [-1, 0, 1]: Keyword to generate mesh with tanh (hyperbolic tangent) variation in the Y-direction. ytanh_dilatation: The value may be -1,0,1 (0 by default): 0: coarse mesh at the middle of the channel and smaller near the walls -1: coarse mesh at the bottom of the channel and smaller near the top 1: coarse mesh at the top of the channel and smaller near the bottom.
- **ytanh_taille_premiere_maille** *float*: Size of the first cell of the mesh with tanh (hyperbolic tangent) variation in the Y-direction.
- **ztanh** *float*: Keyword to generate mesh with tanh (hyperbolic tangent) variation in the Z-direction.
- **ztanh_dilatation** *int into [-1, 0, 1]*: Keyword to generate mesh with tanh (hyperbolic tangent) variation in the Z-direction. tanh_dilatation: The value may be -1,0,1 (0 by default): 0: coarse mesh

at the middle of the channel and smaller near the walls -1: coarse mesh at the back of the channel and smaller near the front 1: coarse mesh at the front of the channel and smaller near the back.

• **ztanh_taille_premiere_maille** *float*: Size of the first cell of the mesh with tanh (hyperbolic tangent) variation in the Z-direction.

3.71.4 List bord

```
Description: The block sides.

See also: listobj (38.5)

Usage:
{ object1 object2 .... }
list of bord_base (3.71.5)
```

3.71.5 Bord_base

Description: Basic class for block sides. Block sides that are neither edges nor connectors are not specified. The duplicate nodes of two blocks in contact are automatically recognized and deleted.

```
See also: objet_lecture (39) raccord (3.71.6) internes (3.71.10) bord (3.71.11)
```

Usage:

3.71.6 Raccord

Description: The block side is in contact with the block of another domain (case of two coupled problems).

```
See also: bord_base (3.71.5)
```

Usage:

raccord type1 type2 nom defbord

where

- type1 str into ['local', 'distant']: Contact type.
- type2 str into ['homogene']: Contact type.
- nom str: Name of block side.
- **defbord** *defbord* (3.71.7): Definition of block side.

3.71.7 Defbord

```
Description: Class to define an edge.
```

```
See also: objet_lecture (39) defbord_2 (3.71.8) defbord_3 (3.71.9)
```

Usage:

3.71.8 **Defbord_2**

```
Description: 1-D edge (straight line) in the 2-D space.
```

```
See also: (3.71.7)
```

Usage:

dir eq pos pos2_min inf1 dir2 inf2 pos2_max where

- **dir** str into ['X', 'Y']: Edge is perpendicular to this direction.
- eq str into ['=']: Equality sign.
- pos float: Position value.
- pos2_min *float*: Minimal value.
- inf1 str into ['<=']: Less than or equal to sign.
- dir2 str into ['X', 'Y']: Edge is parallel to this direction.
- inf2 str into ['<=']: Less than or equal to sign.
- pos2_max float: Maximal value.

3.71.9 Defbord_3

Description: 2-D edge (plane) in the 3-D space.

See also: (3.71.7)

Usage:

dir eq pos pos2_min inf1 dir2 inf2 pos2_max pos3_min inf3 dir3 inf4 pos3_max where

- dir str into ['X', 'Y', 'Z']: Edge is perpendicular to this direction.
- eq str into ['=']: Equality sign.
- pos float: Position value.
- pos2_min *float*: Minimal value.
- inf1 str into ['<=']: Less than or equal to sign.
- **dir2** *str into* ['X', 'Y']: Edge is parallel to this direction.
- inf2 str into ['<=']: Less than or equal to sign.
- pos2_max float: Maximal value.
- pos3_min float: Minimal value.
- inf3 str into ['<=']: Less than or equal to sign.
- dir3 str into ['Y', 'Z']: Edge is parallel to this direction.
- inf4 str into ['<=']: Less than or equal to sign.
- pos3_max *float*: Maximal value.

3.71.10 Internes

Description: To indicate that the block has a set of internal faces (these faces will be duplicated automatically by the program and will be processed in a manner similar to edge faces).

Two boundaries with the same boundary conditions may have the same name (whether or not they belong to the same block).

The keyword Internes (Internal) must be used to execute a calculation with plates, followed by the equation of the surface area covered by the plates.

See also: bord_base (3.71.5)

Usage:

internes nom defbord

where

- nom str: Name of block side.
- **defbord** *defbord* (3.71.7): Definition of block side.

3.71.11 Bord

Description: The block side is not in contact with another block and boundary conditions are applied to it.

```
See also: bord_base (3.71.5)

Usage:
bord nom defbord
where
```

- nom str: Name of block side.
- **defbord** *defbord* (3.71.7): Definition of block side.

3.71.12 **Epsilon**

Description: Two points will be confused if the distance between them is less than eps. By default, eps is set to 1e-12. The keyword Epsilon allows an alternative value to be assigned to eps.

```
See also: mailler_base (3.71.1)

Usage: epsilon eps
where
```

• eps float: New value of precision.

3.71.13 Domain

Description: Class to reuse a domain.

```
See also: mailler base (3.71.1)
```

Usage:

domain domain_name where

• domain_name str: Name of domain.

3.72 Maillerparallel

Description: creates a parallel distributed hexaedral mesh of a parallelipipedic box. It is equivalent to creating a mesh with a single Pave, splitting it with Decouper and reloading it in parallel with Scatter. It only works in 3D at this time. It can also be used for a sequential computation (with all NPARTS=1)}

```
See also: interprete (3)

Usage:
maillerparallel {

domain str
nb_nodes n n1 n2 ... nn
splitting n n1 n2 ... nn
ghost_thickness int
```

```
[perio_x]
     [perio_y]
     [perio z ]
     [function_coord_x str]
     [function coord y str]
     [function_coord_z str]
     [ file coord x str]
     [ file coord y str]
     [ file coord z str]
     [boundary xmin str]
     [boundary xmax str]
     [boundary_ymin str]
     [boundary_ymax str]
     [boundary_zmin str]
     [boundary_zmax str]
}
where
```

• **domain** str: the name of the domain to mesh (it must be an empty domain object).

- **nb_nodes** *n n1 n2* ... *nn*: dimension defines the spatial dimension (currently only dimension=3 is supported), and nX, nY and nZ defines the total number of nodes in the mesh in each direction.
- **splitting** *n n1 n2 ... nn*: dimension is the spatial dimension and npartsX, npartsY and npartsZ are the number of parts created. The product of the number of parts must be equal to the number of processors used for the computation.
- **ghost_thickness** *int*: the number of ghost cells (equivalent to the epaisseur_joint parameter of Decouper.
- perio_x : change the splitting method to provide a valid mesh for periodic boundary conditions.
- perio_y : change the splitting method to provide a valid mesh for periodic boundary conditions.
- perio_z : change the splitting method to provide a valid mesh for periodic boundary conditions.
- function_coord_x str: By default, the meshing algorithm creates nX nY nZ coordinates ranging between 0 and 1 (eg a unity size box). If function_coord_x} is specified, it is used to transform the [0,1] segment to the coordinates of the nodes. funcX must be a function of the x variable only.
- **function_coord_y** *str*: like function_coord_x for y
- function_coord_z str: like function_coord_x for z
- file_coord_x str: Keyword to read the Nx floating point values used as nodes coordinates in the file.

```
• file coord v str: idem file coord x for y
```

- **file_coord_z** *str*: idem file_coord_x for z
- **boundary_xmin** *str*: the name of the boundary at the minimum X direction. If it not provided, the default boundary names are xmin, xmax, ymin, ymax, zmin and zmax. If the mesh is periodic in a given direction, only the MIN boundary name is used, for both sides of the box.

```
• boundary_xmax str
```

- boundary_ymin str
- boundary ymax str
- boundary zmin str
- boundary_zmax str

3.73 Mass_source

Description: Mass source used in a dilatable simulation to add/reduce a mass at the boundary (volumetric source in the first cell of a given boundary).

See also: interprete (3)

```
Usage:
mass_source {
    bord str
    surfacic_flux champ_front_base
}
where
```

- bord str: Name of the boundary where the source term is applied
- **surfacic_flux** *champ_front_base* (17.1): The boundary field that the user likes to apply: for example, champ_front_uniforme, ch_front_input_uniform or champ_front_fonc_t

3.74 Mkdir

Description: equivalent to system mkdir

See also: interprete (3)

Usage:

mkdir directory

where

• directory str: directory to create

3.75 Modif_bord_to_raccord

Description: Keyword to convert a boundary of domain_name domain of kind Bord to a boundary of kind Raccord (named boundary_name). It is useful when using meshes with boundaries of kind Bord defined and to run a coupled calculation.

See also: interprete (3)

Usage:

modif_bord_to_raccord domaine nom_bord where

- domaine str: Name of domain
- **nom_bord** *str*: Name of the boundary to transform.

3.76 Modifydomaineaxi1d

Description: Convert a 1D mesh to 1D axisymmetric mesh

See also: interprete (3)

Usage:

modifydomaineAxi1d dom bloc

where

- dom str
- bloc bloc_lecture (3.59)

3.77 Moyenne_volumique

Description: This keyword should be used after Resoudre keyword. It computes the convolution product of one or more fields with a given filtering function.

```
See also: interprete (3)

Usage:
moyenne_volumique {
    nom_pb str
    nom_domaine str
    noms_champs n word1 word2 ... wordn
    [format_post str]
    [nom_fichier_post str]
    fonction_filtre bloc_lecture
    [localisation str into ['elem', 'som']]
}
where
```

- **nom pb** *str*: name of the problem where the source fields will be searched.
- **nom_domaine** *str*: name of the destination domain (for example, it can be a coarser mesh, but for optimal performance in parallel, the domain should be split with the same algorithm as the computation mesh, eg, same tranche parameters for example)
- **noms_champs** *n word1 word2 ... wordn*: name of the source fields (these fields must be accessible from the postraitement) N source field1 source field2 ... source fieldN
- **format post** str: gives the fileformat for the result (by default : lata)
- **nom_fichier_post** *str*: indicates the filename where the result is written
- **fonction_filtre** *bloc_lecture* (3.59): to specify the given filter

```
Fonction_filtre {
type filter_type
demie-largeur l
[ omega w ]
[ expression string ]
```

type filter_type: This parameter specifies the filtering function. Valid filter_type are:

```
Boite is a box filter, f(x, y, z) = (abs(x) < l) * (abs(y) < l) * (abs(z) < l)/(8l^3)
```

Chapeau is a hat filter (product of hat filters in each direction) centered on the origin, the half-width of the filter being 1 and its integral being 1.

Quadra is a 2nd order filter.

Gaussienne is a normalized gaussian filter of standard deviation sigma in each direction (all field elements outside a cubic box defined by clipping_half_width are ignored, hence, taking clipping_half_width=2.5*sigma yields an integral of 0.99 for a uniform unity field).

Parser allows a user defined function of the x,y,z variables. All elements outside a cubic box defined by clipping_half_width are ignored. The parser is much slower than the equivalent c++ coded function...

demie-largeur 1: This parameter specifies the half width of the filter

[omega w] : This parameter must be given for the gaussienne filter. It defines the standard deviation of the gaussian filter.

[expression string]: This parameter must be given for the parser filter type. This expression will be interpreted by the math parser with the predefined variables x, y and z.

• **localisation** *str into ['elem', 'som']*: indicates where the convolution product should be computed: either on the elements or on the nodes of the destination domain.

3.78 Multigrid_solver

Description: Object defining a multigrid solver in IJK discretization

```
Usage:
multigrid_solver {

    [coarsen_operators coarsen_operators]
    [ghost_size int]
    [relax_jacobi n x1 x2 ... xn]
    [pre_smooth_steps n n1 n2 ... nn]
    [smooth_steps n n1 n2 ... nn]
    [nb_full_mg_steps n n1 n2 ... nn]
    [solveur_grossier solveur_sys_base]
    [seuil float]
    [impr ]
    [solver_precision str into ['mixed', 'double']]
    [iterations_mixed_solver int]
}
where
```

- **coarsen_operators** *coarsen_operators* (3.79): Definition of the number of grids that will be used, in addition to the finest (original) grid, followed by the list of the coarsen operators that will be applied to get those grids
- ghost_size int: Number of ghost cells known by each processor in each of the three directions
- **relax_jacobi** n x1 x2 ... xn: Parameter between 0 and 1 that will be used in the Jacobi method to solve equation on each grid. Should be around 0.7
- **pre_smooth_steps** *n n1 n2* ... *nn*: First integer of the list indicates the numbers of integers that has to be read next. Following integers define the numbers of iterations done before solving the equation on each grid. For example, 2 7 8 means that we have a list of 2 integers, the first one tells us to perform 7 pre-smooth steps on the first grid, the second one tells us to perform 8 pre-smooth steps on the second grid. If there are more than 2 grids in the solver, then the remaining ones will have as many pre-smooth steps as the last mentionned number (here, 8)
- **smooth_steps** *n n1 n2 ... nn*: First integer of the list indicates the numbers of integers that has to be read next. Following integers define the numbers of iterations done after solving the equation on each grid. Same behavior as pre smooth steps
- **nb_full_mg_steps** *n n1 n2 ... nn*: Number of multigrid iterations at each level
- **solveur_grossier** *solveur_sys_base* (11.16): Name of the iterative solver that will be used to solve the system on the coarsest grid. This resolution must be more precise than the ones occurring on the fine grids. The threshold of this solver must therefore be lower than seuil defined above.
- **seuil** *float*: Define an upper bound on the norm of the final residue (i.e. the one obtained after applying the multigrid solver). With hybrid precision, as long as we have not obtained a residue whose norm is lower than the imposed threshold, we keep applying the solver
- impr : Flag to display some info on the resolution on eahc grid
- **solver_precision** *str into ['mixed', 'double']*: Precision with which the variables at stake during the resolution of the system will be stored. We can have a simple or floattant precision or both. In the case of a hybrid precision, the multigrid solver is launched in simple precision, but the residual is calculated in floattant precision.
- iterations_mixed_solver int: Define the maximum number of iterations in mixed precision solver

3.79 Coarsen_operators

```
Description: not_set

See also: listobj (38.5)

Usage:
n object1 object2 ....
list of coarsen operator uniform (3.79.1)
```

3.79.1 Coarsen_operator_uniform

Description: Object defining the uniform coarsening process of the given grid in IJK discretization

```
See also: objet_lecture (39)
```

Usage:

```
[ Coarsen_Operator_Uniform ] aco [ coarsen_i ] [ coarsen_i_val ] [ coarsen_j ] [ coarsen_j_val ] [ coarsen_k ] [ coarsen_k_val ] acof where
```

- Coarsen_Operator_Uniform str
- aco str into ['{'}]: opening curly brace
- coarsen_i str into ['coarsen_i']
- **coarsen_i_val** int: Integer indicating the number by which we will divide the number of elements in the I direction (in order to obtain a coarser grid)
- coarsen_j str into ['coarsen_j']
- coarsen_j_val int: Integer indicating the number by which we will divide the number of elements in the J direction (in order to obtain a coarser grid)
- coarsen_k str into ['coarsen_k']
- coarsen_k_val int: Integer indicating the number by which we will divide the number of elements in the K direction (in order to obtain a coarser grid)
- acof str into [']': closing curly brace

3.80 Nettoiepasnoeuds

Description: Keyword NettoiePasNoeuds does not delete useless nodes (nodes without elements) from a domain.

```
See also: interprete (3)
```

Usage:

nettoiepasnoeuds domain_name

where

• domain_name str: Name of domain.

3.81 Option_vdf

Description: Class of VDF options.

See also: interprete (3)

Usage:

```
option_vdf {
    [ traitement_coins str into ['oui', 'non']]
    [ traitement_gradients str into ['oui', 'non']]
    [ p_imposee_aux_faces str into ['oui', 'non']]
    [ toutes_les_options|all_options ]
}
where
```

- **traitement_coins** *str into ['oui', 'non']*: Treatment of corners (yes or no). This option modifies slightly the calculations at the outlet of the plane channel. It supposes that the boundary continues after channel outlet (i.e. velocity vector remains parallel to the boundary).
- **traitement_gradients** *str into ['oui', 'non']*: Treatment of gradient calculations (yes or no). This option modifies slightly the gradient calculation at the corners and activates also the corner treatment option.
- p_imposee_aux_faces str into ['oui', 'non']: Pressure imposed at the faces (yes or no).
- **toutes_les_options**lall_**options**: Activates all Option_VDF options. If used, must be used alone without specifying the other options, nor combinations.

3.82 Orientefacesbord

Description: Keyword to modify the order of the boundary vertices included in a domain, such that the surface normals are outer pointing.

See also: interprete (3)

Usage:

orientefacesbord domain_name

where

• domain name str: Name of domain.

3.83 Partition

Synonymous: decouper

Description: Class for parallel calculation to cut a domain for each processor. By default, this keyword is commented in the reference test cases.

See also: interprete (3)

Usage:

partition domaine bloc_decouper

where

- domaine str: Name of the domain to be cut.
- bloc_decouper bloc_decouper (3.84): Description how to cut a domain.

3.84 Bloc_decouper

Description: Auxiliary class to cut a domain.

See also: objet_lecture (39)

```
Usage:

[ Partition_toollpartitionneur partitionneur_deriv]

[ larg_joint int]
[ nom_zones str]
[ ecrire_decoupage str]
[ ecrire_lata str]
[ ecrire_med str]
[ nb_parts_tot int]
[ periodique n word1 word2 ... wordn]
[ reorder int]
[ single_hdf ]
[ print_more_infos int]

}

where
```

- **Partition_toollpartitionneur** *partitionneur_deriv* (26): Defines the partitionning algorithm (the effective C++ object used is 'Partitionneur_ALGORITHM_NAME').
- larg_joint int: This keyword specifies the thickness of the virtual ghost domaine (data known by one processor though not owned by it). The default value is 1 and is generally correct for all algorithms except the QUICK convection scheme that require a thickness of 2. Since the 1.5.5 version, the VEF discretization imply also a thickness of 2 (except VEF P0). Any non-zero positive value can be used, but the amount of data to store and exchange between processors grows quickly with the thickness.
- nom_zones str: Name of the files containing the different partition of the domain. The files will be

```
name_0001.Zones
name_0002.Zones
```

..

name_000n.Zones. If this keyword is not specified, the geometry is not written on disk (you might just want to generate a 'ecrire_decoupage' or 'ecrire_lata').

- ecrire_decoupage str: After having called the partitionning algorithm, the resulting partition is written on disk in the specified filename. See also partitionneur Fichier_Decoupage. This keyword is useful to change the partition numbers: first, you write the partition into a file with the option ecrire_decoupage. This file contains the domaine number for each element's mesh. Then you can easily permute domaine numbers in this file. Then read the new partition to create the .Zones files with the Fichier_Decoupage keyword.
- ecrire lata str: Save the partition field in a LATA format file for visualization
- ecrire_med str: Save the partition field in a MED format file for visualization
- **nb_parts_tot** *int*: Keyword to generates N .Domaine files, instead of the default number M obtained after the partitionning algorithm. N must be greater or equal to M. This option might be used to perform coupled parallel computations. Supplemental empty domaines from M to N-1 are created. This keyword is used when you want to run a parallel calculation on several domains with for example, 2 processors on a first domain and 10 on the second domain because the first domain is very small compare to second one. You will write Nb_parts 2 and Nb_parts_tot 10 for the first domain and Nb_parts 10 for the second domain.
- **periodique** *n word1 word2* ... *wordn*: N BOUNDARY_NAME_1 BOUNDARY_NAME_2 ... : N is the number of boundary names given. Periodic boundaries must be declared by this method. The partitionning algorithm will ensure that facing nodes and faces in the periodic boundaries are located on the same processor.
- **reorder** *int*: If this option is set to 1 (0 by default), the partition is renumbered in order that the processes which communicate the most are nearer on the network. This may slighly improves parallel performance.

- **single_hdf**: Optional keyword to enable you to write the partitioned domaines in a single file in hdf5 format.
- **print_more_infos** *int*: If this option is set to 1 (0 by default), print infos about number of remote elements (ghosts) and additional infos about the quality of partitionning. Warning, it slows down the cutting operations.

3.85 Partition_multi

Synonymous: decouper_multi

Description: allows to partition multiple domains in contact with each other in parallel: necessary for resolution monolithique in implicit schemes and for all coupled problems using PolyMAC_P0P1NC. By default, this keyword is commented in the reference test cases.

See also: interprete (3)

Usage:

partition_multi aco domaine1 dom blocdecoupdom1 domaine2 dom2 blocdecoupdom2 acof where

- aco str into ['{'}: Opening curly bracket.
- domaine1 str into ['domaine']: not set.
- dom str: Name of the first domain to be cut.
- **blocdecoupdom1** *bloc_decouper* (3.84): *Partition bloc for the first domain.*
- domaine2 str into ['domaine']: not set.
- dom2 str: Name of the second domain to be cut.
- **blocdecoupdom2** *bloc_decouper* (3.84): *Partition bloc for the second domain.*
- acof str into ['}']: Closing curly bracket.

3.86 Pilote_icoco

```
Description: not_set

See also: interprete (3)

Usage:
pilote_icoco {
    pb_name str
    main str

}
where

• pb_name str

• main str
```

3.87 Polyedriser

Description: cast hexahedra into polyhedra so that the indexing of the mesh vertices is compatible with PolyMAC_P0P1NC discretization. Must be used in PolyMAC_P0P1NC discretization if a hexahedral mesh has been produced with TRUST's internal mesh generator.

```
See also: interprete (3)

Usage:
polyedriser domain_name
where

• domain name str: Name of domain.
```

3.88 Postraiter_domaine

Description: To write one or more domains in a file with a specified format (MED,LML,LATA,SINGLE_LATA,CGNS).

```
See also: interprete (3)

Usage:
postraiter_domaine {
    format    str into ['lml', 'lata', 'single_lata', 'lata_v2', 'med', 'cgns']
        [ binaire    int into [0, 1]]
        [ ecrire_frontiere    int into [0, 1]]
        [ dual    int into [0, 1]]
        [ filelfichier    str]
        [ joints_non_postraites    int into [0, 1]]
        [ domainldomaine    str]
        [ domaines    bloc_lecture]
}
where
```

- format str into ['lml', 'lata', 'single_lata', 'lata_v2', 'med', 'cgns']: File format.
- **binaire** *int into* [0, 1]: Binary (binaire 1) or ASCII (binaire 0) may be used. By default, it is 0 for LATA and only ASCII is available for LML and only binary is available for MED.
- **ecrire_frontiere** *int into* [0, 1]: This option will write (if set to 1, the default) or not (if set to 0) the boundaries as fields into the file (it is useful to not add the boundaries when writing a domain extracted from another domain)
- **dual** *int into* [0, 1]: This option indicates whether the original mesh (default) or the dual one (the one used for postprocessing of field faces) is to be written.
- **filelfichier** *str*: The file name can be changed with the fichier option.
- **joints_non_postraites** *int into [0, 1]*: The joints_non_postraites (1 by default) will not write the boundaries between the partitioned mesh.
- domainldomaine str: Name of domain
- **domaines** *bloc_lecture* (3.59): Names of domains : { name1 name2 }

3.89 Precisiongeom

Description: Class to change the way floating-point number comparison is done. By default, two numbers are equal if their absolute difference is smaller than 1e-10. The keyword is useful to modify this value. Moreover, nodes coordinates will be written in .geom files with this same precision.


```
See also: interprete (3)


Usage: precisiongeom precision where
```

• **precision** *float*: New value of precision.

3.90 Raffiner_anisotrope

Description: Only for VEF discretizations, allows to cut triangle elements in 3, or tetrahedra in 4 parts, by defining a new summit located at the center of the element:





Note that such a cut creates flat elements (anisotropic).

See also: interprete (3)

Usage:

raffiner_anisotrope domain_name where


• domain_name str: Name of domain.

3.91 Raffiner_isotrope

Synonymous: raffiner_simplexes

Description: For VDF and VEF discretizations, allows to cut triangles/quadrangles or tetrahedral/hexaedras elements respectively in 4 or 8 new ones by defining new summits located at the middle of edges (and center of faces and elements for quadrangles and hexaedra). Such a cut preserves the shape of original elements (isotropic). For 2D elements:

For 3D elements:



See also: interprete (3)

Usage:

raffiner_isotrope domain_name

where

• domain_name str: Name of domain.

3.92 Read

Synonymous: lire

Description: Interpretor to read the a_object objet defined between the braces.

See also: interprete (3)

Usage:

read a_object bloc

where

• **a_object** *str*: Object to be read.

• bloc str: Definition of the object.

3.93 Read file

Synonymous: lire_fichier

Description: Keyword to read the object name_obj contained in the file filename.

This is notably used when the calculation domain has already been meshed and the mesh contains the file filename, simply write read_file dom filename (where dom is the name of the meshed domain).

If the filename is ;, is to execute a data set given in the file of name name_obj (a space must be entered between the semi-colon and the file name).

See also: interprete (3) read_unsupported_ascii_file_from_icem (3.96) read_file_binary (3.94)

Usage:

read_file name_obj filename

where

• name_obj str: Name of the object to be read.

• filename str: Name of the file.

3.94 Read_file_binary

Synonymous: lire_fichier_bin

Description: Keyword to read an object name_obj in the unformatted type file filename.

See also: read_file (3.93)

Usage:

read_file_binary name_obj filename

where

- name obj str: Name of the object to be read.
- **filename** *str*: Name of the file.

3.95 Lire tgrid

Description: Keyword to reaf Tgrid/Gambit mesh files. 2D (triangles or quadrangles) and 3D (tetra or hexa elements) meshes, may be read by TRUST.

See also: interprete (3)

Usage:

lire_tgrid dom filename

where

- dom str: Name of domaine.
- filename str: Name of file containing the mesh.

3.96 Read_unsupported_ascii_file_from_icem

Description: not_set

See also: read_file (3.93)

Usage:

 $read_unsupported_ascii_file_from_icem \quad name_obj \quad filename$

where

• name_obj str: Name of the object to be read.

• filename str: Name of the file.

3.97 Orienter_simplexes

Synonymous: rectify_mesh

Description: Keyword to raffine a mesh

See also: interprete (3)

Usage:

orienter_simplexes domain_name

where

• domain_name str: Name of domain.

3.98 Redresser_hexaedres_vdf

Description: Keyword to convert a domain (named domain_name) with quadrilaterals/VEF hexaedras which looks like rectangles/VDF hexaedras into a domain with real rectangles/VDF hexaedras.

See also: interprete (3)

Usage:

redresser_hexaedres_vdf domain_name

where

• domain name str: Name of domain to resequence.

3.99 Refine mesh

Description: not_set

See also: interprete (3)

Usage:

refine_mesh domaine

where

• domaine str

3.100 Regroupebord

Description: Keyword to build one boundary new_bord with several boundaries of the domain named domaine.

See also: interprete (3)

Usage:

regroupebord domaine new_bord bords where

• domaine str: Name of domain

• **new_bord** *str*: Name of the new boundary


• **bords** *bloc_lecture* (3.59): { Bound1 Bound2 }

3.101 Remove_elem

Description: Keyword to remove element from a VDF mesh (named domaine_name), either from an explicit list of elements or from a geometric condition defined by a condition f(x,y)>0 in 2D and f(x,y,z)>0 in 3D. All the new borders generated are gathered in one boundary called: newBord (to rename it, use RegroupeBord keyword. To split it to different boundaries, use DecoupeBord_Pour_Rayonnement keyword). Example of a removed zone of radius 0.2 centered at (x,y)=(0.5,0.5):

Remove_elem dom { fonction $0.2 * 0.2 - (x - 0.5)^2 - (y - 0.5)^2 > 0$ }

Warning: the thickness of removed zone has to be large enough to avoid singular nodes as decribed below:



See also: interprete (3)

Usage:

remove_elem domaine bloc where

- **domaine** *str*: Name of domain
- **bloc** remove_elem_bloc (3.102)

3.102 Remove_elem_bloc

Description: not_set

```
See also: objet_lecture (39)

Usage:
{
    [liste n n1 n2 ... nn]
    [fonction str]
}
where
• liste n n1 n2 ... nn
```

• fonction str

3.103 Remove_invalid_internal_boundaries

Description: Keyword to suppress an internal boundary of the domain_name domain. Indeed, some mesh tools may define internal boundaries (eg: for post processing task after the calculation) but TRUST does not support it yet.

See also: interprete (3)

Usage:

 $remove_invalid_internal_boundaries \quad domain_name$

where

• domain_name str: Name of domain.

3.104 Reorienter_tetraedres

Description: This keyword is mandatory for front-tracking computations with the VEF discretization. For each tetrahedral element of the domain, it checks if it has a positive volume. If the volume (determinant of the three vectors) is negative, it swaps two nodes to reverse the orientation of this tetrahedron.

See also: interprete (3)

Usage

reorienter_tetraedres domain_name where

• domain_name str: Name of domain.

3.105 Reorienter_triangles

Description: not_set

See also: interprete (3)

Usage:
reorienter_triangles domain_name

where

• domain_name str: Name of domain.

3.106 Reordonner

Description: The Reordonner_32_64 interpretor is required sometimes for a VDF mesh which is not produced by the internal mesher. Example where this is used:

Read_file dom fichier.geom

Reordonner_32_64 dom

Observations: This keyword is redundant when the mesh that is read is correctly sequenced in the TRUST sense. This significant mesh operation may take some time... The message returned by TRUST is not explicit when the Reordonner 32 64 (Resequencing) keyword is required but not included in the data set...

See also: interprete (3)

Usage:

reordonner domain_name

where

• domain_name str: Name of domain to resequence.

3.107 Residuals

Description: To specify how the residuals will be computed.

```
See also: interprete (3)

Usage:
residuals {
    [norm str into ['L2', 'max']]
    [relative str into ['0', '1', '2']]
}
where
```

- **norm** *str into ['L2', 'max']*: allows to choose the norm we want to use (max norm by default). Possible to specify L2-norm.
- **relative** *str into ['0', '1', '2']*: This is the old keyword seuil_statio_relatif_deconseille. If it is set to 1, it will normalize the residuals with the residuals of the first 5 timesteps (default is 0). if set to 2, residual will be computed as R/(max-min).

3.108 Rotation

Description: Keyword to rotate the geometry of an arbitrary angle around an axis aligned with Ox, Oy or Oz axis.

See also: interprete (3)

Usage:

rotation domain_name dir coord1 coord2 angle where

- **domain_name** str: Name of domain to wich the transformation is applied.
- dir str into ['X', 'Y', 'Z']: X, Y or Z to indicate the direction of the rotation axis
- **coord1** *float*: coordinates of the center of rotation in the plane orthogonal to the rotation axis. These coordinates must be specified in the direct triad sense.
- coord2 float
- angle *float*: angle of rotation (in degrees)

3.109 Scatter

Description: Class to read a partionned mesh from the files during a parallel calculation. The files are in binary format.

See also: interprete (3) scattermed (3.110)

Usage:

scatter file domaine

where

• file str: Name of file.

• domaine str: Name of domain.

3.110 Scattermed

Description: This keyword will read the partition of the domain_name domain into a the MED format files file.med created by Medsplitter.

See also: scatter (3.109)

Usage:

scattermed file domaine

where

• file str: Name of file.

• domaine str: Name of domain.

3.111 Solve

Synonymous: resoudre

Description: Interpretor to start calculation with TRUST.

Keyword Discretize should have already been used to read the object.

See also: interprete (3)

Usage:

solve pb

where

• **pb** *str*: Name of problem to be solved.

3.112 Stat_per_proc_perf_log

Description: Keyword allowing to activate the detailed statistics per processor (by default this is false, and only the master proc will produce stats).

See also: interprete (3)

Usage:

$stat_per_proc_perf_log \ flg$

where

• flg int: A rien that can be either 0 or 1 to turn off (default) or on the detailed stats.

3.113 Supprime_bord

Description: Keyword to remove boundaries (named Boundary_name1 Boundary_name2) of the domain named domain_name.

```
See also: interprete (3)

Usage:
supprime_bord domaine bords
where

• domaine str: Name of domain
• bords list_nom (3.114): { Boundary_name1 Boundaray_name2 }
```

3.114 List_nom

```
Description: List of name.

See also: listobj (38.5)

Usage:
{ object1 object2 .... }
list of nom_anonyme (25.1)
```

3.115 System

Description: To run Unix commands from the data file. Example: System 'echo The End | mail trust@cea.fr'

```
See also: interprete (3)
Usage:
system cmd
```

where

• cmd str: command to execute.

3.116 Test_solveur

```
Description: To test several solvers

See also: interprete (3)

Usage:
test_solveur {

    [fichier_secmem str]
    [fichier_matrice str]
    [fichier_solution str]
    [nb_test int]
    [impr ]
    [solveur solveur_sys_base]
    [fichier_solveur str]
```

[genere_fichier_solveur float]

```
[ seuil_verification float]
        [ pas_de_solution_initiale ]
        [ ascii ]
}
where
```

- fichier_secmem str: Filename containing the second member B
- fichier_matrice str: Filename containing the matrix A
- fichier solution str: Filename containing the solution x
- **nb test** int: Number of tests to measure the time resolution (one preconditionnement)
- impr : To print the convergence solver
- solveur solveur_sys_base (11.16): To specify a solver
- fichier_solveur str: To specify a file containing a list of solvers
- genere_fichier_solveur float: To create a file of the solver with a threshold convergence
- **seuil_verification** *float*: Check if the solution satisfy ||Ax-B||precision
- pas_de_solution_initiale : Resolution isn't initialized with the solution x
- ascii : Ascii files

3.117 Testeur

```
Description: not_set

See also: interprete (3)

Usage:
testeur data
where

• data bloc_lecture (3.59)
```

3.118 Testeur_medcoupling

```
Description: not_set

See also: interprete (3)

Usage: testeur_medcoupling pb_name field_name where

• pb_name str: Name of domain.
```


• field_name str: Name of domain.

3.119 Tetraedriser

Description: To achieve a tetrahedral mesh based on a mesh comprising blocks, the Tetrahedralise) interpretor is used in VEF discretization. Initial block is divided in 6 tetrahedra:

```
See also: interprete (3) tetraedriser_homogene_fin (3.122) tetraedriser_homogene_compact (3.121) tetraedriser_homogene (3.120) tetraedriser_par_prisme (3.123)
```

Usage:




tetraedriser domain_name where

• domain_name str: Name of domain.

3.120 Tetraedriser_homogene

Description: Use the Tetraedriser_homogene (Homogeneous_Tetrahedralisation) interpretor in VEF discretization to mesh a block in tetrahedrals. Each block hexahedral is no longer divided into 6 tetrahedrals (keyword Tetraedriser (Tetrahedralise)), it is now broken down into 40 tetrahedrals. Thus a block defined with 11 nodes in each X, Y, Z direction will contain 10*10*10*40=40,000 tetrahedrals. This also allows problems in the mesh corners with the P1NC/P1iso/P1bulle or P1/P1 discretization items to be avoided. Initial block is divided in 40 tetrahedra:



See also: tetraedriser (3.119)

Usage:


tetraedriser_homogene domain_name where

• domain_name str: Name of domain.

3.121 Tetraedriser_homogene_compact

Description: This new discretization generates tetrahedral elements from cartesian or non-cartesian hexahedral elements. The process cut each hexahedral in 6 pyramids, each of them being cut then in 4 tetrahedral.

So, in comparison with tetra_homogene, less elements (*24 instead of*40) with more homogeneous volumes are generated. Moreover, this process is done in a faster way. Initial block is divided in 24 tetrahedra:



See also: tetraedriser (3.119)

Usage:


tetraedriser_homogene_compact domain_name where

• domain_name str: Name of domain.

3.122 Tetraedriser_homogene_fin

Description: Tetraedriser_homogene_fin is the recommended option to tetrahedralise blocks. As an extension (subdivision) of Tetraedriser_homogene_compact, this last one cut each initial block in 48 tetrahedra (against 24, previously). This cutting ensures:

- a correct cutting in the corners (in respect to pressure discretization PreP1B),
- a better isotropy of elements than with Tetraedriser_homogene_compact,
- a better alignment of summits (this could have a benefit effect on calculation near walls since first elements in contact with it are all contained in the same constant thickness and ii/ by the way, a 3D cartesian grid based on summits can be engendered and used to realise spectral analysis in HIT for instance). Initial block is divided in 48 tetrahedra:



See also: tetraedriser (3.119)


Usage:


tetraedriser_homogene_fin domain_name where

• domain_name str: Name of domain.

3.123 Tetraedriser_par_prisme

Description: Tetraedriser_par_prisme generates 6 iso-volume tetrahedral element from primary hexahedral one (contrarily to the 5 elements ordinarily generated by tetraedriser). This element is suitable for calculation of gradients at the summit (coincident with the gravity centre of the jointed elements related with) and spectra (due to a better alignment of the points).





Initial block is divided in 6 prismes.

See also: tetraedriser (3.119)

Usage:

tetraedriser_par_prisme domain_name where

• **domain_name** *str*: Name of domain.

3.124 Transformer

Description: Keyword to transform the coordinates of the geometry.

Exemple to rotate your mesh by a 90o rotation and to scale the z coordinates by a factor 2: Transformer domain_name -y -x 2*z

See also: interprete (3)

Usage:

transformer domain_name formule


where

- domain_name str: Name of domain.
- **formule** *word1 word2 (word3)*: Function_for_x Function_for_y

 $Function_forz$

3.125 Trianguler

Description: To achieve a triangular mesh from a mesh comprising rectangles (2 triangles per rectangle). Should be used in VEF discretization. Principle:



See also: interprete (3) trianguler_h (3.127) trianguler_fin (3.126)

Usage:

trianguler domain name

where


• domain_name str: Name of domain.

3.126 Trianguler fin

Description: Trianguler_fin is the recommended option to triangulate rectangles.

As an extension (subdivision) of Triangulate_h option, this one cut each initial rectangle in 8 triangles (against 4, previously). This cutting ensures :

- a correct cutting in the corners (in respect to pressure discretization PreP1B).
- a better isotropy of elements than with Trianguler_h option.
- a better alignment of summits (this could have a benefit effect on calculation near walls since first elements in contact with it are all contained in the same constant thickness, and, by this way, a 2D cartesian grid based on summits can be engendered and used to realize statistical analysis in plane channel configuration for instance). Principle:



See also: trianguler (3.125)

Usage:


 $trianguler_fin \quad domain_name$

where

• domain_name str: Name of domain.

3.127 Trianguler_h

Description: To achieve a triangular mesh from a mesh comprising rectangles (4 triangles per rectangle). Should be used in VEF discretization. Principle:



See also: trianguler (3.125)

Usage:

trianguler_h domain_name

where

• **domain_name** *str*: Name of domain.

3.128 Verifier_qualite_raffinements

Description: not_set

See also: interprete (3)

Usage:

 $verifier_qualite_raffinements \quad domain_names$

• domain_names vect_nom (3.129)

3.129 Vect_nom

```
Description: Vect of name.

See also: listobj (38.5)

Usage:
n object1 object2 ....
list of nom_anonyme (25.1)

3.130 Verifier_simplexes

Description: Keyword to raffine a simplexes

See also: interprete (3)

Usage:
verifier_simplexes domain_name
where
```

• domain_name str: Name of domain.

3.131 Verifiercoin

Description: This keyword subdivides inconsistent 2D/3D cells used with VEFPreP1B discretization. Must be used before the mesh is discretized. The Read_file option can be used only if the file.decoupage_som was previously created by TRUST. This option, only in 2D, reverses the common face at two cells (at least one is inconsistent), through the nodes opposed. In 3D, the option has no effect.

The expert_only option deactivates, into the VEFPreP1B divergence operator, the test of inconsistent cells.

```
Usage:
verifiercoin domain_name bloc
where

• domain_name str: Name of the domaine
• bloc verifiercoin_bloc (3.132)

3.132 Verifiercoin_bloc

Description: not_set

See also: objet_lecture (39)

Usage:
{

[Lire fichier|Read file str]
```

[expert_only]

```
}
where
   • Lire_fichier|Read_file str: name of the *.decoupage_som file
   • expert_only: to not check the mesh
3.133 Ecrire
Description: Keyword to write the object of name name_obj to a standard outlet.
See also: interprete (3)
Usage:
ecrire name_obj
where
   • name_obj str: Name of the object to be written.
3.134 Ecrire_fichier_bin
Synonymous: ecrire fichier
Description: Keyword to write the object of name name_obj to a file filename. Since the v1.6.3, the
default format is now binary format file.
See also: interprete (3) ecrire_fichier_formatte (3.38)
Usage:
ecrire_fichier_bin name_obj filename
where
   • name_obj str: Name of the object to be written.
   • filename str: Name of the file.
    pb_gen_base
Description: Basic class for problems.
See also: objet_u (40) Pb_base (4.22) pbc_med (4.53) probleme_couple (4.23)
Usage:
4.1 Pb_conduction
Description: Resolution of the heat equation.
Keyword Discretize should have already been used to read the object.
See also: Pb_base (4.22)
Usage:
```

Pb Conduction str

Read str {

```
[ solide solide]
[ Conduction conduction]
[ milieu milieu_base]
[ constituant constituant]
[ Post_processing|postraitement corps_postraitement]
[ Post_processings|postraitements post_processings]
[ liste_de_postraitements liste_post_ok]
[ liste_postraitements liste_post]
[ sauvegarde format_file_base]
[ sauvegarde_simple format_file_base]
[ reprise format_file_base]
[ resume_last_time format_file_base]
}
where
```

- solide solide (22.13): The medium associated with the problem.
- **Conduction** *conduction* (5.1): Heat equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.
- **Post_processinglyostraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.2 Corps_postraitement

```
Description: not_set

See also: post_processing (4.4.3)

Usage:
{
```

```
[fichier str]
     [format str into ['lml', 'lata', 'single_lata', 'lata_v2', 'med', 'med_major', 'cgns']]
     [dt post str]
     [ nb_pas_dt_post int]
     [domaine str]
     [ sous_zonelsous_domaine str]
     [ parallele str into ['simple', 'multiple', 'mpi-io']]
     [ definition champs definition champs]
     [ definition champs file|definition champs fichier | definition champs fichier]
     [ probes|sondes | sondes]
     [ probes file|sondes fichier | sondes fichier]
     [ mobile probes|sondes mobiles sondes]
     [ mobile_probes_file|sondes_mobiles_fichier | sondes_fichier]
     [ deprecatedkeepduplicatedprobes int]
     [ fields|champs champs_posts]
     [ fields_file|champs_fichier champs_posts_fichier]
     [ statistics|statistiques stats_posts]
     [statistics_file|statistiques_fichier stats_posts_fichier]
     [serial_statistics_file|statistiques_en_serie_fichier stats_serie_posts_fichier]
     [ suffix for reset str]
}
where
```

- fichier str for inheritance: Name of file.
- format str into ['lml', 'lata', 'single_lata', 'lata_v2', 'med', 'med_major', 'cgns'] for inheritance: This optional parameter specifies the format of the output file. The basename used for the output file is the basename of the data file. For the fmt parameter, choices are lml or lata. A short description of each format can be found below. The default value is lml.
- **dt_post** *str* for inheritance: Field's write frequency (as a time period) can also be specified after the 'field' keyword.
- **nb_pas_dt_post** *int* for inheritance: Field's write frequency (as a number of time steps) can also be specified after the 'field' keyword.
- **domaine** *str* for inheritance: This optional parameter specifies the domain on which the data should be interpolated before it is written in the output file. The default is to write the data on the domain of the current problem (no interpolation).
- **sous_zonelsous_domaine** *str* for inheritance: This optional parameter specifies the sub_domaine on which the data should be interpolated before it is written in the output file. It is only available for sequential computation.
- parallele *str into ['simple', 'multiple', 'mpi-io']* for inheritance: Select simple (single file, sequential write), multiple (several files, parallel write), or mpi-io (single file, parallel write) for LATA format
- **definition_champs** *definition_champs* (4.2.1) for inheritance: Keyword to create new or more complex field for advanced postprocessing.
- **definition_champs_file|definition_champs_fichier** *definition_champs_fichier* (4.2.3) for inheritance: Definition_champs read from file.
- **probesisondes** sondes (4.2.4) for inheritance: Probe.
- probes_filelsondes_fichier sondes_fichier (4.2.22) for inheritance: Probe read from a file.
- **mobile_probes|sondes_mobiles** *sondes* (4.2.4) for inheritance: Mobile probes useful for ALE, their positions will be updated in the mesh.
- **mobile_probes_file|sondes_mobiles_fichier** *sondes_fichier* (4.2.22) for inheritance: Mobile probes read in a file
- **deprecatedkeepduplicatedprobes** *int* for inheritance: Flag to not remove duplicated probes in .son files (1: keep duplicate probes, 0: remove duplicate probes)

- **fieldslchamps** *champs_posts* (4.2.23) for inheritance: Field's write mode.
- fields_filelchamps_fichier champs_posts_fichier (4.2.26) for inheritance: Fields read from file.
- **statisticsIstatistiques** *stats_posts* (4.2.28) for inheritance: Statistics between two points fixed : start of integration time and end of integration time.
- statistics_file|statistiques_fichier stats_posts_fichier (4.2.36) for inheritance: Statistics read from file.
- **serial_statistics|statistiques_en_serie** *stats_serie_posts* (4.2.37) for inheritance: Statistics between two points not fixed : on period of integration.
- serial_statistics_file|statistiques_en_serie_fichier stats_serie_posts_fichier (4.2.38) for inheritance: Serial statistics read from a file
- **suffix_for_reset** *str* for inheritance: Suffix used to modify the postprocessing file name if the ICoCo resetTime() method is invoked.

4.2.1 Definition_champs

```
Description: List of definition champ

See also: listobj (38.5)

Usage:
{ object1 object2 .... }
list of definition_champ (4.2.2)
```

4.2.2 Definition_champ

Description: Keyword to create new complex field for advanced postprocessing.

```
See also: objet_lecture (39)
Usage:
name champ_generique
where
```

- name str: The name of the new created field.
- champ_generique champ_generique_base (9)

4.2.3 Definition_champs_fichier

Description: Keyword to read definition_champs from a file

```
See also: objet_lecture (39)

Usage: {

filelfichier str
}
where
```

• filelfichier str: name of file

4.2.4 Sondes

```
Description: List of probes.

See also: listobj (38.5)

Usage:
{ object1 object2 .... }
list of sonde (4.2.5)
```

4.2.5 Sonde

Description: Keyword is used to define the probes. Observations: the probe coordinates should be given in Cartesian coordinates (X, Y, Z), including axisymmetric.

```
See also: objet_lecture (39)
```

Usage:

```
nom_sonde [ special ] nom_inco mperiode prd type
where
```

- **nom_sonde** *str*: Name of the file in which the values taken over time will be saved. The complete file name is nom sonde.son.
- **special** *str into ['grav', 'som', 'nodes', 'chsom', 'gravcl']*: Option to change the positions of the probes. Several options are available:

grav: each probe is moved to the nearest cell center of the mesh;

som: each probe is moved to the nearest vertex of the mesh

nodes: each probe is moved to the nearest face center of the mesh;

 $chsom: only \ available \ for \ P1NC \ sampled \ field. \ The \ values \ of \ the \ probes \ are \ calculated \ according \ to \ P1-Conform \ corresponding \ field.$

gravel: Extend to the domain face boundary a cell-located segment probe in order to have the boundary condition for the field. For this type the extreme probe point has to be on the face center of gravity.

- nom_inco str: Name of the sampled field.
- mperiode str into ['periode']: Keyword to set the sampled field measurement frequency.
- **prd** *float*: Period value. Every prd seconds, the field value calculated at the previous time step is written to the nom sonde.son file.
- **type** *sonde_base* (4.2.6): Type of probe.

4.2.6 Sonde base

Description: Basic probe. Probes refer to sensors that allow a value or several points of the domain to be monitored over time. The probes may be a set of points defined one by one (keyword Points) or a set of points evenly distributed over a straight segment (keyword Segment) or arranged according to a layout (keyword Plan) or according to a parallelepiped (keyword Volume). The fields allow all the values of a physical value on the domain to be known at several moments in time.

```
See also: objet_lecture (39) points (4.2.7) segment (4.2.11) segmentfacesx (4.2.12) segmentfacesy (4.2.13) segmentfacesz (4.2.14) radius (4.2.15) numero_elem_sur_maitre (4.2.16) position_like (4.2.17) plan (4.2.18) volume (4.2.19) circle (4.2.20) circle_3 (4.2.21)
```

Usage:

sonde_base

4.2.7 Points

Description: Keyword to define the number of probe points. The file is arranged in columns.

```
See also: sonde_base (4.2.6) point (4.2.9) segmentpoints (4.2.10)
```

Usage:

points points

where

• points *listpoints* (4.2.8): Probe points.

4.2.8 Listpoints

Description: Points.

See also: listobj (38.5)

Usage:

n object1 object2 list of un_point (3.24.3)

4.2.9 Point

Description: Point as class-daughter of Points.

See also: points (4.2.7)

Usage:

point points

where

• points listpoints (4.2.8): Probe points.

4.2.10 Segmentpoints

Description: This keyword is used to define a probe segment from specifics points. The nom_champ field is sampled at ns specifics points.

```
See also: points (4.2.7)
```

Usage:

segmentpoints points

where

• points listpoints (4.2.8): Probe points.

4.2.11 Segment

Description: Keyword to define the number of probe segment points. The file is arranged in columns.

```
See also: sonde_base (4.2.6)
```

Usage:

$segment \ nbr \ point_deb \ point_fin$

- **nbr** *int*: Number of probe points of the segment, evenly distributed.
- point_deb un_point (3.24.3): First outer probe segment point.
- **point_fin** *un_point* (3.24.3): Second outer probe segment point.

4.2.12 Segmentfacesx

Description: Segment probe where points are moved to the nearest x faces

See also: sonde_base (4.2.6)

Usage:

segmentfacesx nbr point_deb point_fin where

- **nbr** *int*: Number of probe points of the segment, evenly distributed.
- point_deb un_point (3.24.3): First outer probe segment point.
- **point_fin** *un_point* (3.24.3): Second outer probe segment point.

4.2.13 Segmentfacesy

Description: Segment probe where points are moved to the nearest y faces

See also: sonde_base (4.2.6)

Usage:

segmentfacesy nbr point_deb point_fin where

- **nbr** *int*: Number of probe points of the segment, evenly distributed.
- point_deb un_point (3.24.3): First outer probe segment point.
- point_fin un_point (3.24.3): Second outer probe segment point.

4.2.14 Segmentfacesz

Description: Segment probe where points are moved to the nearest z faces

See also: sonde_base (4.2.6)

Usage:

segmentfacesz nbr point_deb point_fin where

- **nbr** *int*: Number of probe points of the segment, evenly distributed.
- point_deb un_point (3.24.3): First outer probe segment point.
- point_fin un_point (3.24.3): Second outer probe segment point.

4.2.15 Radius

Description: not_set

See also: sonde_base (4.2.6)

Usage:

radius nbr point_deb radius teta1 teta2 where

- **nbr** *int*: Number of probe points of the segment, evenly distributed.
- **point_deb** *un_point* (3.24.3): First outer probe segment point.
- radius float
- teta1 float
- teta2 float

4.2.16 Numero_elem_sur_maitre

Description: Keyword to define a probe at the special element. Useful for min/max sonde.

See also: sonde_base (4.2.6)

Usage:

numero_elem_sur_maitre numero

where

• numero int: element number

4.2.17 Position like

Description: Keyword to define a probe at the same position of another probe named autre sonde.

See also: sonde_base (4.2.6)

Usage:

position_like autre_sonde

where

• autre_sonde str: Name of the other probe.

4.2.18 Plan

Description: Keyword to set the number of probe layout points. The file format is type .lml

See also: sonde_base (4.2.6)

Usage:

plan nbr nbr2 point_deb point_fin point_fin_2
where

- **nbr** *int*: Number of probes in the first direction.
- **nbr2** *int*: Number of probes in the second direction.
- point_deb un_point (3.24.3): First point defining the angle. This angle should be positive.
- point_fin un_point (3.24.3): Second point defining the angle. This angle should be positive.
- point_fin_2 un_point (3.24.3): Third point defining the angle. This angle should be positive.

4.2.19 Volume

Description: Keyword to define the probe volume in a parallelepiped passing through 4 points and the number of probes in each direction.

See also: sonde_base (4.2.6)

Usage:

volume nbr nbr2 nbr3 point_deb point_fin point_fin_2 point_fin_3 where

- **nbr** *int*: Number of probes in the first direction.
- **nbr2** *int*: Number of probes in the second direction.
- **nbr3** *int*: Number of probes in the third direction.
- point_deb un_point (3.24.3): Point of origin.
- point_fin un_point (3.24.3): Point defining the first direction (from point of origin).
- point_fin_2 un_point (3.24.3): Point defining the second direction (from point of origin).
- point_fin_3 un_point (3.24.3): Point defining the third direction (from point of origin).

4.2.20 Circle

Description: Keyword to define several probes located on a circle.

See also: sonde_base (4.2.6)

Usage:

circle nbr point_deb [direction] radius theta1 theta2 where

- **nbr** *int*: Number of probes between teta1 and teta2 (angles given in degrees).
- point_deb un_point (3.24.3): Center of the circle.
- direction int into [0, 1, 2]: Axis normal to the circle plane (0:x axis, 1:y axis, 2:z axis).
- radius float: Radius of the circle.
- theta1 *float*: First angle.
- theta2 float: Second angle.

4.2.21 Circle_3

Description: Keyword to define several probes located on a circle (in 3-D space).

See also: sonde_base (4.2.6)

Usage:

circle_3 nbr point_deb direction radius theta1 theta2 where

- **nbr** *int*: Number of probes between teta1 and teta2 (angles given in degrees).
- point_deb un_point (3.24.3): Center of the circle.
- direction int into [0, 1, 2]: Axis normal to the circle plane (0:x axis, 1:y axis, 2:z axis).
- radius float: Radius of the circle.
- theta1 float: First angle.
- theta2 float: Second angle.

4.2.22 Sondes_fichier

```
Description: Keyword to read probes from a file
```

```
See also: objet_lecture (39)

Usage:
{

filelfichier str
}
where
```

• filelfichier str: name of file

4.2.23 Champs_posts

Description: Field's write mode.

See also: objet_lecture (39)

Usage:

[format][mot][period] fields|champs

where

- **format** *str into ['binaire', 'formatte']*: Type of file.
- mot str into ['dt_post', 'nb_pas_dt_post']: Keyword to set the kind of the field's write frequency. Either a time period or a time step period. it can be specified either here, or at the beginning of the postprocessing bloc.
- **period** *str*: Value of the period which can be like (2.*t).
- **fieldslchamps** *champs_a_post* (4.2.24): Post-processed fields.

4.2.24 Champs_a_post

Description: Fields to be post-processed.

```
See also: listobj (38.5)

Usage: { object1 object2 .... } list of champ_a_post (4.2.25)
```

4.2.25 Champ_a_post

Description: Field to be post-processed.

See also: objet_lecture (39)

Usage:

champ [localisation]

- **champ** *str*: Name of the post-processed field.
- **localisation** *str into ['elem', 'som', 'faces']*: Localisation of post-processed field values: The two available values are elem, som, or faces (LATA format only) used respectively to select field values at mesh centres (CHAMPMAILLE type field in the lml file) or at mesh nodes (CHAMPPOINT type field in the lml file). If no selection is made, localisation is set to som by default.

4.2.26 Champs_posts_fichier

Description: Fields read from file.

See also: objet_lecture (39)

Usage:

[format] [mot] [period] fichier

where

- format str into ['binaire', 'formatte']: Type of file.
- **mot** *str into* ['dt_post', 'nb_pas_dt_post']: Keyword to set the kind of the field's write frequency. Either a time period or a time step period.
- **period** str: Value of the period which can be like (2.*t).
- fichier bloc_fichier (4.2.27): name of file

4.2.27 Bloc_fichier

Description: Block containing the name of the file

```
See also: objet_lecture (39)

Usage:
{

fichier str
}
where
```

• fichier str: File name

4.2.28 Stats_posts

Description: Post-processing for statistics.

Example:

Statistiques Dt_post dtst { t_deb 0.1 t_fin 0.12

Moyenne Pression

Ecart_type Pression

Correlation Vitesse Vitesse }

It will write every **dt post** the mean, standard deviation and correlation value:

```
 \begin{split} t <& = t_{\text{deb}} \text{ or } t > = t_{\text{fin}}: \\ \text{average: } \overline{P(t)} &= 0 \\ \text{std\_deviation: } &< P(t) > = 0 \\ \text{correlation: } &< U(t).V(t) > = 0 \\ t > t_{\text{deb}} \text{ and } t < t_{\text{fin}}: \\ \text{average: } \overline{P(t)} &= \frac{1}{t - t_{\text{deb}}} \int\limits_{t_{\text{deb}}}^{t} P(s) \mathrm{ds} \\ \text{std\_deviation: } &< P(t) > = \sqrt{\frac{1}{t - t_{\text{deb}}}} \int\limits_{t_{\text{deb}}}^{t} \left[ P(s) - \overline{P(t)} \right]^2 \mathrm{ds} \\ \text{correlation: } &< U(t).V(t) > = \frac{1}{t - t_{\text{deb}}} \int\limits_{t_{\text{deb}}}^{t} \left[ U(s) - \overline{U(t)} \right]. \left[ V(s) - \overline{V(t)} \right] \mathrm{ds} \\ \end{split}
```

```
See also: objet_lecture (39)
Usage:
[ mot ] [ period ] fields|champs
where
   • mot str into ['dt_post', 'nb_pas_dt_post']: Keyword to set the kind of the field's write frequency.
     Either a time period or a time step period.
   • period str: Value of the period which can be like (2.*t).
   • fieldslchamps list_stat_post (4.2.29): Post-processed fields.
4.2.29 List_stat_post
Description: Post-processing for statistics
See also: listobj (38.5)
Usage:
{ object1 object2 .... }
list of stat_post_deriv (4.2.30)
4.2.30 Stat_post_deriv
Description: not_set
See also: objet_lecture (39) t_deb (4.2.31) t_fin (4.2.32) moyenne (4.2.33) ecart_type (4.2.34) correla-
tion (4.2.35)
Usage:
stat_post_deriv
4.2.31 T_deb
Description: Start of integration time
See also: stat_post_deriv (4.2.30)
Usage:
t deb val
where
   • val float
4.2.32 T_fin
Description: End of integration time
See also: stat_post_deriv (4.2.30)
Usage:
t_fin val
```

• val float

4.2.33 Moyenne

Synonymous: champ_post_statistiques_moyenne

Description: to calculate the average of the field over time

See also: stat_post_deriv (4.2.30)

Usage:

moyenne field [localisation]

where

- **field** *str*: name of the field on which statistical analysis will be performed. Possible keywords are Vitesse (velocity), Pression (pressure), Temperature, Concentration, ...
- localisation str into ['elem', 'som', 'faces']: Localisation of post-processed field value

4.2.34 Ecart_type

Synonymous: champ_post_statistiques_ecart_type

Description: to calculate the standard deviation (statistic rms) of the field

See also: stat_post_deriv (4.2.30)

Usage:

ecart_type field [localisation]

where

- **field** *str*: name of the field on which statistical analysis will be performed. Possible keywords are Vitesse (velocity), Pression (pressure), Temperature, Concentration, ...
- localisation str into ['elem', 'som', 'faces']: Localisation of post-processed field value

4.2.35 Correlation

Synonymous: champ_post_statistiques_correlation

Description: correlation between the two fields

See also: stat_post_deriv (4.2.30)

Usage:

correlation first_field second_field [localisation]

- first field str: first field
- second_field str: second field
- localisation str into ['elem', 'som', 'faces']: Localisation of post-processed field value

4.2.36 Stats_posts_fichier

Description: Statistics read from file..

Example:

It will write every **dt_post** the mean, standard deviation and correlation value:

```
 \begin{split} t <&= t_{\text{deb}} \text{ or } t >= t_{\text{fin}} : \\ \text{average: } \overline{P(t)} &= 0 \\ \text{std\_deviation: } &< P(t) >= 0 \\ \text{correlation: } &< U(t).V(t) >= 0 \\ \end{split}   t > t_{\text{deb}} \text{ and } t < t_{\text{fin}} : \\ \text{average: } \overline{P(t)} &= \frac{1}{t-t_{\text{deb}}} \int\limits_{t_{\text{deb}}}^t P(s) \mathrm{ds} \\ \text{std\_deviation: } &< P(t) >= \sqrt{\frac{1}{t-t_{\text{deb}}} \int\limits_{t_{\text{deb}}}^t \left[ P(s) - \overline{P(t)} \right]^2 \mathrm{ds}} \\ \text{correlation: } &< U(t).V(t) >= \frac{1}{t-t_{\text{deb}}} \int\limits_{t_{\text{deb}}}^t \left[ U(s) - \overline{U(t)} \right]. \left[ V(s) - \overline{V(t)} \right] \mathrm{ds} \\ \end{split}
```

See also: objet_lecture (39)

Usage:

mot period fichier

where

- **mot** *str into* ['dt_post', 'nb_pas_dt_post']: Keyword to set the kind of the field's write frequency. Either a time period or a time step period.
- **period** *str*: Value of the period which can be like (2.*t).
- fichier bloc fichier (4.2.27): name of file

4.2.37 Stats_serie_posts

Description: This keyword is used to set the statistics. Average on dt_integr time interval is post-processed every dt_integr seconds.

Example:

Statistiques_en_serie Dt_integr dtst {
Moyenne Pression
}

Will calculate and write every dtst seconds the mean value:

$$(n+1) \text{dt_integr} > t > n * \text{dt_integr}, \overline{P(t)} = \frac{1}{t-n*\text{dt_integr}} \int\limits_{t_n*\text{dt_integr}}^t P(t) \text{dt}$$

See also: objet_lecture (39)

Usage:

 $mot \ dt_integr \ stat$

where

- mot str into ['dt_integr']: Keyword is used to set the statistics period of integration and write period.
- dt_integr float: Average on dt_integr time interval is post-processed every dt_integr seconds.
- **stat** *list_stat_post* (4.2.29)

4.2.38 Stats_serie_posts_fichier

Description: This keyword is used to set the statistics read from a file. Average on dt_integr time interval is post-processed every dt_integr seconds.

Example:

Statistiques_en_serie Dt_integr dtst {
Moyenne Pression
}

Will calculate and write every dtst seconds the mean value:

$$(n+1) \text{dt_integr} > t > n * \text{dt_integr}, \overline{P(t)} = \frac{1}{t-n* \text{dt_integr}} \int\limits_{t_n* \text{dt_integr}}^t P(t) \text{dt}$$

See also: objet_lecture (39)

Usage:

mot dt_integr fichier

where

- mot str into ['dt_integr']: Keyword is used to set the statistics period of integration and write period.
- **dt_integr** *float*: Average on dt_integr time interval is post-processed every dt_integr seconds.
- fichier bloc_fichier (4.2.27): name of file

4.3 Post_processings

Synonymous: postraitements

Description: Keyword to use several results files. List of objects of post-processing (with name).

See also: listobj (38.5)

Usage:

{ object1 object2 }

list of un_postraitement (4.3.1)

```
4.3.1 Un_postraitement
Description: An object of post-processing (with name).
See also: objet_lecture (39)
Usage:
nom post
where
   • nom str: Name of the post-processing.
   • post corps_postraitement (4.2): Definition of the post-processing.
4.4 Liste_post_ok
Description: Keyword to use several results files. List of objects of post-processing (with name)
See also: listobj (38.5)
Usage:
{ object1 object2 .... }
list of nom_postraitement (4.4.1)
4.4.1 Nom_postraitement
Description: not_set
See also: objet_lecture (39)
Usage:
nom post
where
   • nom str: Name of the post-processing.
   • post postraitement_base (4.4.2): the post
4.4.2 Postraitement_base
Description: not_set
See also: objet_lecture (39) post_processing (4.4.3)
Usage:
4.4.3 Post_processing
Synonymous: postraitement
Description: An object of post-processing (without name).
See also: postraitement_base (4.4.2) corps_postraitement (4.2)
```

Usage:

post_processing {

```
[fichier str]
     [format str into ['lml', 'lata', 'single_lata', 'lata_v2', 'med', 'med_major', 'cgns']]
     [dt post str]
     [ nb_pas_dt_post int]
     [domaine str]
     [ sous_zonelsous_domaine str]
     [ parallele str into ['simple', 'multiple', 'mpi-io']]
     [ definition champs definition champs]
     [ definition champs file|definition champs fichier | definition champs fichier]
     [ probes|sondes | sondes]
     [ probes file|sondes fichier | sondes fichier]
     [ mobile probes|sondes mobiles sondes]
     [ mobile_probes_file|sondes_mobiles_fichier | sondes_fichier]
     [ deprecatedkeepduplicatedprobes int]
     [ fields|champs champs_posts]
     [ fields_file|champs_fichier champs_posts_fichier]
     [ statistics|statistiques stats_posts]
     [ statistics_file|statistiques_fichier stats_posts_fichier]
     [serial_statistics_file|statistiques_en_serie_fichier stats_serie_posts_fichier]
     [ suffix for reset str]
}
where
```

- fichier str: Name of file.
- format str into ['lml', 'lata', 'single_lata', 'lata_v2', 'med', 'med_major', 'cgns']: This optional parameter specifies the format of the output file. The basename used for the output file is the basename of the data file. For the fmt parameter, choices are lml or lata. A short description of each format can be found below. The default value is lml.
- dt_post str: Field's write frequency (as a time period) can also be specified after the 'field' keyword.
- **nb_pas_dt_post** *int*: Field's write frequency (as a number of time steps) can also be specified after the 'field' keyword.
- **domaine** *str*: This optional parameter specifies the domain on which the data should be interpolated before it is written in the output file. The default is to write the data on the domain of the current problem (no interpolation).
- **sous_zonelsous_domaine** *str*: This optional parameter specifies the sub_domaine on which the data should be interpolated before it is written in the output file. It is only available for sequential computation.
- parallele *str into ['simple'*, *'multiple'*, *'mpi-io']*: Select simple (single file, sequential write), multiple (several files, parallel write), or mpi-io (single file, parallel write) for LATA format
- **definition_champs** *definition_champs* (4.2.1): Keyword to create new or more complex field for advanced postprocessing.
- **definition_champs_file|definition_champs_fichier** *definition_champs_fichier* (4.2.3): Definition_champs read from file.
- **probesisondes** sondes (4.2.4): Probe.
- probes_file|sondes_fichier sondes_fichier (4.2.22): Probe read from a file.
- **mobile_probes|sondes_mobiles** *sondes* (4.2.4): Mobile probes useful for ALE, their positions will be updated in the mesh.
- mobile_probes_filelsondes_mobiles_fichier sondes_fichier (4.2.22): Mobile probes read in a file
- **deprecatedkeepduplicatedprobes** *int*: Flag to not remove duplicated probes in .son files (1: keep duplicate probes, 0: remove duplicate probes)
- **fieldslchamps** *champs_posts* (4.2.23): Field's write mode.
- **fields_filelchamps_fichier** *champs_posts_fichier* (4.2.26): Fields read from file.

- **statisticsIstatistiques** *stats_posts* (4.2.28): Statistics between two points fixed : start of integration time and end of integration time.
- statistics_file|statistiques_fichier stats_posts_fichier (4.2.36): Statistics read from file.
- serial_statistics|statistiques_en_serie stats_serie_posts (4.2.37): Statistics between two points not fixed: on period of integration.
- serial_statistics_file|statistiques_en_serie_fichier stats_serie_posts_fichier (4.2.38): Serial_statistics read from a file
- **suffix_for_reset** *str*: Suffix used to modify the postprocessing file name if the ICoCo resetTime() method is invoked.

```
4.5 Liste_post
Description: Keyword to use several results files. List of objects of post-processing (with name)
See also: listobj (38.5)
Usage:
{ object1 object2 .... }
list of un postraitement spec (4.5.1)
4.5.1 Un_postraitement_spec
Description: An object of post-processing (with type +name).
See also: objet_lecture (39)
Usage:
[ type_un_post ] [ type_postraitement_ft_lata ]
where
   • type_un_post type_un_post (4.5.2)
   • type postraitement ft lata type postraitement ft lata (4.5.3)
4.5.2 Type_un_post
Description: not_set
See also: objet_lecture (39)
Usage:
type post
where
   • type str into ['postraitement', 'post_processing']
   • post un_postraitement (4.3.1)
4.5.3 Type_postraitement_ft_lata
Description: not_set
See also: objet_lecture (39)
```

Usage:

where

type nom bloc

```
• type str into ['postraitement_ft_lata', 'postraitement_lata']
```

• **nom** *str*: Name of the post-processing.

• bloc str

4.6 Format_file_base

Description: Format of the file

See also: objet_lecture (39) binaire (4.6.1) formatte (4.6.2) xyz (4.6.3) single_hdf (4.6.4) pdi (4.6.5) pdi_expert (4.6.6)

Usage:

checkpoint_fname

where

• checkpoint_fname str: Name of file.

4.6.1 Binaire

Description: Format of the file - binary version

See also: (4.6)

Usage:

binaire checkpoint_fname

where

• checkpoint_fname str: Name of file.

4.6.2 Formatte

Description: Format of the file - formatte version

See also: (4.6)

Usage:

formatte checkpoint_fname

where

• **checkpoint_fname** *str*: Name of file.

4.6.3 Xyz

Description: Format of the file - xyz version

See also: (4.6)

Usage:

xyz checkpoint_fname

where

• checkpoint_fname str: Name of file.

```
4.6.4 Single_hdf
Description: Format of the file - single_hdf version
See also: (4.6)
Usage:
single_hdf checkpoint_fname
where
   • checkpoint_fname str: Name of file.
4.6.5 Pdi
Description: Format of the file - pdi version
See also: (4.6)
Usage:
pdi checkpoint_fname
where
   • checkpoint_fname str: Name of file.
4.6.6 Pdi_expert
Description: Format of the file - PDI expert version
See also: (4.6)
Usage:
pdi_expert {
     yaml_fname str
     checkpoint_fname str
where
   • yaml_fname str: YAML file name
   • checkpoint_fname str for inheritance: Name of file.
4.7 Pb_conduction_ibm
Description: Resolution of the IBM heat equation.
Keyword Discretize should have already been used to read the object.
See also: Pb_base (4.22)
Usage:
Pb_Conduction_ibm str
Read str {
     [solide solide]
```

```
[Conduction_ibm conduction_ibm]
[milieu milieu_base]
[constituant constituant]
[Post_processing|postraitement corps_postraitement]
[Post_processings|postraitements post_processings]
[liste_de_postraitements liste_post_ok]
[liste_postraitements liste_post]
[sauvegarde format_file_base]
[sauvegarde_simple format_file_base]
[reprise format_file_base]
[resume_last_time format_file_base]
}
where
```

- solide solide (22.13): The medium associated with the problem.
- **Conduction ibm** *conduction ibm* (5.8): IBM Heat equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.8 Pb_hydraulique_cloned_concentration

Description: Resolution of Navier-Stokes/multiple constituent transport equations.

Keyword Discretize should have already been used to read the object.

See also: Pb_base (4.22)

Usage:

Pb_Hydraulique_Cloned_Concentration *str* **Read** *str* {

```
fluide_incompressible fluide_incompressible

[ constituant constituant]

[ navier_stokes_standard navier_stokes_standard]

[ convection_diffusion_concentration convection_diffusion_concentration]

[ milieu milieu_base]

[ Post_processinglpostraitement corps_postraitement]

[ Post_processingslpostraitements post_processings]

[ liste_de_postraitements liste_post_ok]

[ liste_postraitements liste_post]

[ sauvegarde format_file_base]

[ sauvegarde_simple format_file_base]

[ reprise format_file_base]

[ resume_last_time format_file_base]

}

where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- constituant constituant (22.1): Constituents.
- navier_stokes_standard navier_stokes_standard (5.42): Navier-Stokes equations.
- **convection_diffusion_concentration** *convection_diffusion_concentration* (5.21): Constituent transport vectorial equation (concentration diffusion convection).
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processinglpostraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.9 Pb_hydraulique_cloned_concentration_turbulent

Description: Resolution of Navier-Stokes/multiple constituent transport equations, with turbulence modelling.

Keyword Discretize should have already been used to read the object. See also: Pb base (4.22) Usage: Pb Hydraulique Cloned Concentration Turbulent str Read str { fluide_incompressible fluide_incompressible [constituant constituant] [navier_stokes_turbulent navier_stokes_turbulent] $[\ \ convection_diffusion_concentration_turbulent \ \ \ convection_diffusion_concentration_turbulent]$ [milieu milieu_base] [Post_processing|postraitement corps_postraitement] [Post_processings|postraitements post_processings] [liste_de_postraitements liste_post_ok] [liste postraitements liste post] [sauvegarde format_file_base] [sauvegarde_simple format_file_base] [reprise format_file_base] [resume_last_time format_file_base] }

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem
- **constituant** *constituant* (22.1): Constituents.

- navier_stokes_turbulent navier_stokes_turbulent (5.43): Navier-Stokes equations as well as the associated turbulence model equations.
- convection_diffusion_concentration_turbulent convection_diffusion_concentration_turbulent (5.22): Constituent transport equations (concentration diffusion convection) as well as the associated turbulence model equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** corps_postraitement (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- **reprise** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz

file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.

• **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.10 Pb_hydraulique_ibm_turbulent

Description: Resolution of Navier-Stokes equations with turbulence modelling.

Keyword Discretize should have already been used to read the object. See also: Pb_base (4.22)

```
Pb_Hydraulique_IBM_Turbulent str
Read str {
     fluide_incompressible fluide_incompressible
     navier stokes ibm turbulent navier stokes ibm turbulent
     [ milieu milieu_base]
     [constituant constituant]
     [ Post_processing|postraitement corps_postraitement]
     [ Post processings|postraitements post processings]
     [liste de postraitements liste post ok]
     [liste postraitements liste post]
     [ sauvegarde format_file_base]
     [ sauvegarde_simple format_file_base]
     [reprise format_file_base]
     [ resume_last_time format_file_base]
}
where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- navier_stokes_ibm_turbulent navier_stokes_ibm_turbulent (5.40): IBM Navier-Stokes equations as well as the associated turbulence model equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.
- **Post_processinglpostraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified

for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.

- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.11 Pb_hydraulique_list_concentration

Pb_Hydraulique_List_Concentration str

[reprise format_file_base]

Description: Resolution of Navier-Stokes/multiple constituent transport equations.

Keyword Discretize should have already been used to read the object. See also: pb_avec_liste_conc (4.25)

```
Usage:
```

} where

```
fluide_incompressible fluide_incompressible

[ constituant constituant]

[ navier_stokes_standard navier_stokes_standard]

list_equations listeqn

[ milieu milieu_base]

[ Post_processing|postraitement corps_postraitement]

[ Post_processings|postraitements post_processings]

[ liste_de_postraitements liste_post_ok]

[ liste_postraitements liste_post]

[ sauvegarde format_file_base]

[ sauvegarde simple format file base]
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- **constituant** *constituant* (22.1): Constituents.

[resume_last_time format_file_base]

- navier_stokes_standard navier_stokes_standard (5.42): Navier-Stokes equations.
- **list_equations** *listeqn* (4.12) for inheritance: convection_diffusion_concentration equations. The unknown of the concentration equation number N is named concentrationN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.

- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.12 Listegn

```
Description: List of equations.

See also: listobj (38.5)

Usage:
{ object1 object2 .... }
list of eqn_base (5.33)
```

4.13 Pb_hydraulique_list_concentration_turbulent

Description: Resolution of Navier-Stokes/multiple constituent transport equations, with turbulence modelling.

```
Keyword Discretize should have already been used to read the object. See also: pb_avec_liste_conc (4.25)

Usage:
Pb_Hydraulique_List_Concentration_Turbulent str
Read str {
```

```
fluide_incompressible fluide_incompressible

[ constituant constituant]

[ navier_stokes_turbulent navier_stokes_turbulent]

list_equations listeqn

[ milieu milieu_base]
```

```
[ Post_processing|postraitement corps_postraitement]
[ Post_processings|postraitements post_processings]
[ liste_de_postraitements liste_post_ok]
[ liste_postraitements liste_post]
[ sauvegarde format_file_base]
[ sauvegarde_simple format_file_base]
[ reprise format_file_base]
[ resume_last_time format_file_base]
}
where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- **constituant** *constituant* (22.1): Constituents.
- navier_stokes_turbulent navier_stokes_turbulent (5.43): Navier-Stokes equations as well as the associated turbulence model equations.
- **list_equations** *listeqn* (4.12) for inheritance: convection_diffusion_concentration equations. The unknown of the concentration equation number N is named concentrationN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- Post_processing|postraitement corps_postraitement (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- liste de postraitements liste post ok (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- sauvegarde format_file_base (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.14 Pb_multiphase

Description: A problem that allows the resolution of N-phases with 3*N equations

```
Keyword Discretize should have already been used to read the object.
See also: Pb_base (4.22) Pb_Multiphase_h (4.15) Pb_HEM (4.16)
Usage:
Pb Multiphase str
Read str {
     [ milieu composite bloc lecture]
     [ Milieu_MUSIG bloc_lecture]
     [correlations bloc_lecture]
     [ models bloc_lecture]
     QDM_Multiphase qdm_multiphase
     Masse_Multiphase masse_multiphase
     Energie_Multiphase energie_multiphase
     [ Echelle_temporelle_turbulente | echelle_temporelle_turbulente]
     [ Energie_cinetique_turbulente energie_cinetique_turbulente]
     [ Energie_cinetique_turbulente_WIT energie_cinetique_turbulente_wit]
     [ Taux dissipation turbulent taux dissipation turbulent]
     [ milieu milieu base]
     [constituant constituant]
     [ Post_processing|postraitement corps_postraitement]
     [ Post_processings|postraitements post_processings]
     [liste de postraitements liste post ok]
     [liste_postraitements liste_post]
     [sauvegarde format file base]
     [ sauvegarde_simple format_file_base]
     [reprise format_file_base]
     [ resume_last_time format_file_base]
}
where
```

- milieu_composite bloc_lecture (3.59): The composite medium associated with the problem.
- Milieu_MUSIG bloc_lecture (3.59): The composite medium associated with the problem.
- **correlations** *bloc_lecture* (3.59): List of correlations used in specific source terms (i.e. interfacial flux, interfacial friction, ...)
- **models** *bloc_lecture* (3.59): List of models used in specific source terms (i.e. interfacial flux, interfacial friction, ...)
- **QDM_Multiphase** *qdm_multiphase* (5.16): Momentum conservation equation for a multi-phase problem where the unknown is the velocity
- Masse_Multiphase masse_multiphase (5.15): Mass consevation equation for a multi-phase problem where the unknown is the alpha (void fraction)
- **Energie_Multiphase** *energie_multiphase* (5.11): Internal energy conservation equation for a multiphase problem where the unknown is the temperature
- **Echelle_temporelle_turbulente** *echelle_temporelle_turbulente* (5.10): Turbulent Dissipation time scale equation for a turbulent mono/multi-phase problem (available in TrioCFD)
- Energie_cinetique_turbulente energie_cinetique_turbulente (5.13): Turbulent kinetic Energy conservation equation for a turbulent mono/multi-phase problem (available in TrioCFD)
- Energie_cinetique_turbulente_WIT energie_cinetique_turbulente_wit (5.14): Bubble Induced Turbulent kinetic Energy equation for a turbulent multi-phase problem (available in TrioCFD)
- Taux_dissipation_turbulent taux_dissipation_turbulent (5.17): Turbulent Dissipation frequency equation for a turbulent mono/multi-phase problem (available in TrioCFD)
- milieu milieu base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.

- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.15 Pb multiphase h

Description: A problem that allows the resolution of N-phases with 3*N equations

Keyword Discretize should have already been used to read the object.

```
See also: Pb Multiphase (4.14)
```

```
Usage:
Pb Multiphase h str
Read str {
     [ milieu composite bloc lecture]
     [correlations bloc_lecture]
     QDM_Multiphase qdm_multiphase
     Masse_Multiphase masse_multiphase
     Energie Multiphase h energie multiphase h
     [Milieu MUSIG bloc lecture]
     [ models bloc lecture]
     [ Echelle_temporelle_turbulente echelle_temporelle_turbulente]
     [ Energie_cinetique_turbulente energie_cinetique_turbulente]
     [Energie cinetique turbulente WIT energie cinetique turbulente wit]
     [ Taux_dissipation_turbulent taux_dissipation_turbulent]
     [ milieu milieu_base]
     [constituant constituant]
     [ Post_processing|postraitement corps_postraitement]
```

[Post_processings|postraitements post_processings]

```
[ liste_de_postraitements liste_post_ok]
    [ liste_postraitements liste_post]
    [ sauvegarde format_file_base]
    [ sauvegarde_simple format_file_base]
    [ reprise format_file_base]
    [ resume_last_time format_file_base]
}
where
```

- milieu composite bloc lecture (3.59): The composite medium associated with the problem.
- **correlations** *bloc_lecture* (3.59): List of correlations used in specific source terms (i.e. interfacial flux, interfacial friction, ...)
- **QDM_Multiphase** *qdm_multiphase* (5.16): Momentum conservation equation for a multi-phase problem where the unknown is the velocity
- Masse_Multiphase masse_multiphase (5.15): Mass consevation equation for a multi-phase problem where the unknown is the alpha (void fraction)
- **Energie_Multiphase_h** *energie_multiphase_h* (5.12): Internal energy conservation equation for a multi-phase problem where the unknown is the enthalpy
- Milieu_MUSIG bloc_lecture (3.59) for inheritance: The composite medium associated with the problem.
- **models** *bloc_lecture* (3.59) for inheritance: List of models used in specific source terms (i.e. interfacial flux, interfacial friction, ...)
- **Echelle_temporelle_turbulente** *echelle_temporelle_turbulente* (5.10) for inheritance: Turbulent Dissipation time scale equation for a turbulent mono/multi-phase problem (available in TrioCFD)
- Energie_cinetique_turbulente energie_cinetique_turbulente (5.13) for inheritance: Turbulent kinetic Energy conservation equation for a turbulent mono/multi-phase problem (available in TrioCFD)
- Energie_cinetique_turbulente_WIT energie_cinetique_turbulente_wit (5.14) for inheritance: Bubble Induced Turbulent kinetic Energy equation for a turbulent multi-phase problem (available in TrioCFD)
- Taux_dissipation_turbulent taux_dissipation_turbulent (5.17) for inheritance: Turbulent Dissipation frequency equation for a turbulent mono/multi-phase problem (available in TrioCFD)
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- liste de postraitements liste post ok (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- **reprise** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the

calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.

• **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.16 Pb_hem

Description: A problem that allows the resolution of 2-phases mechanicaly and thermally coupled with 3 equations

Keyword Discretize should have already been used to read the object. See also: Pb_Multiphase (4.14)

```
Usage:
Pb HEM str
Read str {
     [ milieu composite bloc lecture]
     [ Milieu_MUSIG bloc_lecture]
     [correlations bloc_lecture]
     [ models bloc_lecture]
     QDM_Multiphase qdm_multiphase
     Masse_Multiphase masse_multiphase
     Energie Multiphase energie multiphase
     [ Echelle temporelle turbulente echelle temporelle turbulente]
     [ Energie_cinetique_turbulente energie_cinetique_turbulente]
     [ Energie_cinetique_turbulente_WIT energie_cinetique_turbulente_wit]
     [ Taux_dissipation_turbulent taux_dissipation_turbulent]
     [ milieu milieu base]
     [constituant constituant]
     [ Post_processing|postraitement corps_postraitement]
     [ Post_processings|postraitements post_processings]
     [ liste_de_postraitements liste_post_ok]
     [liste_postraitements liste_post]
     [sauvegarde format file base]
     [ sauvegarde_simple format_file_base]
     [reprise format_file_base]
     [ resume_last_time format_file_base]
where
```

- milieu_composite bloc_lecture (3.59) for inheritance: The composite medium associated with the problem.
- Milieu_MUSIG bloc_lecture (3.59) for inheritance: The composite medium associated with the problem.
- **correlations** *bloc_lecture* (3.59) for inheritance: List of correlations used in specific source terms (i.e. interfacial flux, interfacial friction, ...)
- **models** *bloc_lecture* (3.59) for inheritance: List of models used in specific source terms (i.e. interfacial flux, interfacial friction, ...)
- **QDM_Multiphase** *qdm_multiphase* (5.16) for inheritance: Momentum conservation equation for a multi-phase problem where the unknown is the velocity

- Masse_Multiphase masse_multiphase (5.15) for inheritance: Mass consevation equation for a multi-phase problem where the unknown is the alpha (void fraction)
- **Energie_Multiphase** *energie_multiphase* (5.11) for inheritance: Internal energy conservation equation for a multi-phase problem where the unknown is the temperature
- **Echelle_temporelle_turbulente** *echelle_temporelle_turbulente* (5.10) for inheritance: Turbulent Dissipation time scale equation for a turbulent mono/multi-phase problem (available in TrioCFD)
- Energie_cinetique_turbulente energie_cinetique_turbulente (5.13) for inheritance: Turbulent kinetic Energy conservation equation for a turbulent mono/multi-phase problem (available in TrioCFD)
- Energie_cinetique_turbulente_WIT energie_cinetique_turbulente_wit (5.14) for inheritance: Bubble Induced Turbulent kinetic Energy equation for a turbulent multi-phase problem (available in TrioCFD)
- **Taux_dissipation_turbulent** *taux_dissipation_turbulent* (5.17) for inheritance: Turbulent Dissipation frequency equation for a turbulent mono/multi-phase problem (available in TrioCFD)
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.
- **Post_processinglpostraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.17 Pb_thermohydraulique_cloned_concentration

Description: Resolution of Navier-Stokes/energy/multiple constituent transport equations.

Keyword Discretize should have already been used to read the object. See also: Pb_base (4.22)

Usage:

Pb_Thermohydraulique_Cloned_Concentration *str* **Read** *str* {

```
fluide_incompressible fluide_incompressible

[ constituant constituant]

[ navier_stokes_standard navier_stokes_standard]

[ convection_diffusion_concentration convection_diffusion_concentration]

[ convection_diffusion_temperature convection_diffusion_temperature]

[ milieu milieu_base]

[ Post_processing|postraitement corps_postraitement]

[ Post_processings|postraitements post_processings]

[ liste_de_postraitements liste_post_ok]

[ liste_postraitements liste_post]

[ sauvegarde format_file_base]

[ sauvegarde_simple format_file_base]

[ reprise format_file_base]

[ resume_last_time format_file_base]

}

where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- constituent constituent (22.1): Constituents.
- navier_stokes_standard navier_stokes_standard (5.42): Navier-Stokes equations.
- **convection_diffusion_concentration** *convection_diffusion_concentration* (5.21): Constituent transport equations (concentration diffusion convection).
- **convection_diffusion_temperature** *convection_diffusion_temperature* (5.28): Energy equation (temperature diffusion convection).
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.18 Pb_thermohydraulique_cloned_concentration_turbulent

Description: Resolution of Navier-Stokes/energy/multiple constituent transport equations, with turbulence modelling.

Keyword Discretize should have already been used to read the object. See also: Pb base (4.22) Usage: ${\bf Pb_Thermohydraulique_Cloned_Concentration_Turbulent} \ \ str$ Read str { fluide_incompressible fluide_incompressible [constituant constituant] [navier_stokes_turbulent navier_stokes_turbulent] [convection_diffusion_concentration_turbulent] convection_diffusion_concentration_turbulent] [convection_diffusion_temperature_turbulent convection_diffusion_temperature_turbulent] [milieu milieu_base] [**Post_processing|postraitement** corps_postraitement] [Post_processings|postraitements post_processings] [liste de postraitements liste post ok] [liste_postraitements liste_post] [sauvegarde format file base] [sauvegarde_simple format_file_base] [reprise format_file_base] [resume last time format file base] }

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem
- **constituant** *constituant* (22.1): Constituents.

where

- navier_stokes_turbulent navier_stokes_turbulent (5.43): Navier-Stokes equations as well as the associated turbulence model equations.
- convection_diffusion_concentration_turbulent convection_diffusion_concentration_turbulent (5.22): Constituent transport equations (concentration diffusion convection) as well as the associated turbulence model equations.
- convection_diffusion_temperature_turbulent convection_diffusion_temperature_turbulent (5.32): Energy equation (temperature diffusion convection) as well as the associated turbulence model equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- liste_de_postraitements liste_post_ok (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.

- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format file base (4.6) for inheritance: Keyword to resume a calculation based on the name-_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema temps base) time fields are taken from the name file file. If there is no backup corresponding to this time in the name file, TRUST exits in
- resume_last_time format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

Pb_thermohydraulique_ibm_turbulent

Description: Resolution of thermohydraulic problem, with turbulence modelling.

```
Keyword Discretize should have already been used to read the object.
See also: Pb base (4.22)
```

```
Usage:
```

```
Pb_Thermohydraulique_IBM_Turbulent str
Read str {
```

```
fluide incompressible fluide incompressible
     navier stokes ibm turbulent navier stokes ibm turbulent
     convection diffusion temperature ibm turbulent convection diffusion temperature ibm turbulent
     [ milieu milieu base]
     [constituant constituant]
     [ Post_processing|postraitement corps_postraitement]
     [ Post processings|postraitements post processings]
     [ liste_de_postraitements liste_post_ok]
     [ liste_postraitements liste_post]
     [ sauvegarde format_file_base]
     [ sauvegarde_simple format_file_base]
     [reprise format_file_base]
     [ resume_last_time format_file_base]
}
where
```

- fluide_incompressible fluide_incompressible (22.4): The fluid medium associated with the problem.
- navier_stokes_ibm_turbulent navier_stokes_ibm_turbulent (5.40): IBM Navier-Stokes equations as well as the associated turbulence model equations.
- convection_diffusion_temperature_ibm_turbulent convection_diffusion_temperature_ibm_turbulent (5.31): Energy equation (temperature diffusion convection) as well as the associated turbulence model equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.
- Post_processing|postraitement corps_postraitement (4.2) for inheritance: One post-processing (without name).
- Post_processings|postraitements post_processings (4.3) for inheritance: List of Postraitement objects (with name).

- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- sauvegarde format_file_base (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.20 Pb_thermohydraulique_list_concentration

where

Description: Resolution of Navier-Stokes/energy/multiple constituent transport equations.

```
Keyword Discretize should have already been used to read the object.
See also: pb avec liste conc (4.25)
Pb_Thermohydraulique_List_Concentration str
Read str {
     fluide_incompressible fluide_incompressible
     [constituant constituant]
     [ navier stokes standard navier stokes standard]
     [convection_diffusion_temperature convection_diffusion_temperature]
     list equations listean
     [ milieu milieu_base]
     [ Post_processing|postraitement corps_postraitement]
     [ Post_processings|postraitements post_processings]
     [liste de postraitements liste post ok]
     [liste postraitements liste post]
     [sauvegarde format file base]
     [ sauvegarde_simple format_file_base]
     [reprise format_file_base]
     [resume last time format file base]
}
```

• **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.

- **constituant** *constituant* (22.1): Constituents.
- navier_stokes_standard navier_stokes_standard (5.42): Navier-Stokes equations.
- **convection_diffusion_temperature** *convection_diffusion_temperature* (5.28): Energy equation (temperature diffusion convection).
- **list_equations** *listeqn* (4.12) for inheritance: convection_diffusion_concentration equations. The unknown of the concentration equation number N is named concentrationN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processinglpostraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.21 Pb_thermohydraulique_list_concentration_turbulent

Description: Resolution of Navier-Stokes/energy/multiple constituent transport equations, with turbulence modelling.

```
Keyword Discretize should have already been used to read the object. See also: pb_avec_liste_conc (4.25)
```

Usage:

```
Pb_Thermohydraulique_List_Concentration_Turbulent str

Read str {

fluide incompressible fluide incompressible
```

```
fluide_incompressible fluide_incompressible
[ constituant constituant]
[ navier_stokes_turbulent navier_stokes_turbulent]
[ convection_diffusion_temperature_turbulent convection_diffusion_temperature_turbulent]
```

```
list_equations listeqn
[milieu milieu_base]
[Post_processinglpostraitement corps_postraitement]
[Post_processingslpostraitements post_processings]
[liste_de_postraitements liste_post_ok]
[liste_postraitements liste_post]
[sauvegarde format_file_base]
[sauvegarde_simple format_file_base]
[reprise format_file_base]
[resume_last_time format_file_base]
}
where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- **constituant** *constituant* (22.1): Constituents.
- navier_stokes_turbulent navier_stokes_turbulent (5.43): Navier-Stokes equations as well as the associated turbulence model equations.
- **convection_diffusion_temperature_turbulent** *convection_diffusion_temperature_turbulent* (5.32): Energy equation (temperature diffusion convection) as well as the associated turbulence model equations
- **list_equations** *listeqn* (4.12) for inheritance: convection_diffusion_concentration equations. The unknown of the concentration equation number N is named concentrationN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- sauvegarde format_file_base (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.22 Pb_base

Description: Resolution of equations on a domain. A problem is defined by creating an object and assigning the problem type that the user wishes to resolve. To enter values for the problem objects created, the Lire (Read) interpretor is used with a data block.

Keyword Discretize should have already been used to read the object.

See also: pb_gen_base (4) Pb_Conduction (4.1) Pb_Conduction_ibm (4.7) Pb_Thermohydraulique_IBM_Turbulent (4.19) pb_thermohydraulique_ibm (4.48) Pb_Hydraulique_IBM_Turbulent (4.10) pb_hydraulique_ibm (4.32) Pb_Multiphase (4.14) pb_thermohydraulique_concentration_turbulent (4.43) pb_thermohydraulique_turbulent (4.50) pb_avec_liste_conc (4.25) pb_thermohydraulique_turbulent_qc (4.51) pb_hydraulique_turbulent (4.36) Pb_Thermohydraulique_Cloned_Concentration_Turbulent (4.18) Pb_Hydraulique_Cloned_Concentration_Turbulent (4.9) pb_hydraulique_concentration_turbulent (4.30) pb_hydraulique_melange_binaire_turbulent_qc (4.35) pb_avec_passif (4.26) pb_thermohydraulique_QC (4.39) pb_hydraulique_melange_binaire_QC (4.33) pb_thermohydraulique_WC (4.40) pb_hydraulique_melange_binaire_WC (4.34) Pb_Thermohydraulique_Cloned_Concentration (4.17) Pb_Hydraulique_Cloned_Concentration (4.8) pb_thermohydraulique
(4.38) pb_hydraulique_concentration (4.28) pb_thermohydraulique_concentration (4.41) pb_hydraulique
(4.27) pb_post (4.37) problem_read_generic (4.55)

```
Usage:

Pb_base str

Read str {

    [milieu milieu_base]
    [constituant constituant]
    [Post_processing|postraitement corps_postraitement]
    [Post_processings|postraitements post_processings]
    [liste_de_postraitements liste_post_ok]
    [liste_postraitements liste_post]
    [sauvegarde format_file_base]
    [sauvegarde_simple format_file_base]
    [reprise format_file_base]
    [resume_last_time format_file_base]
}
where
```

- milieu milieu_base (22): The medium associated with the problem.
- constituent constituent (22.1): Constituent.
- Post processing|postraitement corps postraitement (4.2): One post-processing (without name).
- Post processings|postraitements post processings (4.3): List of Postraitement objects (with name).
- liste_de_postraitements liste_post_ok (4.4): This
- **liste_postraitements** *liste_post* (4.5): This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6): Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- sauvegarde_simple format_file_base (4.6): The same keyword than Sauvegarde except, the last time step only is saved.
- **reprise** *format_file_base* (4.6): Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by

the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.

• **resume_last_time** *format_file_base* (4.6): Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.23 Probleme_couple

Description: This instruction causes a probleme_couple type object to be created. This type of object has an associated problem list, that is, the coupling of n problems among them may be processed. Coupling between these problems is carried out explicitly via conditions at particular contact limits. Each problem may be associated either with the Associate keyword or with the Read/groupes keywords. The difference is that in the first case, the four problems exchange values then calculate their timestep, rather in the second case, the same strategy is used for all the problems listed inside one group, but the second group of problem exchange values with the first group of problems after the first group did its timestep. So, the first case may then also be written like this:

```
Probleme Couple pbc
```

```
Read pbc { groupes { { pb1 , pb2 , pb3 , pb4 } } }
```

There is a physical environment per problem (however, the same physical environment could be common to several problems).

Each problem is resolved in a domain.

Warning: Presently, coupling requires coincident meshes. In case of non-coincident meshes, boundary condition 'paroi_contact' in VEF returns error message (see paroi_contact for correcting procedure).

```
See also: pb_gen_base (4)

Usage:
probleme_couple str
Read str {
        [groupes list_list_nom]
}
where
        • groupes list_list_nom (4.24): { groupes { { pb1 , pb2 } , { pb3 , pb4 } } }

4.24 List_list_nom

Description: pour les groupes
See also: listobj (38.5)

Usage:
{ object1 , object2 .... }
list of list_un_pb (38.3) separeted with ,
```

4.25 Pb_avec_liste_conc

Description: Class to create a classical problem with a list of scalar concentration equations.

Keyword Discretize should have already been used to read the object.

```
See also: Pb_base (4.22) Pb_Thermohydraulique_List_Concentration_Turbulent (4.21) Pb_Hydraulique_List_Concentration_Turbulent (4.13) Pb_Thermohydraulique_List_Concentration (4.20) Pb_Hydraulique_List_Concentration (4.21)

Usage:

pb_avec_liste_conc str

Read str {

    list_equations listeqn
    [ milieu milieu_base]
    [ constituant constituant]
    [ Post_processing|postraitement corps_postraitement]
    [ Post_processings|postraitements post_processings]
```

} where

- **list_equations** *listeqn* (4.12): convection_diffusion_concentration equations. The unknown of the concentration equation number N is named concentrationN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.

[liste_de_postraitements liste_post_ok]
[liste_postraitements liste_post]
[sauvegarde format_file_base]
[sauvegarde_simple format_file_base]

[resume_last_time format_file_base]

[reprise format_file_base]

- **Post_processinglpostraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- resume_last_time format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name file file, resume the calculation at the last time found in the file (tinit is set to last time

of saved files).

4.26 Pb_avec_passif

Description: Class to create a classical problem with a scalar transport equation (e.g. temperature or concentration) and an additional set of passive scalars (e.g. temperature or concentration) equations.

Keyword Discretize should have already been used to read the object.

See also: Pb_base (4.22) pb_thermohydraulique_turbulent_scalaires_passifs (4.52) pb_thermohydraulique_especes_turbulent_qc (4.47) pb_hydraulique_concentration_turbulent_scalaires_passifs (4.31) pb_thermohydraulique_concentration_turbulent_scalaires_passifs (4.44) pb_thermohydraulique_especes_QC (4.45) pb_thermohydraulique_especes_WC (4.46) pb_thermohydraulique_concentration_scalaires_passifs (4.42) pb_thermohydraulique_scalaires_passifs (4.49) pb_hydraulique_concentration_scalaires_passifs (4.29)

```
Usage:
```

```
pb_avec_passif str

Read str {

    equations_scalaires_passifs listeqn
    [milieu milieu_base]
    [constituant constituant]
    [Post_processing|postraitement corps_postraitement]
    [Post_processings|postraitements post_processings]
    [liste_de_postraitements liste_post_ok]
    [liste_postraitements liste_post]
    [sauvegarde format_file_base]
    [sauvegarde_simple format_file_base]
    [reprise format_file_base]
    [resume_last_time format_file_base]
}
where
```

- equations_scalaires_passifs listeqn (4.12): Passive scalar equations. The unknowns of the passive scalar equation number N are named temperatureN or concentrationN or fraction_massiqueN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- liste de postraitements liste post ok (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.

- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.27 Pb_hydraulique

Description: Resolution of the Navier-Stokes equations.

Keyword Discretize should have already been used to read the object.

```
See also: Pb_base (4.22)
```

where

```
Usage:
pb hydraulique str
Read str {
     fluide_incompressible fluide_incompressible
     navier stokes standard navier stokes standard
     [ milieu milieu base]
     [constituant constituant]
     [ Post_processing|postraitement corps_postraitement]
     [ Post processings|postraitements post processings]
     [ liste_de_postraitements liste_post_ok]
     [liste postraitements liste post]
     [ sauvegarde format_file_base]
     [ sauvegarde_simple format_file_base]
     [reprise format_file_base]
     [ resume_last_time format_file_base]
}
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- navier_stokes_standard navier_stokes_standard (5.42): Navier-Stokes equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.

- sauvegarde format_file_base (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- sauvegarde simple format file base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the namefile file (see the class format file). If format reprise is xyz, the name file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema temps base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- resume_last_time format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.28 Pb_hydraulique_concentration

Description: Resolution of Navier-Stokes/multiple constituent transport equations.

```
Keyword Discretize should have already been used to read the object.
```

```
Usage:
pb_hydraulique_concentration str
```

}

See also: Pb_base (4.22)

```
Read str {
     fluide_incompressible fluide_incompressible
     [constituant constituant]
     [ navier stokes standard navier stokes standard]
     [ convection_diffusion_concentration convection_diffusion_concentration]
     [ milieu milieu_base]
     [ Post_processing|postraitement corps_postraitement]
     [ Post_processings|postraitements post_processings]
     [ liste_de_postraitements liste_post_ok]
     [liste postraitements liste post]
     [ sauvegarde format_file_base]
     [ sauvegarde_simple format_file_base]
     [reprise format_file_base]
     [ resume_last_time format_file_base]
where
```

- fluide_incompressible fluide_incompressible (22.4): The fluid medium associated with the prob-
- **constituant** *constituant* (22.1): Constituents.
- navier_stokes_standard navier_stokes_standard (5.42): Navier-Stokes equations.
- convection_diffusion_concentration convection_diffusion_concentration (5.21): Constituent transport vectorial equation (concentration diffusion convection).
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- Post_processing|postraitement corps_postraitement (4.2) for inheritance: One post-processing (without name).

- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.29 Pb_hydraulique_concentration_scalaires_passifs

Description: Resolution of Navier-Stokes/multiple constituent transport equations with the additional passive scalar equations.

```
Keyword Discretize should have already been used to read the object.
See also: pb_avec_passif (4.26)
Usage:
pb hydraulique concentration scalaires passifs str
Read str {
     fluide incompressible fluide incompressible
     [constituant constituant]
     [ navier stokes standard navier stokes standard]
     [convection_diffusion_concentration convection_diffusion_concentration]
     equations scalaires passifs listegn
      [ milieu milieu base]
      [ Post processing|postraitement corps_postraitement]
      [ Post_processings|postraitements post_processings]
     [ liste_de_postraitements liste_post_ok]
      [liste_postraitements liste_post]
     [ sauvegarde format_file_base]
     [ sauvegarde_simple format_file_base]
     [reprise format_file_base]
      [ resume_last_time format_file_base]
}
where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- **constituant** *constituant* (22.1): Constituents.
- navier_stokes_standard navier_stokes_standard (5.42): Navier-Stokes equations.
- **convection_diffusion_concentration** *convection_diffusion_concentration* (5.21): Constituent transport equations (concentration diffusion convection).
- equations_scalaires_passifs listeqn (4.12) for inheritance: Passive scalar equations. The unknowns of the passive scalar equation number N are named temperatureN or concentrationN or fraction_massiqueN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.30 Pb_hydraulique_concentration_turbulent

Description: Resolution of Navier-Stokes/multiple constituent transport equations, with turbulence modelling.

```
Keyword Discretize should have already been used to read the object.

See also: Pb_base (4.22)

Usage:

pb_hydraulique_concentration_turbulent str

Read str {

fluide_incompressible fluide_incompressible

[ constituant constituant]
```

```
[ navier_stokes_turbulent navier_stokes_turbulent]
[ convection_diffusion_concentration_turbulent convection_diffusion_concentration_turbulent]
[ milieu milieu_base]
[ Post_processing|postraitement corps_postraitement]
[ Post_processings|postraitements post_processings]
[ liste_de_postraitements liste_post_ok]
[ liste_postraitements liste_post]
[ sauvegarde format_file_base]
[ sauvegarde_simple format_file_base]
[ reprise format_file_base]
[ resume_last_time format_file_base]
]
where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- **constituant** *constituant* (22.1): Constituents.
- navier_stokes_turbulent navier_stokes_turbulent (5.43): Navier-Stokes equations as well as the associated turbulence model equations.
- convection_diffusion_concentration_turbulent convection_diffusion_concentration_turbulent (5.22): Constituent transport equations (concentration diffusion convection) as well as the associated turbulence model equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- liste_de_postraitements liste_post_ok (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.31 Pb_hydraulique_concentration_turbulent_scalaires_passifs

Description: Resolution of Navier-Stokes/multiple constituent transport equations, with turbulence modelling and with the additional passive scalar equations.

Keyword Discretize should have already been used to read the object. See also: pb avec passif (4.26) pb hydraulique concentration turbulent scalaires passifs str Read str { fluide_incompressible fluide_incompressible [constituant constituant] [navier_stokes_turbulent navier_stokes_turbulent] $[\ \ convection_diffusion_concentration_turbulent \ \ \ convection_diffusion_concentration_turbulent]$ equations_scalaires_passifs listeqn [milieu milieu_base] [Post_processing|postraitement corps_postraitement] [Post_processings|postraitements post_processings] [liste de postraitements liste post ok] [liste_postraitements liste_post] [sauvegarde format file base] [sauvegarde_simple format_file_base] [reprise format file base] [resume last time format file base] } where

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem
- **constituant** *constituant* (22.1): Constituents.
- navier_stokes_turbulent navier_stokes_turbulent (5.43): Navier-Stokes equations as well as the associated turbulence model equations.
- convection_diffusion_concentration_turbulent convection_diffusion_concentration_turbulent (5.22): Constituent transport equations (concentration diffusion convection) as well as the associated turbulence model equations.
- equations_scalaires_passifs listeqn (4.12) for inheritance: Passive scalar equations. The unknowns of the passive scalar equation number N are named temperatureN or concentrationN or fraction_massiqueN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified

for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.

- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.32 Pb_hydraulique_ibm

Description: Resolution of the IBM Navier-Stokes equations.

```
Keyword Discretize should have already been used to read the object. See also: Pb_base (4.22)
```

```
Usage:
pb_hydraulique_ibm str
Read str {
     fluide incompressible fluide incompressible
     navier_stokes_ibm navier_stokes_ibm
     [ milieu milieu base]
     [constituant constituant]
     [ Post processing|postraitement corps postraitement]
     [ Post_processings|postraitements post_processings]
     [ liste_de_postraitements liste_post_ok]
     [liste_postraitements liste_post]
     [ sauvegarde format_file_base]
     [ sauvegarde_simple format_file_base]
     [reprise format file base]
     [ resume_last_time format_file_base]
}
where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- navier stokes ibm navier stokes ibm (5.39): IBM Navier-Stokes equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This

block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.

- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.33 Pb_hydraulique_melange_binaire_qc

where

Description: Resolution of a binary mixture problem for a quasi-compressible fluid with an iso-thermal condition.

```
Keywords for the unknowns other than pressure, velocity, fraction_massique are:
masse_volumique : density
pression: reduced pressure
pression_tot: total pressure.
Keyword Discretize should have already been used to read the object.
See also: Pb base (4.22)
pb_hydraulique_melange_binaire_QC str
Read str {
     fluide_quasi_compressible fluide_quasi_compressible
     [constituant constituant]
     navier_stokes_QC navier_stokes_qc
     convection_diffusion_espece_binaire_QC convection_diffusion_espece_binaire_qc
     [ milieu milieu_base]
     [ Post_processing|postraitement corps_postraitement]
     [ Post processings|postraitements post processings]
     [liste de postraitements liste post ok]
     [liste postraitements liste post]
     [ sauvegarde format_file_base]
     [sauvegarde simple format file base]
     [reprise format_file_base]
     [resume last time format file base]
```

• **fluide_quasi_compressible** *fluide_quasi_compressible* (22.6): The fluid medium associated with the problem.

- **constituant** *constituant* (22.1): The various constituants associated to the problem.
- navier_stokes_QC navier_stokes_qc (5.34): Navier-Stokes equation for a quasi-compressible fluid.
- convection_diffusion_espece_binaire_QC convection_diffusion_espece_binaire_qc (5.23): Species conservation equation for a binary quasi-compressible fluid.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- sauvegarde format_file_base (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.34 Pb_hydraulique_melange_binaire_wc

Description: Resolution of a binary mixture problem for a weakly-compressible fluid with an iso-thermal condition.

```
Keywords for the unknowns other than pressure, velocity, fraction_massique are:
```

```
masse_volumique : density
pression : reduced pressure
pression_tot : total pressure
pression_hydro : hydro-static pressure
pression_eos : pressure used in state equation.
```

Keyword Discretize should have already been used to read the object.

```
See also: Pb base (4.22)
```

```
Usage:
```

```
pb_hydraulique_melange_binaire_WC str
Read str {
    fluide_weakly_compressible fluide_weakly_compressible
    navier_stokes_WC navier_stokes_wc
```

```
convection_diffusion_espece_binaire_WC convection_diffusion_espece_binaire_wc
[ milieu milieu_base]
[ constituant constituant]
[ Post_processing|postraitement corps_postraitement]
[ Post_processings|postraitements post_processings]
[ liste_de_postraitements liste_post_ok]
[ liste_postraitements liste_post]
[ sauvegarde format_file_base]
[ sauvegarde_simple format_file_base]
[ reprise format_file_base]
[ resume_last_time format_file_base]
]
```

- **fluide_weakly_compressible** *fluide_weakly_compressible* (22.12): The fluid medium associated with the problem.
- navier_stokes_WC navier_stokes_wc (5.38): Navier-Stokes equation for a weakly-compressible fluid.
- **convection_diffusion_espece_binaire_WC** *convection_diffusion_espece_binaire_wc* (5.24): Species conservation equation for a binary weakly-compressible fluid.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- liste de postraitements liste post ok (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- sauvegarde format_file_base (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.35 Pb_hydraulique_melange_binaire_turbulent_qc

Description: Resolution of a turbulent binary mixture problem for a quasi-compressible fluid with an isothermal condition.

```
Keyword Discretize should have already been used to read the object.
See also: Pb base (4.22)
Usage:
pb_hydraulique_melange_binaire_turbulent_qc str
Read str {
     fluide_quasi_compressible fluide_quasi_compressible
     navier stokes turbulent qc navier stokes turbulent qc
     Convection_Diffusion_Espece_Binaire_Turbulent_QC convection_diffusion_espece_binaire_turbulent-
     [ milieu milieu_base]
     [constituant constituant]
     [ Post_processing|postraitement corps_postraitement]
     [ Post_processings|postraitements post_processings]
     [ liste_de_postraitements liste_post_ok]
     [liste_postraitements liste_post]
     [sauvegarde format file base]
     [sauvegarde simple format file base]
     [ reprise format_file_base]
     [ resume_last_time format_file_base]
}
where
```

- **fluide_quasi_compressible** *fluide_quasi_compressible* (22.6): The fluid medium associated with the problem.
- navier_stokes_turbulent_qc navier_stokes_turbulent_qc (5.44): Navier-Stokes equation for a quasi-compressible fluid as well as the associated turbulence model equations.
- Convection_Diffusion_Espece_Binaire_Turbulent_QC convection_diffusion_espece_binaire_turbulent_ _qc (5.9): Species conservation equation for a quasi-compressible fluid as well as the associated turbulence model equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- liste de postraitements liste post ok (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- **reprise** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the

calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.

• **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.36 Pb_hydraulique_turbulent

Description: Resolution of Navier-Stokes equations with turbulence modelling.

Keyword Discretize should have already been used to read the object.

```
See also: Pb_base (4.22)
```

```
Usage:
pb hydraulio
```

```
pb_hydraulique_turbulent str
Read str {
     fluide_incompressible fluide_incompressible
     navier stokes turbulent navier stokes turbulent
     [ milieu milieu_base]
     [constituant constituant]
     [ Post_processing|postraitement corps_postraitement]
     [ Post_processings|postraitements post_processings]
     [liste de postraitements liste post ok]
     [liste postraitements liste post]
     [sauvegarde format file base]
     [ sauvegarde_simple format_file_base]
     [ reprise format_file_base]
     [ resume_last_time format_file_base]
}
where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- navier_stokes_turbulent navier_stokes_turbulent (5.43): Navier-Stokes equations as well as the associated turbulence model equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- liste de postraitements liste post ok (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.

- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.37 Pb_post

```
Description: not_set
Keyword Discretize should have already been used to read the object.
See also: Pb_base (4.22)
Usage:
pb_post str
Read str {
     [ milieu milieu base]
     [constituant constituant]
      [ Post_processing|postraitement corps_postraitement]
     [ Post_processings|postraitements post_processings]
     [ liste_de_postraitements liste_post_ok]
     [liste_postraitements liste_post]
      [ sauvegarde format_file_base]
     [ sauvegarde_simple format_file_base]
     [reprise format_file_base]
     [ resume_last_time format_file_base]
}
where
```

- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.

- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format file base (4.6) for inheritance: Keyword to resume a calculation based on the name-_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema temps base) time fields are taken from the name file file. If there is no backup corresponding to this time in the name file, TRUST exits in
- resume_last_time format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

Pb_thermohydraulique

where

Description: Resolution of thermohydraulic problem.

```
Keyword Discretize should have already been used to read the object.
```

```
See also: Pb base (4.22)
Usage:
pb_thermohydraulique str
Read str {
     [ fluide_incompressible | fluide_incompressible]
     [ fluide ostwald]
     [fluide sodium liquide fluide sodium liquide]
     [fluide sodium gaz fluide sodium gaz]
     [correlations bloc_lecture]
     [ navier_stokes_standard navier_stokes_standard]
     [convection diffusion temperature convection diffusion temperature]
     [ milieu milieu_base]
     [constituant constituant]
     [ Post_processing|postraitement corps_postraitement]
     [ Post_processings|postraitements post_processings]
     [ liste_de_postraitements liste_post_ok]
     [liste postraitements liste post]
     [ sauvegarde format_file_base]
     [ sauvegarde_simple format_file_base]
     [ reprise format_file_base]
     [ resume_last_time format_file_base]
}
```

- fluide_incompressible fluide_incompressible (22.4): The fluid medium associated with the problem (only one possibility).
- fluide_ostwald fluide_ostwald (22.5): The fluid medium associated with the problem (only one possibility).
- fluide_sodium_liquide fluide_sodium_liquide (22.10): The fluid medium associated with the problem (only one possibility).
- fluide_sodium_gaz fluide_sodium_gaz (22.9): The fluid medium associated with the problem (only one possibility).

- **correlations** *bloc_lecture* (3.59): List of correlations used in specific source terms (i.e. interfacial flux, interfacial friction, ...)
- navier stokes standard navier stokes standard (5.42): Navier-Stokes equations.
- **convection_diffusion_temperature** *convection_diffusion_temperature* (5.28): Energy equation (temperature diffusion convection).
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.
- **Post_processinglyostraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.39 Pb_thermohydraulique_qc

```
Description: Resolution of thermo-hydraulic problem for a quasi-compressible fluid.

Keywords for the unknowns other than pressure, velocity, temperature are:
masse_volumique: density
enthalpie: enthalpy
pression: reduced pressure
pression_tot: total pressure.

Keyword Discretize should have already been used to read the object.

See also: Pb_base (4.22)

Usage:
pb_thermohydraulique_QC str
Read str {

fluide_quasi_compressible fluide_quasi_compressible
navier_stokes_QC navier_stokes_qc
convection_diffusion_chaleur_QC convection_diffusion_chaleur_qc
```

```
[ milieu milieu_base]
[ constituant constituant]
[ Post_processinglpostraitement corps_postraitement]
[ Post_processings|postraitements post_processings]
[ liste_de_postraitements liste_post_ok]
[ liste_postraitements liste_post]
[ sauvegarde format_file_base]
[ sauvegarde_simple format_file_base]
[ reprise format_file_base]
[ resume_last_time format_file_base]
}
where
```

- **fluide_quasi_compressible** *fluide_quasi_compressible* (22.6): The fluid medium associated with the problem.
- navier_stokes_QC navier_stokes_qc (5.34): Navier-Stokes equation for a quasi-compressible fluid.
- **convection_diffusion_chaleur_QC** *convection_diffusion_chaleur_qc* (5.18): Temperature equation for a quasi-compressible fluid.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.
- **Post_processinglyostraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.40 Pb_thermohydraulique_wc

Description: Resolution of thermo-hydraulic problem for a weakly-compressible fluid.

Keywords for the unknowns other than pressure, velocity, temperature are:

masse_volumique : density

```
pression: reduced pressure
pression_tot: total pressure
pression hydro: hydro-static pressure
pression_eos: pressure used in state equation.
Keyword Discretize should have already been used to read the object.
See also: Pb base (4.22)
Usage:
pb thermohydraulique WC str
Read str {
     fluide_weakly_compressible fluide_weakly_compressible
     navier stokes WC navier stokes wc
     convection_diffusion_chaleur_WC convection_diffusion_chaleur_wc
     [ milieu milieu_base]
     [constituant constituant]
     [ Post _processing|postraitement _corps_postraitement]
     [ Post processings|postraitements post processings]
     [liste de postraitements liste post ok]
     [liste postraitements liste post]
     [sauvegarde format file base]
     [ sauvegarde_simple format_file_base]
     [reprise format file base]
     [resume last time format file base]
where
```

- **fluide_weakly_compressible** *fluide_weakly_compressible* (22.12): The fluid medium associated with the problem.
- navier_stokes_WC navier_stokes_wc (5.38): Navier-Stokes equation for a weakly-compressible fluid.
- **convection_diffusion_chaleur_WC** *convection_diffusion_chaleur_wc* (5.19): Temperature equation for a weakly-compressible fluid.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- **reprise** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz

file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.

• **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.41 Pb_thermohydraulique_concentration

Description: Resolution of Navier-Stokes/energy/multiple constituent transport equations.

```
Keyword Discretize should have already been used to read the object.
See also: Pb_base (4.22)
pb thermohydraulique concentration str
Read str {
     fluide_incompressible fluide_incompressible
     [constituant constituant]
     [ navier_stokes_standard navier_stokes_standard]
     [convection diffusion concentration convection diffusion concentration]
     [convection diffusion temperature convection diffusion temperature]
     [ milieu milieu base]
     [ Post processing|postraitement corps postraitement]
     [ Post processings|postraitements post processings]
     [ liste_de_postraitements liste_post_ok]
     [liste_postraitements liste_post]
     [sauvegarde format file base]
     [ sauvegarde_simple format_file_base]
     [reprise format_file_base]
     [ resume_last_time format_file_base]
}
where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- constituant constituant (22.1): Constituents.
- navier_stokes_standard navier_stokes_standard (5.42): Navier-Stokes equations.
- **convection_diffusion_concentration** *convection_diffusion_concentration* (5.21): Constituent transport equations (concentration diffusion convection).
- **convection_diffusion_temperature** *convection_diffusion_temperature* (5.28): Energy equation (temperature diffusion convection).
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This

block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.

- sauvegarde format_file_base (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.42 Pb_thermohydraulique_concentration_scalaires_passifs

Description: Resolution of Navier-Stokes/energy/multiple constituent transport equations, with the additional passive scalar equations.

```
Keyword Discretize should have already been used to read the object.
See also: pb_avec_passif (4.26)
pb_thermohydraulique_concentration_scalaires_passifs str
Read str {
     fluide_incompressible fluide_incompressible
     [constituant constituant]
     [ navier_stokes_standard navier_stokes_standard]
     [ convection_diffusion_concentration convection_diffusion_concentration]
     [convection diffusion temperature]
     equations_scalaires_passifs listeqn
     [ milieu milieu base]
     [ Post_processing|postraitement corps_postraitement]
     [ Post processings|postraitements post processings]
     [ liste_de_postraitements liste_post_ok]
     [liste postraitements liste post]
     [sauvegarde format file base]
     [ sauvegarde simple format file base]
     [ reprise format_file_base]
     [ resume_last_time format_file_base]
where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- **constituant** *constituant* (22.1): Constituents.

- navier_stokes_standard navier_stokes_standard (5.42): Navier-Stokes equations.
- **convection_diffusion_concentration** *convection_diffusion_concentration* (5.21): Constituent transport equations (concentration diffusion convection).
- **convection_diffusion_temperature** *convection_diffusion_temperature* (5.28): Energy equations (temperature diffusion convection).
- equations_scalaires_passifs listeqn (4.12) for inheritance: Passive scalar equations. The unknowns of the passive scalar equation number N are named temperatureN or concentrationN or fraction_massiqueN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.43 Pb_thermohydraulique_concentration_turbulent

Description: Resolution of Navier-Stokes/energy/multiple constituent transport equations, with turbulence modelling.

```
Keyword Discretize should have already been used to read the object. See also: Pb_base (4.22)

Usage:
pb_thermohydraulique_concentration_turbulent str

Read str {

fluide_incompressible fluide_incompressible
[ constituant constituant]
[ navier_stokes_turbulent navier_stokes_turbulent]
```

```
[ convection_diffusion_concentration_turbulent convection_diffusion_concentration_turbulent]
    [ convection_diffusion_temperature_turbulent convection_diffusion_temperature_turbulent]
    [ milieu milieu_base]
    [ Post_processing|postraitement corps_postraitement]
    [ Post_processings|postraitements post_processings]
    [ liste_de_postraitements liste_post_ok]
    [ liste_postraitements liste_post]
    [ sauvegarde format_file_base]
    [ sauvegarde_simple format_file_base]
    [ reprise format_file_base]
    [ resume_last_time format_file_base]
}
where
```

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- **constituant** *constituant* (22.1): Constituents.
- navier_stokes_turbulent navier_stokes_turbulent (5.43): Navier-Stokes equations as well as the associated turbulence model equations.
- convection_diffusion_concentration_turbulent convection_diffusion_concentration_turbulent (5.22): Constituent transport equations (concentration diffusion convection) as well as the associated turbulence model equations.
- **convection_diffusion_temperature_turbulent** *convection_diffusion_temperature_turbulent* (5.32): Energy equation (temperature diffusion convection) as well as the associated turbulence model equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.44 Pb_thermohydraulique_concentration_turbulent_scalaires_passifs

Description: Resolution of Navier-Stokes/energy/multiple constituent transport equations, with turbulence modelling and with the additional passive scalar equations.

Keyword Discretize should have already been used to read the object. See also: pb_avec_passif (4.26) pb thermohydraulique concentration turbulent scalaires passifs str Read str { **fluide_incompressible** *fluide_incompressible* [constituant constituant] [navier_stokes_turbulent navier_stokes_turbulent] [convection_diffusion_concentration_turbulent convection_diffusion_concentration_turbulent] [convection_diffusion_temperature_turbulent convection_diffusion_temperature_turbulent] equations scalaires passifs listegn [milieu milieu base] [Post_processing|postraitement corps_postraitement] [Post processings|postraitements post processings] [liste_de_postraitements liste_post_ok] [liste postraitements liste post] [sauvegarde format file base] [sauvegarde_simple format_file_base] [reprise format_file_base] [resume_last_time format_file_base] where

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- **constituant** *constituant* (22.1): Constituents.
- navier_stokes_turbulent navier_stokes_turbulent (5.43): Navier-Stokes equations as well as the associated turbulence model equations.
- convection_diffusion_concentration_turbulent convection_diffusion_concentration_turbulent (5.22): Constituent transport equations (concentration diffusion convection) as well as the associated turbulence model equations.
- convection_diffusion_temperature_turbulent convection_diffusion_temperature_turbulent (5.32): Energy equations (temperature diffusion convection) as well as the associated turbulence model equations.
- equations_scalaires_passifs listeqn (4.12) for inheritance: Passive scalar equations. The unknowns of the passive scalar equation number N are named temperatureN or concentrationN or fraction_massiqueN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu base (22) for inheritance: The medium associated with the problem.
- **Post_processinglyostraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- liste de postraitements liste post ok (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This

block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.

- sauvegarde format_file_base (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- sauvegarde simple format file base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name-_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in
- **resume_last_time** format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

Pb_thermohydraulique_especes_qc

Description: Resolution of thermo-hydraulic problem for a multi-species quasi-compressible fluid.

Keyword Discretize should have already been used to read the object. See also: pb_avec_passif (4.26)

```
Usage:
```

}

```
pb_thermohydraulique_especes_QC str
Read str {
     fluide_quasi_compressible fluide_quasi_compressible
     navier_stokes_QC navier_stokes_qc
     {\bf convection\_diffusion\_chaleur\_QC} \quad {\it convection\_diffusion\_chaleur\_qc}
     equations_scalaires_passifs listeqn
     [ milieu milieu_base]
     [constituant constituant]
     [ Post_processing|postraitement corps_postraitement]
      [ Post processings|postraitements post_processings]
     [ liste_de_postraitements liste_post_ok]
     [liste postraitements liste post]
     [ sauvegarde format_file_base]
      [ sauvegarde simple format file base]
     [reprise format_file_base]
     [ resume_last_time format_file_base]
where
```

- fluide_quasi_compressible fluide_quasi_compressible (22.6): The fluid medium associated with the problem.
- navier_stokes_QC navier_stokes_qc (5.34): Navier-Stokes equation for a quasi-compressible fluid.

- **convection_diffusion_chaleur_QC** *convection_diffusion_chaleur_qc* (5.18): Temperature equation for a quasi-compressible fluid.
- equations_scalaires_passifs listeqn (4.12) for inheritance: Passive scalar equations. The unknowns of the passive scalar equation number N are named temperatureN or concentrationN or fraction_massiqueN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.
- **Post_processinglyostraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.46 Pb_thermohydraulique_especes_wc

[milieu milieu_base]
[constituant constituant]

Description: Resolution of thermo-hydraulic problem for a multi-species weakly-compressible fluid.

Keyword Discretize should have already been used to read the object.

See also: pb_avec_passif (4.26)

Usage:
pb_thermohydraulique_especes_WC str

Read str {

fluide_weakly_compressible fluide_weakly_compressible
navier_stokes_WC navier_stokes_wc
convection_diffusion_chaleur_WC convection_diffusion_chaleur_wc
equations_scalaires_passifs listegn

```
[ Post_processing|postraitement corps_postraitement]
[ Post_processings|postraitements post_processings]
[ liste_de_postraitements liste_post_ok]
[ liste_postraitements liste_post]
[ sauvegarde format_file_base]
[ sauvegarde_simple format_file_base]
[ reprise format_file_base]
[ resume_last_time format_file_base]
}
where
```

- **fluide_weakly_compressible** *fluide_weakly_compressible* (22.12): The fluid medium associated with the problem.
- navier_stokes_WC navier_stokes_wc (5.38): Navier-Stokes equation for a weakly-compressible fluid.
- **convection_diffusion_chaleur_WC** *convection_diffusion_chaleur_wc* (5.19): Temperature equation for a weakly-compressible fluid.
- equations_scalaires_passifs listeqn (4.12) for inheritance: Passive scalar equations. The unknowns of the passive scalar equation number N are named temperatureN or concentrationN or fraction_massiqueN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.47 Pb_thermohydraulique_especes_turbulent_qc

Description: Resolution of turbulent thermohydraulic problem under low Mach number with passive scalar equations.

Keyword Discretize should have already been used to read the object. See also: pb avec passif (4.26) Usage: pb_thermohydraulique_especes_turbulent_qc str Read str { fluide_quasi_compressible fluide_quasi_compressible navier stokes turbulent qc navier stokes turbulent qc convection_diffusion_chaleur_turbulent_qc convection_diffusion_chaleur_turbulent_qc equations_scalaires_passifs listeqn [milieu milieu_base] [constituant constituant] [Post_processing|postraitement corps_postraitement] [Post_processings|postraitements post_processings] [liste de postraitements liste post ok] [liste_postraitements liste_post] [sauvegarde format file base] [sauvegarde_simple format_file_base] [reprise format file base] [resume last time format file base] } where

- **fluide_quasi_compressible** *fluide_quasi_compressible* (22.6): The fluid medium associated with the problem.
- navier_stokes_turbulent_qc navier_stokes_turbulent_qc (5.44): Navier-Stokes equations under low Mach number as well as the associated turbulence model equations.
- **convection_diffusion_chaleur_turbulent_qc** convection_diffusion_chaleur_turbulent_qc (5.20): Energy equation under low Mach number as well as the associated turbulence model equations.
- equations_scalaires_passifs listeqn (4.12) for inheritance: Passive scalar equations. The unknowns of the passive scalar equation number N are named temperatureN or concentrationN or fraction_massiqueN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified

for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.

- sauvegarde simple format file base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format file base (4.6) for inheritance: Keyword to resume a calculation based on the name-_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema temps base) time fields are taken from the name file file. If there is no backup corresponding to this time in the name file, TRUST exits in error.
- resume_last_time format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

Pb thermohydraulique ibm

Description: Resolution of IBM thermohydraulic problem.

```
Keyword Discretize should have already been used to read the object.
See also: Pb_base (4.22)
```

```
Usage:
```

```
pb_thermohydraulique_ibm str
Read str {
     [fluide incompressible fluide incompressible]
     [fluide ostwald]
     [ navier_stokes_ibm navier_stokes_ibm]
     [ convection_diffusion_temperature_ibm convection_diffusion_temperature_ibm]
     [ milieu milieu base]
     [constituant constituant]
     [ Post_processing|postraitement corps_postraitement]
     [ Post_processings|postraitements post_processings]
     [ liste_de_postraitements liste_post_ok]
     [liste_postraitements liste_post]
     [sauvegarde format file base]
     [ sauvegarde_simple format_file_base]
     [reprise format_file_base]
     [ resume_last_time format_file_base]
where
```

- fluide incompressible fluide incompressible (22.4): The fluid medium associated with the problem (only one possibility).
- fluide ostwald fluide ostwald (22.5): The fluid medium associated with the problem (only one possibility).
- navier_stokes_ibm navier_stokes_ibm (5.39): IBM Navier-Stokes equations.
- convection_diffusion_temperature_ibm convection_diffusion_temperature_ibm (5.30): IBM Energy equation (temperature diffusion convection).
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.

- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.49 Pb_thermohydraulique_scalaires_passifs

Description: Resolution of thermohydraulic problem, with the additional passive scalar equations.

Keyword Discretize should have already been used to read the object. See also: pb_avec_passif (4.26)

```
Usage: pb_thermohydraulique_scalaires_passifs str Read str {
```

}

```
fluide_incompressible fluide_incompressible

[ constituant constituant]

[ navier_stokes_standard navier_stokes_standard]

[ convection_diffusion_temperature convection_diffusion_temperature]

equations_scalaires_passifs listeqn

[ milieu milieu_base]

[ Post_processinglpostraitement corps_postraitement]

[ Post_processings|postraitements post_processings]

[ liste_de_postraitements liste_post_ok]

[ liste_postraitements liste_post]

[ sauvegarde format_file_base]

[ sauvegarde_simple format_file_base]

[ reprise format_file_base]

[ resume_last_time format_file_base]
```

where

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem
- **constituant** *constituant* (22.1): Constituents.
- navier_stokes_standard navier_stokes_standard (5.42): Navier-Stokes equations.
- **convection_diffusion_temperature** *convection_diffusion_temperature* (5.28): Energy equations (temperature diffusion convection).
- equations_scalaires_passifs listeqn (4.12) for inheritance: Passive scalar equations. The unknowns of the passive scalar equation number N are named temperatureN or concentrationN or fraction_massiqueN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.50 Pb_thermohydraulique_turbulent

Description: Resolution of thermohydraulic problem, with turbulence modelling.

Keyword Discretize should have already been used to read the object. See also: Pb base (4.22)

Usage:

pb_thermohydraulique_turbulent str Read str {

fluide_incompressible fluide_incompressible navier stokes turbulent navier stokes turbulent

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- navier_stokes_turbulent navier_stokes_turbulent (5.43): Navier-Stokes equations as well as the associated turbulence model equations.
- **convection_diffusion_temperature_turbulent** *convection_diffusion_temperature_turbulent* (5.32): Energy equation (temperature diffusion convection) as well as the associated turbulence model equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.
- **Post_processinglyostraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- liste_de_postraitements liste_post_ok (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- **sauvegarde_simple** *format_file_base* (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.51 Pb_thermohydraulique_turbulent_qc

Description: Resolution of turbulent thermohydraulic problem under low Mach number. Warning: Available for VDF and VEF P0/P1NC discretization only. Keyword Discretize should have already been used to read the object. See also: Pb base (4.22) Usage: pb_thermohydraulique_turbulent_qc str Read str { fluide_quasi_compressible fluide_quasi_compressible navier stokes turbulent qc navier stokes turbulent qc convection_diffusion_chaleur_turbulent_qc convection_diffusion_chaleur_turbulent_qc [milieu milieu base] [constituant constituant] [Post_processing|postraitement corps_postraitement] [Post_processings|postraitements post_processings] [liste_de_postraitements liste_post_ok] [liste postraitements liste post] [sauvegarde format_file_base] [sauvegarde_simple format_file_base] [reprise format_file_base] [resume_last_time format_file_base]

- **fluide_quasi_compressible** *fluide_quasi_compressible* (22.6): The fluid medium associated with the problem.
- navier_stokes_turbulent_qc navier_stokes_turbulent_qc (5.44): Navier-Stokes equations under low Mach number as well as the associated turbulence model equations.
- **convection_diffusion_chaleur_turbulent_qc** convection_diffusion_chaleur_turbulent_qc (5.20): Energy equation under low Mach number as well as the associated turbulence model equations.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- constituant constituant (22.1) for inheritance: Constituent.

} where

- Post_processing|postraitement corps_postraitement (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- **reprise** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz

file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.

• **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.52 Pb_thermohydraulique_turbulent_scalaires_passifs

Description: Resolution of thermohydraulic problem, with turbulence modelling and with the additional passive scalar equations.

Keyword Discretize should have already been used to read the object. See also: pb avec passif (4.26) Usage: pb thermohydraulique turbulent scalaires passifs str Read str { **fluide_incompressible** *fluide_incompressible* [constituant constituant] [navier stokes turbulent navier stokes turbulent] [convection_diffusion_temperature_turbulent convection_diffusion_temperature_turbulent] equations scalaires passifs listegn [milieu milieu base] [Post_processing|postraitement corps_postraitement] [Post_processings|postraitements post_processings] [liste_de_postraitements liste_post_ok] [liste postraitements liste post] [sauvegarde format_file_base] [sauvegarde_simple format_file_base] [reprise format_file_base] [resume_last_time format_file_base] }

- **fluide_incompressible** *fluide_incompressible* (22.4): The fluid medium associated with the problem.
- constituant constituant (22.1): Constituents.

where

- navier_stokes_turbulent navier_stokes_turbulent (5.43): Navier-Stokes equations as well as the associated turbulence model equations.
- convection_diffusion_temperature_turbulent convection_diffusion_temperature_turbulent (5.32): Energy equations (temperature diffusion convection) as well as the associated turbulence model equations.
- equations_scalaires_passifs listeqn (4.12) for inheritance: Passive scalar equations. The unknowns of the passive scalar equation number N are named temperatureN or concentrationN or fraction_massiqueN. This keyword is used to define initial conditions and the post processing fields. This kind of problem is very useful to test in only one data file (and then only one calculation) different schemes or different boundary conditions for the scalar transport equation.
- milieu milieu_base (22) for inheritance: The medium associated with the problem.

- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings**|**postraitements**| post_processings (4.3) for inheritance: List of Postraitement objects (with name).
- **liste_de_postraitements** *liste_post_ok* (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.
- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

4.53 Pbc med

Description: Allows to read med files and post-process them.

```
See also: pb_gen_base (4)

Usage:
pbc_med list_info_med
where

• list_info_med list_info_med (4.54)
```

4.54 List_info_med

```
Description: not_set

See also: listobj (38.5)

Usage:
{ object1 , object2 .... }
list of info_med (4.54.1) separeted with ,
```

4.54.1 Info_med

Description: not_set

```
See also: objet_lecture (39)

Usage:
file_med domaine pb_post
where

• file_med str: Name of the MED file.
• domaine str: Name of domain.
• pb_post pb_post (4.37)
```

4.55 Problem_read_generic

Description: The probleme_read_generic differs rom the rest of the TRUST code: The problem does not state the number of equations that are enclosed in the problem. As the list of equations to be solved in the generic read problem is declared in the data file and not pre-defined in the structure of the problem, each equation has to be distinctively associated with the problem with the Associate keyword.

Keyword Discretize should have already been used to read the object. See also: Pb base (4.22)

```
Usage:

problem_read_generic str

Read str {

    [ milieu milieu_base]
    [ constituant constituant]
    [ Post_processing|postraitement corps_postraitement]
    [ Post_processings|postraitements post_processings]
    [ liste_de_postraitements liste_post_ok]
    [ liste_postraitements liste_post]
    [ sauvegarde format_file_base]
    [ sauvegarde_simple format_file_base]
    [ reprise format_file_base]
    [ resume_last_time format_file_base]
}
where
```

- milieu milieu_base (22) for inheritance: The medium associated with the problem.
- **constituant** *constituant* (22.1) for inheritance: Constituent.
- **Post_processing|postraitement** *corps_postraitement* (4.2) for inheritance: One post-processing (without name).
- **Post_processings|postraitements** *post_processings* (4.3) for inheritance: List of Postraitement objects (with name).
- liste_de_postraitements liste_post_ok (4.4) for inheritance: This
- **liste_postraitements** *liste_post* (4.5) for inheritance: This block defines the output files to be written during the computation. The output format is lata in order to use OpenDX to draw the results. This block can be divided in one or several sub-blocks that can be written at different frequencies and in different directories. Attention. The directory lata used in this example should be created before running the computation or the lata files will be lost.
- **sauvegarde** *format_file_base* (4.6) for inheritance: Keyword used when calculation results are to be backed up. When a coupling is performed, the backup-recovery file name must be well specified for each problem. In this case, you must save to different files and correctly specify these files when resuming the calculation.

- sauvegarde_simple format_file_base (4.6) for inheritance: The same keyword than Sauvegarde except, the last time step only is saved.
- reprise format_file_base (4.6) for inheritance: Keyword to resume a calculation based on the name_file file (see the class format_file). If format_reprise is xyz, the name_file file should be the .xyz file created by the previous calculation. With this file, it is possible to resume a parallel calculation on P processors, whereas the previous calculation has been run on N (N<>P) processors. Should the calculation be resumed, values for the tinit (see schema_temps_base) time fields are taken from the name_file file. If there is no backup corresponding to this time in the name_file, TRUST exits in error.
- **resume_last_time** *format_file_base* (4.6) for inheritance: Keyword to resume a calculation based on the name_file file, resume the calculation at the last time found in the file (tinit is set to last time of saved files).

5 mor_eqn

```
Description: Class of equation pieces (morceaux d'equation).
See also: objet_u (40) eqn_base (5.33)
Usage:
5.1
      Conduction
Description: Heat equation.
Keyword Discretize should have already been used to read the object.
See also: eqn_base (5.33) Conduction_ibm (5.8)
Usage:
Conduction str
Read str {
     [ disable equation residual str]
     [convection bloc convection]
     [ diffusion bloc_diffusion]
     [boundary_conditions|conditions_limites condlims]
     [initial conditions|conditions initiales condinits]
     [sources sources]
     [ ecrire fichier xyz valeur ecrire fichier xyz valeur]
     [ parametre_equation parametre_equation_base]
     [ equation_non_resolue str]
     [renommer_equation str]
}
where
```

- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** bloc_convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)

- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }

• renommer_equation str for inheritance: Rename the equation with a specific name.

5.2 Bloc_convection

Description: not_set

See also: objet_lecture (39)

Usage:

aco operateur acof where

- aco str into ['{'}]: Opening curly bracket.
- **operateur** *convection_deriv* (5.2.1)
- acof str into ['}']: Closing curly bracket.

5.2.1 Convection_deriv

Description: not set

See also: objet_lecture (39) ale (5.2.2) muscl_old (5.2.3) muscl3 (5.2.4) ef (5.2.5) di_12 (5.2.7) amont_old (5.2.8) generic (5.2.9) ef_stab (5.2.10) kquick (5.2.13) muscl (5.2.14) muscl_new (5.2.15) quick (5.2.16) centre_old (5.2.17) negligeable (5.2.18) amont (5.2.19) centre (5.2.20) centre4 (5.2.21) btd (5.2.22) supg (5.2.23)

Usage:

convection_deriv

5.2.2 Ale

Description: A convective scheme for ALE (Arbitrary Lagrangian-Eulerian) framework.

See also: convection_deriv (5.2.1)

Usage:

ale opconv

where

• **opconv** *bloc_convection* (5.2): Choice between: amont and muscl Example: convection { ALE { amont } }

5.2.3 Muscl_old

Description: Only for VEF discretization.

```
See also: convection_deriv (5.2.1)
```

Usage:

muscl_old

5.2.4 Muscl3

Description: Keyword for a scheme using a ponderation between muscl and center schemes in VEF.

```
See also: convection_deriv (5.2.1)

Usage:
muscl3 {
    [alpha float]
}
where
```

• **alpha** *float*: To weight the scheme centering with the factor floattant (between 0 (full centered) and 1 (muscl), by default 1).

5.2.5 Ef

Description: For VEF calculations, a centred convective scheme based on Finite Elements formulation can be called through the following data:

Convection { EF transportant_bar val transporte_bar val antisym val filtrer_resu val }

This scheme is 2nd order accuracy (and get better the property of kinetic energy conservation). Due to possible problems of instabilities phenomena, this scheme has to be coupled with stabilisation process (see Source_Qdm_lambdaup). These two last data are equivalent from a theoretical point of view in variationnal writing to: div((u. grad ub , vb) - (u. grad vb, ub)), where vb corresponds to the filtered reference test functions.

Remark:

This class requires to define a filtering operator: see solveur_bar

```
See also: convection_deriv (5.2.1)
```

Usage:

```
ef [ mot1 ] [ bloc_ef ]
where
```

- mot1 str into ['defaut_bar']: equivalent to transportant_bar 0 transporte_bar 1 filtrer_resu 1 antisym
- **bloc_ef** *bloc_ef* (5.2.6)

5.2.6 Bloc_ef Description: not_set See also: objet lecture (39) Usage: mot1 val1 mot2 val2 mot3 val3 mot4 val4 where • mot1 str into ['transportant_bar', 'transporte_bar', 'filtrer_resu', 'antisym'] • **val1** int into [0, 1] • mot2 str into ['transportant_bar', 'transporte_bar', 'filtrer_resu', 'antisym'] • val2 int into [0, 1] • mot3 str into ['transportant_bar', 'transporte_bar', 'filtrer_resu', 'antisym'] • val3 int into [0, 1] • mot4 str into ['transportant_bar', 'transporte_bar', 'filtrer_resu', 'antisym'] • **val4** int into [0, 1] 5.2.7 Di 12 Description: Only for VEF discretization. See also: convection_deriv (5.2.1) Usage: di 12 5.2.8 Amont old Description: Only for VEF discretization, obsolete keyword, see amont. See also: convection_deriv (5.2.1)

5.2.9 Generic

Usage: amont_old

Description: Keyword for generic calling of upwind and muscl convective scheme in VEF discretization. For muscl scheme, limiters and order for fluxes calculations have to be specified. The available limiters are: minmod - vanleer -vanalbada - chakravarthy - superbee, and the order of accuracy is 1 or 2. Note that chakravarthy is a non-symmetric limiter and superbee may engender results out of physical limits. By consequence, these two limiters are not recommended.

```
Examples:
convection { generic amont }
convection { generic muscl minmod 1 }
convection { generic muscl vanleer 2 }
```

In case of results out of physical limits with muscl scheme (due for instance to strong non-conformal velocity flow field), user can redefine in data file a lower order and a smoother limiter, as : convection { generic muscl minmod 1 }

```
See also: convection_deriv (5.2.1)
```

```
Usage:
generic type [limiteur] [ordre] [alpha]
where
   • type str into ['amont', 'muscl', 'centre']: type of scheme
   • limiteur str into ['minmod', 'vanleer', 'vanalbada', 'chakravarthy', 'superbee']: type of limiter
   • ordre int into [1, 2, 3]: order of accuracy
   • alpha float: alpha
5.2.10 Ef stab
Description: Keyword for a VEF convective scheme.
See also: convection_deriv (5.2.1)
Usage:
ef_stab {
     [ alpha float]
     [test int]
     [tdivu]
     [ old ]
     [volumes_etendus]
```

- alpha *float*: To weight the scheme centering with the factor floattant (between 0 (full centered) and 1 (mix between upwind and centered), by default 1). For scalar equation, it is adviced to use alpha=1 and for the momentum equation, alpha=0.2 is adviced.
- test int: Developer option to compare old and new version of EF stab
- **tdivu**: To have the convective operator calculated as div(TU)-TdivU(=UgradT).
- **old**: To use old version of EF_stab scheme (default no).
- volumes_etendus: Option for the scheme to use the extended volumes (default, yes).
- volumes_non_etendus : Option for the scheme to not use the extended volumes (default, no).
- amont_sous_zone str: Option to degenerate EF_stab scheme into Amont (upwind) scheme in the sub zone of name sz_name. The sub zone may be located arbitrarily in the domain but the more often this option will be activated in a zone where EF_stab scheme generates instabilities as for free outlet for example.
- alpha_sous_zone listsous_zone_valeur (5.2.11): Option to change locally the alpha value on N subzones named sub_zone_name_I. Generally, it is used to prevent from a local divergence by increasing locally the alpha parameter.

5.2.11 Listsous_zone_valeur

Description: List of groups of two words.

[volumes_non_etendus] [amont_sous_zone str]

} where

[alpha_sous_zone listsous_zone_valeur]

```
See also: listobj (38.5)

Usage:
n object1 object2 ....
list of sous_zone_valeur (5.2.12)
```

```
5.2.12 Sous_zone_valeur
Description: Two words.
See also: objet_lecture (39)
Usage:
sous_zone valeur
where
   • sous_zone str: sous zone
   • valeur float: value
5.2.13 Kquick
Description: Only for VEF discretization.
See also: convection_deriv (5.2.1)
Usage:
kquick
5.2.14 Muscl
Description: Keyword for muscl scheme in VEF discretization equivalent to generic muscl vanleer 2 for the
1.5 version or later. The previous muscl scheme can be used with the obsolete in future muscl_old keyword.
See also: convection_deriv (5.2.1)
Usage:
muscl
5.2.15 Muscl_new
Description: Only for VEF discretization.
See also: convection_deriv (5.2.1)
Usage:
muscl_new
5.2.16 Quick
Description: Only for VDF discretization.
See also: convection_deriv (5.2.1)
Usage:
quick
5.2.17 Centre_old
Description: Only for VEF discretization.
```

See also: convection_deriv (5.2.1)

```
Usage: centre_old
```

5.2.18 Negligeable

Description: For VDF and VEF discretizations. Suppresses the convection operator.

```
See also: convection_deriv (5.2.1)
```

Usage:

where

negligeable

5.2.19 Amont

Description: Keyword for upwind scheme for VDF or VEF discretizations. In VEF discretization equivalent to generic amont for TRUST version 1.5 or later. The previous upwind scheme can be used with the obsolete in future amont_old keyword.

```
See also: convection_deriv (5.2.1)
Usage:
amont
5.2.20 Centre
Description: For VDF and VEF discretizations.
See also: convection_deriv (5.2.1)
Usage:
centre
5.2.21 Centre4
Description: For VDF and VEF discretizations.
See also: convection_deriv (5.2.1)
Usage:
centre4
5.2.22 Btd
Description: Only for EF discretization.
See also: convection_deriv (5.2.1)
Usage:
btd {
     btd float
     facteur float
```

```
• btd float
   • facteur float
5.2.23 Supg
Description: Only for EF discretization.
See also: convection_deriv (5.2.1)
Usage:
supg {
      facteur float
}
where
   • facteur float
5.3 Bloc_diffusion
Description: not_set
See also: objet_lecture (39)
Usage:
aco [operateur][op_implicite] acof
where
   • aco str into ['{'}: Opening curly bracket.
   • operateur diffusion_deriv (5.3.1): if none is specified, the diffusive scheme used is a 2nd-order
      scheme.
   • op_implicite op_implicite (5.3.17): To have diffusive implicitation, it use Uzawa algorithm. Very
      useful when viscosity has large variations.
   • acof str into ['}']: Closing curly bracket.
5.3.1 Diffusion_deriv
Description: not_set
See also: objet_lecture (39) turbulente (5.3.2) stab (5.3.10) standard (5.3.11) p1ncp1b (5.3.13) p1b (5.3.14)
negligeable (5.3.15) option (5.3.16)
Usage:
diffusion_deriv
5.3.2 Turbulente
Description: Turbulent diffusion operator for multiphase problem
See also: diffusion_deriv (5.3.1)
Usage:
turbulente [type]
where
```

• type type_diffusion_turbulente_multiphase_deriv (5.3.3): Turbulence model for multiphase problem

```
5.3.3 Type_diffusion_turbulente_multiphase_deriv
Description: not_set
See also: objet_lecture (39) interfacial_area (5.3.4) wale (5.3.5) l_melange (5.3.6) smago (5.3.7) Prandtl
(5.3.8) SGDH (5.3.9)
Usage:
5.3.4 Interfacial_area
Synonymous: aire_interfaciale
Description: not_set
See also: type_diffusion_turbulente_multiphase_deriv (5.3.3)
Usage:
interfacial_area {
      [cstdiff float]
      [ ng2 ]
}
where
   • cstdiff float: Kataoka diffusion model constant. By default it is se to 0.236.
   • ng2
5.3.5 Wale
Description: LES WALE type.
See also: type_diffusion_turbulente_multiphase_deriv (5.3.3)
Usage:
wale {
     [cw float]
}
where
   • cw float: WALE's model constant. By default it is se to 0.5.
5.3.6 L_melange
Description: not_set
See also: type_diffusion_turbulente_multiphase_deriv (5.3.3)
Usage:
l_melange {
```

```
l_melange float
}
where
   • l_melange float
5.3.7 Smago
Description: LES Smagorinsky type.
See also: type_diffusion_turbulente_multiphase_deriv (5.3.3)
Usage:
smago {
      [cs float]
}
where
   • cs float: Smagorinsky's model constant. By default it is se to 0.18.
5.3.8 Prandtl
Description: Scalar Prandtl model.
See also: type_diffusion_turbulente_multiphase_deriv (5.3.3)
Usage:
Prandtl {
      [ prandtl_turbulent|pr_t float]
}
where
   • prandtl_turbulent|pr_t float: Prandtl's model constant. By default it is se to 0.9.
5.3.9 Sgdh
Description: not_set
See also: type_diffusion_turbulente_multiphase_deriv (5.3.3)
Usage:
SGDH {
      [ Pr_t float]
      [ sigma_turbulent|sigma float]
      [no_alpha]
      [gas_turb]
}
where
   • Pr_t float
   • sigma_turbulent|sigma float
   • no_alpha
   • gas_turb
```

5.3.10 Stab

Description: keyword allowing consistent and stable calculations even in case of obtuse angle meshes.

```
See also: diffusion_deriv (5.3.1)

Usage:
stab {

    [ standard int]
    [ info int]
    [ new_jacobian int]
    [ nu int]
    [ nut int]
    [ nu_transp int]
    [ nut_transp int]
}
where
```

- **standard** *int*: to recover the same results as calculations made by standard laminar diffusion operator. However, no stabilization technique is used and calculations may be unstable when working with obtuse angle meshes (by default 0)
- **info** *int*: developer option to get the stabilizing ratio (by default 0)
- **new_jacobian** *int*: when implicit time schemes are used, this option defines a new jacobian that may be more suitable to get stationary solutions (by default 0)
- **nu** *int*: (respectively nut 1) takes the molecular viscosity (resp. eddy viscosity) into account in the velocity gradient part of the diffusion expression (by default nu=1 and nut=1)
- nut int
- **nu_transp** *int*: (respectively nut_transp 1) takes the molecular viscosity (resp. eddy viscosity) into account in the transposed velocity gradient part of the diffusion expression (by default nu_transp=0 and nut_transp=1)
- nut_transp int

5.3.11 Standard

Description: A new keyword, intended for LES calculations, has been developed to optimise and parameterise each term of the diffusion operator. Remark:

- 1. This class requires to define a filtering operator : see solveur_bar
- 2. The former (original) version: diffusion { } -which omitted some of the term of the diffusion operatorcan be recovered by using the following parameters in the new class : diffusion { standard grad_Ubar 0 nu 1 nut 1 nu_transp 0 nut_transp 1 filtrer_resu 0}.

diffusion (standard grad_coar o na 1 nat 1 na_transp o nat_transp 1 mitor_resu

```
See also: diffusion_deriv (5.3.1)

Usage: standard [ mot1 ] [ bloc_diffusion_standard ] where
```

- mot1 str into ['defaut_bar']: equivalent to grad_Ubar 1 nu 1 nu 1 nu_transp 1 nut_transp 1 filtrer-resu 1
- bloc diffusion standard bloc diffusion standard (5.3.12)

5.3.12 Bloc_diffusion_standard

Description: grad_Ubar 1 makes the gradient calculated through the filtered values of velocity (P1-conform). nu 1 (respectively nut 1) takes the molecular viscosity (eddy viscosity) into account in the velocity gradient part of the diffusion expression.

nu_transp 1 (respectively nut_transp 1) takes the molecular viscosity (eddy viscosity) into account according in the TRANSPOSED velocity gradient part of the diffusion expression.

filtrer resu 1 allows to filter the resulting diffusive fluxes contribution.

```
See also: objet_lecture (39)
Usage:
mot1 val1 mot2 val2 mot3 val3 mot4 val4 mot5 val5 mot6 val6
where
   • mot1 str into ['grad Ubar', 'nu', 'nut', 'nu transp', 'nut transp', 'filtrer resu']
   • val1 int into [0, 1]
   • mot2 str into ['grad_Ubar', 'nu', 'nut', 'nu_transp', 'nut_transp', 'filtrer_resu']
   • val2 int into [0, 1]
   • mot3 str into ['grad_Ubar', 'nu', 'nut', 'nu_transp', 'nut_transp', 'filtrer_resu']
   • val3 int into [0, 1]
   • mot4 str into ['grad_Ubar', 'nu', 'nut', 'nu_transp', 'nut_transp', 'filtrer_resu']
   • val4 int into [0, 1]
   • mot5 str into ['grad_Ubar', 'nu', 'nut', 'nu_transp', 'nut_transp', 'filtrer_resu']
   • val5 int into [0, 1]
   • mot6 str into ['grad_Ubar', 'nu', 'nut', 'nu_transp', 'nut_transp', 'filtrer_resu']
   • val6 int into [0, 1]
5.3.13 P1ncp1b
Description: not set
See also: diffusion_deriv (5.3.1)
Usage:
5.3.14 P1b
Description: not set
See also: diffusion_deriv (5.3.1)
Usage:
p1b
5.3.15 Negligeable
Description: the diffusivity will not taken in count
See also: diffusion_deriv (5.3.1)
Usage:
negligeable
```

```
5.3.16 Option
Description: not_set
See also: diffusion_deriv (5.3.1)
Usage:
option bloc_lecture
where
   • bloc_lecture bloc_lecture (3.59)
5.3.17 Op_implicite
Description: not_set
See also: objet_lecture (39)
Usage:
implicite mot solveur
where
   • implicite str into ['implicite']
   • mot str into ['solveur']
   • solveur_sys_base (11.16)
5.4 Condlims
Description: Boundary conditions.
See also: listobj (38.5)
Usage:
{ object1 object2 .... }
list of condlimlu (5.4.1)
5.4.1 Condlimlu
Description: Boundary condition specified.
See also: objet_lecture (39)
Usage:
bord cl
where
```

- cl condlim_base (13): Boundary condition at the boundary called bord (edge).

• **bord** *str*: Name of the edge where the boundary condition applies.

5.5 Condinits

```
Description: Initial conditions.
See also: listobj (38.5)
Usage:
{ object1 object2 .... }
list of condinit (5.5.1)
5.5.1 Condinit
Description: Initial condition.
See also: objet_lecture (39)
Usage:
nom ch
where
   • nom str: Name of initial condition field.
   • ch champ_base (16.1): Type field and the initial values.
5.6 Sources
Description: The sources.
See also: listobj (38.5)
Usage:
{ object1, object2.... }
list of source_base (34) separeted with,
5.7
    Parametre_equation_base
Description: Basic class for parametre_equation
See also: objet_lecture (39) parametre_implicite (5.7.1) parametre_diffusion_implicite (5.7.2)
Usage:
5.7.1 Parametre_implicite
Description: Keyword to change for this equation only the parameter of the implicit scheme used to solve
the problem.
See also: parametre_equation_base (5.7)
Usage:
parametre_implicite {
      [ seuil_convergence_implicite float]
      [ seuil_convergence_solveur float]
```

[solveur_sys_base]

```
[ resolution_explicite ]
    [ equation_non_resolue ]
    [ equation_frequence_resolue str]
}
where
```

- **seuil_convergence_implicite** *float*: Keyword to change for this equation only the value of seuil_convergence_implicite used in the implicit scheme.
- **seuil_convergence_solveur** *float*: Keyword to change for this equation only the value of seuil_convergence_solveur used in the implicit scheme
- **solveur** *solveur_sys_base* (11.16): Keyword to change for this equation only the solver used in the implicit scheme
- resolution_explicite : To solve explicitly the equation whereas the scheme is an implicit scheme.
- equation_non_resolue : Keyword to specify that the equation is not solved.
- equation_frequence_resolue *str*: Keyword to specify that the equation is solved only every n time steps (n is an integer or given by a time-dependent function f(t)).

5.7.2 Parametre_diffusion_implicite

Description: To specify additional parameters for the equation when using impliciting diffusion

```
See also: parametre_equation_base (5.7)

Usage:
parametre_diffusion_implicite {

    [ crank int into [0, 1]]
    [ preconditionnement_diag int into [0, 1]]
    [ niter_max_diffusion_implicite int]
    [ seuil_diffusion_implicite float]
    [ solveur solveur_sys_base]
}

where
```

- **crank** *int into* [0, 1]: Use (1) or not (0, default) a Crank Nicholson method for the diffusion implicitation algorithm. Setting crank to 1 increases the order of the algorithm from 1 to 2.
- **preconditionnement_diag** *int into* [0, 1]: The CG used to solve the implicitation of the equation diffusion operator is not preconditioned by default. If this option is set to 1, a diagonal preconditionning is used. Warning: this option is not necessarily more efficient, depending on the treated case.
- **niter_max_diffusion_implicite** *int*: Change the maximum number of iterations for the CG (Conjugate Gradient) algorithm when solving the diffusion implicitation of the equation.
- **seuil_diffusion_implicite** *float*: Change the threshold convergence value used by default for the CG resolution for the diffusion implicitation of this equation.
- **solveur** *solveur_sys_base* (11.16): Method (different from the default one, Conjugate Gradient) to solve the linear system.

5.8 Conduction_ibm

Description: IBM Heat equation.

Keyword Discretize should have already been used to read the object.

```
See also: Conduction (5.1)
Usage:
Conduction_ibm str
Read str {
     [correction variable initiale int]
     [ disable equation residual str]
     [convection bloc convection]
     [ diffusion bloc diffusion]
     [boundary conditions|conditions limites condlims]
     [initial_conditions|conditions_initiales condinits]
     [sources sources]
     [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
     [ parametre_equation parametre_equation_base]
     [ equation_non_resolue str]
     [renommer_equation str]
}
where
```

- **correction_variable_initiale** *int*: Modify initial variable
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary conditions limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.9 Convection_diffusion_espece_binaire_turbulent_qc

Description: Species conservation equation for a binary quasi-compressible fluid as well as the associated turbulence model equations.

```
Keyword Discretize should have already been used to read the object. See also: convection_diffusion_espece_binaire_QC (5.23)

Usage:

Convection_Diffusion_Espece_Binaire_Turbulent_QC str

Read str {

[ modele turbulence modele turbulence scal base]
```

```
[ disable_equation_residual str]
  [ convection bloc_convection]
  [ diffusion bloc_diffusion]
  [ boundary_conditions|conditions_limites condlims]
  [ initial_conditions|conditions_initiales condinits]
  [ sources sources]
  [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
  [ parametre_equation parametre_equation_base]
  [ equation_non_resolue str]
  [ renommer_equation str]
}
where
```

- modele_turbulence modele_turbulence_scal_base (23): Turbulence model for the species conservation equation.
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc_convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** bloc_diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.10 Echelle_temporelle_turbulente

Echelle temporelle turbulente str

Description: Turbulent Dissipation time scale equation for a turbulent mono/multi-phase problem (available in TrioCFD)

Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33)

```
Usage:
```

```
Read str {

[ disable_equation_residual str]
[ convection bloc_convection]
[ diffusion bloc_diffusion]
[ boundary_conditions|conditions_limites condlims]
[ initial_conditions|conditions_initiales condinits]
[ sources sources]
```

```
[ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
     [ parametre_equation parametre_equation_base]
     [ equation non resolue str]
     [renommer_equation str]
}
where
```

- disable equation residual str for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- sources sources (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation non resolue str for inheritance: The equation will not be solved while condition(t) is verified if equation non resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier Sokes Standard
{ equation non resolue (t>t0)*(t<t1) }
```

Energie multiphase 5.11

Description: Internal energy conservation equation for a multi-phase problem where the unknown is the temperature

Keyword Discretize should have already been used to read the object. See also: eqn base (5.33)

```
Usage:
```

}

```
Energie_Multiphase str
Read str {
```

```
[ disable_equation_residual str]
     [convection bloc convection]
     [ diffusion bloc diffusion]
     [boundary conditions|conditions limites condlims]
     [initial conditions|conditions initiales condinits]
     [sources sources]
     [ ecrire fichier xyz valeur ecrire fichier xyz valeur]
     [ parametre_equation parametre_equation_base]
     [ equation_non_resolue str]
     [renommer_equation str]
where
```

- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- diffusion bloc_diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.12 Energie_multiphase_h

Description: Internal energy conservation equation for a multi-phase problem where the unknown is the enthalpy

Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33)

```
Usage:
Energie_Multiphase_h str

Read str {

    [disable_equation_residual str]
    [convection bloc_convection]
    [diffusion bloc_diffusion]
    [boundary_conditions|conditions_limites condlims]
    [initial_conditions|conditions_initiales condinits]
    [sources sources]
    [ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
    [parametre_equation parametre_equation_base]
    [equation_non_resolue str]
    [renommer_equation str]
}
where
```

- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** bloc_convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)

- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.13 Energie_cinetique_turbulente

Description: Turbulent kinetic Energy conservation equation for a turbulent mono/multi-phase problem (available in TrioCFD)

Keyword Discretize should have already been used to read the object.

```
See also: eqn_base (5.33)
```

```
Usage:
```

```
Energie_cinetique_turbulente str

Read str {

    [ disable_equation_residual str]
    [ convection bloc_convection]
    [ diffusion bloc_diffusion]
    [ boundary_conditions|conditions_limites condlims]
    [ initial_conditions|conditions_initiales condinits]
    [ sources sources]
    [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
    [ parametre_equation parametre_equation_base]
    [ equation_non_resolue str]
    [ renommer_equation str]
}
where
```

- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** bloc_diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.14 Energie cinetique turbulente wit

Description: Bubble Induced Turbulent kinetic Energy equation for a turbulent multi-phase problem (available in TrioCFD)

Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33)

```
Usage:
Energie_cinetique_turbulente_WIT str
Read str {
     [disable equation residual str]
     [convection bloc_convection]
     [ diffusion bloc diffusion]
     [boundary conditions|conditions limites condlims]
     [initial conditions|conditions initiales condinits]
     [sources sources]
     [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
     [ parametre_equation parametre_equation_base]
     [ equation_non_resolue str]
     [renommer_equation str]
where
```

- disable equation residual str for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary conditions limites condlims (5.4) for inheritance: Boundary conditions.
- initial conditions londitions initiales condinits (5.5) for inheritance: Initial conditions.
- sources sources (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue str for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier Sokes Standard
{ equation non resolue (t>t0)*(t<t1) }
```

• renommer equation str for inheritance: Rename the equation with a specific name.

Masse_multiphase

Description: Mass consevation equation for a multi-phase problem where the unknown is the alpha (void fraction)

Keyword Discretize should have already been used to read the object.

```
Usage:

Masse_Multiphase str

Read str {

    [ disable_equation_residual str]
    [ convection bloc_convection]
    [ diffusion bloc_diffusion]
    [ boundary_conditions|conditions_limites condlims]
    [ initial_conditions|conditions_initiales condinits]
    [ sources sources]
    [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
    [ parametre_equation parametre_equation_base]
    [ equation_non_resolue str]
    [ renommer_equation str]
}
where
```

- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- **boundary_conditions|conditions_limites** *condlims* (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation non resolue (t>t0)*(t<t1) }
```

[solveur pression solveur sys base]

[evanescence bloc lecture]

• renommer equation str for inheritance: Rename the equation with a specific name.

5.16 Qdm multiphase

Description: Momentum conservation equation for a multi-phase problem where the unknown is the velocity

Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33)

Usage:

QDM_Multiphase str

Read str {

```
[ disable_equation_residual str]
        [ convection bloc_convection]
        [ diffusion bloc_diffusion]
        [ boundary_conditions|conditions_limites condlims]
        [ initial_conditions|conditions_initiales condinits]
        [ sources sources]
        [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
        [ parametre_equation parametre_equation_base]
        [ equation_non_resolue str]
        [ renommer_equation str]
}
```

- solveur_pression solveur_sys_base (11.16): Linear pressure system resolution method.
- evanescence bloc_lecture (3.59): Management of the vanishing phase (when alpha tends to 0 or 1)
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** bloc_diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary conditions limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.17 Taux_dissipation_turbulent

Taux dissipation turbulent str

Description: Turbulent Dissipation frequency equation for a turbulent mono/multi-phase problem (available in TrioCFD)

Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33)

```
Usage:
```

```
Read str {

[ disable_equation_residual str]
[ convection bloc_convection]
[ diffusion bloc_diffusion]
[ boundary_conditions|conditions_limites condlims]
[ initial_conditions|conditions_initiales condinits]
[ sources sources]
```

```
[ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
     [ parametre_equation parametre_equation_base]
     [ equation non resolue str]
     [renommer_equation str]
}
where
```

- disable equation residual str for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- sources sources (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation non resolue str for inheritance: The equation will not be solved while condition(t) is verified if equation non resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier Sokes Standard
{ equation non resolue (t>t0)*(t<t1) }
```

5.18 Convection diffusion chaleur qc

```
Description: Temperature equation for a quasi-compressible fluid.
```

```
Keyword Discretize should have already been used to read the object.
See also: eqn base (5.33) convection diffusion chaleur turbulent qc (5.20)
```

```
Usage:
```

```
convection diffusion chaleur QC str
```

```
Read str {
     [ mode_calcul_convection str into ['ancien', 'divuT_moins_Tdivu', 'divrhouT_moins_Tdivrhou']]
     [ disable_equation_residual str]
     [convection bloc convection]
     [ diffusion bloc diffusion]
     [boundary conditions|conditions limites condlims]
     [initial conditions|conditions initiales condinits]
     [sources sources]
     [ ecrire fichier xyz valeur ecrire fichier xyz valeur]
     [ parametre_equation parametre_equation_base]
     [ equation_non_resolue str]
     [renommer_equation str]
}
where
```

- mode_calcul_convection str into ['ancien', 'divuT_moins_Tdivu', 'divrhouT_moins_Tdivrhou']: Option to set the form of the convective operator divrhouT_moins_Tdivrhou (the default since 1.6.8): rho.u.gradT = div(rho.u.T) Tdiv(rho.u.1) ancien: u.gradT = div(u.T) T.div(u) divuT_moins_Tdivu: u.gradT = div(u.T) Tdiv(u.1)
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc_convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** bloc_diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary conditions|conditions limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.19 Convection_diffusion_chaleur_wc

Description: Temperature equation for a weakly-compressible fluid.

Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33)

Usage:

where

```
convection_diffusion_chaleur_WC str

Read str {

    [ disable_equation_residual str]
    [ convection bloc_convection]
    [ diffusion bloc_diffusion]
    [ boundary_conditions|conditions_limites condlims]
    [ initial_conditions|conditions_initiales condinits]
    [ sources sources]
    [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
    [ parametre_equation parametre_equation_base]
    [ equation_non_resolue str]
    [ renommer_equation str]
}
```

- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.

- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- sources sources (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre equation parametre equation base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue str for inheritance: The equation will not be solved while condition(t) is verified if equation non resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard
{ equation non resolue (t>t0)*(t<t1) }
```

5.20 Convection diffusion chaleur turbulent qc

Description: Temperature equation for a quasi-compressible fluid as well as the associated turbulence model equations.

Keyword Discretize should have already been used to read the object. See also: convection_diffusion_chaleur_QC (5.18)

```
Usage:
```

```
convection_diffusion_chaleur_turbulent_qc str
Read str {
     [ modele_turbulence modele_turbulence_scal_base]
     [ mode_calcul_convection str into ['ancien', 'divuT_moins_Tdivu', 'divrhouT_moins_Tdivrhou']]
     [ disable equation residual str]
     [convection bloc convection]
     [ diffusion bloc_diffusion]
     [boundary_conditions|conditions_limites condlims]
     [initial_conditions|conditions_initiales condinits]
     [sources sources]
     [ ecrire fichier xvz valeur ecrire fichier xvz valeur]
     [ parametre_equation parametre_equation_base]
     [ equation non resolue str]
     [renommer_equation str]
where
```

- modele turbulence modele turbulence scal base (23): Turbulence model for the temperature (energy) conservation equation.
- mode_calcul_convection str into ['ancien', 'divuT_moins_Tdivu', 'divrhouT_moins_Tdivrhou'] for inheritance: Option to set the form of the convective operator divrhouT moins Tdivrhou (the default since 1.6.8); rho.u.gradT = div(rho.u.T) - Tdiv(rho.u.1) ancien: u.gradT = div(u.T) - T.div(u) $divuT_moins_Tdivu : u.gradT = div(u.T) - Tdiv(u.1)$
- disable_equation_residual str for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** bloc_convection (5.2) for inheritance: Keyword to alter the convection scheme.

- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial conditions|conditions initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.21 Convection diffusion concentration

Description: Constituent transport vectorial equation (concentration diffusion convection).

```
Keyword Discretize should have already been used to read the object.
See also: eqn_base (5.33) convection_diffusion_concentration_turbulent (5.22)
```

Usage:

```
convection_diffusion_concentration str
Read str {
     [ nom_inconnue str]
     [alias str]
     [ masse molaire float]
     [is_multi_scalar_diffusion|is_multi_scalar ]
     [ disable_equation_residual str]
     [convection bloc_convection]
     [ diffusion bloc_diffusion]
     [boundary_conditions|conditions_limites condlims]
     [initial conditions|conditions initiales condinits]
     [sources sources]
     [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
     [ parametre_equation parametre_equation_base]
     [ equation non resolue str]
     [renommer_equation str]
}
where
```

- **nom_inconnue** *str*: Keyword Nom_inconnue will rename the unknown of this equation with the given name. In the postprocessing part, the concentration field will be accessible with this name. This is usefull if you want to track more than one concentration (otherwise, only the concentration field in the first concentration equation can be accessed).
- alias str
- masse_molaire float
- is_multi_scalar_diffusionlis_multi_scalar : Flag to activate the multi_scalar diffusion operator

- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.22 Convection_diffusion_concentration_turbulent

Description: Constituent transport equations (concentration diffusion convection) as well as the associated turbulence model equations.

Keyword Discretize should have already been used to read the object. See also: convection_diffusion_concentration (5.21)

```
Usage:
```

```
convection_diffusion_concentration_turbulent str
Read str {
```

```
[ modele_turbulence modele_turbulence_scal_base]
     [ nom_inconnue str]
     [alias str]
     [ masse_molaire float]
     [ is multi scalar diffusionlis multi scalar ]
     [ disable_equation_residual str]
     [convection bloc convection]
     [ diffusion bloc_diffusion]
     [boundary conditions|conditions limites condlims]
     [initial_conditions|conditions_initiales condinits]
     [sources sources]
     [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
     [ parametre equation parametre equation base]
     [ equation_non_resolue str]
     [renommer_equation str]
where
```

• **modele_turbulence** *modele_turbulence_scal_base* (23): Turbulence model to be used in the constituent transport equations. The only model currently available is Schmidt.

- **nom_inconnue** *str* for inheritance: Keyword Nom_inconnue will rename the unknown of this equation with the given name. In the postprocessing part, the concentration field will be accessible with this name. This is usefull if you want to track more than one concentration (otherwise, only the concentration field in the first concentration equation can be accessed).
- alias str for inheritance
- masse_molaire *float* for inheritance
- is_multi_scalar_diffusionlis_multi_scalar for inheritance: Flag to activate the multi_scalar diffusion operator
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc_convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** bloc_diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- **boundary_conditions|conditions_limites** *condlims* (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.23 Convection_diffusion_espece_binaire_qc

Description: Species conservation equation for a binary quasi-compressible fluid.

```
Keyword Discretize should have already been used to read the object.
See also: eqn_base (5.33) Convection_Diffusion_Espece_Binaire_Turbulent_QC (5.9)
```

Usage:

```
convection_diffusion_espece_binaire_QC str

Read str {

    [ disable_equation_residual str]
    [ convection bloc_convection]
    [ diffusion bloc_diffusion]
    [ boundary_conditions|conditions_limites condlims]
    [ initial_conditions|conditions_initiales condinits]
    [ sources sources]
    [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
    [ parametre_equation parametre_equation_base]
    [ equation_non_resolue str]
    [ renommer_equation str]
}
where
```

• **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step

- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.24 Convection_diffusion_espece_binaire_wc

Description: Species conservation equation for a binary weakly-compressible fluid.

Keyword Discretize should have already been used to read the object.

See also: eqn_base (5.33)

```
Usage: convection diffusion espece binaire WC str
```

```
Read str {

[ disable_equation_residual str]
[ convection bloc_convection]
[ diffusion bloc_diffusion]
[ boundary_conditions|conditions_limites condlims]
[ initial_conditions|conditions_initiales condinits]
[ sources sources]
[ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
[ parametre_equation parametre_equation_base]
[ equation_non_resolue str]
[ renommer_equation str]
}
where
```

- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file

- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.25 Convection_diffusion_espece_multi_qc

Description: Species conservation equation for a multi-species quasi-compressible fluid.

Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33)

```
Usage:
convection_diffusion_espece_multi_QC str

Read str {

    [espece espece]
    [disable_equation_residual str]
    [convection bloc_convection]
    [diffusion bloc_diffusion]
    [boundary_conditions|conditions_limites condlims]
    [initial_conditions|conditions_initiales condinits]
    [sources sources]
    [ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
    [parametre_equation parametre_equation_base]
    [equation_non_resolue str]
    [renommer_equation str]
}
```

- espece espece (3.41): Assosciate a species (with its properties) to the equation
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc_convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

where

• renommer_equation str for inheritance: Rename the equation with a specific name.

5.26 Convection_diffusion_espece_multi_wc

Description: Species conservation equation for a multi-species weakly-compressible fluid.

Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33)

```
Usage:
```

```
convection_diffusion_espece_multi_WC str
Read str {

    [ disable_equation_residual str]
    [ convection bloc_convection]
    [ diffusion bloc_diffusion]
    [ boundary_conditions|conditions_limites condlims]
    [ initial_conditions|conditions_initiales condinits]
    [ sources sources]
    [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
    [ parametre_equation parametre_equation_base]
    [ equation_non_resolue str]
    [ renommer_equation str]
}
where
```

- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc convection (5.2) for inheritance: Keyword to alter the convection scheme.
- diffusion bloc diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary conditions limites condlims (5.4) for inheritance: Boundary conditions.
- initial conditions|conditions initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

• renommer_equation str for inheritance: Rename the equation with a specific name.

5.27 Convection diffusion espece multi turbulent qc

```
Description: not_set

Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33)

Usage:
convection_diffusion_espece_multi_turbulent_qc str
Read str {
```

```
[ modele_turbulence modele_turbulence_scal_base]
espece espece
[ disable_equation_residual str]
[ convection bloc_convection]
[ diffusion bloc_diffusion]
[ boundary_conditions|conditions_limites condlims]
[ initial_conditions|conditions_initiales condinits]
[ sources sources]
[ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
[ parametre_equation parametre_equation_base]
[ equation_non_resolue str]
[ renommer_equation str]
}
where
```

- modele_turbulence modele_turbulence_scal_base (23): Turbulence model to be used.
- **espece** *espece* (3.41)
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc_convection (5.2) for inheritance: Keyword to alter the convection scheme.
- diffusion bloc_diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.28 Convection_diffusion_temperature

```
Description: Energy equation (temperature diffusion convection).

Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33) convection_diffusion_temperature_ibm (5.30)

Usage:
convection_diffusion_temperature str

Read str {

[ penalisation_12_ftd pp]
    [ disable_equation_residual str]
    [ convection bloc_convection]
    [ diffusion bloc_diffusion]
    [ boundary_conditions|conditions_limites condlims]
```

```
[ initial_conditions|conditions_initiales condinits]
    [ sources sources]
    [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
    [ parametre_equation parametre_equation_base]
    [ equation_non_resolue str]
    [ renommer_equation str]
}
where
```

- **penalisation_12_ftd** *pp* (5.29): to activate or not (the default is Direct Forcing method) the Penalized Direct Forcing method to impose the specified temperature on the solid-fluid interface.
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.29 Pp

```
Description: not_set

See also: listobj (38.5)

Usage:
{ object1 object2 .... }
list of penalisation_l2_ftd_lec (5.29.1)

5.29.1 Penalisation_l2_ftd_lec

Description: not_set

See also: objet_lecture (39)

Usage:
```

5.30 Convection_diffusion_temperature_ibm

Description: IBM Energy equation (temperature diffusion convection).

Keyword Discretize should have already been used to read the object.

```
See also: convection_diffusion_temperature (5.28)
Usage:
convection_diffusion_temperature_ibm str
Read str {
     [correction_variable_initiale int]
     [ penalisation_l2_ftd pp]
     [ disable equation residual str]
     [convection bloc convection]
     [ diffusion bloc_diffusion]
     [boundary conditions|conditions limites condlims]
     [initial_conditions|conditions_initiales condinits]
     [sources sources]
     [ ecrire fichier xyz valeur ecrire fichier xyz valeur]
     [ parametre_equation parametre_equation_base]
     [ equation non resolue str]
     [renommer_equation str]
}
where
```

- correction_variable_initiale int: Modify initial variable
- **penalisation_12_ftd** *pp* (5.29) for inheritance: to activate or not (the default is Direct Forcing method) the Penalized Direct Forcing method to impose the specified temperature on the solid-fluid interface.
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** bloc_convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary conditions limites condlims (5.4) for inheritance: Boundary conditions.
- initial conditions londitions initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.31 Convection_diffusion_temperature_ibm_turbulent

Description: IBM Energy equation (temperature diffusion convection) as well as the associated turbulence model equations.

```
Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33)
```

Usage:

```
convection_diffusion_temperature_ibm_turbulent str
Read str {

    [ modele_turbulence modele_turbulence_scal_base]
    [ disable_equation_residual str]
    [ convection bloc_convection]
    [ diffusion bloc_diffusion]
    [ boundary_conditions|conditions_limites condlims]
    [ initial_conditions|conditions_initiales condinits]
    [ sources sources]
    [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
    [ parametre_equation parametre_equation_base]
    [ equation_non_resolue str]
    [ renommer_equation str]
}
where
```

- modele_turbulence modele_turbulence_scal_base (23): Turbulence model for the energy equation.
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation non resolue (t>t0)*(t<t1) }
```

5.32 Convection diffusion temperature turbulent

Description: Energy equation (temperature diffusion convection) as well as the associated turbulence model equations.

```
Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33)

Usage:
convection_diffusion_temperature_turbulent str

Read str {

[ modele_turbulence modele_turbulence_scal_base]

[ disable equation residual str]
```

```
[ convection bloc_convection]
[ diffusion bloc_diffusion]
[ boundary_conditions|conditions_limites condlims]
[ initial_conditions|conditions_initiales condinits]
[ sources sources]
[ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
[ parametre_equation parametre_equation_base]
[ equation_non_resolue str]
[ renommer_equation str]
}
where
```

- modele_turbulence modele_turbulence_scal_base (23): Turbulence model for the energy equation.
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- diffusion bloc_diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- **boundary_conditions|conditions_limites** *condlims* (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.33 Eqn_base

Description: Basic class for equations.

Keyword Discretize should have already been used to read the object.

See also: mor_eqn (5) Conduction (5.1) convection_diffusion_temperature (5.28) navier_stokes_standard (5.42) convection_diffusion_temperature_ibm_turbulent (5.31) Energie_Multiphase (5.11) Energie_Multiphase_h (5.12) Masse_Multiphase (5.15) QDM_Multiphase (5.16) Echelle_temporelle_turbulente (5.10) Energie_cinetique_turbulente (5.13) Energie_cinetique_turbulente_WIT (5.14) Taux_dissipation_turbulent (5.17) convection_diffusion_espece_multi_turbulent_qc (5.27) convection_diffusion_concentration (5.21) convection_diffusion_chaleur_QC (5.18) convection_diffusion_temperature_turbulent (5.32) convection_diffusion_espece_binaire_QC (5.23) convection_diffusion_chaleur_WC (5.19) convection_diffusion_espece_multi_QC (5.25) convection_diffusion_espece_binaire_WC (5.24) convection_diffusion_espece_multi_WC (5.26)

```
Usage:
eqn_base str
Read str {
    [ disable_equation_residual str]
```

```
[ convection bloc_convection]
[ diffusion bloc_diffusion]
[ boundary_conditions|conditions_limites condlims]
[ initial_conditions|conditions_initiales condinits]
[ sources sources]
[ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
[ parametre_equation parametre_equation_base]
[ equation_non_resolue str]
[ renommer_equation str]
}
where
```

- **disable_equation_residual** *str*: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2): Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3): Keyword to specify the diffusion operator.
- **boundary_conditions|conditions_limites** *condlims* (5.4): Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5): Initial conditions.
- **sources** *sources* (5.6): To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39): This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7): Keyword used to specify additional parameters for the equation
- equation_non_resolue *str*: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

• renommer equation str: Rename the equation with a specific name.

5.34 Navier_stokes_qc

Description: Navier-Stokes equation for a quasi-compressible fluid.

Keyword Discretize should have already been used to read the object. See also: navier_stokes_standard (5.42)

```
Usage:
navier_stokes_QC str
Read str {
    [ solveur_pression of the str ]
```

```
[ solveur_pression solveur_sys_base]
[ dt_projection deuxmots]
[ traitement_particulier traitement_particulier]
[ seuil_divU floatfloat]
[ solveur_bar solveur_sys_base]
[ projection_initiale int]
[ postraiter_gradient_pression_sans_masse ]
[ methode_calcul_pression_initiale str into ['avec_les_cl', 'avec_sources', 'avec_sources_et_operateurs', 'sans_rien']]
[ disable_equation_residual str]
```

```
[ convection bloc_convection]
[ diffusion bloc_diffusion]
[ boundary_conditions|conditions_limites condlims]
[ initial_conditions|conditions_initiales condinits]
[ sources sources]
[ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
[ parametre_equation parametre_equation_base]
[ equation_non_resolue str]
[ renommer_equation str]
}
where
```

- solveur_pression solveur_sys_base (11.16) for inheritance: Linear pressure system resolution method.
- **dt_projection** *deuxmots* (5.35) for inheritance: nb value: This keyword checks every nb time-steps the equality of velocity divergence to zero. value is the criteria convergency for the solver used.
- **traitement_particulier** *traitement_particulier* (5.36) for inheritance: Keyword to post-process particular values.
- seuil_divU floatfloat (5.37) for inheritance: value factor: this keyword is intended to minimise the number of iterations during the pressure system resolution. The convergence criteria during this step ('seuil' in solveur_pression) is dynamically adapted according to the mass conservation. At tn, the linear system Ax=B is considered as solved if the residual ||Ax-B||<seuil(tn). For tn+1, the threshold value seuil(tn+1) will be evualated as:

```
If ( |max(DivU)*dt|<value )
Seuil(tn+1)= Seuil(tn)*factor
Else
Seuil(tn+1)= Seuil(tn)*factor
Endif
```

- solveur_bar solveur_sys_base (11.16) for inheritance: This keyword is used to define when filtering operation is called (typically for EF convective scheme, standard diffusion operator and Source_Qdm_lambdaup). A file (solveur.bar) is then created and used for inversion procedure. Syntax is the same then for pressure solver (GCP is required for multi-processor calculations and, in a general way, for big meshes).
- **projection_initiale** *int* for inheritance: Keyword to suppress, if boolean equals 0, the initial projection which checks DivU=0. By default, boolean equals 1.
- postraiter_gradient_pression_sans_masse for inheritance: Avoid mass matrix multiplication for the gradient postprocessing
- methode_calcul_pression_initiale str into ['avec_les_cl', 'avec_sources', 'avec_sources_et_operateurs', 'sans_rien'] for inheritance: Keyword to select an option for the pressure calculation before the fist time step. Options are: avec_les_cl (default option lapP=0 is solved with Neuman boundary conditions on pressure if any), avec_sources (lapP=f is solved with Neuman boundaries conditions and f integrating the source terms of the Navier-Stokes equations) and avec_sources_et_operateurs (lapP=f is solved as with the previous option avec_sources but f integrating also some operators of the Navier-Stokes equations). The two last options are useful and sometime necessary when source terms are implicited when using an implicit time scheme to solve the Navier-Stokes equations.
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- **boundary_conditions|conditions_limites** *condlims* (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.

- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }

• renommer_equation str for inheritance: Rename the equation with a specific name.

5.35 Deuxmots

Description: Two words.

See also: objet_lecture (39)

Usage:

mot_1 mot_2 where

- mot_1 str: First word.
- mot_2 str: Second word.

5.36 Traitement_particulier

Description: Auxiliary class to post-process particular values.

See also: objet_lecture (39)

Usage:

aco trait_part acof where

- aco str into ['{'}]: Opening curly bracket.
- trait_part traitement_particulier_base (5.36.1): Type of traitement_particulier.
- acof str into ['}']: Closing curly bracket.

5.36.1 Traitement_particulier_base

Description: Basic class to post-process particular values.

See also: objet_lecture (39) profils_thermo (5.36.2) temperature (5.36.3) canal (5.36.4) chmoy_faceperio (5.36.5) ec (5.36.6) thi (5.36.7)

Usage:

5.36.2 Profils thermo

Description: non documente

```
See also: traitement_particulier_base (5.36.1)
Usage:
profils_thermo bloc
where
   • bloc bloc_lecture (3.59)
5.36.3 Temperature
Description: not_set
See also: traitement_particulier_base (5.36.1)
Usage:
temperature {
     bord str
     direction int
where
   • bord str
   • direction int
5.36.4 Canal
Description: Keyword for statistics on a periodic plane channel.
See also: traitement_particulier_base (5.36.1)
Usage:
canal {
     [ dt_impr_moy_spat float]
     [ dt_impr_moy_temp float]
     [ debut_stat float]
     [fin_stat float]
     [ pulsation_w float]
     [ nb_points_par_phase int]
     [ reprise str]
}
where
```

- **dt_impr_moy_spat** *float*: Period to print the spatial average (default value is 1e6).
- **dt_impr_moy_temp** *float*: Period to print the temporal average (default value is 1e6).
- **debut_stat** *float*: Time to start the temporal averaging (default value is 1e6).
- fin stat float: Time to end the temporal averaging (default value is 1e6).
- **pulsation_w** *float*: Pulsation for phase averaging (in case of pulsating forcing term) (no default value).
- **nb_points_par_phase** *int*: Number of samples to represent phase average all along a period (no default value).

• **reprise** *str*: val_moy_temp_xxxxxx.sauv : Keyword to resume a calculation with previous averaged quantities.

Note that for thermal and turbulent problems, averages on temperature and turbulent viscosity are automatically calculated. To resume a calculation with phase averaging, val_moy_temp_xxxxxx.sauv_phase file is required on the directory where the job is submitted (this last file will be then automatically loaded by TRUST).

5.36.5 Chmoy_faceperio

```
Description: non documente

See also: traitement_particulier_base (5.36.1)

Usage:
chmoy_faceperio bloc
where
```

• bloc bloc_lecture (3.59)

5.36.6 Ec

Description: Keyword to print total kinetic energy into the referential linked to the domain (keyword Ec). In the case where the domain is moving into a Galilean referential, the keyword Ec_dans_repere_fixe will print total kinetic energy in the Galilean referential whereas Ec will print the value calculated into the moving referential linked to the domain

```
See also: traitement_particulier_base (5.36.1)

Usage:
ec {

    [Ec]
    [Ec_dans_repere_fixe]
    [periode float]
}

where
```

- Ec
- Ec_dans_repere_fixe
- **periode** *float*: periode is the keyword to set the period of printing into the file datafile_Ec.son or datafile_Ec_dans_repere_fixe.son.

5.36.7 Thi

Description: Keyword for a THI (Homogeneous Isotropic Turbulence) calculation.

```
See also: traitement_particulier_base (5.36.1)

Usage:
thi {
    init_Ec int
    [val_Ec float]
```

```
[ facon_init int into [0, 1]]
[ calc_spectre int into [0, 1]]
[ periode_calc_spectre float]
[ spectre_3D int into [0, 1]]
[ spectre_1D int into [0, 1]]
[ conservation_Ec ]
[ longueur_boite float]
}
where
```

- init_Ec int: Keyword to renormalize initial velocity so that kinetic energy equals to the value given by keyword val Ec.
- val_Ec *float*: Keyword to impose a value for kinetic energy by velocity renormalizated if init_Ec value is 1.
- **facon_init** *int into* [0, 1]: Keyword to specify how kinetic energy is computed (0 or 1).
- calc_spectre int into [0, 1]: Calculate or not the spectrum of kinetic energy.

Files called Sorties_THI are written with inside four columns:

time:t global kinetic energy:Ec enstrophy:D skewness:S

If calc_spectre is set to 1, a file Sorties_THI2_2 is written with three columns:

time:t kinetic_energy_at_kc=32 enstrophy_at_kc=32

If calc_spectre is set to 1, a file spectre_xxxxx is written with two columns at each time xxxxx: frequency:k energy:E(k).

- periode calc spectre *float*: Period for calculating spectrum of kinetic energy
- spectre 3D int into [0, 1]: Calculate or not the 3D spectrum
- spectre_1D int into [0, 1]: Calculate or not the 1D spectrum
- **conservation_Ec**: If set to 1, velocity field will be changed as to have a constant kinetic energy (default 0)
- longueur_boite float: Length of the calculation domain

5.37 Floatfloat

```
Description: Two reals.

See also: objet_lecture (39)

Usage:
a b
where

• a float: First real.
• b float: Second real.
```

5.38 Navier stokes wc

Description: Navier-Stokes equation for a weakly-compressible fluid.

Keyword Discretize should have already been used to read the object. See also: navier stokes standard (5.42)

```
Usage:
navier_stokes_WC str
Read str {

[ mass source mass source]
```

```
[solveur_pression solveur_sys_base]
     [dt_projection deuxmots]
     [traitement_particulier traitement_particulier]
     [ seuil_divU floatfloat]
     [solveur bar solveur sys base]
     [ projection_initiale int]
     [postraiter gradient pression sans masse]
     methode calcul pression initiale str into ['avec les cl', 'avec sources', 'avec sources et-
     _operateurs', 'sans_rien']
     [ disable equation residual str]
     [convection bloc convection]
     [ diffusion bloc diffusion]
     [boundary_conditions|conditions_limites condlims]
     [initial_conditions|conditions_initiales condinits]
     [sources sources]
     [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
     [ parametre_equation parametre_equation_base]
     [ equation_non_resolue str]
     [renommer_equation str]
}
where
```

- mass_source mass_source (3.73): Mass source used in a dilatable simulation to add/reduce a mass at the boundary (volumetric source in the first cell of a given boundary).
- solveur_pression solveur_sys_base (11.16) for inheritance: Linear pressure system resolution method.
- **dt_projection** *deuxmots* (5.35) for inheritance: nb value: This keyword checks every nb time-steps the equality of velocity divergence to zero. value is the criteria convergency for the solver used.
- **traitement_particulier** *traitement_particulier* (5.36) for inheritance: Keyword to post-process particular values.
- seuil_divU floatfloat (5.37) for inheritance: value factor: this keyword is intended to minimise the number of iterations during the pressure system resolution. The convergence criteria during this step ('seuil' in solveur_pression) is dynamically adapted according to the mass conservation. At tn, the linear system Ax=B is considered as solved if the residual ||Ax-B||<seuil(tn). For tn+1, the threshold value seuil(tn+1) will be evualated as:

```
If ( |max(DivU)*dt|<value )
Seuil(tn+1)= Seuil(tn)*factor
Else
Seuil(tn+1)= Seuil(tn)*factor
Endif
```

- solveur_bar solveur_sys_base (11.16) for inheritance: This keyword is used to define when filtering operation is called (typically for EF convective scheme, standard diffusion operator and Source_Qdm_lambdaup). A file (solveur.bar) is then created and used for inversion procedure. Syntax is the same then for pressure solver (GCP is required for multi-processor calculations and, in a general way, for big meshes).
- **projection_initiale** *int* for inheritance: Keyword to suppress, if boolean equals 0, the initial projection which checks DivU=0. By default, boolean equals 1.
- **postraiter_gradient_pression_sans_masse** for inheritance: Avoid mass matrix multiplication for the gradient postprocessing
- methode_calcul_pression_initiale str into ['avec_les_cl', 'avec_sources', 'avec_sources_et_operateurs', 'sans_rien'] for inheritance: Keyword to select an option for the pressure calculation before the fist

time step. Options are: avec_les_cl (default option lapP=0 is solved with Neuman boundary conditions on pressure if any), avec_sources (lapP=f is solved with Neuman boundaries conditions and f integrating the source terms of the Navier-Stokes equations) and avec_sources_et_operateurs (lapP=f is solved as with the previous option avec_sources but f integrating also some operators of the Navier-Stokes equations). The two last options are useful and sometime necessary when source terms are implicited when using an implicit time scheme to solve the Navier-Stokes equations.

- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation non resolue (t>t0)*(t<t1) }
```

• renommer equation str for inheritance: Rename the equation with a specific name.

5.39 Navier_stokes_ibm

```
Description: IBM Navier-Stokes equations.
```

Keyword Discretize should have already been used to read the object.

```
See also: navier_stokes_standard (5.42)
```

```
Usage:
navier_stokes_ibm str
Read str {
```

```
[ correction_matrice_projection_initiale int]
[ correction_calcul_pression_initiale int]
[ correction_vitesse_projection_initiale int]
[correction matrice pression int]
[ matrice_pression_penalisee_H1 int]
[correction vitesse modifie int]
[ correction_pression_modifie int]
[gradient pression qdm modifie int]
[correction_variable_initiale int]
[solveur_pression solveur_sys_base]
[ dt projection deuxmots]
[traitement_particulier traitement_particulier]
[ seuil_divU floatfloat]
[solveur_bar solveur_sys_base]
[ projection_initiale int]
[ postraiter_gradient_pression_sans_masse ]
```

- correction_matrice_projection_initiale int: (IBM advanced) fix matrix of initial projection for PDF
- correction_calcul_pression_initiale int: (IBM advanced) fix initial pressure computation for PDF
- correction_vitesse_projection_initiale int: (IBM advanced) fix initial velocity computation for PDF
- correction_matrice_pression int: (IBM advanced) fix pressure matrix for PDF
- matrice_pression_penalisee_H1 int: (IBM advanced) fix pressure matrix for PDF
- correction_vitesse_modifie int: (IBM advanced) fix velocity for PDF
- correction_pression_modifie int: (IBM advanced) fix pressure for PDF
- gradient pression qdm modifie int: (IBM advanced) fix pressure gradient
- correction_variable_initiale int: Modify initial variable
- solveur_pression solveur_sys_base (11.16) for inheritance: Linear pressure system resolution method.
- **dt_projection** *deuxmots* (5.35) for inheritance: nb value: This keyword checks every nb time-steps the equality of velocity divergence to zero. value is the criteria convergency for the solver used.
- **traitement_particulier** *traitement_particulier* (5.36) for inheritance: Keyword to post-process particular values.
- seuil_divU floatfloat (5.37) for inheritance: value factor: this keyword is intended to minimise the number of iterations during the pressure system resolution. The convergence criteria during this step ('seuil' in solveur_pression) is dynamically adapted according to the mass conservation. At tn, the linear system Ax=B is considered as solved if the residual ||Ax-B||<seuil(tn). For tn+1, the threshold value seuil(tn+1) will be evualated as:

```
If ( |max(DivU)*dt|<value )
Seuil(tn+1)= Seuil(tn)*factor
Else
Seuil(tn+1)= Seuil(tn)*factor
Endif
```

- **solveur_bar** *solveur_sys_base* (11.16) for inheritance: This keyword is used to define when filtering operation is called (typically for EF convective scheme, standard diffusion operator and Source_Qdm_lambdaup). A file (solveur.bar) is then created and used for inversion procedure. Syntax is the same then for pressure solver (GCP is required for multi-processor calculations and, in a general way, for big meshes).
- **projection_initiale** *int* for inheritance: Keyword to suppress, if boolean equals 0, the initial projection which checks DivU=0. By default, boolean equals 1.
- **postraiter_gradient_pression_sans_masse** for inheritance: Avoid mass matrix multiplication for the gradient postprocessing

- methode_calcul_pression_initiale str into ['avec_les_cl', 'avec_sources', 'avec_sources_et_operateurs', 'sans_rien'] for inheritance: Keyword to select an option for the pressure calculation before the fist time step. Options are: avec_les_cl (default option lapP=0 is solved with Neuman boundary conditions on pressure if any), avec_sources (lapP=f is solved with Neuman boundaries conditions and f integrating the source terms of the Navier-Stokes equations) and avec_sources_et_operateurs (lapP=f is solved as with the previous option avec_sources but f integrating also some operators of the Navier-Stokes equations). The two last options are useful and sometime necessary when source terms are implicited when using an implicit time scheme to solve the Navier-Stokes equations.
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** bloc_diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.40 Navier stokes ibm turbulent

Description: IBM Navier-Stokes equations as well as the associated turbulence model equations.

Keyword Discretize should have already been used to read the object. See also: navier_stokes_standard (5.42)

[boundary_conditions|conditions_limites condlims]

```
Usage:
navier_stokes_ibm_turbulent str

Read str {

    [ modele_turbulence modele_turbulence_hyd_deriv]
    [ solveur_pression solveur_sys_base]
    [ dt_projection deuxmots]
    [ traitement_particulier traitement_particulier]
    [ seuil_divU floatfloat]
    [ solveur_bar solveur_sys_base]
    [ projection_initiale int]
    [ postraiter_gradient_pression_sans_masse ]
    [ methode_calcul_pression_initiale str into ['avec_les_cl', 'avec_sources', 'avec_sources_et_operateurs', 'sans_rien']]
    [ disable_equation_residual str]
    [ convection bloc_convection]
    [ diffusion bloc_diffusion]
```

- **modele_turbulence** *modele_turbulence_hyd_deriv* (5.41): Turbulence model for Navier-Stokes equations.
- solveur_pression solveur_sys_base (11.16) for inheritance: Linear pressure system resolution method.
- **dt_projection** *deuxmots* (5.35) for inheritance: nb value: This keyword checks every nb time-steps the equality of velocity divergence to zero. value is the criteria convergency for the solver used.
- **traitement_particulier** *traitement_particulier* (5.36) for inheritance: Keyword to post-process particular values.
- seuil_divU floatfloat (5.37) for inheritance: value factor: this keyword is intended to minimise the number of iterations during the pressure system resolution. The convergence criteria during this step ('seuil' in solveur_pression) is dynamically adapted according to the mass conservation. At tn, the linear system Ax=B is considered as solved if the residual ||Ax-B||<seuil(tn). For tn+1, the threshold value seuil(tn+1) will be evualated as:

```
If ( |max(DivU)*dt|<value )
Seuil(tn+1)= Seuil(tn)*factor
Else
Seuil(tn+1)= Seuil(tn)*factor
Endif
```

- **solveur_bar** *solveur_sys_base* (11.16) for inheritance: This keyword is used to define when filtering operation is called (typically for EF convective scheme, standard diffusion operator and Source_Qdm_lambdaup). A file (solveur.bar) is then created and used for inversion procedure. Syntax is the same then for pressure solver (GCP is required for multi-processor calculations and, in a general way, for big meshes).
- **projection_initiale** *int* for inheritance: Keyword to suppress, if boolean equals 0, the initial projection which checks DivU=0. By default, boolean equals 1.
- **postraiter_gradient_pression_sans_masse** for inheritance: Avoid mass matrix multiplication for the gradient postprocessing
- methode_calcul_pression_initiale str into ['avec_les_cl', 'avec_sources', 'avec_sources_et_operateurs',
 'sans_rien'] for inheritance: Keyword to select an option for the pressure calculation before the fist
 time step. Options are: avec_les_cl (default option lapP=0 is solved with Neuman boundary conditions on pressure if any), avec_sources (lapP=f is solved with Neuman boundaries conditions and f
 integrating the source terms of the Navier-Stokes equations) and avec_sources_et_operateurs (lapP=f
 is solved as with the previous option avec_sources but f integrating also some operators of the NavierStokes equations). The two last options are useful and sometime necessary when source terms are
 implicited when using an implicit time scheme to solve the Navier-Stokes equations.
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- **boundary_conditions|conditions_limites** *condlims* (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- sources sources (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be

- separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

5.41 Modele turbulence hyd deriv

Description: Basic class for turbulence model for Navier-Stokes equations.

```
See also: objet_lecture (39) mod_turb_hyd_ss_maille (5.41.2) mod_turb_hyd_rans (5.41.7) null (5.41.8)

Usage:
modele_turbulence_hyd_deriv {

    [ turbulence_paroi turbulence_paroi_base]
    [ dt_impr_ustar float]
    [ dt_impr_ustar_mean_only dt_impr_ustar_mean_only]
    [ nut_max float]
    [ correction_visco_turb_pour_controle_pas_de_temps ]
    [ correction_visco_turb_pour_controle_pas_de_temps_parametre float]
}
where
```

- **turbulence_paroi** *turbulence_paroi_base* (36): Keyword to set the wall law.
- dt_impr_ustar float: This keyword is used to print the values (U +, d+, u*) obtained with the wall
 laws into a file named datafile_ProblemName_Ustar.face and periode refers to the printing period,
 this value is expressed in seconds.
- dt_impr_ustar_mean_only dt_impr_ustar_mean_only (5.41.1): This keyword is used to print the mean values of u* (obtained with the wall laws) on each boundary, into a file named datafile_ProblemName_Ustar_mean_only.out. periode refers to the printing period, this value is expressed in seconds. If you don't use the optional keyword boundaries, all the boundaries will be considered. If you use it, you must specify nb_boundaries which is the number of boundaries on which you want to calculate the mean values of u*, then you have to specify their names.
- nut_max float: Upper limitation of turbulent viscosity (default value 1.e8).
- correction_visco_turb_pour_controle_pas_de_temps: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is calculated so that diffusive time-step is equal or higher than convective time-step. For a stationary flow, the correction for turbulent viscosity should apply only during the first time steps and not when permanent state is reached. To check that, we could post process the corr_visco_turb field which is the correction of turbulent viscosity: it should be 1. on the whole domain.
- correction_visco_turb_pour_controle_pas_de_temps_parametre float: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is the ratio between diffusive time-step and convective time-step is higher or equal to the given value [0-1]

```
5.41.1 Dt_impr_ustar_mean_only
Description: not set
See also: objet lecture (39)
Usage:
{
     dt_impr float
     [ boundaries n word1 word2 ... wordn]
where
   • dt_impr float
   • boundaries n word1 word2 ... wordn
5.41.2 Mod_turb_hyd_ss_maille
Description: Class for sub-grid turbulence model for Navier-Stokes equations.
See also: modele_turbulence_hyd_deriv (5.41) sous_maille_smago (5.41.4) sous_maille_wale (5.41.5)
longueur_melange (5.41.6)
Usage:
mod_turb_hyd_ss_maille {
     [formulation_a_nb_points form_a_nb_points]
     [longueur_maille str into ['volume', 'volume_sans_lissage', 'scotti', 'arrete']]
     [turbulence_paroi turbulence_paroi_base]
     [ dt impr ustar float]
     [ dt_impr_ustar_mean_only dt_impr_ustar_mean_only]
     [ nut_max float]
     [ correction_visco_turb_pour_controle_pas_de_temps ]
     [correction_visco_turb_pour_controle_pas_de_temps_parametre float]
}
where
```

- **formulation_a_nb_points** *form_a_nb_points* (5.41.3): The structure fonction is calculated on nb points and we should add the 2 directions (0:OX, 1:OY, 2:OZ) constituting the homegeneity planes. Example for channel flows, planes parallel to the walls.
- longueur_maille str into ['volume', 'volume_sans_lissage', 'scotti', 'arrete']: Different ways to calculate the characteristic length may be specified:
 - volume: It is the default option. Characteristic length is based on the cubic root of the volume cells. A smoothing procedure is applied to avoid discontinuities of this quantity in VEF from a cell to another.
 - volume_sans_lissage: For VEF only. Characteristic length is based on the cubic root of the volume cells (without smoothing procedure).
 - scotti : Characteristic length is based on the cubic root of the volume cells and the Scotti correction is applied to take into account the stretching of the cell in the case of anisotropic meshes.
 - arete: For VEF only. Characteristic length relies on the max edge (+ smoothing procedure) is taken into account.
- turbulence_paroi_turbulence_paroi_base (36) for inheritance: Keyword to set the wall law.

- **dt_impr_ustar** *float* for inheritance: This keyword is used to print the values (U +, d+, u*) obtained with the wall laws into a file named datafile_ProblemName_Ustar.face and periode refers to the printing period, this value is expressed in seconds.
- **dt_impr_ustar_mean_only** *dt_impr_ustar_mean_only* (5.41.1) for inheritance: This keyword is used to print the mean values of u* (obtained with the wall laws) on each boundary, into a file named datafile_ProblemName_Ustar_mean_only.out. periode refers to the printing period, this value is expressed in seconds. If you don't use the optional keyword boundaries, all the boundaries will be considered. If you use it, you must specify nb_boundaries which is the number of boundaries on which you want to calculate the mean values of u*, then you have to specify their names.
- nut_max float for inheritance: Upper limitation of turbulent viscosity (default value 1.e8).
- correction_visco_turb_pour_controle_pas_de_temps for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is calculated so that diffusive time-step is equal or higher than convective time-step. For a stationary flow, the correction for turbulent viscosity should apply only during the first time steps and not when permanent state is reached. To check that, we could post process the corr_visco_turb field which is the correction of turbulent viscosity: it should be 1. on the whole domain.
- correction_visco_turb_pour_controle_pas_de_temps_parametre float for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is the ratio between diffusive time-step and convective time-step is higher or equal to the given value [0-1]

5.41.3 Form_a_nb_points

See also: objet_lecture (39)

Description: The structure function is calculated on nb points and we should add the 2 directions (0:OX, 1:OY, 2:OZ) constituting the homegeneity planes. Example for channel flows, planes parallel to the walls.

```
Usage:
nb dir1 dir2
where
   • nb int into [4]: Number of points.
   • dir1 int: First direction.
   • dir2 int: Second direction.
5.41.4 Sous maille smago
Description: Smagorinsky sub-grid turbulence model.
Nut=Cs1*Cs1*l*l*sqrt(2*S*S)
K=Cs2*Cs2*1*1*2*S
See also: mod_turb_hyd_ss_maille (5.41.2)
Usage:
sous_maille_smago {
     [cs float]
     [ formulation_a_nb_points form_a_nb_points]
     [longueur_maille str into ['volume', 'volume_sans_lissage', 'scotti', 'arrete']]
     [turbulence paroi turbulence paroi base]
     [ dt_impr_ustar float]
     [ dt_impr_ustar_mean_only dt_impr_ustar_mean_only]
     [ nut_max float]
```

```
[ correction_visco_turb_pour_controle_pas_de_temps ]
    [ correction_visco_turb_pour_controle_pas_de_temps_parametre float]
}
where
```

- **cs** *float*: This is an optional keyword and the value is used to set the constant used in the Smagorinsky model (This is currently only valid for Smagorinsky models and it is set to 0.18 by default).
- **formulation_a_nb_points** *form_a_nb_points* (5.41.3) for inheritance: The structure fonction is calculated on nb points and we should add the 2 directions (0:OX, 1:OY, 2:OZ) constituting the homegeneity planes. Example for channel flows, planes parallel to the walls.
- **longueur_maille** *str into ['volume', 'volume_sans_lissage', 'scotti', 'arrete']* for inheritance: Different ways to calculate the characteristic length may be specified:
 - volume: It is the default option. Characteristic length is based on the cubic root of the volume cells. A smoothing procedure is applied to avoid discontinuities of this quantity in VEF from a cell to another
 - volume_sans_lissage: For VEF only. Characteristic length is based on the cubic root of the volume cells (without smoothing procedure).
 - scotti: Characteristic length is based on the cubic root of the volume cells and the Scotti correction is applied to take into account the stretching of the cell in the case of anisotropic meshes.
 - arete: For VEF only. Characteristic length relies on the max edge (+ smoothing procedure) is taken into account.
- turbulence_paroi turbulence_paroi_base (36) for inheritance: Keyword to set the wall law.
- **dt_impr_ustar** *float* for inheritance: This keyword is used to print the values (U +, d+, u*) obtained with the wall laws into a file named datafile_ProblemName_Ustar.face and periode refers to the printing period, this value is expressed in seconds.
- **dt_impr_ustar_mean_only** *dt_impr_ustar_mean_only* (5.41.1) for inheritance: This keyword is used to print the mean values of u* (obtained with the wall laws) on each boundary, into a file named datafile_ProblemName_Ustar_mean_only.out. periode refers to the printing period, this value is expressed in seconds. If you don't use the optional keyword boundaries, all the boundaries will be considered. If you use it, you must specify nb_boundaries which is the number of boundaries on which you want to calculate the mean values of u*, then you have to specify their names.
- nut_max *float* for inheritance: Upper limitation of turbulent viscosity (default value 1.e8).
- correction_visco_turb_pour_controle_pas_de_temps for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is calculated so that diffusive time-step is equal or higher than convective time-step. For a stationary flow, the correction for turbulent viscosity should apply only during the first time steps and not when permanent state is reached. To check that, we could post process the corr_visco_turb field which is the correction of turbulent viscosity: it should be 1. on the whole domain.
- correction_visco_turb_pour_controle_pas_de_temps_parametre float for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is the ratio between diffusive time-step and convective time-step is higher or equal to the given value [0-1]

5.41.5 Sous_maille_wale

Description: This is the WALE-model. It is a new sub-grid scale model for eddy-viscosity in LES that has the following properties:

- it goes naturally to 0 at the wall (it doesn't need any information on the wall position or geometry)
- it has the proper wall scaling in o(y3) in the vicinity of the wall
- it reproduces correctly the laminar to turbulent transition.

See also: mod_turb_hyd_ss_maille (5.41.2)

```
Usage:
sous_maille_wale {

[ cw float]

[ formulation_a_nb_points form_a_nb_points]

[ longueur_maille str into ['volume', 'volume_sans_lissage', 'scotti', 'arrete']]

[ turbulence_paroi turbulence_paroi_base]

[ dt_impr_ustar float]

[ dt_impr_ustar_mean_only dt_impr_ustar_mean_only]

[ nut_max float]

[ correction_visco_turb_pour_controle_pas_de_temps ]

[ correction_visco_turb_pour_controle_pas_de_temps_parametre float]

}

where
```

- cw float: The unique parameter (constant) of the WALE-model (by default value 0.5).
- **formulation_a_nb_points** *form_a_nb_points* (5.41.3) for inheritance: The structure fonction is calculated on nb points and we should add the 2 directions (0:OX, 1:OY, 2:OZ) constituting the homegeneity planes. Example for channel flows, planes parallel to the walls.
- **longueur_maille** *str into ['volume', 'volume_sans_lissage', 'scotti', 'arrete']* for inheritance: Different ways to calculate the characteristic length may be specified:
 - volume: It is the default option. Characteristic length is based on the cubic root of the volume cells. A smoothing procedure is applied to avoid discontinuities of this quantity in VEF from a cell to another.
 - volume_sans_lissage : For VEF only. Characteristic length is based on the cubic root of the volume cells (without smoothing procedure).
 - scotti: Characteristic length is based on the cubic root of the volume cells and the Scotti correction is applied to take into account the stretching of the cell in the case of anisotropic meshes.
 - arete: For VEF only. Characteristic length relies on the max edge (+ smoothing procedure) is taken into account.
- turbulence_paroi_turbulence_paroi_base (36) for inheritance: Keyword to set the wall law.
- dt_impr_ustar float for inheritance: This keyword is used to print the values (U +, d+, u⋆) obtained with the wall laws into a file named datafile_ProblemName_Ustar.face and periode refers to the printing period, this value is expressed in seconds.
- **dt_impr_ustar_mean_only** *dt_impr_ustar_mean_only* (5.41.1) for inheritance: This keyword is used to print the mean values of u* (obtained with the wall laws) on each boundary, into a file named datafile_ProblemName_Ustar_mean_only.out. periode refers to the printing period, this value is expressed in seconds. If you don't use the optional keyword boundaries, all the boundaries will be considered. If you use it, you must specify nb_boundaries which is the number of boundaries on which you want to calculate the mean values of u*, then you have to specify their names.
- **nut_max** *float* for inheritance: Upper limitation of turbulent viscosity (default value 1.e8).
- **correction_visco_turb_pour_controle_pas_de_temps** for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is calculated so that diffusive time-step is equal or higher than convective time-step. For a stationary flow, the correction for turbulent viscosity should apply only during the first time steps and not when permanent state is reached. To check that, we could post process the corr_visco_turb field which is the correction of turbulent viscosity: it should be 1. on the whole domain.
- correction_visco_turb_pour_controle_pas_de_temps_parametre float for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is the ratio between diffusive time-step and convective time-step is higher or equal to the given value [0-1]

5.41.6 Longueur_melange

Description: This model is based on mixing length modelling. For a non academic configuration, formulation used in the code can be expressed basically as:

```
nu\_t = (Kappa.y)^2.dU/dy
```

Till a maximum distance (dmax) set by the user in the data file, y is set equal to the distance from the wall (dist_w) calculated previously and saved in file Wall_length.xyz. [see Distance_paroi keyword]

Then (from y=dmax), y decreases as an exponential function : y=dmax*exp[-2.*(dist_w-dmax)/dmax]

```
See also: mod_turb_hyd_ss_maille (5.41.2)
```

```
Usage:
```

```
longueur_melange {
     [canalx float]
     [tuyauz float]
     [ verif_dparoi str]
     [dmax float]
     [fichier str]
     [fichier_ecriture_K_Eps str]
     [formulation a nb points form a nb points]
     [longueur_maille str into ['volume', 'volume_sans_lissage', 'scotti', 'arrete']]
     [turbulence paroi turbulence paroi base]
     [ dt impr ustar float]
     [ dt_impr_ustar_mean_only dt_impr_ustar_mean_only]
     [ nut_max float]
     [correction_visco_turb_pour_controle_pas_de_temps]
     [correction_visco_turb_pour_controle_pas_de_temps_parametre float]
}
where
```

- **canalx** *float*: [height]: plane channel according to Ox direction (for the moment, formulation in the code relies on fixed heigh: H=2).
- **tuyauz** *float*: [diameter] : pipe according to Oz direction (for the moment, formulation in the code relies on fixed diameter : D=2).
- verif dparoi str
- dmax float: Maximum distance.
- fichier str
- fichier_ecriture_K_Eps str: When a resume with k-epsilon model is envisaged, this keyword allows to generate external MED-format file with evaluation of k and epsilon quantities (based on eddy turbulent viscosity and turbulent characteristic length returned by mixing length model). The frequency of the MED file print is set equal to dt_impr_ustar. Moreover, k-eps MED field is automatically saved at the last time step. MED file is then used for resuming a K-Epsilon calculation with the Champ_Fonc_Med keyword.
- **formulation_a_nb_points** *form_a_nb_points* (5.41.3) for inheritance: The structure fonction is calculated on nb points and we should add the 2 directions (0:OX, 1:OY, 2:OZ) constituting the homegeneity planes. Example for channel flows, planes parallel to the walls.
- **longueur_maille** *str into ['volume', 'volume_sans_lissage', 'scotti', 'arrete']* for inheritance: Different ways to calculate the characteristic length may be specified:
 - volume: It is the default option. Characteristic length is based on the cubic root of the volume cells. A smoothing procedure is applied to avoid discontinuities of this quantity in VEF from a cell to another.
 - volume_sans_lissage: For VEF only. Characteristic length is based on the cubic root of the volume cells (without smoothing procedure).

scotti: Characteristic length is based on the cubic root of the volume cells and the Scotti correction is applied to take into account the stretching of the cell in the case of anisotropic meshes. arete: For VEF only. Characteristic length relies on the max edge (+ smoothing procedure) is taken into account.

- turbulence_paroi turbulence_paroi_base (36) for inheritance: Keyword to set the wall law.
- **dt_impr_ustar** *float* for inheritance: This keyword is used to print the values (U +, d+, u*) obtained with the wall laws into a file named datafile_ProblemName_Ustar.face and periode refers to the printing period, this value is expressed in seconds.
- **dt_impr_ustar_mean_only** *dt_impr_ustar_mean_only* (5.41.1) for inheritance: This keyword is used to print the mean values of u* (obtained with the wall laws) on each boundary, into a file named datafile_ProblemName_Ustar_mean_only.out. periode refers to the printing period, this value is expressed in seconds. If you don't use the optional keyword boundaries, all the boundaries will be considered. If you use it, you must specify nb_boundaries which is the number of boundaries on which you want to calculate the mean values of u*, then you have to specify their names.
- nut_max float for inheritance: Upper limitation of turbulent viscosity (default value 1.e8).
- correction_visco_turb_pour_controle_pas_de_temps for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is calculated so that diffusive time-step is equal or higher than convective time-step. For a stationary flow, the correction for turbulent viscosity should apply only during the first time steps and not when permanent state is reached. To check that, we could post process the corr_visco_turb field which is the correction of turbulent viscosity: it should be 1. on the whole domain.
- correction_visco_turb_pour_controle_pas_de_temps_parametre float for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is the ratio between diffusive time-step and convective time-step is higher or equal to the given value [0-1]

5.41.7 Mod_turb_hyd_rans

Description: Class for RANS turbulence model for Navier-Stokes equations.

```
See also: modele_turbulence_hyd_deriv (5.41)

Usage:
mod_turb_hyd_rans {

    [k_min float]
    [quiet ]
    [turbulence_paroi turbulence_paroi_base]
    [dt_impr_ustar float]
    [dt_impr_ustar_mean_only dt_impr_ustar_mean_only]
    [nut_max float]
    [correction_visco_turb_pour_controle_pas_de_temps ]
    [correction_visco_turb_pour_controle_pas_de_temps_parametre float]
}
where
```

- k min *float*: Lower limitation of k (default value 1.e-10).
- quiet: To disable printing of information about K and Epsilon/Omega.
- turbulence_paroi_turbulence_paroi_base (36) for inheritance: Keyword to set the wall law.
- dt_impr_ustar float for inheritance: This keyword is used to print the values (U +, d+, u⋆) obtained with the wall laws into a file named datafile_ProblemName_Ustar.face and periode refers to the printing period, this value is expressed in seconds.

- **dt_impr_ustar_mean_only** *dt_impr_ustar_mean_only* (5.41.1) for inheritance: This keyword is used to print the mean values of u* (obtained with the wall laws) on each boundary, into a file named datafile_ProblemName_Ustar_mean_only.out. periode refers to the printing period, this value is expressed in seconds. If you don't use the optional keyword boundaries, all the boundaries will be considered. If you use it, you must specify nb_boundaries which is the number of boundaries on which you want to calculate the mean values of u*, then you have to specify their names.
- nut max float for inheritance: Upper limitation of turbulent viscosity (default value 1.e8).
- correction_visco_turb_pour_controle_pas_de_temps for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is calculated so that diffusive time-step is equal or higher than convective time-step. For a stationary flow, the correction for turbulent viscosity should apply only during the first time steps and not when permanent state is reached. To check that, we could post process the corr_visco_turb field which is the correction of turbulent viscosity: it should be 1. on the whole domain.
- correction_visco_turb_pour_controle_pas_de_temps_parametre float for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is the ratio between diffusive time-step and convective time-step is higher or equal to the given value [0-1]

5.41.8 Null

Description: Null turbulence model (turbulent viscosity = 0) which can be used with a turbulent problem.

```
See also: modele_turbulence_hyd_deriv (5.41)

Usage:
null {

    [turbulence_paroi turbulence_paroi_base]
    [dt_impr_ustar float]
    [dt_impr_ustar_mean_only dt_impr_ustar_mean_only]
    [nut_max float]
    [correction_visco_turb_pour_controle_pas_de_temps]
    [correction_visco_turb_pour_controle_pas_de_temps_parametre float]
}
where
```

- turbulence_paroi turbulence_paroi_base (36) for inheritance: Keyword to set the wall law.
- **dt_impr_ustar** *float* for inheritance: This keyword is used to print the values (U +, d+, u*) obtained with the wall laws into a file named datafile_ProblemName_Ustar.face and periode refers to the printing period, this value is expressed in seconds.
- **dt_impr_ustar_mean_only** *dt_impr_ustar_mean_only* (5.41.1) for inheritance: This keyword is used to print the mean values of u* (obtained with the wall laws) on each boundary, into a file named datafile_ProblemName_Ustar_mean_only.out. periode refers to the printing period, this value is expressed in seconds. If you don't use the optional keyword boundaries, all the boundaries will be considered. If you use it, you must specify nb_boundaries which is the number of boundaries on which you want to calculate the mean values of u*, then you have to specify their names.
- nut_max float for inheritance: Upper limitation of turbulent viscosity (default value 1.e8).
- correction_visco_turb_pour_controle_pas_de_temps for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is calculated so that diffusive time-step is equal or higher than convective time-step. For a stationary flow, the correction for turbulent viscosity should apply only during the first time steps and not when permanent state is reached. To check that, we could post process the corr_visco_turb field which is the correction of turbulent viscosity: it should be 1. on the whole domain.

• correction_visco_turb_pour_controle_pas_de_temps_parametre float for inheritance: Keyword to set a limitation to low time steps due to high values of turbulent viscosity. The limit for turbulent viscosity is the ratio between diffusive time-step and convective time-step is higher or equal to the given value [0-1]

5.42 Navier stokes standard

```
Description: Navier-Stokes equations.
```

Keyword Discretize should have already been used to read the object. See also: eqn_base (5.33) navier_stokes_ibm_turbulent (5.40) navier_stokes_ibm (5.39) navier_stokes-turbulent (5.43) navier stokes QC (5.34) navier stokes WC (5.38)

```
Usage:
navier_stokes_standard str
Read str {
     [solveur_pression solveur_sys_base]
     [dt_projection deuxmots]
     [traitement_particulier traitement_particulier]
     [ seuil_divU floatfloat]
     [solveur_bar solveur_sys_base]
     [projection_initiale int]
     [ postraiter_gradient_pression_sans_masse ]
     operateurs', 'sans rien']
     [disable equation residual str]
     [convection bloc convection]
     [ diffusion bloc_diffusion]
     [boundary conditions|conditions limites condlims]
     [initial conditions|conditions initiales condinits]
     [sources sources]
     [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
     [ parametre_equation parametre_equation_base]
     [ equation_non_resolue str]
     [renommer_equation str]
```

- solveur_pression solveur_sys_base (11.16): Linear pressure system resolution method.
- **dt_projection** *deuxmots* (5.35): nb value: This keyword checks every nb time-steps the equality of velocity divergence to zero. value is the criteria convergency for the solver used.
- **traitement_particulier** *traitement_particulier* (5.36): Keyword to post-process particular values.
- **seuil_divU** *floatfloat* (5.37): value factor: this keyword is intended to minimise the number of iterations during the pressure system resolution. The convergence criteria during this step ('seuil' in solveur_pression) is dynamically adapted according to the mass conservation. At tn, the linear system Ax=B is considered as solved if the residual ||Ax-B||<seuil(tn). For tn+1, the threshold value seuil(tn+1) will be evualated as:

```
If ( |max(DivU)*dt|<value )
Seuil(tn+1)= Seuil(tn)*factor
Else
Seuil(tn+1)= Seuil(tn)*factor
Endif
```

where

- **solveur_sys_base** (11.16): This keyword is used to define when filtering operation is called (typically for EF convective scheme, standard diffusion operator and Source_Qdm_lambdaup). A file (solveur.bar) is then created and used for inversion procedure. Syntax is the same then for pressure solver (GCP is required for multi-processor calculations and, in a general way, for big meshes).
- **projection_initiale** *int*: Keyword to suppress, if boolean equals 0, the initial projection which checks DivU=0. By default, boolean equals 1.
- **postraiter_gradient_pression_sans_masse** : Avoid mass matrix multiplication for the gradient postprocessing
- methode_calcul_pression_initiale str into ['avec_les_cl', 'avec_sources', 'avec_sources_et_operateurs', 'sans_rien']: Keyword to select an option for the pressure calculation before the fist time step. Options are: avec_les_cl (default option lapP=0 is solved with Neuman boundary conditions on pressure if any), avec_sources (lapP=f is solved with Neuman boundaries conditions and f integrating the source terms of the Navier-Stokes equations) and avec_sources_et_operateurs (lapP=f is solved as with the previous option avec_sources but f integrating also some operators of the Navier-Stokes equations). The two last options are useful and sometime necessary when source terms are implicited when using an implicit time scheme to solve the Navier-Stokes equations.
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** bloc_convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** bloc_diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary conditions|conditions limites condlims (5.4) for inheritance: Boundary conditions.
- initial conditions|conditions initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

• renommer equation str for inheritance: Rename the equation with a specific name.

5.43 Navier_stokes_turbulent

Description: Navier-Stokes equations as well as the associated turbulence model equations.

```
Keyword Discretize should have already been used to read the object.

See also: navier_stokes_standard (5.42) navier_stokes_turbulent_qc (5.44)

Usage:
navier_stokes_turbulent str

Read str {

[ modele_turbulence modele_turbulence_hyd_deriv]
[ solveur_pression solveur_sys_base]
[ dt_projection deuxmots]
```

```
[traitement_particulier traitement_particulier]
    [ seuil_divU floatfloat]
    [solveur bar solveur sys base]
    [ projection_initiale int]
    [ postraiter_gradient_pression_sans_masse ]
    operateurs', 'sans rien']
    [ disable equation residual str]
    [convection bloc convection]
    [ diffusion bloc diffusion]
    [boundary conditions|conditions limites condlims]
    [initial conditions|conditions initiales condinits]
    [sources sources]
    [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
    [ parametre_equation parametre_equation_base]
    [ equation_non_resolue str]
    [renommer_equation str]
}
where
```

- **modele_turbulence** *modele_turbulence_hyd_deriv* (5.41): Turbulence model for Navier-Stokes equations.
- solveur_pression solveur_sys_base (11.16) for inheritance: Linear pressure system resolution method.
- **dt_projection** *deuxmots* (5.35) for inheritance: nb value: This keyword checks every nb time-steps the equality of velocity divergence to zero. value is the criteria convergency for the solver used.
- **traitement_particulier** *traitement_particulier* (5.36) for inheritance: Keyword to post-process particular values.
- seuil_divU floatfloat (5.37) for inheritance: value factor: this keyword is intended to minimise the number of iterations during the pressure system resolution. The convergence criteria during this step ('seuil' in solveur_pression) is dynamically adapted according to the mass conservation. At tn, the linear system Ax=B is considered as solved if the residual ||Ax-B||<seuil(tn). For tn+1, the threshold value seuil(tn+1) will be evualated as:

```
If ( |max(DivU)*dt|<value )
Seuil(tn+1)= Seuil(tn)*factor
Else
Seuil(tn+1)= Seuil(tn)*factor
Endif
```

- **solveur_bar** *solveur_sys_base* (11.16) for inheritance: This keyword is used to define when filtering operation is called (typically for EF convective scheme, standard diffusion operator and Source_Qdm_lambdaup). A file (solveur.bar) is then created and used for inversion procedure. Syntax is the same then for pressure solver (GCP is required for multi-processor calculations and, in a general way, for big meshes).
- **projection_initiale** *int* for inheritance: Keyword to suppress, if boolean equals 0, the initial projection which checks DivU=0. By default, boolean equals 1.
- **postraiter_gradient_pression_sans_masse** for inheritance: Avoid mass matrix multiplication for the gradient postprocessing
- methode_calcul_pression_initiale str into ['avec_les_cl', 'avec_sources', 'avec_sources_et_operateurs', 'sans_rien'] for inheritance: Keyword to select an option for the pressure calculation before the fist time step. Options are: avec_les_cl (default option lapP=0 is solved with Neuman boundary conditions on pressure if any), avec_sources (lapP=f is solved with Neuman boundaries conditions and f integrating the source terms of the Navier-Stokes equations) and avec_sources_et_operateurs (lapP=f

is solved as with the previous option avec_sources but f integrating also some operators of the Navier-Stokes equations). The two last options are useful and sometime necessary when source terms are implicited when using an implicit time scheme to solve the Navier-Stokes equations.

- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- **convection** *bloc_convection* (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** bloc_diffusion (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial conditions londitions initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file
- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

• renommer_equation str for inheritance: Rename the equation with a specific name.

5.44 Navier_stokes_turbulent_qc

Description: Navier-Stokes equations under low Mach number as well as the associated turbulence model equations.

```
Keyword Discretize should have already been used to read the object.
```

```
See also: navier_stokes_turbulent (5.43)
```

```
Usage:
```

```
navier stokes turbulent qc str
Read str {
    [ modele_turbulence modele_turbulence_hyd_deriv]
    [solveur_pression solveur_sys_base]
    [dt_projection deuxmots]
     [traitement_particulier traitement_particulier]
    [ seuil_divU floatfloat]
    [solveur_bar solveur_sys_base]
    [ projection_initiale int]
     [ postraiter gradient pression sans masse ]
    _operateurs', 'sans_rien']
    [ disable equation residual str]
    [convection bloc convection]
    [ diffusion bloc diffusion]
    [boundary conditions|conditions limites condlims]
    [initial_conditions|conditions_initiales condinits]
     [sources sources]
    [ ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur]
    [ parametre_equation parametre_equation_base]
```

```
[ equation_non_resolue str]
  [ renommer_equation str]
}
where
```

- modele_turbulence modele_turbulence_hyd_deriv (5.41) for inheritance: Turbulence model for Navier-Stokes equations.
- solveur pression solveur sys base (11.16) for inheritance: Linear pressure system resolution method.
- **dt_projection** *deuxmots* (5.35) for inheritance: nb value: This keyword checks every nb time-steps the equality of velocity divergence to zero. value is the criteria convergency for the solver used.
- **traitement_particulier** *traitement_particulier* (5.36) for inheritance: Keyword to post-process particular values.
- seuil_divU floatfloat (5.37) for inheritance: value factor: this keyword is intended to minimise the number of iterations during the pressure system resolution. The convergence criteria during this step ('seuil' in solveur_pression) is dynamically adapted according to the mass conservation. At tn, the linear system Ax=B is considered as solved if the residual ||Ax-B||<seuil(tn). For tn+1, the threshold value seuil(tn+1) will be evualated as:

```
If ( |max(DivU)*dt|<value )
Seuil(tn+1)= Seuil(tn)*factor
Else
Seuil(tn+1)= Seuil(tn)*factor
Endif
```

- solveur_bar solveur_sys_base (11.16) for inheritance: This keyword is used to define when filtering operation is called (typically for EF convective scheme, standard diffusion operator and Source_Qdm_lambdaup). A file (solveur.bar) is then created and used for inversion procedure. Syntax is the same then for pressure solver (GCP is required for multi-processor calculations and, in a general way, for big meshes).
- **projection_initiale** *int* for inheritance: Keyword to suppress, if boolean equals 0, the initial projection which checks DivU=0. By default, boolean equals 1.
- **postraiter_gradient_pression_sans_masse** for inheritance: Avoid mass matrix multiplication for the gradient postprocessing
- methode_calcul_pression_initiale str into ['avec_les_cl', 'avec_sources', 'avec_sources_et_operateurs', 'sans_rien'] for inheritance: Keyword to select an option for the pressure calculation before the fist time step. Options are: avec_les_cl (default option lapP=0 is solved with Neuman boundary conditions on pressure if any), avec_sources (lapP=f is solved with Neuman boundaries conditions and f integrating the source terms of the Navier-Stokes equations) and avec_sources_et_operateurs (lapP=f is solved as with the previous option avec_sources but f integrating also some operators of the Navier-Stokes equations). The two last options are useful and sometime necessary when source terms are implicited when using an implicit time scheme to solve the Navier-Stokes equations.
- **disable_equation_residual** *str* for inheritance: The equation residual will not be used for the problem residual used when checking time convergence or computing dynamic time-step
- convection bloc_convection (5.2) for inheritance: Keyword to alter the convection scheme.
- **diffusion** *bloc_diffusion* (5.3) for inheritance: Keyword to specify the diffusion operator.
- boundary_conditions|conditions_limites condlims (5.4) for inheritance: Boundary conditions.
- initial_conditions|conditions_initiales condinits (5.5) for inheritance: Initial conditions.
- **sources** *sources* (5.6) for inheritance: To introduce a source term into an equation (in case of several source terms into the same equation, the blocks corresponding to the various terms need to be separated by a comma)
- ecrire_fichier_xyz_valeur ecrire_fichier_xyz_valeur (3.39) for inheritance: This keyword is used to write the values of a field only for some boundaries in a text file

- parametre_equation parametre_equation_base (5.7) for inheritance: Keyword used to specify additional parameters for the equation
- equation_non_resolue *str* for inheritance: The equation will not be solved while condition(t) is verified if equation_non_resolue keyword is used. Exemple: The Navier-Stokes equations are not solved between time t0 and t1.

```
Navier_Sokes_Standard { equation_non_resolue (t>t0)*(t<t1) }
```

6 domaine_base

```
Description: base for most domains

See also: objet_u (40) domaine_ijk (6.1)

Usage:

6.1 Domaine_ijk

Description: domain for IJK simulation (used in TrioCFD)

See also: Domaine_base (6)

Usage:
domaine_ijk str

Read str {

    nbelem n1 n2 (n3)
    size_dom x1 x2 (x3)
    perio n1 n2 (n3)
    nproc n1 n2 (n3)
}

where
```

- **nbelem** *n1 n2 (n3)*: Number of elements in each direction (integers, 2 or 3 values depending on dimension)
- size_dom x1 x2 (x3): Domain size in each direction (floats, 2 or 3 values depending on dimension)
- perio n1 n2 (n3): Is the direction periodic? (0 or 1, 2 or 3 values depending on dimension)
- **nproc** *n1 n2 (n3)*: Number of procs in each direction (integers, 2 or 3 values depending on dimension)

7 interface base

```
Description: Basic class for a liquid-gas interface (used in pb_multiphase)

See also: objet_u (40) saturation_base (7.2) Interface_sigma_constant (7.1)

Usage:
Interface_base str
Read str {

[surface_tension|tension_superficielle float]
```

```
}
where
```

• surface_tension|tension_superficielle float: surface tension

7.1 Interface_sigma_constant

```
Description: Liquid-gas interface with a constant surface tension sigma
```

```
See also: Interface_base (7)

Usage:
Interface_sigma_constant str

Read str {
    [surface_tension|tension_superficielle float]
}
where
```

• surface_tension|tension_superficielle float for inheritance: surface tension

7.2 Saturation_base

```
Description: fluide-gas interface with phase change (used in pb_multiphase)
```

```
See also: Interface_base (7) saturation_sodium (7.4) saturation_constant (7.3)
```

Usage:

```
saturation_base str
Read str {
      [ p_ref float]
      [ t_ref float]
      [ surface_tension|tension_superficielle float]
}
where
```

- p_ref float
- t_ref float
- surface_tension|tension_superficielle float for inheritance: surface tension

7.3 Saturation_constant

```
Description: Class for saturation constant
```

```
See also: saturation_base (7.2)
```

Usage:

```
saturation_constant str
Read str {
```

```
[P_sat float]
```

```
[ T_sat float]
[ Lvap float]
[ Hlsat float]
[ Hvsat float]
[ p_ref float]
[ t_ref float]
[ surface_tension|tension_superficielle float]
}
where
```

- **P_sat** *float*: Define the saturation pressure value (this is a required parameter)
- **T_sat** *float*: Define the saturation temperature value (this is a required parameter)
- Lvap float: Latent heat of vaporization
- Hlsat float: Liquid saturation enthalpy
- Hvsat float: Vapor saturation enthalpy
- **p_ref** *float* for inheritance
- **t_ref** *float* for inheritance
- surface_tension|tension_superficielle float for inheritance: surface tension

7.4 Saturation_sodium

```
Description: Class for saturation sodium
```

```
See also: saturation_base (7.2)

Usage:
saturation_sodium str

Read str {

    [P_ref float]
    [T_ref float]
    [p_ref float]
    [t_ref float]
    [surface_tension|tension_superficielle float]
}
```

- **P_ref** *float*: Use to fix the pressure value in the closure law. If not specified, the value of the pressure unknown will be used
- **T_ref** *float*: Use to fix the temperature value in the closure law. If not specified, the value of the temperature unknown will be used
- p ref float for inheritance
- **t_ref** *float* for inheritance
- surface_tension|superficielle float for inheritance: surface tension

```
8 /*
8.1 /*
```

where

Description: bloc of Comment in a data file.

See also: objet_u (40)

```
Usage:
/* comm
where
   • comm str: Text to be commented.
    champ_generique_base
Description: not_set
See also: objet_u (40) champ_post_de_champs_post (9.1) champ_post_refchamp (9.17) predefini (9.15)
Usage:
      Champ_post_de_champs_post
9.1
Description: not_set
See also: champ_generique_base (9) champ_post_tparoi_vef (9.18) champ_post_statistiques_base (9.6)
champ_post_extraction (9.10) champ_post_transformation (9.19) champ_post_operateur_base (9.4) champ-
_post_morceau_equation (9.13) interpolation (9.12) champ_post_reduction_0d (9.16) champ_post_operateur-
_eqn (9.5)
Usage:
champ_post_de_champs_post str
Read str {
     [ source champ_generique_base]
     [sources listchamp_generique]
     [ nom_source str]
     [ source_reference str]
     [ sources_reference list_nom_virgule]
}
where
   • source champ_generique_base (9): the source field.
   • sources listchamp_generique (9.2): sources { Champ_Post.... { ... } Champ_Post... { ... }}
   • nom_source str: To name a source field with the nom_source keyword
   • source_reference str
   • sources reference list nom virgule (9.3)
9.2 Listchamp_generique
Description: XXX
See also: listobj (38.5)
Usage:
{ object1, object2....}
```

list of champ_generique_base (9) separeted with,

```
9.3 List_nom_virgule
```

[compo int]

[source champ_generique_base]

```
Description: List of name.
See also: listobj (38.5)
Usage:
{ object1, object2 .... }
list of nom_anonyme (25.1) separeted with,
9.4 Champ_post_operateur_base
Description: not_set
See also: champ_post_de_champs_post (9.1) champ_post_operateur_gradient (9.11) champ_post_operateur-
_divergence (9.8)
Usage:
champ_post_operateur_base str
Read str {
     [ source champ_generique_base]
     [sources listchamp_generique]
     [ nom_source str]
     [ source_reference str]
     [sources_reference list_nom_virgule]
}
where
   • source champ_generique_base (9) for inheritance: the source field.
   • sources listchamp_generique (9.2) for inheritance: sources { Champ_Post.... { ... } Champ_Post...
   • nom_source str for inheritance: To name a source field with the nom_source keyword
   • source_reference str for inheritance
   • sources_reference list_nom_virgule (9.3) for inheritance
9.5 Champ_post_operateur_eqn
Synonymous: operateur_eqn
Description: Post-process equation operators/sources
See also: champ_post_de_champs_post (9.1)
Usage:
champ_post_operateur_eqn str
Read str {
     [ numero_source int]
     [ numero_op int]
     [ numero_masse int]
     [sans_solveur_masse]
```

```
[ sources listchamp_generique]
  [ nom_source str]
  [ source_reference str]
  [ sources_reference list_nom_virgule]
}
where
```

- **numero_source** *int*: the source to be post-processed (its number). If you have only one source term, numero_source will correspond to 0 if you want to post-process that unique source
- **numero_op** *int*: numero_op will be 0 (diffusive operator) or 1 (convective operator) or 2 (gradient operator) or 3 (divergence operator).
- numero_masse int: numero_masse will be 0 for the mass equation operator in Pb_multiphase.
- sans_solveur_masse
- **compo** *int*: If you want to post-process only one component of a vector field, you can specify the number of the component after compo keyword. By default, it is set to -1 which means that all the components will be post-processed. This feature is not available in VDF disretization.
- source champ_generique_base (9) for inheritance: the source field.
- **sources** *listchamp_generique* (9.2) for inheritance: sources { Champ_Post.... { ... } Champ_Post... { ... }}
- nom_source str for inheritance: To name a source field with the nom_source keyword
- source reference str for inheritance
- sources_reference list_nom_virgule (9.3) for inheritance

• sources_reference list_nom_virgule (9.3) for inheritance

9.6 Champ_post_statistiques_base

```
Description: not_set
See also: champ post de champs post (9.1) moyenne (9.14) ecart type (9.9) correlation (9.7)
Usage:
champ_post_statistiques_base str
Read str {
     t_deb float
     t_fin float
     [source champ_generique_base]
     [sources listchamp_generique]
      [ nom_source str]
     [ source_reference str]
     [ sources_reference list_nom_virgule]
}
where
   • t deb float: Start of integration time
   • t_fin float: End of integration time
   • source champ_generique_base (9) for inheritance: the source field.
   • sources listchamp generique (9.2) for inheritance: sources { Champ Post.... { ... } Champ Post...
   • nom_source str for inheritance: To name a source field with the nom_source keyword
   • source reference str for inheritance
```

9.7 Correlation

{ ... }}

```
Synonymous: champ_post_statistiques_correlation
Description: to calculate the correlation between the two fields.
See also: champ_post_statistiques_base (9.6)
Usage:
correlation str
Read str {
     t_deb float
     t fin float
     [ source champ_generique_base]
     [sources listchamp_generique]
     [ nom_source str]
     [ source_reference str]
     [sources_reference list_nom_virgule]
}
where
   • t_deb float for inheritance: Start of integration time
   • t_fin float for inheritance: End of integration time
   • source champ_generique_base (9) for inheritance: the source field.
   • sources listchamp_generique (9.2) for inheritance: sources { Champ_Post.... { ... } Champ_Post...
   • nom_source str for inheritance: To name a source field with the nom_source keyword
   • source reference str for inheritance
   • sources_reference list_nom_virgule (9.3) for inheritance
9.8
      Champ_post_operateur_divergence
Synonymous: divergence
Description: To calculate divergency of a given field.
See also: champ_post_operateur_base (9.4)
Usage:
champ_post_operateur_divergence str
Read str {
     [source champ_generique_base]
     [sources listchamp_generique]
     [ nom source str]
     [source reference str]
     [ sources_reference list_nom_virgule]
}
where
   • source champ_generique_base (9) for inheritance: the source field.
   • sources listchamp_generique (9.2) for inheritance: sources { Champ_Post... { ... } Champ_Post...
```

- nom_source str for inheritance: To name a source field with the nom_source keyword
- source_reference str for inheritance
- sources_reference list_nom_virgule (9.3) for inheritance

9.9 Ecart_type

```
Synonymous: champ_post_statistiques_ecart_type
Description: to calculate the standard deviation (statistic rms) of the field nom_champ.
See also: champ_post_statistiques_base (9.6)
Usage:
ecart_type str
Read str {
     t_deb float
     t_fin float
     [ source champ_generique_base]
     [sources listchamp_generique]
     [ nom_source str]
     [ source_reference str]
     [sources reference list nom virgule]
}
where
   • t_deb float for inheritance: Start of integration time
   • t fin float for inheritance: End of integration time
   • source champ_generique_base (9) for inheritance: the source field.
   • sources listchamp_generique (9.2) for inheritance: sources { Champ_Post... { ... } Champ_Post...
   • nom_source str for inheritance: To name a source field with the nom_source keyword
```

• source_reference str for inheritance

• sources_reference list_nom_virgule (9.3) for inheritance

[methode str into ['trace', 'champ_frontiere']]

[**source** champ_generique_base] [sources listchamp_generique]

[nom_source str]

```
9.10
       Champ_post_extraction
Synonymous: extraction
Description: To create a surface field (values at the boundary) of a volume field
See also: champ_post_de_champs_post (9.1)
Usage:
champ_post_extraction str
Read str {
     domaine str
     nom frontiere str
```

```
[ source_reference str]
    [ sources_reference list_nom_virgule]
}
where
```

- **domaine** *str*: name of the volume field
- nom_frontiere str: boundary name where the values of the volume field will be picked
- **methode** *str into ['trace', 'champ_frontiere']*: name of the extraction method (trace by_default or champ_frontiere)
- **source** *champ_generique_base* (9) for inheritance: the source field.
- **sources** *listchamp_generique* (9.2) for inheritance: sources { Champ_Post.... { ... } Champ_Post... { ... }}
- nom_source str for inheritance: To name a source field with the nom_source keyword
- source reference str for inheritance
- sources_reference list_nom_virgule (9.3) for inheritance

9.11 Champ_post_operateur_gradient

```
Synonymous: gradient
Description: To calculate gradient of a given field.
See also: champ post operateur base (9.4)
Usage:
champ_post_operateur_gradient str
Read str {
     [ source champ_generique_base]
     [sources listchamp generique]
     [ nom source str]
     [source reference str]
     [ sources_reference list_nom_virgule]
}
where
   • source champ generique base (9) for inheritance: the source field.
   • sources listchamp_generique (9.2) for inheritance: sources { Champ_Post.... { ... } Champ_Post...
   • nom_source str for inheritance: To name a source field with the nom_source keyword
   • source reference str for inheritance
   • sources_reference list_nom_virgule (9.3) for inheritance
```

9.12 Interpolation

Synonymous: champ_post_interpolation

Description: To create a field which is an interpolation of the field given by the keyword source.

```
See also: champ_post_de_champs_post (9.1)
Usage:
interpolation str
Read str {
```

```
localisation str
[ methode str]
[ domaine str]
[ optimisation_sous_maillage str into ['default', 'yes', 'no']]
[ source champ_generique_base]
[ sources listchamp_generique]
[ nom_source str]
[ source_reference str]
[ sources_reference list_nom_virgule]
}
where
```

- **localisation** *str*: type_loc indicate where is done the interpolation (elem for element or som for node).
- methode str: The optional keyword methode is limited to calculer_champ_post for the moment.
- domaine str: the domain name where the interpolation is done (by default, the calculation domain)
- optimisation_sous_maillage str into ['default', 'yes', 'no']
- source champ_generique_base (9) for inheritance: the source field.
- **sources** *listchamp_generique* (9.2) for inheritance: sources { Champ_Post... { ... } Champ_Post... { ... }}
- nom_source str for inheritance: To name a source field with the nom_source keyword
- source reference str for inheritance
- sources_reference list_nom_virgule (9.3) for inheritance

9.13 Champ_post_morceau_equation

Synonymous: morceau_equation

Description: To calculate a field related to a piece of equation. For the moment, the field which can be calculated is the stability time step of an operator equation. The problem name and the unknown of the equation should be given by Source refChamp { Pb_Champ problem_name unknown_field_of_equation }

```
See also: champ_post_de_champs_post (9.1)
Usage:
champ_post_morceau_equation str
Read str {
     type str
     [ numero int]
     [unite str]
     option str into ['stabilite', 'flux bords', 'flux surfacique bords']
     [compo int]
     [source champ generique base]
     [sources listchamp_generique]
     [ nom source str]
     [ source_reference str]
     [ sources_reference list_nom_virgule]
}
where
```

• type str: can only be operateur for equation operators.

- **numero** *int*: numero will be 0 (diffusive operator) or 1 (convective operator) or 2 (gradient operator) or 3 (divergence operator).
- unite str: will specify the field unit
- **option** *str into ['stabilite', 'flux_bords', 'flux_surfacique_bords']*: option is stability for time steps or flux_bords for boundary fluxes or flux_surfacique_bords for boundary surfacic fluxes
- **compo** *int*: compo will specify the number component of the boundary flux (for boundary fluxes, in this case compo permits to specify the number component of the boundary flux choosen).
- source champ generique base (9) for inheritance: the source field.
- **sources** *listchamp_generique* (9.2) for inheritance: sources { Champ_Post.... { ... } Champ_Post... { ... }}
- nom_source str for inheritance: To name a source field with the nom_source keyword
- source_reference str for inheritance
- sources_reference list_nom_virgule (9.3) for inheritance

9.14 Moyenne

```
Synonymous: champ post statistiques moyenne
```

Description: to calculate the average of the field over time

```
See also: champ_post_statistiques_base (9.6)
```

```
Usage:
moyenne str
Read str {

    [moyenne_convergee champ_base]
    t_deb float
    t_fin float
    [source champ_generique_base]
    [sources listchamp_generique]
    [nom_source str]
    [source_reference str]
    [sources_reference list_nom_virgule]
}
where
```

- moyenne_convergee champ_base (16.1): This option allows to read a converged time averaged field in a .xyz file in order to calculate, when resuming the calculation, the statistics fields (rms, correlation) which depend on this average. In that case, the time averaged field is not updated during the resume of calculation. In this case, the time averaged field must be fully converged to avoid errors when calculating high order statistics.
- t deb float for inheritance: Start of integration time
- t fin float for inheritance: End of integration time
- **source** *champ_generique_base* (9) for inheritance: the source field.
- **sources** *listchamp_generique* (9.2) for inheritance: sources { Champ_Post... { ... } Champ_Post... { ... }}
- nom_source str for inheritance: To name a source field with the nom_source keyword
- source_reference str for inheritance
- sources_reference list_nom_virgule (9.3) for inheritance

9.15 Predefini

Description: This keyword is used to post process predefined postprocessing fields.

```
See also: champ_generique_base (9)

Usage:
predefini str
Read str {
    pb_champ deuxmots
}
where
```

• **pb_champ** *deuxmots* (5.35): { Pb_champ nom_pb nom_champ } : nom_pb is the problem name and nom_champ is the selected field name. The available keywords for the field name are: energie_cinetique_totale, energie_cinetique_elem, viscosite_turbulente, viscous_force_x, viscous_force_y, viscous_force_z, pressure_force_x, pressure_force_y, pressure_force_z, total_force_x, total_force_y, total_force_z, viscous_force, pressure_force, total_force

9.16 Champ_post_reduction_0d

See also: champ_post_de_champs_post (9.1)

Synonymous: reduction_0d

Description: To calculate the min, max, sum, average, weighted sum, weighted average, weighted sum by porosity, weighted average by porosity, euclidian norm, normalized euclidian norm, L1 norm, L2 norm of a field.

```
Usage:
champ_post_reduction_0d str

Read str {

methode str into ['min', 'max', 'moyenne', 'average', 'moyenne_ponderee', 'weighted_average', 'somme', 'sum', 'somme_ponderee', 'weighted_sum', 'somme_ponderee_porosite', 'weighted_sum-_porosity', 'euclidian_norm', 'normalized_euclidian_norm', 'L1_norm', 'L2_norm', 'valeur_a_gauche', 'left_value']

[ source champ_generique_base]
[ sources listchamp_generique]
[ nom_source str]
```

- methode str into ['min', 'max', 'moyenne', 'average', 'moyenne_ponderee', 'weighted_average', 'somme', 'sum', 'somme_ponderee', 'weighted_sum', 'somme_ponderee_porosite', 'weighted_sum-porosity', 'euclidian_norm', 'normalized_euclidian_norm', 'L1_norm', 'L2_norm', 'valeur_a_gauche', 'left_value']: name of the reduction method:
 - min for the minimum value,

[source_reference str]

} where

[sources_reference list_nom_virgule]

- max for the maximum value,
- average (or moyenne) for a mean,

- weighted_average (or moyenne_ponderee) for a mean ponderated by integration volumes, e.g. cell volumes for temperature and pressure in VDF, volumes around faces for velocity and temperature in VEF,
- sum (or somme) for the sum of all the values of the field,
- weighted_sum (or somme_ponderee) for a weighted sum (integral),
- weighted_average_porosity (or moyenne_ponderee_porosite) and weighted_sum_porosity (or somme_ponderee_porosite) for the mean and sum weighted by the volumes of the elements, only for ELEM localisation,
- euclidian norm for the euclidian norm,
- normalized euclidian norm for the euclidian norm normalized,
- L1 norm for norm L1,
- L2_norm for norm L2
- **source** *champ_generique_base* (9) for inheritance: the source field.
- **sources** *listchamp_generique* (9.2) for inheritance: sources { Champ_Post.... { ... } Champ_Post... { ... }}
- nom_source str for inheritance: To name a source field with the nom_source keyword
- source_reference str for inheritance
- sources_reference list_nom_virgule (9.3) for inheritance

9.17 Champ_post_refchamp

```
Synonymous: refchamp

Description: Field of prolem

See also: champ_generique_base (9)

Usage:
champ_post_refchamp str

Read str {

    [nom_source str]
    pb_champ deuxmots
}

where
```

- nom source str: The alias name for the field
- **pb_champ** *deuxmots* (5.35): { Pb_champ nom_pb nom_champ } : nom_pb is the problem name and nom_champ is the selected field name.

9.18 Champ_post_tparoi_vef

Synonymous: tparoi_vef

Description: This keyword is used to post process (only for VEF discretization) the temperature field with a slight difference on boundaries with Neumann condition where law of the wall is applied on the temperature field. nom_pb is the problem name and field_name is the selected field name. A keyword (temperature_physique) is available to post process this field without using Definition_champs.

```
See also: champ_post_de_champs_post (9.1)
```

Usage:

```
champ_post_tparoi_vef str
Read str {
      [ source champ_generique_base]
      [ sources listchamp_generique]
      [ nom_source str]
      [ source_reference str]
      [ sources_reference list_nom_virgule]
}
where

• source champ_generique_base (9) for inheritance: the source field.
• sources listchamp_generique (9.2) for inheritance: sources { Champ_Post.... { ... } Champ_Post... { ... }}

• nom_source str for inheritance: To name a source field with the nom_source keyword
• source_reference str for inheritance
• sources_reference list_nom_virgule (9.3) for inheritance
```

9.19 Champ_post_transformation

Synonymous: transformation

Description: To create a field with a transformation using source fields and x, y, z, t. If you use in your datafile source refChamp { Pb_champ pb pression }, the field pression may be used in the expression with the name pression_natif_dom; this latter is the same as pression. If you specify nom_source in refChamp bloc, you should use the alias given to pressure field. This is avail for all equations unknowns in transformation.

```
See also: champ_post_de_champs_post (9.1)
Usage:
champ_post_transformation str
Read str {
     methode str into ['produit_scalaire', 'norme', 'vecteur', 'formule', 'composante']
     [unite str]
     [ expression n word1 word2 ... wordn]
     [ numero int]
     [localisation str]
     [source champ_generique_base]
     [sources listchamp_generique]
     [ nom source str]
     [ source_reference str]
     [ sources_reference list_nom_virgule]
}
where
```

• **methode** *str into ['produit_scalaire', 'norme', 'vecteur', 'formule', 'composante']*: methode 0 methode norme: will calculate the norm of a vector given by a source field methode produit_scalaire: will calculate the dot product of two vectors given by two sources fields methode composante numero integer: will create a field by extracting the integer component of a field given by a source field methode formule expression 1: will create a scalar field located to elements using expressions with

x,y,z,t parameters and field names given by a source field or several sources fields. methode vecteur expression N f1(x,y,z,t) fN(x,y,z,t): will create a vector field located to elements by defining its N components with N expressions with x,y,z,t parameters and field names given by a source field or several sources fields.

- unite str: will specify the field unit
- expression n word1 word2 ... wordn: expression 1 see methodes formule and vecteur
- **numero** *int*: numero 1 see methode composante
- **localisation** *str*: localisation 1 type_loc indicate where is done the interpolation (elem for element or som for node). The optional keyword methode is limited to calculer_champ_post for the moment
- **source** *champ_generique_base* (9) for inheritance: the source field.
- **sources** *listchamp_generique* (9.2) for inheritance: sources { Champ_Post.... { ... } Champ_Post... { ... }}
- nom_source str for inheritance: To name a source field with the nom_source keyword
- source reference str for inheritance
- sources_reference list_nom_virgule (9.3) for inheritance

10 chimie

Description: Keyword to describe the chmical reactions

```
See also: objet_u (40)

Usage:
chimie str
Read str {

reactions reactions
[modele_micro_melange int]
[constante_modele_micro_melange float]
[espece_en_competition_micro_melange str]
}
where
```

- reactions reactions (10.1): list of reactions
- modele_micro_melange int: modele_micro_melange (0 by default)
- constante_modele_micro_melange float: constante of modele (1 by default)
- espece_en_competition_micro_melange str: espece in competition in reactions

10.1 Reactions

```
Description: list of reactions

See also: listobj (38.5)

Usage:
{ object1 , object2 .... }
list of reaction (10.1.1) separeted with ,

10.1.1 Reaction
```

Description: Keyword to describe reaction: w =K pow(T,beta) exp(-Ea/(R T)) Π pow(Reactif_i,activitivity_i). If K_inv >0,

```
w= K pow(T,beta) exp(-Ea/( R T)) ( Π pow(Reactif_i,activitivity_i) - Kinv/exp(-c_r_Ea/(R T)) Π pow(Produit-
_i,activitivity_i ))
See also: objet_lecture (39)
Usage:
{
     reactifs str
     produits str
     [constante_taux_reaction float]
     enthalpie_reaction float
     energie_activation float
     exposant_beta float
     [coefficients_activites bloc_lecture]
     [contre_reaction float]
     [contre_energie_activation float]
}
where
   • reactifs str: LHS of equation (ex CH4+2*O2)
   • produits str: RHS of equation (ex CO2+2*H20)
   • constante taux reaction float: constante of cinetic K
   • enthalpie_reaction float: DH
   • energie_activation float: Ea
   • exposant_beta float: Beta
   • coefficients_activites bloc_lecture (3.59): coefficients od ativity (exemple { CH4 1 O2 2 })
   • contre_reaction float: K_inv
   • contre_energie_activation float: c_r_Ea
11
      class_generic
Description: not_set
See also: objet_u (40) solveur_sys_base (11.16) dt_start (11.7)
Usage:
11.1 Amg
Description: Wrapper for AMG preconditioner-based solver which switch for the best one on CPU/GPU
Nvidia/GPU AMD
See also: solveur_sys_base (11.16)
Usage:
amg solveur option_solveur
where
   • solveur str
   • option_solveur bloc_lecture (3.59)
```

```
11.2 Amgx
```

```
Description: Solver via AmgX API
See also: petsc (11.12)
Usage:
amgx solveur option_solveur
where
   • solveur str
   • option_solveur bloc_lecture (3.59)
11.3
      Cholesky
Description: Cholesky direct method.
See also: solveur_sys_base (11.16)
Usage:
cholesky str
Read str {
     [impr]
     [quiet]
}
where
   • impr : Keyword which may be used to print the resolution time.
   • quiet : To disable printing of information
11.4 Dt_calc
Description: The time step at first iteration is calculated in agreement with CFL condition.
See also: dt_start (11.7)
Usage:
dt_calc
11.5 Dt fixe
Description: The first time step is fixed by the user (recommended when resuming calculation with Crank
Nicholson temporal scheme to ensure continuity).
See also: dt_start (11.7)
Usage:
dt_fixe value
where
```

• value float: first time step.

11.6 Dt_min

```
Description: The first iteration is based on dt min.
See also: dt start (11.7)
Usage:
dt min
11.7 Dt start
Description: not_set
See also: class generic (11) dt calc (11.4) dt min (11.6) dt fixe (11.5)
Usage:
dt_start
11.8 Gcp_ns
Description: not_set
See also: gcp (11.15)
Usage:
gcp_ns str
Read str {
     solveur0 solveur_sys_base
     solveur1 solveur_sys_base
     seuil float
     [ nb_it_max int]
     [impr]
     [quiet]
     [ save_matrix|save_matrice ]
     [ precond precond_base]
     [precond nul]
     [ precond_diagonal ]
     [ optimized ]
where
```

- solveur0 solveur_sys_base (11.16): Solver type.
- solveur1 solveur sys base (11.16): Solver type.
- **seuil** *float* for inheritance: Value of the final residue. The gradient ceases iteration when the Euclidean residue standard ||Ax-B|| is less than this value.
- **nb_it_max** *int* for inheritance: Keyword to set the maximum iterations number for the Gcp.
- **impr** for inheritance: Keyword which is used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- quiet for inheritance: To not displaying any outputs of the solver.
- save_matrix|save_matrice for inheritance: to save the matrix in a file.
- **precond** *precond_base* (29) for inheritance: Keyword to define system preconditioning in order to accelerate resolution by the conjugated gradient. Many parallel preconditioning methods are not equivalent to their sequential counterpart, and you should therefore expect differences, especially

when you select a high value of the final residue (seuil). The result depends on the number of processors and on the mesh splitting. It is sometimes useful to run the solver with no preconditioning at all. In particular:

- when the solver does not converge during initial projection,
- when comparing sequential and parallel computations.

With no preconditioning, except in some particular cases (no open boundary), the sequential and the parallel computations should provide exactly the same results within fpu accuracy. If not, there might be a coding error or the system of equations is singular.

- **precond_nul** for inheritance: Keyword to not use a preconditioning method.
- precond_diagonal for inheritance: Keyword to use diagonal preconditioning.
- **optimized** for inheritance: This keyword triggers a memory and network optimized algorithms useful for strong scaling (when computing less than 100 000 elements per processor). The matrix and the vectors are duplicated, common items removed and only virtual items really used in the matrix are exchanged.

Warning: this is experimental and known to fail in some VEF computations (L2 projection step will not converge). Works well in VDF.

11.9 Gen

```
Description: not_set

See also: solveur_sys_base (11.16)

Usage:
gen str
Read str {

    solv_elem str
    precond precond_base
    [seuil float]
    [impr ]
    [save_matrix|save_matrice]
    [quiet ]
    [nb_it_max int]
    [force ]

}

where
```

- solv_elem str: To specify a solver among gmres or bicgstab.
- precond precond_base (29): The only preconditionner that we can specify is ilu.
- **seuil** *float*: Value of the final residue. The solver ceases iterations when the Euclidean residue standard ||Ax-B|| is less than this value. default value 1e-12.
- **impr**: Keyword which is used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- save matrix|save matrice: To save the matrix in a file.
- quiet: To not displaying any outputs of the solver.
- **nb_it_max** *int*: Keyword to set the maximum iterations number for the GEN solver.
- **force**: Keyword to set ipar[5]=-1 in the GEN solver. This is helpful if you notice that the solver does not perform more than 100 iterations. If this keyword is specified in the datafile, you should provide nb_it_max.

11.10 **Gmres**

```
Description: Gmres method (for non symetric matrix).
See also: solveur_sys_base (11.16)
Usage:
gmres str
Read str {
     [impr]
     [quiet]
     [seuil float]
     [diag]
     [ nb_it_max int]
     [ controle_residu int into [0, 1]]
     [ save_matrix|save_matrice ]
     [ dim_espace_krilov int]
}
where
   • impr : Keyword which may be used to print the convergence.
   • quiet : To disable printing of information
   • seuil float: Convergence value.
```

diag: Keyword to use diagonal preconditionner (in place of pilut that is not parallel).
nb_it_max int: Keyword to set the maximum iterations number for the Gmres.

- occurs if the residu suddenly increases.
- save_matrix|save_matrice : to save the matrix in a file.dim_espace_krilov int

11.11 Optimal

Description: Optimal is a solver which tests several solvers of the previous list to choose the fastest one for the considered linear system.

• controle_residu int into [0, 1]: Keyword of Boolean type (by default 0). If set to 1, the convergence

```
See also: solveur_sys_base (11.16)

Usage:
optimal str
Read str {

    seuil float
    [impr]
    [quiet]
    [save_matrix|save_matrice]
    [frequence_recalc int]
    [nom_fichier_solveur str]
    [fichier_solveur_non_recree]
}
where
```

• seuil *float*: Convergence threshold

- **impr**: To print the convergency of the fastest solver
- quiet : To disable printing of information
- save_matrix|save_matrice : To save the linear system (A, x, B) into a file
- frequence_recalc int: To set a time step period (by default, 100) for re-checking the fatest solver
- nom_fichier_solveur str: To specify the file containing the list of the tested solvers
- fichier_solveur_non_recree : To avoid the creation of the file containing the list

11.12 **Petsc**

Description: Solver via Petsc API

See also: solveur_sys_base (11.16) amgx (11.2) petsc_gpu (11.13) rocalution (11.14)

Usage:
petsc_solveur
where

• solveur solveur_petsc_deriv (33): solver type and options

11.13 Petsc_gpu

Description: GPU solver via Petsc API

See also: petsc (11.12)

Usage:

petsc_gpu solveur option_solveur [atol] [rtol]
where

- solveur str
- option_solveur bloc_lecture (3.59)
- atol float: Absolute threshold for convergence (same as seuil option)
- rtol float: Relative threshold for convergence

11.14 Rocalution

Description: Solver via rocALUTION API

See also: petsc (11.12)

Usage:

rocalution solveur option_solveur where

- solveur str
- option_solveur bloc_lecture (3.59)

11.15 Gcp

Description: Preconditioned conjugated gradient.

```
See also: solveur_sys_base (11.16) gcp_ns (11.8)

Usage:
gcp str

Read str {

    seuil float
    [nb_it_max int]
    [impr ]
    [quiet ]
    [save_matrix|save_matrice ]
    [precond_precond_base]
    [precond_diagonal ]
    [optimized ]
}

where
```

- **seuil** *float*: Value of the final residue. The gradient ceases iteration when the Euclidean residue standard ||Ax-B|| is less than this value.
- **nb_it_max** *int*: Keyword to set the maximum iterations number for the Gcp.
- **impr**: Keyword which is used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- quiet: To not displaying any outputs of the solver.
- save_matrixlsave_matrice : to save the matrix in a file.
- **precond** *precond_base* (29): Keyword to define system preconditioning in order to accelerate resolution by the conjugated gradient. Many parallel preconditioning methods are not equivalent to their sequential counterpart, and you should therefore expect differences, especially when you select a high value of the final residue (seuil). The result depends on the number of processors and on the mesh splitting. It is sometimes useful to run the solver with no preconditioning at all. In particular:
 - when the solver does not converge during initial projection,
 - when comparing sequential and parallel computations.

With no preconditioning, except in some particular cases (no open boundary), the sequential and the parallel computations should provide exactly the same results within fpu accuracy. If not, there might be a coding error or the system of equations is singular.

- **precond_nul**: Keyword to not use a preconditioning method.
- **precond_diagonal**: Keyword to use diagonal preconditioning.
- **optimized**: This keyword triggers a memory and network optimized algorithms useful for strong scaling (when computing less than 100 000 elements per processor). The matrix and the vectors are duplicated, common items removed and only virtual items really used in the matrix are exchanged. Warning: this is experimental and known to fail in some VEF computations (L2 projection step will not converge). Works well in VDF.

11.16 Solveur_sys_base

Description: Basic class to solve the linear system.

```
See also: class_generic (11) gen (11.9) petsc (11.12) gcp (11.15) optimal (11.11) cholesky (11.3) gmres (11.10) amg (11.1)
```

Usage:

12

12.1

```
Description: Comments in a data file.

See also: objet_u (40)

Usage:
# comm
where
```

• comm str: Text to be commented.

13 condlim_base

Description: Basic class of boundary conditions.

See also: objet_u (40) Paroi_echange_interne_global_impose (13.2) Paroi_echange_interne_global_parfait (13.3) paroi_echange_global_impose (13.39) neumann (13.28) paroi_echange_contact_vdf (13.36) paroi_echange_contact_correlation_vdf (13.34) Paroi_echange_interne_parfait (13.5) Paroi_echange_interne_impose (13.4) paroi_decalee_robin (13.32) dirichlet (13.10) paroi_echange_externe_impose (13.37) paroi_fixe (13.40) Paroi (13.9) Neumann_homogene (13.6) paroi_echange_contact_correlation_vef (13.35) periodique (13.45) paroi_echange_externe_radiatif (13.11) paroi_adiabatique (13.29) paroi_contact (13.30) frontiere_ouverte_fraction_massique_impose (13.16) paroi_contact_fictif (13.31) Neumann_paroi (13.7) symetrie (13.48) paroi_flux_impose (13.42)

Usage: condlim_base

13.1 Echange_couplage_thermique

```
Description: Thermal coupling boundary condition

See also: paroi_echange_global_impose (13.39)

Usage:

Echange_couplage_thermique str

Read str {

    [temperature_paroi champ_base]
    [flux_paroi champ_base]
}

where

• temperature_paroi champ_base (16.1): Temperature
```

13.2 Paroi_echange_interne_global_impose

• flux paroi champ base (16.1): Wall heat flux

Description: Internal heat exchange boundary condition with global exchange coefficient.

```
See also: condlim base (13)
```

Usage:

Paroi_echange_interne_global_impose h_imp ch where

- **h_imp** *str*: Global exchange coefficient value. The global exchange coefficient value is expressed in W.m-2.K-1.
- **ch** *champ_front_base* (17.1): Boundary field type.

13.3 Paroi_echange_interne_global_parfait

Description: Internal heat exchange boundary condition with perfect (infinite) exchange coefficient.

See also: condlim_base (13)

Usage:

Paroi_echange_interne_global_parfait

13.4 Paroi_echange_interne_impose

Description: Internal heat exchange boundary condition with exchange coefficient.

See also: condlim_base (13)

Usage:

Paroi_echange_interne_impose h_imp ch where

- **h_imp** *str*: Exchange coefficient value expressed in W.m-2.K-1.
- ch champ_front_base (17.1): Boundary field type.

13.5 Paroi_echange_interne_parfait

Description: Internal heat exchange boundary condition with perfect (infinite) exchange coefficient.

See also: condlim_base (13)

Usage:

Paroi_echange_interne_parfait

13.6 Neumann_homogene

Description: Homogeneous neumann boundary condition

See also: condlim_base (13) Neumann_paroi_adiabatique (13.8)

Usage:

Neumann_homogene

13.7 Neumann_paroi

Description: Neumann boundary condition for mass equation (multiphase problem)

See also: condlim base (13)

Usage:

Neumann_paroi ch

where

• **ch** champ front base (17.1): Boundary field type.

13.8 Neumann paroi adiabatique

Description: Adiabatic wall neumann boundary condition

See also: Neumann_homogene (13.6)

Usage:

Neumann_paroi_adiabatique

13.9 Paroi

Description: Impermeability condition at a wall called bord (edge) (standard flux zero). This condition must be associated with a wall type hydraulic condition.

See also: condlim_base (13)

Usage:

Paroi

13.10 Dirichlet

Description: Dirichlet condition at the boundary called bord (edge): 1). For Navier-Stokes equations, velocity imposed at the boundary; 2). For scalar transport equation, scalar imposed at the boundary.

See also: condlim_base (13) frontiere_ouverte_vitesse_imposee (13.26) frontiere_ouverte_enthalpie_imposee (13.25) paroi_knudsen_non_negligeable (13.43) paroi_temperature_imposee (13.44) frontiere_ouverte_concentration_imposee (13.15) frontiere_ouverte_alpha_impose (13.14) paroi_defilante (13.33) scalaire_impose_paroi (13.46)

Usage:

dirichlet

13.11 Paroi echange externe radiatif

Synonymous: echange_externe_radiatif

Description: Combines radiative $(sigma * eps * (T^4 - T_ext^4))$ and convective $(h * (T - T_ext))$ heat transfer boundary conditions, where sigma is the Stefan-Boltzmann constant, eps is the emi

See also: condlim_base (13)

Usage:

paroi_echange_externe_radiatif h_imp himpc emissivite emissivitebc t_ext ch temp_unit temp_unit_val

where

- **h_imp** *str into ['h_imp', 't_ext', 'emissivite']*: Heat exchange coefficient value (expressed in W.m-2.K-1).
- himpc champ_front_base (17.1): Boundary field type.
- emissivite str into ['emissivite', 'h_imp', 't_ext']: Emissivity coefficient value.
- emissivitebc *champ_front_base* (17.1): Boundary field type.
- t_ext str into ['t_ext', 'h_imp', 'emissivite']: External temperature value (expressed in oC or K).
- ch champ_front_base (17.1): Boundary field type.
- **temp_unit** *str into* ['temperature_unit']: Temperature unit
- temp_unit_val str into ['kelvin', 'celsius']: Temperature unit

13.12 Entree_temperature_imposee_h

Description: Particular case of class frontiere_ouverte_temperature_imposee for enthalpy equation.

See also: frontiere_ouverte_enthalpie_imposee (13.25)

Usage:

entree_temperature_imposee_h ch
where

• ch champ_front_base (17.1): Boundary field type.

13.13 Frontiere_ouverte

Description: Boundary outlet condition on the boundary called bord (edge) (diffusion flux zero). This condition must be associated with a boundary outlet hydraulic condition.

See also: neumann (13.28)

Usage:

frontiere_ouverte var_name ch where

- var_name str into ['T_ext', 'C_ext', 'Y_ext', 'K_Eps_ext', 'K_Omega_ext', 'Fluctu_Temperature_ext', 'Flux_Chaleur_Turb_ext', 'V2_ext', 'a_ext', 'tau_ext', 'k_ext', 'omega_ext', 'H_ext']: Field name.
- **ch** *champ_front_base* (17.1): Boundary field type.

13.14 Frontiere_ouverte_alpha_impose

Description: Imposed alpha condition at the open boundary.

See also: dirichlet (13.10)

Usage:

frontiere_ouverte_alpha_impose ch where

• **ch** *champ_front_base* (17.1): Boundary field type.

13.15 Frontiere_ouverte_concentration_imposee

Description: Imposed concentration condition at an open boundary called bord (edge) (situation corresponding to a fluid inlet). This condition must be associated with an imposed inlet velocity condition.

See also: dirichlet (13.10)

Usage:

frontiere_ouverte_concentration_imposee ch where

• **ch** *champ_front_base* (17.1): Boundary field type.

13.16 Frontiere_ouverte_fraction_massique_imposee

Description: not_set

See also: condlim base (13)

Usage:

 $\label{lem:continuous} \textbf{frontiere_ouverte_fraction_massique_imposee} \quad \textbf{ch} \\ \text{where} \\$

• **ch** *champ_front_base* (17.1): Boundary field type.

13.17 Frontiere_ouverte_gradient_pression_impose

Description: Normal imposed pressure gradient condition on the open boundary called bord (edge). This boundary condition may be only used in VDF discretization. The imposed $\partial P/\partial n$ value is expressed in Pa.m-1.

See also: neumann (13.28) frontiere_ouverte_gradient_pression_impose_vefprep1b (13.18)

Usage:

frontiere_ouverte_gradient_pression_impose ch where

• **ch** *champ_front_base* (17.1): Boundary field type.

13.18 Frontiere_ouverte_gradient_pression_impose_vefprep1b

Description: Keyword for an outlet boundary condition in VEF P1B/P1NC on the gradient of the pressure.

See also: frontiere_ouverte_gradient_pression_impose (13.17)

Usage:

 $frontiere_ouverte_gradient_pression_impose_vefprep1b \quad ch \\$ where

• **ch** *champ_front_base* (17.1): Boundary field type.

13.19 Frontiere_ouverte_gradient_pression_libre_vef

Description: Class for outlet boundary condition in VEF like Orlansky. There is no reference for pressure for theses boundary conditions so it is better to add pressure condition (with Frontiere_ouverte_pression_imposee) on one or two cells (for symmetry in a channel) of the boundary where Orlansky conditions are imposed.

See also: neumann (13.28)

Usage:

 $frontiere_ouverte_gradient_pression_libre_vef$

13.20 Frontiere_ouverte_gradient_pression_libre_vefprep1b

Description: Class for outlet boundary condition in VEF P1B/P1NC like Orlansky.

See also: neumann (13.28)

Usage:

frontiere_ouverte_gradient_pression_libre_vefprep1b

13.21 Frontiere_ouverte_pression_imposee

Description: Imposed pressure condition at the open boundary called bord (edge). The imposed pressure field is expressed in Pa.

See also: neumann (13.28)

Usage:

frontiere_ouverte_pression_imposee ch

where

• **ch** *champ_front_base* (17.1): Boundary field type.

13.22 Frontiere_ouverte_pression_imposee_orlansky

Description: This boundary condition may only be used with VDF discretization. There is no reference for pressure for this boundary condition so it is better to add pressure condition (with Frontiere_ouverte_pression_imposee) on one or two cells (for symetry in a channel) of the boundary where Orlansky conditions are imposed.

See also: neumann (13.28)

Usage:

frontiere_ouverte_pression_imposee_orlansky

13.23 Frontiere_ouverte_pression_moyenne_imposee

Description: Class for open boundary with pressure mean level imposed.

See also: neumann (13.28)

Usage:

frontiere ouverte pression movenne imposee pext

where

• pext *float*: Mean pressure.

13.24 Frontiere_ouverte_rho_u_impose

Description: This keyword is used to designate a condition of imposed mass rate at an open boundary called bord (edge). The imposed mass rate field at the inlet is vectorial and the imposed velocity values are expressed in kg.s-1. This boundary condition can be used only with the Quasi compressible model.

See also: frontiere_ouverte_vitesse_imposee_sortie (13.27)

Usage:

frontiere_ouverte_rho_u_impose ch where

• **ch** *champ_front_base* (17.1): Boundary field type.

13.25 Frontiere_ouverte_enthalpie_imposee

Synonymous: frontiere_ouverte_temperature_imposee

Description: Imposed temperature condition at the open boundary called bord (edge) (in the case of fluid inlet). This condition must be associated with an imposed inlet velocity condition. The imposed temperature value is expressed in oC or K.

See also: dirichlet (13.10) entree_temperature_imposee_h (13.12)

Usage:

frontiere_ouverte_enthalpie_imposee ch where

• **ch** *champ_front_base* (17.1): Boundary field type.

13.26 Frontiere_ouverte_vitesse_imposee

Description: Class for velocity-inlet boundary condition. The imposed velocity field at the inlet is vectorial and the imposed velocity values are expressed in m.s-1.

See also: dirichlet (13.10) frontiere_ouverte_vitesse_imposee_sortie (13.27)

Usage:

frontiere_ouverte_vitesse_imposee ch where

• **ch** *champ_front_base* (17.1): Boundary field type.

13.27 Frontiere_ouverte_vitesse_imposee_sortie

Description: Sub-class for velocity boundary condition. The imposed velocity field at the open boundary is vectorial and the imposed velocity values are expressed in m.s-1.

See also: frontiere_ouverte_vitesse_imposee (13.26) frontiere_ouverte_rho_u_impose (13.24)

Usage:

frontiere_ouverte_vitesse_imposee_sortie ch where

• **ch** *champ_front_base* (17.1): Boundary field type.

13.28 Neumann

Description: Neumann condition at the boundary called bord (edge): 1). For Navier-Stokes equations, constraint imposed at the boundary; 2). For scalar transport equation, flux imposed at the boundary.

See also: condlim_base (13) frontiere_ouverte_pression_imposee_orlansky (13.22) frontiere_ouverte_gradientpression_impose (13.17) sortie_libre_temperature_imposee_h (13.47) frontiere_ouverte_pression_imposee (13.21) frontiere_ouverte (13.13) frontiere_ouverte_pression_moyenne_imposee (13.23) frontiere_ouvertegradient_pression_libre_vefprep1b (13.20) frontiere_ouverte_gradient_pression_libre_vef (13.19)

Usage:

neumann

13.29 Paroi_adiabatique

Description: Normal zero flux condition at the wall called bord (edge).

See also: condlim_base (13)

Usage:

paroi_adiabatique

13.30 Paroi_contact

Description: Thermal condition between two domains. Important: the name of the boundaries in the two domains should be the same. (Warning: there is also an old limitation not yet fixed on the sequential algorithm in VDF to detect the matching faces on the two boundaries: faces should be ordered in the same way). The kind of condition depends on the discretization. In VDF, it is a heat exchange condition, and in VEF, a temperature condition.

Such a coupling requires coincident meshes for the moment. In case of non-coincident meshes, run is stopped and two external files are automatically generated in VEF (connectivity_failed_boundary_name and connectivity_failed_pb_name.med). In 2D, the keyword Decouper_bord_coincident associated to the connectivity_failed_boundary_name file allows to generate a new coincident mesh.

In 3D, for a first preliminary cut domain with HOMARD (fluid for instance), the second problem associated to pb_name (solide in a fluid/solid coupling problem) has to be submitted to HOMARD cutting procedure with connectivity_failed_pb_name.med.

Such a procedure works as while the primary refined mesh (fluid in our example) impacts the fluid/solid interface with a compact shape as described below (values 2 or 4 indicates the number of division from primary faces obtained in fluid domain at the interface after HOMARD cutting):

2-2-2-2-2

2-4-4-4-4-2 2-2-2

```
2-4-4-4-4-2 2-4-2
2-2-2-2-2 2-2
OK

2-2 2-2-2
2-4-2 2-2
2-4-2 2-2
NOT OK

See also: condlim_base (13)

Usage:
paroi_contact autrepb nameb
where
```

- autrepb str: Name of other problem.
- nameb str: boundary name of the remote problem which should be the same than the local name

13.31 Paroi_contact_fictif

Description: This keyword is derivated from paroi_contact and is especially dedicated to compute coupled fluid/solid/fluid problem in case of thin material. Thanks to this option, solid is considered as a fictitious media (no mesh, no domain associated), and coupling is performed by considering instantaneous thermal equilibrium in it (for the moment).

```
See also: condlim_base (13)

Usage:
paroi_contact_fictif autrepb nameb conduct_fictif ep_fictive
where
```

- autrepb str: Name of other problem.
- nameb str: Name of bord.
- **conduct_fictif** *float*: thermal conductivity
- ep_fictive float: thickness of the fictitious media

13.32 Paroi_decalee_robin

Description: This keyword is used to designate a Robin boundary condition (a.u+b.du/dn=c) associated with the Pironneau methodology for the wall laws. The value of given by the delta option is the distance between the mesh (where symmetry boundary condition is applied) and the fictious wall. This boundary condition needs the definition of the dedicated source terms (Source_Robin_or Source_Robin_Scalaire) according the equations used.

```
See also: condlim_base (13)

Usage:
paroi_decalee_robin str

Read str {
    delta float
}
where
```

• delta float

13.33 Paroi_defilante

Description: Keyword to designate a condition where tangential velocity is imposed on the wall called bord (edge). If the velocity components set by the user is not tangential, projection is used.

```
See also: dirichlet (13.10)

Usage:
paroi_defilante ch
where

• ch champ_front_base (17.1): Boundary field type.
```

13.34 Paroi_echange_contact_correlation_vdf

Description: Class to define a thermohydraulic 1D model which will apply to a boundary of 2D or 3D domain.

Warning: For parallel calculation, the only possible partition will be according the axis of the model with the keyword Tranche.

```
See also: condlim_base (13)
paroi_echange_contact_correlation_vdf str
Read str {
      [dir int]
      [tinf float]
      [tsup float]
      [lambda str]
      [ rho str]
      [ dt_impr float]
      [cp float]
      \begin{bmatrix} \mathbf{mu} & str \end{bmatrix}
      [ debit float]
      [ dh float]
      [ volume str]
      [ nu str]
      [reprise correlation]
}
where
```

- dir int: Direction (0 : axis X, 1 : axis Y, 2 : axis Z) of the 1D model.
- **tinf** *float*: Inlet fluid temperature of the 1D model (oC or K).
- **tsup** *float*: Outlet fluid temperature of the 1D model (oC or K).
- **lambda** str: Thermal conductivity of the fluid (W.m-1.K-1).
- **rho** str: Mass density of the fluid (kg.m-3) which may be a function of the temperature T.
- **dt_impr** *float*: Printing period in name_of_data_file_time.dat files of the 1D model results.
- cp float: Calorific capacity value at a constant pressure of the fluid (J.kg-1.K-1).
- mu str: Dynamic viscosity of the fluid (kg.m-1.s-1) which may be a function of the temperature T.

- debit float: Surface flow rate (kg.s-1.m-2) of the fluid into the channel.
- **dh** *float*: Hydraulic diameter may be a function f(x) with x position along the 1D axis (xinf <= x <= xsup)
- **volume** *str*: Exact volume of the 1D domain (m3) which may be a function of the hydraulic diameter (Dh) and the lateral surface (S) of the meshed boundary.
- **nu** *str*: Nusselt number which may be a function of the Reynolds number (Re) and the Prandtl number (Pr).
- reprise_correlation : Keyword in the case of a resuming calculation with this correlation.

13.35 Paroi_echange_contact_correlation_vef

Description: Class to define a thermohydraulic 1D model which will apply to a boundary of 2D or 3D domain.

Warning: For parallel calculation, the only possible partition will be according the axis of the model with the keyword Tranche_geom.

```
See also: condlim base (13)
Usage:
paroi_echange_contact_correlation_vef str
Read str {
      [dir int]
      [tinf float]
      [tsup float]
      [lambda str]
      [ rho str]
      [ dt_impr float]
      [ cp float]
      [ mu str]
      [ debit float]
      [ n int]
      [dh str]
      [surface str]
      [ xinf float]
      [xsup float]
      \begin{bmatrix} \mathbf{nu} & str \end{bmatrix}
      [ emissivite_pour_rayonnement_entre_deux_plaques_quasi_infinies float]
      [reprise_correlation]
}
where
```

- dir int: Direction (0 : axis X, 1 : axis Y, 2 : axis Z) of the 1D model.
- **tinf** *float*: Inlet fluid temperature of the 1D model (oC or K).
- **tsup** *float*: Outlet fluid temperature of the 1D model (oC or K).
- **lambda** *str*: Thermal conductivity of the fluid (W.m-1.K-1).
- **rho** *str*: Mass density of the fluid (kg.m-3) which may be a function of the temperature T.
- **dt_impr** *float*: Printing period in name_of_data_file_time.dat files of the 1D model results.
- cp float: Calorific capacity value at a constant pressure of the fluid (J.kg-1.K-1).
- mu str: Dynamic viscosity of the fluid (kg.m-1.s-1) which may be a function of the temperature T.
- **debit** *float*: Surface flow rate (kg.s-1.m-2) of the fluid into the channel.
- **n** int: Number of 1D cells of the 1D mesh.

- **dh** *str*: Hydraulic diameter may be a function f(x) with x position along the 1D axis (xinf <= x <= xsup)
- surface str: Section surface of the channel which may be function f(Dh,x) of the hydraulic diameter (Dh) and x position along the 1D axis (xinf $\leq x \leq x$ xsup)
- xinf float: Position of the inlet of the 1D mesh on the axis direction.
- xsup float: Position of the outlet of the 1D mesh on the axis direction.
- **nu** *str*: Nusselt number which may be a function of the Reynolds number (Re) and the Prandtl number (Pr).
- emissivite_pour_rayonnement_entre_deux_plaques_quasi_infinies float: Coefficient of emissivity for radiation between two quasi infinite plates.
- reprise_correlation : Keyword in the case of a resuming calculation with this correlation.

13.36 Paroi_echange_contact_vdf

Description: Boundary condition type to model the heat flux between two problems. Important: the name of the boundaries in the two problems should be the same.

See also: condlim_base (13)

Usage:

paroi_echange_contact_vdf autrepb nameb temp h
where

- autrepb str: Name of other problem.
- nameb str: Name of bord.
- temp str: Name of field.
- **h** *float*: Value assigned to a coefficient (expressed in W.K-1m-2) that characterises the contact between the two mediums. In order to model perfect contact, h must be taken to be infinite. This value must obviously be the same in both the two problems blocks.

The surface thermal flux exchanged between the two mediums is represented by:

fi = h (T1-T2) where $1/h = d1/lambda1 + 1/val_h_contact + d2/lambda2$

where di: distance between the node where Ti and the wall is found.

13.37 Paroi_echange_externe_impose

Description: External type exchange condition with a heat exchange coefficient and an imposed external temperature.

See also: condlim_base (13) paroi_echange_externe_impose_h (13.38)

Usage:

paroi_echange_externe_impose h_or_t himpc t_or_h ch where

- h_or_t str into ['h_imp', 't_ext']: Heat exchange coefficient value (expressed in W.m-2.K-1).
- himpc champ_front_base (17.1): Boundary field type.
- t_or_h str into ['t_ext', 'h_imp']: External temperature value (expressed in oC or K).
- ch champ_front_base (17.1): Boundary field type.

13.38 Paroi_echange_externe_impose_h

Description: Particular case of class paroi_echange_externe_impose for enthalpy equation.

See also: paroi_echange_externe_impose (13.37)

Usage:

 $paroi_echange_externe_impose_h \ h_or_t \ himpc \ t_or_h \ ch$ where

- h_or_t str into ['h_imp', 't_ext']: Heat exchange coefficient value (expressed in W.m-2.K-1).
- himpc champ_front_base (17.1): Boundary field type.
- t_or_h str into ['t_ext', 'h_imp']: External temperature value (expressed in oC or K).
- ch champ_front_base (17.1): Boundary field type.

13.39 Paroi_echange_global_impose

Description: Global type exchange condition (internal) that is to say that diffusion on the first fluid mesh is not taken into consideration.

See also: condlim_base (13) Echange_couplage_thermique (13.1)

Usage:

paroi_echange_global_impose h_imp himpc text ch where

- **h_imp** *str*: Global exchange coefficient value. The global exchange coefficient value is expressed in W.m-2.K-1.
- himpc champ_front_base (17.1): Boundary field type.
- text str: External temperature value. The external temperature value is expressed in oC or K.
- ch champ front base (17.1): Boundary field type.

13.40 Paroi_fixe

Description: Keyword to designate a situation of adherence to the wall called bord (edge) (normal and tangential velocity at the edge is zero).

See also: condlim_base (13) paroi_fixe_iso_Genepi2_sans_contribution_aux_vitesses_sommets (13.41)

Usage:

paroi_fixe

13.41 Paroi fixe iso genepi2 sans contribution aux vitesses sommets

Description: Boundary condition to obtain iso Geneppi2, without interest

See also: paroi_fixe (13.40)

Usage:

paroi_fixe_iso_Genepi2_sans_contribution_aux_vitesses_sommets

13.42 Paroi_flux_impose

Description: Normal flux condition at the wall called bord (edge). The surface area of the flux (W.m-1 in 2D or W.m-2 in 3D) is imposed at the boundary according to the following convention: a positive flux is a flux that enters into the domain according to convention.

See also: condlim_base (13)

Usage:
paroi_flux_impose ch
where

• ch champ_front_base (17.1): Boundary field type.

13.43 Paroi_knudsen_non_negligeable

Description: Boundary condition for number of Knudsen (Kn) above 0.001 where slip-flow condition appears: the velocity near the wall depends on the shear stress: Kn=l/L with l is the mean-free-path of the molecules and L a characteristic length scale.

U(y=0)-Uwall=k(dU/dY)

Where k is a coefficient given by several laws:

Mawxell: k=(2-s)*l/s

Bestok&Karniadakis:k=(2-s)/s*L*Kn/(1+Kn)

Xue&Fan : k=(2-s)/s*L*tanh(Kn)

s is a value between 0 and 2 named accommodation coefficient. s=1 seems a good value.

Warning: The keyword is available for VDF calculation only for the moment.

See also: dirichlet (13.10)

Usage:

paroi_knudsen_non_negligeable name_champ_1 champ_1 name_champ_2 champ_2
where

- name_champ_1 str into ['vitesse_paroi', 'k']: Field name.
- **champ_1** *champ_front_base* (17.1): Boundary field type.
- name_champ_2 str into ['vitesse_paroi', 'k']: Field name.
- champ_front_base (17.1): Boundary field type.

13.44 Paroi temperature imposee

Description: Imposed temperature condition at the wall called bord (edge).

See also: dirichlet (13.10) enthalpie_imposee_paroi (13.49)

Usage:

paroi_temperature_imposee ch where

• ch champ_front_base (17.1): Boundary field type.

13.45 Periodique

Description: 1). For Navier-Stokes equations, this keyword is used to indicate that the horizontal inlet velocity values are the same as the outlet velocity values, at every moment. As regards meshing, the inlet and outlet edges bear the same name.; 2). For scalar transport equation, this keyword is used to set a periodic condition on scalar. The two edges dealing with this periodic condition bear the same name.

See also: condlim_base (13)
Usage:
periodique

13.46 Scalaire_impose_paroi

Description: Imposed temperature condition at the wall called bord (edge).

See also: dirichlet (13.10)

Usage:

scalaire_impose_paroi ch where

• ch champ_front_base (17.1): Boundary field type.

13.47 Sortie_libre_temperature_imposee_h

Description: Open boundary for heat equation with enthalpy as unknown.

See also: neumann (13.28)

Usage:

sortie_libre_temperature_imposee_h ch
where

• **ch** *champ_front_base* (17.1): Boundary field type.

13.48 Symetrie

Description: 1). For Navier-Stokes equations, this keyword is used to designate a symmetry condition concerning the velocity at the boundary called bord (edge) (normal velocity at the edge equal to zero and tangential velocity gradient at the edge equal to zero); 2). For scalar transport equation, this keyword is used to set a symmetry condition on scalar on the boundary named bord (edge).

See also: condlim_base (13)

Usage: **symetrie**

13.49 Enthalpie_imposee_paroi

Synonymous: temperature_imposee_paroi

Description: Imposed temperature condition at the wall called bord (edge).

```
See also: paroi_temperature_imposee (13.44)
Usage:
enthalpie_imposee_paroi ch
where
   • ch champ_front_base (17.1): Boundary field type.
      discretisation_base
14
Description: Basic class for space discretization of thermohydraulic turbulent problems.
See also: objet_u (40) vdf (14.8) polymac (14.5) polymac_P0P1NC (14.6) polymac_p0 (14.7) DG (14.1)
vef (14.9) ijk (14.4) EF_axi (14.2) ef (14.3)
Usage:
14.1 Dg
Description: DG discretization
See also: discretisation_base (14)
Usage:
14.2 Ef_axi
Description: Element Finite discretization.
See also: discretisation_base (14)
Usage:
14.3 Ef
Description: Element Finite discretization.
See also: discretisation_base (14)
Usage:
14.4 Ijk
Description: IJK discretization.
See also: discretisation_base (14)
Usage:
```

14.5 Polymac

Description: polymac discretization (polymac discretization that is not compatible with pb_multi).

```
See also: discretisation_base (14)
```

Usage:

14.6 Polymac_p0p1nc

Description: polymac_P0P1NC discretization (previously polymac discretization compatible with pb_multi).

```
See also: discretisation_base (14)
```

Usage:

14.7 Polymac_p0

Description: polymac_p0 discretization (previously covimac discretization compatible with pb_multi).

```
See also: discretisation_base (14)
```

Usage:

14.8 Vdf

Description: Finite difference volume discretization.

```
See also: discretisation base (14)
```

Usage:

14.9 Vef

Synonymous: vefprep1b

Description: Finite element volume discretization (P1NC/P1-bubble element). Since the 1.5.5 version, several new discretizations are available thanks to the optional keyword Read. By default, the VEFPreP1B keyword is equivalent to the former VEFPreP1B formulation (v1.5.4 and sooner). P0P1 (if used with the strong formulation for imposed pressure boundary) is equivalent to VEFPreP1B but the convergence is slower. VEFPreP1B dis is equivalent to VEFPreP1B dis Read dis { P0 P1 Changement_de_base_P1Bulle 1 Cl_pression_sommet_faible 0 }

```
See also: discretisation_base (14)

Usage:
vef str
Read str {

    [ changement_de_base_p1bulle int into [0, 1]]
    [ p0  ]
    [ p1  ]
    [ pa  ]
    [ rt  ]
```

[modif_div_face_dirichlet int into [0, 1]]

```
[ cl_pression_sommet_faible int into [0, 1]] } where
```

- **changement_de_base_p1bulle** *int into* [0, 1]: **changement_de_base_p1bulle** 1 This option may be used to have the P1NC/P0P1 formulation (value set to 0) or the P1NC/P1Bulle formulation (value set to 1, the default).
- **p0**: Pressure nodes are added on element centres
- p1 : Pressure nodes are added on vertices
- pa : Only available in 3D, pressure nodes are added on bones
- rt : For P1NCP1B (in TrioCFD)
- modif_div_face_dirichlet int into [0, 1]: This option (by default 0) is used to extend control volumes for the momentum equation.
- cl_pression_sommet_faible int into [0, 1]: This option is used to specify a strong formulation (value set to 0, the default) or a weak formulation (value set to 1) for an imposed pressure boundary condition. The first formulation converges quicker and is stable in general cases. The second formulation should be used if there are several outlet boundaries with Neumann condition (see Ecoulement_Neumann test case for example).

15 domaine

```
Description: Keyword to create a domain.
```

```
See also: objet_u (40) DomaineAxi1d (15.1) IJK_Grid_Geometry (15.2)
```

Usage:

Usage:

15.1 Domaineaxi1d

```
Description: 1D domain
See also: domaine (15)
```

15.2 Ijk_grid_geometry

Description: Object to define the grid that will represent the domain of the simulation in IJK discretization

```
See also: domaine (15)

Usage:

IJK_Grid_Geometry str

Read str {

    [ perio_i ]
    [ perio_j ]
    [ perio_k ]
    [ nbelem_i int]
    [ nbelem_j int]
    [ nbelem_k int]
    [ uniform_domain_size_i float]
```

[uniform_domain_size_j float]

```
[uniform_domain_size_k float]
     [ origin_i float]
     [ origin_j float]
     [ origin_k float]
}
where
   • perio i : rien to specify the border along the I direction is periodic
   • perio_j: rien to specify the border along the J direction is periodic
   • perio k: rien to specify the border along the K direction is periodic
   • nbelem_i int: the number of elements of the grid in the I direction
   • nbelem_j int: the number of elements of the grid in the J direction
   • nbelem_k int: the number of elements of the grid in the K direction
   • uniform_domain_size_i float: the size of the elements along the I direction
   • uniform_domain_size_j float: the size of the elements along the J direction
   • uniform_domain_size_k float: the size of the elements along the K direction
   • origin_i float: I-coordinate of the origin of the grid
   • origin_j float: J-coordinate of the origin of the grid
   • origin_k float: K-coordinate of the origin of the grid
16
      champ_base
       Champ_base
16.1
Description: Basic class of fields.
See also: objet_u (40) champ_don_base (16.9) champ_ostwald (16.25) champ_fonc_med (16.14) champ-
_input_base (16.21)
Usage:
16.2
       Champ fonc interp
Description: Field that is interpolated from a distant domain via MEDCoupling (remapper).
See also: champ_don_base (16.9)
Usage:
Champ_Fonc_Interp str
Read str {
     nom champ str
     pb loc str
     pb dist str
     [ dom_loc str]
     [dom dist str]
     [ default_value str]
     nature str
     [use_overlapdec str]
```

• **nom_champ** *str*: Name of the field (for example: temperature).

} where

- **pb_loc** *str*: Name of the local problem.
- **pb_dist** *str*: Name of the distant problem.
- dom loc str: Name of the local domain.
- dom dist str: Name of the distant domain.
- **default_value** *str*: Name of the distant domain.
- **nature** *str*: Nature of the field (knowledge from MEDCoupling is required; IntensiveMaximum, IntensiveConservation, ...).
- **use_overlapdec** *str*: Nature of the field (knowledge from MEDCoupling is required; IntensiveMaximum, IntensiveConservation, ...).

16.3 Champ_fonc_med_table_temps

Description: Field defined as a fixed spatial shape scaled by a temporal coefficient

```
See also: champ_fonc_med (16.14)
Usage:
Champ Fonc MED Table Temps str
Read str {
     [table_temps bloc_lecture]
     [ table_temps_lue str]
     [ use_existing_domain ]
     [last time]
     [decoup str]
     [ mesh str]
     domain str
     file str
     field str
     [loc str into ['som', 'elem']]
     [time float]
}
where
```

- table_temps bloc_lecture (3.59): Table containing the temporal coefficient used to scale the field
- table_temps_lue str: Name of the file containing the values of the temporal coefficient used to scale the field
- use_existing_domain for inheritance: whether to optimize the field loading by indicating that the field is supported by the same mesh that was initially loaded as the domain
- last_time for inheritance: to use the last time of the MED file instead of the specified time. Mutually exclusive with 'time' parameter.
- **decoup** *str* for inheritance: specify a partition file.
- **mesh** *str* for inheritance: Name of the mesh supporting the field. This is the name of the mesh in the MED file, and if this mesh was also used to create the TRUST domain, loading can be optimized with option 'use existing domain'.
- **domain** *str* for inheritance: Name of the domain supporting the field. This is the name of the mesh in the MED file, and if this mesh was also used to create the TRUST domain, loading can be optimized with option 'use_existing_domain'.
- file str for inheritance: Name of the .med file.
- field str for inheritance: Name of field to load.
- loc str into ['som', 'elem'] for inheritance: To indicate where the field is localised. Default to 'elem'.
- **time** *float* for inheritance: Timestep to load from the MED file. Mutually exclusive with 'last_time' flag.

16.4 Champ_fonc_med_tabule

```
Description: not_set
See also: champ fonc med (16.14)
Usage:
Champ Fonc MED Tabule str
Read str {
     [ use_existing_domain ]
     [last_time]
     [ decoup str]
     [ mesh str]
     domain str
     file str
     field str
     [loc str into ['som', 'elem']]
     [time float]
}
where
```

- **use_existing_domain** for inheritance: whether to optimize the field loading by indicating that the field is supported by the same mesh that was initially loaded as the domain
- **last_time** for inheritance: to use the last time of the MED file instead of the specified time. Mutually exclusive with 'time' parameter.
- **decoup** *str* for inheritance: specify a partition file.
- mesh *str* for inheritance: Name of the mesh supporting the field. This is the name of the mesh in the MED file, and if this mesh was also used to create the TRUST domain, loading can be optimized with option 'use_existing_domain'.
- **domain** *str* for inheritance: Name of the domain supporting the field. This is the name of the mesh in the MED file, and if this mesh was also used to create the TRUST domain, loading can be optimized with option 'use_existing_domain'.
- file str for inheritance: Name of the .med file.
- field str for inheritance: Name of field to load.
- loc str into ['som', 'elem'] for inheritance: To indicate where the field is localised. Default to 'elem'.
- **time** *float* for inheritance: Timestep to load from the MED file. Mutually exclusive with 'last_time' flag.

16.5 Champ_tabule_morceaux

Description: Field defined by tabulated data in each sub-domaine. It makes possible the definition of a field which is a function of other fields.

```
See also: champ_don_base (16.9) Champ_Fonc_Tabule_Morceaux_Interp (16.6)
```

Usage:

Champ_Tabule_Morceaux domain_name nb_comp data where

- **domain_name** *str*: Name of the domain.
- **nb_comp** *int*: Number of field components.

• data bloc_lecture (3.59): { Defaut val_def sous_domaine_1 val_1 ... sous_domaine_i val_i } By default, the value val_def is assigned to the field. It takes the sous_domaine_i identifier Sous_Domaine (sub_area) type object function, val_i. Sous_Domaine (sub_area) type objects must have been previously defined if the operator wishes to use a champ_fonc_tabule_morceaux type object.

16.6 Champ_fonc_tabule_morceaux_interp

Description: Field defined by tabulated data in each sub-domaine. It makes possible the definition of a field which is a function of other fields. Here we use MEDCoupling to interpolate fields between the two domains.

See also: Champ_Tabule_Morceaux (16.5)

Usage:

Champ_Fonc_Tabule_Morceaux_Interp problem_name nb_comp data where

- **problem_name** *str*: Name of the problem.
- **nb_comp** *int*: Number of field components.
- data bloc_lecture (3.59): { Defaut val_def sous_domaine_1 val_1 ... sous_domaine_i val_i } By default, the value val_def is assigned to the field. It takes the sous_domaine_i identifier Sous_Domaine (sub_area) type object function, val_i. Sous_Domaine (sub_area) type objects must have been previously defined if the operator wishes to use a champ_fonc_tabule_morceaux type object.

16.7 Champ_parametrique

```
Description: Parametric field

See also: champ_don_base (16.9)

Usage:
Champ_Parametrique str
Read str {
    fichier str
}
where
```

• fichier str: Filename where fields are read

16.8 Champ_composite

Description: Composite field. Used in multiphase problems to associate data to each phase.

See also: champ_don_base (16.9) champ_musig (16.24)

Usage:

champ_composite dim bloc

where

- dim int: Number of field components.
- **bloc** *bloc_lecture* (3.59): Values Various pieces of the field, defined per phase. Part 1 goes to phase 1, etc...

16.9 Champ_don_base

Description: Basic class for data fields (not calculated), p.e. physics properties.

See also: champ_base (16.1) champ_som_lu_vdf (16.26) champ_som_lu_vef (16.27) champ_fonc_tabule (16.18) champ_tabule_temps (16.29) champ_uniforme_morceaux (16.30) champ_fonc_t (16.17) tayl_green (16.35) champ_don_lu (16.10) Champ_Tabule_Morceaux (16.5) champ_init_canal_sinal (16.19) init_par_partie (16.34) uniform_field (16.36) champ_composite (16.8) champ_fonc_txyz (16.32) champ_fonc_xyz (16.33) champ_fonc_fonction_txyz_morceaux (16.13) champ_fonc_reprise (16.15) Champ_Parametrique (16.7) Champ_Fonc_Interp (16.2)

Usage:

16.10 Champ_don_lu

Description: Field to read a data field (values located at the center of the cells) in a file.

See also: champ_don_base (16.9)

Usage:

champ_don_lu dom nb_comp file
where

- **dom** *str*: Name of the domain.
- **nb_comp** *int*: Number of field components.
- file str: Name of the file.

This file has the following format:

nb val lues -> Number of values readen in th file

Xi Yi Zi -> Coordinates readen in the file

Ui Vi Wi -> Value of the field

16.11 Champ_fonc_fonction

Description: Field that is a function of another field.

See also: champ_fonc_tabule (16.18) champ_fonc_fonction_txyz (16.12)

Usage:

champ_fonc_fonction problem_name inco expression
where

- problem_name str: Name of problem.
- inco str: Name of the field (for example: temperature).
- **expression** *n word1 word2* ... *wordn*: Number of field components followed by the analytical expression for each field component.

16.12 Champ_fonc_fonction_txyz

Description: this refers to a field that is a function of another field and time and/or space coordinates

See also: champ_fonc_fonction (16.11)

champ_fonc_fonction_txyz problem_name inco expression where

- **problem_name** *str*: Name of problem.
- inco str: Name of the field (for example: temperature).
- **expression** *n word1 word2* ... *wordn*: Number of field components followed by the analytical expression for each field component.

16.13 Champ_fonc_fonction_txyz_morceaux

Description: Field defined by analytical functions in each sub-domaine. On each zone, the value is defined as a function of x,y,z,t and of scalar value taken from a parameter field. This values is associated to the variable 'val' in the expression.

See also: champ_don_base (16.9)

Usage:

champ_fonc_fonction_txyz_morceaux problem_name inco nb_comp data where

- **problem_name** *str*: Name of the problem.
- **inco** *str*: Name of the field (for example: temperature).
- **nb_comp** *int*: Number of field components.
- data bloc_lecture (3.59): { Defaut val_def sous_domaine_1 val_1 ... sous_domaine_i val_i } By default, the value val_def is assigned to the field. It takes the sous_domaine_i identifier Sous_Domaine (sub_area) type object function, val_i. Sous_Domaine (sub_area) type objects must have been previously defined if the operator wishes to use a champ_fonc_fonction_txyz_morceaux type object.

16.14 Champ_fonc_med

Description: Field to read a data field in a MED-format file .med at a specified time. It is very useful, for example, to resume a calculation with a new or refined geometry. The field post-processed on the new geometry at med format is used as initial condition for the resume.

See also: champ_base (16.1) Champ_Fonc_MED_Table_Temps (16.3) Champ_Fonc_MED_Tabule (16.4)

```
champ_fonc_med str
Read str {
    [ use_existing_domain ]
    [ last_time ]
    [ decoup str]
    [ mesh str]
    domain str
    file str
    field str
    [ loc str into ['som', 'elem']]
    [ time float]
}
where
```

- **use_existing_domain**: whether to optimize the field loading by indicating that the field is supported by the same mesh that was initially loaded as the domain
- **last_time**: to use the last time of the MED file instead of the specified time. Mutually exclusive with 'time' parameter.
- **decoup** str: specify a partition file.
- **mesh** *str*: Name of the mesh supporting the field. This is the name of the mesh in the MED file, and if this mesh was also used to create the TRUST domain, loading can be optimized with option 'use_existing_domain'.
- **domain** *str*: Name of the domain supporting the field. This is the name of the mesh in the MED file, and if this mesh was also used to create the TRUST domain, loading can be optimized with option 'use existing domain'.
- file str: Name of the .med file.
- field str: Name of field to load.
- loc str into ['som', 'elem']: To indicate where the field is localised. Default to 'elem'.
- time float: Timestep to load from the MED file. Mutually exclusive with 'last_time' flag.

16.15 Champ_fonc_reprise

Description: This field is used to read a data field in a save file (.xyz or .sauv) at a specified time. It is very useful, for example, to run a thermohydraulic calculation with velocity initial condition read into a save file from a previous hydraulic calculation.

See also: champ_don_base (16.9)

Usage:

champ_fonc_reprise [format] filename pb_name champ [fonction] temps
where

- **format** *str into* ['binaire', 'formatte', 'xyz', 'single_hdf', 'pdi']: Type of file (the file format). If xyz format is activated, the .xyz file from the previous calculation will be given for filename, and if formatte or binaire is choosen, the .sauv file of the previous calculation will be specified for filename. In the case of a parallel calculation, if the mesh partition does not changed between the previous calculation and the next one, the binaire format should be preferred, because is faster than the xyz format. If pdi is used, the same constraints/advantages as binaire apply, but it produces one (HDF5) file per node on the filesystem instead of having one file per processor. The single_hdf format is still supported but is obsolete, the PDI format is recommended.
- **filename** *str*: Name of the save file.
- **pb_name** *str*: Name of the problem.
- **champ** *str*: Name of the problem unknown. It may also be the temporal average of a problem unknown (like moyenne_vitesse, moyenne_temperature,...)
- **fonction** *fonction_champ_reprise* (16.16): Optional keyword to apply a function on the field being read in the save file (e.g. to read a temperature field in Celsius units and convert it for the calculation on Kelvin units, you will use: fonction 1 273.+val)
- **temps** *str*: Time of the saved field in the save file or last_time. If you give the keyword last_time instead, the last time saved in the save file will be used.

16.16 Fonction_champ_reprise

Description: not_set

See also: objet_lecture (39)

mot fonction

where

- mot str into ['fonction']
- **fonction** n word1 word2 ... wordn: n f1(val) f2(val) ... fn(val)] time

16.17 Champ_fonc_t

Description: Field that is constant in space and is a function of time.

See also: champ_don_base (16.9)

Usage:

champ_fonc_t val

where

• val n word1 word2 ... wordn: Values of field components (time dependant functions).

16.18 Champ_fonc_tabule

Description: Field that is tabulated as a function of another field.

See also: champ_don_base (16.9) champ_fonc_fonction (16.11)

Usage:

champ_fonc_tabule pb_field dim bloc

where

- pb_field bloc_lecture (3.59): block similar to { pb1 field1 } or { pb1 field1 ... pbN fieldN }
- **dim** *int*: Number of field components.
- **bloc** *bloc_lecture* (3.59): Values (the table (the value of the field at any time is calculated by linear interpolation from this table) or the analytical expression (with keyword expression to use an analytical expression)).

16.19 Champ_init_canal_sinal

Description: For a parabolic profile on U velocity with an unpredictable disturbance on V and W and a sinusoidal disturbance on V velocity.

See also: champ_don_base (16.9)

Usage:

champ_init_canal_sinal dim bloc

where

- dim int: Number of field components.
- bloc bloc_lec_champ_init_canal_sinal (16.20): Parameters for the class champ_init_canal_sinal.

16.20 Bloc_lec_champ_init_canal_sinal

Description: Parameters for the class champ init canal sinal.

```
in 2D:
U=ucent*y(2h-y)/h/h
V=ampli_bruit*rand+ampli_sin*sin(omega*x)
rand: unpredictable value between -1 and 1.
in 3D:
U=ucent*y(2h-y)/h/h
V=ampli_bruit*rand1+ampli_sin*sin(omega*x)
W=ampli bruit*rand2
rand1 and rand2: unpredictables values between -1 and 1.
See also: objet_lecture (39)
Usage:
{
      ucent float
      h float
      ampli_bruit float
      [ ampli sin float]
      omega float
      [ dir_flow int into [0, 1, 2]]
      [dir wall int into [0, 1, 2]]
      [ min dir flow float]
      [ min_dir_wall float]
}
where
   • ucent float: Velocity value at the center of the channel.
   • h float: Half hength of the channel.
   • ampli bruit float: Amplitude for the disturbance.
   • ampli_sin float: Amplitude for the sinusoidal disturbance (by default equals to ucent/10).
   • omega float: Value of pulsation for the of the sinusoidal disturbance.
   • dir_flow int into [0, 1, 2]: Flow direction for the initialization of the flow in a channel.
      - if dir_flow=0, the flow direction is X
      - if dir_flow=1, the flow direction is Y
      - if dir flow=2, the flow direction is Z
      Default value for dir flow is 0
   • dir wall int into [0, 1, 2]: Wall direction for the initialization of the flow in a channel.
      - if dir_wall=0, the normal to the wall is in X direction
      - if dir_wall=1, the normal to the wall is in Y direction
      - if dir_wall=2, the normal to the wall is in Z direction
      Default value for dir flow is 1
```

- min_dir_flow *float*: Value of the minimum coordinate in the flow direction for the initialization of the flow in a channel. Default value for dir flow is 0.
- min_dir_wall *float*: Value of the minimum coordinate in the wall direction for the initialization of the flow in a channel. Default value for dir_flow is 0.

16.21 Champ_input_base

Description: not_set

```
See also: champ_base (16.1) champ_input_p0 (16.22) champ_input_p0_composite (16.23)
Usage:
champ_input_base str
Read str {
     nb_comp int
     nom str
     [ initial_value n \times 1 \times 2 \dots \times n]
     probleme str
     [sous_zone str]
}
where
   • nb_comp int
   • nom str
   • initial_value n x1 x2 ... xn
   • probleme str
   • sous_zone str
16.22 Champ_input_p0
Description: not_set
See also: champ_input_base (16.21)
Usage:
champ_input_p0 str
Read str {
     nb_comp int
     nom str
     [ initial_value n \times 1 \times 2 \dots \times n]
     probleme str
     [ sous_zone str]
}
where
   • nb_comp int for inheritance
   • nom str for inheritance
   • initial_value n x1 x2 ... xn for inheritance
   • probleme str for inheritance
   • sous zone str for inheritance
        Champ_input_p0_composite
Description: Field used to define a classical champ input p0 field (for ICoCo), but with a predefined field
for the initial state.
See also: champ_input_base (16.21)
Usage:
champ_input_p0_composite str
```

Read str {

```
[initial_field champ_base]
      [input_field champ_input_p0]
      nb_comp int
      nom str
      [ initial_value n \times 1 \times 2 \dots \times n]
      probleme str
      [ sous_zone str]
}
where
   • initial_field champ_base (16.1): The field used for initialization
   • input_field champ_input_p0 (16.22): The input field for ICoCo
   • nb_comp int for inheritance
   • nom str for inheritance
   • initial_value n x1 x2 ... xn for inheritance
   • probleme str for inheritance
   • sous_zone str for inheritance
```

16.24 Champ_musig

Description: MUSIG field. Used in multiphase problems to associate data to each phase.

```
See also: champ_composite (16.8)

Usage:
champ_musig bloc
where

• bloc bloc_lecture (3.59): Not set
```

16.25 Champ_ostwald

```
Description: This keyword is used to define the viscosity variation law: Mu(T) = K(T)*(D:D/2)**((n-1)/2)
See also: champ_base (16.1)
Usage: champ_ostwald
```

16.26 Champ_som_lu_vdf

Description: Keyword to read in a file values located at the nodes of a mesh in VDF discretization.

```
See also: champ_don_base (16.9)

Usage: champ_som_lu_vdf domain_name dim tolerance file where
```

- domain name str: Name of the domain.
- dim int: Value of the dimension of the field.

- tolerance float: Value of the tolerance to check the coordinates of the nodes.
- file str: name of the file

This file has the following format:

Xi Yi Zi -> Coordinates of the node

Ui Vi Wi -> Value of the field on this node

Xi+1 Yi+1 Zi+1 -> Next point

Ui+1 Vi+1 Zi+1 -> Next value ...

16.27 Champ_som_lu_vef

Description: Keyword to read in a file values located at the nodes of a mesh in VEF discretization.

See also: champ_don_base (16.9)

Usage:

champ_som_lu_vef domain_name dim tolerance file

where

- **domain_name** *str*: Name of the domain.
- dim int: Value of the dimension of the field.
- tolerance float: Value of the tolerance to check the coordinates of the nodes.
- file str: Name of the file.

This file has the following format:

Xi Yi Zi -> Coordinates of the node

Ui Vi Wi -> Value of the field on this node

Xi+1 Yi+1 Zi+1 -> Next point

Ui+1 Vi+1 Zi+1 -> Next value ...

16.28 Champ_tabule_lu

Description: Uniform field, tabulated from a specified column file. Lines starting with # are ignored.

See also: champ_tabule_temps (16.29)

Usage:

champ_tabule_lu nb_comp column_file dim

where

- **nb_comp** *int*: Number of field components.
- column_file str: Name of the column file.
- dim int: Number of field components.

16.29 Champ_tabule_temps

Description: Field that is constant in space and tabulated as a function of time.

See also: champ_don_base (16.9) champ_tabule_lu (16.28)

Usage:

champ_tabule_temps dim bloc

where

- dim int: Number of field components.
- **bloc** *bloc_lecture* (3.59): Values as a table. The value of the field at any time is calculated by linear interpolation from this table.

16.30 Champ_uniforme_morceaux

Description: Field which is partly constant in space and stationary.

See also: champ_don_base (16.9) valeur_totale_sur_volume (16.37) champ_uniforme_morceaux_tabule_temps (16.31)

Usage:

champ_uniforme_morceaux nom_dom nb_comp data where

- nom dom str: Name of the domain to which the sub-areas belong.
- **nb_comp** *int*: Number of field components.
- data bloc_lecture (3.59): { Defaut val_def sous_zone_1 val_1 ... sous_zone_i val_i } By default, the value val_def is assigned to the field. It takes the sous_zone_i identifier Sous_Zone (sub_area) type object value, val_i. Sous_Zone (sub_area) type objects must have been previously defined if the operator wishes to use a Champ_Uniforme_Morceaux(partly_uniform_field) type object.

16.31 Champ_uniforme_morceaux_tabule_temps

Description: this type of field is constant in space on one or several sub_zones and tabulated as a function of time.

See also: champ_uniforme_morceaux (16.30)

Usage:

champ_uniforme_morceaux_tabule_temps nom_dom nb_comp data where

- nom dom str: Name of the domain to which the sub-areas belong.
- **nb comp** *int*: Number of field components.
- data bloc_lecture (3.59): { Defaut val_def sous_zone_1 val_1 ... sous_zone_i val_i } By default, the value val_def is assigned to the field. It takes the sous_zone_i identifier Sous_Zone (sub_area) type object value, val_i. Sous_Zone (sub_area) type objects must have been previously defined if the operator wishes to use a Champ_Uniforme_Morceaux(partly_uniform_field) type object.

16.32 Champ fonc txyz

Description: Field defined by analytical functions. It makes it possible the definition of a field that depends on the time and the space.

See also: champ_don_base (16.9)

Usage:

champ_fonc_txyz dom val
where

- dom str: Name of domain of calculation
- val n word1 word2 ... wordn: List of functions on (t,x,y,z).

16.33 Champ_fonc_xyz

Description: Field defined by analytical functions. It makes it possible the definition of a field that depends on (x,y,z).

See also: champ_don_base (16.9)

Usage:

champ_fonc_xyz dom val
where

- dom str: Name of domain of calculation.
- val n word1 word2 ... wordn: List of functions on (x,y,z).

16.34 Init_par_partie

Description: ne marche que pour n_comp=1

See also: champ_don_base (16.9)

Usage:

init_par_partie n_comp val1 val2 val3 where

- **n_comp** *int into* [1]
- val1 float
- val2 float
- val3 float

16.35 Tayl_green

Description: Class Tayl_green.

See also: champ_don_base (16.9)

Usage:

tayl_green dim

where

• dim int: Dimension.

16.36 Uniform_field

Synonymous: champ_uniforme

Description: Field that is constant in space and stationary.

See also: champ_don_base (16.9)

Usage:

uniform_field val

where

• val n x1 x2 ... xn: Values of field components.

16.37 Valeur_totale_sur_volume

Description: Similar as Champ_Uniforme_Morceaux with the same syntax. Used for source terms when we want to specify a source term with a value given for the volume (eg: heat in Watts) and not a value per volume unit (eg: heat in Watts/m3).

See also: champ_uniforme_morceaux (16.30)

Usage:

valeur_totale_sur_volume nom_dom nb_comp data where

- **nom_dom** *str*: Name of the domain to which the sub-areas belong.
- **nb comp** *int*: Number of field components.
- data bloc_lecture (3.59): { Defaut val_def sous_zone_1 val_1 ... sous_zone_i val_i } By default, the value val_def is assigned to the field. It takes the sous_zone_i identifier Sous_Zone (sub_area) type object value, val_i. Sous_Zone (sub_area) type objects must have been previously defined if the operator wishes to use a Champ_Uniforme_Morceaux(partly_uniform_field) type object.

17 champ_front_base

17.1 Champ_front_base

Description: Basic class for fields at domain boundaries.

See also: objet_u (40) Champ_front_debit_QC_VDF_fonc_t (17.5) Champ_front_debit_QC_VDF (17.4) champ_front_pression_from_u (17.25) champ_front_contact_vef (17.13) champ_front_tangentiel_vef (17.29) champ_front_MED (17.9) champ_front_uniforme (17.30) champ_front_fonction (17.21) champ_front_debit_massique (17.15) champ_front_tabule (17.27) ch_front_input (17.7) champ_front_debit (17.14) champ_front_xyz_debit (17.31) champ_front_lu (17.22) boundary_field_inward (17.6) champ_front_normal_vef (17.24) champ_front_fonc_pois_tube (17.17) champ_front_bruite (17.10) champ_front_fonc_txyz (17.19) champ_front_fonc_pois_ipsn (17.16) champ_front_calc (17.11) champ_front_composite (17.12) champ_front_fonc_t (17.18) champ_front_fonc_xyz (17.20) champ_front_recyclage (17.26) Champ_front_Parametrique (17.3)

Usage:

17.2 Champ_front_xyz_tabule

Description: Space dependent field on the boundary, tabulated as a function of time.

See also: champ_front_fonc_txyz (17.19)

Usage:

Champ_Front_xyz_Tabule val bloc where

• val n word1 word2 ... wordn: Values of field components (mathematical expressions).

• **bloc** *bloc_lecture* (3.59): {nt1 t2 t3tn u1 [v1 w1 ...] u2 [v2 w2 ...] u3 [v3 w3 ...] ... un [vn wn ...] }

Values are entered into a table based on n couples (ti, ui) if nb_comp value is 1. The value of a field at a given time is calculated by linear interpolation from this table.

17.3 Champ_front_parametrique

```
Description: Parametric boundary field

See also: champ_front_base (17.1)

Usage:
Champ_front_Parametrique str

Read str {
    fichier str
}
where
```

• fichier str: Filename where boundary fields are read

17.4 Champ_front_debit_qc_vdf

Description: This keyword is used to define a flow rate field for quasi-compressible fluids in VDF discretization. The flow rate is kept constant during a transient.

See also: champ_front_base (17.1)

Usage:

$\label{lem:champ_front_debit_QC_VDF} \ \ dimension \ \ liste \ [\ moyen \] \ pb_name \\ \ where$

- **dimension** *int*: Problem dimension
- **liste** *bloc_lecture* (3.59): List of the mass flow rate values [kg/s/m2] with the following syntaxe: { val1 ... valdim }
- moyen str: Option to use rho mean value
- **pb_name** *str*: Problem name

17.5 Champ_front_debit_qc_vdf_fonc_t

Description: This keyword is used to define a flow rate field for quasi-compressible fluids in VDF discretization. The flow rate could be constant or time-dependent.

```
See also: champ_front_base (17.1)
```

Usage:

$\label{lem:champ_front_debit_QC_VDF_fonc_t} \ \ dimension \ \ liste \ [\ moyen \] \ \ pb_name \\ \ \ where$

- **dimension** *int*: Problem dimension
- **liste** *bloc_lecture* (3.59): List of the mass flow rate values [kg/s/m2] with the following syntaxe: { val1 ... valdim } where val1 ... valdim are constant or function of time.
- moyen str: Option to use rho mean value
- **pb_name** *str*: Problem name

17.6 Boundary_field_inward

Description: this field is used to define the normal vector field standard at the boundary in VDF or VEF discretization.

```
See also: champ_front_base (17.1)

Usage:
boundary_field_inward str

Read str {

    normal_value str
}
where
```

• **normal_value** *str*: normal vector value (positive value for a vector oriented outside to inside) which can depend of the time.

17.7 Ch_front_input

```
Description: not_set
See also: champ_front_base (17.1) ch_front_input_uniforme (17.8)
Usage:
ch_front_input str
Read str {
     nb_comp int
      nom str
      [ initial_value n \times 1 \times 2 \dots \times n]
      probleme str
      [ sous_zone str]
}
where
   • nb_comp int
   • nom str
   • initial_value n x1 x2 ... xn
   • probleme str
   • sous zone str
```

17.8 Ch_front_input_uniforme

Description: for coupling, you can use ch_front_input_uniforme which is a champ_front_uniforme, which use an external value. It must be used with Problem.setInputField.

```
See also: ch_front_input (17.7)

Usage:
ch_front_input_uniforme str
Read str {
```

```
nb_comp int
      nom str
      [initial value n \times 1 \times 2 \dots \times n]
      probleme str
      [ sous_zone str]
where
   • nb_comp int for inheritance
   • nom str for inheritance
```

- initial_value n x1 x2 ... xn for inheritance
- probleme str for inheritance
- sous_zone str for inheritance

17.9 Champ front med

Description: Field allowing the loading of a boundary condition from a MED file using Champ fonc med

```
See also: champ_front_base (17.1)
```

Usage:

```
champ_front_MED champ_fonc_med
where
```

• champ_fonc_med champ_base (16.1): a champ_fonc_med loading the values of the unknown on a domain boundary

17.10 Champ_front_bruite

Description: Field which is variable in time and space in a random manner.

```
See also: champ front base (17.1)
Usage:
champ_front_bruite nb_comp bloc
where
```

- **nb comp** *int*: Number of field components.
- bloc bloc_lecture (3.59): { [N val L val] Moyenne m_1.....[m_i] Amplitude A_1.....[A_i]}: Random nois: If N and L are not defined, the ith component of the field varies randomly around an average value m_i with a maximum amplitude A_i.

White noise: If N and L are defined, these two additional parameters correspond to L, the domain length and N, the number of nodes in the domain. Noise frequency will be between 2*Pi/L and 2*Pi*N/(4*L).

For example, formula for velocity: u=U0(t) v=U1(t)Uj(t)=Mj+2*Aj*bruit_blanc where bruit_blanc (white_noise) is the formula given in the mettre_a_jour (update) method of the Champ_front_bruite (noise_boundary_field) (Refer to the Champ_front_bruite.cpp file).

17.11 Champ_front_calc

Description: This keyword is used on a boundary to get a field from another boundary. The local and remote boundaries should have the same mesh. If not, the Champ_front_recyclage keyword could be used instead. It is used in the condition block at the limits of equation which itself refers to a problem called pb1. We are working under the supposition that pb1 is coupled to another problem.

See also: champ_front_base (17.1)

Usage:

champ_front_calc problem_name bord field_name
where

• **problem name** str: Name of the other problem to which pb1 is coupled.

- **bord** *str*: Name of the side which is the boundary between the 2 domains in the domain object description associated with the problem name object.
- **field_name** *str*: Name of the field containing the value that the user wishes to use at the boundary. The field_name object must be recognized by the problem_name object.

17.12 Champ_front_composite

Description: Composite front field. Used in multiphase problems to associate data to each phase.

See also: champ_front_base (17.1) champ_front_musig (17.23)

Usage:

 $champ_front_composite \ dim \ bloc$

where

- dim int: Number of field components.
- **bloc** *bloc_lecture* (3.59): Values Various pieces of the field, defined per phase. Part 1 goes to phase 1, etc...

17.13 Champ_front_contact_vef

Description: This field is used on a boundary between a solid and fluid domain to exchange a calculated temperature at the contact face of the two domains according to the flux of the two problems.

See also: champ_front_base (17.1)

Usage:

champ_front_contact_vef local_pb local_boundary remote_pb remote_boundary
where

- local_pb str: Name of the problem.
- local_boundary str: Name of the boundary.
- remote_pb str: Name of the second problem.
- remote_boundary str: Name of the boundary in the second problem.

17.14 Champ_front_debit

Description: This field is used to define a flow rate field instead of a velocity field for a Dirichlet boundary condition on Navier-Stokes equations.

See also: champ_front_base (17.1)

Usage:

champ_front_debit ch

where

• **ch** *champ_front_base* (17.1): uniform field in space to define the flow rate. It could be, for example, champ_front_uniforme, ch_front_input_uniform or champ_front_fonc_txyz that depends only on time

17.15 Champ_front_debit_massique

Description: This field is used to define a flow rate field using the density

See also: champ_front_base (17.1)

Usage:

champ_front_debit_massique ch

where

• **ch** *champ_front_base* (17.1): uniform field in space to define the flow rate. It could be, for example, champ_front_uniforme, ch_front_input_uniform or champ_front_fonc_txyz that depends only on time.

17.16 Champ_front_fonc_pois_ipsn

Description: Boundary field champ_front_fonc_pois_ipsn.

See also: champ_front_base (17.1)

Usage:

 $\begin{array}{lll} champ_front_fonc_pois_ipsn & r_tube & umoy & r_loc \\ \\ where & & \\ \end{array}$

- r_tube float
- **umoy** n x1 x2 ... xn
- $r_{loc} x1 x2 (x3)$

17.17 Champ_front_fonc_pois_tube

Description: Boundary field champ_front_fonc_pois_tube.

See also: champ front base (17.1)

Usage:

 $champ_front_fonc_pois_tube \ r_tube \ umoy \ r_loc \ r_loc_mult$

where

- r_tube float
- **umoy** n x1 x2 ... xn
- $r_{loc} x1 x2 (x3)$
- r_loc_mult n1 n2 (n3)

17.18 Champ_front_fonc_t

Description: Boundary field that depends only on time.

See also: champ_front_base (17.1)

Usage:

 $champ_front_fonc_t \quad val$

where

• val n word1 word2 ... wordn: Values of field components (mathematical expressions).

17.19 Champ_front_fonc_txyz

Description: Boundary field which is not constant in space and in time.

See also: champ_front_base (17.1) Champ_Front_xyz_Tabule (17.2)

Usage:

champ_front_fonc_txyz val

where

• val n word1 word2 ... wordn: Values of field components (mathematical expressions).

17.20 Champ_front_fonc_xyz

Description: Boundary field which is not constant in space.

See also: champ_front_base (17.1)

Usage:

champ_front_fonc_xyz val

where

• val n word1 word2 ... wordn: Values of field components (mathematical expressions).

17.21 Champ_front_fonction

Description: boundary field that is function of another field

See also: champ_front_base (17.1)

Usage:

where

• dim int: Number of field components.

- inco str: Name of the field (for example: temperature).
- **expression** *str*: keyword to use a analytical expression like 10.*EXP(-0.1*val) where val be the keyword for the field.

17.22 Champ_front_lu

Description: boundary field which is given from data issued from a read file. The format of this file has to be the same that the one generated by Ecrire_fichier_xyz_valeur

Example for K and epsilon quantities to be defined for inlet condition in a boundary named 'entree': entree frontiere_ouverte_K_Eps_impose Champ_Front_lu dom 2pb_K_EPS_PERIO_1006.306198.dat

See also: champ_front_base (17.1)

Usage:

champ_front_lu domaine dim file where

• domaine str: Name of domain

• dim int: number of components

• **file** *str*: path for the read file

17.23 Champ_front_musig

Description: MUSIG front field. Used in multiphase problems to associate data to each phase.

See also: champ_front_composite (17.12)

Usage:

champ_front_musig bloc

where

• **bloc** *bloc_lecture* (3.59): Not set

17.24 Champ_front_normal_vef

Description: Field to define the normal vector field standard at the boundary in VEF discretization.

See also: champ_front_base (17.1)

Usage:

champ_front_normal_vef mot vit_tan

where

- mot str into ['valeur_normale']: Name of vector field.
- vit_tan float: normal vector value (positive value for a vector oriented outside to inside).

17.25 Champ_front_pression_from_u

Description: this field is used to define a pressure field depending of a velocity field.

```
See also: champ_front_base (17.1)

Usage: champ_front_pression_from_u expression where
```

• **expression** *str*: value depending of a velocity (like $2 * u_moy^2$).

17.26 Champ_front_recyclage

Description: This keyword is used on a boundary to get a field from another boundary.

It is to use, in a general way, on a boundary of a local_pb problem, a field calculated from a linear combination of an imposed field g(x,y,z,t) with an instantaneous f(x,y,z,t) and a spatial mean field f(x,y,z) or a temporal mean field f(x,y,z) extracted from a plane of a problem named pb (pb may be local_pb itself): For each component i, the field F applied on the boundary will be:

```
F_{-i}(x,y,z,t) = alpha_{-i}*g_{-i}(x,y,z,t) + xsi_{-i}*[f_{-i}(x,y,z,t)-beta_{-i}*<fi>]
```

```
See also: champ_front_base (17.1)

Usage:
champ_front_recyclage str

Read str {

    pb_champ_evaluateur pb_champ_evaluateur
    [ distance_plan x1 x2 (x3)]
    [ ampli_moyenne_imposee n x1 x2 ... xn]
    [ ampli_fluctuation n x1 x2 ... xn]
    [ direction_anisotrope int into [1, 2, 3]]
    [ moyenne_imposee moyenne_imposee_deriv]
    [ moyenne_recyclee str]
    [ fichier str]
}
```

• pb_champ_evaluateur pb_champ_evaluateur (27)

where

- **distance_plan** x1 x2 (x3): Vector which gives the distance between the boundary and the plane from where the field F will be extracted. By default, the vector is zero, that should imply the two domains have coincident boundaries.
- ampli_moyenne_imposee n x1 x2 ... xn: 2|3 alpha(0) alpha(1) [alpha(2)]: alpha_i coefficients (by default =1)
- ampli_moyenne_recyclee *n x1 x2 ... xn*: 2l3 beta(0) beta(1) [beta(2)]}: beta_i coefficients (by default =1)
- **ampli_fluctuation** $n \times 1 \times 2 \dots \times n$: 2|3 gamma(0) gamma(1) [gamma(2)]}: gamma_i coefficients (by default =1)
- **direction_anisotrope** *int into* [1, 2, 3]: If an integer is given for direction (X:1, Y:2, Z:3, by default, direction is negative), the imposed field g will be 0 for the 2 other directions.
- moyenne_imposee moyenne_imposee_deriv (24): Value of the imposed g field.

- moyenne_recyclee str: Method used to perform a spatial or a temporal averaging of field to specify <f>. <f> can be the surface mean of f on the plane (surface option, see below) or it can be read from several files (for example generated by the chmoy_faceperio option of the Traitement_particulier keyword to obtain a temporal mean field). The option methode_recyc can be: surfacique, Surface mean for <f> from f values on the plane; Or one of the following methode_moy options applied to read a temporal mean field <f>(x,y,z): interpolation, connexion_approchee or connexion_exacte
- fichier str

17.27 Champ_front_tabule

Description: Constant field on the boundary, tabulated as a function of time.

See also: champ_front_base (17.1) champ_front_tabule_lu (17.28)

Usage:

champ_front_tabule nb_comp bloc

where

- **nb comp** *int*: Number of field components.
- **bloc** *bloc_lecture* (3.59): {nt1 t2 t3tn u1 [v1 w1 ...] u2 [v2 w2 ...] u3 [v3 w3 ...] ... un [vn wn ...] }

Values are entered into a table based on n couples (ti, ui) if nb_comp value is 1. The value of a field at a given time is calculated by linear interpolation from this table.

17.28 Champ front tabule lu

Description: Constant field on the boundary, tabulated from a specified column file. Lines starting with # are ignored.

See also: champ_front_tabule (17.27)

Usage:

champ_front_tabule_lu nb_comp column_file where

- **nb comp** *int*: Number of field components.
- column_file str: Name of the column file.

17.29 Champ_front_tangentiel_vef

Description: Field to define the tangential velocity vector field standard at the boundary in VEF discretization.

See also: champ_front_base (17.1)

Usage:

champ_front_tangentiel_vef mot vit_tan where

- mot str into ['vitesse tangentielle']: Name of vector field.
- vit_tan float: Vector field standard [m/s].

17.30 Champ_front_uniforme

Description: Boundary field which is constant in space and stationary.

```
See also: champ_front_base (17.1)

Usage: champ_front_uniforme val where

• val n x1 x2 ... xn: Values of field components.
```

17.31 Champ_front_xyz_debit

Description: This field is used to define a flow rate field with a velocity profil which will be normalized to match the flow rate chosen.

```
See also: champ_front_base (17.1)
Usage:
champ_front_xyz_debit str
Read str {
    [velocity_profil champ_front_base]
    flow_rate champ_front_base
}
where
```

- **velocity_profil** *champ_front_base* (17.1): velocity_profil 0 velocity field to define the profil of velocity.
- flow_rate champ_front_base (17.1): flow_rate 1 uniform field in space to define the flow rate. It could be, for example, champ_front_uniforme, ch_front_input_uniform or champ_front_fonc_t

18 interpolation_ibm_base

Description: Base class for all the interpolation methods available in the Immersed Boundary Method (IBM).

```
See also: objet_u (40) ibm_element_fluide (18.3) ibm_gradient_moyen (18.5) ibm_aucune (18.2)
```

Usage:

```
interpolation_ibm_base [ impr ] [ nb_histo_boxes_impr ]
where
```

- impr : To print IBM-related data
- nb_histo_boxes_impr int: number of histogram boxes for printed data

18.1 Interpolation_ibm_power_law_tbl_u_star

Description: Immersed Boundary Method (IBM): law u star.

```
See also: ibm_gradient_moyen (18.5)
```

```
Usage:
Interpolation_IBM_power_law_tbl_u_star str
Read str {

    points_solides champ_base
    est_dirichlet champ_base
    correspondance_elements champ_base
    elements_solides champ_base
    [ impr ]
    [ nb_histo_boxes_impr int]
}
where
```

- **points_solides** *champ_base* (16.1): Node field giving the projection of the node on the immersed boundary
- est_dirichlet champ_base (16.1): Node field of booleans indicating whether the node belong to an element where the interface is
- correspondance_elements champ_base (16.1): Cell field giving the SALOME cell number
- **elements_solides** *champ_base* (16.1): Node field giving the element number containing the solid point
- impr for inheritance: To print IBM-related data
- nb_histo_boxes_impr int for inheritance: number of histogram boxes for printed data

18.2 Ibm_aucune

```
Synonymous: interpolation_ibm_aucune
```

Description: Immersed Boundary Method (IBM): no interpolation.

```
See also: interpolation_ibm_base (18)
```

Usage:

ibm_aucune [impr] [nb_histo_boxes_impr]
where

- impr : To print IBM-related data
- nb_histo_boxes_impr int: number of histogram boxes for printed data

18.3 Ibm_element_fluide

```
Synonymous: interpolation_ibm_element_fluide
```

Description: Immersed Boundary Method (IBM): fluid element interpolation.

```
See also: interpolation_ibm_base (18) ibm_hybride (18.4) ibm_power_law_tbl (18.6)
```

```
ibm_element_fluide str
Read str {
    points_fluides champ_base
    points_solides champ_base
```

```
elements_fluides champ_base
    correspondance_elements champ_base
[ impr ]
    [ nb_histo_boxes_impr int]
}
where
```

- **points_fluides** *champ_base* (16.1): Node field giving the projection of the point below (points_solides) falling into the pure cell fluid
- **points_solides** *champ_base* (16.1): Node field giving the projection of the node on the immersed boundary
- **elements_fluides** *champ_base* (16.1): Node field giving the number of the element (cell) containing the pure fluid point
- correspondance_elements champ_base (16.1): Cell field giving the SALOME cell number
- impr for inheritance: To print IBM-related data
- **nb_histo_boxes_impr** *int* for inheritance: number of histogram boxes for printed data

18.4 Ibm hybride

Synonymous: interpolation_ibm_hybride

Description: Immersed Boundary Method (IBM): hybrid (fluid/mean gradient) interpolation.

```
See also: ibm_element_fluide (18.3)

Usage:
ibm_hybride str

Read str {

    est_dirichlet champ_base
    elements_solides champ_base
    points_fluides champ_base
    points_solides champ_base
    elements_fluides champ_base
    elements_fluides champ_base
    correspondance_elements champ_base
    [ impr ]
    [ nb_histo_boxes_impr int]
}

where
```

- **est_dirichlet** *champ_base* (16.1): Node field of booleans indicating whether the node belong to an element where the interface is
- **elements_solides** *champ_base* (16.1): Node field giving the element number containing the solid point
- **points_fluides** *champ_base* (16.1) for inheritance: Node field giving the projection of the point below (points_solides) falling into the pure cell fluid
- **points_solides** *champ_base* (16.1) for inheritance: Node field giving the projection of the node on the immersed boundary
- **elements_fluides** *champ_base* (16.1) for inheritance: Node field giving the number of the element (cell) containing the pure fluid point
- **correspondance_elements** *champ_base* (16.1) for inheritance: Cell field giving the SALOME cell number
- impr for inheritance: To print IBM-related data
- nb_histo_boxes_impr int for inheritance: number of histogram boxes for printed data

18.5 Ibm_gradient_moyen

```
Synonymous: interpolation_ibm_gradient_moyen

Description: Immersed Boundary Method (IBM): mean gradient interpolation.

See also: interpolation_ibm_base (18) Interpolation_IBM_power_law_tbl_u_star (18.1)

Usage: ibm_gradient_moyen str

Read str {

    points_solides champ_base
    est_dirichlet champ_base
    correspondance_elements champ_base
    elements_solides champ_base
    [ impr ]
    [ nb_histo_boxes_impr int]

} where
```

- **points_solides** *champ_base* (16.1): Node field giving the projection of the node on the immersed boundary
- **est_dirichlet** *champ_base* (16.1): Node field of booleans indicating whether the node belong to an element where the interface is
- correspondance_elements champ_base (16.1): Cell field giving the SALOME cell number
- **elements_solides** *champ_base* (16.1): Node field giving the element number containing the solid point
- impr for inheritance: To print IBM-related data
- nb_histo_boxes_impr int for inheritance: number of histogram boxes for printed data

```
18.6 Ibm_power_law_tbl

Synonymous: interpolation_ibm_power_law_tbl

Description: Immersed Boundary Method (IBM): power law interpolation.

See also: ibm_element_fluide (18.3)

Usage: ibm_power_law_tbl str

Read str {

    [formulation_linear_pwl int]
    points_fluides champ_base
    points_solides champ_base
    elements_fluides champ_base
    correspondance_elements champ_base
    [impr ]
    [nb_histo_boxes_impr int]
```

• formulation linear pwl int: Choix formulation lineaire ou non

} where

- **points_fluides** *champ_base* (16.1) for inheritance: Node field giving the projection of the point below (points_solides) falling into the pure cell fluid
- **points_solides** *champ_base* (16.1) for inheritance: Node field giving the projection of the node on the immersed boundary
- **elements_fluides** *champ_base* (16.1) for inheritance: Node field giving the number of the element (cell) containing the pure fluid point
- **correspondance_elements** *champ_base* (16.1) for inheritance: Cell field giving the SALOME cell number
- impr for inheritance: To print IBM-related data
- nb_histo_boxes_impr int for inheritance: number of histogram boxes for printed data

19 loi etat base

Description: Basic class for state laws used with a dilatable fluid.

```
See also: objet_u (40) loi_etat_gaz_reel_base (19.8) loi_etat_gaz_parfait_base (19.7) loi_etat_tppi_base (19.9)
```

Usage:

Usage:

19.1 **Eos_qc**

```
Description: Class for using EOS with QC problem
```

```
See also: loi_etat_tppi_base (19.9)
```

```
EOS_QC str
Read str {

Cp float fluid str
```

model str

} where

- Cp *float*: Specific heat at constant pressure (J/kg/K).
- fluid str: Fluid name in the EOS model
- model str: EOS model name

19.2 **Eos_wc**

Description: Class for using EOS with WC problem

```
See also: loi_etat_tppi_base (19.9)
```

```
Usage:
```

```
EOS_WC str
Read str {
    Cp float fluid str
```

model str

```
Property of the strict of the stric
```

19.3 Binaire_gaz_parfait_qc

Description: Class for perfect gas binary mixtures state law used with a quasi-compressible fluid under the iso-thermal and iso-bar assumptions.

```
Usage:
binaire_gaz_parfait_QC str
Read str {

molar_mass1 float
molar_mass2 float
mu1 float
mu2 float
temperature float
diffusion_coeff float
}
where
```

- molar_mass1 float: Molar mass of species 1 (in kg/mol).
- molar_mass2 *float*: Molar mass of species 2 (in kg/mol).
- mu1 float: Dynamic viscosity of species 1 (in kg/m.s).
- mu2 float: Dynamic viscosity of species 2 (in kg/m.s).
- **temperature** *float*: Temperature (in Kelvin) which will be constant during the simulation since this state law only works for iso-thermal conditions.
- diffusion_coeff float: Diffusion coefficient assumed the same for both species (in m2/s).

19.4 Binaire_gaz_parfait_wc

Description: Class for perfect gas binary mixtures state law used with a weakly-compressible fluid under the iso-thermal and iso-bar assumptions.

```
See also: loi_etat_gaz_parfait_base (19.7)

Usage:
binaire_gaz_parfait_WC str

Read str {

    molar_mass1 float
    molar_mass2 float
    mu1 float
    mu2 float
    temperature float
    diffusion_coeff float
```

```
}
where
   • molar_mass1 float: Molar mass of species 1 (in kg/mol).
   • molar_mass2 float: Molar mass of species 2 (in kg/mol).
   • mu1 float: Dynamic viscosity of species 1 (in kg/m.s).
   • mu2 float: Dynamic viscosity of species 2 (in kg/m.s).
   • temperature float: Temperature (in Kelvin) which will be constant during the simulation since this
     state law only works for iso-thermal conditions.
   • diffusion coeff float: Diffusion coefficient assumed the same for both species (in m2/s).
19.5
       Coolprop_qc
Description: Class for using CoolProp with QC problem
See also: loi_etat_tppi_base (19.9)
Usage:
coolprop_QC str
Read str {
     Cp float
     fluid str
     model str
}
where
   • Cp float: Specific heat at constant pressure (J/kg/K).
   • fluid str: Fluid name in the CoolProp model
   • model str: CoolProp model name
19.6
       Coolprop_wc
Description: Class for using CoolProp with WC problem
See also: loi_etat_tppi_base (19.9)
Usage:
coolprop_WC str
Read str {
     Cp float
     fluid str
     model str
where
```

• Cp *float*: Specific heat at constant pressure (J/kg/K).

• fluid str: Fluid name in the CoolProp model

• model str: CoolProp model name

19.7 Loi_etat_gaz_parfait_base

Description: Basic class for perfect gases state laws used with a dilatable fluid.

```
See also: loi_etat_base (19) rhoT_gaz_parfait_QC (19.14) binaire_gaz_parfait_QC (19.3) multi_gaz_parfait_QC (19.10) gaz_parfait_QC (19.12) multi_gaz_parfait_WC (19.11) binaire_gaz_parfait_WC (19.4) gaz_parfait_WC (19.13)
```

Usage:

19.8 Loi_etat_gaz_reel_base

Description: Basic class for real gases state laws used with a dilatable fluid.

```
See also: loi etat base (19) rhoT gaz reel QC (19.15)
```

Usage:

19.9 Loi_etat_tppi_base

Description: Basic class for thermo-physical properties interface (TPPI) used for dilatable problems

```
See also: loi_etat_base (19) coolprop_QC (19.5) EOS_QC (19.1) EOS_WC (19.2) coolprop_WC (19.6)
```

Usage:

19.10 Multi_gaz_parfait_qc

Description: Class for perfect gas multi-species mixtures state law used with a quasi-compressible fluid.

```
See also: loi_etat_gaz_parfait_base (19.7)
```

```
Usage:
```

```
multi_gaz_parfait_QC str

Read str {

sc float
prandtl float
[cp float]
[dtol_fraction float]
[correction_fraction]
[ignore_check_fraction]
}
where
```

- sc float: Schmidt number of the gas Sc=nu/D (D: diffusion coefficient of the mixing).
- prandtl float: Prandtl number of the gas Pr=mu*Cp/lambda
- cp float: Specific heat at constant pressure of the gas Cp.
- dtol fraction float: Delta tolerance on mass fractions for check testing (default value 1.e-6).
- **correction_fraction**: To force mass fractions between 0. and 1.
- **ignore_check_fraction**: Not to check if mass fractions between 0. and 1.

19.11 Multi_gaz_parfait_wc

Description: Class for perfect gas multi-species mixtures state law used with a weakly-compressible fluid.

```
See also: loi_etat_gaz_parfait_base (19.7)

Usage:
multi_gaz_parfait_WC str

Read str {

    species_number int
    diffusion_coeff champ_base
    molar_mass champ_base
    mu champ_base
    cp champ_base
    prandtl float

}

where
```

- species_number int: Number of species you are considering in your problem.
- **diffusion_coeff** *champ_base* (16.1): Diffusion coefficient of each species, defined with a Champ_uniforme of dimension equals to the species_number.
- **molar_mass** *champ_base* (16.1): Molar mass of each species, defined with a Champ_uniforme of dimension equals to the species_number.
- **mu** *champ_base* (16.1): Dynamic viscosity of each species, defined with a Champ_uniforme of dimension equals to the species_number.
- **cp** *champ_base* (16.1): Specific heat at constant pressure of the gas Cp, defined with a Champ_uniforme of dimension equals to the species_number..
- **prandtl** *float*: Prandtl number of the gas Pr=mu*Cp/lambda.

19.12 Gaz_parfait_qc

See also: loi etat gaz parfait base (19.7)

Description: Class for perfect gas state law used with a quasi-compressible fluid.

- Cp float: Specific heat at constant pressure (J/kg/K).
- Cv float: Specific heat at constant volume (J/kg/K).
- gamma float: Cp/Cv
- **Prandtl** *float*: Prandtl number of the gas Pr=mu*Cp/lambda
- **rho_constant_pour_debug** *champ_base* (16.1): For developers to debug the code with a constant rho.

19.13 Gaz_parfait_wc

Description: Class for perfect gas state law used with a weakly-compressible fluid.

19.14 Rhot_gaz_parfait_qc

Description: Class for perfect gas used with a quasi-compressible fluid where the state equation is defined as rho = f(T).

```
See also: loi_etat_gaz_parfait_base (19.7)

Usage:
rhoT_gaz_parfait_QC str

Read str {

    cp float
    [prandtl float]
    [rho_xyz champ_base]
    [rho_t str]
    [t_min float]
}

where
```

- cp float: Specific heat at constant pressure of the gas Cp.
- **prandtl** *float*: Prandtl number of the gas Pr=mu*Cp/lambda
- **rho_xyz** *champ_base* (16.1): Defined with a Champ_Fonc_xyz to define a constant rho with time (space dependent)
- **rho_t** *str*: Expression of T used to calculate rho. This can lead to a variable rho, both in space and in time.
- t_min *float*: Temperature may, in some cases, locally and temporarily be very small (and negative) even though computation converges. T_min keyword allows to set a lower limit of temperature (in Kelvin, -1000 by default). WARNING: DO NOT USE THIS KEYWORD WITHOUT CHECKING CAREFULY YOUR RESULTS!

19.15 Rhot_gaz_reel_qc

```
Description: Class for real gas state law used with a quasi-compressible fluid.
```

```
See also: loi_etat_gaz_reel_base (19.8)

Usage:
rhoT_gaz_reel_QC bloc
where

• bloc bloc_lecture (3.59): Description.
```

20 loi_fermeture_base

Description: Class for appends fermeture to problem

Keyword Discretize should have already been used to read the object. See also: objet_u (40) loi_fermeture_test (20.1)

Usage:

20.1 Loi_fermeture_test

```
Description: Loi for test only
```

Keyword Discretize should have already been used to read the object.

See also: loi_fermeture_base (20)

```
Usage:
```

```
loi_fermeture_test str
Read str {
     [ coef float]
}
where
```

• coef float: coefficient

21 loi_horaire

Description: to define the movement with a time-dependant law for the solid interface.

```
See also: objet_u (40)

Usage:
loi_horaire str
Read str {

    position n word1 word2 ... wordn
    vitesse n word1 word2 ... wordn
    [rotation n word1 word2 ... wordn]
    [derivee_rotation n word1 word2 ... wordn]
    [verification_derivee int]
```

```
[impr int]
}
where
   • position n word1 word2 ... wordn: Vecteur position
   • vitesse n word1 word2 ... wordn: Vecteur vitesse
   • rotation n word1 word2 ... wordn: Matrice de passage
   • derivee rotation n word1 word2 ... wordn: Derivee matrice de passage
   • verification derivee int
   • impr int: Whether to print output
22
      milieu_base
Description: Basic class for medium (physics properties of medium).
See also: objet_u (40) constituant (22.1) solide (22.13) fluide_base (22.2)
Usage:
milieu_base str
Read str {
     [gravite champ_base]
     [ porosites_champ champ_base]
      [ diametre_hyd_champ champ_base]
     [ porosites porosites]
     [rho champ base]
     [lambda champ_base]
     [cp champ_base]
}
where
   • gravite champ_base (16.1): Gravity field (optional).
   • porosites champ champ base (16.1): The porosity is given at each element and the porosity at
     each face, Psi(face), is calculated by the average of the porosities of the two neighbour elements
     Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
   • diametre_hyd_champ champ_base (16.1): Hydraulic diameter field (optional).
   • porosites porosites (28): Porosities.
   • rho champ_base (16.1): Density (kg.m-3).
   • lambda champ_base (16.1): Conductivity (W.m-1.K-1).
   • cp champ_base (16.1): Specific heat (J.kg-1.K-1).
22.1
       Constituant
Description: Constituent.
See also: milieu_base (22)
```

Usage:

constituant str
Read str {

[coefficient_diffusion champ_base]

```
[is_multi_scalar]
[gravite champ_base]
[porosites_champ champ_base]
[diametre_hyd_champ champ_base]
[porosites porosites]
[rho champ_base]
[lambda champ_base]
[cp champ_base]
}
where
```

- **coefficient_diffusion** *champ_base* (16.1): Constituent diffusion coefficient value (m2.s-1). If a multi-constituent problem is being processed, the diffusivite will be a vectorial and each components will be the diffusion of the constituent.
- is_multi_scalar : Flag to activate the multi_scalar diffusion operator
- gravite champ_base (16.1) for inheritance: Gravity field (optional).
- **porosites_champ** *champ_base* (16.1) for inheritance: The porosity is given at each element and the porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour elements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
- diametre_hyd_champ champ_base (16.1) for inheritance: Hydraulic diameter field (optional).
- porosites porosites (28) for inheritance: Porosities.
- **rho** *champ_base* (16.1) for inheritance: Density (kg.m-3).
- lambda champ_base (16.1) for inheritance: Conductivity (W.m-1.K-1).
- cp champ base (16.1) for inheritance: Specific heat (J.kg-1.K-1).

22.2 Fluide_base

Description: Basic class for fluids.

Keyword Discretize should have already been used to read the object.

See also: milieu base (22) fluide incompressible (22.4) fluide reel base (22.8) fluide dilatable base (22.3)

```
Usage:
```

```
fluide_base str

Read str {

    [indice champ_base]
    [kappa champ_base]
    [gravite champ_base]
    [porosites_champ champ_base]
    [diametre_hyd_champ champ_base]
    [porosites porosites]
    [rho champ_base]
    [lambda champ_base]
    [cp champ_base]
}

where
```

- indice champ_base (16.1): Refractivity of fluid.
- **kappa** *champ_base* (16.1): Absorptivity of fluid (m-1).
- gravite champ_base (16.1) for inheritance: Gravity field (optional).

- **porosites_champ** *champ_base* (16.1) for inheritance: The porosity is given at each element and the porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour elements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
- diametre_hyd_champ champ_base (16.1) for inheritance: Hydraulic diameter field (optional).
- porosites porosites (28) for inheritance: Porosities.
- **rho** *champ_base* (16.1) for inheritance: Density (kg.m-3).
- lambda champ_base (16.1) for inheritance: Conductivity (W.m-1.K-1).
- **cp** *champ_base* (16.1) for inheritance: Specific heat (J.kg-1.K-1).

22.3 Fluide_dilatable_base

Description: Basic class for dilatable fluids.

Keyword Discretize should have already been used to read the object.

See also: fluide_base (22.2) fluide_quasi_compressible (22.6) fluide_weakly_compressible (22.12)

```
Usage:
```

```
fluide_dilatable_base str

Read str {

    [indice champ_base]
    [kappa champ_base]
    [gravite champ_base]
    [porosites_champ champ_base]
    [diametre_hyd_champ champ_base]
    [porosites porosites]
    [rho champ_base]
    [lambda champ_base]
    [cp champ_base]
}
where
```

- indice champ_base (16.1) for inheritance: Refractivity of fluid.
- **kappa** *champ_base* (16.1) for inheritance: Absorptivity of fluid (m-1).
- gravite champ_base (16.1) for inheritance: Gravity field (optional).
- **porosites_champ** *champ_base* (16.1) for inheritance: The porosity is given at each element and the porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour elements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
- diametre_hyd_champ champ_base (16.1) for inheritance: Hydraulic diameter field (optional).
- porosites porosites (28) for inheritance: Porosities.
- **rho** *champ_base* (16.1) for inheritance: Density (kg.m-3).
- lambda champ base (16.1) for inheritance: Conductivity (W.m-1.K-1).
- **cp** *champ_base* (16.1) for inheritance: Specific heat (J.kg-1.K-1).

22.4 Fluide_incompressible

Description: Class for non-compressible fluids.

Keyword Discretize should have already been used to read the object.

```
See also: fluide_base (22.2) fluide_ostwald (22.5)
Usage:
fluide_incompressible str
Read str {
     [beta th champ base]
     [mu champ base]
     [beta_co champ_base]
     [rho champ_base]
     [cp champ base]
     [lambda champ base]
     [ porosites bloc_lecture]
     [indice champ_base]
     [kappa champ_base]
     [gravite champ_base]
     [ porosites_champ champ_base]
     [ diametre_hyd_champ champ_base]
where
   • beta_th champ_base (16.1): Thermal expansion (K-1).
   • mu champ_base (16.1): Dynamic viscosity (kg.m-1.s-1).
   • beta co champ base (16.1): Volume expansion coefficient values in concentration.
   • rho champ_base (16.1): Density (kg.m-3).
   • cp champ_base (16.1): Specific heat (J.kg-1.K-1).
   • lambda champ_base (16.1): Conductivity (W.m-1.K-1).
   • porosites bloc lecture (3.59): Porosity (optional)
   • indice champ base (16.1) for inheritance: Refractivity of fluid.
   • kappa champ_base (16.1) for inheritance: Absorptivity of fluid (m-1).
   • gravite champ_base (16.1) for inheritance: Gravity field (optional).
   • porosites_champ champ_base (16.1) for inheritance: The porosity is given at each element and the
     porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour el-
     ements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
   • diametre_hyd_champ champ_base (16.1) for inheritance: Hydraulic diameter field (optional).
22.5
      Fluide ostwald
Description: Non-Newtonian fluids governed by Ostwald's law. The law applicable to stress tensor is:
tau=K(T)*(D:D/2)**((n-1)/2)*D Where:
D refers to the deformation tensor
K refers to fluid consistency (may be a function of the temperature T)
n refers to the fluid structure index n=1 for a Newtonian fluid, n<1 for a rheofluidifier fluid, n>1 for a
rheothickening fluid.
Keyword Discretize should have already been used to read the object.
See also: fluide_incompressible (22.4)
Usage:
fluide_ostwald str
Read str {
```

[k champ base]

```
[n champ_base]
     [beta_th champ_base]
     [mu champ base]
     [beta_co champ_base]
     [rho champ base]
     [ cp champ_base]
     [lambda champ base]
     [porosites bloc lecture]
     [indice champ base]
     [kappa champ_base]
     [gravite champ_base]
     [ porosites_champ champ_base]
     [ diametre_hyd_champ champ_base]
}
where
   • k champ_base (16.1): Fluid consistency.
   • n champ_base (16.1): Fluid structure index.
   • beta_th champ_base (16.1) for inheritance: Thermal expansion (K-1).
   • mu champ base (16.1) for inheritance: Dynamic viscosity (kg.m-1.s-1).
   • beta_co champ_base (16.1) for inheritance: Volume expansion coefficient values in concentration.
   • rho champ_base (16.1) for inheritance: Density (kg.m-3).
   • cp champ_base (16.1) for inheritance: Specific heat (J.kg-1.K-1).
   • lambda champ_base (16.1) for inheritance: Conductivity (W.m-1.K-1).
   • porosites bloc lecture (3.59) for inheritance: Porosity (optional)
   • indice champ base (16.1) for inheritance: Refractivity of fluid.
   • kappa champ base (16.1) for inheritance: Absorptivity of fluid (m-1).
   • gravite champ_base (16.1) for inheritance: Gravity field (optional).
     porosites_champ champ_base (16.1) for inheritance: The porosity is given at each element and the
     porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour el-
```

• diametre_hyd_champ champ_base (16.1) for inheritance: Hydraulic diameter field (optional).

ements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.

22.6 Fluide_quasi_compressible

Description: Quasi-compressible flow with a low mach number assumption; this means that the thermodynamic pressure (used in state law) is uniform in space.

Keyword Discretize should have already been used to read the object. See also: fluide_dilatable_base (22.3)

Usage: fluide_quasi_compressible str

Read str {

```
[ sutherland bloc_sutherland]
[ pression float]
[ loi_etat loi_etat_base]
[ traitement_pth str into ['edo', 'constant', 'conservation_masse']]
[ traitement_rho_gravite str into ['standard', 'moins_rho_moyen']]
[ temps_debut_prise_en_compte_drho_dt float]
[ omega_relaxation_drho_dt float]
```

```
[lambda champ_base]
[mu champ_base]
[indice champ_base]
[kappa champ_base]
[gravite champ_base]
[porosites_champ champ_base]
[diametre_hyd_champ champ_base]
[porosites porosites]
[rho champ_base]
[cp champ_base]
}
where
```

- sutherland bloc_sutherland (22.7): Sutherland law for viscosity and for conductivity.
- **pression** *float*: Initial thermo-dynamic pressure used in the assosciated state law.
- loi_etat loi_etat_base (19): The state law that will be associated to the Quasi-compressible fluid.
- **traitement_pth** *str into ['edo', 'constant', 'conservation_masse']*: Particular treatment for the thermodynamic pressure Pth; there are three possibilities:
 - 1) with the keyword 'edo' the code computes Pth solving an O.D.E.; in this case, the mass is not strictly conserved (it is the default case for quasi compressible computation):
 - 2) the keyword 'conservation_masse' forces the conservation of the mass (closed geometry or with periodic boundaries condition)
 - 3) the keyword 'constant' makes it possible to have a constant Pth; it's the good choice when the flow is open (e.g. with pressure boundary conditions).
 - It is possible to monitor the volume averaged value for temperature and density, plus Pth evolution in the .evol_glob file.
- traitement_rho_gravite str into ['standard', 'moins_rho_moyen']: It may be :1) standard: the gravity term is evaluated with rho*g (It is the default). 2) moins_rho_moyen: the gravity term is evaluated with (rho-rhomoy) *g. Unknown pressure is then P*=P+rhomoy*g*z. It is useful when you apply uniforme pressure boundary condition like P*=0.
- temps_debut_prise_en_compte_drho_dt *float*: While time<value, dRho/dt is set to zero (Rho, volumic mass). Useful for some calculation during the first time steps with big variation of temperature and volumic mass.
- omega_relaxation_drho_dt *float*: Optional option to have a relaxed algorithm to solve the mass equation. value is used (1 per default) to specify omega.
- lambda champ_base (16.1): Conductivity (W.m-1.K-1).
- mu champ_base (16.1): Dynamic viscosity (kg.m-1.s-1).
- **indice** champ base (16.1) for inheritance: Refractivity of fluid.
- **kappa** champ base (16.1) for inheritance: Absorptivity of fluid (m-1).
- gravite champ_base (16.1) for inheritance: Gravity field (optional).
- **porosites_champ** *champ_base* (16.1) for inheritance: The porosity is given at each element and the porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour elements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
- diametre_hyd_champ champ_base (16.1) for inheritance: Hydraulic diameter field (optional).
- porosites porosites (28) for inheritance: Porosities.
- **rho** *champ_base* (16.1) for inheritance: Density (kg.m-3).
- cp champ_base (16.1) for inheritance: Specific heat (J.kg-1.K-1).

22.7 Bloc sutherland

Description: Sutherland law for viscosity mu(T)=mu0*((T0+C)/(T+C))*(T/T0)**1.5 and (optional) for conductivity lambda(T)=mu0*Cp/Prandtl*((T0+Slambda)/(T+Slambda))*(T/T0)**1.5

```
See also: objet_lecture (39)
Usage:
problem name mu0 mu0 val t0 t0 val [Slambda][s] C c val
where
   • problem name str: Name of problem.
   • mu0 str into ['mu0']
   • mu0_val float
   • t0 str into ['T0']
   • t0_val float
   • Slambda str into ['Slambda']
   • s float
   • C str into ['C']
   • c_val float
22.8
       Fluide_reel_base
Description: Class for real fluids.
Keyword Discretize should have already been used to read the object.
See also: fluide base (22.2) fluide sodium gaz (22.9) fluide stiffened gas (22.11) fluide sodium liquide
(22.10)
Usage:
fluide reel base str
Read str {
     [indice champ_base]
     [kappa champ_base]
     [gravite champ_base]
     [porosites_champ champ_base]
     [ diametre_hyd_champ champ_base]
     [ porosites porosites]
     [rho champ_base]
     [lambda champ_base]
     [cp champ_base]
}
where
   • indice champ base (16.1) for inheritance: Refractivity of fluid.
   • kappa champ_base (16.1) for inheritance: Absorptivity of fluid (m-1).
   • gravite champ_base (16.1) for inheritance: Gravity field (optional).
   • porosites_champ champ_base (16.1) for inheritance: The porosity is given at each element and the
     porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour el-
     ements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
   • diametre_hyd_champ champ_base (16.1) for inheritance: Hydraulic diameter field (optional).
   • porosites porosites (28) for inheritance: Porosities.
   • rho champ_base (16.1) for inheritance: Density (kg.m-3).
   • lambda champ_base (16.1) for inheritance: Conductivity (W.m-1.K-1).
   • cp champ_base (16.1) for inheritance: Specific heat (J.kg-1.K-1).
```

22.9 Fluide_sodium_gaz

} where

```
Description: Class for Fluide_sodium_liquide
Keyword Discretize should have already been used to read the object.
See also: fluide_reel_base (22.8)
Usage:
fluide sodium gaz str
Read str {
     [ P_ref float]
     [ T_ref float]
     [indice champ base]
     [kappa champ_base]
     [gravite champ_base]
     [ porosites_champ champ_base]
     [ diametre_hyd_champ champ_base]
     [ porosites porosites]
     [rho champ_base]
     [lambda champ_base]
     [ cp champ_base]
```

- **P_ref** *float*: Use to set the pressure value in the closure law. If not specified, the value of the pressure unknown will be used
- **T_ref** *float*: Use to set the temperature value in the closure law. If not specified, the value of the temperature unknown will be used
- indice champ base (16.1) for inheritance: Refractivity of fluid.
- **kappa** *champ_base* (16.1) for inheritance: Absorptivity of fluid (m-1).
- gravite champ_base (16.1) for inheritance: Gravity field (optional).
- **porosites_champ** *champ_base* (16.1) for inheritance: The porosity is given at each element and the porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour elements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
- diametre_hyd_champ champ_base (16.1) for inheritance: Hydraulic diameter field (optional).
- porosites porosites (28) for inheritance: Porosities.
- **rho** *champ_base* (16.1) for inheritance: Density (kg.m-3).
- lambda champ_base (16.1) for inheritance: Conductivity (W.m-1.K-1).
- **cp** *champ_base* (16.1) for inheritance: Specific heat (J.kg-1.K-1).

22.10 Fluide_sodium_liquide

```
Description: Class for Fluide_sodium_liquide

Keyword Discretize should have already been used to read the object. See also: fluide_reel_base (22.8)

Usage: fluide_sodium_liquide str

Read str {

[P_ref float]
```

```
[ T_ref float]
[ indice champ_base]
[ kappa champ_base]
[ gravite champ_base]
[ porosites_champ champ_base]
[ diametre_hyd_champ champ_base]
[ porosites porosites]
[ rho champ_base]
[ lambda champ_base]
[ cp champ_base]
]
```

- **P_ref** *float*: Use to set the pressure value in the closure law. If not specified, the value of the pressure unknown will be used
- **T_ref** *float*: Use to set the temperature value in the closure law. If not specified, the value of the temperature unknown will be used
- **indice** *champ_base* (16.1) for inheritance: Refractivity of fluid.
- **kappa** *champ_base* (16.1) for inheritance: Absorptivity of fluid (m-1).
- gravite champ_base (16.1) for inheritance: Gravity field (optional).
- **porosites_champ** *champ_base* (16.1) for inheritance: The porosity is given at each element and the porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour elements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
- diametre hyd champ champ base (16.1) for inheritance: Hydraulic diameter field (optional).
- porosites porosites (28) for inheritance: Porosities.
- **rho** *champ_base* (16.1) for inheritance: Density (kg.m-3).
- lambda champ_base (16.1) for inheritance: Conductivity (W.m-1.K-1).
- cp champ_base (16.1) for inheritance: Specific heat (J.kg-1.K-1).

```
22.11
        Fluide_stiffened_gas
Description: Class for Stiffened Gas
Keyword Discretize should have already been used to read the object.
See also: fluide reel base (22.8)
Usage:
fluide_stiffened_gas str
Read str {
     [gamma float]
     [ pinf float]
     [ mu float]
     [lambda float]
     [ Cv float]
     [ q float]
     [q_prim float]
     [indice champ_base]
     [kappa champ_base]
```

[gravite champ_base]

[porosites_champ champ_base] [diametre_hyd_champ champ_base]

```
[porosites porosites]
     [rho champ_base]
     [lambda champ base]
     [cp champ_base]
}
where
     perfect gases)
```

- gamma float: Heat capacity ratio (Cp/Cv)
- pinf float: Stiffened gas pressure constant (if set to zero, the state law becomes identical to that of
- mu float: Dynamic viscosity
- lambda float: Thermal conductivity
- Cv float: Thermal capacity at constant volume
- q float: Reference energy
- q_prim float: Model constant
- **indice** *champ_base* (16.1) for inheritance: Refractivity of fluid.
- **kappa** *champ_base* (16.1) for inheritance: Absorptivity of fluid (m-1).
- gravite champ_base (16.1) for inheritance: Gravity field (optional).
- porosites_champ champ_base (16.1) for inheritance: The porosity is given at each element and the porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour elements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
- diametre_hyd_champ *champ_base* (16.1) for inheritance: Hydraulic diameter field (optional).
- porosites porosites (28) for inheritance: Porosities.
- **rho** champ base (16.1) for inheritance: Density (kg.m-3).
- **lambda** champ base (16.1) for inheritance: Conductivity (W.m-1.K-1).
- cp champ base (16.1) for inheritance: Specific heat (J.kg-1.K-1).

22.12 Fluide weakly compressible

fluide_weakly_compressible str

Description: Weakly-compressible flow with a low mach number assumption; this means that the thermodynamic pressure (used in state law) can vary in space.

Keyword Discretize should have already been used to read the object. See also: fluide_dilatable_base (22.3)

```
Usage:
```

```
Read str {
     [loi_etat loi_etat_base]
     [sutherland bloc sutherland]
     [traitement_pth str into ['constant']]
     [lambda champ base]
     [mu champ base]
     [ pression thermo float]
     [ pression_xyz champ_base]
     [ use_total_pressure int]
     [ use_hydrostatic_pressure int]
     [ use_grad_pression_eos int]
     [ time_activate_ptot float]
     [indice champ_base]
     [kappa champ_base]
```

```
[ gravite champ_base]
[ porosites_champ champ_base]
[ diametre_hyd_champ champ_base]
[ porosites porosites]
[ rho champ_base]
[ cp champ_base]
}
where
```

- loi etat loi etat base (19): The state law that will be associated to the Weakly-compressible fluid.
- sutherland bloc_sutherland (22.7): Sutherland law for viscosity and for conductivity.
- **traitement_pth** *str into ['constant']*: Particular treatment for the thermodynamic pressure Pth; there is currently one possibility:
 - 1) the keyword 'constant' makes it possible to have a constant Pth but not uniform in space; it's the good choice when the flow is open (e.g. with pressure boundary conditions).
- lambda champ_base (16.1): Conductivity (W.m-1.K-1).
- **mu** champ_base (16.1): Dynamic viscosity (kg.m-1.s-1).
- pression_thermo float: Initial thermo-dynamic pressure used in the assosciated state law.
- **pression_xyz** *champ_base* (16.1): Initial thermo-dynamic pressure used in the assosciated state law. It should be defined with as a Champ_Fonc_xyz.
- **use_total_pressure** *int*: Flag (0 or 1) used to activate and use the total pressure in the assosciated state law. The default value of this Flag is 0.
- use_hydrostatic_pressure *int*: Flag (0 or 1) used to activate and use the hydro-static pressure in the assosciated state law. The default value of this Flag is 0.
- use_grad_pression_eos int: Flag (0 or 1) used to specify whether or not the gradient of the thermodynamic pressure will be taken into account in the source term of the temperature equation (case of a non-uniform pressure). The default value of this Flag is 1 which means that the gradient is used in the source.
- time_activate_ptot float: Time (in seconds) at which the total pressure will be used in the assosciated state law.
- indice champ base (16.1) for inheritance: Refractivity of fluid.
- **kappa** *champ_base* (16.1) for inheritance: Absorptivity of fluid (m-1).
- gravite champ_base (16.1) for inheritance: Gravity field (optional).
- **porosites_champ** *champ_base* (16.1) for inheritance: The porosity is given at each element and the porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour elements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
- diametre hyd champ champ base (16.1) for inheritance: Hydraulic diameter field (optional).
- porosites porosites (28) for inheritance: Porosities.
- **rho** *champ_base* (16.1) for inheritance: Density (kg.m-3).
- **cp** *champ_base* (16.1) for inheritance: Specific heat (J.kg-1.K-1).

22.13 Solide

Description: Solid with cp and/or rho non-uniform.

```
See also: milieu_base (22)

Usage:
solide str
Read str {

[rho champ_base]
```

```
[cp champ_base]
     [lambda champ_base]
     [user field champ base]
     [gravite champ_base]
     [porosites champ champ base]
     [ diametre_hyd_champ champ_base]
     [porosites porosites]
}
where
   • rho champ_base (16.1): Density (kg.m-3).
   • cp champ_base (16.1): Specific heat (J.kg-1.K-1).
   • lambda champ_base (16.1): Conductivity (W.m-1.K-1).
   • user field champ base (16.1): user defined field.
   • gravite champ base (16.1) for inheritance: Gravity field (optional).
```

- porosites champ champ base (16.1) for inheritance: The porosity is given at each element and the porosity at each face, Psi(face), is calculated by the average of the porosities of the two neighbour elements Psi(elem1), Psi(elem2): Psi(face)=2/(1/Psi(elem1)+1/Psi(elem2)). This keyword is optional.
- diametre hyd champ champ base (16.1) for inheritance: Hydraulic diameter field (optional).
- porosites porosites (28) for inheritance: Porosities.

23 modele turbulence scal base

Description: Basic class for turbulence model for energy equation.

```
See also: objet_u (40) schmidt (23.4) null (23.2) prandtl (23.3)
Usage:
modele turbulence scal base str
Read str {
     [ dt impr nusselt float]
     [ dt_impr_nusselt_mean_only dt_impr_nusselt_mean_only]
     [turbulence paroi turbulence paroi scalaire base]
}
where
```

- dt impr nusselt float: Keyword to print local values of Nusselt number and temperature near a wall during a turbulent calculation. The values will be printed in the _Nusselt.face file each dtimpr nusselt time period. The local Nusselt expression is as follows: Nu = ((lambda+lambda-_t)/lambda)*d_wall/d_eq where d_wall is the distance from the first mesh to the wall and d_eq is given by the wall law. This option also gives the value of d eq and h = (lambda+lambda t)/d eq and the fluid temperature of the first mesh near the wall.
 - For the Neumann boundary conditions (flux impose), the «equivalent» wall temperature given by the wall law is also printed (Tparoi equiv.) preceded for VEF calculation by the edge temperature «T face de bord».
- dt_impr_nusselt_mean_only dt_impr_nusselt_mean_only (23.1): This keyword is used to print the mean values of Nusselt (obtained with the wall laws) on each boundary, into a file named datafile-_ProblemName_nusselt_mean_only.out. periode refers to the printing period, this value is expressed in seconds. If you don't use the optional keyword boundaries, all the boundaries will be considered. If you use it, you must specify nb_boundaries which is the number of boundaries on which you want to calculate the mean values, then you have to specify their names.
- turbulence paroi turbulence paroi scalaire base (37): Keyword to set the wall law.

23.1 Dt_impr_nusselt_mean_only

```
Description: not_set

See also: objet_lecture (39)

Usage:
{
    dt_impr float
    [boundaries n word1 word2 ... wordn]
}
where

• dt_impr float
• boundaries n word1 word2 ... wordn
```

23.2 Null

Description: Null scalar turbulence model (turbulent diffusivity = 0) which can be used with a turbulent problem.

```
See also: modele_turbulence_scal_base (23)

Usage:
null str
Read str {

    [dt_impr_nusselt float]
    [dt_impr_nusselt_mean_only dt_impr_nusselt_mean_only]
}
where
```

- **dt_impr_nusselt** *float* for inheritance: Keyword to print local values of Nusselt number and temperature near a wall during a turbulent calculation. The values will be printed in the _Nusselt.face file each dt_impr_nusselt time period. The local Nusselt expression is as follows: Nu = ((lambda+lambda_t)/lambda)*d_wall/d_eq where d_wall is the distance from the first mesh to the wall and d_eq is given by the wall law. This option also gives the value of d_eq and h = (lambda+lambda_t)/d_eq and the fluid temperature of the first mesh near the wall.
 - For the Neumann boundary conditions (flux_impose), the «equivalent» wall temperature given by the wall law is also printed (Tparoi equiv.) preceded for VEF calculation by the edge temperature «T face de bord».
- **dt_impr_nusselt_mean_only** *dt_impr_nusselt_mean_only* (23.1) for inheritance: This keyword is used to print the mean values of Nusselt (obtained with the wall laws) on each boundary, into a file named datafile_ProblemName_nusselt_mean_only.out. periode refers to the printing period, this value is expressed in seconds. If you don't use the optional keyword boundaries, all the boundaries will be considered. If you use it, you must specify nb_boundaries which is the number of boundaries on which you want to calculate the mean values, then you have to specify their names.

23.3 Prandtl

Description: The Prandtl model. For the scalar equations, only the model based on Reynolds analogy is available. If K_Epsilon was selected in the hydraulic equation, Prandtl must be selected for the convection-diffusion temperature equation coupled to the hydraulic equation and Schmidt for the concentration equations.

```
See also: modele_turbulence_scal_base (23)

Usage:

prandtl str

Read str {

    [prdt str]
    [prandt_turbulent_fonction_nu_t_alpha str]
    [dt_impr_nusselt float]
    [dt_impr_nusselt_mean_only dt_impr_nusselt_mean_only]
    [turbulence_paroi turbulence_paroi_scalaire_base]
}

where
```

- **prdt** *str*: Keyword to modify the constant (Prdt) of Prandtl model : Alphat=Nut/Prdt Default value is 0.9
- **prandt_turbulent_fonction_nu_t_alpha** *str*: Optional keyword to specify turbulent diffusivity (by default, alpha_t=nu_t/Prt) with another formulae, for example: alpha_t=nu_t2/(0,7*alpha+0,85*nu_t) with the string nu_t*nu_t/(0,7*alpha+0,85*nu_t) where alpha is the thermal diffusivity.
- **dt_impr_nusselt** *float* for inheritance: Keyword to print local values of Nusselt number and temperature near a wall during a turbulent calculation. The values will be printed in the _Nusselt.face file each dt_impr_nusselt time period. The local Nusselt expression is as follows: Nu = ((lambda+lambda_t)/lambda)*d_wall/d_eq where d_wall is the distance from the first mesh to the wall and d_eq is given by the wall law. This option also gives the value of d_eq and h = (lambda+lambda_t)/d_eq and the fluid temperature of the first mesh near the wall.
 - For the Neumann boundary conditions (flux_impose), the «equivalent» wall temperature given by the wall law is also printed (Tparoi equiv.) preceded for VEF calculation by the edge temperature «T face de bord».
- **dt_impr_nusselt_mean_only** *dt_impr_nusselt_mean_only* (23.1) for inheritance: This keyword is used to print the mean values of Nusselt (obtained with the wall laws) on each boundary, into a file named datafile_ProblemName_nusselt_mean_only.out. periode refers to the printing period, this value is expressed in seconds. If you don't use the optional keyword boundaries, all the boundaries will be considered. If you use it, you must specify nb_boundaries which is the number of boundaries on which you want to calculate the mean values, then you have to specify their names.
- **turbulence_paroi** *turbulence_paroi_scalaire_base* (37) for inheritance: Keyword to set the wall law.

23.4 Schmidt

Description: The Schmidt model. For the scalar equations, only the model based on Reynolds analogy is available. If K_Epsilon was selected in the hydraulic equation, Schmidt must be selected for the convection-diffusion temperature equation coupled to the hydraulic equation and Schmidt for the concentration equations.

```
See also: modele_turbulence_scal_base (23)
```

Usage:

```
schmidt str
Read str {

    [ scturb float]
    [ dt_impr_nusselt float]
    [ dt_impr_nusselt_mean_only dt_impr_nusselt_mean_only]
    [ turbulence_paroi turbulence_paroi_scalaire_base]
}
where
```

- **scturb** *float*: Keyword to modify the constant (Sct) of Schmlidt model : Dt=Nut/Sct Default value is 0.7.
- **dt_impr_nusselt** *float* for inheritance: Keyword to print local values of Nusselt number and temperature near a wall during a turbulent calculation. The values will be printed in the _Nusselt.face file each dt_impr_nusselt time period. The local Nusselt expression is as follows: Nu = ((lambda+lambda_t)/lambda)*d_wall/d_eq where d_wall is the distance from the first mesh to the wall and d_eq is given by the wall law. This option also gives the value of d_eq and h = (lambda+lambda_t)/d_eq and the fluid temperature of the first mesh near the wall.
 - For the Neumann boundary conditions (flux_impose), the «equivalent» wall temperature given by the wall law is also printed (Tparoi equiv.) preceded for VEF calculation by the edge temperature «T face de bord».
- **dt_impr_nusselt_mean_only** *dt_impr_nusselt_mean_only* (23.1) for inheritance: This keyword is used to print the mean values of Nusselt (obtained with the wall laws) on each boundary, into a file named datafile_ProblemName_nusselt_mean_only.out. periode refers to the printing period, this value is expressed in seconds. If you don't use the optional keyword boundaries, all the boundaries will be considered. If you use it, you must specify nb_boundaries which is the number of boundaries on which you want to calculate the mean values, then you have to specify their names.
- **turbulence_paroi** *turbulence_paroi_scalaire_base* (37) for inheritance: Keyword to set the wall law.

24 moyenne_imposee_deriv

```
Description: not_set
```

See also: objet_u (40) profil (24.5) connexion_exacte (24.2) connexion_approchee (24.1) interpolation (24.3) logarithmique (24.4)

Usage:

24.1 Connexion_approchee

Description: To read the imposed field from a file where positions and values are given (it is not necessary that the coordinates of points match the coordinates of the boundary faces, indeed, the nearest point of each face of the boundary will be used).

```
See also: moyenne_imposee_deriv (24)
Usage:
connexion_approchee fichier file1
where
```

• fichier str into ['fichier']

```
• file1 str: filename. The format of the file is: N
    x(1) y(1) [z(1)] valx(1) valy(1) [valz(1)]
    x(2) y(2) [z(2)] valx(2) valy(2) [valz(2)]
    ...
    x(N) y(N) [z(N)] valx(N) valy(N) [valz(N)]
```

24.2 Connexion_exacte

Description: To read the imposed field from two files.

See also: moyenne_imposee_deriv (24)

Usage:

connexion_exacte fichier file1 [file2]
where

- fichier str into ['fichier']
- **file1** *str*: first file, contains the points coordinates (which should be the same as the coordinates of the boundary faces). The format of this file is:

N 1 x(1) y(1) [z(1)] 2 x(2) y(2) [z(2)] ... N x(N) y(N) [z(N)]

• file2 str: second file, contains the mean values. The format of this file is:

N
1 valx(1) valy(1) [valz(1)]
2 valx(2) valy(2) [valz(2)]
...
N valx(N) valy(N) [valz(N)]

24.3 Interpolation

Synonymous: champ_post_interpolation

Description: To create an imposed field built by interpolation of values read from a file. The imposed field is applied on the direction given by the keyword direction_anisotrope (the field is zero for the other directions).

See also: moyenne_imposee_deriv (24)

Usage:

interpolation fichier file1

where

• **fichier** *str into ['fichier']*: The format of the file is: pos(1) val(1)

pos(2) val(2)

pos(N) val(N)

If direction given by direction

-_anisotrope is 1 (or 2 or 3), then pos will be X (or Y or Z) coordinate and val will be X value (or Y value, or Z value) of the imposed field.

• file1 str: name of geom_face_perio

24.4 Logarithmique

```
Description: To specify the imposed field (in this case, velocity) by an analytical logarithmic law of the wall:
```

```
g(x,y,z) = u_t = u^* (log(0.5*diametre*u_t = u_v = v_t = v
```

See also: moyenne_imposee_deriv (24)

Usage:

logarithmique diametre val u_tau val_u_tau visco_cin val_visco_cin direction val_direction where

- diametre str into ['diametre']
- val float: diameter
- **u_tau** str into ['u_tau']
- val_u_tau *float*: value of u_tau
- visco_cin str into ['visco_cin']
- val_visco_cin float: value of visco_cin
- **direction** str into ['direction']
- val direction int: direction

24.5 Profil

Description: To specify analytic profile for the imposed g field.

```
See also: moyenne_imposee_deriv (24)
```

Usage:

profil profile

where

• profile n word1 word2 ... wordn: specifies the analytic profile: 2l3 valx(x,y,z,t) valy(x,y,z,t) [valz(x,y,z,t)]

25 nom

Description: Class to name the TRUST objects.

```
See also: objet_u (40) nom_anonyme (25.1)
```

Usage:

nom [mot]

where

• mot str: Chain of characters.

25.1 Nom_anonyme

```
Description: not_set

See also: nom (25)

Usage:
[ mot ]
where
```

• mot str: Chain of characters.

26 partitionneur_deriv

```
Description: not_set
```

See also: objet_u (40) metis (26.3) fichier_med (26.1) sous_dom (26.5) partition (26.4) union (26.8) tranche (26.7) sous_zones (26.6) fichier_decoupage (26.2)

Usage:

```
partitionneur_deriv str
Read str {
      [nb_parts int]
}
where
```

• **nb_parts** *int*: The number of non empty parts that must be generated (generally equal to the number of processors in the parallel run).

26.1 Fichier_med

Description: Partitioning a domain using a MED file containing an integer field providing for each element the processor number on which the element should be located.

See also: partitionneur_deriv (26)

```
Usage:
fichier_med str

Read str {

file str

[ field str]

[ nb_parts int]
}
```

where

- file str: file name of the MED file to load
 - field str: field name of the integer (or double) field to load
 - **nb_parts** *int* for inheritance: The number of non empty parts that must be generated (generally equal to the number of processors in the parallel run).

26.2 Fichier_decoupage

Description: This algorithm reads an array of integer values on the disc, one value for each mesh element. Each value is interpreted as the target part number n>=0 for this element. The number of parts created is the highest value in the array plus one. Empty parts can be created if some values are not present in the array.

The file format is ASCII, and contains space, tab or carriage-return separated integer values. The first value is the number nb_elem of elements in the domain, followed by nb_elem integer values (positive or zero). This algorithm has been designed to work together with the 'ecrire_decoupage' option. You can generate a partition with any other algorithm, write it to disc, modify it, and read it again to generate the .Zone files. Contrary to other partitioning algorithms, no correction is applied by default to the partition (eg. element 0 on processor 0 and corrections for periodic boundaries). If 'corriger_partition' is specified, these corrections are applied.

See also: partitionneur_deriv (26)

```
Usage:
fichier_decoupage str

Read str {
fichier str
[corriger_partition]
[nb_parts int]
}
where
```

- fichier str: File name
- corriger partition
- **nb_parts** *int* for inheritance: The number of non empty parts that must be generated (generally equal to the number of processors in the parallel run).

26.3 Metis

where

Description: Metis is an external partitionning library. It is a general algorithm that will generate a partition of the domain.

See also: partitionneur_deriv (26)

Usage:
metis str
Read str {
 [kmetis]
 [use_weights]
 [nb_parts int]

}

• **kmetis**: The default values are pmetis, default parameters are automatically chosen by Metis. 'kmetis' is faster than pmetis option but the last option produces better partitioning quality. In both cases, the partitioning quality may be slightly improved by increasing the nb_essais option (by default N=1). It will compute N partitions and will keep the best one (smallest edge cut number). But this option is CPU expensive, taking N=10 will multiply the CPU cost of partitioning by 10. Experiments show that only marginal improvements can be obtained with non default parameters.

- use_weights: If use_weights is specified, weighting of the element-element links in the graph is used to force metis to keep opposite periodic elements on the same processor. This option can slightly improve the partitionning quality but it consumes more memory and takes more time. It is not mandatory since a correction algorithm is always applied afterwards to ensure a correct partitionning for periodic boundaries.
- **nb_parts** *int* for inheritance: The number of non empty parts that must be generated (generally equal to the number of processors in the parallel run).

26.4 Partition

Synonymous: decouper

Description: This algorithm re-use the partition of the domain named DOMAINE_NAME. It is useful to partition for example a post processing domain. The partition should match with the calculation domain.

See also: partitionneur_deriv (26)

```
Usage:
partition str
Read str {
    domaine str
    [nb_parts int]
}
where
```

- domaine str: domain name
- **nb_parts** *int* for inheritance: The number of non empty parts that must be generated (generally equal to the number of processors in the parallel run).

26.5 Sous dom

Description: Given a global partition of a global domain, 'sous-domaine' allows to produce a conform partition of a sub-domain generated from the bigger one using the keyword create_domain_from_sub_domain. The sub-domain will be partitionned in a conform fashion with the global domain.

See also: partitionneur deriv (26)

```
Usage:
sous_dom str
Read str {
fichier str
[fichier_ssz str]
[name_ssz str]
[nb_parts int]
}
where
```

- fichier str: fichier
- fichier_ssz str: fichier sous zonne
- name_ssz str: nom sous zonne
- **nb_parts** *int* for inheritance: The number of non empty parts that must be generated (generally equal to the number of processors in the parallel run).

26.6 Sous_zones

Description: This algorithm will create one part for each specified subdomaine/domain. All elements contained in the first subdomaine/domain are put in the first part, all remaining elements contained in the second subdomaine/domain in the second part, etc...

If all elements of the current domain are contained in the specified subdomaines/domain, then N parts are created, otherwise, a supplemental part is created with the remaining elements.

If no subdomaine is specified, all subdomaines defined in the domain are used to split the mesh.

```
See also: partitionneur_deriv (26)

Usage:
sous_zones str

Read str {

    [sous_zones n word1 word2 ... wordn]
    [domaines n word1 word2 ... wordn]
    [nb_parts int]
}
where
```

- sous zones n word1 word2 ... wordn: N SUBZONE NAME 1 SUBZONE NAME 2 ...
- **domaines** *n word1 word2 ... wordn*: N DOMAIN_NAME_1 DOMAIN_NAME_2 ...
- **nb_parts** *int* for inheritance: The number of non empty parts that must be generated (generally equal to the number of processors in the parallel run).

26.7 Tranche

Description: This algorithm will create a geometrical partitionning by slicing the mesh in the two or three axis directions, based on the geometric center of each mesh element. nz must be given if dimension=3. Each slice contains the same number of elements (slices don't have the same geometrical width, and for VDF meshes, slice boundaries are generally not flat except if the number of mesh elements in each direction is an exact multiple of the number of slices). First, nx slices in the X direction are created, then each slice is split in ny slices in the Y direction, and finally, each part is split in nz slices in the Z direction. The resulting number of parts is nx*ny*nz. If one particular direction has been declared periodic, the default slicing (0, 1, 2, ..., n-1) is replaced by (0, 1, 2, ... n-1, 0), each of the two '0' slices having twice less elements than the other slices.

```
See also: partitionneur_deriv (26)

Usage:
tranche str
Read str {
    [tranches n1 n2 (n3)]
    [nb_parts int]
}
where
```

- **tranches** *n1 n2 (n3)*: Partitioned by nx in the X direction, ny in the Y direction, nz in the Z direction. Works only for structured meshes. No warranty for unstructured meshes.
- **nb_parts** *int* for inheritance: The number of non empty parts that must be generated (generally equal to the number of processors in the parallel run).

26.8 Union

Description: Let several local domains be generated from a bigger one using the keyword create_domain_from_sub_domain, and let their partitions be generated in the usual way. Provided the list of partition files for each small domain, the keyword 'union' will partition the global domain in a conform fashion with the smaller domains.

See also: partitionneur_deriv (26)

Usage:
union liste [nb_parts]
where

- **liste** *bloc_lecture* (3.59): List of the partition files with the following syntaxe: {sous_domaine1 decoupage1 ... sous_domaineim decoupageim } where sous_domaine1 ... sous_zomeim are small domains names and decoupage1 ... decoupageim are partition files.
- **nb_parts** *int*: The number of non empty parts that must be generated (generally equal to the number of processors in the parallel run).

27 pb_champ_evaluateur

Description: specifies problem name, the field name beloging to the problem and number of field components.

See also: objet u (40)

Usage:

pb champ ncomp

where

- **pb** *str*: name of the problem where the source fields will be searched.
- champ str: name of the field
- ncomp int: number of components

28 porosites

Description: To define the volume porosity and surface porosity that are uniform in every direction in space on a sub-area.

Porosity was only usable in VDF discretization, and now available for VEF P1NC/P0.

Observations:

- Surface porosity values must be given in every direction in space (set this value to 1 if there is no porosity),
- Prior to defining porosity, the problem must have been discretized.

Can 't be used in VEF discretization, use Porosites_champ instead.

See also: objet_u (40)

Usage:

porosites aco sous_zone1|sous_zone bloc [sous_zone2][bloc2] acof where

- aco str into ['{'}]: Opening curly bracket.
- sous_zone1|sous_zone str: Name of the sub-area to which porosity are allocated.

```
• bloc bloc_lecture_poro (28.1): Surface and volume porosity values.
```

- sous_zone2 str: Name of the 2nd sub-area to which porosity are allocated.
- **bloc2** *bloc_lecture_poro* (28.1): *Surface and volume porosity values.*
- acof str into ['}']: Closing curly bracket.

28.1 Bloc_lecture_poro

```
Description: Surface and volume porosity values.
```

```
See also: objet_lecture (39)

Usage:
{

volumique float
surfacique n x1 x2 ... xn
}
where
```

- volumique float: Volume porosity value.
- **surfacique** n x1 x2 ... xn: Surface porosity values (in X, Y, Z directions).

29 precond_base

Description: Basic class for preconditioning.

```
See also: objet_u (40) ilu (29.1) ssor_bloc (29.4) precondsolv (29.2) ssor (29.3)
```

Usage:

where

29.1 Ilu

Description: This preconditionner can be only used with the generic GEN solver.

```
See also: precond_base (29)

Usage:
ilu str

Read str {

[ type int]

[ filling int]
}
```

- type *int*: values can be 0|1|2|3 for null|left|right|left-and-right preconditionning (default value = 2)
- **filling** *int*: default value = 1.

```
29.2 Precondsolv
```

• alpha_a float

```
Description: not_set
See also: precond_base (29)
Usage:
precondsolv solveur
where
   • solveur solveur_sys_base (11.16): Solver type.
29.3 Ssor
Description: Symmetric successive over-relaxation algorithm.
See also: precond_base (29)
Usage:
ssor str
Read str {
     [ omega float]
where
   • omega float: Over-relaxation facteur (between 1 and 2, default value 1.6).
29.4 Ssor_bloc
Description: not_set
See also: precond_base (29)
Usage:
ssor_bloc str
Read str {
     [ precond0 precond_base]
     [ precond1 precond_base]
     [ preconda precond_base]
     [ alpha_0 float]
     [ alpha_1 float]
     [ alpha_a float]
}
where
   • precond0 precond_base (29)
   • precond1 precond_base (29)
   • preconda precond_base (29)
   • alpha_0 float
   • alpha_1 float
```

30 preconditionneur_petsc_deriv

Description: Preconditioners available with petsc solvers

See also: objet_u (40) diag (30.6) c-amg (30.5) sa-amg (30.11) BLOCK_JACOBI_ICC (30.1) boomeramg (30.4) null (30.9) lu (30.8) jacobi (30.7) EISENTAT (30.2) ssor (30.13) block_jacobi_ilu (30.3) spai (30.12) pilut (30.10)

Usage:

30.1 Block_jacobi_icc

Description: Incomplete Cholesky factorization for symmetric matrix with the PETSc implementation.

See also: preconditionneur_petsc_deriv (30)

```
Usage:
```

```
BLOCK_JACOBI_ICC str

Read str {

    [level int]
    [ordering str into ['natural', 'rcm']]
}
where
```

- **level** *int*: factorization level (default value, 1). In parallel, the factorization is done by block (one per processor by default).
- **ordering** *str into* ['natural', 'rcm']: The ordering of the local matrix is natural by default, but rcm ordering, which reduces the bandwith of the local matrix, may interestingly improves the quality of the decomposition and reduces the number of iterations.

30.2 Eisentat

Description: SSOR version with Eisenstat trick which reduces the number of computations and thus CPU cost...

See also: preconditionneur_petsc_deriv (30)

Usage:

```
EISENTAT str
Read str {
    [ omega float]
}
where
```

• omega float: relaxation factor

```
30.3 Block_jacobi_ilu
```

```
Description: preconditionner
See also: preconditionneur_petsc_deriv (30)
Usage:
block_jacobi_ilu str
Read str {
     [level int]
where
   • level int
30.4
       Boomeramg
Description: Multigrid preconditioner (no option is available yet, look at CLI command and Petsc docu-
mentation to try other options).
See also: preconditionneur_petsc_deriv (30)
Usage:
30.5 C-amg
Description: preconditionner
See also: preconditionneur_petsc_deriv (30)
Usage:
30.6 Diag
Description: Diagonal (Jacobi) preconditioner.
See also: preconditionneur_petsc_deriv (30)
Usage:
30.7
       Jacobi
Description: preconditionner
See also: preconditionneur_petsc_deriv (30)
Usage:
30.8 Lu
Description: preconditionner
```

See also: preconditionneur_petsc_deriv (30)

```
Usage:
30.9 Null
Description: No preconditioner used
See also: preconditionneur_petsc_deriv (30)
Usage:
30.10 Pilut
Description: Dual Threashold Incomplete LU factorization.
See also: preconditionneur_petsc_deriv (30)
Usage:
pilut str
Read str {
     [level int]
     [ epsilon float]
}
where
   • level int: factorization level
   • epsilon float: drop tolerance
30.11 Sa-amg
Description: preconditionner
See also: preconditionneur_petsc_deriv (30)
Usage:
30.12
        Spai
Description: Spai Approximate Inverse algorithm from Parasails Hypre library.
See also: preconditionneur_petsc_deriv (30)
Usage:
spai str
Read str {
     [level int]
     [ epsilon float]
}
where
   • level int: first parameter
```

• epsilon *float*: second parameter

30.13 Ssor

Description: Symmetric Successive Over Relaxation algorithm.

• omega float: relaxation factor (default value, 1.5)

```
See also: preconditionneur_petsc_deriv (30)

Usage:
ssor str
Read str {
    [omega float]
}
where
```

31 schema_temps_base

Description: Basic class for time schemes. This scheme will be associated with a problem and the equations of this problem.

See also: objet_u (40) Sch_CN_iteratif (31.2) schema_implicite_base (31.20) runge_kutta_ordre_2 (31.5) runge_kutta_ordre_3 (31.7) runge_kutta_ordre_4_d3p (31.9) runge_kutta_rationnel_ordre_2 (31.12) schema_predictor_corrector (31.21) runge_kutta_ordre_2_classique (31.6) runge_kutta_ordre_3_classique (31.8) runge_kutta_ordre_4_classique (31.10) runge_kutta_ordre_4_classique_3_8 (31.11) scheme_euler_explicit (31.3) leap_frog (31.4) schema_adams_bashforth_order_2 (31.13) schema_adams_bashforth_order_3 (31.14)

Usage:

```
schema_temps_base str
Read str {
     [tinit float]
     [tmax float]
     [tcpumax float]
     [ dt_min float]
     [ dt_max str]
     [ dt sauv float]
     [ nb_sauv_max int]
     [ dt_impr float]
     [facsec str]
     [ seuil_statio float]
     [residuals residuals]
     [ diffusion implicite int]
     [ seuil_diffusion_implicite float]
     [impr diffusion implicite int]
     [ impr_extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
     [ no_conv_subiteration_diffusion_implicite int]
     [ dt_start dt_start]
     [ nb_pas_dt_max int]
     [ niter_max_diffusion_implicite int]
     [ precision_impr int]
     [ periode_sauvegarde_securite_en_heures float]
     [ no_check_disk_space ]
```

```
[ disable_progress ]
    [ disable_dt_ev ]
    [ gnuplot_header int]
}
where
```

- tinit *float*: Value of initial calculation time (0 by default).
- tmax *float*: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float*: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float*: Minimum calculation time step (1e-16s by default).
- **dt_max** *str*: Maximum calculation time step as function of time (1e30s by default).
- dt_sauv float: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int*: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float*: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str*: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5. Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- **seuil_statio** *float*: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107): To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- diffusion_implicite int: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float*: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int*: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int
- no_conv_subiteration_diffusion_implicite int
- **dt_start** *dt_start* (11.7): dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.

- **nb_pas_dt_max** *int*: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int*: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int*: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- periode_sauvegarde_securite_en_heures *float*: To change the default period (23 hours) between the save of the fields in .sauv file.
- no_check_disk_space: To disable the check of the available amount of disk space during the calculation.
- **disable progress**: To disable the writing of the .progress file.
- **disable_dt_ev**: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int*: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.1 Sch_cn_ex_iteratif

Description: This keyword also describes a Crank-Nicholson method of second order accuracy but here, for scalars, because of instablities encountered when dt>dt_CFL, the Crank Nicholson scheme is not applied to scalar quantities. Scalars are treated according to Euler-Explicite scheme at the end of the CN treatment for velocity flow fields (by doing p Euler explicite under-iterations at dt<=dt_CFL). Parameters are the sames (but default values may change) compare to the Sch_CN_iterative scheme plus a relaxation keyword: niter_min (2 by default), niter_max (6 by default), niter_avg (3 by default), facsec_max (20 by default), seuil (0.05 by default)

```
See also: Sch_CN_iteratif (31.2)
Usage:
Sch_CN_EX_iteratif str
Read str {
     [ omega float]
     [seuil float]
     [ niter_min int]
     [ niter_max int]
      [ niter_avg int]
     [ facsec_max float]
     [tinit float]
     [tmax float]
      [tcpumax float]
     [ dt_min float]
     [dt max str]
     [ dt_sauv float]
     [ nb sauv max int]
     [ dt_impr float]
     [facsec str]
     [ seuil_statio float]
     [residuals residuals]
     [ diffusion implicite int]
     [ seuil_diffusion_implicite float]
     [ impr_diffusion_implicite int]
     [ impr_extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
     [ no_conv_subiteration_diffusion_implicite int]
```

```
[ dt_start dt_start]
  [ nb_pas_dt_max int]
  [ niter_max_diffusion_implicite int]
  [ precision_impr int]
  [ periode_sauvegarde_securite_en_heures float]
  [ no_check_disk_space ]
  [ disable_progress ]
  [ disable_dt_ev ]
  [ gnuplot_header int]
}
where
```

- omega *float*: relaxation factor (0.1 by default)
- **seuil** *float* for inheritance: criteria for ending iterative process (Max(|| u(p) u(p-1)||/Max || u(p) ||) < seuil) (0.001 by default)
- **niter_min** *int* for inheritance: minimal number of p-iterations to satisfy convergence criteria (2 by default)
- **niter_max** *int* for inheritance: number of maximum p-iterations allowed to satisfy convergence criteria (6 by default)
- **niter_avg** *int* for inheritance: threshold of p-iterations (3 by default). If the number of p-iterations is greater than niter_avg, facsec is reduced, if lesser than niter_avg, facsec is increased (but limited by the facsec max value).
- **facsec_max** *float* for inheritance: maximum ratio allowed between dynamical time step returned by iterative process and stability time returned by CFL condition (2 by default).
- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax float for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- dt_min float for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- dt_sauv float for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the out file
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).

- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- niter_max_diffusion_implicite int for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- **no_check_disk_space** for inheritance: To disable the check of the available amount of disk space during the calculation.
- **disable_progress** for inheritance: To disable the writing of the .progress file.
- **disable_dt_ev** for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.2 Sch cn iteratif

Description: The Crank-Nicholson method of second order accuracy. A mid-point rule formulation is used (Euler-centered scheme). The basic scheme is:

$$u(t+1) = u(t) + \frac{du}{dt}(t+1/2) * dt$$

The estimation of the time derivative du/dt at the level (t+1/2) is obtained either by iterative process. The time derivative du/dt at the level (t+1/2) is calculated iteratively with a simple under-relaxations method. Since the method is implicit, neither the cfl nor the fourier stability criteria must be respected. The time step is calculated in a way that the iterative procedure converges with the less iterations as possible.

Remark: for stationary or RANS calculations, no limitation can be given for time step through high value of facsec_max parameter (for instance: facsec_max 1000). In counterpart, for LES calculations, high values of facsec_max may engender numerical instabilities.

See also: schema_temps_base (31) Sch_CN_EX_iteratif (31.1)

Usage:

```
Sch_CN_iteratif str
Read str {
      [seuil float]
      [ niter_min int]
      [ niter max int]
      [ niter avg int]
      [facsec_max float]
      [tinit float]
      [tmax float]
      [tcpumax float]
      [ dt_min float]
      \begin{bmatrix} dt_{max} & str \end{bmatrix}
      [ dt_sauv float]
      [ nb_sauv_max int]
      [ dt_impr float]
      [facsec str]
      [ seuil statio float]
      [residuals residuals]
      [ diffusion implicite int]
      [ seuil diffusion implicite float]
      [ impr_diffusion_implicite int]
      [impr extremums int]
      [ no_error_if_not_converged_diffusion_implicite int]
      [ no_conv_subiteration_diffusion_implicite int]
      [ dt_start dt_start]
      [ nb_pas_dt_max int]
      [ niter_max_diffusion_implicite int]
      [ precision_impr int]
      [ periode_sauvegarde_securite_en_heures | float]
      [ no_check_disk_space ]
      [ disable_progress ]
      [disable dt ev ]
      [ gnuplot_header int]
}
where
```

- seuil *float*: criteria for ending iterative process (Max($\| u(p) u(p-1)\|$ /Max $\| u(p) \|$) < seuil) (0.001 by default)
- niter_min int: minimal number of p-iterations to satisfy convergence criteria (2 by default)
- **niter_max** *int*: number of maximum p-iterations allowed to satisfy convergence criteria (6 by default)
- **niter_avg** *int*: threshold of p-iterations (3 by default). If the number of p-iterations is greater than niter_avg, facsec is reduced, if lesser than niter_avg, facsec is increased (but limited by the facsec_max value).
- **facsec_max** *float*: maximum ratio allowed between dynamical time step returned by iterative process and stability time returned by CFL condition (2 by default).
- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax float for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- dt min float for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).

- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the out file
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no conv subiteration diffusion implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- **nb pas dt max** *int* for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- **no_check_disk_space** for inheritance: To disable the check of the available amount of disk space during the calculation.

- disable_progress for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.3 Scheme_euler_explicit

```
Synonymous: schema_euler_explicite
Description: This is the Euler explicit scheme.
See also: schema temps base (31)
Usage:
scheme_euler_explicit str
Read str {
      [tinit float]
      [tmax float]
      [tcpumax float]
      [ dt_min float]
      \begin{bmatrix} dt_{max} & str \end{bmatrix}
      [ dt_sauv float]
      [ nb_sauv_max int]
      [ dt_impr float]
      [facsec str]
      [ seuil_statio float]
      [residuals residuals]
      [ diffusion_implicite int]
      [ seuil_diffusion_implicite float]
      [impr diffusion implicite int]
      [ impr_extremums int]
      [ no_error_if_not_converged_diffusion_implicite int]
      [ no_conv_subiteration_diffusion_implicite int]
      [ dt_start dt_start]
      [ nb_pas_dt_max int]
      [ niter_max_diffusion_implicite int]
      [ precision_impr int]
      [ periode_sauvegarde_securite_en_heures float]
      [ no_check_disk_space ]
      [ disable_progress ]
      [ disable_dt_ev ]
      [gnuplot header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax float for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).

- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the out file
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no conv subiteration diffusion implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb pas dt max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- **no_check_disk_space** for inheritance: To disable the check of the available amount of disk space during the calculation.

- **disable_progress** for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- gnuplot_header int for inheritance: Optional keyword to modify the header of the .out files. Allows
 to use the column title instead of columns number.

31.4 Leap_frog

```
Description: This is the leap-frog scheme.
```

```
See also: schema_temps_base (31)
Usage:
leap_frog str
Read str {
     [tinit float]
      [tmax float]
     [tcpumax float]
     [ dt_min float]
      [\mathbf{dt}_{\mathbf{max}} \ str]
      [ dt_sauv float]
      [ nb_sauv_max int]
     [ dt_impr float]
      [facsec str]
     [ seuil_statio float]
     [residuals residuals]
     [ diffusion implicite int]
      [ seuil diffusion implicite float]
     [ impr_diffusion_implicite int]
     [impr extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
      [ no conv subiteration diffusion implicite int]
      [ dt_start dt_start]
     [ nb_pas_dt_max int]
     [ niter_max_diffusion_implicite int]
     [ precision_impr int]
     [ periode_sauvegarde_securite_en_heures float]
     [ no_check_disk_space ]
      [ disable_progress ]
     [ disable_dt_ev ]
     [gnuplot_header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).

- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema-Adams Bashforth order 3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- **no_check_disk_space** for inheritance: To disable the check of the available amount of disk space during the calculation.
- **disable_progress** for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.5 Runge_kutta_ordre_2

Description: This is a low-storage Runge-Kutta scheme of second order that uses 2 integration points. The method is presented by Williamson (case 1) in https://www.sciencedirect.com/science/article/pii/0021999180900339

```
See also: schema_temps_base (31)
Usage:
runge kutta ordre 2 str
Read str {
      [tinit float]
      [tmax float]
      [tcpumax float]
      [ dt_min float]
      \begin{bmatrix} dt_{max} & str \end{bmatrix}
      [ dt_sauv float]
      [ nb_sauv_max int]
      [ dt_impr float]
      [facsec str]
      [seuil statio float]
      [residuals residuals]
      [ diffusion implicite int]
      [ seuil_diffusion_implicite float]
      [impr diffusion implicite int]
      [impr extremums int]
      [ no error if not converged diffusion implicite int]
      [ no_conv_subiteration_diffusion_implicite int]
      [ dt start dt start]
      [ nb_pas_dt_max int]
      [ niter_max_diffusion_implicite int]
      [ precision_impr int]
      [ periode_sauvegarde_securite_en_heures float]
      [ no_check_disk_space ]
      [ disable_progress ]
      [ disable_dt_ev ]
      [ gnuplot_header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones

- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- seuil_statio float for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- diffusion_implicite int for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- no_check_disk_space for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.6 Runge_kutta_ordre_2_classique

Description: This is a classical Runge-Kutta scheme of second order that uses 2 integration points.

```
See also: schema temps base (31)
Usage:
runge kutta ordre 2 classique str
Read str {
     [tinit float]
     [tmax float]
     [tcpumax float]
     [ dt_min float]
     [\mathbf{dt}_{\mathbf{max}} \ str]
     [ dt_sauv float]
     [ nb_sauv_max int]
     [ dt_impr float]
     [facsec str]
     [ seuil_statio float]
     [residuals residuals]
     [ diffusion_implicite int]
     [ seuil diffusion implicite float]
     [impr diffusion implicite int]
     [impr extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
     [ no_conv_subiteration_diffusion_implicite int]
     [ dt_start dt_start]
     [ nb pas dt max int]
     [ niter_max_diffusion_implicite int]
     [ precision_impr int]
     [ periode_sauvegarde_securite_en_heures | float]
     [ no_check_disk_space ]
     [ disable_progress ]
     [disable dt ev ]
     [gnuplot header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones

- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- no_check_disk_space for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.7 Runge_kutta_ordre_3

See also: schema_temps_base (31)

Description: This is a low-storage Runge-Kutta scheme of third order that uses 3 integration points. The method is presented by Williamson (case 7) in https://www.sciencedirect.com/science/article/pii/0021999180900339

```
Usage:
runge kutta ordre 3 str
Read str {
      [tinit float]
      [tmax float]
      [tcpumax float]
      [ dt_min float]
      \begin{bmatrix} dt_{max} & str \end{bmatrix}
      [ dt_sauv float]
      [ nb_sauv_max int]
      [ dt_impr float]
      [facsec str]
      [seuil statio float]
      [residuals residuals]
      [ diffusion implicite int]
      [ seuil_diffusion_implicite float]
      [impr diffusion implicite int]
      [impr extremums int]
      [ no error if not converged diffusion implicite int]
      [ no_conv_subiteration_diffusion_implicite int]
      [ dt start dt start]
      [ nb_pas_dt_max int]
      [ niter_max_diffusion_implicite int]
      [ precision_impr int]
      [ periode_sauvegarde_securite_en_heures float]
      [ no_check_disk_space ]
      [ disable_progress ]
      [ disable_dt_ev ]
      [ gnuplot_header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones

- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- no_check_disk_space for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.8 Runge_kutta_ordre_3_classique

Description: This is a classical Runge-Kutta scheme of third order that uses 3 integration points.

```
See also: schema temps base (31)
Usage:
runge kutta ordre 3 classique str
Read str {
     [tinit float]
      [tmax float]
     [tcpumax float]
     [ dt_min float]
      [\mathbf{dt}_{\mathbf{max}} \ str]
     [ dt_sauv float]
     [ nb_sauv_max int]
     [ dt_impr float]
     [facsec str]
     [ seuil_statio float]
     [residuals residuals]
     [ diffusion_implicite int]
      [ seuil diffusion implicite float]
     [impr diffusion implicite int]
     [impr extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
      [ no_conv_subiteration_diffusion_implicite int]
     [ dt_start dt_start]
     [ nb pas dt max int]
      [ niter_max_diffusion_implicite int]
      [ precision_impr int]
      [ periode_sauvegarde_securite_en_heures | float]
     [ no_check_disk_space ]
     [ disable_progress ]
     [disable dt ev ]
     [gnuplot header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- nb_sauv_max int for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones

- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema-Adams Bashforth order 3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- diffusion_implicite int for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- no_check_disk_space for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.9 Runge_kutta_ordre_4_d3p

Synonymous: runge_kutta_ordre_4

Description: This is a low-storage Runge-Kutta scheme of fourth order that uses 3 integration points. The method is presented by Williamson (case 17) in https://www.sciencedirect.com/science/article/pii/0021999180900339

```
See also: schema temps base (31)
Usage:
runge_kutta_ordre_4_d3p str
Read str {
     [tinit float]
     [tmax float]
     [tcpumax float]
     [ dt_min float]
     [\mathbf{dt} \ \mathbf{max} \ \mathit{str}]
     [dt sauv float]
     [ nb_sauv_max int]
     [dt impr float]
     [ facsec str]
     [ seuil statio float]
     [residuals residuals]
     [ diffusion implicite int]
     [ seuil_diffusion_implicite float]
      [ impr_diffusion_implicite int]
     [ impr_extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
      [ no_conv_subiteration_diffusion_implicite int]
      [ dt_start dt_start]
     [ nb_pas_dt_max int]
     [ niter_max_diffusion_implicite int]
     [ precision_impr int]
     [ periode sauvegarde securite en heures float]
     [ no check disk space ]
     [disable progress]
     [disable dt ev ]
     [ gnuplot_header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax float for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- dt min float for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with

- parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- **nb pas dt max** int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- **no_check_disk_space** for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.10 Runge_kutta_ordre_4_classique

Description: This is a classical Runge-Kutta scheme of fourth order that uses 4 integration points.

```
See also: schema temps base (31)
Usage:
runge kutta ordre 4 classique str
Read str {
     [tinit float]
     [tmax float]
     [tcpumax float]
     [ dt_min float]
     [dt_max str]
     [ dt_sauv float]
     [ nb_sauv_max int]
     [ dt_impr float]
     [facsec str]
     [ seuil_statio float]
     [residuals residuals]
     [ diffusion_implicite int]
     [ seuil diffusion implicite float]
     [impr diffusion implicite int]
     [impr extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
     [ no_conv_subiteration_diffusion_implicite int]
     [ dt_start dt_start]
     [ nb pas dt max int]
     [ niter_max_diffusion_implicite int]
     [ precision_impr int]
     [ periode_sauvegarde_securite_en_heures | float]
     [ no_check_disk_space ]
     [ disable_progress ]
     [disable dt ev ]
     [gnuplot header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- **dt_max** str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- nb_sauv_max int for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones

- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the out file
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- no_check_disk_space for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.11 Runge_kutta_ordre_4_classique_3_8

Description: This is a classical Runge-Kutta scheme of fourth order that uses 4 integration points and the 3/8 rule.

```
See also: schema_temps_base (31)
Usage:
runge kutta ordre 4 classique 3 8 str
Read str {
      [tinit float]
      [tmax float]
      [tcpumax float]
      [ dt_min float]
      \begin{bmatrix} dt_{max} & str \end{bmatrix}
      [ dt_sauv float]
      [ nb_sauv_max int]
      [ dt_impr float]
      [facsec str]
      [seuil statio float]
      [residuals residuals]
      [ diffusion implicite int]
      [ seuil_diffusion_implicite float]
      [impr diffusion implicite int]
      [impr extremums int]
      [ no error if not converged diffusion implicite int]
      [ no_conv_subiteration_diffusion_implicite int]
      [ dt start dt start]
      [ nb_pas_dt_max int]
      [ niter max diffusion implicite int]
      [ precision_impr int]
      [ periode_sauvegarde_securite_en_heures float]
      [ no_check_disk_space ]
      [ disable_progress ]
      [ disable_dt_ev ]
      [ gnuplot_header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones

- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the out file
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- seuil_statio float for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- diffusion_implicite int for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- no_check_disk_space for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.12 Runge_kutta_rationnel_ordre_2

Description: This is the Runge-Kutta rational scheme of second order. The method is described in the note: Wambeck - Rational Runge-Kutta methods for solving systems of ordinary differential equations, at the link: https://link.springer.com/article/10.1007/BF02252381. Although rational methods require more computational work than linear ones, they can have some other properties, such as a stable behaviour with explicitness, which make them preferable. The CFD application of this RRK2 scheme is described in the note: https://link.springer.com/content/pdf/10.1007%2F3-540-13917-6 112.pdf.

```
See also: schema_temps_base (31)
Usage:
runge_kutta_rationnel_ordre_2 str
Read str {
     [tinit float]
     [tmax float]
     [tcpumax float]
     [ dt min float]
     [ dt_max str]
     [ dt sauv float]
     [ nb_sauv_max int]
     [ dt impr float]
     [facsec str]
     [ seuil_statio float]
     [residuals residuals]
     [ diffusion_implicite int]
     [ seuil_diffusion_implicite float]
     [ impr_diffusion_implicite int]
     [ impr_extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
     [ no_conv_subiteration_diffusion_implicite int]
     [ dt_start dt_start]
     [ nb_pas_dt_max int]
     [ niter max diffusion implicite int]
     [ precision impr int]
     [ periode_sauvegarde_securite_en_heures float]
     [ no check disk space ]
     [ disable_progress ]
     [disable dt ev ]
     [gnuplot header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).

- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- seuil_statio float for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- **no_check_disk_space** for inheritance: To disable the check of the available amount of disk space during the calculation.
- **disable_progress** for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.13 Schema_adams_bashforth_order_2

```
Description: not set
See also: schema temps base (31)
Usage:
schema adams bashforth order 2 str
Read str {
     [tinit float]
      [tmax float]
     [tcpumax float]
     [ dt_min float]
      [\mathbf{dt}_{\mathbf{max}} \ str]
     [ dt_sauv float]
     [ nb_sauv_max int]
     [ dt_impr float]
     [facsec str]
     [ seuil_statio float]
     [residuals residuals]
     [ diffusion_implicite int]
      [ seuil diffusion implicite float]
     [impr diffusion implicite int]
     [impr extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
      [ no_conv_subiteration_diffusion_implicite int]
     [ dt_start dt_start]
     [ nb_pas_dt_max int]
      [ niter_max_diffusion_implicite int]
      [ precision_impr int]
      [ periode_sauvegarde_securite_en_heures | float]
     [ no_check_disk_space ]
     [ disable_progress ]
     [disable dt ev ]
     [gnuplot header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- nb_sauv_max int for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones

- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- no_check_disk_space for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.14 Schema_adams_bashforth_order_3

```
Description: not set
See also: schema temps base (31)
Usage:
schema adams bashforth order 3 str
Read str {
     [tinit float]
      [tmax float]
     [tcpumax float]
     [ dt_min float]
      [\mathbf{dt}_{\mathbf{max}} \ str]
     [ dt_sauv float]
     [ nb_sauv_max int]
     [ dt_impr float]
     [facsec str]
     [ seuil_statio float]
     [residuals residuals]
     [ diffusion_implicite int]
      [ seuil diffusion implicite float]
     [impr diffusion implicite int]
     [impr extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
      [ no_conv_subiteration_diffusion_implicite int]
     [ dt_start dt_start]
     [ nb_pas_dt_max int]
      [ niter_max_diffusion_implicite int]
      [ precision_impr int]
      [ periode_sauvegarde_securite_en_heures | float]
     [ no_check_disk_space ]
     [ disable_progress ]
     [disable dt ev ]
     [gnuplot header int]
}
where
```

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- nb_sauv_max int for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones

- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the out file
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema-Adams Bashforth order 3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- no_check_disk_space for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.15 Schema_adams_moulton_order_2

```
Description: not set
See also: schema implicite base (31.20)
Usage:
schema adams moulton order 2 str
Read str {
     [facsec_max float]
     [ max iter implicite int]
     solveur solveur_implicite_base
     [tinit float]
     [tmax float]
     [tcpumax float]
     [ dt_min float]
     [\mathbf{dt} \ \mathbf{max} \ \mathit{str}]
     [dt sauv float]
     [ nb_sauv_max int]
     [dt impr float]
     [ facsec str]
     [ seuil statio float]
     [residuals residuals]
     [ diffusion implicite int]
     [ seuil_diffusion_implicite float]
     [impr_diffusion_implicite int]
     [ impr_extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
     [ no_conv_subiteration_diffusion_implicite int]
      [ dt_start dt_start]
     [ nb_pas_dt_max int]
     [ niter_max_diffusion_implicite int]
     [ precision_impr int]
     [ periode sauvegarde securite en heures float]
     [ no check disk space ]
     [disable progress]
     [disable dt ev ]
     [ gnuplot_header int]
}
where
```

• facsec_max float: Maximum ratio allowed between time step and stability time returned by CFL condition. The initial ratio given by facsec keyword is changed during the calculation with the implicit scheme but it couldn't be higher than facsec_max value.

Warning: Some implicit schemes do not permit high facsec_max, example Schema_Adams_Moulton_order_3 needs facsec=facsec_max=1.

Advice:

The calculation may start with a facsec specified by the user and increased by the algorithm up to the facsec_max limit. But the user can also choose to specify a constant facsec (facsec_max will be set to facsec value then). Faster convergence has been seen and depends on the kind of calculation:

- -Hydraulic only or thermal hydraulic with forced convection and low coupling between velocity and temperature (Boussinesq value beta low), facsec between 20-30
- -Thermal hydraulic with forced convection and strong coupling between velocity and temperature

(Boussinesq value beta high), facsec between 90-100

- -Thermohydralic with natural convection, facsec around 300
- -Conduction only, facsec can be set to a very high value (1e8) as if the scheme was unconditionally stable

These values can also be used as rule of thumb for initial facsec with a facsec_max limit higher.

- max_iter_implicite int for inheritance: Maximum number of iterations allowed for the solver (by default 200).
- solveur solveur_implicite_base (32) for inheritance: This keyword is used to designate the solver selected in the situation where the time scheme is an implicit scheme. solver is the name of the solver that allows equation diffusion and convection operators to be set as implicit terms. Keywords corresponding to this functionality are Simple (SIMPLE type algorithm), Simpler (SIMPLER type algorithm) for incompressible systems, Piso (Pressure Implicit with Split Operator), and Implicite (similar to PISO, but as it looks like a simplified solver, it will use fewer timesteps, and ICE (for PB_multiphase). But it may run faster because the pressure matrix is not re-assembled and thus provides CPU gains.

Advice: Since the 1.6.0 version, we recommend to use first the Implicite or Simple, then Piso, and at least Simpler. Because the two first give a fastest convergence (several times) than Piso and the Simpler has not been validated. It seems also than Implicite and Piso schemes give better results than the Simple scheme when the flow is not fully stationary. Thus, if the solution obtained with Simple is not stationary, it is recommended to switch to Piso or Implicite scheme.

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- dt min *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- dt_sauv float for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.

Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.

- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened

meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.

- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- no_check_disk_space for inheritance: To disable the check of the available amount of disk space during the calculation.
- **disable_progress** for inheritance: To disable the writing of the .progress file.
- **disable_dt_ev** for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.16 Schema_adams_moulton_order_3

```
Description: not set
See also: schema implicite base (31.20)
schema_adams_moulton_order_3 str
Read str {
      [ facsec_max float]
      [ max iter implicite int]
      solveur solveur_implicite_base
      [tinit float]
      [tmax float]
      [tcpumax float]
      [ dt min float]
      \begin{bmatrix} dt_{max} & str \end{bmatrix}
      [ dt_sauv float]
      [ nb_sauv_max int]
      [ dt_impr float]
      [facsec str]
```

```
[ seuil_statio float]
     [residuals residuals]
     [ diffusion implicite int]
     [ seuil_diffusion_implicite float]
     [impr diffusion implicite int]
     [ impr_extremums int]
     [ no error if not converged diffusion implicite int]
     [ no conv subiteration diffusion implicite int]
     [ dt start dt start]
     [ nb_pas_dt_max int]
     [ niter max diffusion implicite int]
     [ precision impr int]
     [ periode_sauvegarde_securite_en_heures | float]
     [ no_check_disk_space ]
     [ disable_progress ]
     [ disable_dt_ev ]
     [ gnuplot_header int]
}
where
```

• facsec_max float: Maximum ratio allowed between time step and stability time returned by CFL condition. The initial ratio given by facsec keyword is changed during the calculation with the implicit scheme but it couldn't be higher than facsec_max value.

Warning: Some implicit schemes do not permit high facsec_max, example Schema_Adams_Moulton-order 3 needs facsec=facsec max=1.

Advice

The calculation may start with a facsec specified by the user and increased by the algorithm up to the facsec_max limit. But the user can also choose to specify a constant facsec (facsec_max will be set to facsec value then). Faster convergence has been seen and depends on the kind of calculation:

- -Hydraulic only or thermal hydraulic with forced convection and low coupling between velocity and temperature (Boussinesq value beta low), facsec between 20-30
- -Thermal hydraulic with forced convection and strong coupling between velocity and temperature (Boussinesq value beta high), facsec between 90-100
- -Thermohydralic with natural convection, facsec around 300
- -Conduction only, facsec can be set to a very high value (1e8) as if the scheme was unconditionally stable

These values can also be used as rule of thumb for initial facsec with a facsec max limit higher.

- max_iter_implicite int for inheritance: Maximum number of iterations allowed for the solver (by default 200).
- **solveur** *solveur_implicite_base* (32) for inheritance: This keyword is used to designate the solver selected in the situation where the time scheme is an implicit scheme. solver is the name of the solver that allows equation diffusion and convection operators to be set as implicit terms. Keywords corresponding to this functionality are Simple (SIMPLE type algorithm), Simpler (SIMPLER type algorithm) for incompressible systems, Piso (Pressure Implicit with Split Operator), and Implicite (similar to PISO, but as it looks like a simplified solver, it will use fewer timesteps, and ICE (for PB_multiphase). But it may run faster because the pressure matrix is not re-assembled and thus provides CPU gains.

Advice: Since the 1.6.0 version, we recommend to use first the Implicite or Simple, then Piso, and at least Simpler. Because the two first give a fastest convergence (several times) than Piso and the Simpler has not been validated. It seems also than Implicite and Piso schemes give better results than the Simple scheme when the flow is not fully stationary. Thus, if the solution obtained with Simple is not stationary, it is recommended to switch to Piso or Implicite scheme.

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax float for inheritance: Time during which the calculation will be stopped (1e30s by default).

- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema-Adams Bashforth order 3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- **nb_pas_dt_max** *int* for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).

- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- **no_check_disk_space** for inheritance: To disable the check of the available amount of disk space during the calculation.
- **disable_progress** for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.17 Schema_backward_differentiation_order_2

```
Description: not_set
See also: schema_implicite_base (31.20)
Usage:
schema_backward_differentiation_order_2 str
Read str {
     [facsec_max float]
     [ max_iter_implicite int]
     solveur solveur_implicite_base
     [tinit float]
     [tmax float]
     [tcpumax float]
     [ dt min float]
     [ dt_max str]
     [ dt sauv float]
     [ nb_sauv_max int]
     [ dt_impr float]
     [facsec str]
     [ seuil statio float]
     [residuals residuals]
     [ diffusion implicite int]
     [ seuil_diffusion_implicite float]
     [ impr_diffusion_implicite int]
     [ impr_extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
     [ no_conv_subiteration_diffusion_implicite int]
     [ dt_start dt_start]
     [ nb_pas_dt_max int]
     [ niter_max_diffusion_implicite int]
     [ precision impr int]
     [ periode_sauvegarde_securite_en_heures float]
     [ no check disk space ]
     [ disable_progress ]
     [disable dt ev ]
     [ gnuplot_header int]
}
where
```

• facsec_max *float*: Maximum ratio allowed between time step and stability time returned by CFL condition. The initial ratio given by facsec keyword is changed during the calculation with the implicit scheme but it couldn't be higher than facsec max value.

Warning: Some implicit schemes do not permit high facsec_max, example Schema_Adams_Moulton_order_3 needs facsec=facsec_max=1.

Advice:

The calculation may start with a facsec specified by the user and increased by the algorithm up to the facsec_max limit. But the user can also choose to specify a constant facsec (facsec_max will be set to facsec value then). Faster convergence has been seen and depends on the kind of calculation:

- -Hydraulic only or thermal hydraulic with forced convection and low coupling between velocity and temperature (Boussinesq value beta low), facsec between 20-30
- -Thermal hydraulic with forced convection and strong coupling between velocity and temperature (Boussinesq value beta high), facsec between 90-100
- -Thermohydralic with natural convection, facsec around 300
- -Conduction only, facsec can be set to a very high value (1e8) as if the scheme was unconditionally stable

These values can also be used as rule of thumb for initial facsec with a facsec_max limit higher.

- max_iter_implicite int for inheritance: Maximum number of iterations allowed for the solver (by default 200).
- solveur solveur_implicite_base (32) for inheritance: This keyword is used to designate the solver selected in the situation where the time scheme is an implicit scheme. solver is the name of the solver that allows equation diffusion and convection operators to be set as implicit terms. Keywords corresponding to this functionality are Simple (SIMPLE type algorithm), Simpler (SIMPLER type algorithm) for incompressible systems, Piso (Pressure Implicit with Split Operator), and Implicite (similar to PISO, but as it looks like a simplified solver, it will use fewer timesteps, and ICE (for PB_multiphase). But it may run faster because the pressure matrix is not re-assembled and thus provides CPU gains.

Advice: Since the 1.6.0 version, we recommend to use first the Implicite or Simple, then Piso, and at least Simpler. Because the two first give a fastest convergence (several times) than Piso and the Simpler has not been validated. It seems also than Implicite and Piso schemes give better results than the Simple scheme when the flow is not fully stationary. Thus, if the solution obtained with Simple is not stationary, it is recommended to switch to Piso or Implicite scheme.

- tinit *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.

Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.

• seuil statio float for inheritance: Value of the convergence threshold (1e-12 by default). Problems

using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.

- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no conv subiteration diffusion implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- **nb pas dt max** int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- **no_check_disk_space** for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- **disable_dt_ev** for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.18 Schema_backward_differentiation_order_3

```
Description: not_set

See also: schema_implicite_base (31.20)

Usage:
schema_backward_differentiation_order_3 str

Read str {

    [facsec_max float]
    [max_iter_implicite int]
    solveur solveur_implicite_base
```

```
[tinit float]
     [tmax float]
     [tcpumax float]
     [ dt_min float]
     [dt max str]
     [ dt_sauv float]
     [ nb sauv max int]
     [ dt impr float]
     [facsec str]
     [ seuil statio float]
     [residuals residuals]
     [ diffusion implicite int]
     [ seuil_diffusion_implicite float]
     [ impr_diffusion_implicite int]
     [ impr_extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
     [ no_conv_subiteration_diffusion_implicite int]
     [ dt_start dt_start]
     [ nb_pas_dt_max int]
     [ niter max diffusion implicite int]
     [ precision_impr int]
     [ periode sauvegarde securite en heures float]
     [ no_check_disk_space ]
     [ disable_progress ]
     [disable dt ev ]
     [gnuplot header int]
}
where
```

• facsec_max *float*: Maximum ratio allowed between time step and stability time returned by CFL condition. The initial ratio given by facsec keyword is changed during the calculation with the implicit scheme but it couldn't be higher than facsec max value.

Warning: Some implicit schemes do not permit high facsec_max, example Schema_Adams_Moulton_order_3 needs facsec=facsec_max=1.

Advice:

The calculation may start with a facsec specified by the user and increased by the algorithm up to the facsec_max limit. But the user can also choose to specify a constant facsec (facsec_max will be set to facsec value then). Faster convergence has been seen and depends on the kind of calculation:

- -Hydraulic only or thermal hydraulic with forced convection and low coupling between velocity and temperature (Boussinesq value beta low), facsec between 20-30
- -Thermal hydraulic with forced convection and strong coupling between velocity and temperature (Boussinesq value beta high), facsec between 90-100
- -Thermohydralic with natural convection, facsec around 300
- -Conduction only, facsec can be set to a very high value (1e8) as if the scheme was unconditionally stable

These values can also be used as rule of thumb for initial facsec with a facsec_max limit higher.

- max_iter_implicite int for inheritance: Maximum number of iterations allowed for the solver (by default 200).
- solveur solveur_implicite_base (32) for inheritance: This keyword is used to designate the solver selected in the situation where the time scheme is an implicit scheme. solver is the name of the solver that allows equation diffusion and convection operators to be set as implicit terms. Keywords corresponding to this functionality are Simple (SIMPLE type algorithm), Simpler (SIMPLER type algorithm) for incompressible systems, Piso (Pressure Implicit with Split Operator), and Implicite (similar to PISO, but as it looks like a simplified solver, it will use fewer timesteps, and ICE (for

PB_multiphase). But it may run faster because the pressure matrix is not re-assembled and thus provides CPU gains.

Advice: Since the 1.6.0 version, we recommend to use first the Implicite or Simple, then Piso, and at least Simpler. Because the two first give a fastest convergence (several times) than Piso and the Simpler has not been validated. It seems also than Implicite and Piso schemes give better results than the Simple scheme when the flow is not fully stationary. Thus, if the solution obtained with Simple is not stationary, it is recommended to switch to Piso or Implicite scheme.

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- **dt_max** *str* for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.

Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema-Adams Bashforth order 3.

- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- ullet no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition.

dt_start dt_fixe value : the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity).

By default, the first iteration is based on dt_calc.

- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- **no_check_disk_space** for inheritance: To disable the check of the available amount of disk space during the calculation.
- **disable_progress** for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.19 Scheme_euler_implicit

```
Synonymous: schema_euler_implicite
Description: This is the Euler implicit scheme.
See also: schema_implicite_base (31.20)
Usage:
scheme_euler_implicit str
Read str {
     [ facsec max float]
     [ facsec_expert | facsec_expert]
     [ facsec_func str]
     [ resolution_monolithique bloc_lecture]
     [ max_iter_implicite int]
     solveur_implicite_base
     [tinit float]
     [tmax float]
     [tcpumax float]
     [ dt_min float]
     [dt max str]
     [ dt_sauv float]
     [ nb sauv max int]
     [ dt_impr float]
     [facsec str]
     [ seuil_statio float]
     [residuals residuals]
     [ diffusion implicite int]
     [ seuil_diffusion_implicite float]
     [ impr_diffusion_implicite int]
     [ impr_extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
     [ no_conv_subiteration_diffusion_implicite int]
```

```
[ dt_start dt_start]
  [ nb_pas_dt_max int]
  [ niter_max_diffusion_implicite int]
  [ precision_impr int]
  [ periode_sauvegarde_securite_en_heures float]
  [ no_check_disk_space ]
  [ disable_progress ]
  [ disable_dt_ev ]
  [ gnuplot_header int]
}
where
```

- facsec_max *float*: For old syntax, see the complete parameters of facsec for details
- facsec_expert facsec_expert (3.55): Advanced facsec specification
- facsec_func str: Advanced facsec specification as a function
- resolution_monolithique bloc_lecture (3.59): Activate monolithic resolution for coupled problems. Solves together the equations corresponding to the application domains in the given order. All aplication domains of the coupled equations must be given to determine the order of resolution. If the monolithic solving is not wanted for a specific application domain, an underscore can be added as prefix. For example, resolution_monolithique { dom1 { dom2 dom3 } _dom4 } will solve in a single matrix the equations having dom1 as application domain, then the equations having dom2 or dom3 as application domain in a single matrix, then the equations having dom4 as application domain in a sequential way (not in a single matrix).
- max_iter_implicite int for inheritance: Maximum number of iterations allowed for the solver (by default 200).
- solveur solveur_implicite_base (32) for inheritance: This keyword is used to designate the solver selected in the situation where the time scheme is an implicit scheme. solver is the name of the solver that allows equation diffusion and convection operators to be set as implicit terms. Keywords corresponding to this functionality are Simple (SIMPLE type algorithm), Simpler (SIMPLER type algorithm) for incompressible systems, Piso (Pressure Implicit with Split Operator), and Implicite (similar to PISO, but as it looks like a simplified solver, it will use fewer timesteps, and ICE (for PB_multiphase). But it may run faster because the pressure matrix is not re-assembled and thus provides CPU gains.

Advice: Since the 1.6.0 version, we recommend to use first the Implicite or Simple, then Piso, and at least Simpler. Because the two first give a fastest convergence (several times) than Piso and the Simpler has not been validated. It seems also than Implicite and Piso schemes give better results than the Simple scheme when the flow is not fully stationary. Thus, if the solution obtained with Simple is not stationary, it is recommended to switch to Piso or Implicite scheme.

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- dt_sauv float for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones

- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema-Adams Bashforth order 3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- no_conv_subiteration_diffusion_implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.
- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- no_check_disk_space for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- disable_dt_ev for inheritance: To disable the writing of the .dt_ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.20 Schema_implicite_base

Description: Basic class for implicite time scheme.

See also: schema_temps_base (31) schema_backward_differentiation_order_3 (31.18) schema_backward_differentiation_order_2 (31.17) scheme_euler_implicit (31.19) schema_adams_moulton_order_3 (31.16) schema_adams_moulton_order_2 (31.15)

```
Usage:
schema_implicite_base str
Read str {
     [ max_iter_implicite int]
     solveur solveur_implicite_base
     [tinit float]
     [tmax float]
     [tcpumax float]
     [ dt_min float]
     [ dt max str]
     [ dt_sauv float]
     [ nb sauv max int]
     [ dt_impr float]
     [facsec str]
     [ seuil statio float]
     [residuals residuals]
     [ diffusion_implicite int]
     [ seuil_diffusion_implicite float]
     [ impr_diffusion_implicite int]
     [ impr_extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
     [ no_conv_subiteration_diffusion_implicite int]
     [ dt_start dt_start]
     [ nb_pas_dt_max int]
     [ niter_max_diffusion_implicite int]
     [ precision impr int]
     [ periode sauvegarde securite en heures float]
     [ no_check_disk_space ]
     [ disable_progress ]
     [ disable_dt_ev ]
     [ gnuplot_header int]
}
where
```

- max_iter_implicite int: Maximum number of iterations allowed for the solver (by default 200).
- solveur solveur_implicite_base (32): This keyword is used to designate the solver selected in the situation where the time scheme is an implicit scheme. solver is the name of the solver that allows equation diffusion and convection operators to be set as implicit terms. Keywords corresponding to this functionality are Simple (SIMPLE type algorithm), Simpler (SIMPLER type algorithm) for incompressible systems, Piso (Pressure Implicit with Split Operator), and Implicite (similar to PISO, but as it looks like a simplified solver, it will use fewer timesteps, and ICE (for PB_multiphase). But it may run faster because the pressure matrix is not re-assembled and thus provides CPU gains. Advice: Since the 1.6.0 version, we recommend to use first the Implicite or Simple, then Piso, and at least Simpler. Because the two first give a fastest convergence (several times) than Piso and the Simpler has not been validated. It seems also than Implicite and Piso schemes give better results than

the Simple scheme when the flow is not fully stationary. Thus, if the solution obtained with Simple is not stationary, it is recommended to switch to Piso or Implicite scheme.

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- **dt_min** *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema-Adams Bashforth order 3.
- seuil_statio float for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr extremums int for inheritance: Print unknowns extremas
- no_error_if_not_converged_diffusion_implicite int for inheritance
- **no_conv_subiteration_diffusion_implicite** *int* for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- niter_max_diffusion_implicite int for inheritance: This keyword changes the default value (num-

ber of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.

- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- **no_check_disk_space** for inheritance: To disable the check of the available amount of disk space during the calculation.
- **disable_progress** for inheritance: To disable the writing of the .progress file.
- disable dt ev for inheritance: To disable the writing of the .dt ev file.
- **gnuplot_header** *int* for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

31.21 Schema_predictor_corrector

Description: This is the predictor-corrector scheme (second order). It is more accurate and economic than MacCormack scheme. It gives best results with a second ordre convective scheme like quick, centre (VDF).

```
See also: schema temps base (31)
Usage:
schema_predictor_corrector str
Read str {
     [tinit float]
     [tmax float]
     [tcpumax float]
     [ dt_min float]
     [ dt_max str]
     [ dt_sauv float]
     [ nb sauv max int]
     [ dt_impr float]
     [facsec str]
     [ seuil_statio float]
     [residuals residuals]
     [ diffusion_implicite int]
     [ seuil diffusion implicite float]
     [ impr_diffusion_implicite int]
     [impr extremums int]
     [ no_error_if_not_converged_diffusion_implicite int]
     [ no_conv_subiteration_diffusion_implicite int]
     [ dt_start dt_start]
     [ nb pas dt max int]
     [ niter max diffusion implicite int]
     [ precision impr int]
     [ periode_sauvegarde_securite_en_heures float]
     [ no_check_disk_space ]
     [disable progress]
     [disable dt ev ]
     [ gnuplot_header int]
}
```

where

- **tinit** *float* for inheritance: Value of initial calculation time (0 by default).
- tmax *float* for inheritance: Time during which the calculation will be stopped (1e30s by default).
- **tcpumax** *float* for inheritance: CPU time limit (must be specified in hours) for which the calculation is stopped (1e30s by default).
- dt_min *float* for inheritance: Minimum calculation time step (1e-16s by default).
- dt_max str for inheritance: Maximum calculation time step as function of time (1e30s by default).
- **dt_sauv** *float* for inheritance: Save time step value (1e30s by default). Every dt_sauv, fields are saved in the .sauv file. The file contains all the information saved over time. If this instruction is not entered, results are saved only upon calculation completion. To disable the writing of the .sauv files, you must specify 0. Note that dt_sauv is in terms of physical time (not cpu time).
- **nb_sauv_max** *int* for inheritance: Maximum number of timesteps that will be stored in backup file (10 by default). This value is only useful when doing a complete backup of the calculation with parallel PDI (as it needs to allocate the proper amount of dataspace in advance). If this number is reached (ie we already stored the data of nb_sauv_max timesteps in the file), the next checkpoints will overwrite the first ones
- **dt_impr** *float* for inheritance: Scheme parameter printing time step in time (1e30s by default). The time steps and the flux balances are printed (incorporated onto every side of processed domains) into the .out file.
- **facsec** *str* for inheritance: Value assigned to the safety factor for the time step (1. by default). It can also be a function of time. The time step calculated is multiplied by the safety factor. The first thing to try when a calculation does not converge with an explicit time scheme is to reduce the facsec to 0.5.
 - Warning: Some schemes needs a facsec lower than 1 (0.5 is a good start), for example Schema_Adams_Bashforth_order_3.
- **seuil_statio** *float* for inheritance: Value of the convergence threshold (1e-12 by default). Problems using this type of time scheme converge when the derivatives dGi/dt of all the unknown transported values Gi have a combined absolute value less than this value. This is the keyword used to set the permanent rating threshold.
- **residuals** *residuals* (3.107) for inheritance: To specify how the residuals will be computed (default max norm, possible to choose L2-norm instead).
- **diffusion_implicite** *int* for inheritance: Keyword to make the diffusive term in the Navier-Stokes equations implicit (in this case, it should be set to 1). The stability time step is then only based on the convection time step (dt=facsec*dt_convection). Thus, in some circumstances, an important gain is achieved with respect to the time step (large diffusion with respect to convection on tightened meshes). Caution: It is however recommended that the user avoids exceeding the convection time step by selecting a too large facsec value. Start with a facsec value of 1 and then increase it gradually if you wish to accelerate calculation. In addition, for a natural convection calculation with a zero initial velocity, in the first time step, the convection time is infinite and therefore dt=facsec*dt_max.
- **seuil_diffusion_implicite** *float* for inheritance: This keyword changes the default value (1e-6) of convergency criteria for the resolution by conjugate gradient used for implicit diffusion.
- **impr_diffusion_implicite** *int* for inheritance: Unactivate (default) or not the printing of the convergence during the resolution of the conjugate gradient.
- impr_extremums int for inheritance: Print unknowns extremas
- no error if not converged diffusion implicite int for inheritance
- no conv subiteration diffusion implicite int for inheritance
- **dt_start** *dt_start* (11.7) for inheritance: dt_start dt_min: the first iteration is based on dt_min. dt_start dt_calc: the time step at first iteration is calculated in agreement with CFL condition. dt_start dt_fixe value: the first time step is fixed by the user (recommended when resuming calculation with Crank Nicholson temporal scheme to ensure continuity). By default, the first iteration is based on dt_calc.
- nb_pas_dt_max int for inheritance: Maximum number of calculation time steps (1e9 by default).
- **niter_max_diffusion_implicite** *int* for inheritance: This keyword changes the default value (number of unknowns) of the maximal iterations number in the conjugate gradient method used for implicit diffusion.

- **precision_impr** *int* for inheritance: Optional keyword to define the digit number for flux values printed into .out files (by default 3).
- **periode_sauvegarde_securite_en_heures** *float* for inheritance: To change the default period (23 hours) between the save of the fields in .sauv file.
- **no_check_disk_space** for inheritance: To disable the check of the available amount of disk space during the calculation.
- disable_progress for inheritance: To disable the writing of the .progress file.
- **disable_dt_ev** for inheritance: To disable the writing of the .dt_ev file.
- gnuplot_header int for inheritance: Optional keyword to modify the header of the .out files. Allows to use the column title instead of columns number.

32 solveur_implicite_base

Description: Class for solver in the situation where the time scheme is the implicit scheme. Solver allows equation diffusion and convection operators to be set as implicit terms.

```
See also: objet_u (40) simpler (32.6) solveur_lineaire_std (32.7) Usage:
```

32.1 Ice

Description: Implicit Continuous-fluid Eulerian solver which is useful for a multiphase problem. Robust pressure reduction resolution.

```
See also: sets (32.4)
Usage:
ice str
Read str {
     [ pression_degeneree int]
     [ pressure reduction|reduction pression int]
     [ criteres_convergence bloc_criteres_convergence]
     [ iter_min int]
     [iter_max int]
     [ seuil_convergence_implicite float]
     [ nb_corrections_max int]
     [facsec diffusion for sets float]
     [ seuil_convergence_solveur | float]
     [ seuil_generation_solveur float]
     [ seuil_verification_solveur float]
     [ seuil_test_preliminaire_solveur float]
     [solveur_sys_base]
     [no_qdm]
     [ nb it max int]
     [ controle_residu ]
}
where
```

• **pression_degeneree** *int*: Set to 1 if the pressure field is degenerate (ex. : incompressible fluid with no imposed-pressure BCs). Default: autodetected

- **pressure_reduction|reduction_pression** *int*: Set to 1 if the user wants a resolution with a pressure reduction. Otherwise, the rien is to be set to 0 so that the complete matrix is considered. The default value of this rien is 1.
- **criteres_convergence** *bloc_criteres_convergence* (3.59.1) for inheritance: Set the convergence thresholds for each unknown (i.e. alpha, temperature, velocity and pressure). The default values are respectively 0.01, 0.1, 0.01 and 100
- iter_min int for inheritance: Number of minimum iterations (default value 1)
- iter max int for inheritance: Number of maximum iterations (default value 10)
- seuil convergence implicite *float* for inheritance: Convergence criteria.
- **nb_corrections_max** *int* for inheritance: Maximum number of corrections performed by the PISO algorithm to achieve the projection of the velocity field. The algorithm may perform less corrections then nb_corrections_max if the accuracy of the projection is sufficient. (By default nb_corrections_max is set to 21).
- **facsec_diffusion_for_sets** *float* for inheritance: facsec to impose on the diffusion time step in sets while the total time step stays smaller than the convection time step.
- **seuil_convergence_solveur** *float* for inheritance: value of the convergence criteria for the resolution of the implicit system build by solving several times per time step the Navier_Stokes equation and the scalar equations if any. This value MUST be used when a coupling between problems is considered (should be set to a value typically of 0.1 or 0.01).
- seuil_generation_solveur *float* for inheritance: Option to create a GMRES solver and use vrel as the convergence threshold (implicit linear system Ax=B will be solved if residual error ||Ax-B|| is lesser than vrel).
- **seuil_verification_solveur** *float* for inheritance: Option to check if residual error ||Ax-B|| is lesser than vrel after the implicit linear system Ax=B has been solved.
- seuil_test_preliminaire_solveur *float* for inheritance: Option to decide if the implicit linear system Ax=B should be solved by checking if the residual error ||Ax-B|| is bigger than vrel.
- **solveur** *solveur_sys_base* (11.16) for inheritance: Method (different from the default one, Gmres with diagonal preconditioning) to solve the linear system.
- **no_qdm** for inheritance: Keyword to not solve qdm equation (and turbulence models of these equation).
- nb_it_max int for inheritance: Keyword to set the maximum iterations number for the Gmres.
- **controle_residu** for inheritance: Keyword of Boolean type (by default 0). If set to 1, the convergence occurs if the residu suddenly increases.

32.2 Implicite

Description: similar to PISO, but as it looks like a simplified solver, it will use fewer timesteps. But it may run faster because the pressure matrix is not re-assembled and thus provides CPU gains.

```
See also: piso (32.3)

Usage:
implicite str

Read str {

    [ seuil_convergence_implicite float]
    [ nb_corrections_max int]
    [ seuil_convergence_solveur float]
    [ seuil_generation_solveur float]
    [ seuil_verification_solveur float]
    [ seuil_test_preliminaire_solveur float]
    [ solveur solveur_sys_base]
    [ no_qdm ]
```

```
[ nb_it_max int]
  [ controle_residu ]
}
where
```

- seuil convergence implicite *float* for inheritance: Convergence criteria.
- nb_corrections_max *int* for inheritance: Maximum number of corrections performed by the PISO algorithm to achieve the projection of the velocity field. The algorithm may perform less corrections then nb_corrections_max if the accuracy of the projection is sufficient. (By default nb_corrections_max is set to 21).
- seuil_convergence_solveur *float* for inheritance: value of the convergence criteria for the resolution of the implicit system build by solving several times per time step the Navier_Stokes equation and the scalar equations if any. This value MUST be used when a coupling between problems is considered (should be set to a value typically of 0.1 or 0.01).
- seuil_generation_solveur *float* for inheritance: Option to create a GMRES solver and use vrel as the convergence threshold (implicit linear system Ax=B will be solved if residual error ||Ax-B|| is lesser than vrel).
- **seuil_verification_solveur** *float* for inheritance: Option to check if residual error ||Ax-B|| is lesser than vrel after the implicit linear system Ax=B has been solved.
- seuil_test_preliminaire_solveur *float* for inheritance: Option to decide if the implicit linear system Ax=B should be solved by checking if the residual error ||Ax-B|| is bigger than vrel.
- **solveur** *solveur_sys_base* (11.16) for inheritance: Method (different from the default one, Gmres with diagonal preconditioning) to solve the linear system.
- **no_qdm** for inheritance: Keyword to not solve qdm equation (and turbulence models of these equation).
- nb_it_max int for inheritance: Keyword to set the maximum iterations number for the Gmres.
- **controle_residu** for inheritance: Keyword of Boolean type (by default 0). If set to 1, the convergence occurs if the residu suddenly increases.

32.3 Piso

Description: Piso (Pressure Implicit with Split Operator) - method to solve N S.

See also: simpler (32.6) implicite (32.2) simple (32.5) Usage: piso str Read str { [seuil_convergence_implicite | float] [nb corrections max int] [seuil_convergence_solveur | float] [seuil generation solveur *float*] [seuil_verification_solveur float] [seuil_test_preliminaire_solveur float] [solveur solveur sys base] [no qdm] [**nb** it max int] [controle residu] } where

• **seuil_convergence_implicite** *float*: Convergence criteria.

- **nb_corrections_max** *int*: Maximum number of corrections performed by the PISO algorithm to achieve the projection of the velocity field. The algorithm may perform less corrections then nb_corrections_max if the accuracy of the projection is sufficient. (By default nb_corrections_max is set to 21).
- **seuil_convergence_solveur** *float* for inheritance: value of the convergence criteria for the resolution of the implicit system build by solving several times per time step the Navier_Stokes equation and the scalar equations if any. This value MUST be used when a coupling between problems is considered (should be set to a value typically of 0.1 or 0.01).
- seuil_generation_solveur *float* for inheritance: Option to create a GMRES solver and use vrel as the convergence threshold (implicit linear system Ax=B will be solved if residual error ||Ax-B|| is lesser than vrel).
- **seuil_verification_solveur** *float* for inheritance: Option to check if residual error ||Ax-B|| is lesser than vrel after the implicit linear system Ax=B has been solved.
- seuil_test_preliminaire_solveur *float* for inheritance: Option to decide if the implicit linear system Ax=B should be solved by checking if the residual error ||Ax-B|| is bigger than vrel.
- **solveur** *solveur_sys_base* (11.16) for inheritance: Method (different from the default one, Gmres with diagonal preconditioning) to solve the linear system.
- **no_qdm** for inheritance: Keyword to not solve qdm equation (and turbulence models of these equation).
- **nb_it_max** *int* for inheritance: Keyword to set the maximum iterations number for the Gmres.
- **controle_residu** for inheritance: Keyword of Boolean type (by default 0). If set to 1, the convergence occurs if the residu suddenly increases.

32.4 Sets

Description: Stability-Enhancing Two-Step solver which is useful for a multiphase problem. Ref: J. H. MAHAFFY, A stability-enhancing two-step method for fluid flow calculations, Journal of Computational Physics, 46, 3, 329 (1982).

```
See also: simpler (32.6) ice (32.1)
Usage:
sets str
Read str {
     [ criteres_convergence bloc_criteres_convergence]
     [iter min int]
     [iter_max int]
     [ seuil convergence_implicite float]
     [ nb_corrections_max int]
     [facsec diffusion for sets float]
     [ seuil_convergence_solveur float]
     [seuil generation solveur float]
     [ seuil verification solveur float]
     [ seuil test preliminaire solveur float]
     [solveur_sys_base]
     [no_qdm]
     [ nb it max int]
     [controle_residu]
}
where
```

- **criteres_convergence** *bloc_criteres_convergence* (3.59.1): Set the convergence thresholds for each unknown (i.e. alpha, temperature, velocity and pressure). The default values are respectively 0.01, 0.1, 0.01 and 100
- iter_min int: Number of minimum iterations (default value 1)
- iter_max int: Number of maximum iterations (default value 10)
- seuil_convergence_implicite float: Convergence criteria.
- **nb_corrections_max** *int*: Maximum number of corrections performed by the PISO algorithm to achieve the projection of the velocity field. The algorithm may perform less corrections then nb_corrections_max if the accuracy of the projection is sufficient. (By default nb_corrections_max is set to 21).
- **facsec_diffusion_for_sets** *float*: facsec to impose on the diffusion time step in sets while the total time step stays smaller than the convection time step.
- **seuil_convergence_solveur** *float* for inheritance: value of the convergence criteria for the resolution of the implicit system build by solving several times per time step the Navier_Stokes equation and the scalar equations if any. This value MUST be used when a coupling between problems is considered (should be set to a value typically of 0.1 or 0.01).
- seuil_generation_solveur *float* for inheritance: Option to create a GMRES solver and use vrel as the convergence threshold (implicit linear system Ax=B will be solved if residual error ||Ax-B|| is lesser than vrel).
- **seuil_verification_solveur** *float* for inheritance: Option to check if residual error ||Ax-B|| is lesser than vrel after the implicit linear system Ax=B has been solved.
- **seuil_test_preliminaire_solveur** *float* for inheritance: Option to decide if the implicit linear system Ax=B should be solved by checking if the residual error ||Ax-B|| is bigger than vrel.
- **solveur** *solveur_sys_base* (11.16) for inheritance: Method (different from the default one, Gmres with diagonal preconditioning) to solve the linear system.
- **no_qdm** for inheritance: Keyword to not solve qdm equation (and turbulence models of these equation).
- nb_it_max int for inheritance: Keyword to set the maximum iterations number for the Gmres.
- **controle_residu** for inheritance: Keyword of Boolean type (by default 0). If set to 1, the convergence occurs if the residu suddenly increases.

32.5 Simple

```
Description: SIMPLE type algorithm
See also: piso(32.3) solveur_u_p (32.8)
Usage:
simple str
Read str {
     [ relax_pression float]
     [ seuil_convergence_implicite | float]
     [ nb_corrections_max int]
     [ seuil_convergence_solveur | float]
     [ seuil_generation_solveur float]
     [ seuil_verification_solveur float]
     [ seuil_test_preliminaire_solveur float]
     [solveur_sys_base]
     [no_qdm]
     [ nb it max int]
     [ controle_residu ]
}
```

where

- **relax_pression** *float*: Value between 0 and 1 (by default 1), this keyword is used only by the SIM-PLE algorithm for relaxing the increment of pressure.
- seuil_convergence_implicite float for inheritance: Convergence criteria.
- nb_corrections_max *int* for inheritance: Maximum number of corrections performed by the PISO algorithm to achieve the projection of the velocity field. The algorithm may perform less corrections then nb_corrections_max if the accuracy of the projection is sufficient. (By default nb_corrections_max is set to 21).
- **seuil_convergence_solveur** *float* for inheritance: value of the convergence criteria for the resolution of the implicit system build by solving several times per time step the Navier_Stokes equation and the scalar equations if any. This value MUST be used when a coupling between problems is considered (should be set to a value typically of 0.1 or 0.01).
- seuil_generation_solveur *float* for inheritance: Option to create a GMRES solver and use vrel as the convergence threshold (implicit linear system Ax=B will be solved if residual error ||Ax-B|| is lesser than vrel).
- seuil_verification_solveur *float* for inheritance: Option to check if residual error ||Ax-B|| is lesser than vrel after the implicit linear system Ax=B has been solved.
- **seuil_test_preliminaire_solveur** *float* for inheritance: Option to decide if the implicit linear system Ax=B should be solved by checking if the residual error ||Ax-B|| is bigger than vrel.
- **solveur** *solveur_sys_base* (11.16) for inheritance: Method (different from the default one, Gmres with diagonal preconditioning) to solve the linear system.
- **no_qdm** for inheritance: Keyword to not solve qdm equation (and turbulence models of these equation).
- nb_it_max int for inheritance: Keyword to set the maximum iterations number for the Gmres.
- **controle_residu** for inheritance: Keyword of Boolean type (by default 0). If set to 1, the convergence occurs if the residu suddenly increases.

32.6 Simpler

Description: Simpler method for incompressible systems.

```
See also: solveur_implicite_base (32) sets (32.4) piso (32.3)

Usage:
simpler str

Read str {

seuil_convergence_implicite float
[seuil_convergence_solveur float]
[seuil_generation_solveur float]
[seuil_verification_solveur float]
[seuil_test_preliminaire_solveur float]
[solveur solveur_sys_base]
[no_qdm ]
[nb_it_max int]
[controle_residu ]

}

where
```

• seuil_convergence_implicite float: Keyword to set the value of the convergence criteria for the resolution of the implicit system build to solve either the Navier_Stokes equation (only for Simple and Simpler algorithms) or a scalar equation. It is adviced to use the default value (1e6) to solve

- the implicit system only once by time step. This value must be decreased when a coupling between problems is considered.
- **seuil_convergence_solveur** *float*: value of the convergence criteria for the resolution of the implicit system build by solving several times per time step the Navier_Stokes equation and the scalar equations if any. This value MUST be used when a coupling between problems is considered (should be set to a value typically of 0.1 or 0.01).
- **seuil_generation_solveur** *float*: Option to create a GMRES solver and use vrel as the convergence threshold (implicit linear system Ax=B will be solved if residual error ||Ax-B|| is lesser than vrel).
- seuil_verification_solveur *float*: Option to check if residual error ||Ax-B|| is lesser than vrel after the implicit linear system Ax=B has been solved.
- **seuil_test_preliminaire_solveur** *float*: Option to decide if the implicit linear system Ax=B should be solved by checking if the residual error ||Ax-B|| is bigger than vrel.
- **solveur** *solveur_sys_base* (11.16): Method (different from the default one, Gmres with diagonal preconditioning) to solve the linear system.
- no_qdm: Keyword to not solve qdm equation (and turbulence models of these equation).
- **nb_it_max** *int*: Keyword to set the maximum iterations number for the Gmres.
- **controle_residu**: Keyword of Boolean type (by default 0). If set to 1, the convergence occurs if the residu suddenly increases.

32.7 Solveur_lineaire_std

Description: not_set

```
See also: solveur implicite base (32)
Usage:
solveur_lineaire_std str
Read str {
     [solveur_sys_base]
}
where
   • solveur_sys_base (11.16)
32.8
       Solveur_u_p
Description: similar to simple.
See also: simple (32.5)
Usage:
solveur_u_p str
Read str {
     [relax_pression float]
     [ seuil_convergence_implicite | float]
     [ nb_corrections_max int]
     [ seuil_convergence_solveur | float]
     [ seuil_generation_solveur float]
     [ seuil_verification_solveur float]
     [ seuil_test_preliminaire_solveur float]
     [solveur_sys_base]
```

```
[ no_qdm ]
[ nb_it_max int]
[ controle_residu ]
}
where
```

- **relax_pression** *float* for inheritance: Value between 0 and 1 (by default 1), this keyword is used only by the SIMPLE algorithm for relaxing the increment of pressure.
- seuil_convergence_implicite float for inheritance: Convergence criteria.
- nb_corrections_max *int* for inheritance: Maximum number of corrections performed by the PISO algorithm to achieve the projection of the velocity field. The algorithm may perform less corrections then nb_corrections_max if the accuracy of the projection is sufficient. (By default nb_corrections_max is set to 21).
- **seuil_convergence_solveur** *float* for inheritance: value of the convergence criteria for the resolution of the implicit system build by solving several times per time step the Navier_Stokes equation and the scalar equations if any. This value MUST be used when a coupling between problems is considered (should be set to a value typically of 0.1 or 0.01).
- seuil_generation_solveur *float* for inheritance: Option to create a GMRES solver and use vrel as the convergence threshold (implicit linear system Ax=B will be solved if residual error ||Ax-B|| is lesser than vrel).
- seuil_verification_solveur *float* for inheritance: Option to check if residual error ||Ax-B|| is lesser than vrel after the implicit linear system Ax=B has been solved.
- **seuil_test_preliminaire_solveur** *float* for inheritance: Option to decide if the implicit linear system Ax=B should be solved by checking if the residual error ||Ax-B|| is bigger than vrel.
- **solveur** *solveur_sys_base* (11.16) for inheritance: Method (different from the default one, Gmres with diagonal preconditioning) to solve the linear system.
- **no_qdm** for inheritance: Keyword to not solve qdm equation (and turbulence models of these equation).
- nb_it_max int for inheritance: Keyword to set the maximum iterations number for the Gmres.
- **controle_residu** for inheritance: Keyword of Boolean type (by default 0). If set to 1, the convergence occurs if the residu suddenly increases.

33 solveur_petsc_deriv

Description: Additional information is available in the PETSC documentation: https://petsc.org/release/manual/

See also: objet_u (40) lu (33.14) Cholesky_superlu (33.4) Cholesky_pastix (33.3) Cholesky_umfpack (33.5) Cholesky_out_of_core (33.2) cholesky (33.8) cholesky_mumps_blr (33.9) cli (33.10) cli_quiet (33.11) IBICGSTAB (33.6) BICGSTAB (33.1) gmres (33.13) gcp (33.12) PIPECG (33.7)

```
Usage: solveur
```

```
solveur_petsc_deriv str
Read str {
        [ seuil float]
        [ quiet ]
        [ impr ]
        [ rtol float]
        [ atol float]
        [ save_matrix_mtx_format ]
}
where
```

- **seuil** *float*: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet: is a keyword which is used to not displaying any outputs of the solver.
- **impr**: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- rtol float
- atol float
- save matrix mtx format

33.1 Bicgstab

Description: Stabilized Bi-Conjugate Gradient

```
See also: solveur_petsc_deriv (33)

Usage:
BICGSTAB str

Read str {

    [precond preconditionneur_petsc_deriv]
    [seuil float]
    [quiet ]
    [impr ]
    [rtol float]
    [atol float]
    [save_matrix_mtx_format ]
}
where
```

- **precond** *preconditionneur_petsc_deriv* (30)
- **seuil** *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- rtol float for inheritance
- atol float for inheritance
- save_matrix_mtx_format for inheritance

33.2 Cholesky_out_of_core

Description: Same as the previous one but with a written LU decomposition of disk (save RAM memory but add an extra CPU cost during Ax=B solve).

```
See also: solveur_petsc_deriv (33)

Usage:
Cholesky_out_of_core str

Read str {

    [ seuil float]
    [ quiet ]
    [ impr ]
```

```
[ rtol float]
    [ atol float]
    [ save_matrix_mtx_format ]
}
where
```

- **seuil** *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- rtol float for inheritance
- atol float for inheritance
- save_matrix_mtx_format for inheritance

33.3 Cholesky_pastix

Description: Parallelized Cholesky from PASTIX library.

```
See also: solveur_petsc_deriv (33)

Usage:
Cholesky_pastix str
Read str {
        [ seuil float]
        [ quiet ]
        [ impr ]
        [ rtol float]
        [ atol float]
        [ save_matrix_mtx_format ]
}
where
```

- **seuil** *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- **rtol** *float* for inheritance
- atol float for inheritance
- save_matrix_mtx_format for inheritance

33.4 Cholesky superlu

Description: Parallelized Cholesky from SUPERLU_DIST library (less CPU and RAM, efficient than the previous one)

```
See also: solveur_petsc_deriv (33)

Usage:
Cholesky_superlu str
Read str {
```

```
[ seuil float]
  [ quiet ]
  [ impr ]
  [ rtol float]
  [ atol float]
  [ save_matrix_mtx_format ]
}
where
```

- **seuil** *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- rtol float for inheritance
- atol float for inheritance
- save_matrix_mtx_format for inheritance

33.5 Cholesky_umfpack

Description: Sequential Cholesky from UMFPACK library (seems fast).

```
See also: solveur_petsc_deriv (33)

Usage:
Cholesky_umfpack str
Read str {

    [seuil float]
    [quiet ]
    [impr ]
    [rtol float]
    [atol float]
    [save_matrix_mtx_format ]
}
where
```

- seuil *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- rtol float for inheritance
- atol float for inheritance
- save matrix mtx format for inheritance

33.6 Ibicgstab

Description: Improved version of previous one for massive parallel computations (only a single global reduction operation instead of the usual 3 or 4).

```
See also: solveur_petsc_deriv (33)
```

```
Usage:
IBICGSTAB str

Read str {

        [ precond preconditionneur_petsc_deriv] |
        [ seuil float] |
        [ quiet ] |
        [ impr ] |
        [ rtol float] |
        [ atol float] |
        [ save_matrix_mtx_format ]
}
where
```

- **precond** preconditionneur_petsc_deriv (30)
- **seuil** *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- rtol float for inheritance
- atol float for inheritance
- save_matrix_mtx_format for inheritance

33.7 Pipecg

Description: Pipelined Conjugate Gradient (possible reduced CPU cost during massive parallel calculation due to a single non-blocking reduction per iteration, if TRUST is built with a MPI-3 implementation)... no example in TRUST

```
See also: solveur_petsc_deriv (33)

Usage:
PIPECG str
Read str {
        [ seuil float]
        [ quiet ]
        [ impr ]
        [ rtol float]
        [ atol float]
        [ save_matrix_mtx_format ]
}
where
```

- **seuil** *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- rtol float for inheritance
- atol float for inheritance
- save_matrix_mtx_format for inheritance

33.8 Cholesky


Description: Parallelized version of Cholesky from MUMPS library. This solver accepts an option to select a different ordering than the automatic selected one by MUMPS (and printed by using the impr option). The possible choices are Metis, Scotch, PT-Scotch or Parmetis. The two last options can only be used during a parallel calculation, whereas the two first are available for sequential or parallel calculations. It seems that the CPU cost of A=LU factorization but also of the backward/forward elimination steps may sometimes be reduced by selecting a different ordering (Scotch seems often the best for b/f elimination) than the default one.

Notice that this solver requires a huge amont of memory compared to iterative methods. To know how much RAM you will need by core, then use the improprion to have detailled informations during the analysis phase and before the factorisation phase (in the following output, you will learn that the largest memory is taken by the zeroth CPU with 108MB):

Rank of proc needing largest memory in IC facto: 0

Estimated corresponding MBYTES for IC facto: 108

Thanks to the following graph, you read that in order to solve for instance a flow on a mesh with 2.6e6 cells, you will need to run a parallel calculation on 32 CPUs if you have cluster nodes with only 4GB/core (6.2GB*0.42 2.6GB):



See also: solveur_petsc_deriv (33)

```
Usage: cholesky str Read str {
```

```
[ save_matrix|save_matrice ]
[ save_matrix_petsc_format ]
[ reduce_ram ]
[ cli_quiet solveur_petsc_option_cli]
[ cli solveur_petsc_option_cli]
[ seuil float]
[ quiet ]
[ impr ]
[ rtol float]
[ atol float]
[ save_matrix_mtx_format ]
```

```
}
where
```

- save_matrix|save_matrice
- save_matrix_petsc_format
- reduce ram
- cli_quiet solveur_petsc_option_cli (3.59.2)
- cli solveur_petsc_option_cli (3.59.2)
- seuil *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- rtol float for inheritance
- atol float for inheritance
- save_matrix_mtx_format for inheritance

33.9 Cholesky_mumps_blr

```
Description: BLR for (Block Low-Rank)
See also: solveur_petsc_deriv (33)
Usage:
cholesky_mumps_blr str
Read str {
     [reduce_ram]
     [dropping parameter float]
     [ cli solveur_petsc_option_cli]
     [ seuil float]
     [quiet]
     [impr]
     [rtol float]
     [ atol float]
     [ save_matrix_mtx_format ]
}
where
```

- reduce ram
- dropping_parameter float
- cli solveur_petsc_option_cli (3.59.2)
- **seuil** *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- rtol float for inheritance
- atol float for inheritance
- save_matrix_mtx_format for inheritance

33.10 Cli

Description: Command Line Interface. Should be used only by advanced users, to access the whole solver/preconditioners from the PETSC API. To find all the available options, run your calculation with the -ksp_view -help options:

trust datafile [N] -ksp_view -help

-pc_type Preconditioner:(one of) none jacobi pbjacobi bjacobi sor lu shell mg eisenstat ilu icc cholesky asm ksp composite redundant nn mat fieldsplit galerkin openmp spai hypre tfs (PCSetType)

HYPRE preconditioner options:

-pc_hypre_type pilut (choose one of) pilut parasails boomeramg

HYPRE ParaSails Options

-pc_hypre_parasails_nlevels 1: Number of number of levels (None)

-pc_hypre_parasails_thresh 0.1: Threshold (None)

-pc_hypre_parasails_filter 0.1: filter (None)

-pc_hypre_parasails_loadbal 0: Load balance (None)

-pc_hypre_parasails_logging: FALSE Print info to screen (None)

-pc_hypre_parasails_reuse: FALSE Reuse nonzero pattern in preconditioner (None)

-pc_hypre_parasails_sym nonsymmetric (choose one of) nonsymmetric SPD nonsymmetric,SPD

Krylov Method (KSP) Options

- -ksp_type Krylov method:(one of) cg cgne stcg gltr richardson chebychev gmres tcqmr bcgs bcgsl cgs tfqmr cr lsqr preonly qcg bicg fgmres minres symmlq lgmres lcd (KSPSetType)
- -ksp_max_it 10000: Maximum number of iterations (KSPSetTolerances)
- -ksp_rtol 0: Relative decrease in residual norm (KSPSetTolerances)
- -ksp atol 1e-12: Absolute value of residual norm (KSPSetTolerances)
- -ksp divtol 10000: Residual norm increase cause divergence (KSPSetTolerances)
- -ksp_converged_use_initial_residual_norm: Use initial residual norm for computing relative convergence
- -ksp_monitor_singular_value stdout: Monitor singular values (KSPMonitorSet)
- -ksp_monitor_short stdout: Monitor preconditioned residual norm with fewer digits (KSPMonitorSet)
- -ksp_monitor_draw: Monitor graphically preconditioned residual norm (KSPMonitorSet)
- -ksp monitor draw true residual: Monitor graphically true residual norm (KSPMonitorSet)

Example to use the multigrid method as a solver, not only as a preconditioner:

Solveur_pression Petsc CLI {-ksp_type richardson -pc_type hypre -pc_hypre_type boomeramg -ksp_atol 1.e-7 }

See also: solveur_petsc_deriv (33)

Usage:

cli cli bloc

where

• cli_bloc bloc_lecture (3.59): bloc

33.11 Cli_quiet

Description: solver

See also: solveur_petsc_deriv (33)

Usage:

cli_quiet cli_quiet_bloc

where

• cli_quiet_bloc bloc_lecture (3.59): bloc

33.12 Gcp

```
Description: Preconditioned Conjugate Gradient
See also: solveur_petsc_deriv (33)
Usage:
gcp str
Read str {
     [ precond preconditionneur_petsc_deriv]
     [precond nul]
     [rtol float]
     [ reuse_preconditioner_nb_it_max int]
     [ cli solveur_petsc_option_cli]
     [reorder_matrix int]
     [ read_matrix ]
     [ save_matrix|save_matrice ]
     [ petsc_decide int]
     [ pcshell str]
     [aij]
     [ seuil float]
     [quiet]
     [impr]
     [ atol float]
     [ save matrix mtx format ]
}
where
```

- **precond** *preconditionneur_petsc_deriv* (30): preconditioner
- **precond_nul** : No preconditioner used, equivalent to precond null { }
- rtol float
- reuse_preconditioner_nb_it_max int
- cli solveur_petsc_option_cli (3.59.2)
- reorder matrix int
- read_matrix: save_matrixlread_matrix are the keywords to savelread into a file the constant matrix A of the linear system Ax=B solved (eg: matrix from the pressure linear system for an incompressible flow). It is useful when you want to minimize the MPI communications on massive parallel calculation. Indeed, in VEF discretization, the overlapping width (generaly 2, specified with the largeur_joint option in the partition keyword partition) can be reduced to 1, once the matrix has been properly assembled and saved. The cost of the MPI communications in TRUST itself (not in PETSc) will be reduced with length messages divided by 2. So the strategy is:
 - I) Partition your VEF mesh with a largeur_joint value of 2
 - II) Run your parallel calculation on 0 time step, to build and save the matrix with the save_matrix option. A file named Matrix_NBROWS_rows_NCPUS_cpus.petsc will be saved to the disk (where NBROWS is the number of rows of the matrix and NCPUS the number of CPUs used).
 - III) Partition your VEF mesh with a largeur_joint value of 1
 - IV) Run your parallel calculation completly now and substitute the save_matrix option by the read_matrix option. Some interesting gains have been noticed when the cost of linear system solve with PETSc is small compared to all the other operations.
- save_matrix|save_matrice : see read_matrix

- petsc_decide int
- pcshell str
- aij
- seuil *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- atol float for inheritance
- save_matrix_mtx_format for inheritance

33.13 Gmres

Description: Generalized Minimal Residual

```
See also: solveur_petsc_deriv (33)
Usage:
gmres str
Read str {
     [ precond preconditionneur_petsc_deriv]
     [ reuse_preconditioner_nb_it_max int]
     [ save_matrix_petsc_format ]
     [ nb_it_max int]
     [seuil float]
     [quiet]
     [impr]
     [rtol float]
     [ atol float]
     [ save_matrix_mtx_format ]
}
where
```

- **precond** preconditionneur_petsc_deriv (30)
- reuse_preconditioner_nb_it_max int
- save_matrix_petsc_format
- **nb_it_max** *int*: In order to specify a given number of iterations instead of a condition on the residue with the keyword seuil. May be useful when defining a PETSc solver for the implicit time scheme where convergence is very fast: 5 or less iterations seems enough.
- **seuil** *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- rtol float for inheritance
- atol float for inheritance
- save_matrix_mtx_format for inheritance

33.14 Lu

Description: Several solvers through PETSc API are available. TIPS:

- A) Solver for symmetric linear systems (e.g. Pressure system from Navier-Stokes equations):
- -The CHOLESKY parallel solver is from MUMPS library. It offers better performance than all others solvers if you have enough RAM for your calculation. A parallel calculation on a cluster with 4GBytes on each processor, 40000 cells/processor seems the upper limit. Seems to be very slow to initialize above 500 cpus/cores.
- -When running a parallel calculation with a high number of cpus/cores (typically more than 500) where preconditioner scalability is the key for CPU performance, consider BICGSTAB with BLOCK_JACOBI-ICC(1) as preconditioner or if not converges, GCP with BLOCK_JACOBI-ICC(1) as preconditioner.
- -For other situations, the first choice should be GCP/SSOR. In order to fine tune the solver choice, each one of the previous list should be considered. Indeed, the CPU speed of a solver depends of a lot of parameters. You may give a try to the OPTIMAL solver to help you to find the fastest solver on your study.
- B) Solver for non symmetric linear systems (e.g.: Implicit schemes): The BICGSTAB/DIAG solver seems to offer the best performances.

```
See also: solveur_petsc_deriv (33)

Usage:
lu str

Read str {

    [ seuil float]
    [ quiet ]
    [ impr ]
    [ rtol float]
    [ atol float]
    [ save_matrix_mtx_format ]
}
where
```

- **seuil** *float* for inheritance: corresponds to the iterative solver convergence value. The iterative solver converges when the Euclidean residue standard ||Ax-B|| is less than seuil.
- quiet for inheritance: is a keyword which is used to not displaying any outputs of the solver.
- **impr** for inheritance: used to request display of the Euclidean residue standard each time this iterates through the conjugated gradient (display to the standard outlet).
- rtol float for inheritance
- atol float for inheritance
- save_matrix_mtx_format for inheritance

34 source_base

Description: Basic class of source terms introduced in the equation.

See also: objet_u (40) darcy (34.13) puissance_thermique (34.25) forchheimer (34.16) dirac (34.14) source_constituant (34.27) vitesse_relative_base (34.38) flux_interfacial (34.15) frottement_interfacial (34.17) Portance_interfaciale (34.6) travail_pression (34.36) Dispersion_bulles (34.5) coriolis (34.12) perte_charge_singuliere (34.24) canal_perio (34.11) perte_charge_reguliere (34.22) source_qdm (34.32) acceleration (34.8) DP_Impose (34.3) boussinesq_temperature (34.10) boussinesq_concentration (34.9) terme_puissance_thermique_echange_impose (34.35) Correction_Tomiyama (34.2) Correction_Antal (34.1) radioactive_decay (34.26) source_qdm_lambdaup (34.33) source_th_tdivu (34.34) perte_charge_isotrope (34.21) perte_charge_directionnelle (34.20) perte_charge_anisotrope (34.18) perte_charge_circulaire (34.19) source_generique (34.28) Source_dep_inco_bases (34.7)

```
Usage:
```

34.1 Correction antal

```
Description: Antal correction source term for multiphase problem
```

See also: source_base (34)

Usage:

34.2 Correction_tomiyama

Description: Tomiyama correction source term for multiphase problem

See also: source_base (34)

Usage:

34.3 Dp_impose

Description: Source term to impose a pressure difference according to the formula : DP = dp + dDP/dQ * (Q - Q0)

See also: source_base (34)

Usage:

DP_Impose aco dp_type surface bloc_surface acof where

- aco str into ['{'}]: Opening curly bracket.
- **dp_type** type_perte_charge_deriv (34.4): mass flow rate (kg/s).
- **surface** *str into* ['surface']
- bloc_surface bloc_lecture (3.59): Three syntaxes are possible for the surface definition block: For VDF and VEF: { X|Y|Z = location subzone_name } Only for VEF: { Surface surface_name }.

For polymac { Surface surface_name Orientation champ_uniforme }.

• acof str into ['}']: Closing curly bracket.

34.4 Type_perte_charge_deriv

Description: not_set

See also: objet_lecture (39) dp (34.4.1) dp_regul (34.4.2)

Usage:

34.4.1 Dp

Description: DP field should have 3 components defining dp, dDP/dQ, Q0

See also: type_perte_charge_deriv (34.4)

Usage:

```
dp dp_field where
```

• **dp_field** *champ_base* (16.1): the parameters of the previous formula (DP = dp + dDP/dQ * (Q - Q0)): uniform field 3 dp dDP/dQ Q0 where Q0 is a mass flow rate (kg/s).

34.4.2 Dp_regul

Description: Keyword used to regulate the DP value in order to match a target flow rate. Syntax : dp_regul { DP0 d deb d eps e }

- **DP0** *float*: initial value of DP
- **deb** str: target flow rate in kg/s
- **eps** *str*: strength of the regulation (low values might be slow to find the target flow rate, high values might oscillate around the target value)

34.5 Dispersion_bulles

Description: Base class for source terms of bubble dispersion in momentum equation.

```
See also: source_base (34)

Usage:

Dispersion_bulles str

Read str {

[beta float]
}

where
```

• beta float: Mutliplying factor for the output of the bubble dispersion source term.

34.6 Portance_interfaciale

Description: Base class for source term of lift force in momentum equation.

```
See also: source_base (34)

Usage:
Portance_interfaciale str
Read str {
```

```
[ beta float]
}
where
```

• beta *float*: Multiplying factor for the bubble lift force source term.

34.7 Source_dep_inco_bases

Description: Basic class of source terms depending of inknown.

```
See also: source_base (34) source_pdf_base (34.31)
Usage:
```

34.8 Acceleration

Description: Momentum source term to take in account the forces due to rotation or translation of a non Galilean referential R' (centre 0') into the Galilean referential R (centre 0).

```
See also: source_base (34)

Usage:
acceleration str

Read str {

    [vitesse champ_base]
    [acceleration champ_base]
    [omega champ_base]
    [domegadt champ_base]
    [centre_rotation champ_base]
    [option str into ['terme_complet', 'coriolis_seul', 'entrainement_seul']]
}
where
```

- **vitesse** *champ_base* (16.1): Keyword for the velocity of the referential R' into the R referential (dOO'/dt term [m.s-1]). The velocity is mandatory when you want to print the total cinetic energy into the non-mobile Galilean referential R (see Ec_dans_repere_fixe keyword).
- acceleration *champ_base* (16.1): Keyword for the acceleration of the referential R' into the R referential (d2OO'/dt2 term [m.s-2]). field_base is a time dependant field (eg: Champ_Fonc_t).
- omega champ_base (16.1): Keyword for a rotation of the referential R' into the R referential [rad.s-1]. field_base is a 3D time dependant field specified for example by a Champ_Fonc_t keyword. The time_field field should have 3 components even in 2D (In 2D: 0 0 omega).
- **domegadt** *champ_base* (16.1): Keyword to define the time derivative of the previous rotation [rad.s-2]. Should be zero if the rotation is constant. The time_field field should have 3 components even in 2D (In 2D: 0 0 domegadt).
- **centre_rotation** *champ_base* (16.1): Keyword to specify the centre of rotation (expressed in R' coordinates) of R' into R (if the domain rotates with the R' referential, the centre of rotation is 0'=(0,0,0)). The time_field should have 2 or 3 components according the dimension 2 or 3.
- **option** *str into ['terme_complet', 'coriolis_seul', 'entrainement_seul']*: Keyword to specify the kind of calculation: terme_complet (default option) will calculate both the Coriolis and centrifugal forces, coriolis_seul will calculate the first one only, entrainement_seul will calculate the second one only.

34.9 Boussinesq_concentration

Description: Class to describe a source term that couples the movement quantity equation and constituent transport equation with the Boussinesq hypothesis.

```
See also: source_base (34)

Usage:
boussinesq_concentration str
Read str {
    c0 n x1 x2 ... xn
}
where
```

• **c0** *n x1 x2 ... xn*: Reference concentration field type. The only field type currently available is Champ_Uniforme (Uniform field).

34.10 Boussinesq_temperature

Description: Class to describe a source term that couples the movement quantity equation and energy equation with the Boussinesq hypothesis.

```
See also: source_base (34)

Usage:
boussinesq_temperature str
Read str {
    t0 str
    [verif_boussinesq int]
}
where
```

- **t0** *str*: Reference temperature value (oC or K). It can also be a time dependant function since the 1.6.6 version.
- **verif_boussinesq** *int*: Keyword to check (1) or not (0) the reference value in comparison with the mean value in the domain. It is set to 1 by default.

34.11 Canal_perio

Description: Momentum source term to maintain flow rate. The expression of the source term is: S(t) = (2*(Q(0) - Q(t))-(Q(0)-Q(t-dt))/(coeff*dt*area)

Where:

coeff=damping coefficient area=area of the periodic boundary Q(t)=flow rate at time t dt=time step

Three files will be created during calculation on a datafile named DataFile.data. The first file contains the flow rate evolution. The second file is useful for resuming a calculation with the flow rate of the previous stopped calculation, and the last one contains the pressure gradient evolution:

```
-DataFile_Channel_Flow_Rate_ProblemName_BoundaryName
-DataFile_Channel_Flow_Rate_repr_ProblemName_BoundaryName
-DataFile_Pressure_Gradient_ProblemName_BoundaryName

See also: source_base (34)

Usage:
canal_perio str
Read str {

    [u_etoile float]
    [coeff float]
    [h float]
    bord str
    [debit_impose float]
}
where

• u_etoile float
```

- coeff float: Damping coefficient (optional, default value is 10).
- h float: Half heigth of the channel.
- **bord** *str*: The name of the (periodic) boundary normal to the flow direction.
- **debit_impose** *float*: Optional option to specify the aimed flow rate Q(0). If not used, Q(0) is computed by the code after the projection phase, where velocity initial conditions are slightly changed to verify incompressibility.

34.12 Coriolis

Description: Keyword for a Coriolis term in hydraulic equation. Warning: Only available in VDF.

```
See also: source_base (34)

Usage:
coriolis str
Read str {
    omega n x1 x2 ... xn
}
where
• omega n x1 x2 ... xn: Value of omega.
```

34.13 Darcy

Description: Class for calculation in a porous media with source term of Darcy -nu/K*V. This keyword must be used with a permeability model. For the moment there are two models: permeability constant or Ergun's law. Darcy source term is available for quasi compressible calculation. A new keyword is aded for porosity (porosite).

```
See also: source_base (34)
Usage:
darcy bloc
where
```

• **bloc** *bloc_lecture* (3.59): Description.

34.14 Dirac

Description: Class to define a source term corresponding to a volume power release in the energy equation.

See also: source_base (34)

Usage:

dirac position ch

where

- **position** *n x1 x2 ... xn*
- **ch** *champ_base* (16.1): Thermal power field type. To impose a volume power on a domain sub-area, the Champ_Uniforme_Morceaux (partly_uniform_field) type must be used. Warning: The volume thermal power is expressed in W.m-3.

34.15 Flux_interfacial

Description: Source term of mass transfer between phases connected by the saturation object defined in saturation_xxxx

See also: source_base (34)

Usage:

flux interfacial

34.16 Forchheimer

Description: Class to add the source term of Forchheimer -Cf/sqrt(K)*V2 in the Navier-Stokes equations. We must precise a permeability model: constant or Ergun's law. Moreover we can give the constant Cf: by default its value is 1. Forchheimer source term is available also for quasi compressible calculation. A new keyword is aded for porosity (porosite).

See also: source_base (34)

Usage:

forchheimer bloc

where

• **bloc** *bloc_lecture* (3.59): Description.

34.17 Frottement_interfacial

Description: Source term which corresponds to the phases friction at the interface

See also: source_base (34)

Usage:

frottement_interfacial str

Read str {

[a_res float]

```
[ dv_min float]
[ exp_res int]
}
where
```

- **a_res** *float*: void fraction at which the gas velocity is forced to approach liquid velocity (default alpha_evanescence*100)
- dv_min float: minimal relative velocity used to linearize interfacial friction at low velocities
- exp_res int: exponent that callibrates intensity of velocity convergence (default 2)

34.18 Perte_charge_anisotrope

```
Description: Anisotropic pressure loss.

See also: source_base (34)

Usage:
perte_charge_anisotrope str
Read str {

lambda str
lambda_ortho str
diam_hydr champ_don_base
direction champ_don_base
[ sous_zone str]
}

where
```

- lambda str: Function for loss coefficient which may be Reynolds dependant (Ex: 64/Re).
- lambda_ortho *str*: Function for loss coefficient in transverse direction which may be Reynolds dependant (Ex: 64/Re).
- **diam_hydr** *champ_don_base* (16.9): Hydraulic diameter value.
- **direction** *champ_don_base* (16.9): Field which indicates the direction of the pressure loss.
- **sous_zone** *str*: Optional sub-area where pressure loss applies.

34.19 Perte_charge_circulaire

```
Description: New pressure loss.

See also: source_base (34)

Usage:
perte_charge_circulaire str
Read str {

lambda str
diam_hydr champ_don_base
[sous_zone str]
lambda_ortho str
diam_hydr_ortho champ_don_base
direction champ_don_base
```

```
}
where
```

- lambda str: Function f(Re_tot, Re_long, t, x, y, z) for loss coefficient in the longitudinal direction
- diam_hydr champ_don_base (16.9): Hydraulic diameter value.
- sous_zone str: Optional sub-area where pressure loss applies.
- lambda_ortho str: function: Function f(Re_tot, Re_ortho, t, x, y, z) for loss coefficient in transverse direction
- diam_hydr_ortho champ_don_base (16.9): Transverse hydraulic diameter value.
- **direction** *champ_don_base* (16.9): Field which indicates the direction of the pressure loss.

34.20 Perte_charge_directionnelle

Description: Directional pressure loss (available in VEF and PolyMAC).

```
See also: source_base (34)

Usage:
perte_charge_directionnelle str
Read str {
    lambda str
    diam_hydr champ_don_base
    direction champ_don_base
    [ sous_zone str]
}
where
```

- lambda str: Function for loss coefficient which may be Reynolds dependant (Ex: 64/Re).
- **diam_hydr** *champ_don_base* (16.9): Hydraulic diameter value.
- **direction** *champ_don_base* (16.9): Field which indicates the direction of the pressure loss.
- sous_zone str: Optional sub-area where pressure loss applies.

34.21 Perte_charge_isotrope

Description: Isotropic pressure loss (available in VEF and PolyMAC).

```
See also: source_base (34)

Usage:
perte_charge_isotrope str

Read str {
    lambda str
    diam_hydr champ_don_base
    [ sous_zone str]
}
where
```

- lambda str: Function for loss coefficient which may be Reynolds dependant (Ex: 64/Re).
- diam_hydr champ_don_base (16.9): Hydraulic diameter value.
- sous_zone str: Optional sub-area where pressure loss applies.

34.22 Perte_charge_reguliere

Description: Source term modelling the presence of a bundle of tubes in a flow.

See also: source_base (34)

Usage:

perte_charge_reguliere spec zone_name
where

- spec spec_pdcr_base (34.23): Description of longitudinale or transversale type.
- **zone_name** *str*: Name of the sub-area occupied by the tube bundle. A Sous_Zone (Sub-area) type object called zone_name should have been previously created.

34.23 Spec_pdcr_base

Description: Class to read the source term modelling the presence of a bundle of tubes in a flow. Cf=A Re-B.

See also: objet_lecture (39) longitudinale (34.23.1) transversale (34.23.2)

Usage:

spec_pdcr_base

34.23.1 Longitudinale

Description: Class to define the pressure loss in the direction of the tube bundle.

See also: spec_pdcr_base (34.23)

Usage:

longitudinale dir dd ch_a a [ch_b][b] where

- dir str into ['x', 'y', 'z']: Direction.
- **dd** *float*: Tube bundle hydraulic diameter value. This value is expressed in m.
- **ch_a** *str into ['a', 'cf']*: Keyword to be used to set law coefficient values for the coefficient of regular pressure losses.
- a float: Value of a law coefficient for regular pressure losses.
- ch_b str into ['b']: Keyword to be used to set law coefficient values for regular pressure losses.
- **b** *float*: Value of a law coefficient for regular pressure losses.

34.23.2 Transversale

Description: Class to define the pressure loss in the direction perpendicular to the tube bundle.

See also: spec_pdcr_base (34.23)

Usage:

transversale dir dd chaine_d d ch_a a [ch_b][b] where

- dir str into ['x', 'y', 'z']: Direction.
- **dd** *float*: Value of the tube bundle step.

- chaine_d str into ['d']: Keyword to be used to set the value of the tube external diameter.
- **d** *float*: Value of the tube external diameter.
- **ch_a** *str into ['a', 'cf']*: Keyword to be used to set law coefficient values for the coefficient of regular pressure losses.
- a *float*: Value of a law coefficient for regular pressure losses.
- ch_b str into ['b']: Keyword to be used to set law coefficient values for regular pressure losses.
- **b** *float*: Value of a law coefficient for regular pressure losses.

34.24 Perte_charge_singuliere

Description: Source term that is used to model a pressure loss over a surface area (transition through a grid, sudden enlargement) defined by the faces of elements located on the intersection of a subzone named subzone_name and a X,Y, or Z plane located at X,Y or Z = location.

```
See also: source_base (34)

Usage:
perte_charge_singuliere str
Read str {

    dir str into ['kx', 'ky', 'kz', 'K']
    [coeff float]
    [regul bloc_lecture]
    surface bloc_lecture
}
where
```

- dir str into ['kx', 'ky', 'kz', 'K']: KX, KY or KZ designate directional pressure loss coefficients for respectively X, Y or Z direction. Or in the case where you chose a target flow rate with regul. Use K for isotropic pressure loss coefficient
- **coeff** *float*: Value (float) of friction coefficient (KX, KY, KZ).
- **regul** *bloc_lecture* (3.59): option to have adjustable K with flowrate target { K0 valeur_initiale_de_k deb debit_cible eps intervalle_variation_mutiplicatif}.
- **surface** *bloc_lecture* (3.59): Three syntaxes are possible for the surface definition block:

```
For VDF and VEF: { X|Y|Z = location subzone_name }
Only for VEF: { Surface surface_name }.
For polymac { Surface surface_name Orientation champ_uniforme }
```

34.25 Puissance_thermique

Description: Class to define a source term corresponding to a volume power release in the energy equation.

```
See also: source_base (34)
Usage:
puissance_thermique ch
where
```

• **ch** *champ_base* (16.1): Thermal power field type. To impose a volume power on a domain sub-area, the Champ_Uniforme_Morceaux (partly_uniform_field) type must be used.

Warning: The volume thermal power is expressed in W.m-3 in 3D (in W.m-2 in 2D). It is a power

per volume unit (in a porous media, it is a power per fluid volume unit).

34.26 Radioactive_decay

Description: Radioactive decay source term of the form $-\lambda_{i}c_{i}$, where $0 \le i \le N$, N is the number of component of the constituent, c_{i} and λ_{i} are the concentration and the decay constant of the i-th component of the constituent.

```
See also: source_base (34)
Usage:
radioactive_decay val
where
```

• val n x1 x2 ... xn: n is the number of decay constants to read (int), and val1, val2... are the decay constants (double)

34.27 Source_constituant

Description: Keyword to specify source rates, in [[C]/s], for each one of the nb constituents. [C] is the concentration unit.

```
See also: source_base (34)

Usage:
source_constituant ch
where

• ch champ_base (16.1): Field type.
```

34.28 Source_generique

Description: to define a source term depending on some discrete fields of the problem and (or) analytic expression. It is expressed by the way of a generic field usually used for post-processing.

```
See also: source_base (34)

Usage:
source_generique champ
where

• champ champ_generique_base (9): the source field
```

34.29 Source_pdf

Description: Source term for Penalised Direct Forcing (PDF) method.

```
See also: source_pdf_base (34.31)

Usage:
source_pdf str

Read str {

aire champ_base
rotation champ_base
```

```
[ transpose_rotation ]
    modele bloc_pdf_model
    [interpolation interpolation_ibm_base]
}
where
```

- aire champ_base (16.1) for inheritance: volumic field: a boolean for the cell (0 or 1) indicating if the obstacle is in the cell
- **rotation** *champ_base* (16.1) for inheritance: volumic field with 9 components representing the change of basis on cells (local to global). Used for rotating cases for example.
- transpose_rotation for inheritance: whether to transpose the basis change matrix.
- modele bloc_pdf_model (34.30) for inheritance: model used for the Penalized Direct Forcing
- interpolation interpolation_ibm_base (18) for inheritance: interpolation method

34.30 Bloc_pdf_model

```
Description: not_set

See also: objet_lecture (39)

Usage:
{

    eta float
        [bilan_pdf int]
        [temps_relaxation_coefficient_pdf float]
        [local]
        [vitesse_imposee_data champ_base]
        [vitesse_imposee_fonction n word1 word2 ... wordn]
        [variable_imposee_fonction n word1 word2 ... wordn]
}

where
```

- eta *float*: penalization coefficient
- bilan_pdf int: type de bilan du terme PDF (seul/avec temps/avec convection)
- temps_relaxation_coefficient_pdf float: time relaxation on the forcing term to help
- echelle_relaxation_coefficient_pdf float: time relaxation on the forcing term to help convergence
- local: whether the prescribed velocity is expressed in the global or local basis
- vitesse imposee data champ base (16.1): Prescribed velocity as a field
- vitesse_imposee_fonction n word1 word2 ... wordn: Prescribed velocity as a set of ananlytical component
- variable_imposee_data champ_base (16.1): Prescribed variable as a field
- variable_imposee_fonction *n word1 word2 ... wordn*: Prescribed variable as a set of ananlytical component

34.31 Source pdf base

Description: Basic class of source PDF terms introduced in the equation.

```
See also: Source_dep_inco_bases (34.7) source_pdf (34.29)
```

```
Usage:
source_pdf_base str

Read str {

aire champ_base
rotation champ_base
[transpose_rotation]
modele bloc_pdf_model
[interpolation interpolation_ibm_base]
}
where
```

- aire champ_base (16.1): volumic field: a boolean for the cell (0 or 1) indicating if the obstacle is in the cell
- **rotation** *champ_base* (16.1): volumic field with 9 components representing the change of basis on cells (local to global). Used for rotating cases for example.
- **transpose_rotation**: whether to transpose the basis change matrix.
- modele bloc_pdf_model (34.30): model used for the Penalized Direct Forcing
- interpolation interpolation_ibm_base (18): interpolation method

34.32 Source_qdm

Description: Momentum source term in the Navier-Stokes equations.

```
See also: source_base (34)

Usage:
source_qdm ch
where

• ch champ_base (16.1): Field type.
```

34.33 Source_qdm_lambdaup

Description: This source term is a dissipative term which is intended to minimise the energy associated to non-conformscales u' (responsible for spurious oscillations in some cases). The equation for these scales can be seen as: du'/dt = -lambda. u' + grad P' where -lambda. u' represents the dissipative term, with lambda = a/Delta t For Crank-Nicholson temporal scheme, recommended value for a is 2.

Remark: This method requires to define a filtering operator.

```
See also: source_base (34)

Usage:
source_qdm_lambdaup str

Read str {

    lambda float
    [lambda_min float]
    [lambda_max float]
    [ubar_umprim_cible float]
}
where
```

- lambda float: value of lambda
- lambda_min float: value of lambda_min
- lambda_max *float*: value of lambda_max
- ubar_umprim_cible float: value of ubar_umprim_cible

34.34 Source_th_tdivu

Description: This term source is dedicated for any scalar (called T) transport. Coupled with upwind (amont) or muscl scheme, this term gives for final expression of convection: div(U.T)-T.div(U)=U.grad(T) This ensures, in incompressible flow when divergence free is badly resolved, to stay in a better way in the physical boundaries.

Warning: Only available in VEF discretization.

```
See also: source_base (34)
Usage:
source th tdivu
```

34.35 Terme_puissance_thermique_echange_impose

Description: Source term to impose thermal power according to formula: P = himp * (T - Text). Where T is the Trust temperature, Text is the outside temperature with which energy is exchanged via an exchange coefficient himp

```
See also: source_base (34)

Usage:
terme_puissance_thermique_echange_impose str

Read str {
    himp champ_base
    Text champ_base
    [PID_controler_on_targer_power bloc_lecture]
}
where
```

- himp champ_base (16.1): the exchange coefficient
- **Text** *champ_base* (16.1): the outside temperature
- PID_controler_on_targer_power bloc_lecture (3.59): PID_controler_on_targer_power bloc with parameters target_power (required), Kp, Ki and Kd (at least one of them should be provided)

34.36 Travail_pression

Description: Source term which corresponds to the additional pressure work term that appears when dealing with compressible multiphase fluids

```
See also: source_base (34)
Usage:
travail_pression
```

34.37 Vitesse_derive_base

Description: Source term which corresponds to the drift-velocity between a liquid and a gas phase

```
See also: vitesse_relative_base (34.38)
Usage:
vitesse_derive_base
```

34.38 Vitesse_relative_base

Description: Basic class for drift-velocity source term between a liquid and a gas phase

```
See also: source_base (34) vitesse_derive_base (34.37)
Usage:
vitesse_relative_base
```

35 sous_zone

Synonymous: sous_domaine

Description: It is an object type describing a domain sub-set.

A Sous_Zone (Sub-area) type object must be associated with a Domaine type object. The Read (Lire) interpretor is used to define the items comprising the sub-area.

Caution: The Domain type object nom_domaine must have been meshed (and triangulated or tetrahedralised in VEF) prior to carrying out the Associate (Associer) nom_sous_zone nom_domaine instruction; this instruction must always be preceded by the read instruction.

```
See also: objet u (40)
Usage:
sous_zone str
Read str {
     [ restriction str]
     [ rectangle bloc_origine_cotes]
     [ segment bloc_origine_cotes]
     [boite bloc_origine_cotes]
     [ liste n n1 n2 \dots nn]
     [fichier str]
     [intervalle deuxentiers]
     [ polynomes bloc_lecture]
     [couronne bloc_couronne]
     [ tube bloc_tube]
     [fonction sous zone str]
     [union str]
}
where
```

- **restriction** *str*: The elements of the sub-area nom_sous_zone must be included into the other sub-area named nom_sous_zone2. This keyword should be used first in the Read keyword.
- **rectangle** *bloc_origine_cotes* (35.1): The sub-area will include all the domain elements whose centre of gravity is within the Rectangle (in dimension 2).

- segment bloc_origine_cotes (35.1)
- **boite** *bloc_origine_cotes* (35.1): The sub-area will include all the domain elements whose centre of gravity is within the Box (in dimension 3).
- liste n n1 n2 ... nn: The sub-area will include n domain items, numbers No. 1 No. i No. n.
- **fichier** *str*: The sub-area is read into the file filename.
- **intervalle** *deuxentiers* (35.2): The sub-area will include domain items whose number is between n1 and n2 (where n1<=n2).
- **polynomes** *bloc_lecture* (3.59): A REPRENDRE
- **couronne** *bloc couronne* (35.3): In 2D case, to create a couronne.
- **tube** *bloc_tube* (35.4): In 3D case, to create a tube.
- **fonction_sous_zone** *str*: Keyword to build a sub-area with the elements included into the area defined by fonction>0.
- **union** *str*: The elements of the sub-area nom_sous_zone3 will be added to the sub-area nom_sous_zone. This keyword should be used last in the Read keyword.

35.1 Bloc_origine_cotes

Description: Class to create a rectangle (or a box).

See also: objet_lecture (39)

Usage:

name origin name2 cotes

where

- name str into ['Origine']: Keyword to define the origin of the rectangle (or the box).
- origin x1 x2 (x3): Coordinates of the origin of the rectangle (or the box).
- name2 str into ['Cotes']: Keyword to define the length along the axes.
- cotes $x1 \ x2 \ (x3)$: Length along the axes.

35.2 Deuxentiers

Description: Two integers.

See also: objet_lecture (39)

Usage:

int1 int2

where

- int1 int: First integer.
- int2 int: Second integer.

35.3 Bloc couronne

Description: Class to create a couronne (2D).

See also: objet_lecture (39)

Usage:

name origin name3 ri name4 re

where

- name str into ['Origine']: Keyword to define the center of the circle.
- origin $x1 \ x2 \ (x3)$: Center of the circle.

- name3 str into ['ri']: Keyword to define the interior radius.
- ri float: Interior radius.
- name4 str into ['re']: Keyword to define the exterior radius.
- re float: Exterior radius.

35.4 Bloc tube

Description: Class to create a tube (3D).

See also: objet_lecture (39)

Usage:

name origin name2 direction name3 ri name4 re name5 h where

- name str into ['Origine']: Keyword to define the center of the tube.
- origin x1 x2 (x3): Center of the tube.
- name2 str into ['dir']: Keyword to define the direction of the main axis.
- direction str into ['X', 'Y', 'Z']: direction of the main axis X, Y or Z
- name3 str into ['ri']: Keyword to define the interior radius.
- ri *float*: Interior radius.
- name4 str into ['re']: Keyword to define the exterior radius.
- re float: Exterior radius.
- name5 str into ['hauteur']: Keyword to define the heigth of the tube.
- **h** *float*: Heigth of the tube.

36 turbulence_paroi_base

Description: Basic class for wall laws for Navier-Stokes equations.

See also: objet_u (40) negligeable (36.1)

Usage:

36.1 Negligeable

Description: Keyword to suppress the calculation of a law of the wall with a turbulence model. The wall stress is directly calculated with the derivative of the velocity, in the direction perpendicular to the wall (tau_tan /rho= nu dU/dy).

Warning: This keyword is not available for k-epsilon models. In that case you must choose a wall law.

See also: turbulence_paroi_base (36)

Usage:

negligeable

37 turbulence_paroi_scalaire_base

Description: Basic class for wall laws for energy equation.

See also: objet_u (40) negligeable_scalaire (37.1)

Usage:

37.1 Negligeable_scalaire

Description: Keyword to suppress the calculation of a law of the wall with a turbulence model for thermohydraulic problems. The wall stress is directly calculated with the derivative of the velocity, in the direction perpendicular to the wall.

```
See also: turbulence_paroi_scalaire_base (37)
Usage:
negligeable_scalaire
```

38 listobj_impl

```
Description: not_set

See also: objet_u (40) listobj (38.5)

Usage:
```

38.1 Milieu_musig

Description: MUSIG medium made of several sub mediums.

```
See also: listobj (38.5)

Usage: { object1 object2 .... } list of milieu_base (22)
```

38.2 Milieu_composite

Description: Composite medium made of several sub mediums.

```
See also: listobj (38.5)

Usage: { object1 object2 .... } list of milieu_base (22)
```

38.3 List_un_pb

```
Description: pour les groupes

See also: listobj (38.5)

Usage:
{ object1 , object2 .... }
list of un_pb (38.4) separeted with ,
```

38.4 Un_pb

```
Description: pour les groupes
See also: objet_lecture (39)
```

Usage: **mot** where

• mot str: the string

38.5 Listobj

Description: List of objects.

See also: listobj_impl (38) listchamp_generique (9.2) definition_champs (4.2.1) sondes (4.2.4) champs_a_post (4.2.24) list_stat_post (4.2.29) post_processings (4.3) liste_post_ok (4.4) liste_post (4.5) list_un_pb (38.3) list_list_nom (4.24) condlims (5.4) condinits (5.5) sources (5.6) pp (5.29) Milieu_composite (38.2) Milieu_MUSIG (38.1) listeqn (4.12) reactions (10.1) list_nom_virgule (9.3) listsous_zone_valeur (5.2.11) list_info_med (4.54) list_bord (3.71.4) list_bloc_mailler (3.71) vect_nom (3.129) list_nom (3.114) list_points (4.2.8) coarsen_operators (3.79)

Usage:

39 objet_lecture

Description: Auxiliary class for reading.

See also: objet_u (40) bloc_lecture (3.59) deuxmots (5.35) troismots (39.1) quatremots (39.2) deuxentiers (35.2) floatfloat (5.37) entierfloat (39.3) bloc_lecture_poro (28.1) postraitement_base (4.4.2) definition-_champ (4.2.2) definition_champs_fichier (4.2.3) sonde_base (4.2.6) sonde (4.2.5) sondes_fichier (4.2.22) champ a post (4.2.25) champs posts (4.2.23) bloc fichier (4.2.27) champs posts fichier (4.2.26) statpost deriv (4.2.30) stats posts (4.2.28) stats posts fichier (4.2.36) stats serie posts (4.2.37) stats serie-_posts_fichier (4.2.38) un_postraitement (4.3.1) nom_postraitement (4.4.1) type_un_post (4.5.2) type_postraitement-_ft_lata (4.5.3) un_postraitement_spec (4.5.1) format_file_base (4.6) un_pb (38.4) troisf (3.52) convection-_deriv (5.2.1) bloc_convection (5.2) diffusion_deriv (5.3.1) op_implicite (5.3.17) bloc_diffusion (5.3) condlimlu (5.4.1) condinit (5.5.1) parametre_equation_base (5.7) dt_impr_ustar_mean_only (5.41.1) modele_turbulence-_hyd_deriv (5.41) form_a_nb_points (5.41.3) traitement_particulier_base (5.36.1) penalisation_12_ftd_lec (5.29.1) traitement_particulier (5.36) dt_impr_nusselt_mean_only (23.1) type_diffusion_turbulente_multiphase-_deriv (5.3.3) bloc_sutherland (22.7) spec_pdcr_base (34.23) type_perte_charge_deriv (34.4) reaction (10.1.1) verifiercoin_bloc (3.132) bloc_ef (5.2.6) bloc_origine_cotes (35.1) bloc_couronne (35.3) bloc_tube (35.4) sous_zone_valeur (5.2.12) bloc_diffusion_standard (5.3.12) info_med (4.54.1) bloc_lec_champ_init_canal-_sinal (16.20) fonction_champ_reprise (16.16) bord_base (3.71.5) defbord (3.71.7) mailler_base (3.71.1) bloc_pave (3.71.3) lecture_bloc_moment_base (3.24) un_point (3.24.3) remove_elem_bloc (3.102) blocdecouper (3.84) bloc pdf model (34.30) format lata to CGNS (3.64) format lata to med (3.66) Coarsen-Operator Uniform (3.79.1)

Usage:

39.1 Troismots

Description: Three words.

See also: objet_lecture (39)

Usage:

mot 1 mot 2 mot 3

where

- mot_1 str: First word.
 mot_2 str: Snd word.
- mot_3 *str*: Third word.

39.2 Quatremots

Description: Three words.

See also: objet_lecture (39)

Usage:

mot_1 mot_2 mot_3 mot_4 where

- mot_1 str: First word.
- mot_2 *str*: Snd word.
- mot_3 *str*: Third word.
- **mot_4** *str*: Fourth word.

39.3 Entierfloat

Description: An integer and a real.

See also: objet_lecture (39)

Usage:

the_int the_float

where

- the_int int: Integer.
- the_float float: Real.

40 index

Index

.1. 202 202	14: 1 70 . 02
edo, 292, 293	multiple , 78, 92
elem, 53, 85, 88, 254, 255, 258, 259	musel, 156
emissivite, 238	natural, 312
entrainement_seul, 383	nb_pas_dt_post , 85–87, 89
euclidian_norm, 224	no, 222
faces, 85, 88	nodes, 80
fichier, 302, 303	non, 56
filtrer_resu , 155, 163	normalized_euclidian_norm, 224
Fluctu_Temperature_ext, 238	norme , 226
flux_bords , 222, 223	nu, 163
Flux_Chaleur_Turb_ext, 238	nu_transp, 163
flux_surfacique_bords, 222, 223	nut, 163
fonction, 260	nut_transp, 163
format_post_sup, 44, 45	omega_ext, 238
formatte, 33, 85, 86, 259	Origine, 396, 397
formule, 226	oui, 56
grad_Ubar, 163	pdi, 259
grav, 80	periode, 80
gravel, 80	post_processing, 93
H_ext, 238	postraitement, 93
h_imp, 238, 246, 247	postraitement_ft_lata, 94
hauteur, 397	postraitement_lata , 94
homogene, 48	produit_scalaire, 226
implicite, 164	rcm, 312
integrale_en_z, 43	re, 397
K, 390	ri , 397
k, 248	sans_rien, 189, 190, 195, 197–199, 208–212
K_Eps_ext, 238	scotti, 201–205
k_ext, 238	simple, 78, 92
K_Omega_ext, 238	single_hdf, 259
kelvin, 238	single_lata, 59, 78, 92
kx , 390	Slambda , 294
ky, 390	solveur, 164
kz, 390	som , 53, 80, 85, 88, 254, 255, 258, 259
L1_norm, 224	somme, 224
L2,66	somme_ponderee , 224
L2_norm , 224	somme_ponderee_porosite, 224
last_time , 21	stabilite , 222, 223
lata, 44, 45, 59, 78, 92	standard , 292, 293
lata_v2, 44, 45, 59, 78, 92	sum, 224
left_value, 224	superbee , 156
lml, 44, 45, 59, 78, 92	surface, 381
local, 48	T0, 294
max , 66, 224	T_ext, 238
med , 44, 45, 59, 78, 92	t_ext, 238, 246, 247
med_major , 78, 92	tau_ext, 238
min, 224	temperature_unit, 238
minmod, 156	terme_complet, 383
mixed, 54	trace, 220, 221
moins_rho_moyen, 292, 293	transportant_bar , 155
moyenne, 224	transporte_bar, 155
moyenne_ponderee, 224	u_tau, 304
mpi-io, 78, 92	V2_ext, 238
mu0, 294	valeur_a_gauche, 224

valeur_normale, 274	sans_dec , 24
vanalbada, 156	save_matrice , 230–234, 376, 378
vanleer, 156	sigma , 161
vecteur, 226	sondes , 78, 92
visco_cin, 304	sondes_fichier , 78, 92
vitesse_paroi, 248	sondes_mobiles , 78, 92
vitesse_tangentielle, 276	sondes_mobiles_fichier , 78, 92
volume, 201–205	sous_domaine , 36, 78, 92
volume_sans_lissage, 201–205	statistiques , 79, 92
weighted_average, 224	statistiques_en_serie , 79, 93
weighted_sum, 224	statistiques_en_serie_fichier , 79, 93
weighted_sum_porosity, 224	statistiques_fichier , 79, 93
X, 49, 66, 397	tension_superficielle , 214, 215
x, 389	a_res , 387
xyz, 259	acceleration, 383
Y, 49, 66, 397	aij , 379
y, 389	aire, 392, 393
Y_ext, 238	alias , 178, 180
yes , 222	alpha , 22, 154, 156
Z, 49, 66, 397	alpha_0 , 311
z, 389	alpha_1 , 311
, 29, 55, 58, 153, 159, 191, 309, 381	alpha_a , 311
all_options , 56	alpha_sous_zone , 156
champs , 78, 92	amont_sous_zone , 156
champs_fichier , 79, 92	ampli_bruit , 261
conditions_initiales , 152, 167–190, 196, 198, 199,	ampli_fluctuation , 275
209, 211, 212	ampli_moyenne_imposee , 275
conditions_limites , 152, 167–176, 178–190, 196,	ampli_moyenne_recyclee , 275
198, 199, 209, 211, 212	ampli_sin , 261
definition_champs_fichier , 78, 92	ascii , 25, 69
domain, 26	atol , 371–374, 376, 379, 380
domaine, 59	avec_certains_bords , 38
exclude_groups , 26	avec_certains_bords_pour_extraire_surface , 37
fichier , 59, 79, 85	avec_les_bords , 38
file , 26	bench_ijk_splitting_read , 25
include_additional_face_groups , 26	bench_ijk_splitting_write , 25
is_multi_scalar , 178, 180	beta, 382, 383
maillage_vdf , 24	beta_co , 291, 292
mesh , 26	beta_th , 291, 292
name_of_initial_domaines , 25	bilan_pdf , 392
name_of_new_domaines , 25	binaire , 31, 59
par_sous_zone , 20	binary_file , 34
partitionneur, 57	block_size_bytes , 25
postraitement , 77, 96–100, 102, 103, 105, 107–	block_size_megabytes, 25
110, 112–114, 116–119, 121–124, 126–	boite, 396
130, 132–135, 137–139, 141–144, 146–	bord , 29, 52, 192, 385
149, 151	bords_a_decouper , 31
postraitements , 77, 96–99, 101, 102, 104, 105,	boundaries , 34, 201, 300
	boundary_conditions , 152, 167–176, 178–190,
130, 132–135, 137–139, 141–143, 145–	196, 198, 199, 209, 211, 212
148, 150, 151	boundary_xmax , 51
pr_t , 161	boundary_xmin , 51
Read_file, 76	boundary_ymax , 51
reduction_pression, 363	boundary_ymin , 51

boundary_zmax , 51	$convection_diffusion_temperature_turbulent\ , 109,$
boundary_zmin , 51	113, 138, 139, 147, 149
btd , 158	convertalltopoly, 26
c0 , 384	correction_calcul_pression_initiale , 197
calc_spectre , 194	correction_fraction , 284
canalx, 205	correction_matrice_pression , 197
centre_rotation , 383	correction_matrice_projection_initiale , 197
champ_med , 43	correction_pression_modifie , 197
changement_de_base_p1bulle , 252	correction_variable_initiale , 167, 186, 197
check_divergence , 23	correction_visco_turb_pour_controle_pas_de_temps
checkpoint_fname , 95	, 200, 202–204, 206, 207
cl_pression_sommet_faible , 252	correction_visco_turb_pour_controle_pas_de_temps
cli, 376, 378	_parametre , 200, 202–204, 206, 207
cli_quiet , 376	correction_vitesse_modifie , 197
coarsen_operators , 54	correction_vitesse_projection_initiale , 197
coef , 287	correlations , 103, 105, 106, 131
coeff, 385, 390	correspondance_elements , 278-281
coefficient_diffusion , 289	corriger_partition , 306
coefficients_activites , 228	couronne, 396
compo , 218, 223	Cp , 281–283, 285, 286
condition_elements , 36, 38	cp , 34, 244, 245, 284–286, 288–299
condition_faces , 38	crank , 166
condition_geometrique , 31	critere_absolu , 39
Conduction, 77	criteres_convergence , 364, 366
Conduction_ibm , 96	cs , 161, 203
conservation_Ec , 194	cstdiff, 160
constante_modele_micro_melange , 227	Cv , 285, 286, 297
constante_taux_reaction, 228	cw , 160, 204
constituant , 77, 96–100, 102, 103, 105, 107–111,	
113, 114, 116–119, 121–125, 127–130, 132-	-debit , 244, 245
136, 138, 139, 141–144, 146–149, 151	debit_impose , 385
contre_energie_activation , 228	debut_stat , 192
contre_reaction , 228	decoup, 254, 255, 259
controle_residu , 232, 364–370	default_value, 254
convection , 152, 167–177, 179–190, 196, 198,	definition_champs , 78, 92
199, 209, 211, 212	definition_champs_file , 78, 92
convection_diffusion_chaleur_QC , 133, 140	delta , 243
convection_diffusion_chaleur_turbulent_qc , 143,	
148	derivee_rotation, 288
convection_diffusion_chaleur_WC , 134, 142	dh, 245
convection_diffusion_concentration, 97, 108, 119,	diag , 232
121, 135, 137	diam_hydr , 387, 388
convection_diffusion_concentration_turbulent ,	diam_hydr_ortho , 388
98, 109, 122, 123, 138, 139	diametre_hyd_champ , 288–299
convection_diffusion_espece_binaire_QC , 126	diffusion , 152, 167–177, 179–190, 196, 198, 199,
Convection_Diffusion_Espece_Binaire_Turbulent-	
_QC , 128	diffusion_coeff , 282, 283, 285
convection_diffusion_espece_binaire_WC , 127	diffusion_implicite, 316, 318, 321, 323, 325, 327,
convection_diffusion_temperature, 108, 112, 132,	329, 331, 333, 335, 337, 339, 341, 343,
135, 137, 146	345, 347, 350, 353, 355, 358, 360, 362
convection_diffusion_temperature_ibm , 144	dim_espace_krilov, 232
convection_diffusion_temperature_ibm_turbulent	<u>-</u>
, 110	dir_flow , 261
,	dir_wall, 261

direction , 29, 38–40, 192, 387, 388	Ec , 193
direction_anisotrope , 275	Ec_dans_repere_fixe , 193
disable_diphasique, 24	echelle_relaxation_coefficient_pdf , 392
disable_dt_ev , 317, 319, 322, 324, 325, 327, 329,	Echelle_temporelle_turbulente , 103, 105, 107
331, 333, 335, 337, 339, 341, 343, 345,	ecrire_decoupage , 57
348, 351, 353, 356, 358, 361, 363	ecrire_fichier_xyz_valeur , 152, 167–189, 191, 196,
disable_equation_residual , 152, 167–178, 180–	198, 200, 209, 211, 212
<u>-</u>	
190, 196, 198, 199, 209, 211, 212	ecrire_frontiere , 59
disable_progress , 317, 319, 321, 323, 325, 327,	ecrire_lata , 57
329, 331, 333, 335, 337, 339, 341, 343,	ecrire_med , 57
345, 348, 351, 353, 356, 358, 361, 363	elements_fluides , 279, 281
distance_plan , 275	elements_solides , 278–280
dmax , 205	emissivite_pour_rayonnement_entre_deux_plaques
dom_dist , 254	_quasi_infinies , 246
dom_loc , 254	energie_activation, 228
domain , 51, 59, 254, 255, 259	Energie_cinetique_turbulente , 103, 105, 107
domaine , 26, 29, 31, 36, 37, 39, 40, 78, 92, 221,	Energie_cinetique_turbulente_WIT , 103, 105,
222, 307	107
domaine_final , 20, 38	Energie_Multiphase , 103, 107
domaine_grossier, 31	Energie_Multiphase_h , 105
domaine_init , 20, 38	-
	enthalpie_reaction , 228
domaines , 59, 308	epaisseur, 37, 39
domegadt , 383	eps , 382
DP0,382	epsilon, 314
dropping_parameter , 376	equation_frequence_resolue , 166
dt, 34	equation_non_resolue , 153, 166–189, 191, 196,
dt_impr , 201, 244, 245, 300, 316, 318, 321, 323,	198, 200, 209, 211, 213
325, 326, 328, 330, 332, 335, 336, 338,	equations_scalaires_passifs , 117, 121, 123, 137,
341, 342, 344, 347, 350, 352, 355, 357,	139, 141–143, 146, 149
360, 362	espece , 182, 184
dt_impr_moy_spat , 192	espece_en_competition_micro_melange , 227
dt_impr_moy_temp , 192	est_dirichlet, 278–280
dt_impr_nusselt , 299–302	eta , 392
dt_impr_nusselt_mean_only , 299–302	evanescence , 174
dt_impr_ustar , 200, 201, 203, 204, 206, 207	exclure_groupes , 26
dt_impr_ustar_mean_only , 200, 202–204, 206,	exp_res , 387
-	A = '
207	expert_only , 76
dt_max , 316, 318, 320, 322, 324, 326, 328, 330,	exposant_beta , 228
332, 334, 336, 338, 340, 342, 344, 347,	expression , 227
350, 352, 355, 357, 360, 362	facon_init , 194
dt_min , 316, 318, 320, 322, 324, 326, 328, 330,	facsec , 316, 318, 321, 323, 325, 327, 329, 331,
332, 334, 336, 338, 340, 342, 344, 347,	333, 335, 337, 339, 341, 343, 345, 347,
350, 352, 355, 357, 360, 362	350, 352, 355, 358, 360, 362
dt_post , 78, 92	facsec_diffusion_for_sets , 364, 367
dt_projection, 190, 195, 197, 199, 208, 210, 212	facsec_expert, 357
dt_sauv , 316, 318, 320, 322, 324, 326, 328, 330,	facsec_func , 357
332, 334, 336, 338, 340, 342, 344, 347,	facsec_ini , 41
350, 352, 355, 357, 360, 362	facsec_max , 41, 318, 320, 346, 349, 351, 354, 357
dt_start , 316, 319, 321, 323, 325, 327, 329, 331,	facteur, 159
333, 335, 337, 339, 341, 343, 345, 348,	facteurs, 47
350, 353, 355, 358, 360, 362	fichier , 26, 78, 86, 92, 205, 256, 268, 276, 306,
dtol_fraction , 284	307, 396
dual , 59	fichier_ecriture_K_Eps , 205
dv min , 387	fichier matrice, 69

fichier_post , 29	himp , 394
fichier_secmem , 69	Hlsat, 215
fichier_solution, 69	Hvsat , 215
fichier_solveur , 69	ignore_check_fraction, 284
fichier_solveur_non_recree , 233	impr , 54, 69, 229–232, 234, 278–281, 288, 371–
fichier_sortie , 43	374, 376, 379, 380
fichier_ssz , 307	impr_diffusion_implicite, 316, 319, 321, 323, 325,
field , 254, 255, 259, 305	327, 329, 331, 333, 335, 337, 339, 341,
fields , 34, 78, 92	343, 345, 348, 350, 353, 355, 358, 360,
fields_file , 79, 92	362
file , 59, 79, 85, 254, 255, 259, 305	impr_extremums , 316, 319, 321, 323, 325, 327,
file_coord_x , 51	329, 331, 333, 335, 337, 339, 341, 343,
file_coord_y , 51	345, 348, 350, 353, 355, 358, 360, 362
· · · · · · · · · · · · · · · · · · ·	
file_coord_z , 51	inclure_groupes_faces_additionnels , 26
filling , 310	indice , 289–298
fin_stat , 192	info , 162
flow_rate , 277	init_Ec , 194
fluid , 281–283	initial_conditions , 152, 167–190, 196, 198, 199,
fluide_incompressible, 97–100, 102, 108–111, 113	
118–120, 122–124, 129, 131, 135, 136,	<u> </u>
138, 139, 144, 146, 147, 149	initial_value , 262, 263, 269, 270
fluide_ostwald , 131, 144	input_field , 263
fluide_quasi_compressible , 125, 128, 133, 140,	interp_ve1 , 24
143, 148	interpolation, 392, 393
fluide_sodium_gaz , 131	intervalle, 396
fluide_sodium_liquide , 131	inverse_condition_element , 37
fluide_weakly_compressible , 127, 134, 142	is_multi_scalar , 289
flux_paroi , 235	is_multi_scalar_diffusion , 178, 180
fonction, 65	iter_max , 364, 367
fonction_filtre , 53	iter_min , 364, 367
fonction_sous_zone , 396	iterations_mixed_solver , 54
force , 231	joints_non_postraites , 59
format , 59, 78, 92	k , 292
format_post , 53	k_min , 206
formulation_a_nb_points , 201, 203–205	kappa , 289–298
formulation_linear_pwl , 280	kmetis, 306
frequence_recalc , 233	l_melange , 161
function_coord_x , 51	lambda , 244, 245, 288–299, 387, 388, 393
function_coord_y , 51	lambda_max , 394
function_coord_z , 51	lambda_min , 394
gamma , 285, 286, 297	lambda_ortho , 387, 388
gas_turb , 161	larg_joint , 57
genere_fichier_solveur , 69	last_time , 254, 255, 259
ghost_size , 54	level , 312–314
ghost_thickness, 51	Lire_fichier , 76
gnuplot_header , 317, 319, 322, 324, 325, 327,	list_equations , 100, 102, 112, 113, 116
329, 331, 333, 335, 337, 339, 341, 343,	liste, 65, 396
345, 348, 351, 353, 356, 358, 361, 363	liste_cas , 35
gradient_pression_qdm_modifie , 197	liste_de_postraitements , 77, 96–99, 101, 102, 104,
gram_schmidt , 23	105, 107–110, 112–114, 116–118, 120–
gravite , 288–299	124, 126–130, 132–135, 137–139, 141–
groupes , 115	143, 145–148, 150, 151
h , 261, 385	liste_postraitements , 77, 96–99, 101, 102, 104,
hexa_old , 38	105, 107–109, 111–114, 116–118, 120–

104 106 120 120 125 127 120 141	manian staling them tombulant 00 110
124, 126–130, 132–135, 137–139, 141–	
143, 145–148, 150, 151	navier_stokes_QC , 126, 133, 140
loc , 254, 255, 259	navier_stokes_standard , 97, 100, 108, 112, 118,
local, 392	119, 121, 132, 135, 136, 146
localisation , 53, 222, 227	navier_stokes_turbulent , 98, 102, 109, 113, 122,
loi_etat , 293, 298	123, 129, 138, 139, 147, 149
longueur_boite, 194	navier_stokes_turbulent_qc , 128, 143, 148
longueur_maille , 201, 203–205	navier_stokes_WC , 127, 134, 142
longueurs, 47	nb_comp , 262, 263, 269, 270
Lvap , 215	nb_corrections_max , 364, 365, 367, 368, 370
maillage, 26	nb_full_mg_steps , 54
main , 58	nb_histo_boxes_impr , 278–281
mass_source, 195	nb_it_max , 230–232, 234, 364–370, 379
masse_molaire , 34, 178, 180	nb_ite_sans_accel_max , 41
Masse_Multiphase , 103, 105, 106	nb_nodes , 51
matrice_pression_penalisee_H1 , 197	nb_parts , 305–308
max_iter_implicite , 347, 349, 352, 354, 357, 359	nb_parts_geom , 31
mesh , 254, 255, 259	nb_parts_naif, 31
methode , 43, 221, 222, 224, 226	nb_parts_tot, 57
methode_calcul_pression_initiale , 190, 195, 197,	nb_pas_dt_max , 316, 319, 321, 323, 325, 327,
199, 209, 210, 212	329, 331, 333, 335, 337, 339, 341, 343,
milieu , 77, 96–100, 102, 103, 105, 107–110, 112–	345, 348, 350, 353, 356, 358, 360, 362
114, 116–119, 121–124, 126–130, 132–	nb_pas_dt_post , 78, 92
135, 137–139, 141–144, 146–149, 151	nb_pas_ut_post , 78, 92 nb_points_par_phase , 192
milieu_composite , 103, 105, 106	nb_procs , 35
Milieu_MUSIG , 103, 105, 106	nb_sauv_max , 316, 318, 321, 323, 324, 326, 328,
min_dir_flow , 261	330, 332, 334, 336, 338, 340, 342, 344,
min_dir_wall , 261	347, 350, 352, 355, 357, 360, 362
mobile_probes , 78, 92	nb_test, 69
mobile_probes_file , 78, 92	nb_tranche, 43
mode_calcul_convection , 175, 177	nb_tranches , 38–40
model , 281–283	nbelem , 213
modele , 392, 393	nbelem_i , 253
modele_micro_melange , 227	nbelem_j , 253
modele_turbulence , 168, 177, 179, 184, 187, 188,	nbelem_k , 253
199, 210, 212	new_jacobian , 162
models , 103, 105, 106	ng2, 160
modif_div_face_dirichlet , 252	niter_avg , 318, 320
molar_mass, 285	niter_max , 318, 320
molar_mass1 , 282, 283	niter_max_diffusion_implicite, 166, 317, 319, 321,
molar_mass2 , 282, 283	323, 325, 327, 329, 331, 333, 335, 337,
moyenne_convergee , 223	339, 341, 343, 345, 348, 350, 353, 356,
moyenne_imposee , 275	358, 360, 362
moyenne_recyclee , 275	niter_min , 318, 320
mu , 34, 244, 245, 285, 291–293, 297, 298	nmax, 26
mu1, 282, 283	no_alpha , 161
mu2, 282, 283	no_check_disk_space , 317, 319, 321, 323, 325,
multiple_files , 23	327, 329, 331, 333, 335, 337, 339, 341,
n , 245, 292	343, 345, 348, 351, 353, 356, 358, 361,
name_of_initial_zones , 25	363
name_of_new_zones , 25	no_conv_subiteration_diffusion_implicite , 316,
name_ssz , 307	319, 321, 323, 325, 327, 329, 331, 333,
nature , 254	335, 337, 339, 341, 343, 345, 348, 350,
navier stokes ihm 124 144	353, 357, 359, 341, 343, 343, 346, 350,
110 Y N. J. SIUNES 111111 . 1 / 7 . 1 44	1.1.1. 1.1.1. 1.10. 100. 100.

no_error_if_not_converged_diffusion_implicite ,	parallel_over_zone , 23
316, 319, 321, 323, 325, 327, 329, 331,	parallele , 78, 92
333, 335, 337, 339, 341, 343, 345, 348,	parametre_equation , 153, 167–189, 191, 196,
350, 353, 355, 358, 360, 362	198, 200, 209, 211, 212
no_qdm , 364–370	Partition_tool , 57
nom , 262, 263, 269, 270	pas_de_solution_initiale , 69
nom_bord , 38, 39	pb_champ , 224, 225
nom_champ , 253	pb_champ_evaluateur , 275
nom_cl_derriere , 40	pb_dist , 254
nom_cl_devant , 40	pb_loc , 253
nom_domaine , 53	pb_name, 58
nom_fichier_post , 53	pcshell , 379
nom_fichier_solveur , 233	penalisation_12_ftd , 185, 186
nom_fichier_sortie , 31	perio , 213
nom_frontiere , 221	perio_i , 253
nom_inconnue , 178, 179	perio_j , 253
nom_pb , 53	perio_k , 253
nom_source , 216–223, 225–227	perio_x , 51
nom_zones , 57	-
nombre_de_noeuds , 47	perio_y ,51
	perio_z ,51
noms_champs , 53	periode , 193
norm, 66	periode_calc_spectre , 194
normal_value, 269	periode_sauvegarde_securite_en_heures , 317, 319,
nproc , 213	321, 323, 325, 327, 329, 331, 333, 335,
nu , 162, 245, 246	337, 339, 341, 343, 345, 348, 350, 353,
nu_transp , 162	356, 358, 361, 363
numero , 222, 227	periodique , 57
numero_masse , 218	petsc_decide , 378
numero_op , 218	PID_controler_on_targer_power , 394
numero_source , 218	pinf , 297
nut , 162	point1 , 37
nut_max , 200, 202–204, 206, 207	point2, 37
nut_transp , 162	point3 , 37
old , 156	points_fluides , 279, 280
omega , 261, 311, 312, 315, 318, 383, 385	points_solides , 278–281
omega_relaxation_drho_dt , 293	polynomes, 396
optimisation_sous_maillage , 222	porosites , 288–299
optimized , 231, 234	porosites_champ , 288–299
option, 223, 383	position, 288
order, 23	Post_processing , 77, 96–100, 102, 103, 105, 107–
ordering, 312	110, 112–114, 116–119, 121–124, 126–
origin_i , 253	130, 132–135, 137–139, 141–144, 146–
origin_j , 253	149, 151
origin_k , 253	Post_processings , 77, 96–99, 101, 102, 104, 105,
Origine, 47	107–110, 112–114, 116–119, 121–124, 126–
origine, 37	130, 132–135, 137–139, 141–143, 145–
p0 , 252	148, 150, 151
p1,252	postraiter_gradient_pression_sans_masse , 190,
p_imposee_aux_faces , 56	195, 197, 199, 209, 210, 212
P_ref , 215, 295, 296	Pr_t , 161
p_ref , 214, 215	prandt_turbulent_fonction_nu_t_alpha , 301
P_sat , 215	Prandtl , 285, 286
pa , 252	prandtl , 284–286
par_sous_dom , 20	prandtl_turbulent , 161
par_sous_uom , 20	pranad_turvuttit , tor

prdt , 301	resolution_monolithique , 357
pre_smooth_steps , 54	restriction, 395
precision_impr , 317, 319, 321, 323, 325, 327,	resume_last_time , 77, 96, 97, 99–102, 104, 106–
329, 331, 333, 335, 337, 339, 341, 343,	108, 110–113, 115, 116, 118–122, 124–
345, 348, 350, 353, 356, 358, 361, 362	127, 129–133, 135–138, 140–142, 144–
precond , 230, 231, 234, 371, 374, 378, 379	147, 149, 150, 152
precond0, 311	reuse_preconditioner_nb_it_max , 378, 379
precond1, 311	rho , 244, 245, 288–299
precond_diagonal , 231, 234	rho_constant_pour_debug , 285
precond_nul , 231, 234, 378	rho_t , 286
preconda, 311	rho_xyz , 286
preconditionnement_diag , 166	rotation , 288, 392, 393
pression, 293	rt , 252
pression_degeneree , 363	rtol , 371–374, 376, 378–380
pression_thermo , 298	sans_passer_par_le2d , 38
pression_xyz , 298	sans_solveur_masse , 218
pressure_order , 23	sauvegarde , 77, 96–99, 101, 102, 104, 105, 107–
pressure_reduction , 363	109, 111–114, 116–118, 120–123, 125–
<u>-</u>	
print_more_infos , 58	130, 132–134, 136–138, 140–143, 145–
probes , 78, 92	148, 150, 151
probes_file , 78, 92	sauvegarde_simple , 77, 96–98, 100–102, 104, 105,
probleme , 36–38, 262, 263, 269, 270	107–109, 111–114, 116, 117, 119–122, 124
produits, 228	130, 132–134, 136–138, 140–142, 144–
projection_initiale , 190, 195, 197, 199, 209, 210,	148, 150, 151
212	save_matrix , 230–234, 376, 378
projection_normale_bord , 39	save_matrix_mtx_format , 371–374, 376, 379, 380
pulsation_w , 192	save_matrix_petsc_format , 376, 379
q , 297	sc , 284
q_prim , 297	scturb, 302
QDM_Multiphase , 103, 105, 106	segment, 395
quiet , 206, 229–234, 371–374, 376, 379, 380	serial_statistics , 79, 93
rapport_residus , 41	serial_statistics_file , 79, 93
reactifs, 228	seuil, 54, 230–232, 234, 318, 320, 370–374, 376,
reactions, 227	379, 380
read_matrix, 378	seuil_convergence_implicite, 166, 364, 365, 367,
rectangle, 395	368, 370
reduce_ram , 376	seuil_convergence_solveur , 166, 364–370
regul , 390	seuil_diffusion_implicite, 166, 316, 319, 321, 323,
relative, 66	325, 327, 329, 331, 333, 335, 337, 339,
relax_jacobi , 54	341, 343, 345, 348, 350, 353, 355, 358,
relax_pression, 368, 370	360, 362
renommer_equation , 153, 167–189, 191, 196,	seuil_divU , 190, 195, 197, 199, 208, 210, 212
198, 200, 209, 211, 213	seuil_generation_solveur , 364–370
reorder , 57	seuil_statio , 316, 318, 321, 323, 325, 327, 329,
reorder_matrix , 378	331, 333, 335, 337, 339, 341, 343, 345,
reprise , 77, 96–98, 100–102, 104, 105, 107, 108,	
	347, 350, 352, 355, 358, 360, 362
110–114, 116, 118–122, 124–128, 130–	seuil_test_preliminaire_solveur , 364–370
134, 136–138, 140–142, 144–148, 150, 152	
192	seuil_verification_solveur , 364–370
reprise_correlation , 245, 246	sharing_algo , 24
residuals , 316, 318, 321, 323, 325, 327, 329, 331,	sigma_turbulent, 161
333, 335, 337, 339, 341, 343, 345, 347,	single_hdf , 25, 57
350, 353, 355, 358, 360, 362	single_precision, 23
resolution_explicite , 166	size_dom , 213

```
smooth_steps, 54
                                                  temps_relaxation_coefficient_pdf , 392
solide , 77, 96
                                                  test, 156
solv elem, 231
                                                  Text , 394
                                                  time, 254, 255, 259
solver_precision, 54
solveur, 69, 166, 347, 349, 352, 354, 357, 359,
                                                 time activate ptot, 298
                                                  tinf, 244, 245
         364-370
solveur0, 230
                                                  tinit, 316, 318, 320, 322, 324, 326, 328, 330, 332,
solveur1, 230
                                                           334, 336, 338, 340, 342, 344, 347, 349,
solveur bar, 190, 195, 197, 199, 209, 210, 212
                                                           352, 355, 357, 360, 361
solveur grossier, 54
                                                  tmax, 316, 318, 320, 322, 324, 326, 328, 330, 332,
solveur pression, 174, 190, 195, 197, 199, 208,
                                                           334, 336, 338, 340, 342, 344, 347, 349,
         210, 212
                                                           352, 355, 357, 360, 362
source, 216-223, 225-227
                                                  toutes_les_options, 56
source reference, 216–223, 225–227
                                                  traitement axi, 24
sources , 152, 167–190, 196, 198, 199, 209, 211,
                                                 traitement coins, 56
         212, 216–223, 225–227
                                                  traitement_gradients, 56
sources_reference , 216-223, 225-227
                                                  traitement_particulier , 190, 195, 197, 199, 208,
sous_zone , 36, 78, 92, 262, 263, 269, 270, 387,
                                                           210, 212
         388
                                                  traitement_pth , 293, 298
sous zones, 308
                                                  traitement_rho_gravite, 293
species_number , 285
                                                  tranches, 308
spectre 1D, 194
                                                  transpose rotation, 392, 393
spectre_3D , 194
                                                  triangle, 37
splitting, 51
                                                  trois tetra, 38
standard, 162
                                                  tsup, 244, 245
statistics . 79, 92
                                                  tube . 396
statistics file, 79, 93
                                                  turbulence paroi, 200, 201, 203, 204, 206, 207,
suffix for reset, 79, 93
                                                           299, 301, 302
surface, 246, 390
                                                  tuyauz, 205
surface_tension, 214, 215
                                                  type, 222, 310
surfacic_flux , 52
                                                  u_etoile, 385
surfacique, 310
                                                  ubar_umprim_cible, 394
                                                  ucent, 261
sutherland , 293, 298
symx , 47
                                                  uniform_domain_size_i , 253
symy , 47
                                                  uniform_domain_size_j , 253
symz , 47
                                                  uniform_domain_size_k , 253
t0,384
                                                  union , 396
t deb , 218–220, 223
                                                  unite, 223, 227
t fin , 218–220, 223
                                                  use existing domain , 254, 255, 258
t_min , 286
                                                  use_grad_pression_eos, 298
T ref, 215, 295, 296
                                                  use hydrostatic pressure, 298
t_ref , 214, 215
                                                  use_links, 23
T sat, 215
                                                  use osqp, 24
table temps, 254
                                                  use overlapdec, 254
table temps lue, 254
                                                  use_total_pressure, 298
Taux_dissipation_turbulent , 103, 105, 107
                                                  use_weights, 306
tcpumax, 316, 318, 320, 322, 324, 326, 328, 330,
                                                 user_field, 299
         332, 334, 336, 338, 340, 342, 344, 347,
                                                 val_Ec , 194
         349, 352, 355, 357, 360, 362
                                                  variable_imposee_data, 392
tdivu , 156
                                                  variable_imposee_fonction, 392
temperature, 282, 283
                                                  vdf_mesh, 24
temperature_order, 23
                                                  velocity_order, 23
                                                  velocity_profil, 277
temperature_paroi, 235
temps debut prise en compte drho dt , 293
                                                  verif boussinesq, 384
```

verif_dparoi , 205	Calcul, 28
verification_derivee , 288	Calculer_moments, 28
via_extraire_surface, 37	Canal, 192
vingt_tetra , 38	Canal_perio, 384
vitesse, 288, 383	Centre, 158
vitesse_imposee_data , 392	Centre4, 158
vitesse_imposee_fonction, 392	Centre_de_gravite, 28
volume, 245	Centre_old, 157
volumes_etendus , 156	Ch_front_input, 269
volumes_non_etendus , 156	Ch_front_input_uniforme, 269
volumique, 310	Champ_base, 253
without_dec , 24	Champ_composite, 256
writing_processes , 25	Champ_don_base, 256
xinf, 246	Champ_don_lu, 257
xsup , 246	Champ_fonc_fonction, 257
xtanh , 47	Champ_fonc_fonction_txyz, 257
xtanh_dilatation, 47	Champ_fonc_fonction_txyz_morceaux, 258
xtanh_taille_premiere_maille , 47	Champ_fonc_interp, 253
yaml_fname , 95	Champ_fonc_med, 258
ytanh , 47	Champ_fonc_med_table_temps, 254
ytani, 47 ytanh_dilatation, 47	Champ_fonc_med_tabule, 254
ytani_unatation , 47 ytanh_taille_premiere_maille , 47	<u>*</u>
· -	Champ_fonc_reprise, 259 Champ_fonc_t, 260
zmax , 43	1 — — ·
zmin , 43	Champ_fonc_tabule, 260
ztanh , 47	Champ_fonc_tabule_morceaux_interp, 256
ztanh_dilatation , 47	Champ_fonc_txyz, 265
ztanh_taille_premiere_maille , 48	Champ_fonc_xyz, 265
Acceleration, 383	Champ_front_base, 267
	Champ_front_bruite, 270
Ale, 153	Champ_front_calc, 270
Amg, 228	Champ_front_composite, 271
Amgx, 228	Champ_front_contact_vef, 271
Amont, 158	Champ_front_debit, 271
Amont_old, 155	Champ_front_debit_massique, 272
Analyse_angle, 26	Champ_front_debit_qc_vdf, 268
Associate, 27	Champ_front_debit_qc_vdf_fonc_t, 268
Axi, 27	Champ_front_fonc_pois_ipsn, 272
Piagetch 271	Champ_front_fonc_pois_tube, 272
Bicgstab, 371	Champ_front_fonc_t, 273
Bidim_axi, 27 Binaire, 94	Champ_front_fonc_txyz, 273
Binaire_gaz_parfait_qc, 282	Champ_front_fonc_xyz, 273
Binaire_gaz_parfait_wc, 282	Champ_front_fonction, 273
· ·	Champ_front_lu, 274
Block_jacobi_icc, 312	Champ_front_med, 270
Block_jacobi_ilu, 312	Champ_front_musig, 274
Boomeramg, 313	Champ_front_normal_vef, 274
Bord, 49	Champ_front_parametrique, 267
Bord_base, 48	Champ_front_pression_from_u, 274
Boundary_field_inward, 268	Champ_front_recyclage, 275
Boussinesq_concentration, 383	Champ_front_tabule, 276
Boussinesq_temperature, 384	Champ_front_tabule_lu, 276
Btd, 158	Champ_front_tangentiel_vef, 276
C 212	Champ_front_uniforme, 276
C-amg, 313	Champ_front_xyz_debit, 277

Champ_front_xyz_tabule, 267	Convection_diffusion_concentration, 178
Champ_generique_base, 216	Convection_diffusion_concentration_turbulent, 179
Champ_init_canal_sinal, 260	Convection_diffusion_espece_binaire_qc, 180
Champ_input_base, 261	Convection_diffusion_espece_binaire_turbulent_qc,
Champ_input_p0, 262	167
Champ_input_p0_composite, 262	Convection_diffusion_espece_binaire_wc, 181
Champ_musig, 263	Convection_diffusion_espece_multi_qc, 182
Champ_ostwald, 263	Convection_diffusion_espece_multi_turbulent_qc, 183
Champ_parametrique, 256	Convection_diffusion_espece_multi_wc, 182
Champ_post_de_champs_post, 216	Convection_diffusion_temperature, 184
Champ_post_extraction, 220	Convection_diffusion_temperature_ibm, 185
Champ_post_morceau_equation, 222	Convection_diffusion_temperature_ibm_turbulent, 186
Champ_post_operateur_base, 217	Convection_diffusion_temperature_turbulent, 187
Champ_post_operateur_divergence, 219	Coolprop_qc, 283
Champ_post_operateur_eqn, 217	Coolprop_wc, 283
Champ_post_operateur_gradient, 221	Coriolis, 385
Champ_post_reduction_0d, 224	Correction_antal, 381
Champ_post_refchamp, 225	Correction_tomiyama, 381
Champ_post_statistiques_base, 218	Correlation, 86, 88, 89, 218
Champ_post_tparoi_vef, 225	Corriger_frontiere_periodique, 29
Champ_post_transformation, 226	Create_domain_from_sub_domain, 20
Champ_som_lu_vdf, 263	Create_domain_from_sub_domain, 20
Champ_som_lu_vef, 264	Darcy, 385
Champ_tabule_lu, 264	Debog, 29
Champ_tabule_morceaux, 255	Decoupebord_pour_rayonnement, 30
Champ_tabule_temps, 264	Decouper_bord_coincident, 31
Champ_uniforme_morceaux, 265	Dg, 250
Champ_uniforme_morceaux_tabule_temps, 265	Di_12, 155
	Diag, 313
Champ_front_fonc_txyz, 17	Diffusion_deriv, 159
Chimie, 227	Dilate, 31
Chaladar 220, 274	Dimension, 31
Cholesky, 229, 374	Dirac, 386
Cholesky_mumps_blr, 376	Dirichlet, 237
Cholesky_out_of_core, 371	Disable_tu, 32
Cholesky_pastix, 372	Discretisation_base, 250
Cholesky_superlu, 372	Discretiser_domaine, 32
Cholesky_umfpack, 373	Discretize, 32
Circle, 84	,
Circle_3, 84	Dispersion_bulles, 382 Distance_paroi, 32
Class_generic, 228	Domain, 50
Cli, 376	Domaine, 252
Cli_quiet, 377	
Condinits, 164	Domaine_base, 213
Condlim_base, 235	Domaine_ijk, 213
Condlims, 164	Domaineaxi1d, 252
Conduction, 152	Dp, 381
Conduction_ibm, 166	Dp_impose, 381
Connexion_approchee, 302	Dp_regul, 382
Connexion_exacte, 303	Dt_calc, 229
Constituant, 288	Dt_fixe, 229
Convection_deriv, 153	Dt_min, 229
Convection_diffusion_chaleur_qc, 175	Dt_start, 230
Convection_diffusion_chaleur_turbulent_qc, 177	Dt_post, 86, 89
Convection_diffusion_chaleur_wc, 176	

Ec, 193	Frontiere_ouverte_alpha_impose, 238
Ecart_type, 88, 220	Frontiere_ouverte_concentration_imposee, 238
Ecart_type, 86, 89	Frontiere_ouverte_enthalpie_imposee, 241
Echange_couplage_thermique, 235	Frontiere_ouverte_fraction_massique_imposee, 239
Echelle_temporelle_turbulente, 168	Frontiere_ouverte_gradient_pression_impose, 239
Ecrire, 76	Frontiere_ouverte_gradient_pression_impose_vefprep1b,
Ecrire_champ_med, 33	239
Ecrire_fichier_bin, 76	Frontiere_ouverte_gradient_pression_libre_vef, 239
Ecrire_fichier_formatte, 33	Frontiere_ouverte_gradient_pression_libre_vefprep1b,
Ecriturelecturespecial, 34	240
Ef, 154, 250	Frontiere_ouverte_pression_imposee, 240
Ef_axi, 250	Frontiere_ouverte_pression_imposee_orlansky, 240
Ef_stab, 156	Frontiere_ouverte_pression_moyenne_imposee, 240
Eisentat, 312	Frontiere_ouverte_rho_u_impose, 241
End, 41	Frontiere_ouverte_vitesse_imposee, 241
Energie_cinetique_turbulente, 171	Frontiere_ouverte_vitesse_imposee_sortie, 241
Energie_cinetique_turbulente_wit, 172	Frottement_interfacial, 386
Energie_multiphase, 169	
Energie_multiphase_h, 170	Gaz_parfait_qc, 285
Enthalpie_imposee_paroi, 249	Gaz_parfait_wc, 285
Entree_temperature_imposee_h, 238	Gcp, 233, 378
Eos_qc, 281	Gcp_ns, 230
Eos_wc, 281	Gen, 231
Epsilon, 50	Generic, 155
Eqn_base, 188	Gmres, 231, 379
Execute_parallel, 34	
Export, 35	Ibicgstab, 373
Extract_2d_from_3d, 35	Ibm_aucune, 278
	Ibm_element_fluide, 278
Extract_2daxi_from_3d, 35	Ibm_gradient_moyen, 279
Extraire_domaine, 36 Extraire_plan, 36	Ibm_hybride, 279
_	Ibm_power_law_tbl, 280
Extraire_surface, 37	Ice, 363
Extrudebord, 38	Ijk, 250
Extrudeparoi, 38	Ijk_grid_geometry, 252
Extruder, 39	Ilu, 310
Extruder_en20, 39	Implicite, 364
Extruder_en3, 40	Imprimer_flux, 42
Fichier_decoupage, 305	Imprimer_flux_sum, 42
Fichier_med, 305	Init_par_partie, 266
Fluide_base, 289	Integrer_champ_med, 43
	Interface_base, 213
Fluide_dilatable_base, 290 Fluide_incompressible, 290	Interface_sigma_constant, 214
Fluide_ostwald, 291	Interfacial_area, 160
	Internes, 49
Fluide_quasi_compressible, 292	Interpolation, 221, 303
Fluide_reel_base, 294	Interpolation_ibm_base, 277
Fluide_sodium_gaz, 294	Interpolation_ibm_power_law_tbl_u_star, 277
Fluide_sodium_liquide, 295	Interprete, 19
Fluide_stiffened_gas, 296	Interprete_geometrique_base, 43
Fluide_weakly_compressible, 297	merprete_geometrique_base, 43
Flux_interfacial, 386	Jacobi, 313
Forchheimer, 386	545001, 510
Formatte, 94	Kquick, 157
Frontiere_ouverte, 238	1 /

L_melange, 160	Muscl_new, 157
Lata_2_med, 44	Muscl_old, 153
Lata_2_other, 45	
Lata_to_cgns, 43	Navier_stokes_ibm, 196
Leap_frog, 324	Navier_stokes_ibm_turbulent, 198
Link_cgns_files, 21	Navier_stokes_qc, 189
Lire_ideas, 45	Navier_stokes_standard, 208
Lire_tgrid, 62	Navier_stokes_turbulent, 209
List_bloc_mailler, 46	Navier_stokes_turbulent_qc, 211
List_bord, 48	Navier_stokes_wc, 194
List_nom, 68	Negligeable, 158, 163, 397
List_nom_virgule, 216	Negligeable_scalaire, 397
List_post, 93	Nettoiepasnoeuds, 55
Liste_post_ok, 91	Neumann, 242
Liste_post_ok, 91 Listobj, 399	Neumann_homogene, 236
· ·	Neumann_paroi, 236
Listobj_impl, 398	Neumann_paroi_adiabatique, 237
Lml_2_lata, 45	Nom, 304
Logarithmique, 304	Null, 207, 300, 314
Loi_etat_base, 281	Numero_elem_sur_maitre, 83
Loi_etat_gaz_parfait_base, 283	Numero_elem_sur_matue, 65
Loi_etat_gaz_reel_base, 284	Objet_lecture, 399
Loi_etat_tppi_base, 284	Op_conv_ef_stab_polymac_face, 21
Loi_fermeture_base, 287	Op_conv_ef_stab_polymac_p0_face, 22
Loi_fermeture_test, 287	Op_conv_ef_stab_polymac_p0p1nc_elem, 22
Loi_horaire, 287	Op_conv_ef_stab_polymac_p0p1nc_face, 22
Longitudinale, 389	
Longueur_melange, 204	Optimal, 232
Lu, 313, 379	Option, 163
	Option_cgns, 22
Mailler, 45	Option_dg, 23
Mailler_base, 46	Option_ijk, 23
Maillerparallel, 50	Option_interpolation, 24
Masse_multiphase, 172	Option_polymac, 24
Merge_med, 21	Option_vdf, 55
Metis, 306	Orientefacesbord, 56
Milieu_base, 288	Orienter_simplexes, 63
Milieu_composite, 398	
Milieu_musig, 398	P1b, 163
Mkdir, 52	P1ncp1b, 163
Mod_turb_hyd_rans, 206	Parallel_io_parameters, 24
Mod_turb_hyd_ss_maille, 201	Parametre_diffusion_implicite, 166
Modele_turbulence_hyd_deriv, 200	Parametre_equation_base, 165
Modele_turbulence_scal_base, 299	Parametre_implicite, 165
Modif_bord_to_raccord, 52	Paroi, 237
Modifydomaineaxi1d, 52	Paroi_adiabatique, 242
Mor_eqn, 152	Paroi_contact, 242
Moyenne, 86, 88–90, 223	Paroi_contact_fictif, 243
Moyenne_imposee_deriv, 302	Paroi_decalee_robin, 243
Moyenne_volumique, 52	Paroi_defilante, 244
	Paroi_echange_contact_correlation_vdf, 244
Multi_gaz_parfait_qc, 284	Paroi_echange_contact_correlation_vef, 245
Multiplafiles 21	Paroi_echange_contact_vdf, 246
Multiplefiles, 21	Paroi_echange_externe_impose, 246
Muscl, 157	Paroi_echange_externe_impose_h, 246
Muscl3, 154	1 a. 5 5. mail 5 _ 5. mail 5 _ 111 p 5 5 _ 11, 2 70

```
Paroi_echange_externe_radiatif, 237
                                                   Pb_thermohydraulique_ibm, 144
Paroi_echange_global_impose, 247
                                                   Pb_thermohydraulique_ibm_turbulent, 110
Paroi echange interne global impose, 235
                                                   Pb thermohydraulique list concentration, 111
Paroi_echange_interne_global_parfait, 236
                                                   Pb_thermohydraulique_list_concentration_turbulent,
Paroi echange interne impose, 236
Paroi_echange_interne_parfait, 236
                                                   Pb_thermohydraulique_qc, 132
Paroi fixe, 247
                                                   Pb thermohydraulique scalaires passifs, 145
Paroi fixe iso genepi2 sans contribution aux vitess  thermohydraulique turbulent, 146
         sommets, 247
                                                   Pb thermohydraulique turbulent qc, 147
                                                   Pb thermohydraulique turbulent scalaires passifs, 149
Paroi flux impose, 247
                                                   Pb thermohydraulique wc, 133
Paroi knudsen non negligeable, 248
Paroi temperature imposee, 248
                                                   Pbc med, 150
Partition, 56, 307
                                                   Pdi, 95
Partition multi, 58
                                                   Pdi expert, 95
Partitionneur deriv, 305
                                                   Periodique, 248
Pave, 46
                                                   Perte_charge_anisotrope, 387
Pb_avec_liste_conc, 115
                                                   Perte_charge_circulaire, 387
Pb_avec_passif, 117
                                                   Perte_charge_directionnelle, 388
Pb_base, 113
                                                   Perte_charge_isotrope, 388
Pb conduction, 76
                                                   Perte charge reguliere, 388
Pb conduction ibm, 95
                                                   Perte_charge_singuliere, 390
Pb gen base, 76
                                                   Petsc, 233
Pb hem, 106
                                                   Petsc_gpu, 233
Pb hydraulique, 118
                                                   Pilote icoco, 58
Pb hydraulique cloned concentration, 96
                                                   Pilut, 314
Pb hydraulique cloned concentration turbulent, 97 Pipecg, 374
Pb hydraulique concentration, 119
                                                   Piso, 365
Pb hydraulique concentration scalaires passifs, 120 Plan, 83
Pb hydraulique concentration turbulent, 121
                                                   Point, 81
Pb_hydraulique_concentration_turbulent_scalaires_paRsifnts, 80
         122
                                                   Polyedriser, 58
Pb_hydraulique_ibm, 124
                                                   Polymac, 250
                                                   Polymac_p0, 251
Pb_hydraulique_ibm_turbulent, 99
Pb_hydraulique_list_concentration, 100
                                                   Polymac_p0p1nc, 251
Pb_hydraulique_list_concentration_turbulent, 101
                                                   Porosites, 309
Pb_hydraulique_melange_binaire_qc, 125
                                                   Portance_interfaciale, 382
Pb hydraulique melange binaire turbulent qc, 127
                                                   Position like, 83
Pb hydraulique melange binaire wc, 126
                                                   Post processing, 91
Pb hydraulique turbulent, 129
                                                   Post processings, 90
Pb_multiphase, 102
                                                   Postraitement base, 91
Pb multiphase h, 104
                                                   Postraiter domaine, 59
Pb_thermohydraulique, 131
                                                   Pp, 185
Pb thermohydraulique cloned concentration, 107
                                                   Prandtl, 161, 300
Pb thermohydraulique cloned concentration turbulei Ptrecision geom, 59
                                                   Precond base, 310
Pb_thermohydraulique_concentration, 135
                                                   Preconditionneur_petsc_deriv, 312
Pb_thermohydraulique_concentration_scalaires_passif@recondsolv, 310
         136
                                                   Predefini, 223
Pb thermohydraulique concentration turbulent, 137 Pression, 86, 89, 90
Pb_thermohydraulique_concentration_turbulent_scalaftesblem_read_generic, 151
                                                   Probleme_couple, 115
         _passifs, 138
Pb_thermohydraulique_especes_qc, 140
                                                   Profil, 304
Pb_thermohydraulique_especes_turbulent_qc, 142
                                                   Profils_thermo, 191
Pb thermohydraulique especes wc, 141
                                                   Puissance thermique, 390
```

Qdm_multiphase, 173	Scheme_euler_implicit, 356
Quick, 157	Schmidt, 301
	Segment, 81
Raccord, 48	Segmentfacesx, 82
Radioactive_decay, 390	Segmentfacesy, 82
Radius, 82	Segmentfacesz, 82
Raffiner_anisotrope, 60	Segmentpoints, 81
Raffiner_isotrope, 60	Sets, 366
Raffiner_isotrope_parallele, 25	Sgdh, 161
Read, 61	Simple, 367
Read_file, 62	Simpler, 368
Read_file_binary, 62	Single_hdf, 94
Read_med, 25	Smago, 161
Read_unsupported_ascii_file_from_icem, 63	Solide, 298
Redresser_hexaedres_vdf, 63	Solve, 67
Refine_mesh, 63	Solveur_implicite_base, 363
Regroupebord, 63	Solveur_lineaire_std, 369
Remove_elem, 64	Solveur_petsc_deriv, 370
Remove_invalid_internal_boundaries, 65	Solveur_sys_base, 234
Reordonner, 65	Solveur_u_p, 369
Reorienter_tetraedres, 65	Sonde_base, 80
Reorienter_triangles, 65	Sortie_libre_temperature_imposee_h, 249
Rhot_gaz_parfait_qc, 286	Source_base, 380
Rhot_gaz_reel_qc, 286	
Rocalution, 233	Source_constituent, 391
Rotation, 66	Source_dep_inco_bases, 383
Runge_kutta_ordre_2, 326	Source_generique, 391
Runge_kutta_ordre_2_classique, 327	Source_pdf, 391
Runge_kutta_ordre_3, 329	Source_pdf_base, 392
<u> </u>	Source_qdm, 393
Runge_kutta_ordre_3_classique, 331	Source_qdm_lambdaup, 393
Runge_kutta_ordre_4_classique, 335	Source_th_tdivu, 394
Runge_kutta_ordre_4_classique_3_8, 337	Sources, 165
Runge_kutta_ordre_4_d3p, 333	Sous_dom, 307
Runge_kutta_rationnel_ordre_2, 339	Sous_maille_smago, 202
Sa-amg, 314	Sous_maille_wale, 203
Saturation_base, 214	Sous_zone, 395
	Sous_zones, 307
Saturation_constant, 214	Spai, 314
Saturation_sodium, 215	Spec_pdcr_base, 389
Scalaire_impose_paroi, 249	Ssor, 311, 314
Scatter, 66	Ssor_bloc, 311
Scattermed, 67	Stab, 161
Sch_cn_ex_iteratif, 317	Standard, 162
Sch_cn_iteratif, 319	Stat_per_proc_perf_log, 67
Schema_adams_bashforth_order_2, 342	Stat_post_deriv, 87
Schema_adams_bashforth_order_3, 343	Statistiques, 86, 89, 90
Schema_adams_moulton_order_2, 345	Statistiques_en_serie, 89, 90
Schema_adams_moulton_order_3, 348	Supg, 159
Schema_backward_differentiation_order_2, 351	Supprime_bord, 67
Schema_backward_differentiation_order_3, 353	Symetrie, 249
Schema_implicite_base, 358	System, 68
Schema_predictor_corrector, 361	·
Schema_temps_base, 315	T_deb, 87
Scheme_euler_explicit, 322	T_fin, 87

```
Taux_dissipation_turbulent, 174
Tayl_green, 266
Temperature, 192
Terme_puissance_thermique_echange_impose, 394
Test_solveur, 68
Test_sse_kernels, 26
Testeur, 69
Testeur_medcoupling, 69
Tetraedriser, 69
Tetraedriser_homogene, 70
Tetraedriser_homogene_compact, 70
Tetraedriser_homogene_fin, 71
Tetraedriser_par_prisme, 72
Thi, 193
Traitement_particulier_base, 191
Tranche, 308
Transformer, 72
Transversale, 389
Travail_pression, 394
Trianguler, 73
Trianguler_fin, 73
Trianguler_h, 74
Turbulence_paroi_base, 397
Turbulence_paroi_scalaire_base, 397
Turbulente, 159
type, 86, 89
Type_diffusion_turbulente_multiphase_deriv, 160
Type_perte_charge_deriv, 381
Uniform_field, 266
Union, 308
Valeur_totale_sur_volume, 266
Vdf, 251
Vect nom, 75
Vef, 251
Verifier_qualite_raffinements, 74
Verifier_simplexes, 75
Verifiercoin, 75
Vitesse_derive_base, 394
Vitesse_relative_base, 395
Volume, 83
Wale, 160
Write_med, 20
Xyz, 94
xyz, 17
```