

EchoPoint Component Library
Developer Guide
Version 0.4

[Rakesh Vidyadharan](#)

June 30, 2008

Contents

1	Introduction	3
1.1	Maintaining Component List	3
1.2	Package and Namespace	3
1.3	Java Version	3
1.4	Source Code Repository	4
1.4.1	Checking Out and Building Library	4
1.4.2	Gaining Access to Repository	4
1.5	Licence	4
2	Project Directories	5
2.1	Client Side Sources	5
2.1.1	Client Side Library	6
2.1.2	Client Test Application	6
2.1.2.1	index.html	7
2.1.2.2	ComponentList.js	8
2.1.2.3	XxxTest.js	8
2.2	Server Side Sources	8
2.2.1	Server Side Components	8
2.2.2	Server Side Sync Peers	9
2.2.2.1	Resource Location	9
2.2.2.2	Bootstrapping Environment	9
2.2.2.2.1	CommonResources	9
2.2.2.2.2	CommonService	10
2.2.3	Server Side Test Application	10

2.2.3.1 [ComponentList](#) 10

2.2.3.2 [XxxTest](#) 10

List of Tables

1 [Project directories](#) 5

2 [JavaScript Sources](#) 6

3 [JavaScript Namespaces](#) 6

4 [Test Application Directory Structure](#) 7

5 [Resource Files](#) 9

1 Introduction

This document serves as a guide for the developers working on re-implementing EchoPointNG for Echo3. The guide covers source code organisation, unit testing guidelines etc.

The primary focus of the re-implementation effort is to make available the most popular components from [EchoPointNG](#). Some components from [EchoPointNG](#) are made obsolete by complimentary components in the [Echo3 Extras](#) library. The team will try to avoid duplicating components, unless the features provided by [EchoPointNG](#) were far in excess of those made available by [Echo3 Extras](#). In the event a decision is made to implement a component that already exists in [Echo3 Extras](#), it will be treated as a lower priority. The list of components that are planned to be re-implemented are presented in [\[1\]](#).

Javadoc API Specifications (see [\[2\]](#)) for the component library will be updated and maintained periodically. Javadocs will be generated with linked source code, enabling users to view the implementation files without needing to check out the source code.

1.1 Maintaining Component List

Developers who contribute to the re-implementation effort must update the component list (see [\[1\]](#)) as appropriate. Filling in the implementor name against the component will assist with bug-fixing efforts as well. This is also the best means of taking responsibility of a component to avoid duplication of effort by other developers involved in the effort. Hence updating this list and committing to the repository at frequent intervals is the best way to ensure that no duplication of effort occurs.

1.2 Package and Namespace

In keeping with NextApp using `echo` instead of `echo3` for all packages and namespaces we shall be using `echopoint` as the package/namespace for the library. Accordingly the server side component interfaces are under the `echopoint` package, while the client side components are under the `echopoint` namespace.

1.3 Java Version

At present all the server side sources require Java 5 as the minimum JDK version. This may be changed in future to support Java 1.4 if so required.

1.4 Source Code Repository

The source code for the project is maintained in the subversion server maintained by NextApp. The location of the repository is:

<https://svn.nextapp.com/svn/epng3>

Note that the working copy of the code is available under the **trunk** area. An older attempt to port **EchoPointNG** by just changing package names is available under the **branches/obsolete** directory.

1.4.1 Checking Out and Building Library

The following steps illustrate the process of checking out and building the library.

```
svn co https://svn.nextapp.com/svn/epng3/trunk echopoint
cd echopoint
cp ant.properties.sample ant.properties
vi ant.properties # Edit as necessary to suit environment
ant
```

1.4.2 Gaining Access to Repository

Anyone may check out the source code repository and use the library. Developers who wish to contribute to the project may request write access to the repository by contacting **rakesh** through the Echo Developer Forum.

1.5 Licence

EchoPoint will be distributed under the Mozilla Public Licence (see [3]). The **LICENCE.txt** file under the **trunk** directory in **subversion** (see section 1.4) may be used to copy the licence clauses to each source file in the project.

2 Project Directories

The project contents are organised under the following primary directories:

src - The root directory under which the source code for the library are stored. Note that both client and server side sources are stored under this root.

lib - All third party libraries used to implement and test the library are stored under this directory.

docs - All documentation pertaining to the project are stored under this directory. Note that Javadoc API specifications are generated under a sub-directory of this directory by the build script.

Note that the project directory structure tries to remain similar to the structure followed by the [Echo3](#) and [Echo3 Extras](#) projects. Table 1 shows the key directories and their purpose.

Table 1: Project directories

Directory	Purpose
src/client	The root directory under which client side implementation of the library exists.
src/client/js	The root directory under which the client-side components and their rendering peers are stored.
src/client/test	The root directory under which the test client application is stored.
src/server-java	The root directory under which the server side implementation of the library exists.
src/server-java/app	The root directory under which the sources for the components exist.
src/server-java/webcontainer	The root directory under which the sources for the component sync peers exist.
src/server-java/test	The root directory under which the sources for the server side test web application exist.

2.1 Client Side Sources

All client side sources are stored under the **client** sub-directory. This directory is further split into directories for the library implementation sources and the client test application.

2.1.1 Client Side Library

The component definition and sync peer sources are stored under the `js` sub-directory. Table 2 shows the primary source files available in this directory. Note that the naming convention follows the same convention as followed by [Echo3](#) and [Echo3 Extras](#).

Table 2: JavaScript Sources

File	Purpose
<code>Echopoint.js</code>	The primary source file that bootstraps the client environment. See table 3 for a description of the primary namespaces maintained by the library. See section 2.2.2.2 for a description of how the client-side environment is bootstrapped by the server.
<code>Application.<Component>.js</code>	The source file that defines the client-side interface of the component. Note that inheritance hierarchies may be stored in a single file to reduce client-server interaction.
<code>Sync.<Component>.js</code>	The client-side sync peer for the component.

Table 3: JavaScript Namespaces

Namespace	Purpose
<code>echopoint</code>	The primary namespace for the library. Similar to the server-side library, all components are made available under this root namespace. Add any global routines, objects that may be shared among components to the primary <code>Echopoint.js</code> file.
<code>echopoint.constants</code>	A namespace used to define constants used by the client-side library. In particular constants are defined to hold the component names, since the same name needs to be used in both the component (<code>Application.xxx.js</code>) and sync peer (<code>Sync.xxx.js</code>) files.

2.1.2 Client Test Application

A test application (similar to the server-side test application¹) is used test the client-side library. All the primary classes for the test application are maintained under the `echopoint.test` namespace. A unit test framework like Selenium may be used to create a test suite around the test application. The test application may be accessed at [4].

The test application sources are stored under the `app` sub-directory. Sections 2.1.2.x describe the source files that need to be edited and created to add tests to the application. Table 4 shows the directory structure for the test application.

¹See section 2.2.3 for details.

Note: The contents of the [JavaScript](#) files noted in the succeeding sections may be combined within a single file. They are maintained in separate files to keep the application code structurally similar to the server-side test application (see section [2.2.3](#)).

Table 4: Test Application Directory Structure

Directory	Purpose
app	The root directory under which the sources for the test application are stored.
lib	The root directory under which external libraries required for the application are stored.
lib/corejs	The root directory under which the Echo3 Core client-side library files are stored.
lib/echo	The root directory under which the Echo3 App client-side library files are stored.
lib/extras	The root directory under which the Echo3 Extras client-side library files are stored.

2.1.2.1 index.html

The [XHTML 1.0](#) page that is used to load the client-side test application and all the requisite libraries. This file is maintained under the root **test** directory. Update **head** section with the new [JavaScript](#) files that were added. Note that the client-side test application can be tested directly by loading the index page off the filesystem without needing to be deployed to a web/application server.

Notes

1. The client-side library is accessed using relative file references. This may be changed at a later date to copy the library files to a sub-directory to allow loose coupling with the rest of the library.
2. A utility class may be developed that will automatically scan the **app** directory update the index file to avoid having to manually maintain this file.
3. The YUI compressor may be used to reduce load time of the test application. The **clienttest** ant task can be used to generate the **war** file that contains a compressed deployable version of the client-side test application. Note that the files added to **index.html** should also be added under the **filelist** elements in **build.xml** for a proper test package to be generated.

2.1.2.2 ComponentList.js

The class names of the components to be tested are maintained by the `COMPONENTS` array. Add the class name of the client-side component that is being tested to the array.

2.1.2.3 XxxTest.js

A test class with name `<Component>Test` needs to be added under the `echopoint.test` namespace in the `app` directory. These test classes will take the container component that they will populate as a constructor parameter. If possible user interaction may be enabled to perform manual testing of the components. See the existing test files for samples on usage and set up.

Notes

1. No real styling is done in the test application. The style class as used in the Echo demo application has been copied over, but is not being used properly. Eventually the test application must use proper styles to make the application look presentable.
2. Selenium (or similar) web application testing framework may be used to create a interface unit test suite around the test application.

2.2 Server Side Sources

Sources for the server side components and sync peers are available under the `server-java` sub-directory. Staying similar to the [Echo3](#) source tree, the component sources are stored under the `app` directory, while the sync peer sources are stored under the `webcontainer` directory. The unit test application for the server side code is stored under the `test` directory.

2.2.1 Server Side Components

All the components made available by the library are stored under the `echopoint` package under the `app` directory. Sub-packages may be created as necessary to hide implementation details of the components.

2.2.2 Server Side Sync Peers

All the sync peers for the components made available by the library are stored under the **echopoint** package under the **webcontainer** directory. Sub-packages may be created as necessary to hide implementation details of the components. Note that the library distribution file includes both the components and sync peers in one package unlike the **Echo3** distribution that separates them into two separate distribution files.

2.2.2.1 Resource Location

Resource files² are stored under the **resources** root directory of the distribution library file. Table 5 shows the standard directory structure for referencing resources files from sync peer code.

Table 5: Resource Files

File	Purpose
resource	The root directory under which all resource files are stored. Note that we do not use the package of the class file as a base directory of the resources. There is no difference between the two approaches, this just makes the files easier to find.
resource/js	The root directory under which all JavaScript implementation files (client side component and sync peers) are stored.
resource/image	The root directory under which image resources for the various components are stored.

2.2.2.2 Bootstrapping Environment

The client environment for the library is bootstrapped through the following classes. Each server-side sync peer must invoke the bootstrapping code as appropriate. See existing code samples for examples on how to invoke the bootstrapping code.

2.2.2.2.1 CommonResources

A static class used to bootstrap the **echopoint** namespace. Invoke **CommonResources.install** within a **static** block of code in each sync peer.³

```
static
{
    CommonResources.install();
    WebContainerServlet.getServiceRegistry().add( COMPONENT_SERVICE );
}
```

²JavaScript libraries, images etc.

³This is not necessary if a super class performs this bootstrapping.

2.2.2.2.2 CommonService

A static class used to load the code in the **echopoint** core client library. This class must be used in the [init](#)⁴ method of the sync peer.

```
public void init( final Context context, final Component component )
{
    super.init( context, component );
    ServerMessage serverMessage =
        (ServerMessage) context.get( ServerMessage.class );
    serverMessage.addLibrary( CommonService.ECHOPOINT.SERVICE.getId() );
    serverMessage.addLibrary( COMPONENTNAME );
}
```

2.2.3 Server Side Test Application

A web application has been developed to unit test the server side implementation. Sections 2.2.3.x describe the source files that need to be edited and created to add tests to the application.

2.2.3.1 ComponentList

The class names of the components to be tested are maintained by the **COMPONENTS** array. Add the class name of the component for which a test is being added to the array.

2.2.3.2 XxxTest

A test case class with name **<Component>Test** needs to be added that runs the various unit tests necessary. In addition these tests updates the display area (right side) of the test application window with the component being tested. If possible some user interaction may be enabled to perform manual testing of the components.

Notes

1. All tests are written using JUnit 4 style and not 3.x style. See existing test case sources for samples.
2. No styling is done in the test application at present. This must eventually be modified to make the test application look presentable. Ideally this can be accomplished by creating default styles for the various components used by the application.⁵
3. Selenium (or similar) web application testing framework may be used to create a interface unit test suite around the test application.

⁴This is not necessary if a super-class performs this loading.

⁵At the time of writing default styles are not supported by [Echo3](#).

References

- [1] [EchoPoint Component List](#)
- [2] [Javadoc API Specifications](#)
- [3] [Mozilla Public Licence](#) Version 1.1
- [4] [EchoPoint Client-Side Test Application](#)