

# DOWNLOAD

RELEASE 5.10  
February, 2001

David L. Rotman  
Cedarville University  
PO Box 601  
Cedarville, OH 45314  
[rotmand@cedarville.edu](mailto:rotmand@cedarville.edu)

## Contents

Purpose .....	3
Simple Examples .....	4
Help-file Printout .....	8
Available File Formats .....	14
COMMA .....	14
DBF .....	14
DIF .....	15
FIXED .....	15
HTML .....	16
QUOTE .....	16
WP50 .....	17
WP51 .....	17
Defining Output Data .....	18
Overview .....	18
Using Data Fields and Virtual Fields .....	18
Using Literal Values .....	18
Using VOC Items .....	19
Using an Alternate Dictionary .....	19
Using an Additional Data File .....	19
Using Subroutines .....	19
Using "@" Variables .....	20
Syntax Guide .....	22
Version History .....	52

## Purpose

DOWNLOAD is a utility program which produces output files in ASCII, WordPerfect, HTML, dBASE, or DIF formats. Output files can be used by service bureaus and government agencies or used directly by standard software packages. DOWNLOAD is easy to use, because it uses syntax like the LIST statement. The examples in the next chapter illustrate the ease with which the program can be used.

This software was written at Cedarville University by Doug Sjoquist and modified by Dave Rotman. You may freely distribute this software, but this software is not to be sold by itself nor as part of any other software package. A current version of the software may be obtained via anonymous ftp from:

`ftp.cedarville.edu`

This software is made available on an "as-is" basis, with no warranty of any kind.

Currently, the software is being maintained by Dave Rotman. Suggestions for new features or bug fixes should be sent to `rotmand@cedarville.edu`. Since Dave cannot devote a lot of time to support, you can often get usage questions answered more quickly by posting an item to e-mail list serves which focus on Unidata software and Datatel products.

## Cedarville University

Cedarville University was chartered by the State of Ohio in 1887. Throughout its history, the University has existed "to provide an education consistent with Biblical truth". Academic programs are offered in over 100 areas. The largest majors are engineering, nursing, business, and education. For more information, visit <http://www.cedarville.edu>.

## Simple Examples

1. Create a file of customer names and addresses so that the file can be loaded into a spreadsheet or database program.

```
GET.LIST MY.LIST
DOWNLOAD CUSTOMERS NAME STREET CITY STATE ZIP \
FILE _HOLD_ CUSTOMER.DAT
```

Sample output for two customer records:

```
"Harold Johnson","341 S. Main St.,""Buffalo","NY","12533"
"Elsie Gordon","P.O. Box 18","West Plains","OH","45509"
```

2. Use the same customer database, but this time produce a Web page (HTML file):

```
SELECT CUSTOMERS SAMPLE 3
DOWNLOAD CUSTOMERS NAME STREET CITY STATE ZIP \
FILE _HOLD_ CUSTOMER.HTM FORMAT HTML
```

Note that an HTML file can also be read by many spreadsheet and word-processing programs. This method might actually give better results than reading the comma-separated-values text file.

3. Use the same customer database, but this time produce a fixed-length file for use by an external service bureau.

```
SELECT CUSTOMERS SAMPLE 3
DOWNLOAD CUSTOMERS NAME STREET CITY STATE ZIP \
FILE _HOLD_ CUSTOMER.DAT FORMAT FIXED
```

Sample output for three customer records:

Harold Johnson	341 S. Main St.	Buffalo	NY12533
Elsie Gordon	P.O. Box 18	West Plains	OH45509
Linda Falling	3428 Smith St.	Rockford	MA03291

4. Use the same customer database, but this time produce a "mail merge" file for use by Corel WordPerfect or Microsoft Word.

```
GET.LIST MY.LIST
DOWNLOAD CUSTOMERS NAME STREET CITY STATE ZIP \
FILE _HOLD_ CUSTOMER.DAT FORMAT WP51
```

5. Use the same customer database, but this time produce a "dbf" file for use as a dBASE or Paradox database.

```
GET.LIST MY.LIST
DOWNLOAD CUSTOMERS NAME STREET CITY STATE ZIP \
FILE _HOLD_ CUSTOMER.DAT FORMAT DBF
```

6. Produce a file showing customer id numbers, names, and date of first order.

```
GET.LIST MY.LIST
DOWNLOAD CUSTOMERS ID.NO NAME \
ORDER.DATES \
FILE _HOLD_ CUSTOMER.DAT
```

Sample output for two customer records:

```
"10485","Harold Johnson","05/18/93"
"30216","Elsie Gordon","12/11/96"
```

(By default, only the first value of a multi-valued field is included. This default can be overridden with the NUM.VALUES phrase as shown in the next example.)

7. Revise the previous example to show all order dates, not just the first one.

```
GET.LIST MY.LIST
DOWNLOAD CUSTOMERS ID.NO NAME \
ORDER.DATES NUM.VALUES ALL\
FILE _HOLD_ CUSTOMER.DAT
```

Sample output for two customer records:

```
"10485","Harold Johnson","05/18/93","09/12/94","12/18/95"
"30216","Elsie Gordon","12/11/96","03/12/97"
```

(Harold Johnson has placed a total of three orders and Elsie Gordon has placed a total of two orders.)

8. Produce a file containing customer name, city, and zip code. The first record in

the output file should identify the field names.

```
GET.LIST MY.LIST
DOWNLOAD CUSTOMERS NAME CITY ZIP \
HEADING FIELD.NAMES
FILE _HOLD_ CUSTOMER.DAT
```

Sample output for two customer records:

```
"NAME","CITY","ZIP"
"Harold Johnson","New York","12533"
"Elsie Gordon","West Plains","45509"
```

9. Repeat the previous example, but produce the output as a Web page.

```
GET.LIST MY.LIST
DOWNLOAD CUSTOMERS NAME CITY ZIP \
HEADING FIELD.NAMES \
FILE _HOLD_ CUSTOMER.HTM \
FORMAT HTML
```

Sample output for two customer records:

NAME	CITY	ZIP
Harold Johnson	New York	12533
Elsie Gordon	West Plains	45509

10. Produce a file of invoices showing invoice number, customer name, gross amount, and net amount.

```
GET.LIST INVOICE.LIST
DOWNLOAD INVOICES INV.NO INV.NAME INV.GROSS INV.NET \
FILE _HOLD_ INVOICE.DAT
```

Sample output for two invoice records:

```
"I10345","Harold Johnson",543.28,495.87
"I20956","Elsie Gordon",125.04,125.04
```

11. Produce a file of invoices showing invoice number, customer name, item number, and item amount for all item numbers beginning with the letter Q.

```
GET.LIST INVOICE.LIST
SELECT INVOICES BY @ID BY.EXP ITEM.NUMBER \
      WHEN ITEM.NUMBER LIKE 'Q...'
DOWNLOAD INVOICES INV.NO INV.NAME \
      BY.EXP ITEM.NUMBER ITEM.NUMBER ITEM.AMT \
      FILE _HOLD_ INVOICE.DAT
```

Sample output for two invoice records:

```
"I10345","Harold Johnson","Q104",56.75
"I10345","Harold Johnson","Q131",18.56
"I20956","Elsie Gordon","Q117",41.00
```

(Invoice I10345 contained two items beginning with the letter Q and invoice I20956 contained only one item beginning with the letter Q.)

12. Produce a file showing each term that a student attended our institution. Each term should be on a line by itself. The student's name should appear on each line.

```
SELECT STUDENTS BY NAME BY.EXP REG.TERMS
DOWNLOAD STUDENTS NAME BY.EXP REG.TERMS REG.TERMS \
      FORMAT FIXED
```

Output would look like this:

Anthony, Susan	95/FA
Anthony, Susan	97/WI
Lincoln, Abraham	96/FA
Washington, George	97/FA
Washington, George	98/WI

# Help-file Printout

DOWNLOAD 5.10

February 2001

This is a brief introduction, intended to help you get started with DOWNLOAD. For more extensive help, consult the documentation file DOWNLOAD.DOC which came with the DOWNLOAD software.

## Basic command line syntax

```
DOWNLOAD FileName field.names
```

## More complete syntax

```
DOWNLOAD [BEGIN] [DICT] FileName
  [[field.prefix] field.names [field.qualifiers]]
  [SUBR('sname'[,arg1,etc]) [field.qualifiers]]
  [LITERAL 'value' [field.qualifiers]]
  [@variables]
  [Record.IDs]
  [Phrase from Dict]
  [Phrase from VOC]
  [Options]
```

## Specifying data to include on the output

- Reference a data field or I-descriptor described in the current dictionary.
- Reference a data field or I-descriptor described in the VOC file.
- Use the SECONDARY.FILE option to relate another file to this one. This is like doing a TRANS (translate) to another file, but without creating an i-descriptor.
- Use a literal value specified with the "LITERAL 'value'" clause.
- Return a value from a subroutine specified with the "SUBR('sname')" clause.
- Use an "at" variable to return a system-defined value.

All of these items may also include qualifiers or prefixes which further define how the value is to be downloaded. There are also command options that may be used to change the default behavior of DOWNLOAD.

## Valid Field Clauses

```
DataFieldName [Field Qualifier(s)]
```

You may use any data field from the data file(s) specified on your command line.

```
I-descriptorName [Field Qualifier(s)]
```



The dictionary item for a data field or an I-descriptor can come from either the current dictionary (which can be changed with the USING DICT option,) or the VOC file.

LITERAL 'constant value' [Field Qualifier(s)]

The default format and length for this type of value is the actual length of the data, left-justified.

SUBR('subroutine.name' [, argument2]) [Field Qualifier(s)]

This clause can have from 1 to 10 arguments and functions similar to the SUBR usage in I-descriptors. The subroutine should return the value to be downloaded in the first argument. If the value being returned is multi-valued, then the field qualifier MULTI.VALUE should be added since the default is single-value. The default format and length for this type of value is "30L".

@variable [Field Qualifier(s)]

You may select from any of the following variables:

@ACCOUNT	host operating system path
@DATE	system date (internal format) that DOWNLOAD began running
@DAY	day of the month that DOWNLOAD began running
@LOGNAME	user's login name
@MONTH	month of the year (numeric) that DOWNLOAD began running
@SYSTEM.RETURN.CODE	system return code at the start of execution (usually, the number of records in the active select list)
@TIME	system time (internal format) that DOWNLOAD began running
@YEAR	year (four digit) that DOWNLOAD began running

#### Record Layout Command Options and Default Values

***** Option *****	***** Default Value *****
BY.EXP MVField1	none
COMMA.CHAR comma.char	,
DEFAULT field.qualifier new.default.value	none
DETAIL ...detail layout options....	default is DETAIL
EOR.CHAR end.of.record.char	(null)
FIELD.GAP #blanksbetweencolumns	none (only valid with FIXED)
FOOTING ...record layout options...	no report footing record
FORMAT	
COMMA DBF DIF FIXED HTML QUOTE WP50 WP51	COMMA
HEADING ...record layout options...	no report heading record
NO.LINEFEED	Off (LF between records)
RECORD.LENGTH fixed.size	none (only valid with FIXED)
RECORD.ORIENTATION HORIZONTAL   VERTICAL	HORIZONTAL
REMOVE.PUNCTUATION	Off (leave punctuation)
QUOTE.CHAR quote.char	"
UPCASE	Off (do not change case)
WHEN MVField2 oper Field   Value(s)	none

#### Execution Environment Command Options and Default Values

***** Option *****	***** Default Value *****
--------------------	---------------------------

[NO.]DISPLAY.COUNT	DISPLAY.COUNT
[NO.]PRINT.ERRORS	PRINT.ERRORS
LPTR	Off (errors/layout on screen)
NO.PAGE	Off (pause at end of screen)
PRINT.LAYOUT	Off (do not print layout)
PROGRESS.INTERVAL	10
WRITE.INTERVAL	10 0 (sleep 0 seconds)

#### Records and Files to Process Command Options and Default Values

***** Option *****	***** Default Value *****
APPEND	Off (do not append)
FILE Type1File RecordName	Off (display on screen)
FROM SelectList#	0 (default select list)
OVERWRITING	Off (do not overwrite)
SAMPLE [SampleSize]	Entire list or file
USING [DICT] AlternateInfoFile	DICT InfoFileName

#### HTML Command Options and Default Values

***** Option *****	***** Default Value *****
HTML.TITLE HTMLTitleToUse	none
HTML.BODY HTMLBodyToUse	none
HTML.TOP HTMLTopToUse	none
HTML.TABLE HTMLTableToUse	BORDER="1" (small visible)
HTML.BOTTOM BottomHTMLTextToUse	none

#### Valid operators for WHEN option:

EQ, NE, GE, GT, LE, LT, LIKE, UNLIKE

#### Valid Field Prefixes:

BREAK.ON field.name  
TOTAL field.name  
AVERAGE field.name  
MIN field.name  
MAX field.name

#### ValidField Qualifiers:

	---- Valid for these formats ----						Default Value
	FIXED	COMMA QUOTE	HTML	WP50 WP51	DIF	DBF	
LINE LogicalLine#	Yes	Yes					1
[LENGTH] MaximumLength	Yes	Yes		Yes	Yes	Yes	none
BEG.COL BegColumn#	Yes						1
END.COL EndColumn#	Yes						n/a
COLUMNS BegColumn# EndColumn#	Yes						n/a
FMT FmtCode	Yes	Yes	Yes	Yes	Yes	Yes	dict
CONV ConvCode	Yes	Yes	Yes	Yes	Yes	Yes	dict
HTML.CELL			Yes				none
HTML.START			Yes				none
HTML.END			Yes				none
HTML.ROW			Yes				none

SINGLE.VALUE   MULTI.VALUE	Yes	Yes	Yes	Yes	Yes	Yes	single
NUM.VALUES #Values	Yes	Yes	Yes	Yes	Yes	Yes	1
NUM.VALUES ALL	Y/N	Yes	Yes	Yes			
(valid with FORMAT FIXED & vertical orientation) (default = ALL for FORMAT WP50 or WP51)							
MV.ORIENTATION VERTICAL   HORIZONTAL							
	Yes	Yes	Yes				horizontal
DEFAULT.VALUE value	Yes	Yes	Yes	Yes	Yes	Yes	null
NO.NULLS	Yes	Yes	Yes	Yes	Yes	Yes	false

Valid control heading and footing record layouts:

```

HEADING.ON break.field [...record layout...]
HEADING.ON break.field NONE
FOOTING.ON FINAL [...record layout...]
FOOTING.ON FINAL NONE
FOOTING.ON break.field [...record layout...]
FOOTING.ON break.field NONE
DET.SUP      (show only heading/footing lines)

```

For each break field (each use of BREAK.ON), a default footing record with the same layout as the detail record will be setup, as well as a final control footing record (different from the report footing record). This default may be disabled with the optional keyword NONE following the FOOTING.ON phrase.

SECONDARY.FILE option

```

***** Option ***** Default Value *****
SECONDARY.FILE filename
  [KEY primaryFileFieldName]      @ID
  [ALIAS text]                     filename

```

## Examples

1. To create a "comma-quote" file of id numbers and names, try statements like the following:

```

GET.LIST MAJOR.DONORS
DOWNLOAD PEOPLE ID.NO NAME FILE _HOLD_ DONOR.DAT

```

Sample output for a single record from above statement:  
 "1031567","Carnegie, Andrew"

2. To change the above to a WordPerfect merge file:

```

GET.LIST MAJOR.DONORS
DOWNLOAD PEOPLE ID.NO NAME FILE _HOLD_ DONOR.DAT FORMAT WP51

```

3. To change the above to a Web page (HTML):

```
GET.LIST MAJOR.DONORS
DOWNLOAD PEOPLE ID.NO NAME FILE _HOLD_ DONOR.HTM FORMAT HTML
```

4. The following example creates a data file named GRAD1998.DAT in the directory named &HOLD&. The file is in comma format with the student's name, 2 lines (always) of address, city, state, zip, first and second major, and all terms that have been transcribed or registered.

```
GET.LIST GRADS
DOWNLOAD STUDENTS \
  NAME ADDRESS NUM.VALUES 2 CITY ST ZIP \
  MAJOR NUM.VALUES 2 \
  REG.TERMS WHEN REG.STATUS = 'T''''R' NUM.VALUES ALL \
  FORMAT COMMA FILE &HOLD& GRAD1998.DAT
```

Sample output for a single record from above statement:

```
"Smith, John Q","250 North Main","", "Columbus", "OH", "44444", "ENG",
"BUS", "96/FA", "97/WI", "97/SP", "97/FA", "98/WI", "98/SP"
```

5. The following example uses a subroutine to call a local subroutine with the default key of "AR" to determine the mailing name & address. The rest of the example is the same as above.

```
GET.LIST GRADS.1998
DOWNLOAD STUDENTS \
  SUBR('S.GET.ADDRESS','AR',5) MULTI.VALUE NUM.VALUES 5 \
  MAJOR NUM.VALUES 2 \
  REG.TERMS WHEN REG.STATUS = 'T''''R' NUM.VALUES ALL \
  FORMAT COMMA FILE &HOLD& GRADUATES.1998.DATA
```

Sample output for a single record from above statement:

```
"Mr. John Smith", "250 North Main", "Columbus, OH 44444", "", "", "ENG",
"BUS", "96/FA", "97/WI", "97/SP", "97/FA", "98/WI", "98/SP"
```

6. Examples using the SECONDARY.FILE option

The SECONDARY.FILE option lets you reference fields from other files without creating a lot of i-descriptors.

```
DOWNLOAD PEOPLE SECONDARY.FILE STUDENTS KEY @ID
  LAST FIRST STUDENTS->CLASS
references fields LAST and FIRST from the PEOPLE file and the field
CLASS from the students file (the same record key is used for both
files).
```

```
DOWNLOAD STUDENTS SECONDARY.FILE STUD.SCHS KEY LAST.SS.KEY \
  NAME STUD.SCHS->COURSE NUM.VALUES ALL
references field NAME from the STUDENTS file and field COURSE
from the STUD.SCHS file. The record key for STUD.SCHS is
computed in field LAST.SS.KEY of the STUDENTS file.
```

```
DOWNLOAD STUDENTS \
SECONDARY.FILE PEOPLE KEY PARENT.ID ALIAS PGS \
SECONDARY.FILE PEOPLE KEY SPOUSE ALIAS SP \
NAME PARENT.ID PGS->NAME SPOUSE SP->NAME \
FORMAT FIXED FIELD.GAP 2
retrieves data from the PEOPLE file:
NAME is the person's name
PARENT.ID is the id number of the person's parent
PGS->NAME is the name of the parent (accessed via PARENT.ID)
SPOUSE is the id number of the person's spouse
SP->NAME is the name of the spouse (accessed via SPOUSE)
```

```
* This software was written at Cedarville University by Doug Sjoquist
* and modified by Dave Rotman. You may freely distribute this
* software, but this software is not to be sold by itself nor as
* part of any other software package. A current version of the
* software may be obtained via anonymous ftp from:
* ftp.cedarville.edu
* This software is made available on an "as-is" basis, with no
* warranty of any kind.
```

## Available File Formats

DOWNLOAD can produce output in a variety of formats as described below. Which format you use will likely be dictated by the application that will be reading your output file (spreadsheet, database, word processor, external service bureau, etc.). Here are the available formats:

### **COMMA**

This is the default output format for DOWNLOAD files. Non-numeric fields are surrounded by quotation marks on the output. All fields are separated by commas. This file format can be used by many programs, including word processors and spreadsheets. (See also QUOTE format.)

This is the basic approach:

```
DOWNLOAD PEOPLE NAME CITY MY.INDEX NICKNAME FILE.NO \
  FORMAT COMMA FILE DOCS PEOPLE.DAT
"George Washington","Mt. Vernon",38.56,"Geo",49
"Abraham Lincoln","Gettysburg",123.12,"Abe",56
"William Clinton","Little Rock",108.00,"Bill",17
```

If you want the field names to appear in your output file, try this:

```
DOWNLOAD PEOPLE NAME CITY MY.INDEX NICKNAME FILE.NO \
  FORMAT COMMA FILE DOCS PEOPLE.DAT HEADING FIELD.NAMES
"NAME","CITY","MY.INDEX","NICKNAME","FILE.NO"
"George Washington","Mt. Vernon",38.56,"Geo",49
"Abraham Lincoln","Gettysburg",123.12,"Abe",56
"William Clinton","Little Rock",108.00,"Bill",17
```

If you want a character like a TAB instead of a comma to separate the fields, use the COMMA.CHAR option (see the Syntax Guide chapter of this documentation for examples). You may also change the quotation character via the QUOTE.CHAR option.

### **DBF**

The DBF layout creates a file in native format for the database program dBASE. This layout can also be read by most other database packages (Paradox, FoxPro, etc.) and spreadsheet programs. You should use ".DBF" as part of your file name so that the database program can access the file.

```
DOWNLOAD CUSTOMERS NAME ZIP \
```

## FORMAT DBF FILE DOCS CUST.DBF

The field names from the Unidata file will become the database field names for the dBASE file. Note that dBASE field names are limited to 10 characters. Longer names will be truncated by DOWNLOAD. If the truncation results in a duplicate field name, DOWNLOAD will adjust field names until each one is unique.

Supported dBASE field types include character, numeric, and date. Fields which are not dates and not numeric will be stored as character fields.

dBASE files are limited to about 65,000 records per file.

### ***DIF***

DIF is an acronym for "data interchange format". This format was developed many years ago to facilitate exchange of data between different software packages. It is considered a "native" format for Excel and QuattroPro, so output files in DIF format can be read directly as spreadsheet files (no importing is necessary).

This is an example of creating a DIF file:

```
DOWNLOAD PEOPLE NAME CITY MY.INDEX NICKNAME FILE.NO \
FORMAT DIF FILE DOCS PEOPLE.DIF
```

If you want the field names to be the first row in the spreadsheet, use this variation (with the HEADING option):

```
DOWNLOAD PEOPLE NAME CITY MY.INDEX NICKNAME FILE.NO \
FORMAT DIF FILE DOCS PEOPLE.DIF HEADING FIELD.NAMES
```

### ***FIXED***

This layout forces the value of every field to be formatted to the same length. The actual length of each field is controlled by the dictionary FMT option, or you can override the FMT when you run DOWNLOAD. The FIXED layout is often used by service bureaus. This layout is also useful if the data will be read by languages like COBOL and FORTRAN. Some people like to use this layout for spreadsheet importing, though doing so requires a "parse" statement in the spreadsheet. (The COMMA or DIF formats are much easier to use with spreadsheets.)

```
DOWNLOAD PEOPLE NAME CITY MY.INDEX NICKNAME FILE.NO \
FORMAT COMMA FILE DOCS PEOPLE.DAT
```

George Washington	Mt. Vernon	38.56Geo	49
Abraham Lincoln	Gettysburg	123.12Abe	56

```
William Clinton      Little Rock  108.00Bill      17
```

```
DOWNLOAD PEOPLE NAME CITY MY.INDEX NICKNAME FILE.NO \
FORMAT COMMA FILE DOCS PEOPLE.DAT HEADING FIELD.NAMES
```

```
NAME              CITY              MY.INDEX NICKNAMFILE.
George Washington  Mt. Vernon      38.56Geo      49
Abraham Lincoln   Gettysburg      123.12Abe     56
William Clinton   Little Rock     108.00Bill    17
```

## **HTML**

This layout produces an HTML text file used by browsers such as Netscape and Internet Explorer. The output file would typically be copied to a Web server (or written directly there, if the user has a VOC pointer to an appropriate Web-server directory). Here is an example of generating an HTML file (note that many Web sites require that all file names use lowercase characters):

```
DOWNLOAD PEOPLE NAME CITY MY.INDEX NICKNAME FILE.NO \
FORMAT HTML FILE DOCS people.htm
```

Related keywords include HTML.TITLE, HTML.BODY, HTML.TOP, , HTML.TABLE, and HTML.BOTTOM. Field qualifiers that can be used include HTML.CELL, HTML.START, HTML.END, and HTML.ROW.

The HTML format can also be an efficient mechanism for transferring data to a spreadsheet. In Excel, for example, you can directly read an HTML file containing a table and the cell values will be placed appropriately in the spreadsheet.

## **QUOTE**

This is similar to the COMMA format, except that all fields are surrounded by quotation marks on the output (as opposed to just the non-numeric fields). All fields are separated by commas. This file format can be used by many programs, including word processors and spreadsheets. (See also COMMA format.)

This is the basic approach:

```
DOWNLOAD PEOPLE NAME CITY MY.INDEX NICKNAME FILE.NO \
FORMAT QUOTE FILE DOCS PEOPLE.DAT
"George Washington","Mt. Vernon","38.56","Geo","49"
"Abraham Lincoln","Gettysburg","123.12","Abe","56"
"William Clinton","Little Rock","108.00","Bill","17"
```

If you want the field names to appear in your output file, try this:



DOWNLOAD PEOPLE NAME CITY MY.INDEX NICKNAME FILE.NO \  
FORMAT COMMA FILE DOCS PEOPLE.DAT HEADING FIELD.NAMES

"NAME", "CITY", "MY.INDEX", "NICKNAME", "FILE.NO"  
"George Washington", "Mt. Vernon", "38.56", "Geo", "49"  
"Abraham Lincoln", "Gettysburg", "123.12", "Abe", "56"  
"William Clinton", "Little Rock", "108.00", "Bill", "17"

### **WP50**

This layout produces a "merge" file used by WordPerfect version 5.0. The output file can be used to generate letters, envelopes, etc. using the WordPerfect 5.0 merge operations.

Here is an example of generating a WP50 merge file:

DOWNLOAD PEOPLE NAME CITY MY.INDEX NICKNAME FILE.NO \  
FORMAT WP50 FILE DOCS PEOPLE.DIF

### **WP51**

This layout produces a "merge" file used by WordPerfect version 5.1 and later versions (including Windows versions). The output file can be used to generate letters, envelopes, etc. using the WordPerfect merge operations. This format is also suitable for use by Microsoft Word.

DOWNLOAD PEOPLE NAME CITY MY.INDEX NICKNAME FILE.NO \  
FORMAT WP51 FILE DOCS PEOPLE.DIF

## Defining Output Data

### **Overview**

Output data for DOWNLOAD can be obtained by:

- Using a data field or I-descriptor (virtual field) described in the dictionary of the file being processed
- Using dictionary entries in the VOC file or in some other data file
- Using an additional data file which has a logical relationship to the file being processed (without having to create TRANS virtual fields)
- Using a literal value
- Calling a subroutine
- Using a pre-defined "@" variable

All of these items may also include qualifiers or prefixes which further define how the value is to be downloaded. There are also command options that may be used to change the default behavior of DOWNLOAD. This chapter illustrates field definition. The next chapter explains each of the available qualifiers, modifiers, and command options.

### **Using Data Fields and Virtual Fields**

You may use any data field from the data file(s) specified on your command line. In the example below, "NAME" and "HOME.PHONE" are fields in file CUSTOMERS.

```
SELECT CUSTOMERS SAMPLE  
DOWNLOAD CUSTOMERS NAME HOME.PHONE
```

### **Using Literal Values**

Literal values can be used wherever a regular data field would be expected. The default format and length for this type of value is the actual length of the data, left-justified. (The formatting can be overridden; see "CONV" and "FMT" options in the next chapter.)

These commands would produce a file to be used in generating labels or letters to parents of students:

```
SELECT STUDENTS SAMPLE 3  
DOWNLOAD STUDENTS LITERAL "To the parents of:" \  
NAME STREET CITY ZIP \  
FILE _HOLD_ STU.DAT
```

Output records would look like this:

```
"To the parents of:","Adam Warren","58 Scott St","Aurora","IN","46509"  
"To the parents of:","Susan Van Til","P.O. Box 17","Silas","MN","50187"  
"To the parents of:","Mary Smith","4238 Main","Boktaw","WY","80261"
```

### ***Using VOC Items***

DOWNLOAD can retrieve data based on dictionary entries which have been placed in the VOC. To use this feature, create the item in DICT VOC, compile it, and then copy it to the VOC file. For example, suppose that you want to be able to include the length of the first data field in each output record. Create the DICT entry shown below and then follow the commands illustrated:

```

DICT VOC LEN.FIELD1
001: I
002: LEN(FIELD(@RECORD,@FM,1,1))
003:
004: LEN.FIELD1
005: 4R
006: S

CD VOC LEN.FIELD1
COPY FROM DICT VOC TO VOC 'LEN.FIELD1'
GET.LIST MYLIST
DOWNLOAD CUSTOMERS NAME LEN.FIELD1
```

In this example, NAME is a field on the CUSTOMERS file and LEN.FIELD1 is an I-descriptor defined in the VOC file. Because LEN.FIELD1 is defined in the VOC, it can be used when DOWNLOADing **any** file.

### ***Using an Alternate Dictionary***

You can DOWNLOAD using data from one file and control the DOWNLOAD using a dictionary of another file. See USING in the chapter "Syntax Guide" for more information.

### ***Using an Additional Data File***

DOWNLOAD has the capability of obtaining data from more than one file during processing. This is especially useful when a field in the first file is actually the key to a second file. See SECONDARY.FILE in the chapter "Syntax Guide" for more information.

### ***Using Subroutines***

Subroutines are invoked in a fashion similar to use of SUBR in I-descriptors. The subroutine should return the value to be downloaded in the first argument. If the value

being returned is multi-valued, then the field qualifier MULTI.VALUE should be added since the default is single-value. The default format and length for this type of value is "30L".

Suppose that letters are to be generated to customers, indicating the balance due, the due date, and the rate of interest. The rate of interest depends on the customer rating and the size of the balance due. A subroutine named "GET.RATE" has been written to determine the interest rate. "GET.RATE" has the following definition:

```
SUBROUTINE GET.RATE(OUT.INT.RATE,IN.CUST.RATING,IN.BAL.DUE)
```

This subroutine can be called directly by DOWNLOAD without having to create a virtual field:

```
SELECT CUSTOMERS WITH BAL.DUE GT 0.00
DOWNLOAD CUSTOMERS \
  BAL.DUE DUE.DATE \
  SUBR('GET.RATE',CUSTOMER.RATING,BAL.DUE) CONV "MD2" FMT
  "6R" \
  NAME STREET CITY STATE ZIP \
  FILE DOCS CUSTOMER.DAT
```

Subroutines used by DOWNLOAD can have up to ten arguments.

### **Using "@" Variables**

"@" variables (pronounced "at variables") give you access to predefined system values as shown below. These variables can be used anywhere a regular dictionary item can be used. Here is a typical example using the "@DATE" variable:

```
SELECT CUSTOMERS SAMPLE 2
DOWNLOAD CUSTOMERS \
  NAME BUS.PHONE @DATE CONV "D4/" \
  FILE DOCS CUSTOMER.DAT
```

Output would look like this:

```
"Richards Paint Shop","937-555-4040","03/15/1997"
"Abas Abacus Company","616-444-1212","03/15/1997"
```

The "@" variables can be used to generate a heading record required by some service bureaus. Suppose that the header must contain a record count and the date that the data file was created. The following commands could be used:

```
GET.LIST MY.LIST
DOWNLOAD CUSTOMERS \
  DETAIL NAME BUS.PHONE \
  HEADING @YEAR @MONTH @DAY \
    @SYSTEM.RETURN.CODE FMT "6'0'R" \
  FILE DOCS PHONE.DAT FORMAT FIXED
```

The first record in the output file would look like this (assuming that the DOWNLOAD occurred on 03/17/97 and the select list contained 156 records):

19970317000156

Detail records (after the heading record) would look like this:

Harrison, William E.	513-777-9812
Johnson, Wilma	937-444-1212
Kennedy, Marla Ima	800-412-9812

Each of the "@" variables is described in the table below.

At variables may also be used in output filenames. See the "File" section in the "Syntax Guide".

Description of "@" Variables		
Variable	Definition and typical usage	Sample output
@ACCOUNT	host operating system path where DOWNLOAD is being run DOWNLOAD MYFILE @ACCOUNT	/user3/livedir
@DATE	system date (internal format) that DOWNLOAD began running DOWNLOAD MYFILE @DATE DOWNLOAD MYFILE @DATE CONV "MD2/"	10669 03/17/97
@DAY	day of the month that DOWNLOAD began running DOWNLOAD MYFILE @DAY	17 (run on 03/17/97)
@LOGNAME	login name for person running DOWNLOAD DOWNLOAD MYFILE @LOGNAME	harryg
@MONTH	month of the year that DOWNLOAD began running DOWNLOAD MYFILE @MONTH	03 (run on 03/17/97)
@PATH	host operating system path where DOWNLOAD is being run DOWNLOAD MYFILE @PATH	/user3/livedir
@SYSTEM.RETURN.CODE	system return code at the start of DOWNLOAD execution (This is usually the number of records in active select list.) GET.LIST MY.LIST 48 records retrieved to list 0. DOWNLOAD MYFILE @SYSTEM.RETURN.CODE	48

@TIME	system time (internal format) that DOWNLOAD began running DOWNLOAD MYFILE @TIME DOWNLOAD MYFILE @TIME CONV "MTH"	37197 10:19AM
@YEAR	four-digit year that DOWNLOAD began running DOWNLOAD MYFILE @YEAR	1997 (ru

## Syntax Guide

### **@-VARIABLES**

"@" variables give you access to predefined system values such as the date and time. See the chapter "Defining Output Data" for details.

### **ALIAS**

Some commands which use a SECONDARY.FILE may become quite long and hard to read. The ALIAS option will let you shorten the command. The command:

```
DOWNLOAD STUDENTS CLASS MAJOR \
    SECONDARY FILE PEOPLE KEY @ID \
    PEOPLE->LASTNAME PEOPLE->FIRSTNAME \
    PEOPLE->PHONE
```

could be written as:

```
DOWNLOAD STUDENTS CLASS MAJOR \
    SECONDARY FILE PEOPLE KEY @ID ALIAS PEO \
    PEO->LASTNAME PEO->FIRSTNAME \
    PEO->PHONE
```

### **APPEND**

If the DOWNLOAD command specifies an output file which already exists, the default behavior is to terminate with an error message. If you want the output of the current session to be added to an existing file, use the APPEND option. The APPEND option is only appropriate for ASCII-style output (FIXED, COMMA, and QUOTE).

```
DOWNLOAD CUSTOMERS NAME ZIP \
    FILE DOCS CUSTOMER.DAT APPEND
```

See also OVERWRITING.

### **AVERAGE**

To include the average of a numeric field in a control-break line, use the AVERAGE modifier. (See also BREAK.ON and FOOTING.ON.)

```
SELECT CUSTOMERS BY STATE
DOWNLOAD CUSTOMERS BREAK.ON STATE \
```

## FOOTING.ON STATE STATE AVERAGE BAL.DUE

```
"FL",600.00
"FL",300.00
"FL",450.00          {this is the detail break line}
"OH",180.00
"OH",                {note the null value}
"OH",60.00
"OH",80.00          {this is the detail break line}
"TN",900.00
"TN",900.00          {this is the detail break line}
"TN",340.00          {this is the final break line}
```

Adding the NO.NULLS qualifier will exclude null values from calculation of the average.

## SELECT CUSTOMERS BY STATE DOWNLOAD CUSTOMERS BREAK.ON STATE \ FOOTING.ON STATE STATE AVERAGE BAL.DUE NO.NULLS

```
"FL",600.00
"FL",300.00
"FL",450.00          {this is the detail break line}
"OH",180.00
"OH",                {note the null value}
"OH",60.00
"OH",120.00          {this is the detail break line}
"TN",900.00
"TN",900.00          {this is the detail break line}
"TN",408.00          {this is the final break line}
```

### **BEGIN**

For readability, you may wish to modify how you store paragraphs which execute DOWNLOAD. DOWNLOAD command lines can be as long as your operating environment will allow. You can split the lines using the command-continuation character for your environment (typically, a backslash "\" or underscore "\_"), or you can use the BEGIN/END built into DOWNLOAD. The following three paragraphs are equivalent.

```
001: PA
002: GET.LIST <<I2,LIST TO GET>>
003: DOWNLOAD CUSTOMERS NAME CITY ZIP
```

```
001: PA
002: GET.LIST <<I2,LIST TO GET>>
003: DOWNLOAD CUSTOMERS \  

```



```
004: NAME \
005: CITY \
006: ZIP
```

```
001: PA
002: GET.LIST <<I2,LIST TO GET>>
003: DOWNLOAD CUSTOMERS BEGIN
004: DATA NAME
005: DATA CITY
006: DATA ZIP
007: DATA END
```

### **BEG.COL**

One method of setting up layouts for fixed-length records is to specify the beginning column for each field. The command:

```
DOWNLOAD CUSTOMERS NAME BEG.COL 1 \
      STATE BEG.COL 40 \
      ZIP BEG.COL 55 \
      FORMAT FIXED
```

would produce an output file where the NAME would be in positions 1-39, the STATE in positions 40-54, and the ZIP starting in position 55.

### **BREAK.ON**

The BREAK.ON clause works much like the BREAK.ON clause for the LIST statement. BREAK.ON allows you to generate a total line when the value of the specified field changes. By default, the break line contains the same fields as the detail lines. The layout of the total line can be changed by using the FOOTING.ON clause.

Example using the default break line:

```
SELECT CUSTOMERS BY STATE
DOWNLOAD CUSTOMERS BREAK.ON STATE BAL.DUE
```

```
"FL",552.87
"FL",300.00
"FL",300.00                                {this is the detail break line}
"OH",250.00
"OH",125.00
"OH",50.00
"OH",50.00                                {this is the detail break line}
"TN",985.12
"TN",985.12                                {this is the detail break line}
"TN",985.12                                {this is the final break line}
```

Example using explicit break line specifications:

```
SELECT CUSTOMERS BY STATE
DOWNLOAD CUSTOMERS BREAK.ON STATE BAL.DUE \
  FOOTING.ON STATE \
  LITERAL "SUBTOT" TOTAL BAL.DUE
  FOOTING.ON FINAL \
  LITERAL "GRANDTOT" TOTAL BAL.DUE
```

```
"FL",552.87
"FL",300.00
"SUBTOT",852.87           {this is the detail break line}
"OH",250.00
"OH",125.00
"OH",50.00
"SUBTOT",425.00          {this is the detail break line}
"TN",985.12
"SUBTOT",985.12          {this is the detail break line}
"GRANDTOT",2289.99       {this is the final break line}
```

### ***BREAK.SUP***

The BREAK.SUP option causes a control-break to occur without causing the field to appear on output lines. This option is best used when you are explicitly specifying a break line rather than accepting the default.

```
SELECT CUSTOMERS BY STATE
DOWNLOAD CUSTOMERS BREAK.SUP STATE \
  NAME BAL.DUE \
  FOOTING.ON STATE \
  STATE LITERAL "SUBTOT" TOTAL BAL.DUE
  FOOTING.ON FINAL \
  LITERAL "GRAND" LITERAL "TOT" TOTAL BAL.DUE
```

```
"Adams, William",552.87
"Cooker, Anne",300.00
"FL","SUBTOT",852.87       {this is the detail break line}
"Smith, Betty",250.00
"Billings, Thomas",125.00
"Cowder, Mary Ann",50.00
"OH","SUBTOT",425.00       {this is the detail break line}
"Belgia, Torin",985.12
"TN","SUBTOT",985.12       {this is the detail break line}
"GRAND","TOTAL",2289.99    {this is the final break line}
```

### ***BY.EXP***

The BY.EXP option tells DOWNLOAD to process the active select list as an

exploded list and to assume that the explosion was done on the field specified. Other fields which have the same association (field 7 of the dictionary) as the exploded field will be handled accordingly. The commands:

```
SELECT STUDENTS BY.EXP REG.TERMS \
      WHEN REG.TERMS LIKE '...FA...'
DOWNLOAD STUDENTS NAME BY.EXP REG.TERMS \
      REG.TERMS REG.STATUS
```

will generate a DOWNLOAD where the student name appears on each output record, the registration term will appear only if it contains the string "FA", and the registration status corresponding to the "FA" terms will appear.

If a STUDENTS record looks like this:

```
001: 96/FA}97/WI}97/SP}97/FA}98/WI {REG.TERMS}
002: F}P}P}W}F {REG.STATUS}
003: Washington {NAME}
```

the output would look like this:

```
"Washington", "96/FA", "F" {the first value}
"Washington", "97/FA", "W" {the fourth value}
```

## **COLUMNS**

You can specify the starting and ending columns for a field using the COLUMNS option. Note that this option is only appropriate for a FIXED format output.

```
DOWNLOAD CUSTOMERS NAME PHONE \
      COLUMNS 51 65 ZIP FORMAT FIXED
```

will place the PHONE number in columns 51 through 65 of the output. The ZIP code will start in column 66.

## **COMMA.CHAR**

When producing an output file in comma-quote format, data values are separated by a literal comma. If you wish to use a different separator, specify it using the COMMA.CHAR option.

Contrast:

```
DOWNLOAD CUSTOMERS NAME PHONE
"ABC Tooling", "937-555-1212"
"Middletown Catering", "800-555-9898"
```

with:

```
DOWNLOAD CUSTOMERS NAME PHONE \
      COMMA.CHAR "@"
"ABC Tooling"@ "937-555-1212"
"Middletown Catering"@ "800-555-9898"
```

A common use of the COMMA.CHAR option is to insert a tab between fields. This can be done as follows:

```
DOWNLOAD CUSTOMERS NAME PHONE \  
    COMMA.CHAR ^9
```

The carat ("^") tells DOWNLOAD that the "9" references ASCII character 9 (the tab character) rather than a literal "9".

## **CONV**

You can override the dictionary conversion (or specify a conversion for literals, subroutines, and "@" variables) using the CONV field qualifier.

```
DOWNLOAD STUDENTS NAME GPA CONV "MD34"
```

will produce the field GPA using three decimal positions (of the four that are stored on the file), rather than using whatever conversion was specified in the STUDENTS dictionary.

```
DOWNLOAD CUSTOMERS @DATE CONV "D4/"
```

will produce the system date in MM/DD/YYYY format, rather than the (default) internal format.

## **DEBUG.LEVEL**

This option is designed to be used by programmers who are tracing program features. The programmer can insert statements like the following into any of the DOWNLOAD subroutines:

```
IF DEBUG.LEVEL GT 3 THEN  
    CRT 'PROCESSING ITEM WITH VALUE ':SAMPLE.VALUE  
END
```

The DEBUG.LEVEL can then be set when DOWNLOAD is run, so that the programmer can control how many of the "CRT" statements actually execute:

```
DOWNLOAD CUSTOMERS NAME ZIP DEBUG.LEVEL 5
```

## **DEFAULT**

The DEFAULT option lets you change DOWNLOAD's defaults. For example, only the first value of a multi-value list appears unless a NUM.VALUES clause modifies the default behavior. If there are many multi-valued fields being used, you may want to set the default behavior to "NUM.VALUES ALL". The following two statements will produce identical results:

```
DOWNLOAD STUDENTS REG.TERMS NUM.VALUES ALL \  
    REG.STATUS NUM.VALUES ALL \  
    REG.ACTION NUM.VALUES ALL
```

DOWNLOAD STUDENTS REG.TERMS REG.STATUS REG.ACTION \  
DEFAULT NUM.VALUES ALL

### **DEFAULT.VALUE**

If a field being produced by DOWNLOAD is null, it can be replaced (on the output file) by a default value you specify. Contrast the two situations below:

DOWNLOAD CUSTOMERS NAME PHONE

"American Plastics", "937-555-1212"

"Billings Ink", ""

"Cameron Catering", "513-666-8888"

DOWNLOAD CUSTOMERS NAME \  
PHONE DEFAULT.VALUE "No Phone"

"American Plastics", "937-555-1212"

"Billings Ink", "No Phone"

"Cameron Catering", "513-666-8888"

### **DETAIL**

Unless otherwise specified, each field listed on the command line is assumed to be part of the "detail" output, as opposed to being part of a heading or footing line. In some complicated situations, you may want to explicitly define which fields belong to the detail line.

DOWNLOAD CUSTOMERS \  
HEADING @DATE CONV "D2/" @SYSTEM.RETURN.CODE \  
DETAIL NAME PHONE

will ensure that NAME and PHONE are part of the detail line, not the heading line. The heading line will contain the system date and system return code.

While not advisable, you may use the keyword DETAIL as many times as you wish. (Your logic will be clearer if you name all of the detail fields at one time.) Consider the clarity of the following statement, which is equivalent to the previous example:

DOWNLOAD CUSTOMERS HEADING @DATE CONV "D2/" \  
DETAIL NAME \  
HEADING @SYSTEM.RETURN.CODE \  
DETAIL PHONE

### **DET.SUP**

DET.SUP is used in conjunction with a BREAK.ON or BREAK.SUP phrase. Using DET.SP will cause DOWNLOAD to skip the production of the detail lines. Your output will only contain the heading and footing lines.

### **DICT**

The keyword DICT can be used to specify an alternate dictionary. For example, suppose you want to use data from file CUSTOMERS but you want to use the dictionary from the file CONTACTS. You could do this by creating a VOC entry which points to CUSTOMERS data and CONTACTS dictionary, or you could use the following command:

```
DOWNLOAD CUSTOMERS USING DICT CONTACTS \
      PERSON HOME.PHONE
```

Note that PERSON and HOME.PHONE are dictionary entries from CONTACTS. The data, however, will be obtained from the CUSTOMERS file.

### **DISPLAY.COUNT**

DISPLAY.COUNT causes the progress-meter asterisks to display on the screen as DOWNLOAD produces the output file. This is the default behavior. To turn off the display of the asterisks, use NO.DISPLAY.COUNT. To control how many asterisks are printed (i.e., how many records are processed before an asterisk is printed), use PROGRESS.INTERVAL.

### **END**

The keyword END is used to terminate a BEGIN/END block. See the keyword BEGIN for more information.

### **END.COL**

END.COL can be used to specify where data values will end when using FIXED format output. Consider:

```
DOWNLOAD CUSTOMERS NAME BAL.DUE END.COL 75 \
      FORMAT FIXED FILE DOCS CUSTOMER.DAT
```

The NAME field will begin in column 1. The BAL.DUE field will end in column 75 of the output. If the format for BAL.DUE is 10R, then BAL.DUE will start in column 66 (so that the ending column is 75).

### **EOR.CHAR**

When transferring data between operating systems, it is sometimes necessary to adjust the characters which appear between records of the output. For example, if you are creating a file on a Unix system and that file will be processed as

ASCII text on a personal computer, you may need to add a carriage return to the end of each line. This can be done as follows:

```
DOWNLOAD CUSTOMERS NAME PHONE \  
FILE DOCS CUSTOMER.DAT \  
EOR.CHAR ^13
```

The carat ("^") tells DOWNLOAD that the "13" references ASCII character 13 (the carriage-return character) rather than a literal "13".

### **FIELD.GAP**

If you wish to "spread out" data produced in a FIXED format, use the FIELD.GAP option. Contrast these two examples:

```
DOWNLOAD STUDENTS ID.NO CLASS GPA FORMAT FIXED  
8076513FR3.568  
9134892SO2.500  
2342382JR4.000  
2912833FR1.897
```

```
DOWNLOAD STUDENTS ID.NO CLASS GPA FORMAT FIXED \  
FIELD.GAP 3  
8076513    FR    3.568  
9134892    SO    2.500  
2342382    JR    4.000  
2912833    FR    1.897
```

### **FIELD.NAMES**

The FIELD.NAMES option provides an easy method for generating a heading when using COMMA, FIXED, or HTML formats. FIELD.NAMES tells DOWNLOAD to insert the name of each field on the HEADING line. (See also "Heading" for creating customized headings.)

Consider this example:

```
DOWNLOAD CUSTOMERS \  
DETAIL NAME PHONE ZIP \  
HEADING FIELD.NAMES
```

"NAME", "PHONE", "ZIP"	{heading}
"Harrison Electric", "616-444-9283", "49418"	{detail}
"General Toy Repair", "800-123-4400", "88012"	{detail}
"My Pet Store", "912-421-1234", "20001"	{detail}

### **FILE**

By default, DOWNLOAD sends all of its output to the screen. If you want to send your output to a file, use the FILE option. This is especially important if you are creating a WordPerfect or dBASE output file! Following the FILE keyword, you should specify the directory and file name (record name) for storing the output.

```
DOWNLOAD CUSTOMERS NAME PHONE \  
FILE MYDOCS CUSTOMER.DAT
```

will place the output file named CUSTOMER.DAT in directory MYDOCS.

If you are running DOWNLOAD repetitively, you may want to use the OVERWRITING option:

```
DOWNLOAD CUSTOMERS NAME PHONE \  
FILE MYDOCS CUSTOMER.DAT OVERWRITING
```

By default, DOWNLOAD will not create a new output file if a file of the same name already exists. You must use the OVERWRITING option if you want the new output file to replace the old one. The APPEND option will let you add records to an existing output file.

The FILE clause will also accept “@” variables. For example, suppose you wish to have the date and time of the program execution become part of the file name. The following example shows how this can be done:

```
SELECT CUSTOMERS WITH BALANCE GT 0  
DOWNLOAD CUSTOMERS NAME PHONE BALANCE \  
FILE MYDOCS OWE_@DATE_@TIME
```

The resulting file name will have this appearance:

```
OWE_11956_36040
```

The underscores are optional delimiters when using “@” variables, so you could use:

```
SELECT CUSTOMERS WITH BALANCE GT 0  
DOWNLOAD CUSTOMERS NAME PHONE BALANCE \  
FILE MYDOCS OWE@DATE@TIME
```

The resulting file name will have this appearance:

```
OWE1195636040
```

Be careful about introducing undesired characters such as asterisks (“\*”), greater-than signs (“>”), and slashes (“/”) when using “@” variable file names. In particular, you would ordinarily not want to use @ACCOUNT or @PATH in a variable file name.

There may be occasions when the system administrator wants to grant permission to create DOWNLOADED files in a certain directory or any of its subdirectories. This can be accomplished by creating a VOC entry only for the



main directory. For example, suppose that the following Unix directories exist:

```
/disk3/regdata
/disk3/regdata/FALL
/disk3/regdata/WINTER
/disk3/regdata/SPRING
```

DOWNLOAD can access all of these directories by creating a single VOC entry:

```
VOC REGDATA
001: DIR
002: /disk3/regdata
003: D_DIR
```

The following DOWNLOAD commands would write to the various directories:

```
DOWNLOAD STUDENTS NAME FILE REGDATA MYDAT
DOWNLOAD STUDENTS NAME FILE REGDATA/FALL MYDAT
DOWNLOAD STUDENTS NAME FILE REGDATA/WINTER MYDAT
DOWNLOAD STUDENTS NAME FILE REGDATA/SPRING MYDAT
```

The "/" character is the system delimiter for path names on Unix systems. If you are operating on a Prime system, you would use a greater-than sign ">".

## **FINAL**

The FINAL keyword is used to specify that the FOOTING being defined is the "grand total" line, the very last footing line to be produced.

```
SELECT CUSTOMERS BY STATE
DOWNLOAD CUSTOMERS BREAK.ON STATE BAL.DUE \
  FOOTING.ON STATE \
  LITERAL "SUBTOT" TOTAL BAL.DUE
  FOOTING.ON FINAL \
  LITERAL "GRANDTOT" TOTAL BAL.DUE
```

```
"FL",552.87
"FL",300.00
"SUBTOT",852.87           {this is the detail break line}
"OH",250.00
"OH",125.00
"OH",50.00
"SUBTOT",425.00           {this is the detail break line}
"TN",985.12
"SUBTOT",985.12           {this is the detail break line}
"GRANDTOT",2289.99        {this is the final break line}
```

## **FMT**

FMT can be used to override the existing dictionary format or the default format for literals, subroutines, and "@" variables. The syntax is identical to the FMT function within UniBASIC.

```

DOWNLOAD CUSTOMERS \
  NAME FMT "35L" \
  BAL.DUE FMT "12R" \
  NUMBER.OF.ORDERS FMT "8'0'R"

```

In this example, the NAME will be produced using 35 columns and will be left-justified. The BAL.DUE field will be right-justified using 12 columns. The NUMBER.OF.ORDERS field will be right-justified using 8 columns, and any empty columns will be zero-filled.

## **FOOTING**

The FOOTING option will create a single record in the output file after all other output records have been produced. Typical usage would be to add a "trailer" record when creating data for a service bureau.

```

GET.LIST MAILING
295 records retrieved to list 0.
DOWNLOAD CUSTOMERS FORMAT FIXED \
  NAME STREET CITY STATE ZIP \
  FOOTING @SYSTEM.RETURN.CODE FMT "8'0'R" \
  FILE DOCS MAILING.DAT

```

The output file in this case will contain 296 records. There will be 295 detail records (showing customer name, street, city, state, and zip) and one last record containing "00000296".

## **FOOTING.ON**

This option is used in conjunction with the BREAK.ON and BREAK.SUP options. FOOTING.ON is used to specify the contents of control-break output.

```

SELECT CUSTOMERS BY ZIP BY NAME WITH BAL.DUE GT 0.00
DOWNLOAD CUSTOMERS \
  DETAIL ZIP NAME BAL.DUE \
  BREAK.SUP ZIP \
  FOOTING.ON ZIP ZIP LITERAL "TOTALS" TOTAL BAL.DUE \
  FOOTING.ON FINAL LITERAL "GRAND" LITERAL "TOTALS" \
  TOTAL BAL.DUE

```

```

"45314","Adams Excavating",500.00
"45314","Yonker's Donuts",300.00
"45314","TOTALS",800.00
"46517","Elko Camera",250.00
"46517","Furniture by Bill",100.00
"46517","Home Town",200.00

```

```
"46517", "TOTALS", 550.00
"GRAND", "TOTALS", 1350.00
```

## **FORMAT**

DOWNLOAD can produce output files in a variety of formats. You can specify which format you want using the FORMAT option. See the chapter "Available File Formats" for details.

## **FROM**

You may instruct DOWNLOAD to process an active select list other than list zero by using the FROM option. Compare:

```
GET.LIST MY.LIST
17 records retrieve to list 0.
DOWNLOAD CUSTOMERS NAME PHONE
```

with:

```
GET.LIST MY.LIST TO 3
17 records retrieve to list 3.
DOWNLOAD CUSTOMERS NAME PHONE FROM 3
```

## **HEADING**

The HEADING option generates a single record in front of all the other output records. It can be used as a heading in the traditional sense (showing field names, for instance), or it can be used to show record counts, dates, etc. that might be required by the application which will use the output file.

Examples:

```
GET.LIST MY.LIST
3 records retrieved to list 0.
DOWNLOAD CUSTOMERS \
    DETAIL NAME PHONE ZIP \
    HEADING FIELD.NAMES
```

"NAME", "PHONE", "ZIP"	{heading}
"Harrison Electric", "616-444-9283", "49418"	{detail}
"General Toy Repair", "800-123-4400", "88012"	{detail}
"My Pet Store", "912-421-1234", "20001"	{detail}

```
GET.LIST MY.LIST
3 records retrieved to list 0.
DOWNLOAD CUSTOMERS \
```

DETAIL NAME PHONE ZIP \  
 HEADING LITERAL "Customer" LITERAL "Phone" \  
 LITERAL "Zip"

"Customer", "Phone", "Zip"	{heading}
"Harrison Electric", "616-444-9283", "49418"	{detail}
"General Toy Repair", "800-123-4400", "88012"	{detail}
"My Pet Store", "912-421-1234", "20001"	{detail}

GET.LIST MY.LIST

3 records retrieved to list 0.

DOWNLOAD CUSTOMERS \  
 DETAIL NAME PHONE ZIP FORMAT FIXED \  
 HEADING @SYTEM.RETURN.CODE FMT "8'0'R"

00000003		{heading}
Harrison Electric	616-444-928349418	{detail}
General Toy Repair	800-123-440088012	{detail}
My Pet Store	912-421-123420001	{detail}

### **HEADING.ON**

If you need a special record in front of each "control-break" group of output records, use the HEADING.ON option to produce that record.

SELECT CUSTOMERS BY STATE SAMPLE 5

5 records selected to list 0.

DOWNLOAD CUSTOMERS \  
 DETAIL STATE NAME \  
 BREAK.SUP STATE \  
 HEADING.ON STATE LITERAL "STARTING" STATE

"STARTING", "AR"
"AR", "Razorback Industries"
"AR", "Alpha Connections"
"STARTING", "MI"
"MI", "Motor City News"
"MI", "Michigan Outdoors"
"MI", "Alpena Journal"

### **HTML.BODY**

This clause is used specify the body for the output Web page. The default is an empty BODY clause (white background).

SELECT CUSTOMERS BY STATE SAMPLE 5

```

5 records selected to list 0.
DOWNLOAD CUSTOMERS \
  @ID \
  CUSTOMER.NAME \
  STATE \
  HTML.BODY ' BGCOLOR="#FFFF33#' ' \
  FORMAT HTML FILE _HOLD_ CUSTOMER.HTM

```

### **HTML.BOTTOM**

This clause is used to enter HTML tags and text which will appear just after the output data table (but before the '</body>' tag).

```

SELECT CUSTOMERS BY STATE SAMPLE 5
5 records selected to list 0.
DOWNLOAD CUSTOMERS \
  @ID \
  CUSTOMER.NAME \
  STATE \
  HTML.TITLE "Acme Customer List" \
  HTML.BOTTOM \
  "<H2><CENTER>***CONFIDENTIAL***</CENTER></H2>" \
  FORMAT HTML FILE _HOLD_ CUSTOMER.HTM

```

will center the text "\*\*\*CONFIDENTIAL\*\*\*" horizontally on the page just after the data table showing the customers.

### **HTML.CELL**

This clause is used supply HTML code which will be applied to a particular cell in the output table (within the TD tag).

```

SELECT CUSTOMERS BY STATE SAMPLE 5
5 records selected to list 0.
DOWNLOAD CUSTOMERS \
  @ID \
  CUSTOMER.NAME HTML.CELL ' BGCOLOR="BLUE" ' \
  STATE \
  FORMAT HTML FILE _HOLD_ CUSTOMER.HTM

```

will produce a table with three columns (id number, name, state). Each of the customer names will be in cells with a blue background.

### **HTML.END**

This clause is used specify the closing tag of an HTML container-style tag. See HTML.START for an example.

### **HTML.ROW**

This clause is used to specify HTML code which applies to an entire row of the output table (within the TR tag).

```
SELECT CUSTOMERS BY STATE SAMPLE 5
5 records selected to list 0.
DOWNLOAD CUSTOMERS \
  @ID \
  CUSTOMER.NAME \
  STATE \
  HTML.ROW ' BGCOLOR="BLUE" ' \
  HEADING LITERAL "ID" \
    LITERAL "Name" \
    LITERAL "State" \
    HTML.ROW ' BGCOLOR="RED" ' \
  FORMAT HTML FILE _HOLD_ CUSTOMER.HTM
```

will produce a table in which the heading row is red and the detail rows are blue.

### **HTML.START**

This clause is used to specify HTML code which will affect the contents of a particular cell in the output table. A corresponding HTML.END phrase may be used for container tags (tags that have a start-tag and end-tag).

```
SELECT CUSTOMERS BY STATE SAMPLE 5
5 records selected to list 0.
DOWNLOAD CUSTOMERS \
  @ID \
  CUSTOMER.NAME \
    HTML.START '<B>' HTML.END '</B>' \
  STATE \
  FORMAT HTML FILE _HOLD_ CUSTOMER.HTM
```

will produce a table in which each customer name is shown in bold.

### **HTML.TABLE**

This clause is used specify characteristics of the output data table. The default

is a border size of 1 (small, visible lines). To use invisible lines, set the border to zero.

```
SELECT CUSTOMERS BY STATE SAMPLE 5
5 records selected to list 0.
DOWNLOAD CUSTOMERS \
    @ID \
    CUSTOMER.NAME \
    STATE \
    HTML.TABLE ' BORDER="0" ' \
    FORMAT HTML FILE _HOLD_ CUSTOMER.HTM
```

### ***HTML.TITLE***

This clause is used to set an HTML title (the text which will be displayed on the top menu bar of the Web browser). Note that the TITLE might be different from a text line appearing just in front of the data table.

```
SELECT CUSTOMERS BY STATE SAMPLE 5
5 records selected to list 0.
DOWNLOAD CUSTOMERS \
    @ID \
    CUSTOMER.NAME \
    STATE \
    HTML.TITLE "Acme Customer List" \
    HTML.TOP "<H2>Customers</H2>" \
    FORMAT HTML FILE _HOLD_ CUSTOMER.HTM
```

will produce an HTML page with the following structure:

```
<HTML>
<HEADING>
<TITLE>
Acme Customer List
</TITLE>
</HEADING>
<BODY>
<H2>Customers</H2>
<TABLE BORDER="1">
...
</TABLE>
</BODY>
</HTML>
```

### **HTML.TOP**

This clause is used to enter HTML tags and text which will appear prior to the output data table.

```
SELECT CUSTOMERS BY STATE SAMPLE 5
5 records selected to list 0.
DOWNLOAD CUSTOMERS \
  @ID \
  CUSTOMER.NAME \
  STATE \
  HTML.TITLE "Acme Customer List" \
  HTML.TOP \
  "<H2><CENTER>**** CONFIDENTIAL ***</CENTER></H2>" \
  FORMAT HTML FILE _HOLD_ CUSTOMER.HTM
```

will center the text "\*\*\*\* CONFIDENTIAL \*\*\*\*" horizontally on the page just prior to the data table showing the customers. Note that this text need not be the same as the text specified in the title.

### **KEY**

This clause is used to identify the record key for a secondary file. Consider this example:

```
DOWNLOAD CUSTOMERS \
  SECONDARY.FILE EMPLOYEES \
  KEY SALES.REP \
  NAME EMPLOYEES->EMP.NAME
```

This DOWNLOAD command uses a primary file named CUSTOMERS and a secondary file named EMPLOYEES. For each record in CUSTOMERS, the output will contain the NAME (from the CUSTOMERS file) and the EMP.NAME (from the EMPLOYEES file). The key to the EMPLOYEES file is the field SALES.REP on the CUSTOMERS file.

The example above is equivalent to creating an I-descriptor called EMP.NAME on CUSTOMERS as shown below and then using the DOWNLOAD command shown below.

```
DICT CUSTOMERS EMP.NAME
001: I
002: TRANS('EMPLOYEES',SALES.REP,'EMP.NAME','X')

DOWNLOAD CUSTOMERS \
  NAME EMP.NAME
```



See the description for ALIAS and SECONDARY.FILE for further explanations.

### **LENGTH**

The LENGTH field qualifier can be used when producing FIXED output to control the size of a field. (This could also be done using the FMT field qualifier.)

```
DOWNLOAD CUSTOMERS FORMAT FIXED \
      NAME LENGTH 35 ZIP LENGTH 12 PHONE LENGTH 15
```

will produce an output file with NAME in columns 1-35, ZIP in columns 36-47, and PHONE in columns 48-62.

### **LINE**

If you need to produce more than one output line for each input record, use the LINE command. The examples below illustrate a couple of variations achieved using the LINE field qualifier.

Producing each field on a line by itself (could also be achieved using RECORD.ORIENTATION):

```
DOWNLOAD CUSTOMERS FORMAT FIXED \
      NAME LINE 1 \
      ZIP LINE 2 \
      PHONE LINE 3 \
      BAL.DUE LINE 4
```

```
Adams Manufacturing
46514
219-555-0876
568.12
Smith Furniture
60606
312-498-1234
49.00
```

Multiple fields on one line:

```
DOWNLOAD CUSTOMERS FORMAT FIXED \
      NAME \
      ZIP \
      PHONE \
      BAL.DUE LINE 2
```

```
Adams Manufacturing    46514    219-555-0876
568.12
```

```
Smith Furniture      60606    312-498-1234
49.00
```

Once specified, the LINE field qualifier remains in effect until it is overridden:

```
DOWNLOAD CUSTOMERS FORMAT FIXED \
NAME LINE 1\
ZIP \
PHONE LINE 2\
BAL.DUE
```

```
Adams Manufacturing  46514
219-555-0876    568.12
Smith Furniture      60606
312-498-1234    49.00
```

### **LITERAL**

The LITERAL command lets you produce the same character string on all output records. This character string can be entered in a paragraph or prompted at execution time.

```
DOWNLOAD CUSTOMERS \
NAME BAL.DUE \
LITERAL "05/17/97"
```

```
"Adams Welding",56.87,"05/17/97"
"Miller Inc.",123.98,"05/17/97"
"Excitement",1000.00,"05/17/97"
```

To have the literal string change each time you execute the command, try this:

```
DOWNLOAD CUSTOMERS \
NAME BAL.DUE \
LITERAL "<<DUE DATE,2N/2N/2N>>"
```

### **LPTR**

Adding LPTR to the DOWNLOAD command will cause the output-record layout to be sent to the line printer. This clause is ignored if the layout is not being printed (see PRINT.LAYOUT).

### **MAX**

The MAX modifier is used in conjunction with a BREAK.ON or BREAK.SUP option. MAX will generate the maximum value in the group that it follows.

```

SELECT CUSTOMERS BY STATE
DOWNLOAD CUSTOMERS BREAK.ON STATE BAL.DUE \
    FOOTING.ON STATE \
    LITERAL "LARGEST" MAX BAL.DUE
    FOOTING.ON FINAL \
    LITERAL "GRANDTOT" TOTAL BAL.DUE

```

```

"FL",552.87
"FL",300.00
"LARGEST",552.87           {this is the detail break line}
"OH",250.00
"OH",125.00
"OH",50.00
"LARGEST",250.00          {this is the detail break line}
"TN",985.12
"LARGEST",985.12          {this is the detail break line}
"GRANDTOT",2289.99        {this is the final break line}

```

## **MIN**

MIN finds the minimum value within a control-break group. Here is an example:

```

SELECT CUSTOMERS BY STATE
DOWNLOAD CUSTOMERS BREAK.ON STATE BAL.DUE \
    FOOTING.ON STATE \
    LITERAL "SMALLEST" MIN BAL.DUE
    FOOTING.ON FINAL \
    LITERAL "GRANDTOT" TOTAL BAL.DUE

```

```

"FL",552.87
"FL",300.00
"SMALLEST",300.00          {this is the detail break line}
"OH",250.00
"OH",125.00
"OH",50.00
"SMALLEST",50.00          {this is the detail break line}
"TN",985.12
"SMALLEST",985.12          {this is the detail break line}
"GRANDTOT",2289.99        {this is the final break line}

```

## **MULTI.VALUE**

You can have a field which is defined to be single-valued treated as a multi-valued field by DOWNLOAD by using the MULTI.VALUE modifier on the field.

```

DOWNLOAD CUSTOMERS \

```

NAME STREET MULTI.VALUE NUM.VALUES ALL  
will treat the STREET as a multi-valued field and will show all of the values for  
each record, even if the dictionary for CUSTOMERS shows STREET as a  
single-valued field.

### **MV.ORIENTATION**

For some applications like spreadsheets, you want multi-valued output to line up  
in columns. You can accomplish this with the MV.ORIENTATION option.

Here is an example using comma-quote format:

```
DOWNLOAD STUDENTS \
NAME \
REG.TERMS NUM.VALUES ALL MV.ORIENTATION VERTICAL
```

```
"Harris, Amy", "94/FA"
, "95/WI"
, "95/SP"
, "96/FA"
"Jones, Thomas", "93/SP"
, "97/FA"
```

Here is the same example using fixed format:

```
DOWNLOAD STUDENTS FORMAT FIXED \
NAME \
REG.TERMS NUM.VALUES ALL MV.ORIENTATION VERTICAL
```

```
Harris, Amy      94/FA
                  95/WI
                  95/SP
                  96/FA
Jones, Thomas    93/SP
                  97/FA
```

If you want the single-valued fields to repeat on each output record, you can use  
an exploded select list:

```
SELECT STUDENTS SAMPLE 2 BY NAME BY.EXP REG.TERMS
6 records retrieved to list 0.
DOWNLOAD STUDENTS FORMAT FIXED \
NAME \
BY.EXP REG.TERMS REG.TERMS \
```

```
Harris, Amy      94/FA
Harris, Amy      95/WI
Harris, Amy      95/SP
```

Harris, Amy	96/FA
Jones, Thomas	93/SP
Jones, Thomas	97/FA

Note in this last example that MV.ORIENTATION and NUM.VALUES would be meaningless, because we are referencing each of the values explicitly through the exploded select list.

### **NONE**

The keyword NONE can be used to suppress the generation of a break record. In the example below, break line on STATE is being suppressed.

```
SELECT CUSTOMERS BY STATE
DOWNLOAD CUSTOMERS BREAK.ON STATE BAL.DUE \
      FOOTING.ON STATE NONE \
      FOOTING.ON FINAL \
      LITERAL "GRANDTOT" TOTAL BAL.DUE
```

```
"FL",552.87
"FL",300.00
"OH",250.00
"OH",125.00
"OH",50.00
"TN",985.12
"GRANDTOT",2289.99           {this is the final break line}
```

### **NO.DISPLAY.COUNT**

NO.DISPLAY.COUNT turns off the progress meter (printing of asterisks) that usually occurs when DOWNLOAD is processing a large select list.

### **NO.LINEFEED**

NO.LINEFEED tells DOWNLOAD to produce each output record without generating a line feed. This type of file can be used by programs which accept streaming input rather than record-based input (Pascal programs often use streaming input). This option is applicable only to the FIXED format layout. Compare these two examples:

```
GET.LIST MY.LIST
3 records retrieved to list 0.
DOWNLOAD CUSTOMERS ID.NO STATE FORMAT FIXED

102324MI
```

402832IN  
239482OH

GET.LIST MY.LIST  
3 records retrieved to list 0.  
DOWNLOAD CUSTOMERS ID.NO STATE FORMAT FIXED \  
NO.LINEFEED

102324MI402832IN239482OH

### **NO.NULLS**

NO.NULLS excludes null-values from calculation of averages (see AVERAGE).

### **NO.PAGE**

NO.PAGE turns off the screen pausing which is typical in the Unidata database environment. In particular, as DOWNLOAD generates the progress meter (rows of asterisks), the screen may fill. The system will pause at the full screen, indicating that you should press <new line> to continue. If the job is being run at night, there might not be anyone around to press the <new line> key. By including NO.PAGE in the DOWNLOAD command, you will be assured that the program will not be waiting on keyboard input.

### **NO.PRINT.ERRORS**

When doing repetitive processing with DOWNLOAD, you may have a situation where some records in your select list will generate errors (record not found, illegal field value, etc.), but you want to consider this "normal" and not have DOWNLOAD generate an error report. The NO.PRINT.ERRORS option will suppress printing of the error report.

### **NUM.SUBVALUES**

If a multi-valued field is being printed and that field contains sub-values, DOWNLOAD will only copy the first subvalue of each value to the output. If you want more than one subvalue included, specify the NUM.SUBVALUES field qualifier.

DOWNLOAD STUDENTS NAME \  
TERM.CONTACTS NUM.VALUES ALL NUM.SUBVALUES 3

would produce output with all values for TERM.CONTACTS and (for any particular TERM.CONTACT), include up to 3 subvalues.

### **NUM.VALUES**

By default, DOWNLOAD only uses the first value of a multi-valued field. If you want more values included in the output, use the NUM.VALUES field qualifier. You may specify a particular number of values to be used or you may use the keyword ALL to indicate that you want all values.

Note that specifying a particular number of values will cause each record of the output to **always** have that number of values. If you specify the keyword ALL, then the number of values from one record to the next may vary, depending on the number of values on the input data.

Consider these data records:

Record one: 001: ADAMS  
              002: 1996}1997}1998}1999  
Record two: 001: SMITH  
              002: 1994}1997

The default behavior (no NUM.VALUES clause):

```
DOWNLOAD CUSTOMERS NAME ACTIVE.YR
"ADAMS", "1996"
"SMITH", "1994"
```

Specifying two values per record:

```
DOWNLOAD CUSTOMERS NAME ACTIVE.YR \
NUM.VALUES 2
"ADAMS", "1996", "1997"
"SMITH", "1994", "1997"
```

Specifying five values per record:

```
DOWNLOAD CUSTOMERS NAME ACTIVE.YR \
NUM.VALUES 5
"ADAMS", "1996", "1997", "1998", "1999", ""
"SMITH", "1994", "1997", "", "", ""
```

Specifying all values:

```
DOWNLOAD CUSTOMERS NAME ACTIVE.YR \
NUM.VALUES ALL
"ADAMS", "1996", "1997", "1998", "1999"
"SMITH", "1994", "1997"
```

## **OVERWRITING**

If the DOWNLOAD command specifies an output file which already exists, the default behavior is to terminate with an error message. If you want the output file to be deleted and a new one created in its place, use the OVERWRITING option.

```
DOWNLOAD CUSTOMERS NAME ZIP \
FILE DOCS CUSTOMER.DAT OVERWRITING
```

See also APPEND.

## **PRINT.ERRORS**

This option merely reinforces the default behavior: DOWNLOAD generates an error report (on screen) if it encounters processing errors such as record not found, illegal field value, etc.

## **PRINT.LAYOUT**

The PRINT.LAYOUT option generates a report describing the layout of the output file. This report is sometimes useful for debugging and for use by external service bureaus to document the record layouts. The report contains header information (file being processed, date, time, format) and a field listing. For FIXED format output, the report also shows beginning and ending column numbers.

## **PROGRESS.INTERVAL**

By default, the progress meter shows an asterisk for every 10 records processed. You may change this interval using the PROGRESS.INTERVAL option.

```
DOWNLOAD CUSTOMERS NAME ZIP \
PROGRESS.INTERVAL 50
```

will print an asterisk for every 50 records processed.

## **QUOTE.CHAR**

When producing an output file in comma-quote format, non-numeric data values are surrounded by quotation marks. If you wish to use a different character around these values, specify it using the QUOTE.CHAR option.

Contrast:

```
DOWNLOAD CUSTOMERS NAME PHONE
"ABC Tooling", "937-555-1212"
```



```
"Middletown Catering", "800-555-9898"
with:
DOWNLOAD CUSTOMERS NAME PHONE \
      QUOTE.CHAR "$"
$ABC Tooling$, $937-555-1212$
$Middletown Catering$, $800-555-9898$
```

You may set the quote character to null, obtaining results like the following:

```
DOWNLOAD CUSTOMERS NAME PHONE \
      QUOTE.CHAR ""
ABC Tooling, 937-555-1212
Middletown Catering, 800-555-9898
```

### **RECORD.LENGTH**

If each record of the output must have the same length (i.e., must be padded with spaces), use the RECORD.LENGTH option.

```
DOWNLOAD CUSTOMERS NAME ZIP \
      FORMAT FIXED RECORD.LENGTH 60
will produce output records that are always 60 characters long.
```

### **RECORD.ORIENTATION**

The default record orientation is horizontal (each line in the output represents a single record from the input). If you want each output field to appear on a line by itself, use the RECORD.ORIENTATION VERTICAL option.

```
DOWNLOAD CUSTOMERS NAME PHONE ZIP
"ABC Tooling", "937-555-1212", "46514"
"Middletown Catering", "800-555-9898", "55012"
```

```
DOWNLOAD CUSTOMERS NAME PHONE ZIP \
      RECORD.ORIENTATION VERTICAL
"ABC Tooling"
"937-555-1212"
"46514"
"Middletown Catering"
"800-555-9898"
"55012"
```

### **REMOVE.PUNCTUATION**

Some vendors (like the United States Postal Service) require output without punctuation (commas, apostrophes, etc.). The REMOVE.PUNCTUATION option will delete these characters from your output file. Compare the following examples:

#### DOWNLOAD STUDENTS MAIL.NAME CITY

"Miss Monica J. Billings", "St. Louis, MO 63115"  
"Mr. Henry Jordan, Jr.", "Xenia, OH 45385"

#### DOWNLOAD STUDENTS MAIL.NAME CITY REMOVE.PUNCTUATION

"Miss Monica J Billings", "St Louis"  
"Mr Henry Jordan Jr", "Xenia"

See also UPCASE.

### **SAMPLE**

The SAMPLE keyword functions just like the SAMPLE keyword in the LIST statement. You can use SAMPLE to select just the first few records from your file or active select list. The following two examples are equivalent:

DOWNLOAD CUSTOMERS NAME SAMPLE 8

SELECT CUSTOMERS SAMPLE 8  
DOWNLOAD CUSTOMERS NAME

If you do not specify the number of records, SAMPLE will use a default of ten records.

### **SECONDARY.FILE**

The SECONDARY.FILE option lets you reference fields from other files without creating a lot of I-descriptors. The SECONDARY.FILE option is also useful when a field in a file references another record in that same file.

DOWNLOAD PEOPLE \  
SECONDARY.FILE STUDENTS KEY @ID \  
LAST FIRST STUDENTS->CLASS

references fields LAST and FIRST from the PEOPLE file and the field CLASS from the students file (the same record key is used for both files).

DOWNLOAD STUDENTS \  
SECONDARY.FILE STUD.SCHEDS KEY LAST.SS.KEY \  
NAME STUD.SCHEDS->COURSE NUM.VALUES ALL  
references field NAME from the STUDENTS file and field COURSE from the STUD.SCHEDS file. The record key for STUD.SCHEDS is computed in field LAST.SS.KEY of the STUDENTS file.

```
DOWNLOAD STUDENTS \
  SECONDARY.FILE PEOPLE KEY PARENT.ID ALIAS PGS \
  SECONDARY.FILE PEOPLE KEY SPOUSE ALIAS SP \
  NAME PARENT.ID PGS->NAME SPOUSE SP->NAME \
  FORMAT FIXED FIELD.GAP 2
```

retrieves data from the PEOPLE file:

NAME is the person's name

PARENT.ID is the id number of the person's parent

PGS->NAME is the name of the parent (accessed via PARENT.ID)

SPOUSE is the id number of the person's spouse

SP->NAME is the name of the spouse (accessed via SPOUSE)

### **SINGLE.VALUE**

If you wish to treat a multi-valued field as single-valued, use the SINGLE.VALUE field qualifier:

```
DOWNLOAD CUSTOMERS NAME ORDER.DATES SINGLE.VALUE
```

The ORDER.DATES field will be treated as single-valued. This is actually the default behavior, and would likely be useful only if you had changed the default:

```
DOWNLOAD CUSTOMERS DEFAULT NUM.VALUES ALL \
```

```
CONTACT.NAMES SITE.CITIES ORDER.DATES SINGLE.VALUE
```

would include all of the CONTACT.NAMES and SITE.CITIES but only the first ORDER.DATE for each record.

### **SUBR**

The SUBR command allows you to call a subroutine to obtain data, as opposed to using a data field from the file. The syntax is identical to the use of SUBR in defining an I-descriptor. The DOWNLOAD command would look like this:

```
DOWNLOAD PROSPECTS \
  NAME HOME.PHONE \
  SUBR("RATE.PROSPECTS",INCOME,ZIP,EDUCATION)
```

where INCOME, ZIP, and EDUCATION are fields in the PROSPECTS file. The subroutine RATE.PROSPECTS uses these arguments to calculate a rating.

For more information on using SUBR, see the chapter on "Defining Output Data".

### **TOTAL**

Use the TOTAL keyword to define the contents of a control-break (footing) line.

```
SELECT CUSTOMERS BY STATE
DOWNLOAD CUSTOMERS BREAK.ON STATE BAL.DUE \
```

```
FOOTING.ON STATE \
LITERAL "SUBTOT" TOTAL BAL.DUE
FOOTING.ON FINAL \
LITERAL "GRANDTOT" TOTAL BAL.DUE
```

```
"FL",552.87
"FL",300.00
"SUBTOT",852.87           {this is the detail break line}
"OH",250.00
"OH",125.00
"OH",50.00
"SUBTOT",425.00          {this is the detail break line}
"TN",985.12
"SUBTOT",985.12          {this is the detail break line}
"GRANDTOT",2289.99       {this is the final break line}
```

### **UPCASE**

The UPCASE keyword instructs DOWNLOAD to convert all output to upper case. This can be helpful when a vendor (e.g., the United States Postal Service) prefers information in upper case. Compare the following examples:

```
DOWNLOAD STUDENTS NAME CITY
"Billings, Monica","San Jose"
"Jordan, Henry","Wilmington"
```

```
DOWNLOAD STUDENTS NAME CITY UPCASE
"BILLINGS, MONICA","SAN JOSE"
"JORDAN, HENRY","WILMINGTON"
```

See also REMOVE.PUNCTUATION.

### **USING**

The USING option allows you to DOWNLOAD one file but use a dictionary from a different file. See the chapter "Defining Output Data" for more information.

### **WHEN**

The WHEN option for DOWNLOAD can be used to control when an output value appears. WHEN does **not** control which records get produced; only which values show. The following examples illustrate:

```
SELECT STUDENTS BY NAME BY.EXP REG.TERMS SAMPLE 3
7 records selected to list 0.
DOWNLOAD STUDENTS NAME BY.EXP REG.TERMS \
REG.TERMS
```

```

"Johnson, Susan", "95/SP"
"Johnson, Susan", "95/FA"
"Johnson, Susan", "96/FA"
"Kennedy, Abraham", "93/FA"
"Kennedy, Abraham", "94/WI"
"Larson, Jenny", "94/FA"
"Larson, Jenny", "95/FA"

```

SELECT STUDENTS BY NAME BY.EXP REG.TERMS SAMPLE 3

7 records selected to list 0.

DOWNLOAD STUDENTS NAME BY.EXP REG.TERMS \  
 REG.TERMS WHEN REG.TERMS LIKE '...FA...'

```

"Johnson, Susan", " " {note the null value}
"Johnson, Susan", "95/FA"
"Johnson, Susan", "96/FA"
"Kennedy, Abraham", "93/FA"
"Kennedy, Abraham", " " {note the null value}
"Larson, Jenny", "94/FA"
"Larson, Jenny", "95/FA"

```

### **WRITE.INTERVAL**

The WRITE.INTERVAL option is useful if your host system tends to “overrun” the destination system. For example, if you are executing DOWNLOAD on a Unix host but the output is being written to a network file server via an NFS-mounted volume, the host may write data faster than what the file server can accept it. To slow down the output, use the WRITE.INTERVAL command.

```

SELECT CUSTOMERS WITH CUST.SALESPERSON = "SMITH"
DOWNLOAD CUSTOMERS CUST.NAME CUST.ZIP \  

  FILE HERO CUSTOMERS \  

  WRITE.INTERVAL 20 3 \  

  FORMAT FIXED LPTR

```

will cause DOWNLOAD to pause for 3 seconds after processing each set of 20 records. The default WRITE.INTERVAL is 10 records with a sleep time of zero (i.e., no pausing between groups of records).

## Version History

\* Stamped: p3 rotmand, /datatel/live/collive, user #1542, 01 Feb 01, 08:04AM.  
\* Version 5.10  
\* Enable "@" variables in file names  
\* Add WRITE.INTERVAL option to pause between writing groups of  
\* records (necessary on some systems communicating via NFS  
\* or Samba)  
\* Fix bug in WP51 format where null fields were suppressed if they  
\* were at the end of the output record.  
\* Fix bug in field qualifier MAX (used in break lines).  
\*  
\*  
\*  
\* Stamped: pe rotmand, /disk1/coltest, user #12980, 06 Jul 00, 08:04AM.  
\* Version 5.00  
\* Added support for HTML files  
\* Added APPEND option  
\* Added REMOVE.PUNCTUATION option  
\* Corrected typographical errors in the documentation  
\* Produce PDF version of the documentation  
\*  
\*  
\*  
\* Stamped: pty/ttyq5 rotmand, /disk1/collive, user #16160, 14 Feb 97, 03:35PM.  
\* Version 4.0  
\* Added support for DBF files  
\* Changed headings used in FIXED and DBF formats to follow same  
\* lengths as detail records unless over-ridden on the command line  
\* Added FIELD.NAMES clause to HEADING option  
\* Added support for "@" variables such as @DATE, @SYSTEM.RETURN.CODE  
\* Added NO.PAGE option to turn off screen pauses on progress meter  
\* and screen-based output  
\* Added ability to write to a subdirectory without creating a VOC  
\* pointer (see documentation for FILE option).  
\* Various bug fixes, including:  
\* Default @ID when using secondary file  
\* More-complete DIF output (required by Excel)  
\* Moved version history to separate file  
\* Modified on-line help  
\* Created WordPerfect documentation  
\*  
\*  
\*  
\* Version 3.1  
\* Stamped: pty/ttyp4 rotmand, /disk1/collive, user #2968, 05 Jul 95, 01:16PM.  
\* Added BREAK.SUP option.  
\*  
\*  
\*  
\* Version 3.0  
\* Stamped: pty/ttyp8 sjoquist, /disk1/collive, user #3835, 01 Nov 94, 01:38PM.

```

*   Added file relations (avoid building multiple, complicated i-descriptors)
*
*
*
* Version 2.2
* Last updated by TEST (SJOQUISTD) at 16:41:41 on 02/11/1994.
*   Modified COMMA format (numeric values do not have quotes)
*   Added QUOTE format (functions like COMMA used to)
*   Created DIF format
*
*
*
* Version 2.1, miscellaneous changes
* Last updated by LIVE (SJOQUISTD) at 13:42:17 on 10/27/1993.
*   Set up new distributable copy (version 2.1)
* Last updated by LIVE (ROTMAND) at 12:26:26 on 09/01/1993.
*   Add 'T' and 'D' option to LITERAL fields.
* Last updated by LIVE (SJOQUIST) at 09:19:31 on 09/09/1992.
*   Add COMMA.CHAR option.
* Last updated by LIVE (ROTMAN) at 17:19:31 on 08/12/1992.
*   Add QUOTE.CHAR option.
* Last updated by LIVE (SJOQUIST) at 08:18:42 on 08/06/1991.
*   Rename DOWNLOAD.LOAD to DOWNLOAD.PARSE
*   Split DOWNLOAD.PROCESS into DOWNLOAD.LOAD & DOWNLOAD.PROCESS
*
*
*
* Version 2.0, HEADING/FOOTING/BREAK.ON
* Last updated by LIVE (SJOQUIST) at 09:34:44 on 07/26/1991.
*   Split into INIT/LOAD/PROCESS subroutines
*
*
*
* Version 1.1, BEGIN ... END keywords with prompting using PROMPT.STACK
* Last updated by LIVE (SJOQUIST) at 08:28:29 on 07/26/1991.
* Last updated by LIVE (SJOQUIST) at 16:20:31 on 04/10/1991.
*
*

```