

Exercice Pratique AWS S3

Objectif : Créer un site web statique hébergé sur S3 Durée : 45-60 minutes

Étapes :

1. Création du Bucket

- Connectez-vous à la console AWS
- Créez un bucket S3 avec un nom unique “[iprec-aws-sabri-web](#)”
- Désactivez "Bloquer tout accès public"

Create bucket [Info](#)

Buckets are containers for data stored in S3.

General configuration

AWS Region

Europe (Paris) eu-west-3

Bucket name [Info](#)

iprec-aws-sabri-Web

Bucket name must be unique within the global namespace and follow the bucket naming rules. [See rules for bucket naming](#)

Copy settings from existing bucket - optional

Only the bucket settings in the following configuration are copied.

[Choose bucket](#)

Format: s3://bucket/prefix

Object Ownership [Info](#)

Control ownership of objects written to this bucket from other AWS accounts and the use of access control lists (ACLs). Object ownership determines who can specify access to objects.

☒ ACLs disabled (recommended)

All objects in this bucket are owned by this account. Access to this bucket and its objects is specified using only policies.

☐ ACLs enabled

Objects in this bucket can be owned by other AWS accounts. Access to this bucket and its objects can be specified using ACLs.

Object Ownership

Bucket owner enforced

Block Public Access settings for this bucket

Public access is granted to buckets and objects through access control lists (ACLs), bucket policies, access point policies, or all. In order to ensure that public access to this bucket and its objects is blocked, turn on Block all public access. These settings apply only to this bucket and its access points. AWS recommends that you turn on Block all public access, but before applying any of these settings, ensure that your applications will work correctly without public access. If you require some level of public access to this bucket or objects within, you can customize the individual settings below to suit your specific storage use cases. [Learn more](#)

☐ Block all public access

Turning this setting on is the same as turning on all four settings below. Each of the following settings are independent of one another.

☐ Block public access to buckets and objects granted through new access control lists (ACLs)

2. Configuration du Site Web Statique

- Créez les fichiers suivants sur votre ordinateur :

// index.html

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>Mon Site S3</title>
```

```
</head>
```

```
<body>
```

```
<h1>Bienvenue sur mon site hébergé sur S3!</h1>
```

```

```

```
</body>
```

```
</html>
```

Files and folders (1 total, 212.0 B)					Remove	Add files	Add folder
All files and folders in this table will be uploaded.							
Find by name					< 1 >		
☐	Name	Folder	Type	Size			
☐	index.html	-	text/html	212.0 B			

Trouvez une image libre de droits et renommez-la "image.jpg"

3. Upload et Configuration

- Uploadez index.html et image.jpg dans votre bucket

Files and folders

Configuration

Files and folders (1 total, 6.6 KB)

Find by name

Name	Folder	Type	Size	Status	Error
image.jpeg	-	image/jpeg	6.6 KB	✔ Succeeded	-

- Configurez les permissions du bucket (politique) :

```
{  
  "Version": "2012-10-17",  
  "Statement": [  
    {  
      "Effect": "Allow",  
      "Principal": "*",  
      "Action": "s3:GetObject",  
      "Resource": "arn:aws:s3:::NOM-DE-VOTRE-BUCKET/*"  
    }  
  ]  
}
```

Activez l'hébergement de site web statique dans les propriétés du bucket

Bucket policy

EditDelete

The bucket policy, written in JSON, provides access to the objects stored in the bucket. Bucket policies don't apply to objects owned by other accounts. [Learn more](#)

```
{  
  "Version": "2012-10-17",  
  "Statement": [  
    {  
      "Effect": "Allow",  
      "Principal": "*",  
      "Action": "s3:GetObject",  
      "Resource": "arn:aws:s3:::iprec-aws-sabri-web/*"  
    }  
  ]  
}
```

Copy

Edit static website hosting [info](#)

Static website hosting

Use this bucket to host a website or redirect requests. [Learn more](#)

Static website hosting

☐ Disable

☒ Enable

Hosting type

☒ Host a static website

☐ Redirect requests for an object

For your customers to access content at the website endpoint, you must make all your content publicly readable. To do so, you can edit the S3 Block Public Access settings for the bucket. For more information, see [Using Amazon S3 Block Public Access](#)

Index document

Specify the home or default page of the website.

index.html

Error document - optional

This is returned when an error occurs.

error.html

Redirection rules - optional

Redirection rules, written in JSON, automatically redirect webpage requests for specific content. [Learn more](#)

4. Tests et Modifications

- Accédez à votre site via l'URL fournie par S3

Modifiez index.html pour ajouter du contenu

- Créez une page error.html pour les erreurs 404

Bonus :

- Ajoutez du CSS pour styliser votre page

