

# Symbolic Weighted Language Models and Quantitative Parsing over Infinite Alphabets

Florent Jacquemard   

Inria & CNAM, Paris, France

## Abstract

We propose a framework for weighted parsing over infinite alphabets. It is based on language models called Symbolic Weighted Automata (**swA**) at the joint between Symbolic Automata (**sA**) and Weighted Automata (**wA**), as well as Transducers (**swT**) and Visibly Pushdown (**sw-VPA**) variants. Like **sA**, **swA** deal with large or infinite input alphabets, and like **wA**, they output a weight value in a semiring domain. The transitions of **swA** are labeled by functions from an infinite alphabet into the weight domain. This is unlike **sA** whose transitions are guarded by boolean predicates over symbols in an infinite alphabet and also unlike **wA** whose transitions are labeled by constant weight values, and who deal only with finite automata. We present some properties of **swA**, **swT** and **sw-VPA** models, that we use to define and solve a variant of parsing over infinite alphabets. We also briefly describe the application that motivated the introduction of these models: a parse-based approach to automated music transcription.

**2012 ACM Subject Classification** Theory of computation → Quantitative automata

**Keywords and phrases** Weighted Automata, Symbolic Automata, Visibly Pushdown, Parsing

**Digital Object Identifier** 10.4230/LIPIcs...

**Funding** Florent Jacquemard: Inria AEx Codex, ANR Collabscore, EU H2020 Polifonia

**Acknowledgements** I want to thank ...


## 1 Introduction

Parsing is the problem of structuring a linear representation on input (a finite word), according to a language model. Most of the context-free parsing approaches [15] assume a finite and reasonably small input alphabet. Such a restriction makes perfect sense in the context of NLP tasks such as constituency parsing, or of programming languages compilers or interpreters. Considering large or infinite alphabets can however be of practical interest, for instance, when dealing with large characters encodings such as UTF-16, *e.g.* for vulnerability detection in Web-applications [8], for the analyse (*e.g.* validation or filtering) of data streams or serialization of structured documents (with textual or numerical attributes) [26], or for processing timed execution traces [3]. The latter case is related to a study that motivated the present work: automated music transcription. In this problem, a music performance, represented symbolically in the form of a sequence of timed musical events, is converted into a score in Common Western Music Notation [14], structured according to nested grouping and metric strength of events. It can therefore be stated as a parsing problem [12], over an infinite alphabet of timed events.

Various extensions of language models for handling infinite alphabets have been studied. For instance, some automata with memory extensions allow restricted storage and comparison of input symbols, (see [26] for a survey), with pebbles for marking positions [25], registers [18], or the possibility to compute on subsequences with the same attribute values [2]. The automata at the core of model checkers compute on input symbols represented by large bitvectors [27] (sets of assignments of Boolean variables) and in practice, each transition accepts a set of such symbols (instead of an individual symbol), represented by Boolean

I think that we can make the case for a larger set of situations: given a linear music notation input, for instance elements in an XML file, we want to structure the input according to a hierarchical rhythmic space. I can elaborate...

register: skip refs and details, add Mikolaj recent



■ **Figure 1** Classes of Symbolic/Weighted Automata.  $\Sigma_{\text{fin}}$  is a finite alphabet,  $\Sigma_{\text{inf}}$  is a countable alphabet,  $\mathbb{B}$  is the Boolean algebra,  $\mathbb{S}$  is a commutative semiring,  $q \xrightarrow{a} q'$  is a transition between states  $q$  and  $q'$ .

44 formula or Binary Decision Diagrams. Following a similar idea, in symbolic automata  
 45 (sA) [7, 8], the transitions are guarded by predicates over infinite alphabet domains. With  
 46 appropriate closure conditions on the sets of such predicates, all the good properties enjoyed  
 47 by automata over finite alphabets are preserved.

48 Other extensions of language models help in dealing with non-determinism, by the  
 49 computation of weight values. With an ambiguous grammar, there may exist several  
 50 derivations (*abstract syntax trees* – AST) yielding one input word. The association of one  
 51 weight value to each AST permits to select a best one (or  $n$  bests). This is roughly the  
 52 principle of *weighted parsing* approaches [13, 24, 23]. In *weighted language models*, like *e.g.*  
 53 probabilistic context-free grammars and weighted automata (wA) [11], a weight value is  
 54 associated to each transition rule, and the rule’s weights can be combined with a associative  
 55 product operator  $\otimes$  into the weight of an AST. A second operator  $\oplus$ , associative and  
 56 commutative, is moreover used to handle the ambiguity of the model, by summing the  
 57 weights of the possibly several (in general exponentially many) AST associated to a given  
 58 input word. Typically,  $\oplus$  will select the best of two weight values. The weight domain,  
 59 equipped with these two operators shall be, at minima, a *semiring* where  $\oplus$  can be extended  
 60 to infinite sums, such as the Viterbi semiring and the tropical min-plus algebra, see Figure 2.

61 In this paper, we present a uniform framework for weighted parsing over infinite input  
 62 alphabets. It is based on *symbolic weighted* finite states language models (swM), gener-  
 63 alizing sA, with functions into an arbitrary semiring instead of Boolean guards, and wA,  
 64 by handling infinite alphabets, see Figure 1. In the transition rules of swM models, input  
 65 symbols appear as variables, and the weight associated to a transition rule is a function of  
 66 these variables. The models presented here are finite automata called symbolic-weighted  
 67 (swA), transducers (swT), and pushdown automata with a visibly restriction [1] (sw-VPA).  
 68 The latter model of automata operates on *nested words* [1], a structured form of words  
 69 parenthesized with markup symbols, corresponding to a linearization of trees. In the context  
 70 of parsing, they can represent (weighted) AST of CF grammars. More precisely, a sw-VPA  $A$   
 71 associates a weight value  $A(t)$  to a given nested word  $t$ , which is the linearization of an AST.  
 On the other hand, a swT can define a distance  $T(s, t)$  between finite words  $s$  and  $t$  over  
 infinite alphabets. Then, the *SW-parsing* problem aims at finding  $t$  minimizing  $T(s, t) \otimes A(t)$   
 (wrt the ranking defined by  $\oplus$ ), given an input word  $s$ . The latter value is called the distance  
 between  $s$  and  $A$  in [21]. Like weighted-parsing methods [13, 24, 23], our approach proceeds

66 This sentence (sym-  
 67 bols as variables)  
 68 is not immediatly  
 69 clear to me. Maybe  
 70 a short example or  
 71 intuition?

72 The weight is a label  
 73 on edges in the de-  
 74 rivation tree, right?  
 75 Not sure I under-  
 76 stand the sentence

77 You mean the dis-  
 78 tance between  $s$  and  
 79  $t$ ? "The latter value"  
 80 is a bit ambiguous

in two steps, based on properties of the swM. The first step is an intersection (Bar-Hillel construction [15]) where, given a swT  $T$ , a sw-VPA  $A$ , and an input word  $s$ , a sw-VPA  $A_{T,s}$  is built, such that for all  $t$ ,  $A_{T,s}(t) = T(s, t) \otimes A(t)$ . In the second step, a best AST  $t$  is found by applying to  $A_{T,s}$  a best search algorithm similar to the shortest distance in graphs [20, 17].

The main contributions of the paper are: (i) the introduction of automata, swA, transducers, swT (Section 3), and visibly pushdown automata sw-VPA (Section 4), generalizing the corresponding classes of symbolic and weighted models, (ii) a polynomial best-search algorithm for sw-VPA, and (iii) a uniform framework (Section 5) for parsing over infinite alphabets, the keys to which are (iii.a) the swT-based definition of generic edit distances between input and output (yield) words, and (iii.b) the use, convenient in this context, of nested words, and sw-VPA, instead of syntax trees and grammars.

## 2 Preliminary Notions

### Semirings

We shall consider semirings for the weight values of our language models. . A *semiring*  $\langle \mathbb{S}, \oplus, \otimes, \mathbb{0}, \mathbb{1} \rangle$  is a structure with a domain  $\mathbb{S}$ , equipped with two associative binary operators  $\oplus$  and  $\otimes$ , with respective neutral elements  $\mathbb{0}$  and  $\mathbb{1}$ , and such that:

- $\oplus$  is commutative:  $\langle \mathbb{S}, \oplus, \mathbb{0} \rangle$  is a commutative monoid and  $\langle \mathbb{S}, \otimes, \mathbb{1} \rangle$  a monoid,
- $\otimes$  distributes over  $\oplus$ :  $\forall x, y, z \in \mathbb{S}$ ,  $x \otimes (y \oplus z) = (x \otimes y) \oplus (x \otimes z)$ , and  $(x \oplus y) \otimes z = (x \otimes z) \oplus (y \otimes z)$ ,
- $\mathbb{0}$  is absorbing for  $\otimes$ :  $\forall x \in \mathbb{S}$ ,  $\mathbb{0} \otimes x = x \otimes \mathbb{0} = \mathbb{0}$ .

Intuitively, in the models presented in this paper,  $\oplus$  selects an optimal value from two given values, in order to handle non-determinism, and  $\otimes$  combines two values into a single value, in a chaining of transitions.

A semiring  $\mathbb{S}$  is *commutative* if  $\otimes$  is commutative. It is *idempotent* if for all  $x \in \mathbb{S}$ ,  $x \oplus x = x$ . Every idempotent semiring  $\mathbb{S}$  induces a partial ordering  $\leq_{\oplus}$  called the *natural ordering* of  $\mathbb{S}$  [20] defined, by: for all  $x, y \in \mathbb{S}$ ,  $x \leq_{\oplus} y$  iff  $x \oplus y = x$ . The natural ordering is sometimes defined in the opposite direction [10]; We follow here the direction that coincides with the usual ordering on the Tropical semiring *min-plus* (Figure 2). An idempotent semiring  $\mathbb{S}$  is called *total* if it  $\leq_{\oplus}$  is total i.e. when for all  $x, y \in \mathbb{S}$ , either  $x \oplus y = x$  or  $x \oplus y = y$ .

► **Lemma 1** (Monotony, [20]). *Let  $\langle \mathbb{S}, \oplus, \otimes, \mathbb{0}, \mathbb{1} \rangle$  be an idempotent semiring. For all  $x, y, z \in \mathbb{S}$ , if  $x \leq_{\oplus} y$  then  $x \oplus z \leq_{\oplus} y \oplus z$ ,  $x \otimes z \leq_{\oplus} y \otimes z$  and  $z \otimes x \leq_{\oplus} z \otimes y$ .*

To express the property of Lemma 1, we call  $\mathbb{S}$  *monotonic wrt  $\leq_{\oplus}$* . Another important semiring property in the context of optimization is superiority [16], which corresponds to the *non-negative weights* condition in shortest-path algorithms [9]. Intuitively, it means that combining elements with  $\otimes$  always increase their weight. Formally, it is defined as the property (i) below.

► **Lemma 2** (Superiority, Boundedness). *Let  $\langle \mathbb{S}, \oplus, \otimes, \mathbb{0}, \mathbb{1} \rangle$  be an idempotent semiring. The two following statements are equivalent:*

- i. *for all  $x, y \in \mathbb{S}$ ,  $x \leq_{\oplus} x \otimes y$  and  $y \leq_{\oplus} x \otimes y$*
- ii. *for all  $x \in \mathbb{S}$ ,  $\mathbb{1} \oplus x = \mathbb{1}$ .*

**Proof.** (ii)  $\Rightarrow$  (i) :  $x \oplus (x \otimes y) = x \otimes (\mathbb{1} \oplus y) = x$ , by distributivity of  $\otimes$  over  $\oplus$ . Hence  $x \leq_{\oplus} x \otimes y$ . Similarly,  $y \oplus (x \otimes y) = (\mathbb{1} \oplus x) \otimes y = y$ , hence  $y \leq_{\oplus} x \otimes y$ . (i)  $\Rightarrow$  (ii) : by the second inequality of (i), with  $y = \mathbb{1}$ ,  $\mathbb{1} \leq_{\oplus} x \otimes \mathbb{1} = x$ , i.e., by definition of  $\leq_{\oplus}$ ,  $\mathbb{1} \oplus x = \mathbb{1}$ . ◀

chap. intersection in [15]

The notation  $A_{T,s}$  has not been introduced so far. It is not clear why  $T$  is a parameter there

OK, à quelques détails (pour moi), tout ça est très bien expliqué

expressiveness: VPA have restricted equality test. comparable to pebble automata?  $\rightarrow$  conclusion

The results are established for a general class of semirings. They can be instantiated for concrete cases

There is sometimes a confusion in the text between the struture and the domain  $\mathbb{S}$ . Not essential

is total necessary?

	domain	$\oplus$	$\otimes$	$\mathbb{0}$	$\mathbb{1}$
Boolean	$\{\perp, \top\}$	$\vee$	$\wedge$	$\perp$	$\top$
Counting	$\mathbb{N}$	$+$	$\times$	$0$	$1$
Viterbi	$[0, 1] \subset \mathbb{R}$	$\max$	$\times$	$0$	$1$
Tropical min-plus	$\mathbb{R}_+ \cup \{\infty\}$	$\min$	$+$	$\infty$	$0$

■ **Figure 2** Some commutative, bounded, total and complete semirings.

In [16], when the property (i) holds,  $\mathbb{S}$  is called *superior wrt* the ordering  $\leq_\oplus$ . We have seen in the proof of Lemma 2 that it implies that  $\mathbb{1} \leq_\oplus x$  for all  $x \in \mathbb{S}$ . Similarly, by the first inequality of (i) with  $y = \mathbb{0}$ ,  $x \leq_\oplus x \otimes \mathbb{0} = \mathbb{0}$ . Hence, in a superior semiring, it holds that for all  $x \in \mathbb{S}$ ,  $\mathbb{1} \leq_\oplus x \leq_\oplus \mathbb{0}$ . Intuitively, from an optimization point of view, it means that  $\mathbb{1}$  is the best value, and  $\mathbb{0}$  the worst. In [20],  $\mathbb{S}$  with the property (ii) of Lemma 2 is called *bounded* – we shall use this term in the rest of the paper. It implies that, when looking for a best path in a graph whose edges are weighted by values of  $\mathbb{S}$ , the loops can be safely avoided, because, for all  $x \in \mathbb{S}$  and  $n \geq 1$ ,  $x \oplus x^n = x \otimes (\mathbb{1} \oplus x^{n-1}) = x$ .

► **Lemma 3.** *Every bounded semiring is idempotent.*

**Proof.** By boundedness,  $\mathbb{1} \oplus \mathbb{1} = \mathbb{1}$ , and idempotency follows by multiplying both sides by  $x$  and distributing. ◀

We shall need below infinite sums with  $\oplus$ . A semiring  $\mathbb{S}$  is called *complete* [11] if it has an operation  $\bigoplus_{i \in I} x_i$  for every family  $(x_i)_{i \in I}$  of elements of  $\text{dom}(\mathbb{S})$  over an index set  $I \subset \mathbb{N}$ , such that:

i. *infinite sums extend finite sums:*

$$\bigoplus_{i \in \emptyset} x_i = \mathbb{0}, \quad \forall j \in \mathbb{N}, \bigoplus_{i \in \{j\}} x_i = x_j, \quad \forall j, k \in \mathbb{N}, j \neq k, \bigoplus_{i \in \{j, k\}} x_i = x_j \oplus x_k,$$

ii. *associativity and commutativity:*

$$\text{for all } I \subseteq \mathbb{N} \text{ and all partition } (I_j)_{j \in J} \text{ of } I, \bigoplus_{j \in J} \bigoplus_{i \in I_j} x_i = \bigoplus_{i \in I} x_i,$$

iii. *distributivity of product over infinite sum:*

$$\text{for all } I \subseteq \mathbb{N}, \bigoplus_{i \in I} (x \otimes y_i) = x \otimes \bigoplus_{i \in I} y_i, \text{ and } \bigoplus_{i \in I} (x_i \otimes y) = \left( \bigoplus_{i \in I} x_i \right) \otimes y.$$

## Label Theory

We shall now define the functions labeling the transitions of SW automata and transducers, generalizing the Boolean algebras of [7] from Boolean to other semiring domains. We consider *alphabets*, which are countable sets of symbols denoted  $\Sigma, \Delta, \dots$ . Given a semiring  $\langle \mathbb{S}, \oplus, \otimes, \mathbb{0}, \mathbb{1} \rangle$ , a *label theory* over  $\mathbb{S}$  is a set  $\bar{\Phi}$  of recursively enumerable sets denoted  $\Phi_\Sigma$ , containing unary functions of type  $\Sigma \rightarrow \mathbb{S}$ , or  $\Phi_{\Sigma, \Delta}$ , containing binary functions  $\Sigma \times \Delta \rightarrow \mathbb{S}$ , and such that:

- for all  $\Phi_{\Sigma, \Delta} \in \bar{\Phi}$ , we have  $\Phi_\Sigma \in \bar{\Phi}$  and  $\Phi_\Delta \in \bar{\Phi}$
- every  $\Phi_\Sigma \in \bar{\Phi}$  contains all the constant functions from  $\Sigma$  into  $\mathbb{S}$ ,
- for all  $\alpha \in \mathbb{S}$  and  $\phi \in \Phi_\Sigma$ ,  $\alpha \otimes \phi : x \mapsto \alpha \otimes \phi(x)$ , and  $\phi \otimes \alpha : x \mapsto \phi(x) \otimes \alpha$  belong to  $\Phi_\Sigma$ , and similarly for  $\oplus$  and for  $\Phi_{\Sigma, \Delta}$
- for all  $\phi, \phi' \in \Phi_\Sigma$ ,  $\phi \otimes \phi' : x \mapsto \phi(x) \otimes \phi'(x)$  belongs to  $\Phi_\Sigma$
- for all  $\eta, \eta' \in \Phi_{\Sigma, \Delta}$ ,  $\eta \otimes \eta' : x, y \mapsto \eta(x, y) \otimes \eta'(x, y)$  belongs to  $\Phi_{\Sigma, \Delta}$

- 155 – for all  $\phi \in \Phi_\Sigma$  and  $\eta \in \Phi_{\Sigma,\Delta}$ ,  $\phi \otimes_1 \eta : x, y \mapsto \phi(x) \otimes \eta(x, y)$  and
- 156  $\eta \otimes_1 \phi : x, y \mapsto \eta(x, y) \otimes \phi(x)$  belong to  $\Phi_{\Sigma,\Delta}$
- 157 – for all  $\psi \in \Phi_\Delta$  and  $\eta \in \Phi_{\Sigma,\Delta}$ ,  $\psi \otimes_2 \eta : x, y \mapsto \psi(y) \otimes \eta(x, y)$  and
- 158  $\eta \otimes_2 \psi : x, y \mapsto \eta(x, y) \otimes \psi(y)$  belong to  $\Phi_{\Sigma,\Delta}$
- 159 – similar closures hold for  $\oplus$ .

161 Intuitively, the operators  $\bigoplus_\Sigma$  return global minimum, wrt  $\leq_\oplus$ , of functions of  $\Phi_\Sigma$ . When  
 162 the semiring  $\mathbb{S}$  is complete, we consider the following operators on the functions of  $\bar{\Phi}$ .

$$\begin{aligned} \bigoplus_\Sigma : \Phi_\Sigma &\rightarrow \mathbb{S}, \phi \mapsto \bigoplus_{a \in \Sigma} \phi(a) \\ \bigoplus_\Sigma^1 : \Phi_{\Sigma,\Delta} &\rightarrow \Phi_\Delta, \eta \mapsto (y \mapsto \bigoplus_{a \in \Sigma} \eta(a, y)) \quad \bigoplus_\Delta^2 : \Phi_{\Sigma,\Delta} \rightarrow \Phi_\Sigma, \eta \mapsto (x \mapsto \bigoplus_{b \in \Delta} \eta(x, b)) \end{aligned}$$

164 In what follows, we might omit the sub- and superscripts in  $\otimes_1, \bigoplus_\Sigma^1, \dots$ , when there is no  
 165 ambiguity. We shall keep them only for the special case  $\Sigma = \Delta$ , i.e.  $\eta \in \Phi_{\Sigma,\Sigma}$ , in order to be  
 166 able to distinguish between the first and the second argument.

167 ► **Definition 4.** A label theory  $\bar{\Phi}$  is complete when the underlying semiring  $\mathbb{S}$  is complete,  
 168 and for all  $\Phi_{\Sigma,\Delta} \in \bar{\Phi}$  and all  $\eta \in \Phi_{\Sigma,\Delta}$ ,  $\bigoplus_\Sigma^1 \eta \in \Phi_\Delta$  and  $\bigoplus_\Delta^2 \eta \in \Phi_\Sigma$ .

170 The following facts are immediate.

171 ► **Lemma 5.** For  $\bar{\Phi}$  complete  $\alpha \in \mathbb{S}$ ,  $\phi, \phi' \in \Phi_\Sigma$ ,  $\psi \in \Phi_\Delta$ , and  $\eta \in \Phi_{\Sigma,\Delta}$ :

- 172 i.  $\bigoplus_\Sigma \bigoplus_\Delta^2 \eta = \bigoplus_\Delta \bigoplus_\Sigma^1 \eta$
- 173 ii.  $\alpha \otimes \bigoplus_\Sigma \phi = \bigoplus_\Sigma (\alpha \otimes \phi)$  and  $(\bigoplus_\Sigma \phi) \otimes \alpha = \bigoplus_\Sigma (\phi \otimes \alpha)$ , and similarly for  $\oplus$
- 174 iii.  $(\bigoplus_\Sigma \phi) \oplus (\bigoplus_\Sigma \phi') = \bigoplus_\Sigma (\phi \oplus \phi')$  and  $(\bigoplus_\Sigma \phi) \otimes (\bigoplus_\Sigma \phi') = \bigoplus_\Sigma (\phi \otimes \phi')$
- 175 iv.  $(\bigoplus_\Delta^2 \eta) \oplus (\bigoplus_\Delta^2 \eta') = \bigoplus_\Delta^2 (\eta \oplus \eta')$ , and  $(\bigoplus_\Delta^2 \eta) \otimes (\bigoplus_\Delta^2 \eta') = \bigoplus_\Delta^2 (\eta \otimes \eta')$
- 176 v.  $\phi \otimes (\bigoplus_\Delta^2 \eta) = \bigoplus_\Delta (\phi \otimes_1 \eta)$ , and  $(\bigoplus_\Delta^2 \eta) \otimes \phi = \bigoplus_\Delta (\eta \otimes_1 \phi)$ , and similarly for  $\oplus$
- 177 vi.  $\psi \otimes (\bigoplus_\Sigma^1 \eta) = \bigoplus_\Sigma (\psi \otimes_2 \eta)$ , and  $(\bigoplus_\Sigma^1 \eta) \otimes \psi = \bigoplus_\Sigma (\eta \otimes_2 \psi)$ , and similarly for  $\oplus$

179 A label theory is called *effective* when for all  $\phi \in \Phi_\Sigma$  and  $\eta \in \Phi_{\Sigma,\Delta}$ ,  $\bigoplus_\Sigma \phi$ ,  $\bigoplus_\Delta \bigoplus_\Sigma \eta$ , and  
 180  $\bigoplus_\Sigma \bigoplus_\Delta \eta$  can be effectively computed from  $\phi$  and  $\eta$ .

181 Concretely, in one of the language models defined below, we consider a finite number of  
 182 base functions  $\phi, \eta$  of the underlying label theory, labelling transitions, and combine them  
 183 with the above operators for construction of other models. The combinations might be  
 184 represented by dags (diagrams) whose leaves are labeled by base functions and inner nodes  
 185 by operators.

### 3 SW Automata and Transducers

187 We follow the approach of [21] for the computation of distances, between words and languages,  
 188 using weighted transducers, and extend it to infinite alphabets. The models introduced in  
 189 this section generalize weighted automata and transducers [11] by labeling each transition  
 190 with a weight function (instead of a simple weight value), that takes the input and output  
 191 symbols as parameters. These functions are similar to the guards of symbolic automata [7, 8],  
 192 but they can return values in a generic semiring, whereas the latter guards are restricted to  
 193 the Boolean semiring.

194 Let  $\mathbb{S}$  be a commutative semiring,  $\Sigma$  and  $\Delta$  be alphabets called respectively *input* and *output*,  
 195 and  $\bar{\Phi}$  be a label theory over  $\mathbb{S}$  containing  $\Phi_\Sigma, \Phi_\Delta, \Phi_{\Sigma,\Delta}$ .

partial application is  
needed?

notion of diagram of  
functions akin BDD  
for transitions in  
practice

mv appendix?

Je trouve qu'il y a  
beaucoup de notions  
à retenir (complete,  
effective) et ça devient  
difficile pour un  
lecteur non spécial-  
iste. Est-ce que tout  
est nécessaire (je ne  
sais plus qui m'avait  
dit: un concept en  
plus, un point en  
moins.

∃ oracle returning ...  
in worst time com-  
plexity T.

## XX:6 Symbolic Weighted Language Models and Parsing over Infinite Alphabets

► **Definition 6.** A symbolic-weighted transducer (*swT*) over  $\Sigma$ ,  $\Delta$ ,  $\mathbb{S}$  and  $\bar{\Phi}$  is a tuple  $T = \langle Q, \text{in}, \bar{w}, \text{out} \rangle$ , where  $Q$  is a finite set of states,  $\text{in} : Q \rightarrow \mathbb{S}$  (respectively  $\text{out} : Q \rightarrow \mathbb{S}$ ) are functions defining the weight for entering (respectively leaving) computation in a state, and  $\bar{w}$  is a triplet of transition functions  $w_{10} : Q \times Q \rightarrow \Phi_{\Sigma}$ ,  $w_{01} : Q \times Q \rightarrow \Phi_{\Delta}$ , and  $w_{11} : Q \times Q \rightarrow \Phi_{\Sigma, \Delta}$ .

We call *number of transitions* of  $T$  the number of pairs of states  $q, q' \in Q$  such that  $w_{10}$  or  $w_{01}$  or  $w_{11}$  is not the constant  $\mathbb{0}$ . For convenience, we shall sometimes present transitions as functions of  $Q \times (\Sigma \cup \{\varepsilon\}) \times (\Delta \cup \{\varepsilon\}) \times Q \rightarrow \mathbb{S}$ , overloading the function names, such that, for all  $q, q' \in Q$ ,  $a \in \Sigma$ ,  $b \in \Delta$ ,

$$\begin{aligned} w_{10}(q, a, \varepsilon, q') &= \phi(a) & \text{where } \phi &= w_{10}(q, q') \in \Phi_{\Sigma}, \\ w_{01}(q, \varepsilon, b, q') &= \psi(b) & \text{where } \psi &= w_{01}(q, q') \in \Phi_{\Delta}, \\ w_{11}(q, a, b, q') &= \eta(a, b) & \text{where } \eta &= w_{11}(q, q') \in \Phi_{\Sigma, \Delta}. \end{aligned}$$

The *swT*  $T$  computes on pairs of words  $\langle s, t \rangle \in \Sigma^* \times \Delta^*$ ,  $s$  and  $t$ , being respectively called *input* and *output* word. More precisely,  $T$  defines a mapping from  $\Sigma^* \times \Delta^*$  into  $\mathbb{S}$ , based on an intermediate function  $\text{weight}_T$  defined recursively, for every states  $q, q' \in Q$ , and every pairs of strings  $\langle s, t \rangle \in \Sigma^* \times \Delta^*$ , where  $au$ , and  $bv$ , denote the concatenation of the symbol  $a \in \Sigma$  (resp.  $b \in \Delta$ ) with a word  $u \in \Sigma^*$  (resp.  $v \in \Delta^*$ ).

$$\begin{aligned} \text{weight}_T(q, \varepsilon, \varepsilon, q') &= \mathbb{1} \quad \text{if } q = q' \text{ and } \mathbb{0} \text{ otherwise} & (1) \\ \text{weight}_T(q, s, t, q') &= \bigoplus_{\substack{q'' \in Q \\ s=au, a \in \Sigma}} w_{10}(q, a, \varepsilon, q'') \otimes \text{weight}_T(q'', u, t, q') \\ &\quad \oplus \bigoplus_{\substack{q'' \in Q \\ t=bv, b \in \Delta}} w_{01}(q, \varepsilon, b, q'') \otimes \text{weight}_T(q'', s, v, q') \\ &\quad \oplus \bigoplus_{\substack{q'' \in Q \\ s=au, t=bv}} w_{11}(q, a, b, q'') \otimes \text{weight}_T(q'', u, v, q') \end{aligned}$$

We recall that, by convention (Section 2), an empty sum with  $\bigoplus$  is equal to  $\mathbb{0}$ . Intuitively, using a transition  $w_{ij}(q, a, b, q')$  means for  $T$ : when reading respectively  $a$  and  $b$  at the current positions in the input and output words, increment the current position in the input word if and only if  $i = 1$ , and in the output word iff  $j = 1$ , and change state from  $q$  to  $q'$ . When  $a = \varepsilon$  (resp.  $b = \varepsilon$ ), the current symbol in the input (resp. output) is not read. Since  $\mathbb{0}$  is absorbing for  $\otimes$  in  $\mathbb{S}$ , one term  $w_{ij}(q, a, b, q'')$  equal to  $\mathbb{0}$  in the above expression will be ignored in the sum, meaning that there is no possible transition from state  $q$  into state  $q'$  while reading  $a$  and  $b$ . This is analogous to the case of a transition's guard not satisfied by  $\langle a, b \rangle$  for symbolic transducers.

The expression (1) can be seen as a stateful definition of an edit-distance between a word  $s \in \Sigma^*$  and a word  $t \in \Delta^*$ , see also [22]. Intuitively,  $w_{10}(q, a, \varepsilon, r)$  is the cost of the deletion of the symbol  $a \in \Sigma$  in  $s$ ,  $w_{01}(q, \varepsilon, b, r)$  is the cost of the insertion of  $b \in \Delta$  in  $t$ , and  $w_{11}(q, a, b, r)$  is the cost of the substitution of  $a \in \Sigma$  by  $b \in \Delta$ . The cost of a sequence of such operations transforming  $s$  into  $t$ , is the product, with  $\otimes$ , of the individual costs of the operations involved; and the distance between  $s$  and  $t$  is the sum, with  $\oplus$ , of all possible products. Formally, the weight associated by  $T$  to  $\langle s, t \rangle \in \Sigma^* \times \Delta^*$  is:



I missed sth: what is this  $\varepsilon$ ? Intuitively clear but not defined?

added  $u$  and  $v$  def

OK tout ça se lit bien :-)



$$T(s, t) = \bigoplus_{q, q' \in Q} \text{in}(q) \otimes \text{weight}_T(q, s, t, q') \otimes \text{out}(q') \quad (2)$$

► **Example 7.** In Common Western Music Notation [14], several symbols may be used to represent one single sounding event. For instance, several notes can be combined with a tie, like in , and one note can be augmented by half its duration with a dot like in . These notations are perceived equivalent when played, as their duration is equal, yet the notation is different. We thus want to be able to compare a music score with music played by a performer. We propose a small weighted transducer model that calculates the distance between an input sequence of sounding events (music "performance") to an output sequence of written events (music "score"). Let us consider the tropical (*min-plus*) semiring  $\mathbb{S}$  of Figure 2 and let  $\Sigma = \mathbb{R}_+$  be an input alphabet of event dates and  $\Delta = \{\mathbf{e}, -\} \times \mathbb{R}_+$  be an output alphabet of symbols with timestamps. A symbol  $\langle \mathbf{e}, d \rangle \in \Delta$  represents an event starting at date  $d$ , and  $\langle -, d \rangle$  is a continuation of the previous event.

We consider a **swT** with two states  $q_0$  and  $q_1$  whose purpose is to compare a recorded performance  $s \in \Sigma^*$  with a notated music sheet  $t \in \Delta^*$ . One timestamp  $d_i \in \Sigma$  may correspond to one notated event  $\langle \mathbf{e}, d'_i \rangle \in \Delta$ , in which case the weight value computed by the **swT** is the time distance between both (see transitions  $w_{11}$  below). If  $\langle \mathbf{e}, d'_i \rangle$  is followed by continuations  $\langle -, d'_{i+1} \rangle \dots$ , they are just skipped with no cost (transitions  $w_{01}$  or weight 1).

$$\begin{aligned} w_{11}(q_0, d, \langle \mathbf{e}, d' \rangle, q_0) &= |d' - d| & w_{11}(q_1, d, \langle \mathbf{e}, d' \rangle, q_0) &= |d' - d| \\ w_{01}(q_0, \varepsilon, \langle -, d' \rangle, q_0) &= 1 & w_{01}(q_1, \varepsilon, \langle -, d' \rangle, q_0) &= 1 \\ w_{10}(q_0, d, \varepsilon, q_1) &= \alpha \end{aligned}$$

We also must be able to take performing errors into account, while still being able to compare with the score, since a performer could, for example, play an unwritten extra note. This is modelled by the transition  $w_{10}$  with an arbitrary weight value  $\alpha \in \mathbb{S}$ , switching from state  $q_0$  (normal) to  $q_1$  (error). The transitions in the second column below switch back to the normal state  $q_0$ . At last, we let  $q_0$  be the only initial and final state, with  $\text{in}(q_0) = \text{out}(q_0) = 1$ , and  $\text{in}(q_1) = \text{out}(q_1) = 0$ .

That way, an **swT** is capable of evaluating the differences between a score and a performance, all the while ensuring that performance errors are plausible.  $\diamond$

The *Symbolic Weighted Automata* are defined similarly as the transducers of Definition 6, by simply omitting the output symbols.

► **Definition 8.** A symbolic-weighted automaton (*swA*) over  $\Sigma$ ,  $\mathbb{S}$  and  $\bar{\Phi}$  is a tuple  $A = \langle Q, \text{in}, w_1, \text{out} \rangle$ , where  $Q$  is a finite set of states,  $\text{in} : Q \rightarrow \mathbb{S}$  (respectively  $\text{out} : Q \rightarrow \mathbb{S}$ ) are functions defining the weight for entering (respectively leaving) computation in a state, and  $w_1$  is a transition function from  $Q \times Q$  into  $\Phi_\Sigma$ .

As above in the case of **swT**, when  $w_1(q, q') = \phi \in \Phi_\Sigma$ , we may write  $w_1(q, a, q')$  for  $\phi(a)$ . The computation of  $A$  on words  $s \in \Sigma^*$  is defined with an intermediate function  $\text{weight}_A$ , defined as follows for  $q, q' \in Q$ ,  $a \in \Sigma$ ,  $u \in \Sigma^*$ ,

$$\begin{aligned} \text{weight}_A(q, \varepsilon, q) &= 1 \\ \text{weight}_A(q, \varepsilon, q') &= 0 \quad \text{if } q \neq q' \\ \text{weight}_A(q, au, q') &= \bigoplus_{q'' \in Q} w_1(q, a, q'') \otimes \text{weight}_A(q'', u, q') \end{aligned} \quad (3)$$

Je crois qu'il faudrait numéroter les exemples indépendamment des définitions. Cet exemple est le premier qui donne des détails sur l'application visée. Il arrive peut-être un peu tard et est long. On pourrait introduire la motivation dans l'intro, et développer des petits exemples au fur et à mesure.

unique → similar

similar → single

modif.

changed end

reformulated this sentence

ccl to the ex

274 and the weight value associated by  $A$  to  $s \in \Sigma^*$  is defined as follows:

$$275 \quad A(s) = \bigoplus_{q,q' \in Q} \text{in}(q) \otimes \text{weight}_A(q, s, q') \otimes \text{out}(q') \quad (4)$$

276 The following property will be useful to the approach on symbolic weighted parsing presented  
277 in Section 5.

278 ► **Proposition 9.** *Given a swT  $T$  over  $\Sigma, \Delta, \mathbb{S}$  commutative, bounded and complete, and  $\bar{\Phi}$   
279 effective, and a swA  $A$  over  $\Sigma, \mathbb{S}$  and  $\bar{\Phi}$ , there exists an effectively constructible swA  $B_{T,A}$   
280 over  $\Delta, \mathbb{S}$  and  $\bar{\Phi}$ , such that for all  $t \in \Delta^*$ ,  $B_{T,A}(t) = \bigoplus_{s \in \Sigma^*} A(s) \otimes T(s, t)$ .*

281 **Proof.** Let  $T = \langle Q, \text{in}_T, \bar{w}, \text{out}_T \rangle$ , where  $\bar{w}$  contains  $w_{10}, w_{01}$ , and  $w_{11}$ , from  $Q \times Q$  into  
282 respectively  $\Phi_\Sigma, \Phi_\Delta$ , and  $\Phi_{\Sigma, \Delta}$ , and let  $A = \langle P, \text{in}_A, w_1, \text{out}_A \rangle$  with  $w_1 : Q \times Q \rightarrow \Phi_\Sigma$ . The  
283 state set of  $B_{T,A}$  will be  $Q' = P \times Q$ . The entering, leaving and transition functions of  $B_{T,A}$   
284 will simulate synchronized computations of  $A$  and  $T$ , while reading an output word of  $\Delta^*$ .  
285 Its state entering functions is defined for all  $p \in P, q \in Q$  by  $\text{in}'(p, q) = \text{in}_A(p) \otimes \text{in}_T(q)$ . The  
286 transition function  $w'_1$  will roughly perform a synchronized product of transitions defined by  
287  $w_1, w_{01}$  ( $T$  reading in output word and not an input word) and  $w_{11}$  ( $T$  reading both an input  
288 word and an output word). Moreover,  $w'_1$  also needs to simulate transitions defined by  $w_{10}$ :  
289  $T$  reading in input word and not an output word. Since  $B_{T,A}$  will read only in the output  
290 word, such a transition corresponds to an  $\varepsilon$ -transition of swA, but swA have been defined  
291 without  $\varepsilon$ -transitions. Therefore, in order to take care of this case, we perform an on-the-fly  
292 suppression of  $\varepsilon$ -transition in the swA in construction, following the algorithm of [19].  
293 Initially, for all  $p_1, p_2 \in P$ , and  $q_1, q_2 \in Q$ , let

$$294 \quad w'_1(\langle p_1, q_1 \rangle, \langle p_2, q_2 \rangle) = w_1(p_1, p_2) \otimes [w_{01}(q_1, q_2) \oplus \bigoplus_{\Sigma} w_{11}(q_1, q_2)].$$

295 Iterate the following for all  $p_1 \in P$  and  $q_1, q_2 \in Q$ : for all  $p_2 \in P$  and  $q_3 \in Q$ ,

$$296 \quad w'_1(\langle p_1, q_1 \rangle, \langle p_2, q_3 \rangle) \oplus = \bigoplus_{\Sigma} w_{10}(q_1, q_2) \otimes w'_1(\langle p_1, q_2 \rangle, \langle p_2, q_3 \rangle)$$

proof correctness 297 and  $\text{out}'(p_1, q_1) \oplus = \bigoplus_{\Sigma} w_{10}(q_1, q_2) \otimes \text{out}'(p_1, q_2)$  ◀

298 The construction time and size for  $B_{T,A}$  are  $O(\|T\|^3 \cdot \|A\|^2)$ , where the sizes  $\|T\|$  and  $\|A\|$   
are their number of states.

revise with nb of tr.  
and states

300 ► **Corollary 10.** *Given a swT  $T$  over  $\Sigma, \Delta, \mathbb{S}$  commutative, bounded and complete, and  $\bar{\Phi}$   
301 effective, and  $s \in \Sigma^+$ , there exists an effectively constructible swA  $B_{T,s}$  over  $\Delta, \mathbb{S}$  and  $\bar{\Phi}$ ,  
302 such that for all  $t \in \Delta^*$ ,  $B_{T,s}(t) = T(s, t)$ .*

## 4 SW Visibly Pushdown Automata

304 The model presented in this section generalizes Symbolic VPA [6] from Boolean semirings to  
305 arbitrary semiring weight domains. It will compute on nested words over infinite alphabets,  
306 associating to every such word a weight value. Nested words are able to describe structures  
307 of labeled trees, and in the context of parsing, they will be useful to represent AST.

308 Let  $\Omega$  be a countable alphabet that we assume partitioned into three subsets  $\Omega_i, \Omega_c, \Omega_r$ ,  
whose elements are respectively called *internal*, *call* and *return* symbols. Let  $\langle \mathbb{S}, \oplus, \emptyset, \otimes, \mathbf{1} \rangle$

Là je crois qu'il  
faudrait expliquer  
ces Omega, je com-  
mence à fatiguer et  
je suis un peu largué  
par toutes ces défini-  
tions. J'intuie qu'il  
s'agit des symboles,  
parenthèses ouv-  
rantes et fermantes?  
Pourquoi il faut un  
alphabet pour les  
parenthèses?



be a commutative and complete semiring and let  $\bar{\Phi} = \langle \Phi_i, \Phi_c, \Phi_r, \Phi_{ci}, \Phi_{cc}, \Phi_{cr} \rangle$  be a label theory over  $\mathbb{S}$  where  $\Phi_i, \Phi_c, \Phi_r$  and  $\Phi_{cx}$  (with  $x \in \{i, c, r\}$ ) stand respectively for  $\Phi_{\Omega_i}, \Phi_{\Omega_c}, \Phi_{\Omega_r}$  and  $\Phi_{\Omega_c, \Omega_x}$ .

► **Definition 11.** A Symbolic Weighted Visibly Pushdown Automata (*sw-VPA*) over  $\Omega = \Omega_i \uplus \Omega_c \uplus \Omega_r, \mathbb{S}$  and  $\bar{\Phi}$  is a tuple  $A = \langle Q, P, \text{in}, \bar{w}, \text{out} \rangle$ , where  $Q$  is a finite set of states,  $P$  is a finite set of stack symbols,  $\text{in} : Q \rightarrow \mathbb{S}$  (respectively  $\text{out} : Q \rightarrow \mathbb{S}$ ) are functions defining the weight for entering (respectively leaving) a state, and  $\bar{w}$  is a sextuplet composed of the transition functions :  $w_i : Q \times P \times Q \rightarrow \Phi_{ci}, w_i^e : Q \times Q \rightarrow \Phi_i, w_c : Q \times P \times Q \times P \rightarrow \Phi_{cc}, w_c^e : Q \times P \times Q \rightarrow \Phi_c, w_r : Q \times P \times Q \rightarrow \Phi_{cr}, w_r^e : Q \times Q \rightarrow \Phi_r$ .

Est-ce que tout le monde sait ce qu'est un pushdown automata? Je suppose que c'est lié à la pile.

Similarly as in Section 3, we extend the above transition functions as follows for all  $q, q' \in Q, p \in P, a \in \Omega_i, c \in \Omega_c, r \in \Omega_r$ , overloading their names:

$$\begin{array}{lll}
 w_i : Q \times \Omega_c \times P \times \Omega_i \times Q \rightarrow \mathbb{S} & w_i(q, c, p, a, q') = \eta_{ci}(c, a) & \text{where } \eta_{ci} = w_i(q, p, q'), \\
 w_i^e : Q \times \Omega_i \times Q \rightarrow \mathbb{S} & w_i^e(q, a, q') = \phi_i(a) & \text{where } \phi_i = w_i^e(q, q'), \\
 w_c : Q \times \Omega_c \times P \times \Omega_c \times P \times Q \rightarrow \mathbb{S} & w_c(q, c, p, c', p', q') = \eta_{cc}(c, c') & \text{where } \eta_{cc} = w_c(q, p, p', q'), \\
 w_c^e : Q \times \Omega_c \times P \times Q \rightarrow \mathbb{S} & w_c^e(q, c, p, q') = \phi_c(c) & \text{where } \phi_c = w_c^e(q, p, q'), \\
 w_r : Q \times \Omega_c \times P \times \Omega_r \times Q \rightarrow \mathbb{S} & w_r(q, c, p, r, q') = \eta_{cr}(c, r) & \text{where } \eta_{cr} = w_r(q, p, q'), \\
 w_r^e : Q \times \Omega_r \times Q \rightarrow \mathbb{S} & w_r^e(q, r, q') = \phi_r(r) & \text{where } \phi_r = w_r^e(q, q').
 \end{array}$$

The intuition is the following for the above transitions.  $w_i^e, w_c^e$ , and  $w_r^e$  describe the cases where the stack is empty.  $w_i$  and  $w_i^e$  both read an input internal symbol  $a$  and change state from  $q$  to  $q'$ , without changing the stack. Moreover,  $w_i$  reads a pair made of  $c \in \Omega_c$  and  $p \in P$  on the top of the stack ( $c$  is compared to  $a$  by the weight function  $\eta_{ci} \in \Phi_{ci}$ ).  $w_c$  and  $w_c^e$  read the input call symbol  $c'$ , push it to the stack along with  $p'$ , and change state from  $q$  to  $q'$ . Moreover,  $w_c$  reads  $c$  and  $p$  at the top of the stack ( $c$  is compared to  $c'$ ).  $w_r$  and  $w_r^e$  read the input return symbol  $r$ , and change state from  $q$  to  $q'$ . Moreover,  $w_r$  reads and pop from stack a pair made of  $c$  and  $p$ , ( $c$  is compared to  $r$ ).

moved this to the beginning

Formally, the transitions of the automaton  $A$  are defined in term of an intermediate function  $\text{weight}_A$ , like in Section 3. A configuration, denoted by  $q[\gamma]$ , is here composed of a state  $q \in Q$  and a stack content  $\gamma \in \Gamma^*$ , where  $\Gamma = \Omega_c \times P$ . Hence,  $\text{weight}_A$  is a function from  $[Q \times \Gamma^*] \times \Omega^* \times [Q \times \Gamma^*]$  into  $\mathbb{S}$ . The empty stack is denoted by  $\perp$ , and the upmost symbol is the last pushed content. The following functions illustrate each of the possible cases, being : reading  $a \in \Omega_i$ , or  $c \in \Omega_c$ , or  $r \in \Omega_r$  for each possible state of the stack (empty or not), to add to  $u \in \Omega^*$ .

intro to func

introduced the 6 cases

notation  $cp$  for  $\langle c, p \rangle$  ?

$$\begin{aligned}
 & \text{weight}_A(q[\perp], \varepsilon, q'[\perp]) = \mathbb{1} \text{ if } q = q' \text{ and } 0 \text{ otherwise} \tag{5} \\
 & \text{weight}_A\left(q\left[\begin{array}{c} \langle c, p \rangle \\ \gamma \end{array}\right], a, u, q'[\gamma']\right) = \bigoplus_{q'' \in Q} w_i(q, c, p, a, q'') \otimes \text{weight}_A(q''\left[\begin{array}{c} \langle c, p \rangle \\ \gamma \end{array}\right], u, q'[\gamma']) \\
 & \text{weight}_A(q[\perp], a, u, q'[\gamma']) = \bigoplus_{q'' \in Q} w_i^e(q, a, q'') \otimes \text{weight}_A(q''[\perp], u, q'[\gamma']) \\
 & \text{weight}_A\left(q\left[\begin{array}{c} \langle c, p \rangle \\ \gamma \end{array}\right], c', u, q'[\gamma']\right) = \bigoplus_{\substack{q'' \in Q \\ p' \in P}} w_c(q, c, p, c', p', q'') \otimes \text{weight}_A\left(q''\left[\begin{array}{c} \langle c', p' \rangle \\ \langle c, p \rangle \\ \gamma \end{array}\right], u, q'[\gamma']\right) \\
 & \text{weight}_A(q[\perp], c, u, q'[\gamma']) = \bigoplus_{\substack{q'' \in Q \\ p \in P}} w_c^e(q, c, p, q'') \otimes \text{weight}_A(q''[\langle c, p \rangle], u, q'[\gamma'])
 \end{aligned}$$

## XX:10 Symbolic Weighted Language Models and Parsing over Infinite Alphabets

$$\text{weight}_A\left(q \begin{bmatrix} \langle c, p \rangle \\ \gamma \end{bmatrix}, ru, q'[\gamma']\right) = \bigoplus_{q'' \in Q} w_r(q, c, p, r, q'') \otimes \text{weight}_A(q''[\gamma], u, q'[\gamma'])$$

$$\text{weight}_A(q[\perp], ru, q'[\gamma']) = \bigoplus_{q'' \in Q} w_r^e(q, r, q'') \otimes \text{weight}_A(q''[\perp], u, q'[\gamma'])$$

c p to <c, p>

The weight associated by  $A$  to  $s \in \Omega^*$  is defined according to empty stack semantics:

$$A(s) = \bigoplus_{q, q' \in Q} \text{in}(q) \otimes \text{weight}_A(q[\perp], s, q'[\perp]) \otimes \text{out}(q'). \quad (6)$$

todo example VPA

► **Example 12.** structured words with timed symbols... intro language of music notation? (markup = time division, leaves = events etc)

Every swA  $A = \langle Q, \text{in}, w_1, \text{out} \rangle$ , over  $\Sigma, \mathbb{S}$  and  $\bar{\Phi}$  is a particular case of sw-VPA  $\langle Q, \emptyset, \text{in}, \bar{w}, \text{out} \rangle$  over  $\Omega, \mathbb{S}$  and  $\bar{\Phi}$  with  $\Omega_i = \Sigma$  and  $\Omega_c = \Omega_r = \emptyset$ , and computing with an always empty stack:  $w_i^e = w_1$  and all the other functions of  $\bar{w}$  are the constant  $\emptyset$ .

Like VPA and symbolic VPA, the class of sw-VPA is closed under the binary operators of the underlying semiring.

► **Proposition 13.** Let  $A_1$  and  $A_2$  be two sw-VPA over the same  $\Omega, \mathbb{S}$  and  $\bar{\Phi}$ . There exists two effectively constructible sw-VPA  $A_1 \oplus A_2$  and  $A_1 \otimes A_2$ , such that for all  $s \in \Omega^*$ ,  $(A_1 \oplus A_2)(s) = A_1(s) \oplus A_2(s)$  and  $(A_1 \otimes A_2)(s) = A_1(s) \otimes A_2(s)$ .

**Proof.** The construction is essentially the same as in the case of the Boolean semiring [6]. ◀

total?

Let us assume that the semiring  $\mathbb{S}$  is commutative, bounded, and complete, and that  $\bar{\Phi}$  is an effective label theory. We propose a Dijkstra algorithm computing, for a sw-VPA  $A$  over  $\Omega, \mathbb{S}$  and  $\bar{\Phi}$ , the minimal weight for a word in  $\Omega^*$ . We distinguish two cases : when the stack is empty, and when it is not. In the case of an empty stack, let  $b_\perp : Q \times Q \rightarrow \mathbb{S}$  be such that :

introduced 2 cases for b

$$b_\perp(q, q') = \bigoplus_{s \in \Omega^*} \text{weight}_A(q[\perp], s, q'[\perp]). \quad (7)$$

Since  $\mathbb{S}$  is complete, the infinite sum in (7) is well defined, and, providing that  $\mathbb{S}$  is total, it is the minimum in  $\Omega^*$ , wrt  $\leq_\oplus$ , of the function  $s \mapsto \text{weight}_A(q[\perp], s, q'[\perp])$ . The term  $q[\perp], s, q'[\perp]$  of this sum is the central expression in the definition (6) of  $A(s_0)$ , for the minimum  $s_0$  of the function  $\text{weight}_A$ .

so ?

$b_\top$  : mot bien par-  
enthésé c/r

If the stack is not empty, let  $\top$  be a fresh stack symbol which does not belong to  $\Gamma$ , and let  $b_\top : Q \times P \times Q \rightarrow \Phi_c$  be such that, for every two states  $q, q' \in Q$  and stack symbol  $p \in P$ :

$$b_\top(q, p, q') : c \mapsto \bigoplus_{s \in \Omega^*} \text{weight}_A\left(q \begin{bmatrix} \langle c, p \rangle \\ \top \end{bmatrix}, s, q' \begin{bmatrix} \langle c, p \rangle \\ \top \end{bmatrix}\right) \quad (8)$$

Intuitively, the function defined in (8) associates to  $c \in \Omega_c$  the minimum weight of a computation of  $A$  starting in state  $q$  with a stack  $\langle c, p \rangle \cdot \gamma \in \Gamma^+$  and ending in state  $q'$  with the same stack, such that the computation can not pop the pair made of  $c$  and  $p$  at the top of this stack, but may only read these symbols. Moreover,  $A$  may push another pair  $\langle c', p' \rangle$  on the top of  $\langle c, p \rangle \cdot \gamma$ , following the third case of in the definition (5) of  $\text{weight}_A$ , and may pop  $\langle c', p' \rangle$  later, following the fifth case of (5) (return symbol).

Algorithm 1 constructs iteratively markings  $d_\perp : Q \times Q \rightarrow \mathbb{S}$  and  $d_\top : Q \times P \times Q \rightarrow \Phi_c$  that converges eventually to  $b_\top$  and  $b_\perp$ .

■ **Algorithm 1** Best search for sw-VPA

---

**initially** let  $\mathcal{Q} = (Q \times Q) \cup (Q \times P \times Q)$ , and let  $d_{\perp}(q_1, q_2) = d_{\top}(q_1, p, q_2) = \mathbb{1}$  if  $q_1 = q_2$  and  $d_{\perp}(q_1, q_2) = d_{\top}(q_1, p, q_2) = 0$  otherwise

**while**  $\mathcal{Q} \neq \emptyset$  **do**

**extract**  $\langle q_1, q_2 \rangle$  or  $\langle q_1, p, q_2 \rangle$  from  $\mathcal{Q}$  such that  $d_{\perp}(q_1, q_2)$ , resp.  $\bigoplus_{c \in \Omega_c} d_{\top}(q_1, p, q_2)(c)$ , is minimal in  $\mathbb{S}$  wrt  $\leq_{\oplus}$

**update**  $d_{\perp}$  with  $\langle q_1, q_2 \rangle$  or  $d_{\top}$  with  $\langle q_1, p, q_2 \rangle$  (Figure 3).

---

For all  $q_0, q_3 \in Q$ ,

$$\begin{aligned}
 d_{\top}(q_1, p, q_3) &\oplus= d_{\top}(q_1, p, q_2) \otimes \bigoplus_{\Omega_i} w_i(q_2, p, q_3) \\
 d_{\perp}(q_1, p, q_3) &\oplus= d_{\perp}(q_1, q_2) \otimes \bigoplus_{\Omega_i} w_i^e(q_2, q_3) \\
 d_{\top}(q_0, p, q_3) &\oplus= \bigoplus_{\Omega_c}^2 \left[ (w_c(q_0, p, p', q_1) \otimes_2 d_{\top}(q_1, p', q_2)) \otimes_2 \bigoplus_{\Omega_r} w_r(q_2, p', q_3) \right] \\
 d_{\perp}(q_0, q_3) &\oplus= \bigoplus_{\Omega_c} (w_c^e(q_0, p, q_1) \otimes d_{\top}(q_1, p, q_2) \otimes \bigoplus_{\Omega_r} w_r(q_2, p, q_3)) \\
 d_{\perp}(q_1, q_3) &\oplus= d_{\perp}(q_1, q_2) \otimes \bigoplus_{\Omega_r} w_r^e(q_2, q_3) \\
 d_{\top}(q_1, p, q_3) &\oplus= d_{\top}(q_1, p, q_2) \otimes d_{\top}(q_2, p, q_3), \text{ if } \langle q_2, \top, q_3 \rangle \notin P \\
 d_{\perp}(q_1, q_3) &\oplus= d_{\perp}(q_1, q_2) \otimes d_{\perp}(q_2, q_3), \text{ if } \langle q_2, \perp, q_3 \rangle \notin P
 \end{aligned}$$

■ **Figure 3** Update  $d_{\perp}$  with  $\langle q_1, q_2 \rangle$  or  $d_{\top}$  with  $\langle q_1, p, q_2 \rangle$ .

The infinite sums in the updates of  $d$  in Algorithm 1, Figure 3 are well defined since  $\mathbb{S}$  is complete. \*\* effectively computable by hypothesis that the label theory is effective\*\*

The algorithm performs  $2 \cdot |Q|^2$  iterations until  $P$  is empty, and each iteration has a time complexity  $O(|Q|^2 \cdot |P|)$ . That gives a time complexity  $O(|Q|^4 \cdot |P|)$ . It can be reduced by implementing  $P$  as a priority queue, prioritized by the value returned by  $d$ .

The correctness of Algorithm 1 is ensured by the invariant expressed in the following lemma.

► **Lemma 14.** For all  $\langle q_1, q_2 \rangle \notin \mathcal{Q}$ ,  $d_{\perp}(q_1, q_2) = b_{\perp}(q_1, q_2)/$

The proof is by contradiction, assuming a counter-example minimal in the length of the witness word.

► **Lemma 15.** For all  $\langle q_1, p, q_2 \rangle \notin \mathcal{Q}$ ,  $d_{\top}(q_1, p, q_2) = b_{\top}(q_1, p, q_2)$ ,

For computing the minimal weight of a computation of  $A$ , we use the fact that, at the termination of Algorithm 1,  $\bigoplus_{s \in \Omega^*} A(s) = \bigoplus_{q, q' \in Q} \text{in}(q) \otimes d_{\perp}(q, q') \otimes \text{out}(q')$ .

In order to obtain effectively a witness (word of  $\Omega^*$  with a computation of  $A$  of minimal weight), we require the additional property of convexity of weight functions.

► **Proposition 16.** For a sw-VPA  $A$  over  $\Omega$ ,  $\mathbb{S}$  commutative, bounded, total and complete, and  $\bar{\Phi}$  effective, one can construct in PTIME a word  $t \in \Omega^*$  such that  $A(t)$  is minimal wrt the natural ordering for  $\mathbb{S}$ .

explication Fig. 3  
suivant cas de (5)

complete \*\*

detail with nb tr.  
and states

## 5 Symbolic Weighted Parsing

Let us now apply the models and results of the previous sections to the problem of parsing over infinite alphabet. Let  $\Sigma$  be a countable input alphabet, and  $\Omega = \Omega_i \uplus \Omega_c \uplus \Omega_r$  be a countable output alphabet. Let  $\langle \mathbb{S}, \oplus, \mathbb{0}, \otimes, \mathbb{1} \rangle$  be a commutative, bounded, and complete semiring and let  $\bar{\Phi}$  be an effective label theory over  $\mathbb{S}$ , containing  $\Phi_\Sigma$ ,  $\Phi_{\Sigma, \Omega_i}$ , as well as  $\Phi_i$ ,  $\Phi_c$ ,  $\Phi_r$ ,  $\Phi_{cr}$  (following the notations of Section 4). We assume given the following input:

- a  $\text{swT}$   $T$  over  $\Sigma$ ,  $\Omega_i$ ,  $\mathbb{S}$ , and  $\bar{\Phi}$ , defining a measure  $T : \Sigma^* \times \Omega_i^* \rightarrow \mathbb{S}$ ,
- a  $\text{sw-VPA}$   $A$  over  $\Omega$ ,  $\mathbb{S}$ , and  $\bar{\Phi}$ , defining a measure  $A : \Omega^* \rightarrow \mathbb{S}$ ,
- an input word  $s \in \Sigma^*$ .

For all  $s \in \Sigma^*$  and  $t \in \Omega^*$ , let  $d(s, t) = T(s, t|_{\Omega_i})$ , where  $t|_{\Omega_i} \in \Omega_i^*$  is the projection of  $t$  onto  $\Omega_i$ , obtained from  $t$  by removing all symbols in  $\Omega \setminus \Omega_i$ . *Symbolic weighted parsing* is the problem, given the above input, to find  $t \in \Omega^*$  minimizing  $d(s, t) \otimes A(t)$  wrt  $\leq_\oplus$ , i.e. s.t.

$$d(s, t) \otimes A(t) = \bigoplus_{t' \in \mathcal{T}(\Omega)} d(s, t') \otimes A(t') \quad (9)$$

Following the terminology of [21], *sw-parsing* is the problem of computing the distance (9) between the input  $s$  and the output weighted language of  $A$ , and returning a witness  $t$ . Every labeled tree  $t$  can be linearized into a nested word  $\text{lin}(t) \in \Omega^*$ , assuming e.g. that  $\Omega_i$  contain the symbols labelling the leaves (symbols of rank 0) and  $\Omega_c$  and  $\Omega_r$  contain respectively one left and right parenthesis  $\langle_b$  and  $\rangle_b$  for each symbol  $b$  labelling inner nodes (symbols of rank  $> 0$ ). With this representation, the projection  $\text{lin}(t)|_{\Omega_i}$  is then the sequence of leaves of  $t$ , enumerated in a *dfs*-traversal. We show in Appendix A how to convert a (sw) tree automaton  $A$  into a  $\text{sw-VPA}$  computing  $A(\text{lin}(t))$  for every tree  $t$ . That also holds, for the set of ASTs of a weighted CF-grammar. Therefore, *sw-parsing* generalizes the problem of searching, the best derivation of a weighted CF-grammar that yields a given input, sometimes referred as *weighted parsing*, see e.g. [13] and [23] for a more general weighted parsing framework. The latter indeed corresponds to the particular case where the alphabet is finite,  $T$  computes identity and  $A$  is obtained from the weighted CF grammar.

► **Proposition 17.** *The problem of Symbolic Weighted parsing can be solved in PTIME in the size of the input  $\text{swT}$   $T$ ,  $\text{sw-VPA}$   $A$  and input word  $s$ , and the computation time of the functions of the label theory.*

**Proof.** (sketch) We follow a *Bar-Hillel* construction, also called parsing by intersection. We first extend the  $\text{swT}$   $T$  over  $\Sigma$ ,  $\Omega_i$ ,  $\mathbb{S}$ , and  $\bar{\Phi}$ , into a  $\text{swT}$   $T'$  over  $\Sigma$  and  $\Omega$  (and the same semiring and label theory), such that for all  $s \in \Sigma^*$ , and  $u \in \Omega^*$ ,  $T'(s, u) = T(s, u|_{\Omega_i})$ . The transducer  $T'$  simply skips every symbol  $b \in \Omega \setminus \Omega_i$ , by the addition to the transition of  $T$ , of new transitions of the form  $w_{01}(q, \varepsilon, b, q')$ . Then, given an input word  $s \in \Sigma^*$ , using Corolary 10, we compute the  $\text{swA}$   $B_{T', s}$ , such that for all  $t \in \Omega^*$ ,  $B_{T', s}(t) = d(s, t)$ . Next, we compute the  $\text{sw-VPA}$   $B_{T', s} \otimes A$ , using Proposition 13. It remains to compute a best nested-word  $w \in \Omega^*$  using the best-search procedure of Proposition 16. ◀

## Conclusion

We have introduced weighted language models (SW transducers and visibly pushdown automata) computing over infinite alphabets, and applied them to the problem of parsing with infinitely many possible input symbols (typically timed events). This approach extends conventional parsing and weighted parsing by computing a derivation tree modulo a generic

total?

Ah oui, ça aurait pu être dit avant.

2 lines Application to Automated Music Transcription: implementation  $\neq$  but same principle, on-the-fly automata construction during best search, for efficiency.

distance between words, defined by a SW transducer given in input. This enables to consider finer word relationships than strict equality, opening possibilities of quantitative analysis via this method.

Ongoing and future work include

- The study of other theoretical properties of SW models, such as the extension of the best search algorithm from 1-best to  $n$ -best [17], and to  $k$ -closed semirings [20] (instead of *bounded*, which corresponds to 0-closed).
- ...there is room to improve the complexity bounds for the algorithms ... modular approach with oracles ...
- present here an offline algorithm for best search, semi-online implementation for AMT (bar-by-bar approach) with an on-the-fly automata construction.

TODO future work

## References

- 1 R. Alur and P. Madhusudan. Adding nesting structure to words. *Journal of the ACM (JACM)*, 56(3):1–43, 2009.
- 2 M. Bojańczyk, C. David, A. Muscholl, T. Schwentick, and L. Segoufin. Two-variable logic on data words. *ACM Transactions on Computational Logic (TOCL)*, 12(4):1–26, 2011.
- 3 P. Bouyer, A. Petit, and D. Thérien. An algebraic approach to data languages and timed languages. *Information and Computation*, 182(2):137–162, 2003.
- 4 M. Caralp, P.-A. Reynier, and J.-M. Talbot. Visibly pushdown automata with multiplicities: finiteness and  $k$ -boundedness. In *International Conference on Developments in Language Theory*, pages 226–238. Springer, 2012.
- 5 H. Comon, M. Dauchet, R. Gilleron, F. Jacquemard, C. Löding, D. Lugiez, S. Tison, and M. Tommasi. *Tree Automata Techniques and Applications*. <http://tata.gforge.inria.fr>, 2007.
- 6 L. D’Antoni and R. Alur. Symbolic visibly pushdown automata. In *International Conference on Computer Aided Verification*, pages 209–225. Springer, 2014.
- 7 L. D’Antoni and M. Veanes. The power of symbolic automata and transducers. In *International Conference on Computer Aided Verification*, pages 47–67. Springer, 2017.
- 8 L. D’Antoni and M. Veanes. Automata modulo theories. *Communications of the ACM*, 64(5):86–95, 2021.
- 9 E. W. Dijkstra. A note on two problems in connexion with graphs. *Numerische Mathematik*, 1(1):269–271, 1959.
- 10 M. Droste and W. Kuich. Semirings and formal power series. In *Handbook of Weighted Automata*, pages 3–28. Springer, 2009.
- 11 M. Droste, W. Kuich, and H. Vogler. *Handbook of weighted automata*. Springer Science & Business Media, 2009.
- 12 F. Foscarin, F. Jacquemard, P. Rigaux, and M. Sakai. A Parse-based Framework for Coupled Rhythm Quantization and Score Structuring. In *Mathematics and Computation in Music (MCM)*, volume 11502 of *Lecture Notes in Artificial Intelligence*, Madrid, Spain, 2019. Springer.
- 13 J. Goodman. Semiring parsing. *Computational Linguistics*, 25(4):573–606, 1999.
- 14 E. Gould. *Behind Bars: The Definitive Guide to Music Notation*. Faber Music, 2011.
- 15 D. Grune and C. J. Jacobs. *Parsing Techniques*. Number 2nd edition in Monographs in Computer Science. Springer, 2008.
- 16 L. Huang. Advanced dynamic programming in semiring and hypergraph frameworks. In *In COLING*, 2008.
- 17 L. Huang and D. Chiang. Better  $k$ -best parsing. In *Proceedings of the Ninth International Workshop on Parsing Technology*, Parsing ’05, pages 53–64, Stroudsburg, PA, USA, 2005. Association for Computational Linguistics.
- 18 M. Kaminski and N. Francez. Finite-memory automata. *Theor. Comput. Sci.*, 134:329–363, November 1994.

- 490 **19** S. Lombardy and J. Sakarovitch. The removal of weighted  $\varepsilon$ -transitions. In *International*  
491 *Conference on Implementation and Application of Automata*, pages 345–352. Springer, 2012.
- 492 **20** M. Mohri. Semiring frameworks and algorithms for shortest-distance problems. *Journal of*  
493 *Automata, Languages and Combinatorics*, 7(3):321–350, 2002.
- 494 **21** M. Mohri. Edit-distance of weighted automata: General definitions and algorithms. *Interna-*  
495 *tional Journal of Foundations of Computer Science*, 14(06):957–982, 2003.
- 496 **22** M. Mohri. Edit-distance of weighted automata: General definitions and algorithms. *Interna-*  
497 *tional Journal of Foundations of Computer Science*, 14(06):957–982, 2003.
- 498 **23** R. Mörbitz and H. Vogler. Weighted parsing for grammar-based language models. In *Proceedings*  
499 *of the 14th International Conference on Finite-State Methods and Natural Language Processing*,  
500 pages 46–55, Dresden, Germany, Sept. 2019. Association for Computational Linguistics.
- 501 **24** M.-J. Nederhof. Weighted deductive parsing and Knuth’s algorithm. *Computational Linguistics*,  
502 29(1):135–143, 2003.
- 503 **25** F. Neven, T. Schwentick, and V. Vianu. Finite state machines for strings over infinite alphabets.  
504 *ACM Trans. Comput. Logic*, 5(3):403–435, July 2004.
- 505 **26** L. Segoufin. Automata and logics for words and trees over an infinite alphabet. In *Computer*  
506 *Science Logic*, volume 4207 of *LNCS*. Springer, 2006.
- 507 **27** M. Y. Vardi. Linear-time model checking: automata theory in practice. In *International*  
508 *Conference on Implementation and Application of Automata*, pages 5–10. Springer, 2007.



## A Nested-Words and Parse-Trees

The hierarchical structure of nested-words, defined with the *call* and *return* markup symbols suggest a correspondence with trees. The lifting of this correspondence to languages, of tree automata and VPA, has been discussed in [1], and [4] for the weighted case. In this section, we describe a correspondence between the symbolic-weighted extensions of tree automata and VPA.

Let  $\Omega$  be a countable ranked alphabet, such that every symbol  $a \in \Omega$  has a rank  $\text{rk}(a) \in [0..M]$  where  $M$  is a fixed natural number. We denote by  $\Omega_k$  the subset of all symbols  $a$  of  $\Omega$  with  $\text{rk}(a) = k$ , where  $0 \leq k \leq M$ , and  $\Omega_{>0} = \Omega \setminus \Omega_0$ . The free  $\Omega$ -algebra of finite, ordered,  $\Omega$ -labeled trees is denoted by  $\mathcal{T}(\Omega)$ . It is the smallest set such that  $\Omega_0 \subset \mathcal{T}(\Omega)$  and for all  $1 \leq k \leq M$ , all  $a \in \Omega_k$ , and all  $t_1, \dots, t_k \in \mathcal{T}(\Omega)$ ,  $a(t_1, \dots, t_k) \in \mathcal{T}(\Omega)$ . Let us assume a commutative semiring  $\mathbb{S}$  and a label theory  $\bar{\Phi}$  over  $\mathbb{S}$  containing one set  $\Phi_{\Omega_k}$  for each  $k \in [0..M]$ .

► **Definition 18.** A symbolic-weighted tree automaton (*swTA*) over  $\Omega$ ,  $\mathbb{S}$ , and  $\bar{\Phi}$  is a triplet  $A = \langle Q, \text{in}, \bar{w} \rangle$  where  $Q$  is a finite set of states,  $\text{in} : Q \rightarrow \Phi_{\Omega}$  is the starting weight function, and  $\bar{w}$  is a tuple of transition functions containing, for each  $k \in [0..M]$ , the functions  $w_k : Q \times Q^k \rightarrow \Phi_{\Omega_{>0}, \Omega_k}$  and  $w_k^e : Q \times Q^k \rightarrow \Phi_{\Omega_k}$ .

We define a transition function  $w : Q \times (\Omega_{>0} \cup \{\varepsilon\}) \times \Omega \times \bigcup_{k=0}^M Q^k \rightarrow \mathbb{S}$  by:

$$\begin{aligned} w(q_0, a, b, q_1 \dots q_k) &= \eta(a, b) & \text{where } \eta &= w_k(q_0, q_1 \dots q_k) \\ w(q_0, \varepsilon, b, q_1 \dots q_k) &= \phi(b) & \text{where } \phi &= w_k^e(q_0, q_1 \dots q_k). \end{aligned}$$

where  $q_1 \dots q_k$  is  $\varepsilon$  if  $k = 0$ . The first case deals with a strict subtree, with a parent node labeled by  $a$ , and the second case is for a root tree.

Every *swTA* defines a mapping from trees of  $\mathcal{T}(\Omega)$  into  $\mathbb{S}$ , based on the following intermediate function  $\text{weight}_A : Q \times (\Omega \cup \{\varepsilon\}) \times \mathcal{T}(\Omega) \rightarrow \mathbb{S}$

$$\text{weight}_A(q_0, a, t) = \bigoplus_{q_1 \dots q_k \in Q^k} w(q_0, a, b, q_1 \dots q_k) \otimes \bigotimes_{i=1}^k \text{weight}_A(q_i, b, t_i) \quad (10)$$

where  $q_0 \in Q$ ,  $a \in \Omega_{>0} \cup \{\varepsilon\}$  and  $t = b(t_1, \dots, t_k) \in \mathcal{T}(\Omega)$ ,  $0 \leq k \leq M$ .

Finally, the weight associated by  $A$  to  $t \in \mathcal{T}(\Omega)$  is

$$A(t) = \bigoplus_{q \in Q} \text{in}(q) \otimes \text{weight}_A(q, \varepsilon, t) \quad (11)$$

Intuitively,  $w(q_0, a, b, q_1 \dots q_k)$  can be seen as the weight of a production rule  $q_0 \rightarrow b(q_1, \dots, q_k)$  of a regular tree grammar [5], that replaces the non-terminal symbol  $q_0$  by  $b(q_1, \dots, q_k)$ , provided that the parent of  $q_0$  is labeled by  $a$  (or  $q_0$  is the root node if  $a = \varepsilon$ ). The above production rule can also be seen as a rule of a weighted CF grammar, of the form  $[a, b] q_0 := q_1 \dots q_k$  if  $k > 0$ , and  $[a] q_0 := b$  if  $k = 0$ . In the first case,  $b$  is a label of the rule, and in the second case, it is a terminal symbol. And in both cases,  $a$  is a constraint on the label of rule applied on the parent node in the derivation tree. This features of observing the parent's label are useful in the case of infinite alphabet, where it is not possible to memorize a label with the states. The weight of a labeled derivation tree  $t$  of the weighted CF grammar associated to  $A$  as above, is  $\text{weight}_A(q, t)$ , when  $q$  is the start non-terminal. We shall now establish a correspondence between such derivation tree  $t$  and some word describing a linearization of  $t$ , in a way that  $\text{weight}_A(q, t)$  can be computed by a *sw-VPA*.

## XX:16 Symbolic Weighted Language Models and Parsing over Infinite Alphabets

Let  $\hat{\Omega}$  be the countable (unranked) alphabet obtained from  $\Omega$  by:  $\hat{\Omega} = \Omega_i \uplus \Omega_c \uplus \Omega_r$ , with  $\Omega_i = \Omega_0$ ,  $\Omega_c = \{ \langle a \mid a \in \Omega_{>0} \rangle \}$ ,  $\Omega_r = \{ a \mid a \in \Omega_{>0} \}$ .

We associate to  $\hat{\Omega}$  a label theory  $\hat{\Phi}$  like in Section 4, and we define a linearization of trees of  $\mathcal{T}(\Omega)$  into words of  $\hat{\Omega}^*$  as follows:

$$\begin{aligned} \text{lin}(a) &= a \text{ for all } a \in \Omega_0, \\ \text{lin}(b(t_1, \dots, t_k)) &= \langle b \text{ lin}(t_1) \dots \text{lin}(t_k) b \rangle \text{ when } b \in \Omega_k \text{ for } 1 \leq k \leq M. \end{aligned}$$

► **Proposition 19.** *For all swTA  $A$  over  $\Omega$ ,  $\mathbb{S}$  commutative, and  $\bar{\Phi}$ , there exists an effectively constructible sw-VPA  $A'$  over  $\hat{\Omega}$ ,  $\mathbb{S}$  and  $\hat{\Phi}$  such that for all  $t \in \mathcal{T}(\Omega)$ ,  $A'(\text{lin}(t)) = A(t)$ .*

**Proof.** Let  $A = \langle Q, \text{in}, \bar{w} \rangle$  where  $\bar{w}$  is presented as above by a function We build  $A' = \langle Q', P', \text{in}', \bar{w}', \text{out}' \rangle$ , where  $Q' = \bigcup_{k=0}^M Q^k$  is the set of sequences of state symbols of  $A$ , of length at most  $M$ , including the empty sequence denoted by  $\varepsilon$ , and where  $P' = Q'$  and  $\bar{w}$  is defined by:





















$$\begin{aligned} w_i(q_0 \bar{u}, \langle c, \bar{p}, a, \bar{u} \rangle) &= w(q_0, c, a, \varepsilon) && \text{for all } c \in \Omega_{>0}, a \in \Omega_0 \\ w_i^e(q_0 \bar{u}, a, \bar{u}) &= w(q_0, \varepsilon, a, \varepsilon) && \text{for all } a \in \Omega_0 \\ w_c(q_0 \bar{u}, \langle c, \bar{p}, \langle d, \bar{u}, \bar{q} \rangle \rangle) &= w(q_0, c, d, \bar{q}) && \text{for all } c, d \in \Omega_{>0} \\ w_c^e(q_0 \bar{u}, \langle c, \bar{u}, \bar{q} \rangle) &= w(q_0, \varepsilon, c, \bar{q}) && \text{for all } c \in \Omega_{>0} \\ w_r(\varepsilon, \langle c, \bar{p}, c \rangle, \bar{p}) &= \mathbb{1} && \text{for all } c \in \Omega_{>0} \\ w_r^e(\bar{u}, c, \bar{q}) &= \mathbb{0} && \text{for all } c \in \Omega_{>0} \end{aligned}$$

All cases not matched by one of the above equations have a weight  $\mathbb{0}$ , for instance  $w_r(\bar{u}, \langle c, \bar{p}, d \rangle, \bar{q}) = \mathbb{0}$  if  $c \neq d$  or  $\bar{u} \neq \varepsilon$  or  $\bar{q} \neq \bar{p}$ . ◀

563 **Todo list**

564	■ I think that we can make the case for a larger set of situations: given a linear music	
565	notation input, for instance elements in an XML file, we want to structure the	
566	input according to a hierarchical rhythmic space. I can elaborate...	1
567	■ register: skip refs and details, add Mikolaj recent	1
568	■ This sentence (symbols as variables) is not immediatly clear to me. Maybe a short	
569	example or intuition?	2
570	■ The weight is a label on edges in the derivation tree, right? Not sure I understand	
571	the sentence	2
572	■ You mean the distance between $s$ and $t$ ? "The latter value" is a bit ambiguous	2
573	■ chap. intersection in [15]	3
574	■ The notation $A_{T,s}$ has not been introduced so far. It is not clear why $T$ is a	
575	parameter there	3
576	■ OK, à quelques détails (pour moi), tout ça est très bien expliqué	3
577	■ expressiveness: VPA have restricted equality test. comparable to pebble automata?	
578	→ conclusion	3
579	■ The results are established for a general class of semirings. They can be instantiated	
580	for concrete cases	3
581	■ There is sometimes a confusion in the text between the struture and the domain $S$ .	
582	Not essential	3
583	■ is total necessary?	3
584	■ Here the difference between $S$ as a structure and as a domain is blurred.	4
585	■ $j \in \mathbb{N}$ : $j$ is en element of $\mathbb{N}$ , not the same $s \in \mathbb{N}$	4
586	■ results of this paper: for semirings commutative, bounded, total and complete	4
587	■ OK, donc c'est là que les fonctions d'étiquettes prennent en argument l'input de la	
588	règle. Je ne sais pas dans quelle mesure il faut donner un peu d'explications pour	
589	faciliter la compréhension du formalisme.	4
590	■ partial application is needed?	5
591	■ notion of diagram of functions akin BDD for transitions in practice	5
592	■ mv appendix?	5
593	■ Je trouve qu'il y a beaucoup de notions à retenir (complete, effective) et ça devient	
594	difficile pour un lecteur non spécialiste. Est-ce que tout est nécessaire (je ne sais	
595	plus qui m'avait dit: un concept en plus, un point en moins.	5
596	■ $\exists$ oracle returning ... in worst time complexity $T$ .	5
597	■ I missed sth: what is this $\varepsilon$ ? Intuitively clear but not defined?	6
598	■ added $u$ and $v$ def	6
599	■ OK tout ça se lit bien :-)	6
600	■ Je crois qu'il faudrait numéroter les exemples indépendamment des définitions. Cet	
601	exemple est le premier qui donne des détails sur l'application visée. Il arrive	
602	peut-être un peu tard et est long. On pourrait introduire la motivation dans	
603	l'intro, et développer des petits exemples au fur et à mesure.	6
604	■ unique → similar	6
605	■ similar → single	6
606	■ modif.	7
607	■ changed end	7
608	■ reformulated this sentence	7
609	■ ccl to the ex	7
610	■ proof correctness	8

## XX:18 Symbolic Weighted Language Models and Parsing over Infinite Alphabets

611		revise with nb of tr. and states . . . . .	8
612		Là je crois qu'il faudrait expliquer ces Omega, je commence à fatiguer et je suis un peu	
613		largué par toutes ces définitions. J'intuite qu'il s'agit des symboles, parenthèses	
614		ouvrantes et fermantes? Pourquoi il faut un alphabet pour les parenthèses? . . .	8
615		Est-ce que tout le monde sait ce qu'est un pushdown automata? Je suppose que	
616		c'est lié à la pile. . . . .	8
617		moved this to the beginning . . . . .	9
618		intro to func . . . . .	9
619		introduced the 6 cases . . . . .	9
620		notation $cp$ for $\langle c, p \rangle$ ? . . . . .	9
621		c p to $\langle c, p \rangle$ . . . . .	9
622		todo example VPA . . . . .	10
623		total? . . . . .	10
624		introduced 2 cases for b . . . . .	10
625		so ? . . . . .	10
626		$b_{\top}$ : mot bien parenthésé $c/r$ . . . . .	10
627		explication Fig. 3 suivant cas de (5) . . . . .	10
628		complete ** . . . . .	10
629		detail with nb tr. and states . . . . .	10
630		total? . . . . .	11
631		Ah oui, ça aurait pu être dit avant. . . . .	12
632		2 lines Application to Automated Music Transcription: implementation $\neq$ but same	
633		principle, on-the-fly automata construction during best search, for efficiency. . . .	12
634		TODO future work . . . . .	12