

Graph Denoising for Molecular Imaging

Cédric Mendelin <cedric.mendelin@stud.unibas.ch>

Department of Mathematics and Computer Science, University of Basel

29.06.2022

Outline

- 1 Molecular Imaging Methods
- 2 Graphs & Manifolds
- 3 GAT-Denoiser
- 4 Results on LoDoPaB-CT dataset
- 5 Summary & Future Work
- 6 Questions

Outline

- 1 Molecular Imaging Methods
- 2 Graphs & Manifolds
- 3 GAT-Denoiser
- 4 Results on LoDoPaB-CT dataset
- 5 Summary & Future Work
- 6 Questions

Cryo-Electron Microscopy (Cryo-EM)

- Major motivation for Thesis
- Enables observation of molecules in near atomic resolution

Cryo-Electron Microscopy (Cryo-EM)

- Major motivation for Thesis
- Enables observation of molecules in near atomic resolution
- Observation through an electron microscope
- Frozen state required
 - Frozen molecules are fragile, electron microscope needs to work with low power
 - During freezing, molecules rotate randomly
- Observations can be reconstructed to 3D model

Cryo-Electron Microscopy (Cryo-EM)

- › Major motivation for Thesis
- › Enables observation of molecules in near atomic resolution
- › Observation through an electron microscope
- › Frozen state required
 - › Frozen molecules are fragile, electron microscope needs to work with low power
 - › During freezing, molecules rotate randomly
- › Observations can be reconstructed to 3D model

Only single particle cryo-EM is considered.

Cryo-Electron Microscopy (Cryo-EM) - Illustration




Figure: Cryo-EM overview

Cryo-Electron Microscopy (Cryo-EM) - Illustration




Figure: Cryo-EM overview

Cryo-Electron Microscopy (Cryo-EM) - Challenges

- High-noise level
- Unknown rotation during freezing
- (Structural variety of observations)



(a) Clean micrograph



(b) Noisy micrograph


Computed Tomography (CT)

Computed Tomography (CT)


- › Related to cryo-EM
- › Can be seen as a simpler version in 2D
- › Good to start with towards a cryo-EM algorithm

Computed Tomography (CT)

- Related to cryo-EM
- Can be seen as a simpler version in 2D
- Good to start with towards a cryo-EM algorithm



(a) Biological sample



(b) Clean observation
(sinogram)

Shared Observation Model

Shared Observation Model

Observation

$$y = p + \eta \quad (1)$$

- > y : noisy observation
- > p : noiseless observation
- > η : noise, assumed $\eta_i \sim \mathcal{N}(0, \sigma^2)$

Shared Observation Model

Observation

$$\begin{aligned} y &= p + \eta \\ y_i[j] &= p_i[j] + \eta_i[j] \quad \text{with } 1 \leq i \leq N, 1 \leq j \leq M \end{aligned} \tag{1}$$

- > y : noisy observation
- > p : noiseless observation
- > η : noise, assumed $\eta_i \sim \mathcal{N}(0, \sigma^2)$
- > N : number of observations
- > M : observation dimension


Shared Observation Model

Observation


$$\begin{aligned} y &= p + \eta \\ y_i[j] &= p_i[j] + \eta_i[j] \quad \text{with } 1 \leq i \leq N, 1 \leq j \leq M \\ y_i &= A(x, \theta_i) + \eta_i \end{aligned} \tag{1}$$

- > y : noisy observation
- > p : noiseless observation
- > η : noise, assumed $\eta_i \sim \mathcal{N}(0, \sigma^2)$
- > x : biological sample
- > N : number of observations
- > M : observation dimension
- > $A : x \mapsto A(x; \theta_i) \in \mathbb{R}^M$: a non-linear operator
- > θ_i : observation angle

Observation - Illustration



(a) CT Observation - sinogram



(b) Cryo-EM Observation - micrographs

Reconstruction

Reconstruction

Reconstruction

$$Recon : \mathbb{R}^{M \times N} \rightarrow \mathbb{R}^{M \times M} \quad y \mapsto Recon(y; \theta) \quad (2)$$

Signal-to-noise-ratio (SNR)

Signal-to-noise-ratio (SNR)

- SNR is a measure, which compares the power of an input signal to the power of the undesired noise
- Typically given in decibel (dB)
- $\text{SNR} \leq 0$ dB indicated more noise than signal.

Signal-to-noise-ratio (SNR)

- SNR is a measure, which compares the power of an input signal to the power of the undesired noise
- Typically given in decibel (dB)
- $\text{SNR} \leq 0$ dB indicated more noise than signal.

SNR_y is used to define the level of noise in an observation.

Signal-to-noise-ration (SNR)

- SNR is a measure, which compares the power of an input signal to the power of the undesired noise
- Typically given in decibel (dB)
- $\text{SNR} \leq 0$ dB indicated more noise than signal.

SNR_y is used to define the level of noise in an observation.

SNR is used as a metric for the quality of reconstructions.

Reconstruction - Computed Tomography

- Filter Backprojection (FBP)
 - Can be considered historical approach
 - Enables reconstruction for moderate noise


Reconstruction - Computed Tomography

- Filter Backprojection (FBP)
 - Can be considered historical approach
 - Enables reconstruction for moderate noise



(a) Reconstruction clean:

$$\text{Recon}(p, \theta) \approx x$$



(b) Reconstruction noisy

with SNR_y 0 dB:


$$\text{Recon}(y, \theta) \not\approx x$$

Reconstruction - Computed Tomography

- Filter Backprojection (FBP)
 - Can be considered historical approach
 - Enables reconstruction for moderate noise
- Neural Network Approaches
 - Today state-of-the art
 - Using result of FBP and further denoise
 - U-Net Ronneberger, Fischer, and Brox 2015



(a) Reconstruction clean:
 $Recon(p, \theta) \approx x$



(b) Reconstruction noisy
with SNR_y 0 dB:
 $Recon(y, \theta) \not\approx x$

Problem and Goal

Problem and Goal

Problem

p not observable directly only y is observable.

Problem and Goal

Problem

p not observable directly only y is observable.

Goal

$$\text{denoiser} : y_i = (p_i + \eta) \mapsto p_i^* \approx p_i$$

$$\text{Recon}(\text{denoiser}(y; \theta)) \approx x$$

Outline

- 1 Molecular Imaging Methods
- 2 Graphs & Manifolds
- 3 GAT-Denoiser
- 4 Results on LoDoPaB-CT dataset
- 5 Summary & Future Work
- 6 Questions

Graph - Definitions

Graph - Definitions

Graph Definition

A graph is defined as $G = \langle V, E \rangle$, where V is a set of nodes and E is a set of edges.

Graph - Definitions

Graph Definition

A graph is defined as $G = \langle V, E \rangle$, where V is a set of nodes and E is a set of edges.




Figure: Sample graph

Graph - Definitions

Graph Definition

A graph is defined as $G = \langle V, E \rangle$, where V is a set of nodes and E is a set of edges.

Nodes

$(n_1, n_2, \dots) \in \mathbb{R}^F$, with F as node feature dimensions.

Edges

Edges are defined as a set of tuples (i, j) , where i and j determine the index of the nodes.




Figure: Sample graph

Graph - Definitions - Adjacency Matrix

Graph - Definitions - Adjacency Matrix

Adjacency Matrix

The binary adjacency matrix of graph $G = \langle V, E \rangle$ is defined as:

$$A_{ij} = \begin{cases} 1 & \text{if } (i, j) \in E \\ 0, & \text{otherwise} \end{cases} \quad (3)$$

Graph - Definitions - Adjacency Matrix

Adjacency Matrix

The binary adjacency matrix of graph $G = \langle V, E \rangle$ is defined as:

$$A_{ij} = \begin{cases} 1 & \text{if } (i, j) \in E \\ 0, & \text{otherwise} \end{cases} \quad (3)$$




Figure: Sample graph

Graph - Definitions - Degree

Graph - Definitions - Degree

Degree of a node

The *degree* of a node is defined as the number of (incoming) edges.

Graph - Definitions - Degree

Degree of a node

The *degree* of a node is defined as the number of (incoming) edges.




Figure: Sample graph

Graph - Definitions - Degree

Degree of a node

The *degree* of a node is defined as the number of (incoming) edges.

Degree Matrix of Graph G

Is a diagonal matrix with degree of nodes as entries.

$$D_{ii} = \text{degree}(n_i)$$




Figure: Sample graph

Graph for Molecular Imaging Observation

How to construct a graph for molecular imaging?

Graph for Molecular Imaging Observation

How to construct a graph for molecular imaging?

➤ Nodes: Single observation y_i




Figure: Sample graph for cryo-EM observation

Graph for Molecular Imaging Observation

How to construct a graph for molecular imaging?

- Nodes: Single observation y_i
- Edges: Use k-nearest neighbours (k-NN) to construct a graph




Figure: Sample graph for cryo-EM observation

Graph for Molecular Imaging Observation

How to construct a graph for molecular imaging?

- Nodes: Single observation y_i
- Edges: Use k-nearest neighbours (k-NN) to construct a graph
 - Define similarity measure for nodes: ℓ_2 -norm




Figure: Sample graph for cryo-EM observation

Graph for Molecular Imaging Observation

How to construct a graph for molecular imaging?

- > Nodes: Single observation y_i
- > Edges: Use k -nearest neighbours (k-NN) to construct a graph
 - > Define similarity measure for nodes: ℓ_2 -norm




Figure: Sample graph for cryo-EM observation

Graph for Molecular Imaging Observation

How to construct a graph for molecular imaging?

- Nodes: Single observation y_i
- Edges: Use k-nearest neighbours (k-NN) to construct a graph
 - Define similarity measure for nodes: ℓ_2 -norm




Figure: Sample graph for cryo-EM observation

Graph for Molecular Imaging Observation

How to construct a graph for molecular imaging?

- Nodes: Single observation y_i
- Edges: Use k-nearest neighbours (k-NN) to construct a graph
 - Define similarity measure for nodes: ℓ_2 -norm




Figure: Sample graph for cryo-EM observation

Graph for Molecular Imaging Observation - Noise

What happens with our noisy observations?

Graph for Molecular Imaging Observation - Noise

What happens with our noisy observations?

- > With noise, graph will capture neighborhood inaccurately.




Figure: Sample graph for noisy cryo-EM observation

Graph Laplacian (GL)

What can we use this graph for?

Graph Laplacian (GL)

What can we use this graph for?

- Coifman, Shkolnisky, et al. 2008 used it to approximate angles for CT:

Graph Laplacian (GL)


What can we use this graph for?

- Coifman, Shkolnisky, et al. 2008 used it to approximate angles for CT:

Low-dimensional Embedding


1. Construct a k-NN graph from observations.
2. Calculate $L = D - A$
3. Get 2nd and 3rd smallest eigenvalue with corresponding eigenvectors.

Low-dimensional Embedding for Computed Tomography




(a) Clean CT observation

Low-dimensional Embedding for Computed Tomography




(a) Clean CT observation




(b) Building k-NN graph with $k = 2$


Low-dimensional Embedding for Computed Tomography



(a) Clean CT observation



(b) Building k-NN graph with $k = 2$



(c) 2_{nd} and 3_{rd} smallest eigenvectors of $L = D - A$

Computed Tomography with unknown angles

Computed Tomography with unknown angles

- › GL - Embedding estimates observation angles for noiseless case.
- › Can be applied during reconstruction.

Computed Tomography with unknown angles

- › GL - Embedding estimates observation angles for noiseless case.
- › Can be applied during reconstruction.




(a) Reconstruction known angles

Computed Tomography with unknown angles

- GL - Embedding estimates observation angles for noiseless case.
- Can be applied during reconstruction.




(a) Reconstruction known angles




(b) GL-Embedding from $k=2$

Computed Tomography with unknown angles


- › GL - Embedding estimates observation angles for noiseless case.
- › Can be applied during reconstruction.



(a) Reconstruction known angles



(b) GL-Embedding from $k = 2$



(c) Reconstruction unknown angles


Computed Tomography with unknown angles

- GL - Embedding estimates observation angles for noiseless case.
- Can be applied during reconstruction.


What happens in the noisy case?

Computed Tomography with unknown angles


- › GL - Embedding estimates observation angles for noiseless case.
- › Can be applied during reconstruction.



(a) Reconstruction known angles SNR_y : 10 dB




(b) GL-Embedding from $k = 6$ and SNR_y : 10 dB




(c) Reconstruction unknown angles SNR_y : 10 dB

Computed Tomography with unknown angles


- › GL - Embedding estimates observation angles for noiseless case.
- › Can be applied during reconstruction.



(a) Reconstruction known angles $SNR_y : 0$ dB



(b) GL-Embedding from $k = 6$ and $SNR_y : 0$ dB



(c) Reconstruction unknown angles $SNR_y : 0$ dB

Observation Denoising

The fewer noise is available in the observation, the better reconstruction is possible.

Observation Denoising

The fewer noise is available in the observation, the better reconstruction is possible.

- › Use existing denoising algorithms
 - › Block-matching and 3D filtering (BM3D) Dabov et al. 2007
 - › Non-local means Buades, Coll, and Morel 2005
 - › No graph as data structure
 - › But, both exploit neighborhood during averaging

Observation Denoising

The fewer noise is available in the observation, the better reconstruction is possible.

- Use existing denoising algorithms
 - Block-matching and 3D filtering (BM3D) Dabov et al. 2007
 - Non-local means Buades, Coll, and Morel 2005
 - No graph as data structure
 - But, both exploit neighborhood during averaging
- Show potential for graph as a data structure

Observation Denoising

The fewer noise is available in the observation, the better reconstruction is possible.

- Use existing denoising algorithms
 - Block-matching and 3D filtering (BM3D) Dabov et al. 2007
 - Non-local means Buades, Coll, and Morel 2005
 - No graph as data structure
 - But, both exploit neighborhood during averaging
- Show potential for graph as a data structure

Exploit graph as a data structure and the GL-embedding.

Outline

- 1 Molecular Imaging Methods
- 2 Graphs & Manifolds
- 3 GAT-Denoiser
- 4 Results on LoDoPaB-CT dataset
- 5 Summary & Future Work
- 6 Questions


GAT-Denoiser

- › GAT-Denoiser is a graph neural network (GNN) to denoise observations.
- › Consists of three components:
 - › Convolution
 - › Graph Attention Network (GAT) Veličković et al. 2017
 - › End-to-End Learning

GAT-Denoiser

- › GAT-Denoiser is a graph neural network (GNN) to denoise observations.
- › Consists of three components:
 - › Convolution
 - › Graph Attention Network (GAT) Veličković et al. 2017
 - › End-to-End Learning


GAT-Denoiser Pipeline



GAT-Denoiser

- > GAT-Denoiser is a graph neural network (GNN) to denoise observations.
- > Consists of three components:
 - > Convolution
 - > Graph Attention Network (GAT) Veličković et al. 2017
 - > End-to-End Learning


GAT-Denoiser Pipeline



GAT-Denoiser

- > GAT-Denoiser is a graph neural network (GNN) to denoise observations.
- > Consists of three components:
 - > Convolution
 - > Graph Attention Network (GAT) Veličković et al. 2017
 - > End-to-End Learning

GAT-Denoiser Pipeline



GAT-Denoiser Components

GAT-Denoiser Components

- Convolution
 - Denoise single observation

GAT-Denoiser Components


- Convolution
 - Denoise single observation
- Graph Attention Network (GAT) Veličković et al. 2017
 - Denoise neighboring observation

GAT-Denoiser Components

- › Convolution
 - › Denoise single observation
- › Graph Attention Network (GAT) Veličković et al. 2017
 - › Denoise neighboring observation
- › End-to-End Learning
 - › Optimize for reconstruction quality
 - › $\mathcal{L} = \|x - \text{Recon}(\text{GAT-Denoiser}(A(x, \theta) + \eta))\|_2^2$
 - › $\mathcal{L}_{\text{ sino}} = \|p - \text{GAT-Denoiser}(A(x, \theta) + \eta)\|_2^2$


Graph Attention Network - GAT

- Extends Graph Convolution Network with attention (weights)
- Compute new node features
- Averages graph over neighborhood
- Multi-head available, motivated by Vaswani et al. 2017



Graph Attention Network - GAT

- › Extends Graph Convolution Network with attention (weights)
- › Compute new node features
- › Averages graph over neighborhood
- › Multi-head available, motivated by Vaswani et al. 2017
- › σ : activation function (Exponential Linear Unit)
- › W : learnable weight matrix
- › α : normalized attention coefficients



$$h'_1 = \sigma \left(\sum_{i=1}^5 \alpha_i W h_{1,i} \right)$$

Input Graph

Input Graph


- › Exploit information from GL
- › Low-dimensional embedding estimates angles
- › Dominant information in data can be considered observation angles.

Input Graph

- Exploit information from GL
- Low-dimensional embedding estimates angles
- Dominant information in data can be considered observation angles.
- Construct graph from observation angles


Input Graph

- › Exploit information from GL
- › Low-dimensional embedding estimates angles
- › Dominant information in data can be considered observation angles.
- › Construct graph from observation angles



Input Graph


- Exploit information from GL
- Low-dimensional embedding estimates angles
- Dominant information in data can be considered observation angles.
- Construct graph from observation angles



Observation angles θ are assumed to be equally spaced.

Input Graph

- Exploit information from GL
- Low-dimensional embedding estimates angles
- Dominant information in data can be considered observation angles.
- Construct graph from observation angles



Observation angles θ are assumed to be equally spaced.

GAT-Denoiser Implementation for Computed Tomography

- › Use U-Net for reconstruction
- › During Trainig, U-Net might be trained jointly

Outline

- 1 Molecular Imaging Methods
- 2 Graphs & Manifolds
- 3 GAT-Denoiser
- 4 Results on LoDoPaB-CT dataset**
- 5 Summary & Future Work
- 6 Questions

LoDoPaB-CT dataset

- Dataset for low-dose Computed tomography
- 35'820 train samples
- 3'553 test samples
- BM3D as baseline algorithm
- Resolution 64×64






Figure: Some samples from the LoDoPaB-CT dataset.

Evaluation

> Small Scale Experiments

- > 1024 train samples
- > 100 test samples
- > 200 epochs

> Large Scale Experiments

- > Complete LoDoPaB-CT dataset
- > 20 - 40 epochs

Evaluation

> Small Scale Experiments

- > 1024 train samples
- > 100 test samples
- > 200 epochs
- > **Goal: Find most promising architecture**

> Large Scale Experiments

- > Complete LoDoPaB-CT dataset
- > 20 - 40 epochs
- > **Goal: Find best model**


Training

- › U-Net used for reconstruction
 - › Pre-trained with complete dataset and SNR_y in $[-10, 0]$ for 200 epochs
- › Mini-batch gradient descent with batch size 64
- › Adam optimizer
- › Joint U-Net training possible


Small Scale Results

- › Learning fails with random graph
- › Learning succeeds with defined input graph
- › Components contribute to success of GAT-Denoiser
- › Best model with joint U-Net training


Large Scale Results




Large Scale Results - Visual - SNR_y 0 dB




(a) Clean sample




(b) FBP



(c) BM3D




(d) $GAT+U-$
 $Net(10/30)$




(e)
 $Conv+GAT+U-$
 $Net(20/20)$

Figure: Large Scale Experiment: Visual results for SNR_y 0 dB.


Large Scale Results - Visual - SNR_y 0 dB




(a) Clean sample




(b) FBP



(c) BM3D



(d) $GAT+U-$
 $Net(10/30)$




(e)
 $Conv+GAT+U-$
 $Net(20/20)$


Figure: Large Scale Experiment: Visual results for SNR_y 0 dB.

GAT-Denoiser improves BM3D by 27.6%.


Large Scale Results - Visual - SNR_y -10 dB



(a) Clean sample



(b) FBP



(c) BM3D




(d) $GAT+U-$
 $Net(10/30)$




(e)
 $Conv+GAT+U-$
 $Net(20/20)$

Figure: Large Scale Experiment: Visual results for SNR_y -10 dB.


Large Scale Results - Visual - SNR_y -10 dB



(a) Clean sample



(b) FBP



(c) BM3D



(d) *GAT+U-Net(10/30)*




(e) *Conv+GAT+U-Net(20/20)*


Figure: Large Scale Experiment: Visual results for SNR_y -10 dB.

GAT-Denoiser improves BM3D by 126.0%.


Large Scale Results - Visual - SNR_y -15 dB



(a) Clean sample




(b) FBP



(c) BM3D




(d) $GAT+U-$
 $Net(10/30)$




(e)
 $Conv+GAT+U-$
 $Net(20/20)$

Figure: Large Scale Experiment: Visual results for SNR_y -15 dB.


Large Scale Results - Visual - SNR_y -15 dB



(a) Clean sample




(b) FBP



(c) BM3D



(d) $GAT+U-$
 $Net(10/30)$



(e)
 $Conv+GAT+U-$
 $Net(20/20)$

Figure: Large Scale Experiment: Visual results for SNR_y -15 dB.

GAT-Denoiser improves BM3D by 379.9%.

Outline

- 1 Molecular Imaging Methods
- 2 Graphs & Manifolds
- 3 GAT-Denoiser
- 4 Results on LoDoPaB-CT dataset
- 5 Summary & Future Work
- 6 Questions

Summary

- › GAT-Denoiser enables denoising of observations
 - › Convolution
 - › GAT
 - › End-To-End Learning
 - › Joint U-Net training boost performance

Summary

- GAT-Denoiser enables denoising of observations
 - Convolution
 - GAT
 - End-To-End Learning
 - Joint U-Net training boost performance
- Evaluated on LoDoPaB-CT dataset
 - Outperformed baseline BM3D by up to 379.9 %

Future Work

- › Improve current GAT-Denoiser
- › Derive GAT-Denoiser for 3D
- › Make it work for unknown angles

Future Work

- › Improve current GAT-Denoiser
- › Derive GAT-Denoiser for 3D
- › Make it work for unknown angles
- › Cryo-EM
 - › Known angles
 - › Unknown angles
 - › Work with structural variety in observations

Outline

- 1 Molecular Imaging Methods
- 2 Graphs & Manifolds
- 3 GAT-Denoiser
- 4 Results on LoDoPaB-CT dataset
- 5 Summary & Future Work
- 6 Questions

Questions



References

- Basu, Samit and Yoram Bresler (2000). “Feasibility of tomography with unknown view angles”. In: **IEEE Transactions on Image Processing** 9.6, pp. 1107–1122. DOI: 10.1109/83.846252.
- Bendory, Tamir, Alberto Bartesaghi, and Amit Singer (2020). “Single-particle cryo-electron microscopy: Mathematical theory, computational challenges, and opportunities”. In: **IEEE Signal Processing Magazine** 37.2, pp. 58–76. DOI: 10.1109/MSP.2019.2957822.
- Biewald, Lukas (2020). **Experiment Tracking with Weights and Biases**. Software available from wandb.com. URL: <https://www.wandb.com/>.
- Brenner, David J and Eric J Hall (2007). “Computed tomography—an increasing source of radiation exposure”. In: **New England journal of medicine** 357.22, pp. 2277–2284. DOI: 10.1056/NEJMr072149.
- Buades, Antoni, Bartomeu Coll, and J-M Morel (2005). “A non-local algorithm for image denoising”. In: **2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR’05)**. Vol. 2. IEEE, pp. 60–65. DOI: 10.1109/CVPR.2005.38.
- Cayton, Lawrence (2005). “Algorithms for manifold learning”. In: **Univ. of California at San Diego Tech. Rep** 12.1-17, p. 1.
- Clackdoyle, Rolf and Michel Defrise (2010). “Tomographic reconstruction in the 21st century”. In: **IEEE Signal Processing Magazine** 27.6, pp. 82–95. DOI: 10.1109/SPPM.2010.5622212.