

# EXPLORATION DE DONNÉES POUR L'OPTIMISATION DE TRAJECTOIRES AÉRIENNES

Cédric Rommel

Directeurs de thèse: Frédéric Bonnans, Pierre Martinon  
Encadrant Safety Line: Baptiste Gregorutti

Soutenance de thèse, 26 octobre 2018



# CONTEXT

# MOTIVATION




FIGURE: World air traffic - source: Flight Radar

# MOTIVATION




FIGURE: World air traffic - source: Flight Radar

- 20 000 airplanes — 80 000 flights per day,

# MOTIVATION





FIGURE: World air traffic - source: Flight Radar

- 20 000 airplanes — 80 000 flights per day,
- Should double until 2033,


# MOTIVATION

- Most polluting means of transportation,




# MOTIVATION

- Most polluting means of transportation,
- Responsible for 3% of  $CO_2$  emissions,




# MOTIVATION

- Most polluting means of transportation,
- Responsible for 3% of  $CO_2$  emissions,



# MOTIVATION

- Most polluting means of transportation,
- Responsible for 3% of  $CO_2$  emissions,
- Fuel  $\simeq$  30% of an airline operational cost,



# MOTIVATION

How to tackle this problem ?

# MOTIVATION

How to tackle this problem ?

- New hardware ?

# MOTIVATION

How to tackle this problem ?

- New hardware ?
- Better use of existing fleet,

# MOTIVATION


How to tackle this problem ?

- New hardware ?
- Better use of existing fleet,
- Climb is most consuming flight phase...

# MOTIVATION

How to tackle this problem ?


- New hardware ?
- Better use of existing fleet,
- Climb is most consuming flight phase...
- Mostly rectilinear trajectories at full thrust,



# MOTIVATION

How to tackle this problem ?


- New hardware ?
- Better use of existing fleet,
- Climb is most consuming flight phase...
- Mostly rectilinear trajectories at full thrust,
- Thousands of variables recorded every second,



# MOTIVATION

How to tackle this problem ?

- New hardware ?
- Better use of existing fleet,
- Climb is most consuming flight phase...
- Mostly rectilinear trajectories at full thrust,
- Thousands of variables recorded every second,



# OPTICLIMB




Flight  
Data

**Time**



*Many days before flight...*

# OPTICLIMB




Flight  
Data

**Time**

*Many days before flight...*

# OPTICLIMB




**Time**




*Many days before flight...*


# OPTICLIMB




# OPTICLIMB




# OPTICLIMB




# OPTICLIMB




# OPTICLIMB



# OPTICLIMB




# OPTICLIMB



# TRAJECTORY OPTIMIZATION


# TRAJECTORY OPTIMIZATION



# TRAJECTORY OPTIMIZATION

Dynamics:


$$\dot{x}(t) = g(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t)$$



# TRAJECTORY OPTIMIZATION

Dynamics:

$$\dot{x}(t) = g(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t)$$




Optimization objective:  $C(\mathbf{u}(t), \mathbf{x}(t))$

# TRAJECTORY OPTIMIZATION

Dynamics:

$$\dot{x}(t) = g(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t)$$




Optimization objective:  $C(\mathbf{u}(t), \mathbf{x}(t)) \leftarrow \text{min}$ ,

# TRAJECTORY OPTIMIZATION

Dynamics:

$$\dot{x}(t) = g(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t)$$




Optimization objective:  $C(\mathbf{u}(t), \mathbf{x}(t)) \Leftarrow \text{fuel}, \text{time}$

# TRAJECTORY OPTIMIZATION

Dynamics:

$$\dot{x}(t) = g(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t)$$



Optimization objective:  $C(\mathbf{u}(t), \mathbf{x}(t)) \Leftarrow \text{fuel}, \text{location}$


Flight constraints:

{

# TRAJECTORY OPTIMIZATION

Dynamics:

$$\dot{x}(t) = g(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t)$$



Optimization objective:  $C(\mathbf{u}(t), \mathbf{x}(t)) \Leftarrow \text{ℓ}, \text{ traj.}$


Flight constraints:

$$\left\{ \begin{array}{l} \Phi(\mathbf{x}(0), \mathbf{x}(t_f)) \in K_\Phi \\ \end{array} \right. \quad \text{Initial and final conditions}$$

# TRAJECTORY OPTIMIZATION

Dynamics:

$$\dot{x}(t) = g(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t)$$



Optimization objective:  $C(\mathbf{u}(t), \mathbf{x}(t)) \Leftarrow \text{ℓ}, \text{ traj.}$


Flight constraints:

$$\left\{ \begin{array}{l} \Phi(\mathbf{x}(0), \mathbf{x}(t_f)) \in K_\Phi \\ \mathbf{u}(t) \in U_{ad}, \quad \mathbf{x}(t) \in X_{ad}, \end{array} \right. \quad \begin{array}{l} \text{Initial and final conditions} \\ \text{Flight domain} \end{array}$$

# TRAJECTORY OPTIMIZATION

Dynamics:

$$\dot{x}(t) = g(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t)$$



Optimization objective:  $C(\mathbf{u}(t), \mathbf{x}(t)) \Leftarrow \text{flight path}$

Flight constraints:

$$\begin{cases} \Phi(\mathbf{x}(0), \mathbf{x}(t_f)) \in K_\Phi \\ \mathbf{u}(t) \in U_{ad}, \quad \mathbf{x}(t) \in X_{ad}, \\ c(\mathbf{u}(t), \mathbf{x}(t)) \leq 0, \end{cases}$$

Initial and final conditions

Flight domain

Operational path constraints

# TRAJECTORY OPTIMIZATION

## OPTIMAL CONTROL PROBLEM

$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt, \\ \text{s.t. } & \left\{ \begin{array}{ll} \dot{\mathbf{x}}(t) = g(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t), & \text{a.e. } t \in [0, t_f], \\ \Phi(\mathbf{x}(0), \mathbf{x}(t_f)) \in K_\Phi, & \\ \mathbf{u}(t) \in U_{ad}, \quad \mathbf{x}(t) \in X_{ad}, & \text{a.e. } t \in [0, t_f], \\ c(\mathbf{u}(t), \mathbf{x}(t)) \leq 0, & \text{a.e. } t \in [0, t_f]. \end{array} \right. \end{aligned} \quad (\text{OCP})$$

# TRAJECTORY OPTIMIZATION

## OPTIMAL CONTROL PROBLEM

$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt, \\ \text{s.t. } & \left\{ \begin{array}{ll} \dot{\mathbf{x}}(t) = \mathbf{g}(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t), & \text{a.e. } t \in [0, t_f], \\ \Phi(\mathbf{x}(0), \mathbf{x}(t_f)) \in K_\Phi, & \\ \mathbf{u}(t) \in U_{ad}, \quad \mathbf{x}(t) \in X_{ad}, & \text{a.e. } t \in [0, t_f], \\ c(\mathbf{u}(t), \mathbf{x}(t)) \leq 0, & \text{a.e. } t \in [0, t_f]. \end{array} \right. \end{aligned} \quad (\text{OCP})$$

# TRAJECTORY OPTIMIZATION

## OPTIMAL CONTROL PROBLEM

$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt, \\ \text{s.t. } & \left\{ \begin{array}{ll} \dot{\mathbf{x}}(t) = \mathbf{g}(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t), & \text{a.e. } t \in [0, t_f], \\ \Phi(\mathbf{x}(0), \mathbf{x}(t_f)) \in K_\Phi, & \\ \mathbf{u}(t) \in U_{ad}, \quad \mathbf{x}(t) \in X_{ad}, & \text{a.e. } t \in [0, t_f], \\ c(\mathbf{u}(t), \mathbf{x}(t)) \leq 0, & \text{a.e. } t \in [0, t_f]. \end{array} \right. \end{aligned} \quad (\text{OCP})$$

## SYSTEM IDENTIFICATION



Black box

# TRAJECTORY OPTIMIZATION


## OPTIMAL CONTROL PROBLEM

$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt, \\ \text{s.t. } & \left\{ \begin{array}{ll} \dot{\mathbf{x}}(t) = \mathbf{g}(\mathbf{u}(t), \mathbf{x}(t)) + \varepsilon(t), & \text{a.e. } t \in [0, t_f], \\ \Phi(\mathbf{x}(0), \mathbf{x}(t_f)) \in K_\Phi, & \\ \mathbf{u}(t) \in U_{ad}, \quad \mathbf{x}(t) \in X_{ad}, & \text{a.e. } t \in [0, t_f], \\ c(\mathbf{u}(t), \mathbf{x}(t)) \leq 0, & \text{a.e. } t \in [0, t_f]. \end{array} \right. \end{aligned} \quad (\text{OCP})$$

## SYSTEM IDENTIFICATION



Black box



QAR data

# TRAJECTORY OPTIMIZATION


## OPTIMAL CONTROL PROBLEM

$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt, \\ \text{s.t. } & \left\{ \begin{array}{ll} \dot{\mathbf{x}}(t) = \hat{g}(\mathbf{u}(t), \mathbf{x}(t)), & \text{a.e. } t \in [0, t_f], \\ \Phi(\mathbf{x}(0), \mathbf{x}(t_f)) \in K_\Phi, & \\ \mathbf{u}(t) \in U_{ad}, \quad \mathbf{x}(t) \in X_{ad}, & \text{a.e. } t \in [0, t_f], \\ c(\mathbf{u}(t), \mathbf{x}(t)) \leq 0, & \text{a.e. } t \in [0, t_f]. \end{array} \right. \end{aligned} \quad (\text{A OCP})$$

## SYSTEM IDENTIFICATION




Black box




QAR data

## SYSTEM IDENTIFICATION




# SYSTEM IDENTIFICATION




# SYSTEM IDENTIFICATION

# FLIGHT DYNAMICS




# FLIGHT DYNAMICS




$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ \dot{V} = \frac{T \cos \alpha - D - mg \sin \gamma}{m} \\ \dot{\gamma} = \frac{T \sin \alpha + L - mg \cos \gamma}{mV} \\ \dot{m} = -\frac{T}{I_{sp}} \end{array} \right.$$

# FLIGHT DYNAMICS




$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma + \dot{W}_z \\ \dot{V} = \frac{T \cos \alpha - D - mg \sin \gamma - m \dot{W}_{xv}}{m} \\ \dot{\gamma} = \frac{T \sin \alpha + L - mg \cos \gamma - m \dot{W}_{zv}}{mV} \\ \dot{m} = -\frac{T}{I_{sp}} \end{array} \right.$$

# FLIGHT DYNAMICS




$$\begin{cases} \dot{h} = V \sin \gamma + \dot{W}_z \\ \dot{V} = \frac{T \cos \alpha - D - mg \sin \gamma - m \dot{W}_{xv}}{m} \\ \dot{\gamma} = \frac{(T \sin \alpha + L) \cos \mu - mg \cos \gamma - m \dot{W}_{zv}}{mV} \\ \dot{m} = -\frac{T}{I_{sp}} \end{cases}$$

# FLIGHT DYNAMICS



$$\begin{cases} \dot{h} = V \sin \gamma \\ \dot{V} = \frac{T \cos \alpha - D - mg \sin \gamma}{m} \\ \dot{\gamma} = \frac{T \sin \alpha + L - mg \cos \gamma}{mV} \\ \dot{m} = -\frac{T}{I_{sp}} \end{cases}$$


# FLIGHT DYNAMICS



States:  $x = (h, V, \gamma, m)$

$$\begin{cases} \dot{h} = V \sin \gamma \\ \dot{V} = \frac{T \cos \alpha - D - mg \sin \gamma}{m} \\ \dot{\gamma} = \frac{T \sin \alpha + L - mg \cos \gamma}{mV} \\ \dot{m} = -\frac{T}{I_{sp}} \end{cases}$$

# FLIGHT DYNAMICS




States:  $x = (h, V, \gamma, m)$

Controls:  $u = (\alpha, N_1)$

$$\begin{cases} \dot{h} = V \sin \gamma \\ \dot{V} = \frac{T \cos \alpha - D - mg \sin \gamma}{m} \\ \dot{\gamma} = \frac{T \sin \alpha + L - mg \cos \gamma}{mV} \\ \dot{m} = -\frac{T}{I_{sp}} \end{cases}$$

# FLIGHT DYNAMICS




**States:**  $x = (h, V, \gamma, m)$

**Controls:**  $u = (\alpha, N_1)$

**Unknown functions of  $x, u$**

$$\begin{cases} \dot{h} = V \sin \gamma \\ \dot{V} = \frac{T \cos \alpha - D - mg \sin \gamma}{m} \\ \dot{\gamma} = \frac{T \sin \alpha + L - mg \cos \gamma}{mV} \\ \dot{m} = -\frac{T}{I_{sp}} \end{cases}$$

# FLIGHT DYNAMICS



States:  $x = (h, V, \gamma, m)$

Controls:  $u = (\alpha, N_1)$

Unknown functions of  $x, u$

$$\begin{cases} \dot{h} = V \sin \gamma \\ \dot{V} = \frac{T(x, u) \cos \alpha - D(x, u) - mg \sin \gamma}{m} \\ \dot{\gamma} = \frac{T(x, u) \sin \alpha + L(x, u) - mg \cos \gamma}{mV} \\ \dot{m} = -\frac{T(x, u)}{I_{sp}(x, u)} \end{cases}$$

# PHYSICAL MODELS OF NESTED FUNCTIONS

$$\begin{cases} T \text{ function of } (N_1, M, \rho) \\ D \text{ function of } (q, M, \alpha) \\ L \text{ function of } (q, M, \alpha) \\ I_{sp} \text{ function of } (SAT, M, h) \end{cases}$$

# PHYSICAL MODELS OF NESTED FUNCTIONS

$$\begin{cases} T \text{ function of } (N_1, M, \rho) = \varphi_T(\mathbf{x}, \mathbf{u}) \\ D \text{ function of } (q, M, \alpha) = \varphi_D(\mathbf{x}, \mathbf{u}) \\ L \text{ function of } (q, M, \alpha) = \varphi_L(\mathbf{x}, \mathbf{u}) \\ I_{sp} \text{ function of } (SAT, M, h) = \varphi_{I_{sp}}(\mathbf{x}, \mathbf{u}) \end{cases}$$

# PHYSICAL MODELS OF NESTED FUNCTIONS

$$\begin{cases} T = N_1 \times P_T(\rho, M), \\ D = q \times P_D(\alpha, M), \\ L = q \times P_L(\alpha, M), \\ I_{sp} = SAT \times P_{Isp}(h, M), \end{cases}$$

# PHYSICAL MODELS OF NESTED FUNCTIONS

$$\begin{cases} T = X_T \cdot \theta_T, \\ D = X_D \cdot \theta_D, \\ L = X_L \cdot \theta_L, \\ I_{sp} = X_{Isp} \cdot \theta_{Isp}, \end{cases}$$

# PHYSICAL MODELS OF NESTED FUNCTIONS

$$\begin{cases} T = X_T \cdot \theta_T, \\ D = X_D \cdot \theta_D, \\ L = X_L \cdot \theta_L, \\ I_{sp} = X_{Isp} \cdot \theta_{Isp}, \end{cases}$$

$$X_T = N_1(1, \rho, M, \rho^2, \rho M, M^2, \dots)$$

$$X_D = q(1, \alpha, M, \alpha^2, \alpha M, M^2, \dots)$$

$$X_L = q(1, \alpha, M, \alpha^2, \alpha M, M^2, \dots)$$

$$X_{Isp} = SAT(1, h, M, h^2, hM, M^2, \dots)$$

# PHYSICAL MODELS OF NESTED FUNCTIONS

$$\begin{cases} T(\mathbf{x}, \mathbf{u}, \boldsymbol{\theta}_T) = X_T \cdot \boldsymbol{\theta}_T, \\ D(\mathbf{x}, \mathbf{u}, \boldsymbol{\theta}_D) = X_D \cdot \boldsymbol{\theta}_D, \\ L(\mathbf{x}, \mathbf{u}, \boldsymbol{\theta}_L) = X_L \cdot \boldsymbol{\theta}_L, \\ I_{sp}(\mathbf{x}, \mathbf{u}, \boldsymbol{\theta}_{Isp}) = X_{Isp} \cdot \boldsymbol{\theta}_{Isp}, \end{cases}$$

$$X_T = N_1(1, \rho, M, \rho^2, \rho M, M^2, \dots)$$

$$X_D = q(1, \alpha, M, \alpha^2, \alpha M, M^2, \dots)$$

$$X_L = q(1, \alpha, M, \alpha^2, \alpha M, M^2, \dots)$$

$$X_{Isp} = SAT(1, h, M, h^2, hM, M^2, \dots)$$

# STATE-OF-THE-ART

# STATE-OF-THE-ART

- Output-Error Method

$$\{u_f\}_{f \in \mathcal{F}}$$


# STATE-OF-THE-ART

## ■ Output-Error Method




# STATE-OF-THE-ART

- Output-Error Method




# STATE-OF-THE-ART

## ■ Output-Error Method




# STATE-OF-THE-ART

## ■ Output-Error Method



# STATE-OF-THE-ART


- Output-Error Method
- Filter-Error Method



# STATE-OF-THE-ART

- Output-Error Method
- Filter-Error Method


} Not scalable to many trajectories



# STATE-OF-THE-ART

- Output-Error Method
- Filter-Error Method

} Not scalable to many trajectories




- Equation-Error Method

$$\dot{\mathbf{x}}(t) = g(\mathbf{u}(t), \mathbf{x}(t), \boldsymbol{\theta}) + \varepsilon(t), \quad t \in [0, t_f]$$

# STATE-OF-THE-ART

- Output-Error Method
- Filter-Error Method

} Not scalable to many trajectories




- Equation-Error Method

$$\dot{x}_i = g(\mathbf{u}_i, \mathbf{x}_i, \boldsymbol{\theta}) + \varepsilon_i, \quad i = 1, \dots, N$$

# STATE-OF-THE-ART

- Output-Error Method
- Filter-Error Method

} Not scalable to many trajectories




- Equation-Error Method

$$\min_{\theta} \sum_{i=1}^N \ell(\dot{x}_i, g(\mathbf{u}_i, \mathbf{x}_i, \theta))$$

# STATE-OF-THE-ART

- Output-Error Method
- Filter-Error Method

} Not scalable to many trajectories



- Equation-Error Method


Ex: *(Nonlinear) Least-Squares*

$$\min_{\theta} \sum_{i=1}^N \left\| \dot{x}_i - g(\mathbf{u}_i, \mathbf{x}_i, \theta) \right\|_2^2$$

# STATE-OF-THE-ART

- Output-Error Method
- Filter-Error Method

} Not scalable to many trajectories



- Equation-Error Method


Ex: *(Nonlinear) Least-Squares*

$$\min_{\theta} \sum_{i=1}^N \left\| Y(\mathbf{u}_i, \mathbf{x}_i, \dot{\mathbf{x}}_i) - G(\mathbf{u}_i, \mathbf{x}_i, \dot{\mathbf{x}}_i, \theta) \right\|_2^2$$

# STATE-OF-THE-ART

- Output-Error Method
- Filter-Error Method

} Not scalable to many trajectories



- **Equation-Error Method**

Ex: (Nonlinear) Least-Squares

$$\min_{\theta} \sum_{i=1}^N \| Y(\mathbf{u}_i, \mathbf{x}_i, \dot{\mathbf{x}}_i) - G(\mathbf{u}_i, \mathbf{x}_i, \dot{\mathbf{x}}_i, \theta) \|_2^2$$

# LEVERAGING THE DYNAMICS STRUCTURE

$$\begin{cases} \dot{h} = V \sin \gamma \\ \dot{V} = \frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \cos \alpha - D(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_D) - mg \sin \gamma}{m} \\ \dot{\gamma} = \frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \sin \alpha + L(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_L) - mg \cos \gamma}{mV} \\ \dot{m} = -\frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T)}{I_{sp}(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_{Isp})} \end{cases}$$

# LEVERAGING THE DYNAMICS STRUCTURE

$$\begin{cases} \dot{h} = V \sin \gamma \\ \dot{V} = \frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \cos \alpha - D(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_D) - mg \sin \gamma}{m} \\ \dot{\gamma} = \frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \sin \alpha + L(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_L) - mg \cos \gamma}{mV} \\ \dot{m} = -\frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T)}{I_{sp}(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_{Isp})} \end{cases}$$

- Nonlinear in states and controls

# LEVERAGING THE DYNAMICS STRUCTURE

$$\begin{cases} \dot{h} = V \sin \gamma \\ \dot{V} = \frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \cos \alpha - D(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_D) - mg \sin \gamma}{m} \\ \dot{\gamma} = \frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \sin \alpha + L(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_L) - mg \cos \gamma}{mV} \\ \dot{m} = -\frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T)}{I_{sp}(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_{Isp})} \end{cases}$$

- Nonlinear in states and controls
- Nonlinear in parameters

# LEVERAGING THE DYNAMICS STRUCTURE

$$\begin{cases} \dot{h} = V \sin \gamma \\ m\dot{V} = T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \cos \alpha - D(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_D) - mg \sin \gamma \\ mV\dot{\gamma} = T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \sin \alpha + L(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_L) - mg \cos \gamma \\ \dot{m} = -\frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T)}{l_{sp}(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_{lsp})} \end{cases}$$

- Nonlinear in states and controls
- Nonlinear in parameters

# LEVERAGING THE DYNAMICS STRUCTURE

$$\begin{cases} \dot{h} = V \sin \gamma \\ m\dot{V} = T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \cos \alpha - D(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_D) - mg \sin \gamma \\ mV\dot{\gamma} = T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \sin \alpha + L(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_L) - mg \cos \gamma \\ \dot{m} = -\frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T)}{l_{sp}(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_{lsp})} \end{cases}$$

- Nonlinear in states and controls
- Nonlinear in parameters

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m \dot{V} + mg \sin \gamma = T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \cos \alpha - D(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_D) \\ mV \dot{\gamma} + mg \cos \gamma = T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \sin \alpha + L(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_L) \\ \dot{m} = -\frac{T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T)}{I_{sp}(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_{Isp})} \end{array} \right.$$

- Nonlinear in states and controls
- Nonlinear in parameters

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m \dot{V} + mg \sin \gamma = T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \cos \alpha - D(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_D) \\ mV \dot{\gamma} + mg \cos \gamma = T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \sin \alpha + L(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_L) \\ \dot{m} I_{sp}(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_{Isp}) = -T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \end{array} \right.$$

- Nonlinear in states and controls
- Nonlinear in parameters

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m\dot{V} + mg \sin \gamma = T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \cos \alpha - D(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_D) \\ mV\dot{\gamma} + mg \cos \gamma = T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) \sin \alpha + L(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_L) \\ 0 = T(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_T) + \dot{m}l_{sp}(\mathbf{u}, \mathbf{x}, \boldsymbol{\theta}_{lsp}) \end{array} \right.$$

- Nonlinear in states and controls
- Nonlinear in parameters

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m \dot{V} + mg \sin \gamma = (X_T \cdot \theta_T) \cos \alpha - X_D \cdot \theta_D \\ m V \dot{\gamma} + mg \cos \gamma = (X_T \cdot \theta_T) \sin \alpha + X_L \cdot \theta_L \\ 0 = X_T \cdot \theta_T + \dot{m}(X_{Isp} \cdot \theta_{Isp}) \end{array} \right.$$

- Nonlinear in states and controls
- Nonlinear in parameters

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m \dot{V} + mg \sin \gamma = (X_T \cdot \theta_T) \cos \alpha - X_D \cdot \theta_D + \varepsilon_1 \\ m V \dot{\gamma} + mg \cos \gamma = (X_T \cdot \theta_T) \sin \alpha + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + \dot{m}(X_{Isp} \cdot \theta_{Isp}) + \varepsilon_3 \end{array} \right.$$

- Nonlinear in states and controls
- Nonlinear in parameters

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m \dot{V} + mg \sin \gamma = (X_T \cdot \theta_T) \cos \alpha - X_D \cdot \theta_D + \varepsilon_1 \\ m V \dot{\gamma} + mg \cos \gamma = (X_T \cdot \theta_T) \sin \alpha + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + \dot{m}(X_{Isp} \cdot \theta_{Isp}) + \varepsilon_3 \end{array} \right.$$

$$\overbrace{Y(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}})}$$

$$\overbrace{G(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}}, \boldsymbol{\theta})}$$

- Nonlinear in states and controls
- Nonlinear in parameters

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m \dot{V} + mg \sin \gamma = (X_T \cdot \theta_T) \cos \alpha - X_D \cdot \theta_D + \varepsilon_1 \\ m V \dot{\gamma} + mg \cos \gamma = (X_T \cdot \theta_T) \sin \alpha + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + \dot{m}(X_{Isp} \cdot \theta_{Isp}) + \varepsilon_3 \end{array} \right.$$

$$\overbrace{Y(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}})}$$

$$\overbrace{G(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}}, \boldsymbol{\theta})}$$

- Nonlinear in states and controls
- ~~Nonlinear in parameters~~ → Linear in parameters

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m \dot{V} + mg \sin \gamma = (X_T \cdot \theta_T) \cos \alpha - X_D \cdot \theta_D + \varepsilon_1 \\ m V \dot{\gamma} + mg \cos \gamma = (X_T \cdot \theta_T) \sin \alpha + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + \dot{m}(X_{Isp} \cdot \theta_{Isp}) + \varepsilon_3 \end{array} \right.$$

$$\overbrace{Y(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}})}$$

$$\overbrace{G(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}}, \boldsymbol{\theta})}$$

- Nonlinear in states and controls
- ~~Nonlinear in parameters~~ → Linear in parameters
- Structured

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m \dot{V} + mg \sin \gamma = (X_T \cdot \theta_T) \cos \alpha - X_D \cdot \theta_D + \varepsilon_1 \\ m V \dot{\gamma} + mg \cos \gamma = (X_T \cdot \theta_T) \sin \alpha + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + \dot{m}(X_{Isp} \cdot \theta_{Isp}) + \varepsilon_3 \end{array} \right.$$

$$\overbrace{Y(u, x, \dot{x})}^{\text{Nonlinear in states and controls}}$$

$$\overbrace{G(u, x, \dot{x}, \theta)}^{\text{Nonlinear in parameters} \rightarrow \text{Linear in parameters}}$$

- Nonlinear in states and controls
- ~~Nonlinear in parameters~~ → Linear in parameters
- Structured

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m \dot{V} + mg \sin \gamma = (\mathbf{X}_T \cdot \boldsymbol{\theta}_T) \cos \alpha - X_D \cdot \theta_D + \varepsilon_1 \\ m V \dot{\gamma} + mg \cos \gamma = (\mathbf{X}_T \cdot \boldsymbol{\theta}_T) \sin \alpha + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \boldsymbol{\theta}_T + \dot{m}(\mathbf{X}_{Isp} \cdot \boldsymbol{\theta}_{Isp}) + \varepsilon_3 \end{array} \right.$$

$$\overbrace{Y(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}})} \quad \overbrace{G(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}}, \boldsymbol{\theta})}$$

- Nonlinear in states and controls
- ~~Nonlinear in parameters~~ → Linear in parameters
- Structured

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m \dot{V} + mg \sin \gamma = (\textcolor{green}{X_T} \cos \alpha) \cdot \textcolor{red}{\theta_T} - X_D \cdot \theta_D + \varepsilon_1 \\ m V \dot{\gamma} + mg \cos \gamma = (\textcolor{green}{X_T} \sin \alpha) \cdot \textcolor{red}{\theta_T} + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \textcolor{red}{\theta_T} + (\dot{m} \textcolor{green}{X_{Isp}}) \cdot \theta_{Isp} + \varepsilon_3 \end{array} \right.$$

$$\overbrace{Y(\boldsymbol{u}, \boldsymbol{x}, \dot{\boldsymbol{x}})} \quad \overbrace{G(\boldsymbol{u}, \boldsymbol{x}, \dot{\boldsymbol{x}}, \boldsymbol{\theta})}$$

- Nonlinear in states and controls
- ~~Nonlinear in parameters~~ → Linear in parameters
- Structured

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m\dot{V} + mg \sin \gamma = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ mV\dot{\gamma} + mg \cos \gamma = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{array} \right.$$

$$\overbrace{Y(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}})} \quad \overbrace{G(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}}, \boldsymbol{\theta})}$$

- Nonlinear in states and controls
- ~~Nonlinear in parameters~~ → Linear in parameters
- Structured

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ m\dot{V} + mg \sin \gamma = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ mV\dot{\gamma} + mg \cos \gamma = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{array} \right.$$

$$\underbrace{Y(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}})} \quad \underbrace{G(\mathbf{u}, \mathbf{x}, \dot{\mathbf{x}}, \boldsymbol{\theta})}$$

- Nonlinear in states and controls
- ~~Nonlinear in parameters~~ → Linear in parameters
- Structured

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{array} \right.$$

- Nonlinear in states and controls
- ~~Nonlinear in parameters~~ → Linear in parameters
- Structured

# LEVERAGING THE DYNAMICS STRUCTURE

$$\left\{ \begin{array}{l} \dot{h} = V \sin \gamma \\ Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{array} \right.$$

- Nonlinear in states and controls
- ~~Nonlinear in parameters~~ → Linear in parameters
- Structured  $\rightsquigarrow$  **Multi-task Learning**

# MULTI-TASK REGRESSION

Aircraft:

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{lspm} \cdot \theta_{lsp} + \varepsilon_3 \end{cases}$$

# MULTI-TASK REGRESSION

Aircraft:

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{lspm} \cdot \theta_{lsp} + \varepsilon_3 \end{cases}$$

General:

$$\begin{cases} Y_1 = X_{c,1} \cdot \theta_c + X_1 \cdot \theta_1 + \varepsilon_1 \\ Y_2 = X_{c,2} \cdot \theta_c + X_2 \cdot \theta_2 + \varepsilon_2 \\ \vdots \\ Y_K = X_{c,K} \cdot \theta_c + X_K \cdot \theta_K + \varepsilon_K \end{cases}$$

# MULTI-TASK REGRESSION

Aircraft:

General:

$$\left\{ \begin{array}{l} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{lspm} \cdot \theta_{lsp} + \varepsilon_3 \end{array} \right. \quad \left\{ \begin{array}{l} Y_1 = X_{c,1} \cdot \theta_c + X_1 \cdot \theta_1 + \varepsilon_1 \\ Y_2 = X_{c,2} \cdot \theta_c + X_2 \cdot \theta_2 + \varepsilon_2 \\ \vdots \qquad \qquad \vdots \\ Y_K = X_{c,K} \cdot \theta_c + X_K \cdot \theta_K + \varepsilon_K \end{array} \right.$$

Coupling parameters , Task specific parameters

# MULTI-TASK REGRESSION

Aircraft:

General:

$$\left\{ \begin{array}{l} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{array} \right. \quad \left\{ \begin{array}{l} Y_1 = X_{c,1} \cdot \theta_c + X_1 \cdot \theta_1 + \varepsilon_1 \\ Y_2 = X_{c,2} \cdot \theta_c + X_2 \cdot \theta_2 + \varepsilon_2 \\ \vdots \qquad \vdots \\ Y_K = X_{c,K} \cdot \theta_c + X_K \cdot \theta_K + \varepsilon_K \end{array} \right.$$

Coupling parameters , Task specific parameters

Many other examples:

- Giant squid neurons [FitzHugh, 1961, Nagumo et al., 1962],

$$\left\{ \begin{array}{l} \dot{V} = \theta_1 \left( V - \frac{V^3}{3} + R \right), \\ \dot{R} = -\frac{1}{\theta_1} (V - \theta_2 + \theta_3 R), \end{array} \right.$$

# MULTI-TASK REGRESSION

Aircraft:

General:

$$\left\{ \begin{array}{l} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{lspm} \cdot \theta_{lsp} + \varepsilon_3 \end{array} \right. \quad \left\{ \begin{array}{l} Y_1 = X_{c,1} \cdot \theta_c + X_1 \cdot \theta_1 + \varepsilon_1 \\ Y_2 = X_{c,2} \cdot \theta_c + X_2 \cdot \theta_2 + \varepsilon_2 \\ \vdots \qquad \vdots \\ Y_K = X_{c,K} \cdot \theta_c + X_K \cdot \theta_K + \varepsilon_K \end{array} \right.$$

**Coupling parameters , Task specific parameters**

Many other examples:

- *Giant squid neurons* [FitzHugh, 1961, Nagumo et al., 1962],
- *Susceptible-infectious-recovered models* [Anderson and May, 1992],

$$\left\{ \begin{array}{l} \dot{S} = \theta_1 - (\theta_2 I + \theta_3) S, \\ \dot{I} = \theta_2 IS - (\theta_4 + \theta_3) I, \\ \dot{R} = \theta_4 I - \theta_3 R. \end{array} \right.$$

# MULTI-TASK REGRESSION

Aircraft:

General:

$$\left\{ \begin{array}{l} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{lspm} \cdot \theta_{lsp} + \varepsilon_3 \end{array} \right. \quad \left\{ \begin{array}{l} Y_1 = X_{c,1} \cdot \theta_c + X_1 \cdot \theta_1 + \varepsilon_1 \\ Y_2 = X_{c,2} \cdot \theta_c + X_2 \cdot \theta_2 + \varepsilon_2 \\ \vdots \qquad \vdots \\ Y_K = X_{c,K} \cdot \theta_c + X_K \cdot \theta_K + \varepsilon_K \end{array} \right.$$

**Coupling parameters , Task specific parameters**

Many other examples:

- *Giant squid neurons* [FitzHugh, 1961, Nagumo et al., 1962],
- *Susceptible-infectious-recovered models* [Anderson and May, 1992],
- *Mechanical systems,...*

$$m \left( \frac{d\vec{V}}{dt} \right)_x = (\vec{F}(\theta_F))_x, \quad m \left( \frac{d\vec{V}}{dt} \right)_y = (\vec{F}(\theta_F))_y.$$

# MULTI-TASK REGRESSION

Aircraft:

General:

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{lspm} \cdot \theta_{lsp} + \varepsilon_3 \end{cases} \quad \begin{cases} Y_1 = X_{c,1} \cdot \theta_c + X_1 \cdot \theta_1 + \varepsilon_1 \\ Y_2 = X_{c,2} \cdot \theta_c + X_2 \cdot \theta_2 + \varepsilon_2 \\ \vdots \qquad \qquad \vdots \\ Y_K = X_{c,K} \cdot \theta_c + X_K \cdot \theta_K + \varepsilon_K \end{cases}$$

Coupling parameters , Task specific parameters

Multi-task Linear Least-Squares:

$$\min_{\theta} \sum_{k=1}^K \sum_{i=1}^N (Y_{k,i} - X_{c,k,i} \cdot \theta_c - X_{k,i} \cdot \theta_k)^2$$

# MULTI-TASK REGRESSION

Aircraft:

General:

$$\left\{ \begin{array}{l} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{lspm} \cdot \theta_{lsp} + \varepsilon_3 \end{array} \right. \quad \left\{ \begin{array}{l} Y_1 = X_{c,1} \cdot \theta_c + X_1 \cdot \theta_1 + \varepsilon_1 \\ Y_2 = X_{c,2} \cdot \theta_c + X_2 \cdot \theta_2 + \varepsilon_2 \\ \vdots \qquad \vdots \\ Y_K = X_{c,K} \cdot \theta_c + X_K \cdot \theta_K + \varepsilon_K \end{array} \right.$$

Coupling parameters , Task specific parameters

Multi-task Linear Least-Squares:

Block-sparse Coupling Structure

$$\min_{\theta} \sum_{i=1}^N \left\| \begin{pmatrix} Y_{1,i} \\ \vdots \\ Y_{K,i} \end{pmatrix} - \begin{pmatrix} X_{c,1,i} & X_{1,i} & 0 & 0 & \dots & 0 \\ X_{c,2,i} & 0 & X_{2,i} & 0 & \dots & 0 \\ \vdots & 0 & 0 & \ddots & 0 & 0 \\ X_{c,K,i} & 0 & 0 & \dots & 0 & X_{K,i} \end{pmatrix} \begin{pmatrix} \theta_c \\ \theta_1 \\ \vdots \\ \theta_K \end{pmatrix} \right\|_2^2$$

# MULTI-TASK REGRESSION

Aircraft:

General:

$$\left\{ \begin{array}{l} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{lspm} \cdot \theta_{lsp} + \varepsilon_3 \end{array} \right. \quad \left\{ \begin{array}{l} Y_1 = X_{c,1} \cdot \theta_c + X_1 \cdot \theta_1 + \varepsilon_1 \\ Y_2 = X_{c,2} \cdot \theta_c + X_2 \cdot \theta_2 + \varepsilon_2 \\ \vdots \qquad \vdots \\ Y_K = X_{c,K} \cdot \theta_c + X_K \cdot \theta_K + \varepsilon_K \end{array} \right.$$

Coupling parameters , Task specific parameters

Multi-task Linear Least-Squares:

Block-sparse Coupling Structure

$$\min_{\theta} \sum_{i=1}^N \left\| \begin{pmatrix} Y_{1,i} \\ Y_{2,i} \\ Y_{3,i} \end{pmatrix} - \begin{pmatrix} X_{T1,i} & -X_{D,i} & 0 & 0 \\ X_{T2,i} & 0 & X_{L,i} & 0 \\ X_{T,i} & 0 & 0 & X_{lspm,i} \end{pmatrix} \begin{pmatrix} \theta_T \\ \theta_D \\ \theta_L \\ \theta_{lsp} \end{pmatrix} \right\|_2^2$$

# MULTI-TASK REGRESSION

Aircraft:

General:

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ Y_3 = X_T \cdot \theta_T + X_{lspm} \cdot \theta_{lsp} + \varepsilon_3 \end{cases} \quad \begin{cases} Y_1 = X_{c,1} \cdot \theta_c + X_1 \cdot \theta_1 + \varepsilon_1 \\ Y_2 = X_{c,2} \cdot \theta_c + X_2 \cdot \theta_2 + \varepsilon_2 \\ \vdots \qquad \qquad \vdots \\ Y_K = X_{c,K} \cdot \theta_c + X_K \cdot \theta_K + \varepsilon_K \end{cases}$$

**Coupling parameters**, **Task specific parameters**

Multi-task Linear Least-Squares:

Block-sparse Coupling Structure

$$\min_{\theta} \sum_{i=1}^N \|Y_i - X_i \theta\|_2^2$$

with  $\theta = (\theta_c, \theta_1, \dots, \theta_K) \in \mathbb{R}^p$ ,  $p = d_c + \sum_{k=1}^K d_k$ ,  
 $Y_i \in \mathbb{R}^K$  and  $X_i \in \mathbb{R}^{K \times p}$ .

# FEATURE SELECTION

Our model:

$$T = N_1(\theta_{T,1} + \theta_{T,2}\rho + \theta_{T,3}M + \theta_{T,4}\rho^2 + \theta_{T,5}\rho M + \theta_{T,6}M^2 + \\ \theta_{T,7}\rho^3 + \theta_{T,8}\rho^2M + \theta_{T,9}\rho M^2 + \theta_{T,10}M^3 + \theta_{T,11}\rho^4 + \\ \theta_{T,12}\rho^3M + \theta_{T,13}\rho^2M^2 + \theta_{T,14}\rho M^3 + \theta_{T,15}M^4).$$

# FEATURE SELECTION

Our model:

$$T = N_1(\theta_{T,1} + \theta_{T,2}\rho + \theta_{T,3}M + \theta_{T,4}\rho^2 + \theta_{T,5}\rho M + \theta_{T,6}M^2 + \theta_{T,7}\rho^3 + \theta_{T,8}\rho^2M + \theta_{T,9}\rho M^2 + \theta_{T,10}M^3 + \theta_{T,11}\rho^4 + \theta_{T,12}\rho^3M + \theta_{T,13}\rho^2M^2 + \theta_{T,14}\rho M^3 + \theta_{T,15}M^4).$$

Mattingly's model [Mattingly et al., 1992]:

$$T = N_1(\theta_{T,1}\rho + \theta_{T,2}\rho M^3).$$

# FEATURE SELECTION

Our model:

$$T = N_1(\theta_{T,1} + \theta_{T,2}\rho + \theta_{T,3}M + \theta_{T,4}\rho^2 + \theta_{T,5}\rho M + \theta_{T,6}M^2 + \theta_{T,7}\rho^3 + \theta_{T,8}\rho^2M + \theta_{T,9}\rho M^2 + \theta_{T,10}M^3 + \theta_{T,11}\rho^4 + \theta_{T,12}\rho^3M + \theta_{T,13}\rho^2M^2 + \theta_{T,14}\rho M^3 + \theta_{T,15}M^4).$$

Mattingly's model [Mattingly et al., 1992]:

$$T = N_1(\theta_{T,1}\rho + \theta_{T,2}\rho M^3).$$

⇒ High risk of overfitting

# FEATURE SELECTION

Our (sparse) model:

$$T = N_1(\theta_{T,1} + \theta_{T,2}\rho + \theta_{T,3}M + \theta_{T,4}\rho^2 + \theta_{T,5}\rho M + \theta_{T,6}M^2 + \theta_{T,7}\rho^3 + \theta_{T,8}\rho^2M + \theta_{T,9}\rho M^2 + \theta_{T,10}M^3 + \theta_{T,11}\rho^4 + \theta_{T,12}\rho^3M + \theta_{T,13}\rho^2M^2 + \theta_{T,14}\rho M^3 + \theta_{T,15}M^4).$$

Mattingly's model [Mattingly et al., 1992]:

$$T = N_1(\theta_{T,1}\rho + \theta_{T,2}\rho M^3).$$

⇒ High risk of overfitting

# FEATURE SELECTION

Our (sparse) model:

$$T = N_1(\theta_{T,1} + \theta_{T,2}\rho + \theta_{T,3}M + \theta_{T,4}\rho^2 + \theta_{T,5}\rho M + \theta_{T,6}M^2 + \theta_{T,7}\rho^3 + \theta_{T,8}\rho^2M + \theta_{T,9}\rho M^2 + \theta_{T,10}M^3 + \theta_{T,11}\rho^4 + \theta_{T,12}\rho^3M + \theta_{T,13}\rho^2M^2 + \theta_{T,14}\rho M^3 + \theta_{T,15}M^4).$$

Mattingly's model [Mattingly et al., 1992]:

$$T = N_1(\theta_{T,1}\rho + \theta_{T,2}\rho M^3).$$

Sparse models are:

- Less susceptible to overfitting,

# FEATURE SELECTION

Our (sparse) model:

$$T = N_1(\theta_{T,1} + \theta_{T,2}\rho + \theta_{T,3}M + \theta_{T,4}\rho^2 + \theta_{T,5}\rho M + \theta_{T,6}M^2 + \theta_{T,7}\rho^3 + \theta_{T,8}\rho^2M + \theta_{T,9}\rho M^2 + \theta_{T,10}M^3 + \theta_{T,11}\rho^4 + \theta_{T,12}\rho^3M + \theta_{T,13}\rho^2M^2 + \theta_{T,14}\rho M^3 + \theta_{T,15}M^4).$$

Mattingly's model [Mattingly et al., 1992]:

$$T = N_1(\theta_{T,1}\rho + \theta_{T,2}\rho M^3).$$

Sparse models are:

- Less susceptible to overfitting,
- More compliant with physical models,

# FEATURE SELECTION

Our (sparse) model:

$$T = N_1(\theta_{T,1} + \theta_{T,2}\rho + \theta_{T,3}M + \theta_{T,4}\rho^2 + \theta_{T,5}\rho M + \theta_{T,6}M^2 + \theta_{T,7}\rho^3 + \theta_{T,8}\rho^2M + \theta_{T,9}\rho M^2 + \theta_{T,10}M^3 + \theta_{T,11}\rho^4 + \theta_{T,12}\rho^3M + \theta_{T,13}\rho^2M^2 + \theta_{T,14}\rho M^3 + \theta_{T,15}M^4).$$

Mattingly's model [Mattingly et al., 1992]:

$$T = N_1(\theta_{T,1}\rho + \theta_{T,2}\rho M^3).$$

Sparse models are:

- Less susceptible to overfitting,
- More compliant with physical models,
- More interpretable,

# FEATURE SELECTION

Our (sparse) model:

$$T = N_1(\theta_{T,1} + \theta_{T,2}\rho + \theta_{T,3}M + \theta_{T,4}\rho^2 + \theta_{T,5}\rho M + \theta_{T,6}M^2 + \theta_{T,7}\rho^3 + \theta_{T,8}\rho^2M + \theta_{T,9}\rho M^2 + \theta_{T,10}M^3 + \theta_{T,11}\rho^4 + \theta_{T,12}\rho^3M + \theta_{T,13}\rho^2M^2 + \theta_{T,14}\rho M^3 + \theta_{T,15}M^4).$$

Mattingly's model [Mattingly et al., 1992]:

$$T = N_1(\theta_{T,1}\rho + \theta_{T,2}\rho M^3).$$

Sparse models are:

- Less susceptible to overfitting,
- More compliant with physical models,
- More interpretable,
- Lighter/Faster.

# BLOCK-SPARSE LASSO

Lasso [Tibshirani, 1994]:  $\{(X_i, Y_i)\}_{i=1}^N \subset \mathbb{R}^{d+1}$  i.i.d sample,

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \lambda \|\boldsymbol{\theta}\|_1.$$

## BLOCK-SPARSE LASSO

Lasso [Tibshirani, 1994]:  $\{(X_i, Y_i)\}_{i=1}^N \subset \mathbb{R}^{d+1}$  i.i.d sample,

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \lambda \|\boldsymbol{\theta}\|_1.$$




FIGURE:  $^1$ Sparsity induced by  $L^1$  norm in Lasso.

# BLOCK-SPARSE LASSO

$$\min_{\boldsymbol{\theta}} \sum_{k=1}^K \sum_{i=1}^N (Y_{k,i} - X_{c,k,i} \cdot \boldsymbol{\theta}_c - X_{k,i} \cdot \boldsymbol{\theta}_k)^2$$

# BLOCK-SPARSE LASSO

$$\min_{\boldsymbol{\theta}} \sum_{k=1}^K \sum_{i=1}^N (Y_{k,i} - X_{c,k,i} \cdot \boldsymbol{\theta}_c - X_{k,i} \cdot \boldsymbol{\theta}_k)^2 + \lambda_c \|\boldsymbol{\theta}_c\|_1 + \sum_{k=1}^K \lambda_k \|\boldsymbol{\theta}_k\|_1$$

# BLOCK-SPARSE LASSO

Block-sparse structure preserved

$$\min_{\boldsymbol{\theta}} \sum_{k=1}^K \sum_{i=1}^N (Y_{k,i} - X_{c,k,i} \cdot \boldsymbol{\theta}_c - X_{k,i} \cdot \boldsymbol{\theta}_k)^2 + \lambda_c \|\boldsymbol{\theta}_c\|_1 + \sum_{k=1}^K \lambda_k \|\boldsymbol{\theta}_k\|_1$$

# BLOCK-SPARSE LASSO

Block-sparse structure preserved  $\rightsquigarrow$  **Equivalent to Lasso problem**

$$\min_{\boldsymbol{\theta}} \sum_{k=1}^K \sum_{i=1}^N (Y_{k,i} - X_{c,k,i} \cdot \boldsymbol{\theta}_c - X_{k,i} \cdot \boldsymbol{\theta}_k)^2 + \lambda_c \|\boldsymbol{\theta}_c\|_1 + \sum_{k=1}^K \lambda_k \|\boldsymbol{\theta}_k\|_1$$

# BLOCK-SPARSE LASSO

Block-sparse structure preserved  $\rightsquigarrow$  **Equivalent to Lasso problem**

$$\min_{\theta} \sum_{i=1}^N \left\| \begin{pmatrix} Y_{1,i} \\ \vdots \\ Y_{K,i} \end{pmatrix} - \begin{pmatrix} B_{c,1,i} & B_{1,i} & 0 & 0 & \dots & 0 \\ B_{c,2,i} & 0 & B_{2,i} & 0 & \dots & 0 \\ \vdots & 0 & 0 & \ddots & 0 & 0 \\ B_{c,K,i} & 0 & 0 & \dots & 0 & B_{K,i} \end{pmatrix} \begin{pmatrix} \beta_c \\ \beta_1 \\ \vdots \\ \beta_K \end{pmatrix} \right\|_2^2 + \lambda_c \left\| \begin{pmatrix} \beta_c \\ \beta_1 \\ \vdots \\ \beta_K \end{pmatrix} \right\|_1,$$

$$B_{c,k,i} := X_{c,k,i}, \quad \beta_c := \theta_c,$$

$$B_{k,i} := \frac{\lambda_c}{\lambda_k} X_{k,i}, \quad \beta_k := \frac{\lambda_k}{\lambda_c} \theta_k.$$

# BLOCK-SPARSE LASSO

Block-sparse structure preserved  $\rightsquigarrow$  **Equivalent to Lasso problem**

$$\min_{\theta} \sum_{i=1}^N \left\| \begin{pmatrix} Y_{1,i} \\ Y_{2,i} \\ Y_{3,i} \end{pmatrix} - \begin{pmatrix} X_{T1,i} & -\frac{\lambda_c}{\lambda_1} X_{D,i} & 0 & 0 \\ X_{T2,i} & 0 & \frac{\lambda_c}{\lambda_2} X_{L,i} & 0 \\ X_{T,i} & 0 & 0 & \frac{\lambda_c}{\lambda_3} X_{Ispm,i} \end{pmatrix} \begin{pmatrix} \theta_T \\ \frac{\lambda_1}{\lambda_c} \theta_D \\ \frac{\lambda_2}{\lambda_c} \theta_L \\ \frac{\lambda_3}{\lambda_c} \theta_{Isp} \end{pmatrix} \right\|_2^2 + \left\| \begin{pmatrix} \theta_T \\ \frac{\lambda_1}{\lambda_c} \theta_D \\ \frac{\lambda_2}{\lambda_c} \theta_L \\ \frac{\lambda_3}{\lambda_c} \theta_{Isp} \end{pmatrix} \right\|_1.$$

# BLOCK-SPARSE LASSO

Block-sparse structure preserved  $\rightsquigarrow$  **Equivalent to Lasso problem**

$$\min_{\theta} \sum_{i=1}^N \left\| \begin{pmatrix} Y_{1,i} \\ Y_{2,i} \\ Y_{3,i} \end{pmatrix} - \begin{pmatrix} X_{T1,i} & -\frac{\lambda_c}{\lambda_1} X_{D,i} & 0 & 0 \\ X_{T2,i} & 0 & \frac{\lambda_c}{\lambda_2} X_{L,i} & 0 \\ X_{T,i} & 0 & 0 & \frac{\lambda_c}{\lambda_3} X_{Ispm,i} \end{pmatrix} \begin{pmatrix} \theta_T \\ \frac{\lambda_1}{\lambda_c} \theta_D \\ \frac{\lambda_2}{\lambda_c} \theta_L \\ \frac{\lambda_3}{\lambda_c} \theta_{Isp} \end{pmatrix} \right\|_2^2 + \left\| \begin{pmatrix} \theta_T \\ \frac{\lambda_1}{\lambda_c} \theta_D \\ \frac{\lambda_2}{\lambda_c} \theta_L \\ \frac{\lambda_3}{\lambda_c} \theta_{Isp} \end{pmatrix} \right\|_1.$$

In practice:  $\lambda_k = \lambda_c$ , for all  $k = 1, \dots, K$ .

# BLOCK-SPARSE LASSO

Block-sparse structure preserved  $\rightsquigarrow$  **Equivalent to Lasso problem**

$$\min_{\theta} \sum_{i=1}^N \left\| \begin{pmatrix} Y_{1,i} \\ Y_{2,i} \\ Y_{3,i} \end{pmatrix} - \begin{pmatrix} X_{T1,i} & -X_{D,i} & 0 & 0 \\ X_{T2,i} & 0 & X_{L,i} & 0 \\ X_{T,i} & 0 & 0 & X_{Ispm,i} \end{pmatrix} \begin{pmatrix} \theta_T \\ \theta_D \\ \theta_L \\ \theta_{Isp} \end{pmatrix} \right\|_2^2 + \left\| \begin{pmatrix} \theta_T \\ \theta_D \\ \theta_L \\ \theta_{Isp} \end{pmatrix} \right\|_1.$$

In practice:  $\lambda_k = \lambda_c$ , for all  $k = 1, \dots, K$ .

# BLOCK-SPARSE LASSO

Block-sparse structure preserved  $\rightsquigarrow$  **Equivalent to Lasso problem**

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N \|Y_i - X_i \boldsymbol{\theta}\|_2^2 + \lambda_c \|\boldsymbol{\theta}\|_1$$

with  $\boldsymbol{\theta} = (\boldsymbol{\theta}_c, \boldsymbol{\theta}_1, \dots, \boldsymbol{\theta}_K) \in \mathbb{R}^p$ ,  $p = d_c + \sum_{k=1}^K d_k$ ,  
 $Y_i \in \mathbb{R}^K$  and  $X_i \in \mathbb{R}^{K \times p}$ .

# STRUCTURED FEATURE SELECTION STATE-OF-THE-ART

- Group Lasso [Yuan and Lin, 2005] —  $\{(X_i, Y_i)\}_{i=1}^N \subset \mathbb{R}^{d+1}$  i.i.d sample,  
 $\boldsymbol{\theta} = (\boldsymbol{\theta}_g)_{g \in \mathcal{G}}$  partition:

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \sum_{g \in \mathcal{G}} \lambda_g \|\boldsymbol{\theta}_g\|_2,$$

# STRUCTURED FEATURE SELECTION STATE-OF-THE-ART

- Group Lasso [Yuan and Lin, 2005] —  $\{(X_i, Y_i)\}_{i=1}^N \subset \mathbb{R}^{d+1}$  i.i.d sample,  
 $\boldsymbol{\theta} = (\boldsymbol{\theta}_g)_{g \in \mathcal{G}}$  partition:

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \sum_{g \in \mathcal{G}} \lambda_g \|\boldsymbol{\theta}_g\|_2,$$

⇒ Sparsity among groups

# STRUCTURED FEATURE SELECTION STATE-OF-THE-ART

- Group Lasso [Yuan and Lin, 2005] —  $\{(X_i, Y_i)\}_{i=1}^N \subset \mathbb{R}^{d+1}$  i.i.d sample,  
 $\boldsymbol{\theta} = (\boldsymbol{\theta}_g)_{g \in \mathcal{G}}$  partition:

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \sum_{g \in \mathcal{G}} \lambda_g \|\boldsymbol{\theta}_g\|_2,$$

⇒ Sparsity among groups

- Sparse group Lasso [Friedman et al., 2010]:

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \sum_{g \in \mathcal{G}} \lambda_g \|\boldsymbol{\theta}_g\|_2 + \lambda \|\boldsymbol{\theta}\|_1,$$

# STRUCTURED FEATURE SELECTION STATE-OF-THE-ART

- Group Lasso [Yuan and Lin, 2005] —  $\{(X_i, Y_i)\}_{i=1}^N \subset \mathbb{R}^{d+1}$  i.i.d sample,  
 $\boldsymbol{\theta} = (\boldsymbol{\theta}_g)_{g \in \mathcal{G}}$  partition:

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \sum_{g \in \mathcal{G}} \lambda_g \|\boldsymbol{\theta}_g\|_2,$$

$\Rightarrow$  Sparsity among groups

- Sparse group Lasso [Friedman et al., 2010]:

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \sum_{g \in \mathcal{G}} \lambda_g \|\boldsymbol{\theta}_g\|_2 + \lambda \|\boldsymbol{\theta}\|_1,$$

$\Rightarrow$  Sparsity among **and** inside groups

# STRUCTURED FEATURE SELECTION STATE-OF-THE-ART

- Group Lasso [Yuan and Lin, 2005] —  $\{(X_i, Y_i)\}_{i=1}^N \subset \mathbb{R}^{d+1}$  i.i.d sample,  $\boldsymbol{\theta} = (\boldsymbol{\theta}_g)_{g \in \mathcal{G}}$  partition:

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \sum_{g \in \mathcal{G}} \lambda_g \|\boldsymbol{\theta}_g\|_2,$$

⇒ Sparsity among groups

- Sparse group Lasso [Friedman et al., 2010]:

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \sum_{g \in \mathcal{G}} \lambda_g \|\boldsymbol{\theta}_g\|_2 + \lambda \|\boldsymbol{\theta}\|_1,$$

⇒ Sparsity among **and** inside groups

- Multi-task Lasso [Obozinski et al., 2006] —  $K$  tasks,  $X_i \in \mathbb{R}^d$ ,  $Y_i \in \mathbb{R}^K$ ,  $\boldsymbol{\theta} \in \mathbb{R}^{d \times K}$ ,  $\boldsymbol{\theta}^k = (\boldsymbol{\theta}_j^k)_{j=1}^d$  parameter of task  $k$ :

$$\min_{\boldsymbol{\theta}} \sum_{k=1}^K \sum_{i=1}^N (Y_{k,i} - X_i \cdot \boldsymbol{\theta}^k)^2 + \sum_{j=1}^d \lambda_j \|\boldsymbol{\theta}_j\|_2.$$

# STRUCTURED FEATURE SELECTION STATE-OF-THE-ART

- Group Lasso [Yuan and Lin, 2005] —  $\{(X_i, Y_i)\}_{i=1}^N \subset \mathbb{R}^{d+1}$  i.i.d sample,  $\boldsymbol{\theta} = (\boldsymbol{\theta}_g)_{g \in \mathcal{G}}$  partition:

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \sum_{g \in \mathcal{G}} \lambda_g \|\boldsymbol{\theta}_g\|_2,$$

⇒ Sparsity among groups

- Sparse group Lasso [Friedman et al., 2010]:

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N (Y_i - X_i \cdot \boldsymbol{\theta})^2 + \sum_{g \in \mathcal{G}} \lambda_g \|\boldsymbol{\theta}_g\|_2 + \lambda \|\boldsymbol{\theta}\|_1,$$

⇒ Sparsity among **and** inside groups

- Multi-task Lasso [Obozinski et al., 2006] —  $K$  tasks,  $X_i \in \mathbb{R}^d$ ,  $Y_i \in \mathbb{R}^K$ ,  $\boldsymbol{\theta} \in \mathbb{R}^{d \times K}$ ,  $\boldsymbol{\theta}^k = (\boldsymbol{\theta}_j^k)_{j=1}^d$  parameter of task  $k$ :

$$\min_{\boldsymbol{\theta}} \sum_{k=1}^K \sum_{i=1}^N (Y_{k,i} - X_i \cdot \boldsymbol{\theta}^k)^2 + \sum_{j=1}^d \lambda_j \|\boldsymbol{\theta}_j\|_2.$$

⇒ Shared sparsity among tasks

# STRUCTURED FEATURE SELECTION STATE-OF-THE-ART

Other methods

Similarity/Difference with Block-sparse Lasso

# STRUCTURED FEATURE SELECTION STATE-OF-THE-ART

Other methods	Similarity/Difference with Block-sparse Lasso
<u>Group Lasso</u>	Parameters divided into groups, but group sparsity is precoded in quadratic loss function, so no $L^{2,1}$ -norm,

# STRUCTURED FEATURE SELECTION STATE-OF-THE-ART

Other methods	Similarity/Difference with Block-sparse Lasso
<u>Group Lasso</u>	Parameters divided into groups, but group sparsity is pre-coded in quadratic loss function, so no $L^{2,1}$ -norm,
<u>Sparse Group Lasso</u>	Sparsity induced within group,

# STRUCTURED FEATURE SELECTION STATE-OF-THE-ART

---

Other methods	Similarity/Difference with Block-sparse Lasso
<u>Group Lasso</u>	Parameters divided into groups, but group sparsity is pre-coded in quadratic loss function, so no $L^{2,1}$ -norm,
<u>Sparse Group Lasso</u>	Sparsity induced within group,
<u>Multi-task Lasso</u>	Multi-task setting, but not same pattern for every task.

---

# BOOTSTRAP IMPLEMENTATION

**High correlations among between polynomial features...**

# BOOTSTRAP IMPLEMENTATION

**High correlations among between polynomial features...**  
⇒ Inconsistent selections via the lasso !

# BOOTSTRAP IMPLEMENTATION

High correlations among between polynomial features...  
⇒ Inconsistent selections via the lasso !

---

Bolasso - Bach [2008]

---

training data  $\mathcal{T} = \{(X_i, Y_i)\}_{i=1}^N \subset \mathbb{R}^{K \times (K+1)} \times \mathbb{R}^K$ ,

**Require:** number of bootstrap replicates  $b$ ,

$L^1$  penalty parameter  $\lambda_c$ ,

- 1: **for**  $k = 1$  **to**  $b$  **do**
  - 2:   Generate bootstrap sample  $\mathcal{T}_k$ ,
  - 3:   Compute Block sparse Lasso estimate  $\hat{\theta}^k$  from  $\mathcal{T}_k$ ,
  - 4:   Compute support  $J_k = \{j, \hat{\theta}_j^k \neq 0\}$ ,
  - 5: **end for**
  - 6: Compute intersection  $J = \bigcap_{k=1}^b J_k$ ,
  - 7: Compute  $\hat{\theta}_J$  from selected features using Least-Squares.
-

# BOOTSTRAP IMPLEMENTATION

High correlations among between polynomial features...  
⇒ Inconsistent selections via the lasso !

---

Bolasso - Bach [2008]

---

training data  $\mathcal{T} = \{(X_i, Y_i)\}_{i=1}^N \subset \mathbb{R}^{K \times (K+1)} \times \mathbb{R}^K$ ,

**Require:** number of bootstrap replicates  $b$ ,

$L^1$  penalty parameter  $\lambda_c$ ,

- 1: **for**  $k = 1$  **to**  $b$  **do**
  - 2:   Generate bootstrap sample  $\mathcal{T}_k$ ,
  - 3:   Compute Block sparse Lasso estimate  $\hat{\theta}^k$  from  $\mathcal{T}_k$ ,
  - 4:   Compute support  $J_k = \{j, \hat{\theta}_j^k \neq 0\}$ ,
  - 5: **end for**
  - 6: Compute intersection  $J = \bigcap_{k=1}^b J_k$ ,
  - 7: Compute  $\hat{\theta}_J$  from selected features using Least-Squares.
- 

- Consistency under high correlations proved in Bach [2008],

# BOOTSTRAP IMPLEMENTATION

High correlations among between polynomial features...  
⇒ Inconsistent selections via the lasso !

---

Bolasso - Bach [2008]

---

training data  $\mathcal{T} = \{(X_i, Y_i)\}_{i=1}^N \subset \mathbb{R}^{K \times (K+1)} \times \mathbb{R}^K$ ,

**Require:** number of bootstrap replicates  $b$ ,

$L^1$  penalty parameter  $\lambda_c$ ,

- 1: **for**  $k = 1$  **to**  $b$  **do**
  - 2:   Generate bootstrap sample  $\mathcal{T}_k$ ,
  - 3:   Compute Block sparse Lasso estimate  $\hat{\theta}^k$  from  $\mathcal{T}_k$ ,
  - 4:   Compute support  $J_k = \{j, \hat{\theta}_j^k \neq 0\}$ ,
  - 5: **end for**
  - 6: Compute intersection  $J = \bigcap_{k=1}^b J_k$ ,
  - 7: Compute  $\hat{\theta}_J$  from selected features using Least-Squares.
- 

- Consistency under high correlations proved in Bach [2008],
- Efficient implementations exists: LARS [Efron et al., 2004].

# PROBLEM WITH INTRA-GROUP CORRELATIONS

# PROBLEM WITH INTRA-GROUP CORRELATIONS

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{cases}$$

# PROBLEM WITH INTRA-GROUP CORRELATIONS

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{cases}$$

# PROBLEM WITH INTRA-GROUP CORRELATIONS

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{cases}$$

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N \|Y_i - X_i \boldsymbol{\theta}\|_2^2 + \lambda_c \|\boldsymbol{\theta}\|_1$$

# PROBLEM WITH INTRA-GROUP CORRELATIONS

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{cases}$$

$$\min_{\theta} \sum_{i=1}^N \|Y_i - X_i \theta\|_2^2 + \lambda_c \|\theta\|_1 \Rightarrow \hat{\theta}_T = \hat{\theta}_{Isp} = 0!$$

# PROBLEM WITH INTRA-GROUP CORRELATIONS





FIGURE: Features correlations  
higher than 0.9 in absolute value.


# PROBLEM WITH INTRA-GROUP CORRELATIONS



$\Rightarrow \theta \mapsto \sum_{i=1}^N \|Y_i - X_i\theta\|_2^2$  not injective...

FIGURE: Features correlations higher than 0.9 in absolute value.

# PROBLEM WITH INTRA-GROUP CORRELATIONS




$\Rightarrow \theta \mapsto \sum_{i=1}^N \|Y_i - X_i\theta\|_2^2$  not injective...

**III-posed problem !**

FIGURE: Features correlations higher than 0.9 in absolute value.

# PROBLEM WITH INTRA-GROUP CORRELATIONS




$\Rightarrow \theta \mapsto \sum_{i=1}^N \|Y_i - X_i\theta\|_2^2$  not injective...

**III-posed problem !**

Tikhonov penalty [Tikhonov, 1943] known to improve problem conditioning  $\|\theta\|_2^2$ ,

FIGURE: Features correlations higher than 0.9 in absolute value.

# PROBLEM WITH INTRA-GROUP CORRELATIONS



$\Rightarrow \theta \mapsto \sum_{i=1}^N \|Y_i - X_i\theta\|_2^2$  not injective...

**III-posed problem !**

Tikhonov penalty [Tikhonov, 1943] known to improve problem conditioning  $\|\theta\|_2^2$ , but shrinks parameters towards 0...

FIGURE: Features correlations higher than 0.9 in absolute value.

# PROBLEM WITH INTRA-GROUP CORRELATIONS




FIGURE: Features correlations higher than 0.9 in absolute value.

$\Rightarrow \theta \mapsto \sum_{i=1}^N \|Y_i - X_i\theta\|_2^2$  not injective...

**III-posed problem !**

Tikhonov penalty [Tikhonov, 1943] known to improve problem conditioning  $\|\theta\|_2^2$ , but shrinks parameters towards 0...

$\Rightarrow$  Generalized Tikhonov

$$(\theta - \tilde{\theta})^\top Q (\theta - \tilde{\theta}) = \|\Gamma(\theta - \tilde{\theta})\|_2^2,$$

where  $\tilde{\theta}$  is a prior and  $Q \in \mathbb{R}^{p \times p}$ .

# PROBLEM WITH INTRA-GROUP CORRELATIONS

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{cases}$$

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N \|Y_i - X_i \boldsymbol{\theta}\|_2^2 + \lambda_c \|\boldsymbol{\theta}\|_1$$

# PROBLEM WITH INTRA-GROUP CORRELATIONS

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{cases}$$

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N \|Y_i - X_i \boldsymbol{\theta}\|_2^2 + \lambda_c \|\boldsymbol{\theta}\|_1$$

Use prior  $\tilde{l}_{sp} \rightsquigarrow \{\tilde{l}_{sp,i} = \tilde{l}_{sp}(\mathbf{u}_i, \mathbf{x}_i)\}$

# PROBLEM WITH INTRA-GROUP CORRELATIONS

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{cases}$$

$$\min_{\boldsymbol{\theta}} \sum_{i=1}^N \left( \|Y_i - X_i \boldsymbol{\theta}\|_2^2 + \lambda_t \|\tilde{I}_{sp,i} - X_{Isp,i} \cdot \boldsymbol{\theta}_{Isp}\|_2^2 \right) + \lambda_c \|\boldsymbol{\theta}\|_1$$

Use prior  $\tilde{I}_{sp} \rightsquigarrow \{\tilde{I}_{sp,i} = \tilde{I}_{sp}(\mathbf{u}_i, \mathbf{x}_i)\}$

# PROBLEM WITH INTRA-GROUP CORRELATIONS

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \end{cases}$$

$$\min_{\theta} \sum_{i=1}^N \left( \|Y_i - X_i \theta\|_2^2 + \lambda_t \|\tilde{I}_{sp,i} - X_{Isp,i} \cdot \theta_{Isp}\|_2^2 \right) + \lambda_c \|\theta\|_1$$

Equivalent to  $\|\Gamma(\theta - \tilde{\theta})\|_2^2$  with  $\Gamma_i = (\underbrace{0, \dots, 0}_{d_T+d_D+d_L}, X_{Isp}^\top)$  and  $\Gamma_i \tilde{\theta} = \tilde{I}_{sp,i}$ .

# PROBLEM WITH INTRA-GROUP CORRELATIONS

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \\ \lambda_t \tilde{I}_{sp} = \lambda_t X_{Isp} \cdot \theta_{Isp} + \varepsilon_4 \end{cases}$$

$$\min_{\theta} \sum_{i=1}^N \left( \|Y_i - X_i \theta\|_2^2 + \lambda_t \|\tilde{I}_{sp,i} - X_{Isp,i} \cdot \theta_{Isp}\|_2^2 \right) + \lambda_c \|\theta\|_1$$

Equivalent to  $\|\Gamma(\theta - \tilde{\theta})\|_2^2$  with  $\Gamma_i = (\underbrace{0, \dots, 0}_{d_T+d_D+d_L}, X_{Isp}^\top)$  and  $\Gamma_i \tilde{\theta} = \tilde{I}_{sp,i}$ .

# PROBLEM WITH INTRA-GROUP CORRELATIONS

$$\begin{cases} Y_1 = X_{T1} \cdot \theta_T - X_D \cdot \theta_D + \varepsilon_1 \\ Y_2 = X_{T2} \cdot \theta_T + X_L \cdot \theta_L + \varepsilon_2 \\ 0 = X_T \cdot \theta_T + X_{Ispm} \cdot \theta_{Isp} + \varepsilon_3 \\ \lambda_t \tilde{I}_{sp} = \lambda_t X_{Isp} \cdot \theta_{Isp} + \varepsilon_4 \end{cases}$$

$$\min_{\theta} \sum_{i=1}^N \|\tilde{Y}_i - \tilde{X}_i \theta\|_2^2 + \lambda_c \|\theta\|_1$$

$$\tilde{Y}_i = \begin{pmatrix} Y_{1,i} \\ Y_{2,i} \\ 0 \\ \lambda_t \tilde{I}_{sp,i} \end{pmatrix}, \quad \tilde{X}_i = \begin{pmatrix} (X_{T1,i})^\top & -(X_{D,i})^\top & 0 & 0 \\ (X_{T2,i})^\top & 0 & (X_{L,i})^\top & 0 \\ (X_{T,i})^\top & 0 & 0 & (X_{Ispm,i})^\top \\ 0 & 0 & 0 & \lambda_t (X_{Isp,i})^\top \end{pmatrix},$$

Equivalent to  $\|\Gamma(\theta - \tilde{\theta})\|_2^2$  with  $\Gamma_i = (\underbrace{0, \dots, 0}_{d_T+d_D+d_L}, X_{Isp}^\top)$  and  $\Gamma_i \tilde{\theta} = \tilde{I}_{sp,i}$ .

# FEATURE SELECTION RESULTS

# FEATURE SELECTION RESULTS

- 25 different B737-800,

# FEATURE SELECTION RESULTS

- 25 different B737-800,
- 10 471 flights = 8 261 619 observations,


## FEATURE SELECTION RESULTS

- 25 different B737-800,
- 10 471 flights = 8 261 619 observations,
- Block sparse Bolasso used for  $T$ ,  $D$ ,  $L$  and  $I_{sp}$ ,

# FEATURE SELECTION RESULTS


- 25 different B737-800,
- 10 471 flights = 8 261 619 observations,
- Block sparse Bolasso used for  $T$ ,  $D$ ,  $L$  and  $I_{sp}$ ,
- We expect similar model structures,

# FEATURE SELECTION RESULTS



Feature selection results for the thrust, drag, lift and specific impulse models.

# ACCURACY OF DYNAMICS PREDICTIONS



# ACCURACY OF DYNAMICS PREDICTIONS





FIGURE: Leave-one-out off-sample errors distributions for nonlinear least-squares NLLS and block-sparse bolasso BSBL. Median errors are annotated and marked by dashed vertical lines.

# REALISM OF HIDDEN ELEMENTS



# FLIGHT RESIMULATION

# FLIGHT RESIMULATION

- Last assessment criterion = static;

# FLIGHT RESIMULATION

- Last assessment criterion = static;
- Does not incorporate the fact that the observations are time dependent;

# FLIGHT RESIMULATION

- Last assessment criterion = static;
- Does not incorporate the fact that the observations are time dependent;
- Does not take into account the goal of optimally controlling the aircraft system.


# FLIGHT RESIMULATION

- Last assessment criterion = static;
- Does not incorporate the fact that the observations are time dependent;
- Does not take into account the goal of optimally controlling the aircraft system.

$$\min_{(\mathbf{x}, \mathbf{u})} \int_{t_0}^{t_n} (\|\mathbf{u}(t) - \mathbf{u}_{test}(t)\|_{\mathbf{u}}^2 + \|\mathbf{x}(t) - \mathbf{x}_{test}(t)\|_{\mathbf{x}}^2) dt$$
$$\text{s.t. } \dot{\mathbf{x}}(t) = g(\mathbf{x}(t), \mathbf{u}(t), \hat{\theta}),$$

where  $\|\cdot\|_{\mathbf{u}}$ ,  $\|\cdot\|_{\mathbf{x}}$  denote scaling norms.

# FLIGHT RESIMULATION



# FLIGHT RESIMULATION




FIGURE: Distribution of the off-sample simulation error and boxplot of the optimization number of iterations and CPU time.

# SYSTEM IDENTIFICATION CONCLUSION

- Proposed Equation-Error Method approaches which extend to the System Identification framework well-known supervised learning techniques (Lasso, Ridge, bootstrap,...),

# SYSTEM IDENTIFICATION CONCLUSION

- Proposed Equation-Error Method approaches which extend to the System Identification framework well-known supervised learning techniques (Lasso, Ridge, bootstrap,...),
- Applicable to large amounts of data, unlike traditional Output-Error Methods,

# SYSTEM IDENTIFICATION CONCLUSION

- Proposed Equation-Error Method approaches which extend to the System Identification framework well-known supervised learning techniques (Lasso, Ridge, bootstrap,...),
- Applicable to large amounts of data, unlike traditional Output-Error Methods,
- Block-sparse estimators are proved to lead to consistent structured feature selection,

# SYSTEM IDENTIFICATION CONCLUSION

- Proposed Equation-Error Method approaches which extend to the System Identification framework well-known supervised learning techniques (Lasso, Ridge, bootstrap,...),
- Applicable to large amounts of data, unlike traditional Output-Error Methods,
- Block-sparse estimators are proved to lead to consistent structured feature selection,
- Can be efficiently trained using LARS algorithm as they are equivalent to successive Lasso problems,

# SYSTEM IDENTIFICATION CONCLUSION

- Proposed Equation-Error Method approaches which extend to the System Identification framework well-known supervised learning techniques (Lasso, Ridge, bootstrap,...),
- Applicable to large amounts of data, unlike traditional Output-Error Methods,
- Block-sparse estimators are proved to lead to consistent structured feature selection,
- Can be efficiently trained using LARS algorithm as they are equivalent to successive Lasso problems,
- No improvement in accuracy or training time compared to NLLS,

# SYSTEM IDENTIFICATION CONCLUSION

- Proposed Equation-Error Method approaches which extend to the System Identification framework well-known supervised learning techniques (Lasso, Ridge, bootstrap,...),
- Applicable to large amounts of data, unlike traditional Output-Error Methods,
- Block-sparse estimators are proved to lead to consistent structured feature selection,
- Can be efficiently trained using LARS algorithm as they are equivalent to successive Lasso problems,
- No improvement in accuracy or training time compared to NLLS,
- Light, interpretable and compact data-dependent models (more than 50% compression),

# SYSTEM IDENTIFICATION CONCLUSION

- Proposed Equation-Error Method approaches which extend to the System Identification framework well-known supervised learning techniques (Lasso, Ridge, bootstrap,...),
- Applicable to large amounts of data, unlike traditional Output-Error Methods,
- Block-sparse estimators are proved to lead to consistent structured feature selection,
- Can be efficiently trained using LARS algorithm as they are equivalent to successive Lasso problems,
- No improvement in accuracy or training time compared to NLLS,
- Light, interpretable and compact data-dependent models (more than 50% compression),
- Faster convergence of control problems,

# SYSTEM IDENTIFICATION CONCLUSION

- Proposed Equation-Error Method approaches which extend to the System Identification framework well-known supervised learning techniques (Lasso, Ridge, bootstrap,...),
- Applicable to large amounts of data, unlike traditional Output-Error Methods,
- Block-sparse estimators are proved to lead to consistent structured feature selection,
- Can be efficiently trained using LARS algorithm as they are equivalent to successive Lasso problems,
- No improvement in accuracy or training time compared to NLLS,
- Light, interpretable and compact data-dependent models (more than 50% compression),
- Faster convergence of control problems,
- Consistency with physical knowledge,

# SYSTEM IDENTIFICATION CONCLUSION

- Proposed Equation-Error Method approaches which extend to the System Identification framework well-known supervised learning techniques (Lasso, Ridge, bootstrap,...),
- Applicable to large amounts of data, unlike traditional Output-Error Methods,
- Block-sparse estimators are proved to lead to consistent structured feature selection,
- Can be efficiently trained using LARS algorithm as they are equivalent to successive Lasso problems,
- No improvement in accuracy or training time compared to NLLS,
- Light, interpretable and compact data-dependent models (more than 50% compression),
- Faster convergence of control problems,
- Consistency with physical knowledge,
- No initialization required.

# TRAJECTORY ACCEPTABILITY

# TRAJECTORY ACCEPTABILITY

$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt, \\ \text{s.t. } & \left\{ \begin{array}{l} \dot{\mathbf{x}}(t) = \hat{g}(\mathbf{u}(t), \mathbf{x}(t)), \quad \text{a.e. } t \in [0, t_f], \\ \text{Other constraints...} \end{array} \right. \end{aligned} \tag{AOCP}$$

# TRAJECTORY ACCEPTABILITY

$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt, \\ \text{s.t. } & \left\{ \begin{array}{l} \dot{\mathbf{x}}(t) = \hat{g}(\mathbf{u}(t), \mathbf{x}(t)), \quad \text{a.e. } t \in [0, t_f], \\ \text{Other constraints...} \end{array} \right. \end{aligned} \tag{AOCP}$$

$\Rightarrow \hat{\mathbf{z}} = (\hat{\mathbf{x}}, \hat{\mathbf{u}})$  solution of (AOCP).

# TRAJECTORY ACCEPTABILITY

$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt, \\ \text{s.t. } & \left\{ \begin{array}{l} \dot{\mathbf{x}}(t) = \hat{g}(\mathbf{u}(t), \mathbf{x}(t)), \quad \text{a.e. } t \in [0, t_f], \\ \text{Other constraints...} \end{array} \right. \end{aligned} \tag{AOCP}$$

$\Rightarrow \hat{\mathbf{z}} = (\hat{\mathbf{x}}, \hat{\mathbf{u}})$  solution of (AOCP).

**Is  $\hat{\mathbf{z}}$  inside the validity region of the dynamics model  $\hat{g}$  ?**

# TRAJECTORY ACCEPTABILITY


$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt, \\ \text{s.t. } & \left\{ \begin{array}{l} \dot{\mathbf{x}}(t) = \hat{g}(\mathbf{u}(t), \mathbf{x}(t)), \quad \text{a.e. } t \in [0, t_f], \\ \text{Other constraints...} \end{array} \right. \end{aligned} \tag{AOCP}$$

$\Rightarrow \hat{\mathbf{z}} = (\hat{\mathbf{x}}, \hat{\mathbf{u}})$  solution of (AOCP).


Is  $\hat{\mathbf{z}}$  inside the validity region of the dynamics model  $\hat{g}$  ?

Does it look like a real trajectory ?

## TRAJECTORY ACCEPTABILITY




## TRAJECTORY ACCEPTABILITY



## Pilots acceptance

# TRAJECTORY ACCEPTABILITY




## Pilots acceptance



## Air Traffic Control<sup>2</sup>

# TRAJECTORY ACCEPTABILITY



Pilots acceptance



Air Traffic Control<sup>2</sup>

**How can we quantify the closeness from the optimized trajectory to the set of real flights?**

<sup>2</sup>NATS UK air traffic control

## LIKELIHOOD


- $X \sim f_{\theta^*}$ ,
- $x$ : observation of  $X$ ,
- Likelihood function of  $\theta$ , given  $x$ :

$$\mathcal{L}(\theta|x) = f_\theta(x).$$

## LIKELIHOOD

- $X \sim f_{\theta^*}$ ,
- $x$ : observation of  $X$ ,
- Likelihood function of  $\theta$ , given  $x$ :

$$\mathcal{L}(\theta|x) = f_\theta(x).$$




<sup>0</sup>Picture source: wikipedia, P-Value, author: Repapetilo CC.

## LIKELIHOOD

- $X \sim f_{\theta^*}$ ,
- $x$ : observation of  $X$ ,
- Likelihood function of  $\theta$ , given  $x$ :

$$\mathcal{L}(\theta|x) = f_\theta(x).$$




In our case:

- the optimized trajectory plays the role of  $\theta$ ,

## LIKELIHOOD

- $X \sim f_{\theta^*}$ ,
- $x$ : observation of  $X$ ,
- Likelihood function of  $\theta$ , given  $x$ :

$$\mathcal{L}(\theta|x) = f_\theta(x).$$



In our case:

- the optimized trajectory plays the role of  $\theta$ ,
- the set of real flights plays the role of  $x$ ,

# HOW TO APPLY THIS TO FUNCTIONAL DATA?

**Assumption:** We suppose that the real flights are observations of the same functional random variable  $Z = (Z_t)$  valued in  $\mathcal{C}(\mathbb{T}, E)$ , with  $E$  compact subset of  $\mathbb{R}^d$  and  $\mathbb{T} = [0, t_f]$ .

# HOW TO APPLY THIS TO FUNCTIONAL DATA?

**Assumption:** We suppose that the real flights are observations of the same functional random variable  $Z = (Z_t)$  valued in  $\mathcal{C}(\mathbb{T}, E)$ , with  $E$  compact subset of  $\mathbb{R}^d$  and  $\mathbb{T} = [0, t_f]$ .



**Problem:** Computation of probability densities in infinite dimensional space is untractable...

# HOW TO APPLY THIS TO FUNCTIONAL DATA?

**Assumption:** We suppose that the real flights are observations of the same functional random variable  $Z = (Z_t)$  valued in  $\mathcal{C}(\mathbb{T}, E)$ , with  $E$  compact subset of  $\mathbb{R}^d$  and  $\mathbb{T} = [0, t_f]$ .

**Problem:** Computation of probability densities in infinite dimensional space is untractable...

- Standard approach FDA: use FPCA to decompose the data in a small number of coefficients




# HOW TO APPLY THIS TO FUNCTIONAL DATA?

**Assumption:** We suppose that the real flights are observations of the same functional random variable  $Z = (Z_t)$  valued in  $\mathcal{C}(\mathbb{T}, E)$ , with  $E$  compact subset of  $\mathbb{R}^d$  and  $\mathbb{T} = [0, t_f]$ .

**Problem:** Computation of probability densities in infinite dimensional space is untractable...

- Standard approach FDA: use FPCA to decompose the data in a small number of coefficients
- Or: we can aggregate the marginal densities



# HOW DO WE AGGREGATE THE MARGINAL LIKELIHOODS?

# HOW DO WE AGGREGATE THE MARGINAL LIKELIHOODS?

- $f_t$  marginal density of  $Z$ , i.e. probability density function of  $Z_t$ ,

# HOW DO WE AGGREGATE THE MARGINAL LIKELIHOODS?

- $f_t$  marginal density of  $Z$ , i.e. probability density function of  $Z_t$ ,
- $y$  new trajectory,

# HOW DO WE AGGREGATE THE MARGINAL LIKELIHOODS?

- $f_t$  marginal density of  $Z$ , i.e. probability density function of  $Z_t$ ,
- $\mathbf{y}$  new trajectory,
- $f_t(\mathbf{y}(t))$  marginal likelihood of  $\mathbf{y}$  at  $t$ , i.e. likelihood of observing  $Z_t = \mathbf{y}(t)$ .

# HOW DO WE AGGREGATE THE MARGINAL LIKELIHOODS?

- $f_t$  marginal density of  $Z$ , i.e. probability density function of  $Z_t$ ,
- $\mathbf{y}$  new trajectory,
- $f_t(\mathbf{y}(t))$  marginal likelihood of  $\mathbf{y}$  at  $t$ , i.e. likelihood of observing  $Z_t = \mathbf{y}(t)$ .

Why not average over time ?...

$$\frac{1}{t_f} \int_0^{t_f} f_t(\mathbf{y}(t)) dt$$

# HOW DO WE AGGREGATE THE MARGINAL LIKELIHOODS?

- $f_t$  marginal density of  $Z$ , i.e. probability density function of  $Z_t$ ,
- $\mathbf{y}$  new trajectory,
- $f_t(\mathbf{y}(t))$  marginal likelihood of  $\mathbf{y}$  at  $t$ , i.e. likelihood of observing  $Z_t = \mathbf{y}(t)$ .

Why not average over time ?...

$$\frac{1}{t_f} \int_0^{t_f} f_t(\mathbf{y}(t)) dt$$

**Marginal densities may have really different shapes**

# HOW DO WE AGGREGATE THE MARGINAL LIKELIHOODS?

- $f_t$  marginal density of  $Z$ , i.e. probability density function of  $Z_t$ ,
- $\mathbf{y}$  new trajectory,
- $f_t(\mathbf{y}(t))$  marginal likelihood of  $\mathbf{y}$  at  $t$ , i.e. likelihood of observing  $Z_t = \mathbf{y}(t)$ .

## MEAN MARGINAL LIKELIHOOD

$$\text{MML}(Z, \mathbf{y}) = \frac{1}{t_f} \int_0^{t_f} \psi[f_t, \mathbf{y}(t)] dt,$$

where  $\psi : L^1(E, \mathbb{R}_+) \times \mathbb{R} \rightarrow [0; 1]$  is a continuous scaling map.

# HOW DO WE AGGREGATE THE MARGINAL LIKELIHOODS?

Possible scalings are the normalized density

$$\psi[f_t, \mathbf{y}(t)] := \frac{\mathbf{y}(t)}{\max_{z \in E} f_t(z)},$$


# HOW DO WE AGGREGATE THE MARGINAL LIKELIHOODS?

Possible scalings are the normalized density

$$\psi[f_t, \mathbf{y}(t)] := \frac{\mathbf{y}(t)}{\max_{z \in E} f_t(z)},$$

or the confidence level

$$\psi[f_t, \mathbf{y}(t)] := \mathbb{P}(f_t(Z_t) \leq f_t(\mathbf{y}(t))).$$



# HOW DO WE DEAL WITH SAMPLED CURVES?

# HOW DO WE DEAL WITH SAMPLED CURVES?

In practice, the  $m$  trajectories are sampled at variable discrete times:

$$\mathcal{T}^D := \{(t_j^r, z_j^r)\}_{\substack{1 \leq j \leq n \\ 1 \leq r \leq m}} \subset \mathbb{T} \times E, \quad z_j^r := \mathbf{z}^r(t_j^r),$$

$$\mathcal{Y} := \{(\tilde{t}_j, y_j)\}_{j=1}^{\tilde{n}} \subset \mathbb{T} \times E, \quad y_j := \mathbf{y}(\tilde{t}_j).$$

# HOW DO WE DEAL WITH SAMPLED CURVES?

In practice, the  $m$  trajectories are sampled at variable discrete times:

$$\begin{aligned}\mathcal{T}^D &:= \{(t_j^r, z_j^r)\}_{\substack{1 \leq j \leq n \\ 1 \leq r \leq m}} \subset \mathbb{T} \times E, & z_j^r &:= \mathbf{z}^r(t_j^r), \\ \mathcal{Y} &:= \{(\tilde{t}_j, y_j)\}_{j=1}^{\tilde{n}} \subset \mathbb{T} \times E, & y_j &:= \mathbf{y}(\tilde{t}_j).\end{aligned}$$

Hence, we approximate the MML using a Riemann sum which aggregates consistent estimators  $\hat{f}_{\tilde{t}_j}^m$  of the marginal densities  $f_{\tilde{t}_j}$ :

$$\text{EMML}_m(\mathcal{T}^D, \mathcal{Y}) := \frac{1}{t_f} \sum_{j=1}^{\tilde{n}} \psi[\hat{f}_{\tilde{t}_j}^m, y_j] \Delta \tilde{t}_j.$$

# HOW CAN WE ESTIMATE MARGINAL DENSITIES?

- Suppose that sampling times  $\{t_j^r : j = 1, \dots, n; r = 1, \dots, m\}$  are i.i.d. sampled from r.v.  $T$ , indep.  $Z$ ;

# HOW CAN WE ESTIMATE MARGINAL DENSITIES?

- Suppose that sampling times  $\{t_j^r : j = 1, \dots, n; r = 1, \dots, m\}$  are i.i.d. sampled from r.v.  $T$ , indep.  $Z$ ;
- $f_t$  is the density of  $Z_t = (Z_T | T = t) = (Y|X)$ ;

# HOW CAN WE ESTIMATE MARGINAL DENSITIES?

- Suppose that sampling times  $\{t_j^r : j = 1, \dots, n; r = 1, \dots, m\}$  are i.i.d. sampled from r.v.  $T$ , indep.  $Z$ ;
- $f_t$  is the density of  $Z_t = (Z_T | T = t) = (Y|X)$ ;
- Our problem can be seen as a conditional probability density learning problem with  $(X, Y) = (T, Z_T)$ .

# HOW CAN WE ESTIMATE MARGINAL DENSITIES?

- Suppose that sampling times  $\{t_j^r : j = 1, \dots, n; r = 1, \dots, m\}$  are i.i.d. sampled from r.v.  $T$ , indep.  $Z$ ;
- $f_t$  is the density of  $Z_t = (Z_T | T = t) = (Y|X)$ ;
- Our problem can be seen as a conditional probability density learning problem with  $(X, Y) = (T, Z_T)$ .

⇒ We could apply SOA conditional density estimation techniques, such as LS-CDE [Sugiyama et al., 2010],


# HOW CAN WE ESTIMATE MARGINAL DENSITIES?

- Suppose that sampling times  $\{t_j^r : j = 1, \dots, n; r = 1, \dots, m\}$  are i.i.d. sampled from r.v.  $T$ , indep.  $Z$ ;
- $f_t$  is the density of  $Z_t = (Z_T | T = t) = (Y|X)$ ;
- Our problem can be seen as a conditional probability density learning problem with  $(X, Y) = (T, Z_T)$ .


⇒ We could apply SOA conditional density estimation techniques, such as LS-CDE [Sugiyama et al., 2010],

⇒ Instead, we choose to use a fine partitioning of the time domain.

# PARTITION BASED MARGINAL DENSITY ESTIMATION



# PARTITION BASED MARGINAL DENSITY ESTIMATION



Idea: to average in time the marginal densities over small bins by applying classical multivariate density estimation techniques to each subset.

# CONSISTENCY

We denote by:

- $\Theta : \mathcal{S} \rightarrow L^1(E, \mathbb{R}_+)$  multivariate density estimation statistic,
- $\mathcal{S} = \{(z_k)_{k=1}^N \in E^N : N \in \mathbb{N}^*\}$  set of finite sequences,

# CONSISTENCY

We denote by:

- $\Theta : \mathcal{S} \rightarrow L^1(E, \mathbb{R}_+)$  multivariate density estimation statistic,
- $\mathcal{S} = \{(z_k)_{k=1}^N \in E^N : N \in \mathbb{N}^*\}$  set of finite sequences,
- $m$  the number of random curves;
- $\mathcal{T}_t^m$  subset of data points whose sampling times fall in the bin containing  $t$ ;

# CONSISTENCY

We denote by:

- $\Theta : \mathcal{S} \rightarrow L^1(E, \mathbb{R}_+)$  multivariate density estimation statistic,
- $\mathcal{S} = \{(z_k)_{k=1}^N \in E^N : N \in \mathbb{N}^*\}$  set of finite sequences,
- $m$  the number of random curves;
- $\mathcal{T}_t^m$  subset of data points whose sampling times fall in the bin containing  $t$ ;
- $\hat{f}_t^m := \Theta[\mathcal{T}_t^m]$  estimator trained using  $\mathcal{T}_t^m$ .

# CONSISTENCY

ASSUMPTION 1 - POSITIVE TIME DENSITY

$\nu \in L^\infty(E, \mathbb{R}_+)$  density function of  $T$ , s.t.

$$\nu_+ := \text{ess} \sup_{t \in \mathbb{T}} \nu(t) < \infty, \quad \nu_- := \text{ess} \inf_{t \in \mathbb{T}} \nu(t) > 0.$$

# CONSISTENCY

ASSUMPTION 1 - POSITIVE TIME DENSITY

$\nu \in L^\infty(E, \mathbb{R}_+)$  density function of  $T$ , s.t.

$$\nu_+ := \text{ess sup}_{t \in \mathbb{T}} \nu(t) < \infty, \quad \nu_- := \text{ess inf}_{t \in \mathbb{T}} \nu(t) > 0.$$

ASSUMPTION 2 - LIPSCHITZ IN TIME

Function  $(t, z) \in \mathbb{T} \times E \mapsto f_t(z)$  is continuous and

$$|f_{t_1}(z) - f_{t_2}(z)| \leq L|t_1 - t_2|, \quad L > 0.$$

# CONSISTENCY

ASSUMPTION 1 - POSITIVE TIME DENSITY

$\nu \in L^\infty(E, \mathbb{R}_+)$  density function of  $T$ , s.t.

$$\nu_+ := \text{ess sup}_{t \in \mathbb{T}} \nu(t) < \infty, \quad \nu_- := \text{ess inf}_{t \in \mathbb{T}} \nu(t) > 0.$$

ASSUMPTION 2 - LIPSCHITZ IN TIME

Function  $(t, z) \in \mathbb{T} \times E \mapsto f_t(z)$  is continuous and

$$|f_{t_1}(z) - f_{t_2}(z)| \leq L|t_1 - t_2|, \quad L > 0.$$

ASSUMPTION 3 - SHRINKING BINS

The homogeneous partition  $\{B_\ell^m\}_{\ell=1}^{q_m}$  of  $[0; t_f]$ , with binsize  $b_m$ , is s.t.

$$\lim_{m \rightarrow \infty} b_m = 0, \quad \lim_{m \rightarrow \infty} mb_m = \infty.$$

# CONSISTENCY

## ASSUMPTION 4 - I.I.D. CONSISTENCY

- $\mathcal{G}$  arbitrary family of probability density functions on  $E$ ,  $\rho \in \mathcal{G}$ ,
- $S_\rho^N$  i.i.d sample of size  $N$  drawn from  $\rho$  valued in  $\mathcal{S}$ .

The estimator obtained by applying  $\Theta$  to  $S_\rho^N$ , denoted by

$$\hat{\rho}^N := \Theta[S_\rho^N] \in L^1(E, \mathbb{R}_+),$$

is a (pointwise) consistent density estimator, uniformly in  $\rho$ :

For all  $z \in E, \varepsilon > 0, \alpha_1 > 0$ , there is  $N_{\varepsilon, \alpha_1} > 0$  such that, for any  $\rho \in \mathcal{G}$ ,

$$N \geq N_{\varepsilon, \alpha_1} \Rightarrow \mathbb{P} \left( \left| \hat{\rho}^N(z) - \rho(z) \right| < \varepsilon \right) > 1 - \alpha_1.$$

# CONSISTENCY

## THEOREM 1

Under assumptions 1 to 4, for any  $z \in E$  and  $t \in \mathbb{T}$ ,  $\hat{f}_{\ell^m(t)}^m(z)$  consistently approximates the marginal density  $f_t(z)$  as the number of curves  $m$  grows:

$$\forall \varepsilon > 0, \quad \lim_{m \rightarrow \infty} \mathbb{P} \left( |\hat{f}_t^m(z) - f_t(z)| < \varepsilon \right) = 1.$$

# CONSISTENCY

## THEOREM 1

Under assumptions 1 to 4, for any  $z \in E$  and  $t \in \mathbb{T}$ ,  $\hat{f}_{\ell^m(t)}^m(z)$  consistently approximates the marginal density  $f_t(z)$  as the number of curves  $m$  grows:

$$\forall \varepsilon > 0, \quad \lim_{m \rightarrow \infty} \mathbb{P}(|\hat{f}_t^m(z) - f_t(z)| < \varepsilon) = 1.$$

**Note that:**

- $m \rightarrow \infty \neq N \rightarrow \infty$ ,

# CONSISTENCY

## THEOREM 1


Under assumptions 1 to 4, for any  $z \in E$  and  $t \in \mathbb{T}$ ,  $\hat{f}_{\ell^m(t)}^m(z)$  consistently approximates the marginal density  $f_t(z)$  as the number of curves  $m$  grows:

$$\forall \varepsilon > 0, \quad \lim_{m \rightarrow \infty} \mathbb{P} (|\hat{f}_t^m(z) - f_t(z)| < \varepsilon) = 1.$$


**Note that:**

- $m \rightarrow \infty \neq N \rightarrow \infty$ ,
- Number of samples = random.


# MARGINAL DENSITY ESTIMATION RESULTS



# MARGINAL DENSITY ESTIMATION RESULTS



## MARGINAL DENSITY ESTIMATION RESULTS



# HOW GOOD IS IT COMPARED TO OTHER METHODS?

# HOW GOOD IS IT COMPARED TO OTHER METHODS?


- Training set of  $m = 424$  flights  $\simeq 334\ 531$  point observations,

# HOW GOOD IS IT COMPARED TO OTHER METHODS?

- Training set of  $m = 424$  flights  $\simeq 334\ 531$  point observations,
- Test set of 150 flights


# HOW GOOD IS IT COMPARED TO OTHER METHODS?

- Training set of  $m = 424$  flights  $\simeq 334\ 531$  point observations,
- Test set of 150 flights



# HOW GOOD IS IT COMPARED TO OTHER METHODS?


- Training set of  $m = 424$  flights  $\simeq 334\,531$  point observations,
- Test set of 150 flights



- Discrimination power comparison with (gmm-)FPCA and (integrated) LS-CDE:

# HOW GOOD IS IT COMPARED TO OTHER METHODS?

- Training set of  $m = 424$  flights  $\simeq 334\,531$  point observations,
- Test set of 150 flights



- Discrimination power comparison with (gmm-)FPCA and (integrated) LS-CDE:

VAR.	ESTIMATED LIKELIHOODS		
	REAL	OPT1	OPT2
MML	<b><math>0.63 \pm 0.07</math></b>	<b><math>0.43 \pm 0.08</math></b>	<b><math>0.13 \pm 0.02</math></b>
FPCA	$0.16 \pm 0.12$	$6.4\text{E-}03 \pm 3.8\text{E-}03$	$3.6\text{E-}03 \pm 5.4\text{E-}03$
LS-CDE	$0.77 \pm 0.05$	$0.68 \pm 0.04$	$0.49 \pm 0.06$

# MML PENALTY

The MML can be used not only to assess the optimization solutions, but also to penalize the optimization itself:

$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt \\ \text{s.t. } & \left\{ \begin{array}{l} \dot{\mathbf{x}}(t) = \hat{g}(\mathbf{u}(t), \mathbf{x}(t)), \quad \text{a.e. } t \in [0, t_f], \\ \text{Other constraints...} \end{array} \right. \end{aligned} \tag{AOCP}$$

# MML PENALTY

The MML can be used not only to assess the optimization solutions, but also to penalize the optimization itself:

$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt - \lambda \text{MML}(\mathcal{Z}, \mathbf{x}), \\ \text{s.t. } & \left\{ \begin{array}{l} \dot{\mathbf{x}}(t) = \hat{g}(\mathbf{u}(t), \mathbf{x}(t)), \quad \text{a.e. } t \in [0, t_f], \\ \text{Other constraints...} \end{array} \right. \end{aligned} \tag{MML-AOCP}$$


# MML PENALTY

The MML can be used not only to assess the optimization solutions, but also to penalize the optimization itself:

$$\begin{aligned} & \min_{(\mathbf{x}, \mathbf{u}) \in \mathbb{X} \times \mathbb{U}} \int_0^{t_f} C(\mathbf{u}(t), \mathbf{x}(t)) dt - \lambda \text{MML}(\mathcal{Z}, \mathbf{x}), \\ \text{s.t. } & \left\{ \begin{array}{l} \dot{\mathbf{x}}(t) = \hat{g}(\mathbf{u}(t), \mathbf{x}(t)), \quad \text{a.e. } t \in [0, t_f], \\ \text{Other constraints...} \end{array} \right. \end{aligned} \quad (\text{MML-AOCP})$$

- $\lambda$  sets trade-off between a fuel minimization and a likelihood maximization,

# PENALTY EFFECT



# CONSUMPTION X ACCEPTABILITY TRADE-OFF




FIGURE: Average over 20 flights of the fuel consumption and MML score (called acceptability here) of optimized trajectories with varying MML-penalty weight  $\lambda$ .

# TRAJECTORY ACCEPTABILITY CONCLUSION

- 1 General probabilistic criterion for quantifying the closeness between a curve and a set random trajectories,

# TRAJECTORY ACCEPTABILITY CONCLUSION

- 1 General probabilistic criterion for quantifying the closeness between a curve and a set random trajectories,
- 2 Class of consistent plug-in estimators, based on “histogram” of multivariate density estimators,

# TRAJECTORY ACCEPTABILITY CONCLUSION

- 1 General probabilistic criterion for quantifying the closeness between a curve and a set random trajectories,
- 2 Class of consistent plug-in estimators, based on “histogram” of multivariate density estimators,
- 3 Applicable to the case of aircraft climb trajectories,

# TRAJECTORY ACCEPTABILITY CONCLUSION

- 1 General probabilistic criterion for quantifying the closeness between a curve and a set random trajectories,
- 2 Class of consistent plug-in estimators, based on “histogram” of multivariate density estimators,
- 3 Applicable to the case of aircraft climb trajectories,
  - Competitive with other well-established SOA approaches,

# TRAJECTORY ACCEPTABILITY CONCLUSION

- 1 General probabilistic criterion for quantifying the closeness between a curve and a set random trajectories,
- 2 Class of consistent plug-in estimators, based on “histogram” of multivariate density estimators,
- 3 Applicable to the case of aircraft climb trajectories,
  - Competitive with other well-established SOA approaches,
- 4 Particular Adaptive Kernel and Gaussian mixture implementation,

# TRAJECTORY ACCEPTABILITY CONCLUSION

- 1 General probabilistic criterion for quantifying the closeness between a curve and a set random trajectories,
- 2 Class of consistent plug-in estimators, based on “histogram” of multivariate density estimators,
- 3 Applicable to the case of aircraft climb trajectories,
  - Competitive with other well-established SOA approaches,
- 4 Particular Adaptive Kernel and Gaussian mixture implementation,
  - Showed that it can be used in optimal control problems to obtain solutions close to optimal, and still realistic.

**THANK YOU FOR YOUR ATTENTION**

## REFERENCES

- Anderson, R. M. and May, R. M. (1992). Infectious Diseases of Humans: Dynamics and Control. Oxford university press.
- Bach, F. (2008). Bolasso: model consistent Lasso estimation through the bootstrap. In Proceedings of the 25th international conference on Machine learning, pages 33–40.
- Efron, B., Hastie, T., Johnstone, I., and Tibshirani, R. (2004). Least angle regression. The Annals of Statistics, 32:407–499.
- FitzHugh, R. (1961). Impulses and physiological states in theoretical models of nerve membrane. Biophysical journal, 1(6):445–466.
- Friedman, J., Hastie, T., and Tibshirani, R. (2010). A note on the Group Lasso and a Sparse group Lasso. arXiv:1001.0736.
- Mattingly, J. D., Heiser, W. H., and Daley, D. H. (1992). Aircraft Engine Design. University Press.
- Nagumo, J., Arimoto, S., and Yoshizawa, S. (1962). An active pulse transmission line simulating nerve axon. Proceedings of the Japanese Academy, 38(8):664–667.