

Batch QCPA: Manual v1.1

Cedric P. van den Berg^{1,2,3}, Nicholas D. Condon⁴, Cara Conradsen¹, Thomas E. White², Karen L. Cheney¹

¹ School of the Environment, The University of Queensland, St Lucia QLD 4072, Australia

² School of Life and Environmental Sciences, The University of Sydney, Camperdown NSW 2050, Australia

³ School of Biological Sciences, University of Bristol, 24 Tyndall Avenue, BS8 1TQ, UK

⁴ Institute for Molecular Bioscience, The University of Queensland, St Lucia QLD 4067, Australia

Contents

Batch QCPA: Manual v1.1	1
1. General information	2
2. Installing the batch script.....	2
3. Required folder structure	3
4. Auxiliary files	3
4.1 Specifying the image rotation	4
4.2 Specifying the visual model.....	4
4.3 Specifying the ROIs.....	4
5. Using the batch script	5
5.1 'CAA, BSA, VCA & Particle Analysis' settings.....	6
5.2 'LEIA' settings	9
5.3 'GabRat' settings	10
5.4 'Colour Maps' settings	11

1. General information

This script is targeted toward quantifying an animal and its visual background as well as an entire visual scene. The presented workflow is designed for RAW files processed with [calibrated cameras](#), using [visual models](#).

Note: It is not possible to use .mspec files generated using [calibrated jpgs](#) with this script.


This script is an advanced application of the QCPA framework, and we recommend the user get familiar with the manual workflow first. We further recommend testing the script and the accuracy of numerical output on small subsets of larger data sets and their manually obtained output.

This script has been developed using Windows and Linux-based systems but should work well on Macs.

If using this script, cite the pre-print (available [here](#)) in addition to the original QCPA & MICA papers (available [here](#)).

2. Installing the batch script

This extension to the QCPA framework requires a pre-installed version of the mica toolbox. Extract the 'Batch QCPA.zip' folder and paste it into the 'micaToolbox' folder.




Name	Date modified	Type	Size
Batch QCPA	25/07/2022 4:57 PM	File folder	
Camera Calibration	1/07/2022 6:40 PM	File folder	
cameras	1/07/2022 6:40 PM	File folder	
Data Analysis	1/07/2022 6:40 PM	File folder	
Image Analysis	13/07/2022 6:23 PM	File folder	
Image Visualisation	1/07/2022 6:40 PM	File folder	
Linearisation Models	1/07/2022 6:40 PM	File folder	
QCPA	13/07/2022 6:23 PM	File folder	
RNL Colour Maps	1/07/2022 6:40 PM	File folder	
Tools	1/07/2022 6:40 PM	File folder	
weberFractions	13/07/2022 6:20 PM	File folder	
_Generate_Multispectral_Image.ijm	1/07/2022 6:15 PM	IJM File	
_Load_Multispectral_Image.ijm	1/07/2022 6:15 PM	IJM File	
analysisSettings.txt	1/07/2022 6:15 PM	Text Document	
BlueRed.lut	1/07/2022 6:15 PM	LUT File	
Convert_to_Cone_Catch.ijm	1/07/2022 6:15 PM	IJM File	
importSettings.txt	1/07/2022 6:15 PM	Text Document	
Jama-1.0.3.jar	1/07/2022 6:15 PM	JAR File	
mica_Toolbox.jar	1/07/2022 6:15 PM	JAR File	
Photo Screening Page.png	1/07/2022 6:15 PM	PNG File	
Photo_Screening.ijm	1/07/2022 6:15 PM	IJM File	
screeningSettings.txt	1/07/2022 6:15 PM	Text Document	
weberFractionsCustomWeberFraction.txt	22/07/2022 1:42 PM	Text Document	

Detailed information for the installation of the mica toolbox can be found [here](#) and [here](#).

General support for issues with running the toolbox can be found [here](#).

3. Required folder structure

The script requires a specific folder structure. Specifically, individual observations (e.g., an animal on its background, a scene, etc.) must be nested in an 'individual' folder within a 'site' or 'species' folder. The script is then designed to work on a single folder containing this simple structure. See the worked examples data structure for specific examples. We further provide a 'Batch QCPA FileChecker' tool that can be found at the parent level of the imageJ plugin (Plugins -> micaToolbox -> Batch QCPA). Apply the tool to the parent folder (see the figure below).



4. Auxiliary files

In addition to the .mspec and the original RAW image file(s), the script requires a specific set of auxiliary files in each folder. Namely:

- 1) a .zip file containing the regions of interest (ROIs) (mandatory)
- 2) a .txt file with the desired image rotation (optional)
- 3) a .txt file specifying the visual model to be used (mandatory)

It is easiest to obtain these files in the following order for each image:

4.1 Specifying the image rotation

Colour pattern analyses tend to be very sensitive to image orientation. We therefore highly recommend standardising images to a uniform orientation before analysis. To do so, after selecting 'Generate multispectral image' and selecting your appropriate settings, go to 'image'-'Transform'-> 'rotate...'. Select 'Preview' and 'Zoom to fit'. Align the animal head up using the gridlines displayed. Make sure nothing gets clipped. Save the rotation angle with the image as a .txt called 'rotation'.

4.2 Specifying the visual model

The batch script allows multiple visual models to be used with a given dataset. For example, if the dataset contains images that were shot during sunset and those that were shot during broad daylight and yet other images that were shot in forest shade. Provided the user has measured these light environments, a set of lighting-specific models can be trained using the 'Generate cone catch model' function in the 'Camera calibration' menu. The user can then place a .txt file called 'cone model' with each picture specifying which visual model applies (e.g., 1, 2 or 3). For analyses with different animal visual systems, we recommend separate analyses rather than using this feature.

Note: The different visual models must have the same spectral sensitivities, channel names and Weber fractions. This functionality is aimed to allow to account for differences in lighting. For the modelling of different visual systems, we recommend completing separate batch processing cycles.

4.3 Specifying the ROIs


After having opened the image using the 'Generate multispectral image' function and having rotated the image, transform the image to a cone catch image using the 'Convert to cone catch' function. This will allow checking for correct cone mapping. Alternatively, this step can be omitted. Either way, to obtain the ROIs, we recommend working with a colour image rather than a grey-scale image. It is often easier to see animals and objects that way. The ROIs must be obtained with the image being rotated into its final position. To obtain an RGB colour image, click 'Make presentation image' and tick the 'Convert to RGB box'. Use the 'Image' -> 'Adjust' -> 'Brightness & Contrast' -> 'Auto' (or manually if needed) to make the animal as visible as possible. Don't worry about other parts of the image getting too bright. This is to see the outline of the animal as clearly as possible.

First, set the size standard by selecting the 'line tool' to draw a line along the length of your size standard & press 'S' to give its units and save the ROI. We recommend working in mm, i.e., 1cm = 10.

Select the 'animal' outline using the 'Freehand selection' tool. Use the zoom function ('Ctrl' + 'alt' + mouse wheel or zoom buttons) to get a nice and close look at the animal's outline as above. Use the 'Brush Selection Tool' (double click to set size) with 'alt' to add to ROI and 'Shift' to subtract from the ROI to refine the ROI. Press 't' to save the ROI once happy and rename it as 'Animal' (case sensitive). Ensure the 'Show all' box in the ROI manager is disabled.

Select the 'animal+background' ROI by roughly outlining the area of interest including the animal. Press 't' and then 'rename' to 'animal+background' (note: case sensitive! We recommend all lower case and no spaces for ROI names). Avoid areas with excessive shadows cast by the lighting or colour standard. This step is important to exclude unwanted parts of the image.

Combine 'animal+background' with 'animal' to create the final 'background' ROI that does not contain the animal. Use 'CTRL' to select both ROIs in the ROI manager.



Go to 'More' -> 'XOR'. This will subtract the animal from the background. Press 't'. Rename the new ROI to 'background'. Check all ROIs by selecting them in the ROI manager and observing the ROI in the image. If areas need to be excluded from the background, use the same technique as for the 'animal' to remove these areas and save the modified ROI. Save the ROIs once you are happy.

5. Using the batch script

To launch the QCPA batch script, go to 'Plugins' -> 'micaToolbox' -> 'Batch QCPA' and select your prepared dataset's directory. For general considerations on parameter choices, please see the electronic supplement of the original QCPA paper and [the website](#).

Main QCPA Input Parameters

Choose your file Extension

Enter your mspec filename

Add viewing distances in same unit as the scale bar in each image

If using more than one distance ensure values are separated by a comma

Number of spectral sensitivities (excl. luminance channel) required?

☒ Enable rotation?

Choose your lower chromaticity limit

Replace negative cone catch values with:

Use 'IGNORE' above to ignore these settings and use a value of 0

Select the ROIs you would like to measure below:

☒ Animal ROI

☒ Animal + Background

☒ Background ROI

Select the modules you would like to use below:

Note that Colour maps will not work with less than two colour channels (dichromacy)

☒ CAA,BSA,VCA & Particle Analysis

☒ LEIA

☒ GabRat

☒ RNL Colour Maps


OK Cancel

1. Specify the format of your RAW images
2. If you have changed the name of your .mspec files, specify the name here. This name needs to be identical in all images. We recommend not saving a specific name when creating the files.
3. Choose the desired viewing distance(s). The closer the distance and higher the visual acuity, the longer image processing will take.
4. Choose the number of colour channels in your visual system.
5. Select if the images should be rotated or not. We recommend doing so.
6. Choose your [lower chromaticity limit](#).
7. Choose the replacement value for [negative cone catch estimates](#).
8. Select the ROIs you would like to measure. Note: The script assumes all three ROIs to be present. If you want to apply the script to datasets without animals or objects you might want to try creating empty or tiny ROIs.
9. Select the modules you would like to run.

5.1 'CAA, BSA, VCA & Particle Analysis' settings

1. Specify Weber fractions. These will be used for the clustering, and the RNL ranked filter. Make sure these names match the channels specified in your visual model (no need to match the order, though!). The luminance channel is automatically detected as the last row in your visual model and will be called 'lum' irrespective of the name given in your model (e.g. dbl or mw).

Note: Your visual models will need to have a luminance channel. To add one, add it to the spectral sensitivity file, save the file and redo your visual model.




Custom Weber Fractions Input

Weber Fraction Name & Number	lw	0.05
Weber Fraction Name & Number	mw	0.05
Weber Fraction Name & Number	sw	0.05
Specify Weber Fraction for your Luminance channel		0.050

OK Cancel

- Specify your desired [Acuity settings](#). Unless your ROIs are rectangular, use '[Gaussian](#)'.



QCPA sub-Module - QCPA Framework Options

QCPA SETTINGS

Select which aspects of processing to apply:

Acuity Correction Gaussian

AcuityView (modified for QCPA) is fast and uses FFT, but requires use on whole-images.
The Gaussian method is slower, but can measure ROIs independently
of their surroundings

☒ RNL Ranked Filter

Clustering RNL Cluster

When using the QCPA framework cite:
van den Berg & Troscianko et al. (2020) Quantitative Colour Pattern Analysis (QCPA): A Comprehensive Framework for the Analysis of Colour Patterns in Nature,
Methods in Ecology and Evolution, 11, 316-332 (2020)

OK Cancel Help

- Select whether you want to use the RNL ranked filter. We recommend using RNL ranked filtering to compensate for artefacts from the acuity modelling.
- Choose your [acuity modelling settings](#). We recommend using the defaults displayed here with your required cycles per degree acuity value.

AcuityView for ImageJ

QCPA ACUITY PROCESSING FOR IMAGEJ

Acuity Settings

Acuity units:

Acuity value

Distance/Angle Settings

Method:

If using 'Viewing distance' the image must contain a scale-bar, and the units entered above must match the scale bar units (e.g. mm). All angles are in degrees

Rescale to px per MRA

Automatically re-scale the image to a set number of pixels per MRA, 0=off. A value of 5 is recommended to avoid loosing more than 2% of spatial information

Background Info

AcuityView in QCPA is based on a 2016 Matlab script by S. Johnsen. It removes spatial information that isn't available to a given visual system, but a host of other processing steps may go into changing what an animal actually perceives.

If you use this tool, please also consider citing:
Caves, E. M. & Johnsen, S. AcuityView: An R package for portraying the effects of visual acuity on scenes observed by an animal. *Methods in Ecology and Evolution* 9, 793-797 (2018).

OK Cancel Help

- Choose your [RNL ranked filter](#) options.

RNL Ranked Filter Settings

RNL Ranked Filter Settings

Iterations:

Radius:


If you specified a pixels-per-MRA, you should use the same number as the radius here.

Falloff:

Higher falloff values create a steeper falloff in the influence of neighbouring pixels, preserving more fine detail

OK Cancel Help

- Choose your [RNL clustering](#) settings. Note that [Naïve Bayes clustering](#) requires manual input and is not available in the batch script.



RNL Clustering Settings

RNL Clustering Settings

Colour JND Threshold

Luminance JND Threshold

Loops

Radius multiplier

Minimum cluster size

Compare all clusters from pass:

Stop clustering if number of clusters is below


Record output from pass

☒ Show separate horizontal and vertical adjacency results

☒ Output adjacency matrix

OK Cancel Help

7. Select the appropriate visual models. Note that these need to match the ordering specified in your .txt files. Model #1 needs to be '1' in your .txt files. The interface shows both the .java and the .class files for each model. Either one works fine.



Cone Model Option

Cone Model #1

Cone Model #2

Cone Model #3

Cone Model #4

Cone Model #5


OK Cancel

8. Sit back and enjoy! All outputs and log files will be saved in your data next to your images. Please provide the log files in the electronic supplement or data of any publications for reproducibility.

5.2 'LEIA' settings

1. Additional input is required if the user selects only LEIA to be applied. We recommend using the RNL ranked filter but not clustering for LEIA. If LEIA is selected in addition to other QCPA modules, the user will provide a unique set of parameter choices for either.


The user has the choice to log-transform the LEIA output. This might provide additional insights as many behaviours might respond to the log intensity of visual input. The user can visually analyse horizontal and vertical LEIA edge contrast in the image separately and set the upper-intensity level of the LEIA images stored in the LEIA folder of each image.



2. Sit back and enjoy! All outputs and log files will be saved in your data next to your images.

5.3 'GabRat' settings

1. The user interface will ask for an acuity value if [GabRat](#) is selected by itself or combined with other modules requiring acuity modelling. However, unlike other modules considering the 'maximal' acuity, [GabRat](#) should be run at the resolution (and thus spatial frequencies) where a visual system best resolves spatial detail. Therefore, the acuity value provided in this window will override the previously supplied acuity value.




[Gabrat](#) will, by default, use the 'Animal' ROI to define the animal's outline. Therefore, [GabRat](#) output for the 'background' and 'animal+background' ROIs are of no scientific value as [GabRat](#)

measures along the outline of an animal or object. We recommend that GabRat be run without RNL ranked filtering or clustering. If [GabRat](#) is run with other modules, each will request its own set of parameters.

2. Sit back and enjoy! The script will save a .csv file containing the GabRat values for each channel and ROI.

5.4 'Colour Maps' settings

1. When running the [Colour map](#) module, the script will ask you to specify the resolution of the [colour maps](#) and any input needed for RNL filtering or clustering. We recommend applying RNL filtering but not clustering when using this tool. If the Colour Maps module is combined with other QCPA modules, each will request its own set of inputs.



2. Sit back and enjoy! The script will save the colour maps and overlay analysis for each ROI with your images. If you want to [display the colour maps as figures](#), this must be done manually. The script will not provide colour maps for each particle in an ROI. If you want to get colour maps for individual particles (read: colour pattern elements), we recommend clustering your image and running colour maps on the RNL-filtered image using the ROI list obtained from clustering. This will have to be done manually.