

API Documentation — Trading Journal Backend

Base URL: <http://localhost:5000/api>

1. Authentication Endpoints (</api/auth>)

A. Register User

- **Endpoint:** `POST /api/auth/register`
- **Description:** Creates a new user account, hashes the password, and returns a JWT token.
- **Request Body (JSON):**

JSON

```
{
  "name": "John Doe",
  "email": "john@example.com",
  "password": "securepassword123"
}
```

- **Success Response (201 Created):**

JSON

```
{
  "success": true,
  "message": "Account created successfully",
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXLT...",
  "user": {
    "id": "64a7f2e1b8c9d0123456789a",
    "name": "John Doe",
    "email": "john@example.com"
  }
}
```

- **Error Response (400 Bad Request / 500):**

JSON

```
{
  "success": false,
  "error": "User already exists with this email."
}
```

B. Login User

- **Endpoint:** `POST /api/auth/login`
- **Description:** Authenticates user credentials and issues a session token.
- **Request Body (JSON):**

JSON

```
{
  "email": "john@example.com",
  "password": "securepassword123"
}
```

- **Success Response (200 OK):**

JSON

```
{
  "success": true,
  "message": "Logged in successfully",
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXLTJ5IiwiaWF0IjoxNjU0OTU0MDAwfQ",
  "user": {
    "id": "64a7f2e1b8c9d0123456789a",
    "name": "John Doe",
    "email": "john@example.com"
  }
}
```

- **Error Response (400 Bad Request):**

JSON

```
{
  "success": false,
  "error": "Invalid credentials."
}
```

C. Logout User

- **Endpoint:** `POST /api/auth/logout`
- **Description:** Clears the authentication session.
- **Request Body:** None
- **Success Response (200 OK):**

JSON

```
{
  "success": true,
  "message": "Logged out successfully"
}
```

2. Trading Plan Endpoints (/api/plans)

A. Get All Trading Plans

- **Endpoint:** `GET /api/plans/allplans`
- **Description:** Retrieves a list of all trading plans sorted by newest first.
- **Request Body:** None
- **Success Response (200 OK):**

JSON

```
{
  "success": true,
  "count": 1,
  "plans": [
    {
      "_id": "64a7f3c4b8c9d0123456789b",
      "name": "Breakout Strategy",
      "description": "Daily morning session breakout trading strategy.",
      "rules": [
        "Wait for 15-minute candle close",
        "Ensure high relative volume",
        "Risk maximum 1% per trade"
      ],
      "image": {
        "data": "...",
        "mimeType": "image/png"
      },
      "createdAt": "2026-06-06T12:00:00.000Z",
      "updatedAt": "2026-06-06T12:00:00.000Z"
    }
  ]
}
```

B. Get Single Trading Plan

- **Endpoint:** `GET /api/plans/plan/:id`
- **Description:** Fetches details of a specific trading plan by its MongoDB ObjectId.
- **Request Params:** `id` (MongoDB ObjectId)
- **Request Body:** None
- **Success Response (200 OK):**

JSON

```
{
  "success": true,
  "plan": {
    "_id": "64a7f3c4b8c9d0123456789b",
    "name": "Breakout Strategy",
```

```

    "description": "Daily morning session breakout trading strategy.",
    "rules": [
      "Wait for 15-minute candle close",
      "Ensure high relative volume"
    ],
    "image": {
      "data": null,
      "mimeType": null
    },
    "createdAt": "2026-06-06T12:00:00.000Z",
    "updatedAt": "2026-06-06T12:00:00.000Z"
  }
}

```

- **Error Response (400 Bad Request - Invalid ID Format):**

```

JSON
{
  "success": false,
  "message": "Invalid plan ID format"
}

```

- **Error Response (404 Not Found):**

```

JSON
{
  "success": false,
  "message": "Trading plan not found"
}

```

C. Create Trading Plan (Protected)

- **Endpoint:** `POST /api/plans/create`
- **Description:** Creates a new trading plan strategy. Requires authentication header.
- **Headers:** `Authorization: Bearer <your_jwt_token>`
- **Request Body (JSON):**

```

JSON
{
  "name": "Trend Following",
  "description": "Trading with the 200 EMA trend on 1H chart.",
  "rules": [
    "Price must be above 200 EMA",
    "Wait for pullback to support"
  ],
  "image": {

```

```

    "data": "base64_string_here...",
    "mimeType": "image/jpeg"
  }
}

```

- **Success Response (201 Created):**

JSON

```

{
  "success": true,
  "message": "Trading plan created successfully",
  "plan": {
    "_id": "64a7f5a1b8c9d0123456789c",
    "name": "Trend Following",
    "description": "Trading with the 200 EMA trend on 1H chart.",
    "rules": [
      "Price must be above 200 EMA",
      "Wait for pullback to support"
    ],
    "image": {
      "data": "base64_string_here...",
      "mimeType": "image/jpeg"
    },
    "createdAt": "2026-06-06T12:15:00.000Z"
  }
}

```

D. Update Trading Plan (Protected)

- **Endpoint:** PUT /api/plans/update/:id
- **Description:** Partially or fully updates an existing trading plan.
- **Request Params:** id (MongoDB ObjectId)
- **Headers:** Authorization: Bearer <your_jwt_token>
- **Request Body (JSON - All fields optional):**

JSON

```

{
  "name": "Updated Trend Following Plan",
  "rules": [
    "New rule added"
  ]
}

```

- **Success Response (200 OK):**

JSON

```
{
  "success": true,
  "message": "Trading plan updated successfully",
  "plan": {
    "_id": "64a7f5a1b8c9d0123456789c",
    "name": "Updated Trend Following Plan",
    "rules": ["New rule added"]
  }
}
```

E. Delete Trading Plan 🔒 (Protected)

- **Endpoint:** `DELETE /api/plans/delete/:id`
- **Description:** Permanently deletes a specific trading plan.
- **Request Params:** `id` (MongoDB ObjectId)
- **Headers:** `Authorization: Bearer <your_jwt_token>`
- **Request Body:** None
- **Success Response (200 OK):**

JSON

```
{
  "success": true,
  "message": "Trading plan deleted successfully"
}
```

📖 3. Trading Journal Endpoints (`/api/journal`)

A. Create Journal Entry 🔒 (Protected)

- **Endpoint:** `POST /api/journal/create`
- **Description:** Creates a new trading journal entry linked to a plan with trade attributes and multi-timeframe chart images.
- **Headers:** `Authorization: Bearer <your_jwt_token>`
- **Request Body (JSON):**

JSON

```
{
  "plan": "64a7f5a1b8c9d0123456789c",
  "asset": "EURUSD",
  "type": "LONG",
  "pnl": 150.50,
  "entryPrice": 1.0850,
  "exitPrice": 1.0900,
  "lotSize": 1.0,
  "setup": "Breakout",
}
```

```

"emotion": "CONFIDENT",
"notes": "Clean liquidity sweep before expansion.",
"highTimeFrameImage": {
  "data": "base64_hft_string...",
  "mimeType": "image/png"
},
"mediumTimeFrameImage": {
  "data": "base64_mtf_string...",
  "mimeType": "image/png"
},
"lowTimeFrameImage": {
  "data": "base64_ltf_string...",
  "mimeType": "image/png"
},
"date": "2026-06-06T00:00:00.000Z"
}

```

- **Success Response (201 Created):**

JSON

```

{
  "success": true,
  "message": "Journal entry created successfully.",
  "data": {
    "_id": "64a7f8e2b8c9d0123456789d",
    "user": "64a7f2e1b8c9d0123456789a",
    "plan": {
      "_id": "64a7f5a1b8c9d0123456789c",
      "name": "Trend Following",
      "description": "Trading with the 200 EMA trend on 1H chart."
    },
    "asset": "EURUSD",
    "type": "LONG",
    "pnl": 150.50,
    "entryPrice": 1.0850,
    "exitPrice": 1.0900,
    "lotSize": 1.0,
    "setup": "Breakout",
    "emotion": "CONFIDENT",
    "notes": "Clean liquidity sweep before expansion.",
    "highTimeFrameImage": {
      "data": "base64_hft_string...",
      "mimeType": "image/png"
    },
    "mediumTimeFrameImage": {
      "data": "base64_mtf_string...",
      "mimeType": "image/png"
    }
  }
}

```

```

    },
    "lowTimeFrameImage": {
      "data": "base64_ltf_string...",
      "mimeType": "image/png"
    },
    "date": "2026-06-06T00:00:00.000Z",
    "createdAt": "2026-06-06T12:30:00.000Z"
  }
}

```

B. Get All Journal Entries 🔒 (Protected)

- **Endpoint:** `GET /api/journal/all`
- **Description:** Retrieves all journal entries belonging to the authenticated user, complete with automated performance metrics and populated plan details.
- **Headers:** `Authorization: Bearer <your_jwt_token>`
- **Request Body:** None
- **Success Response (200 OK):**

JSON

```

{
  "success": true,
  "count": 1,
  "stats": {
    "totalPnl": 150.50,
    "winRate": "100.00%",
    "winningTrades": 1,
    "losingTrades": 0
  },
  "data": [
    {
      "_id": "64a7f8e2b8c9d0123456789d",
      "user": "64a7f2e1b8c9d0123456789a",
      "plan": {
        "_id": "64a7f5a1b8c9d0123456789c",
        "name": "Trend Following",
        "description": "Trading with the 200 EMA trend on 1H chart."
      },
      "asset": "EURUSD",
      "type": "LONG",
      "pnl": 150.50,
      "entryPrice": 1.0850,
      "exitPrice": 1.0900,
      "lotSize": 1.0,
      "setup": "Breakout",
      "emotion": "CONFIDENT",
      "notes": "Clean liquidity sweep before expansion."
    }
  ]
}

```



```

    "highTimeFrameImage": {
      "data": "base64_htf_string...",
      "mimeType": "image/png"
    },
    "mediumTimeFrameImage": {
      "data": "base64_mtf_string...",
      "mimeType": "image/png"
    },
    "lowTimeFrameImage": {
      "data": "base64_ltf_string...",
      "mimeType": "image/png"
    },
    "date": "2026-06-06T00:00:00.000Z"
  }
]
}

```

C. Get Single Journal Entry 🔒 (Protected)

- **Endpoint:** `GET /api/journal/journal/:id`
- **Description:** Fetches a single journal entry by ID.
- **Request Params:** `id` (MongoDB ObjectId)
- **Headers:** `Authorization: Bearer <your_jwt_token>`
- **Success Response (200 OK):**

JSON

```

{
  "success": true,
  "data": {
    "_id": "64a7f8e2b8c9d0123456789d",
    "plan": {
      "_id": "64a7f5a1b8c9d0123456789c",
      "name": "Trend Following",
      "rules": ["Price must be above 200 EMA"]
    },
    "asset": "EURUSD",
    "type": "LONG",
    "pnl": 150.50,
    "entryPrice": 1.0850,
    "exitPrice": 1.0900,
    "lotSize": 1.0,
    "setup": "Breakout",
    "emotion": "CONFIDENT"
  }
}

```

D. Update Journal Entry (Protected)

- **Endpoint:** PUT `/api/jornal/update/:id` (or POST `/api/jornal/update`)
- **Description:** Updates an existing journal entry.
- **Request Params:** `id` (MongoDB ObjectId)
- **Headers:** `Authorization: Bearer <your_jwt_token>`
- **Request Body (JSON - All fields optional):**

JSON

```
{
  "pnl": 175.00,
  "notes": "Updated exit strategy notes."
}
```

- **Success Response (200 OK):**

JSON

```
{
  "success": true,
  "message": "Journal entry updated successfully.",
  "data": {
    "_id": "64a7f8e2b8c9d0123456789d",
    "pnl": 175.00,
    "notes": "Updated exit strategy notes."
  }
}
```

E. Delete Journal Entry (Protected)

- **Endpoint:** DELETE `/api/jornal/delete/:id` (or POST `/api/jornal/delete`)
- **Description:** Deletes a specific journal entry.
- **Request Params:** `id` (MongoDB ObjectId)
- **Headers:** `Authorization: Bearer <your_jwt_token>`
- **Success Response (200 OK):**

JSON

```
{
  "success": true,
  "message": "Journal entry deleted successfully."
}
```



4. Analytics Endpoints (`/api/analytics`)

A. Get Performance Analytics (Protected)

- **Endpoint:** `GET /api/analytics`
- **Description:** Retrieves calculated performance metrics (Win Rate, Profit Factor, Average PnL, Total Trades, Winning/Losing Breakdown, Best Trade) for the authenticated user. Supports optional date, week, or month filters.
- **Query Parameters (Optional):**
 - `startDate` & `endDate` (Format: YYYY-MM-DD) — e.g.
`/api/analytics?startDate=2026-06-01&endDate=2026-06-07`
 - `month` & `year` (Format: numbers) — e.g.
`/api/analytics?month=6&year=2026`
- **Headers:** `Authorization: Bearer <your_jwt_token>`
- **Request Body:** None
- **Success Response (200 OK):**

JSON

```
{
  "success": true,
  "metrics": {
    "winRate": "57.1%",
    "profitFactor": "1.84",
    "avgPnl": "$45.20",
    "totalTrades": 42,
    "winningTrades": 24,
    "losingTrades": 18,
    "bestTrade": "$420.00"
  }
}
```