Tip of the Week

Tuesday, October 7th, 2014

Source Code Revision Control

Document what changed

- Document what changed
- Document how it changed

- Document what changed
- Document how it changed
- Collaborative work

- Document what changed
- Document how it changed
- Collaborative work
- ▶ Permanent history of versions facilitates comparisons

▶ Improved communication of changes with others

- ▶ Improved communication of changes with others
- Synchronize your work across computers

- ▶ Improved communication of changes with others
- Synchronize your work across computers
- Enables regression testing

- ▶ Improved communication of changes with others
- Synchronize your work across computers
- Enables regression testing
- ► Helps fix bugs faster

- ▶ Improved communication of changes with others
- Synchronize your work across computers
- Enables regression testing
- Helps fix bugs faster
- ► Easier than changelogs + diffs

Example: QGIS versions 1.8.0, 2.0.0, 2.0.1, and 2.4.0

► MAJOR version changed from 1.X - 2.X and broke the existing API

Example: QGIS versions 1.8.0, 2.0.0, 2.0.1, and 2.4.0

- ► MAJOR version changed from 1.X 2.X and broke the existing API
- ► MINOR version changed from 2.0 to 2.4 with new features added

Example: QGIS versions 1.8.0, 2.0.0, 2.0.1, and 2.4.0

- ► MAJOR version changed from 1.X 2.X and broke the existing API
- ► MINOR version changed from 2.0 to 2.4 with new features added
- ▶ PATCH version changed from 2.0.0 to 2.0.1 with bug fixes

Example: QGIS versions 1.8.0, 2.0.0, 2.0.1, and 2.4.0

- ► MAJOR version changed from 1.X 2.X and broke the existing API
- MINOR version changed from 2.0 to 2.4 with new features added
- ▶ PATCH version changed from 2.0.0 to 2.0.1 with bug fixes
- See http://semver.org/

Changelogs

Succinct description of what changed when

Changelogs

- Succinct description of what changed when
- Long lists of changes

Changelogs

- Succinct description of what changed when
- Long lists of changes
- No information on what changed where and how

Summary of how the code changed

- Summary of how the code changed
 - ► Compare insertions and deletions

- Summary of how the code changed
 - ► Compare insertions and deletions
- ► Links first version to current version "delta-encoding"

- Summary of how the code changed
 - Compare insertions and deletions
- Links first version to current version "delta-encoding"
- Try in your terminal:

- Summary of how the code changed
 - ► Compare insertions and deletions
- ▶ Links first version to current version "delta-encoding"
- Try in your terminal:
 - diff file_v1.txt file_v2.txt

- Summary of how the code changed
 - Compare insertions and deletions
- Links first version to current version "delta-encoding"
- Try in your terminal:
 - ▶ diff file_v1.txt file_v2.txt

▶ Git

- ▶ Git
- Subversion (SVN)

- ▶ Git
- Subversion (SVN)
- Mercurial (hg)

- ▶ Git
- Subversion (SVN)
- ► Mercurial (hg)
- ► Many, many more (please don't use CVS)

From wikipedia:

▶ **Repository**: location of files and history, often on a server

- ▶ Repository: location of files and history, often on a server
- ► Working copy: local copy of files from repository, at specific time or revision (where you do your new work)

- Repository: location of files and history, often on a server
- Working copy: local copy of files from repository, at specific time or revision (where you do your new work)
- ► **Commit**: write your changes in your local history, including how the code changed (diff) and why (changelog)

- Repository: location of files and history, often on a server
- Working copy: local copy of files from repository, at specific time or revision (where you do your new work)
- ► **Commit**: write your changes in your local history, including how the code changed (diff) and why (changelog)
- ► **Push**: send your local history to the repository, enabling it to be shared by others

- Repository: location of files and history, often on a server
- Working copy: local copy of files from repository, at specific time or revision (where you do your new work)
- ► **Commit**: write your changes in your local history, including how the code changed (diff) and why (changelog)
- ▶ **Push**: send your local history to the repository, enabling it to be shared by others
- ▶ **Pull** or **Update**: bring changes from the remote repository into your local working copy

Git

A very popularDistributed Version Control System used extensively in open source software (e.g., Linux kernel).

Git

Clone a repository from Github

```
> git clone https://github.com/try-git/try_git.git
Cloning into 'try_git'...
warning: You appear to have cloned an empty repository.
Checking connectivity... done.
```

> cd try_git/

Git

Do some work, then add the text file

- > echo "some work" > my_file.txt
- > git add my_file.txt

```
Check our status
```

```
> git status
On branch master
Initial commit
Changes to be committed:
  (use "git rm --cached <file>..." to unstage)
  new file: my_file.txt
```

Commit the change with a message

> git commit -m "I did some work. Wow!"
1 file changed, 1 insertion(+)
create mode 100644 my_file.txt

Check our history

> git log

commit 9e0e514d7b54e45d2d8667472376d125939a780a

Author: Chris Holden <ceholden@gmail.com>

Date: Sun Oct 5 19:23:53 2014 -0400

I did some work. Wow!

Push the changes to our repository

> git push origin master

Because of some network firewall reasons, we cannot pull or push using HTTPS.

- ▶ Because of some network firewall reasons, we cannot pull or push using HTTPS.
- ▶ Instead we have to use SSH:

- Because of some network firewall reasons, we cannot pull or push using HTTPS.
- Instead we have to use SSH:
 - Generate a SSH key and passphrase

- Because of some network firewall reasons, we cannot pull or push using HTTPS.
- Instead we have to use SSH:
 - ► Generate a SSH key and passphrase
 - Associate your SSH public key with your account on Github

- Because of some network firewall reasons, we cannot pull or push using HTTPS.
- Instead we have to use SSH:
 - ► Generate a SSH key and passphrase
 - Associate your SSH public key with your account on Github
 - Switch your remote URL to the SSH link

- Because of some network firewall reasons, we cannot pull or push using HTTPS.
- Instead we have to use SSH:
 - Generate a SSH key and passphrase
 - Associate your SSH public key with your account on Github
 - Switch your remote URL to the SSH link
 - ► Full details: https://help.github.com/categories/ssh/

https://try.github.io/ (AMAZING!)

- https://try.github.io/(AMAZING!)
- https://help.github.com/articles/
 what-are-other-good-resources-for-learning-git-and-git

- https://try.github.io/(AMAZING!)
- https://help.github.com/articles/
 what-are-other-good-resources-for-learning-git-and-git
- https://help.github.com/articles/set-up-git/

- https://try.github.io/(AMAZING!)
- https://help.github.com/articles/
 what-are-other-good-resources-for-learning-git-and-git
- https://help.github.com/articles/set-up-git/
- http://www.software-carpentry.org/v5/novice/git/ index.html