APPLICATION / SCREEN CLASSES

VaksJFrame

+ VaksJFrame()
+ VaksJFrame(closeOperation: int)

MainExtended

+ userData: UserData
+ currentUser: UserDataBP
- adminAccount: UserDataBP

+ getAdminAccount(): UserDataBP
~ MainExtended()

Account

- current: UserDataBP

~ Account()

AdminHome

~ apartmentPage: ApartmentManagement
~ adminHome: AdminHome
~ tenantManagement: TenantManagement
~ transactionHistory: TransactionHistory
~ fValue: JLabel
~ sValue: JLabel
~ tValue: JLabel

~ AdminHome()

ApartmentManagement

~ apartmentPage: ApartmentManagement
~ adminHome: AdminHome
~ tenantManagement: TenantManagement
~ transactionHistory: TransactionHistory

~ ApartmentManagement()

TenantManagement

~ apartmentPage: ApartmentManagement
~ adminHome: AdminHome
~ tenantManagement: TenantManagement
~ transactionHistory: TransactionHistory

~ openAddTenantPopup(): void
~ TenantManagement()

TransactionHistory

~ table: JTable
~ apartmentPage: ApartmentManagement
~ adminHome: AdminHome
~ tenantManagement: TenantManagement
~ transactionHistory: TransactionHistory
~ paymentHistory: PaymentHistory
~ fromDate: JDateChooser
~ toDate: JDateChooser

~ TransactionHistory()
- dsaMergeSort(model: DefaultTableModel, columnIndex: int, ascending: boolean, isNumeric: boolean): void
- mergeSortHelper(data: Object[][], left: int, right: int, columnIndex: int, ascending: boolean, isNumeric: boolean): void
- merge(data: Object[][], left: int, mid: int, right: int, columnIndex: int, ascending: boolean, isNumeric: boolean): void
- shouldSwapDSA(o1: Object, o2: Object, ascending: boolean, isNumeric: boolean): boolean

TenantHomeDashboard

~ rentAndpayment: RentAndPayment

~ TenantHomeDashboard()

RentAndPayment

~ rentAndpayment: RentAndPayment
- payment: Payment
~ tabs: JTable

~ RentAndPayment()
- getNextDueDate(): LocalDate

Payment

- rentAndpayment: RentAndPayment
- paymentConfirmation: PaymentConfirmation
- t1: JTextField

+ getPaymentAmount(): double
~ Payment()
- getNextDueDate(): LocalDate

DATA / MODEL CLASSES

UserData

- Data: ArrayList<UserDataBP>

+ UserData()
+ addUser(user: UserDataBP): void
+ getUsers(): ArrayList<UserDataBP>
+ login(email: String, password: String): boolean
+ changePassword(email: String, oldPass: String, newPass: String): boolean
+ removeUser(tenantId: String): void

0..* users

UserDataBP

- fullName: String
- email: String
- password: String
- phoneNumber: String
- role: String
- unitType: String
- TenantId: String
- leaseOfStay: String
- apartmentUnit: String
- moveInDate: String
- endDate: String
- gender: String
- monthRate: double
- currentBalance: double
- loginAttempts: int
- blocked: boolean

+ UserDataBP(fullName: String, email: String, password: String, phoneNumber: String, role: String)
+ UserDataBP(fullName: String, email: String, password: String, phoneNumber: String, role: String, unitType: String, TenantId: String, leaseOfStay: String, apartmentUnit: String, moveInDate: String, endDate: String, gender: String, monthRate: int)
+ getFullName(): String
+ setFullName(fullName: String): void
+ getEmail(): String
+ setEmail(email: String): void
+ getPassword(): String
+ setPassword(password: String): void
+ getPhoneNumber(): String
+ setPhoneNumber(phoneNumber: String): void
+ getRole(): String
+ setRole(role: String): void
+ getUnitType(): String
+ setUnitType(unitType: String): void
+ getTenantId(): String
+ setTenantId(residentId: String): void
+ getLeaseOfStay(): String
+ setLeaseOfStay(leaseOfStay: String): void
+ getApartmentUnit(): String
+ setApartmentUnit(apartmentUnit: String): void
+ getMoveInDate(): String
+ setMoveInDate(moveInDate: String): void
+ getEndDate(): String
+ setEndDate(endDate: String): void
+ getMonthRate(): double
+ setMonthRate(monthRate: double): void
+ getGender(): String
+ setGender(gender: String): void
+ getCurrentBalance(): double
+ setCurrentBalance(currentBalance: double): void
+ getLoginAttempts(): int
+ setLoginAttempts(loginAttempts: int): void
+ isBlocked(): boolean
+ setBlocked(blocked: boolean): void

DataStore

+ tenantModel: DefaultTableModel
+ unitModel: DefaultTableModel
+ transactionModel: DefaultTableModel
+ paymentHistoryModel: DefaultTableModel
+ tenantPaymentHistoryModel: DefaultTableModel
+ paymentModel: DefaultTableModel
+ adminRecentTransactionModel: DefaultTableModel
+ paymentComboModel: DefaultComboBoxModel<String>

+ addPayment(date: String, unit: String, tenant: String, method: String, amount: String, status: String): void
+ updatePaymentStatus(rowIndex: int, newStatus: String): void
+ deletePayment(rowIndex: int): void
+ updatePaymentMethod(rowIndex: int, method: String): void
+ updatePaymentAmount(rowIndex: int, amount: String): void
+ updateTenantDetails(oldName: String, oldEmail: String, newName: String, newEmail: String): void
+ checkAndUpdateOverdueStatus(tenantEmail: String, dueDate: LocalDate): void