

## Thunk Layer Discussion: Size, Helpers, and Organization

**Question:** "Won't moving thunks to Presentation make that layer too large? Should we add a helper or another layer?"

**Short Answer:** No, it's not too large. Start explicit. Add helpers only if real duplication emerges.

## The Concern

After moving Redux thunks from Use Cases to Presentation layer, you'll have:

```
src/presentation/state/thunks/  
├─ lifeContext.thunks.ts    (~150 lines, 7 thunks)  
├─ metricLog.thunks.ts     (~100 lines, 4 thunks)  
├─ myHealth.thunks.ts      (~120 lines, 5 thunks)  
├─ carefeed.thunks.ts      (~60 lines, 2 thunks)  
├─ insight.thunks.ts       (~40 lines, 1 thunk)  
└─ onboarding.thunks.ts    (~130 lines, 5 thunks)
```

Total: ~600 lines across 6 files, 24 thunks

**Developer concern:** "That feels large. Should we abstract this?"

## Three Possible Solutions

### Option 1: Keep It Explicit (Recommended ★)

Just write the thunks out:

```
// src/presentation/state/thunks/metricLog.thunks.ts

export const saveMetricLogs = createAsyncThunk<
  SuccessMessage,
  SaveMetricLogsParams,
  { rejectValue: string }
>("metricLog/save", async (params, { rejectWithValue }) => {
  try {
    const useCase = container.resolve(SaveMetricLogsUseCase);
    return await useCase.execute(params);
  } catch (error) {
    return rejectWithValue(
      error instanceof Error ? error.message : "Failed to save metric logs",
    );
  }
});

export const listMetricLogs = createAsyncThunk<
  MetricLog[],
  ListMetricLogsParams,
  { rejectValue: string }
>("metricLog/list", async (params, { rejectWithValue }) => {
  try {
    const useCase = container.resolve(ListMetricLogsUseCase);
    return await useCase.execute(params);
  } catch (error) {
    return rejectWithValue(
      error instanceof Error ? error.message : "Failed to list metric logs",
    );
  }
});

// ... 2 more thunks
```

## Option 2: Create a Helper (Middle Ground 👍)

If you notice real duplication, create a helper:

```
// src/presentation/state/helpers/createUseCaseThunk.ts

import { createAsyncThunk } from "@reduxjs/toolkit";
import { container } from "tsyringe";

/**
 * Helper to create a thunk that wraps a use case.
 * Use for simple cases. Write custom thunks for complex logic.
 */
export function createUseCaseThunk<
  TResult,
  TParams,
  TUseCase extends { execute: (params: TParams) => Promise<TReturn> },
> (actionName: string, UseCaseClass: new (...args: any[]) => TUseCase) {
  return createAsyncThunk<TReturn, TParams, { rejectValue: string }> (
    actionName,
    async (params, { rejectWithValue }) => {
      try {
        const useCase = container.resolve(UseCaseClass);
        return await useCase.execute(params);
      } catch (error) {
        const message =
          error instanceof Error ? error.message : "Operation failed";
        return rejectWithValue(message);
      }
    },
  );
}
```

### Usage:

```
// src/presentation/state/thunks/metricLog.thunks.ts

import { createUseCaseThunk } from "../../helpers/createUseCaseThunk";
import { SaveMetricLogsUseCase } from "@application/useCases/metricLog/SaveMetricLogs.useCase";
import { ListMetricLogsUseCase } from "@application/useCases/metricLog/ListMetricLogs.useCase";
```

### Option 3: Add Another Layer (Not Recommended ❌)

Create "Interface Adapters" layer:

```
src/
├── container.ts      ← DI container (bootstrap)
├── domain/
├── application/
├── adapters/        ← NEW LAYER
│   ├── redux/
│   │   └── thunks/  ← Thunks here
├── infrastructure/
├── presentation/
│   └── ui/          ← Only components
```

#### Arguments for:

- Follows "textbook" Clean Architecture (5 layers)
- Separates "state" from "UI components"
- Thunks aren't "mixed" with UI

#### Arguments against:

- ❌ **Adds complexity** - 5 layers is overkill for most apps
- ❌ **Unclear boundaries** - What's "adapter" vs "presentation"?
- ❌ **Not industry standard** - React community considers Redux part of presentation
- ❌ **Solves wrong problem** - The "size" issue is perception, not architecture
- ❌ **More navigation** - Developers jump between more folders

#### When this WOULD make sense:

- Multi-platform app (Web + Mobile sharing business logic)
- Multiple UI frameworks (React + Vue + Angular)

# Reality Check: Is 600 Lines Actually Large?

Let's compare to other parts of your codebase:

Layer/Folder	Files	Lines	Purpose
Domain	38 files	~2,000 lines	Entities, types
Application	109 files	~6,000 lines	Use cases, services
Infrastructure	51 files	~3,000 lines	Firebase, Sanity
Presentation (current)	59 files	~3,500 lines	ViewModels, components
<b>Presentation (after)</b>	<b>~70 files</b>	<b>~4,100 lines</b>	<b>+ 600 lines of thunks</b>

**Adding 600 lines to a layer that already has 3,500 lines = 17% increase**

That's not "too large." That's normal growth from putting things in the right place.

## Comparison to Alternatives

What if you used different approaches?

### Redux Toolkit Query (RTK Query)

```
// Generated code per endpoint
const api = createApi({
  baseQuery: fetchBaseQuery({ baseUrl: "/api" }),
  endpoints: (builder) => ({
    getLifeContext: builder.query<LifeContext[], string>({
      query: (uid) => `lifeContext/${uid}`,
    }),
    saveMetricLogs: builder.mutation<SuccessMessage, SaveParams>({
      query: (params) => ({
        url: "metricLogs",
        method: "POST",
        body: params,
      }),
    }),
  }),
  // ... 22 more endpoints
});
```

**Generated code size:** 1,000+ lines (hooks, selectors, cache management)

**Your manual thunks:** 600 lines

**Winner:** Your approach is actually leaner!

### Apollo Client (GraphQL)

```
// Queries, mutations, and generated hooks
const GET_LIFE_CONTEXT = gql`...`;
const SAVE_METRIC_LOGS = gql`...`;
// + Generated TypeScript types
```

## The "Explicitness Tax" is Worth Paying

### Scenario 1: Bug Investigation

With helper (implicit):

```
export const saveMetricLogs = createUseCaseThunk(  
  "metricLog/save",  
  SaveMetricLogsUseCase,  
);  
// Where does error handling happen? 🤔  
// What's the error message format? 🤔  
// Can I customize the loading state? 🤔
```

Without helper (explicit):

```
export const saveMetricLogs = createAsyncThunk(  
  "metricLog/save",  
  async (params, { rejectWithValue }) => {  
    try {  
      const useCase = container.resolve(SaveMetricLogsUseCase);  
      return await useCase.execute(params);  
    } catch (error) {  
      return rejectWithValue(error.message); // ← Clear error handling  
    }  
  },  
);
```

When there's a bug, explicit code is your friend.

### Scenario 2: Adding Custom Logic

Need to add analytics tracking to one thunk?



## Organization Strategy

The key is organization, not abstraction:

### ✓ Good Organization

```
src/presentation/state/  
├── store.ts                (1 file, 100 lines)  
├── slices/  
│   ├── lifeContext/  
│   │   └── lifeContext.slice.ts  
│   ├── metricLog/  
│   │   └── metricLog.slice.ts  
│   └── ...                (13 slice files, ~1,500 lines total)  
├── thunks/  
│   ├── lifeContext.thunks.ts    (7 thunks, ~150 lines)  
│   ├── metricLog.thunks.ts      (4 thunks, ~100 lines)  
│   ├── myHealth.thunks.ts       (5 thunks, ~120 lines)  
│   ├── carefeed.thunks.ts       (2 thunks, ~60 lines)  
│   ├── insight.thunks.ts        (1 thunk, ~40 lines)  
│   └── onboarding.thunks.ts     (5 thunks, ~130 lines)  
├── listeners/              (4 files, ~400 lines)  
└── selectors/              (Optional: ~200 lines)
```

Total: ~2,600 lines across ~30 files

Well organized by domain = Easy to navigate

### ✗ Bad Organization

```
src/presentation/state/  
├── store.ts  
├── slices.ts                (ALL slices in one file, 2,000 lines!)  
├── thunks.ts                (ALL thunks in one file, 600 lines!)  
└── listeners.ts             (ALL listeners in one file, 400 lines!)
```

Total: ~3,000 lines across 4 files

## Recommended Approach

### Step 1: Start Explicit (Week 1)

Write your first 5-10 thunks manually:

```
// metricLog.thunks.ts
export const saveMetricLogs = createAsyncThunk(/* ... */);
export const listMetricLogs = createAsyncThunk(/* ... */);
export const deleteMetricLog = createAsyncThunk(/* ... */);

// lifeContext.thunks.ts
export const fetchLifeContext = createAsyncThunk(/* ... */);
export const initiateMenstruation = createAsyncThunk(/* ... */);
```

#### You'll quickly notice:

- Which thunks are simple (just call use case)
- Which thunks need custom logic (auth, analytics, multi-step)
- If a pattern emerges

### Step 2: Assess After 10+ Thunks (Week 2)

Ask yourself:

- Do 80%+ of thunks look identical?
- Is the repetition actually painful?
- Would a helper make things clearer or more magical?

**If YES to all three → Create helper**

**If NO to any → Keep explicit**

## Counter-Arguments

**"But it's so much typing!"**

**Response:**

- 10 lines per thunk × 24 thunks = 240 lines of "boilerplate"
- That's 0.4% of your total codebase
- Not actually a significant amount

**Trade-off:**

- Explicit = More typing, clearer intent
- Helper = Less typing, more magic

**Industry leans toward:** Explicit for thunks (RTK doesn't provide helpers either)

**"Other developers will copy-paste and make mistakes!"**

**Response:**

- Good! They'll see the full pattern and understand it
- VS: They use helper wrong and don't understand what it does

**Better solution:**

- Code review catches copy-paste errors
- Snippet/template reduces typing (see below)

**"Can't we just generate these?"**

## IDE Snippet Solution

Instead of a helper, create an IDE snippet:

### VS Code Snippet

```
// .vscode/thunk.code-snippets
{
  "Create Use Case Thunk": {
    "prefix": "usecasethunk",
    "body": [
      "export const ${1:functionName} = createAsyncThunk<",
      "  ${2:ResultType},",
      "  ${3:ParamsType},",
      "  { rejectValue: string }",
      ">(",
      "  '${4:domain}/${5:action}',",
      "  async (params, { rejectWithValue }) => {",
      "    try {",
      "      const useCase = container.resolve(${6:UseCaseClass});",
      "      return await useCase.execute(params);",
      "    } catch (error) {",
      "      return rejectWithValue(",
      "        error instanceof Error ? error.message : 'Operation failed'",
      "      );",
      "    }",
      "  }",
      ");",
    ],
    "description": "Create a thunk that wraps a use case"
  }
}
```

**Usage:** Type `usecasethunk` + Tab, fill in the blanks

### Benefits:

- ✓ Fast typing (5 seconds per thunk)

## Final Recommendation

### For Your Team

#### Option 1: Start Explicit ★★★★★

- Write thunks manually
- Organize by domain (6 files)
- Create IDE snippet for speed
- Re-evaluate after 15+ thunks

#### Option 2: Helper After Proof ★★★

- Write 10 thunks manually first
- If clear pattern + real pain → create helper
- Use helper for simple cases only
- Keep complex thunks explicit

#### Option 3: Add Layer ★

- Only if multi-platform or multi-framework
- Not for single React Native app

### My Strong Opinion

**"Explicit is better than implicit. DRY is good, but clarity is better."**

The "cost" of writing 10 lines per thunk is tiny compared to the benefit of:

- Immediate understanding when debugging

## Decision Matrix

Use this to decide:

Scenario	Recommendation
Just starting migration	★ Write explicit thunks
Have 5 thunks, all similar	★ Keep explicit (too early to tell)
Have 15 thunks, 80% identical	★★ Consider helper
Have 15 thunks, 50% need customization	★ Keep explicit
Multi-platform app	★★ Maybe add adapter layer
Single React Native app	★ Stay with 4 layers
Team loves abstractions	★★ Helper might be okay
Team is new to Redux	★ Explicit helps learning

## Conclusion

**The developer's concern is understandable but misplaced.**

The "largeness" is not a problem to solve—it's the natural size of making things explicit and properly organized.

**Start explicit. Add helpers only if real pain emerges.**

**Don't add layers. Organize what you have.**

## Quick Reference



### DO

- Write explicit thunks initially
- Organize by domain (one file per domain)
- Keep files under 200 lines
- Allow customization per-thunk
- Create IDE snippets for speed



### DON'T

- Create helpers before seeing patterns
- Put all thunks in one file
- Add a 5th architectural layer
- Optimize for "less typing" over clarity
- Abstract just because it "feels large"



**See Also:**

- [Architecture Analysis Report](#) - Full details on refactoring
- [Migration Example](#) - Step-by-step thunk creation
- [Quick Reference](#) - Daily development guide

**Last Updated:** 2025-11-19