

Level 2 Instructor Answer Key

Document: Level 2 Instructor Answer Key
Version: v1.0.0
Author: Celaya Solutions
Contact: hello@celayasolutions.com
Date: 2026-09-06
SHA256: 6a27cd1c01a41c20f5f83d03cf18d759686a190234d3a0f7e60bee594dd5ecf6
Chain: n/a
Tx: [not anchored]
License: All Rights Reserved / Celaya Solutions

Do not show this page until predictions are recorded. It is a teaching key, not evidence that any hosted pilot ran.

Six-line model spec

Address is the learner's own raw practice-page URL; execution uses the run's immutable commit version. Signal is the one closed watch-value element. A meaningful change is a transition between OPEN and PAUSED; missing/empty/duplicate/unknown text fails. Trigger is manual during class and daily at 13:17 UTC only while enabled. Alert is one issue in that same fork with old/new values and source. Never list forbids buying, replying, deleting, posting elsewhere, private access, people tracking, and automatic spending; it explicitly permits the practice issue.

Expected evidence

Case	Decision and state	New issue
No previous state, OPEN	baseline saved; current OPEN; pending null	0
OPEN again	no change; current OPEN	0
OPEN to PAUSED	changed; current PAUSED; pending null after completion	1
PAUSED again	no change; current PAUSED	0
Only footer changes	no change; current untouched	0
Page missing/invalid or fetch fails	failed; last good state unchanged	0
State write fails before send	failed; no success claimed	0
Issue denied definitively	failed; pending remains retryable after repair	0
Issue created, last state write fails	failed; next run finds same issue, records alert recovered	0 additional
Issue delivery uncertain and not found	failed; attempted pending remains, human reconciliation needed	No automatic resend
Disabled, variable false, no outstanding jobs	disabled state observed; no new manual run	0

The changed issue is `Change spotted: OPEN to PAUSED`, with both values and the practice source in its body. GitHub supplies the creation time; the round receipt supplies time, source commit, run, previous/current values, decision, transition ID, and issue URL when known. If a pending alert is recovered, that round finishes the older pending transition before a later round observes the page again.

Exit answers

1. A GitHub-hosted runner runs each job; the learner laptop need not remain open.

2. No change means a successful valid observation matched the baseline. Failed means no successful decision was completed; it may need issue/state recovery.
3. State lets a new runner compare with the last confirmed value. Deleting it discards memory and may hide a change.
4. The token has repository-wide contents/issues write scopes. The reviewed code writes one state file and one practice issue per transition, within the learner fork.
5. A fresh manual run selects the latest default-branch commit. Re-running an older job uses that older commit and can observe an old status.
6. The learner observed a disabled workflow, false variable, unavailable trigger, and no queued/active work. That is not proof of an unobserved future schedule tick.

Grade understanding fairly

An honest failure is useful evidence when the learner identifies the stage and proposes a bounded recovery. Do not call a blocked hosted build complete. A saved route can demonstrate sound evaluation and a correctly explained stop, but cannot satisfy an individual live issue or operated switch claim.

The local footer exercise passes when before/after status remains equal, the next decision is no change, and the diff changes only the unrelated paragraph. Do not require an assistant or model-generated mistake.

Instructor recovery boundary

See [the project README](#) before repairing uncertain delivery. Keep the workflow disabled while investigating. Check the pending ID against open and closed issues. Never delete good state, delete an issue to force a test, or automatically reset the send flag. Keep a separate private note of any manual repair and rerun the same expectation after review.