


UR5 Technical specifications

Item no. 110105

6-axis robot arm with a working radius of 850 mm / 33.5 in

Weight:	18.4 kg / 40.6 lbs		
Payload:	5 kg / 11 lbs		
Reach:	850 mm / 33.5 in		
Joint ranges:	+/- 360°		
Speed:	All joints: 180°/s. Tool: Typical 1 m/s. / 39.4 in/s.		
Repeatability:	+/- 0.1 mm / +/- 0.0039 in (4 mils)		
Footprint:	Ø149 mm / 5.9 in		
Degrees of freedom:	6 rotating joints		
Control box size (WxHxD):	475 mm x 423 mm x 268 mm / 18.7 x 16.7 x 10.6 in		
I/O ports:		Controlbox	Tool conn.
	Digital in	16	2
	Digital out	16	2
	Analog in	2	2
	Analog out	2	-
I/O power supply:	24 V 2A in control box and 12 V/24 V 600 mA in tool		
Communication:	TCP/IP 100 Mbit: IEEE 802.3u, 100BASE-TX Ethernet socket & Modbus TCP		
Programming:	Polyscope graphical user interface on 12 inch touchscreen with mounting		
Noise:	Comparatively noiseless		
IP classification:	IP54		
ISO Class Cleanroom robot arm:	5		
ISO Class Cleanroom control box:	6		
Power consumption:	Approx. 200 watts using a typical program		
Collaboration operation:	15 Advanced Safety Functions Tested in accordance with: EN ISO 13849:2008 PL d EN ISO 10218-1:2011, Clause 5.4.3		
Materials:	Aluminum, PP plastic		
Temperature:	The robot can work in a temperature range of 0-50°C		
Power supply:	100-240 VAC, 50-60 Hz		
Cabling:	Cable between robot and control box (6 m / 236 in) Cable between touchscreen and control box (4.5 m / 177 in)		



UR5

Performance

Repeatability	±0.1 mm / ±0.0039 in (4 mils)
Ambient temperature range	0-50°
Power consumption	Min 90W, Typical 150W, Max 325W
Collaboration operation	15 advanced adjustable safety functions. TÜV NORD Approved Safety Function Tested in accordance with: EN ISO 13849:2008 PL d

Specification

Payload	5 kg / 11 lbs
Reach	850 mm / 33.5 in
Degrees of freedom	6 rotating joints
Programming	Polyscope graphical user interface on 12 inch touchscreen with mounting

Movement

Axis movement robot arm	Working range	Maximum speed
Base	± 360°	± 180°/Sec.
Shoulder	± 360°	± 180°/Sec.
Elbow	± 360°	± 180°/Sec.
Wrist 1	± 360°	± 180°/Sec.
Wrist 2	± 360°	± 180°/Sec.
Wrist 3	± 360°	± 180°/Sec.
Typical tool	1 m/Sec. / 39.4 in/Sec.	

Features

IP classification	IP54
ISO Class Cleanroom	5
Noise	72dB
Robot mounting	Any
I/O ports	Digital in 2 Digital out 2 Analog in 2 Analog out 0
I/O power supply in tool	12 V/24 V 600 mA in tool

Physical

Footprint	Ø 149mm
Materials	Aluminium, PP plastics
Tool connector type	M8
Cable length robot arm	6 m / 236 in
Weight with cable	18,4 kg / 40.6 lbs

CONTROL BOX

Features

IP classification	IP20
ISO Class Cleanroom	6
Noise	<65dB(A)
I/O ports	Digital in 16 Digital out 16 Analog in 2 Analog out 2
I/O power supply	24V 2A
Communication	TCP/IP 100Mbit, Modbus TCP, Profinet, EthernetIP
Power source	100-240 VAC, 50-60 Hz
Ambient temperature range	0-50°

Physical

Control box size (WxHxD)	475mm x 423mm x 268mm / 18.7 x 16.7 x 10.6 in
Weight	15 kg / 33.1 lbs
Materials	Steel

TEACH PENDANT

Features

IP classification	IP20
Physical	
Materials	Aluminium, PP
Weight	1,5 kg / 3.3 lbs
Cable length	4,5 m / 177 in

